




JERRY GINSBERG

# ENGINEERING DYNAMICS



CAMBRIDGE

# *Engineering Dynamics*

**JERRY GINSBERG**

Georgia Institute of Technology





CAMBRIDGE UNIVERSITY PRESS

Cambridge, New York, Melbourne, Madrid, Cape Town, Singapore, São Paulo, Delhi

Cambridge University Press

32 Avenue of the Americas, New York, NY 10013-2473, USA

[www.cambridge.org](http://www.cambridge.org)

Information on this title: [www.cambridge.org/9780521883030](http://www.cambridge.org/9780521883030)

© Jerry Ginsberg 2008

This publication is in copyright. Subject to statutory exception  
and to the provisions of relevant collective licensing agreements,  
no reproduction of any part may take place without  
the written permission of Cambridge University Press.

First published 2008

Printed in the United States of America

*A catalog record for this publication is available from the British Library.*

*Library of Congress Cataloging in Publication Data*

Ginsberg, Jerry H., 1944–

Engineering dynamics / Jerry H. Ginsberg.

p. cm.

Includes bibliographical references and index.

ISBN 978-0-521-88303-0 (hardback)

1. Dynamics. I. Title.

TA352.G57 2007

620.1'04–dc22 2007018344

ISBN 978-0-521-88303-0 hardback

Cambridge University Press has no responsibility for  
the persistence or accuracy of URLs for external or  
third-party Internet Web sites referred to in this publication  
and does not guarantee that any content on such  
Web sites is, or will remain, accurate or appropriate.

Contents

<i>Preface</i>	<i>page ix</i>
<i>Acknowledgments</i>	xiii
<b>1 Basic Considerations . . . . .</b>	<b>1</b>
1.1 Vector Operations	1
1.1.1 Algebra and Computations	1
1.1.2 Vector Calculus—Velocity and Acceleration	9
1.2 Newtonian Mechanics	13
1.2.1 Newton’s Laws	13
1.2.2 Systems of Units	15
1.2.3 Energy and Momentum	17
1.3 Biographical Perspective	21
<b>2 Particle Kinematics . . . . .</b>	<b>30</b>
2.1 Path Variables	30
2.1.1 Tangent and Normal Components	31
2.1.2 Parametric Description of Curves	38
2.1.3 Binormal Direction and Torsion of a Curve	43
2.2 Rectangular Cartesian Coordinates	45
2.3 Curvilinear Coordinates	50
2.3.1 Cylindrical and Polar Coordinates	51
2.3.2 Spherical Coordinates	58
2.3.3 Arbitrary Curvilinear Coordinates	64
2.4 Mixed Kinematical Descriptions	73
<b>3 Relative Motion . . . . .</b>	<b>91</b>
3.1 Coordinate Transformations	91
3.1.1 Rotation Transformations	92
3.1.2 Rotation Sequences	99
3.2 Displacement	112
3.3 Time Derivatives	119
3.4 Angular Velocity and Acceleration	127
3.4.1 Analytical Description	127
3.4.2 Procedure	128
	<b>v</b>

3.5	Velocity and Acceleration Analysis Using a Moving Reference Frame	134
3.6	Observations from a Moving Reference Frame	147
<b>4</b>	<b>Kinematics of Constrained Rigid Bodies . . . . .</b>	<b>173</b>
4.1	General Equations	173
4.2	Eulerian Angles	178
4.3	Interconnections and Linkages	183
4.4	Rolling	200
<b>5</b>	<b>Inertial Effects for a Rigid Body . . . . .</b>	<b>228</b>
5.1	Linear and Angular Momentum	228
5.1.1	System of Particles	229
5.1.2	Rigid Body—Basic Equations	233
5.1.3	Kinetic Energy	235
5.2	Inertia Properties	240
5.2.1	Moments and Products of Inertia	241
5.2.2	Transformations	253
5.2.3	Inertia Ellipsoid	263
5.2.4	Principal Axes	267
5.3	Rate of Change of Angular Momentum	275
<b>6</b>	<b>Newton–Euler Equations of Motion . . . . .</b>	<b>296</b>
6.1	Fundamental Equations	296
6.1.1	Basic Considerations	296
6.1.2	Procedural Steps	300
6.2	Planar Motion	319
6.3	Newton–Euler Equations for a System	331
6.4	Momentum and Energy Principles	338
6.4.1	Impulse–Momentum Principles	338
6.4.2	Work–Energy Principles	343
6.4.3	Collisions of Rigid Bodies	359
<b>7</b>	<b>Introduction to Analytical Mechanics . . . . .</b>	<b>391</b>
7.1	Background	391
7.1.1	Principle of Virtual Work	392
7.1.2	Principle of Dynamic Virtual Work	394
7.2	Generalized Coordinates and Kinematical Constraints	396
7.2.1	Selection of Generalized Coordinates	397
7.2.2	Constraint Equations	400
7.2.3	Configuration Space	408
7.3	Evaluation of Virtual Displacements	414
7.3.1	Analytical Method	415
7.3.2	Kinematical Method	419

<b>Contents</b>	<b>vii</b>
7.4 Generalized Forces	426
7.4.1 Definition of Generalized Forces	426
7.4.2 Relation Between Constraint Forces and Conditions	431
7.4.3 Conservative Forces	444
7.5 Lagrange's Equations	446
7.6 Solution of Equations for Holonomic Systems	466
<b>8 Constrained Generalized Coordinates . . . . .</b>	<b>492</b>
8.1 Lagrange's Equations—Constrained Case	492
8.2 Computational Methods	508
8.2.1 Algorithms	510
8.2.2 Numerical Error Checking	520
8.2.3 Initial Conditions	521
8.2.4 Analysis of Coulomb Friction	536
<b>9 Alternative Formulations . . . . .</b>	<b>552</b>
9.1 Hamilton's Principle	552
9.1.1 Derivation	553
9.1.2 Calculus of Variations	558
9.1.3 Ritz Series Method	565
9.2 Generalized Momentum Principles	571
9.2.1 Hamilton's Equations	571
9.2.2 Conservation of the Hamiltonian	578
9.2.3 Ignorable Coordinates and Routh's Method	582
9.3 Formulations with Quasi-Coordinates	588
9.3.1 Quasi-Velocities and Quasi-Coordinates	589
9.3.2 Gibbs–Appell Equations	594
9.3.3 Kane's Equations	616
9.3.4 Relationship of the Formulations	618
<b>10 Gyroscopic Effects . . . . .</b>	<b>637</b>
10.1 Free Motion	637
10.1.1 Axisymmetric Bodies	637
10.1.2 Arbitrary Bodies	643
10.1.3 Poinsot's Construction for Arbitrary Bodies	647
10.2 Spinning Top	656
10.3 Gyroscopes for Inertial Guidance	672
10.3.1 Free Gyroscope	672
10.3.2 Gyrocompass	677
10.3.3 Single-Axis Gyroscope	685
<i>Appendix</i>	697
<i>Answers to Selected Homework Problems</i>	703
<i>Index</i>	719



## Preface

It has been more than a decade since the second edition of *Advanced Engineering Dynamics* was published. Although I was pleased with that effort, my experience teaching dynamics with that book as a companion has given me insights that I either did not have or did not fully appreciate. I tried to satisfy multiple objectives as I wrote the present book. I wished to convey both physical and analytical understanding of the fundamental principles, and to expose the beauty of the discipline as a tightly woven sequence of concepts. I wanted to address the complexities of real-world engineering problems and explore the implications of dynamics for other subjects, but to do so in a manner that is accessible to those who come to it from a wide range of experiences. I wanted to provide a self-contained resource from which the motivated reader could learn directly. At first, I thought this book would just be a third edition of *Advanced Engineering Dynamics*, but as I progressed, I realized that the expanded scope and the amount of material that is either new or redone necessitated treating it as a new work.

The subject of dynamics is an interdisciplinary blend of physics, applied mathematics, computational methods, and basic logic. The least difficult aspect of the subject is the basic physical laws, most of which are at least a century old. A primary element that has moved the study of dynamics from natural philosophy to engineering is the development of powerful tools for describing motion and for solving equations of motion. Throughout my career I have operated under the premise that the world is complicated, and that a good text should prepare the student to address these complications. One of the methods I use here to meet this imperative is to provide examples that carefully guide the reader from the inception of a solution to its conclusion. I have tried to select examples that have most of the elements one might encounter in practice but are not so intricate as to mask the tautological features of the solution. An important feature of these examples is that the question of why a solution is assembled in a certain manner is regarded to be as important as the actual steps. In many cases I have used the same system to illustrate alternative approaches or different topics, which tends to give the treatment of those systems some of the aspects of the case study approach.

Almost every section of the text has been rewritten relative to *Advanced Engineering Dynamics*, and yet it should be clearly recognizable as being a descendant of its predecessor. New explanations for fundamental concepts have been introduced. Derivations have been reworked, sometimes to increase their generality and sometimes to enhance their elegance, but always to make them more accessible. Like the previous text,



Chapter 1 develops the fundamental physical laws for a particle, but a section has been added to help the reader use mathematical software as an analytical aid. The early pioneers, who provided us with most of the basic laws and concepts, were correctly considered to be natural philosophers because they provided a framework for understanding how our world works. Partially as a recognition of their importance, I have expanded the biographical section at the conclusion of Chapter 1. I have also tried to bring out this philosophical perspective in the technical development.

Kinematics is the framework supporting the laws of dynamics. Being comfortable with the former vastly aids one to address the various kinetics concepts. For this reason a thorough treatment of the kinematics of particle and rigid-body motion is the focus of the initial development. The development is broad without going into specialized concepts that are primarily used in a confined topical area. The treatment in Chapter 2 of the kinematics of particle motion now derives the basic formulas for cylindrical and spherical coordinates prior to the tensor-oriented derivation of the comparable formulas for arbitrary orthogonal coordinate systems. This enables one to omit the more mathematical derivation without sacrificing fundamental concepts. An item of particular note is the expanded exploration in Chapter 3 of displacement of points relative to various reference frames, which should clarify many of the problematic aspects of the description of relative motion. I have found that it significantly assists students who are not practiced in visualizing spatial motion, and students in computer-aided design have told me that it aided them greatly in that subject. More important, the treatment leads to a derivation of the kinematics equations for relative motion that is simultaneously elegant and intuitive—there should be no misunderstanding of the significance of the various terms. Chapter 4 addresses the kinematics of systems that are subject to kinematical constraints, with an emphasis on linkages and rolling. The modifications here relative to the previous text are mostly incremental, but greater emphasis is now placed on the parallelism of the analysis of displacement, velocity, and acceleration. The example of a cardan joint should be enlightening in this regard.

The treatment of momentum-based concepts for rigid-body motion has now been split into two chapters. Chapter 5 focuses on the fundamental concept of angular momentum and the implications of its variability. The treatment of inertia properties has been expanded. The emphasis in this chapter is on making the angular momentum of a rigid body a quantity that the reader understands on a fundamental physical level, rather than merely being a quantity to be evaluated. These concepts are employed in Chapter 6 to implement the Newton–Euler equations for a single rigid body. The extension of such a formulation to a system of rigid bodies has been expanded. The chapter closes with a treatment of impulsive forces and their role in collisions, which is a topic that was omitted from the previous text.

Prior to delving into the mathematical concepts associated with analytical mechanics, the treatment in Chapter 7 begins by developing the principle of virtual work and applying it to a rigid frame and the analogous dynamic linkage. Seeing how the principle of dynamic virtual work, which has been incorrectly attributed to d’Alembert, can be used directly to formulate equations of motion enables one to view the concepts of analytical mechanics from the Newton–Euler perspective. This approach provides a strong

## Preface

xi

motivation for the theoretical developments that follow. A noteworthy aspect of Chapter 7 is the expanded usage of the configuration space in conjunction with generalized coordinates, so that all of the basic aspects of Lagrangian mechanics now receive a parallel treatment between the configuration and physical spaces. This is the area in which my awareness has expanded most. It is also an area in which misconception is occasionally encountered in the technical literature. For example, a recent journal article stated that virtual displacement and virtual work are confusing concepts! A primary objective of Chapter 7 is to make it unlikely that such statements will continue to be made. The reader will find graphical descriptions of scleronomic, rheonomic, and nonholonomic constraints that should enhance understanding of their unifying features, as well as their differences. One of the desirable outcomes of the presentation should be a greater understanding of the fundamental philosophy underlying analytical mechanics, and of the associated concepts pertaining to generalized coordinates, generalized velocities, and virtual displacement.

Chapter 8 explores reasons why one might need to employ Lagrange's equations with constrained generalized coordinates, and then goes on to present solution methods for the differential equations of such systems. The treatment has been expanded considerably. Several numerical algorithms for solving such equations of motion consistent with constraint equations are examined. The algorithms are worked through carefully, and their relative merits are discussed. The objective here is to prepare the reader to handle situations involving nonholonomic constraints, friction, and geometrical complexity, all of which are at the forefront of contemporary research and practice. The computed results for the example of unsteady rolling of a disk should be of interest to all. I am not sure that the nature of this solution has been recognized previously.

Chapter 9 is a treatment of alternative formulations of equations of motion. Discussion of alternative analytical approaches to formulating equations of motion was reserved for this chapter because I believe it is best to begin by providing a set of tools that can be employed reliably, even though they may not be optimal for any one situation. The reader who has reached the later chapters will have the level of capability required to appreciate the availability of alternatives. Much of the material in this chapter did not appear in *Advanced Engineering Dynamics*. It begins with an introduction to calculus of variations in conjunction with Hamilton's principle to derive equations of motion for continua. Usage of variational principles to formulate approximate solutions of field equations was pioneered by Ritz, whom I hold in high esteem. Although the topic is tangential to a course in rigid-body dynamics, everyone should recognize that the study of vibratory systems is intimately dependent on classical mechanics. A large part of this chapter is devoted to explorations of the Gibbs–Appell equations and Kane's equations. I have endeavored here to clarify the relationship between these formulations and to give a balanced discussion of their relative merits. Writing Chapters 8 and 9 has increased my esteem for Lagrange's contribution; the discussion explains why.

Chapter 10, which treats gyroscopic effects, has been updated. The discussion of inertial guidance systems has been clarified and modernized. Although the latest guidance technology is less reliant on these concepts, understanding them serves to enhance mastery of dynamics. One of the developments in this chapter that anyone should find

interesting is the analysis of the precession of the equinoxes, which appears as an example in Chapter 10 based on the analysis of gravitational torque in Chapter 5.

This project has required more effort than any of my prior books. In part this comes from treating this book as a new work, while simultaneously making sure it retains what was good in the previous version. However, the most time-consuming aspect entailed the selection of additional examples, as well as the modification of examples I used previously. Also, as an instructor, I realized that keeping a course and textbook fresh requires a large number of homework exercises. The instructor who uses this text will find that both the number and variety of homework exercises have been greatly increased.

As I look over the finished manuscript, I am quite satisfied. I believe that I have met the goals that guided me throughout this project. I hope you agree.

## Acknowledgments

From a personal standpoint I have found that the most vital prerequisite to writing a technical book is enthusiasm for the project. For this, I thank all the students I have worked with at Georgia Tech, both students in my graduate dynamics courses and the research assistants with whom I have worked. Seeing them progress as they studied with *Advanced Engineering Dynamics* as their guide was rewarding and made me desirous to build on that success. Being able to try out new ideas on them was enormously helpful, and their tolerance as I arranged and rearranged topics is very much appreciated. I thank all of the faculty in the G. W. Woodruff School of Mechanical Engineering at Georgia Tech for tolerating my focus on this project, which often caused me to neglect my usual academic chores. Two of my colleagues warrant special mention. Dr. Aldo Ferri is exceptionally knowledgeable and insightful. If I had some idea or approach that I was not certain would be suitable, he was the first person whose counsel I would seek. I especially valued his willingness to bring me back to reality when it was warranted to do so. I also very much appreciate John Papastavridis. He is a remarkable resource for anyone who is concerned with the history of mechanics or who needs to find a good entry to some of the less-explored areas of dynamics.

Many faculty at other institutions have approached me in a variety of venues. There is no way to replace the gratification that came from their compliments for *Advanced Engineering Dynamics*. I am sure that my desire to sustain such gratification was responsible in some measure for my decision to redo that work. One person who stands out in particular in this regard is Weidong Zhu at the University of Maryland Baltimore Campus. His suggestions were very useful.

Peter Gordon, my editor at Cambridge University Press, deserves special recognition. If anyone needs a definition of “enthusiasm,” they should have a conversation with Peter. I am especially impressed by his overall perspective for the fundamental issues in the field of dynamics, as well as his general understanding of the publishing world. I found our conversations to be quite informative.

Although my colleagues and students were vital to this effort, I could not have pursued it without the support of my family. My grandchildren, Leah Morgan Ginsberg, Elizabeth Rachel Ginsberg, and Abigail Rose Ginsberg, are wondrous in individual ways, and the careful reader will find them mentioned somewhere herein. One of my hopes is that seeing their grandfather pursue a self-guided path to learning will stimulate them to do the same. My son, Mitchell Robert Ginsberg, and his wife, Tracie Sears Ginsberg, amaze me with the diversity of their talents, especially in their parenting skills.

My son, Daniel Brian Ginsberg, and his wife, Jessica Rose, are equally awe-inspiring, especially in their dedication to improving our society. My children and grandchildren show tremendous tolerance for my preoccupation with research, teaching, and writing and gave me much encouragement when I was ill.

Three who are no longer with us were very important to this effort. My mother, Raechel Bass Ginsberg, pushed me to excel. Although I did not always appreciate how important her emphasis was, I now hope that I am equally successful in this aspect relative to my grandchildren. My father, David Ginsberg, set an intellectual example for me that is unmatched. Despite never going beyond the eighth grade, he showed me the joy of intellectual achievement. He learned for the sake of doing so. He voraciously read all subjects, and did so with me in his lap when I was young. His example started me off on this long path. The last of the departed whom I very much miss is my dog Tundra, a magnificent and imposing Alaskan Malamute, who despite her great size was the most gentle animal I have ever encountered. She loved everyone, especially children, and taught me that there is another plane of existence. For her, a long brisk walk was a great reward, and those walks often provided the mechanism by which I changed my perspective when I could not resolve thorny issues in the preparation of this book.

More than anyone else, I am indebted to my wife, Rona Axelrod Ginsberg, who is the foundation of our family. Even after thirty-nine years of marriage, she still surprises me with her talents and expertise. Her love, understanding, support, and dedication sustained me. I sometimes think that I do not adequately convey my love for her, and I fear that my effort here is equally inadequate.

## CHAPTER 1

# Basic Considerations

Since ancient times many researchers have devoted themselves to predicting and explaining how bodies move under the action of forces. This is the scope of the subject of dynamics, which consists of two phases: kinematics and kinetics. A kinematical analysis entails a quantitative description of the motion of bodies without concern for what is causing the motion. Sometimes that is all that is required, as would be the case if we needed to ascertain the output motion of a gear system or linkage. More significantly, a kinematical analysis will always be a key component of a kinetics study, which analyzes the interplay between forces and motion. Indeed, we will see that the kinematical description provides the skeleton on which the laws of kinetics are applied.

A primary objective will be the development of procedures for applying kinematics and kinetics principles in a logical and consistent manner, so that one may successfully analyze systems that have novel features. Particular emphasis will be placed on three-dimensional systems, some of which feature phenomena that are counterintuitive for those whose experience is limited to systems that move in a plane. A related objective is development of the capability to address realistic situations encountered in current engineering practice.

The scope of this text is limited to situations that are accurately described by the classical laws of physics. The only kinetics laws we will take to be axiomatic are those of Newton, which are accurate whenever the object of interest is moving much more slowly than the speed of light. Newton's Laws pertain only to a particle. The derivation of a variety of principles that extend these laws to bodies having significant dimensions will be treated in depth. We will limit our attention to systems in which all bodies may be considered to be particles or rigid bodies. The dynamics of flexible bodies, which is the subject of vibrations, is founded on the kinematics and kinetics concepts we will establish. We shall begin by reviewing the fundamental aspects of Newton's Laws. Although the reader is likely to have already studied these concepts, the intent is to provide a consistent foundation for later developments.

## 1.1 VECTOR OPERATIONS

### 1.1.1 Algebra and Computations

Almost every quantity of importance in dynamics is vectorial in nature. Such quantities have a direction in which they are oriented, as well as a magnitude. The kinematical



vectors of primary importance for our initial studies are position, velocity, and acceleration, and the kinetics quantities are force and moment. Some quantities have magnitude and direction, but are not vectors. One example, which will play a major role in Chapter 3, is a finite rotation about an axis. An additional requirement for vector quantities is that they add according to the parallelogram law. This entails a graphical representation of vectors in which an arrow indicates the direction of the vector and the length of the arrow is proportional to the magnitude of the vector. A graphical representation of the summation operation is shown in Fig. 1.1(a), which shows that the addition of two vectors  $\vec{A}$  and  $\vec{B}$  may be constructed in either of two ways. Vectors  $\vec{A}$  and  $\vec{B}$  may be placed tail to tail, and then considered to form two sides of a parallelogram. Then  $\vec{A} + \vec{B}$  is the main diagonal, with the sense defined to be from the common tail to the opposite corner. An alternative picture places the tail of  $\vec{B}$  at the head of  $\vec{A}$ . The sum then extends from the tail of  $\vec{A}$  to the head of  $\vec{B}$ .




Figure 1.1. Diagrammatical construction of the sum and difference of two vectors.

An important aspect of these constructions is that a sum is independent of the sequence in which the vectors are added. This is the commutative property, which is stated as

$$\vec{A} + \vec{B} = \vec{B} + \vec{A}. \quad (1.1.1)$$

A diagram showing the sum of three vectors leads to the associative property,

$$(\vec{A} + \vec{B}) + \vec{C} = \vec{A} + (\vec{B} + \vec{C}). \quad (1.1.2)$$

Another important property comes from the observation that multiplying a vector by a scalar number does not affect its direction, but the magnitude is multiplied by that factor's absolute value, that is,

$$|\gamma \vec{A}| = |\gamma| |\vec{A}|. \quad (1.1.3)$$

A corollary of this property is that multiplying  $\vec{A} + \vec{B}$  in Fig. 1.1(a) by a scalar changes the length of the diagonal, which requires that the individual sides be scaled by the same factor. Thus,

$$\gamma (\vec{A} + \vec{B}) = \gamma \vec{A} + \gamma \vec{B}, \quad (1.1.4)$$

which is the distributive property for vector addition.


If the  $\gamma$  factor in Eq. (1.1.3) is negative,  $\gamma \vec{A}$  will be parallel to  $\vec{A}$ , but in the opposite sense. This observation leads to graphical rules for subtracting vectors. Multiplying a vector by  $-1$  only reverses the sense of the vector. Because  $\vec{A} - \vec{B} \equiv \vec{A} + (-\vec{B})$ , the difference of two vectors may be constructed in one of three ways, as depicted graphically in Fig. 1.1(b). The difference may be formed by placing  $\vec{A}$  and  $-\vec{B}$  tail to tail,

## 1.1 Vector Operations

3

which forms a parallelogram. Then  $\vec{A} - \vec{B}$  extends from the common tail to the opposite corner. A different rule leading to the same result comes from the observation that the parallelogram in Fig. 1.1(b) is identical to the one in Fig. 1.11(a). Thus the difference may be formed by placing  $\vec{A}$  and  $\vec{B}$  tail to tail, so that  $\vec{A} - \vec{B}$  extends from the tip of  $\vec{B}$  to the tip of  $\vec{A}$ . The third construction forms  $\vec{A} - \vec{B}$  by placing the tail of  $-\vec{B}$  at the head of  $\vec{A}$ , in which case  $\vec{A} - \vec{B}$  extends from the tail of  $\vec{A}$  to the tip of  $-\vec{B}$ . Regardless of how one goes about forming the difference, it is wise to verify that forming  $\vec{B} + (\vec{A} - \vec{B})$  actually gives  $\vec{A}$ .

We will occasionally employ a diagrammatic approach to vector operations for derivations, but it is awkward and not easily implemented in mathematical software, especially for three-dimensional situations. Representation of vectorial quantities in component form addresses these issues. Let  $xyz$  denote a set of orthogonal Cartesian coordinates. Unit vectors  $\vec{i}$ ,  $\vec{j}$ , and  $\vec{k}$ , whose magnitude is unity without dimensionality, are defined to be parallel to the  $x$ ,  $y$ , and  $z$  axes, respectively. To represent its components, vector  $\vec{A}$  in Fig. 1.2 has been situated with its tail at the origin of  $xyz$ .



**Figure 1.2.** Unit vectors of a Cartesian coordinate system and the construction of vector components.

The edges of the box in the figure are constructed from the three lines that are perpendicular to a coordinate plane and intersect the tip of  $\vec{A}$ . The length of each line is the component of the vector, denoted with the subscript of the associated axis. (The length of a side would be the negative of the corresponding component's value if that side projected onto the negative coordinate axis.) Figure 1.2 shows that a vector along each edge of the box may be constructed by multiplying the component by the corresponding unit vector; see Eq. (1.1.3). The three such vectors depicted in the figure are situated head to tail, so their sum extends from the tail of the first,  $A_x\vec{i}$ , to the head of the third,  $A_z\vec{k}$ , but that is the original vector  $\vec{A}$ . Hence,

$$\vec{A} = A_x\vec{i} + A_y\vec{j} + A_z\vec{k}. \quad (1.1.5)$$

This is the *component representation of a vector*.

The utility of a component representation is that operations can be performed on the individual components without recourse to diagrams. By the Pythagorean theorem the magnitude of  $\vec{A}$  is

$$|\vec{A}| = (A_x^2 + A_y^2 + A_z^2)^{1/2}. \quad (1.1.6)$$

In many situations we need to construct a unit vector parallel to a vector. This is readily obtained from the preceding equation as

$$\vec{A} = |\vec{A}| \vec{e}_A \iff \vec{e}_A = \frac{\vec{A}}{|\vec{A}|}. \quad (1.1.7)$$

The operations of adding or subtracting vectors are performed by operating on the individual components in accord with the properties in Eqs. (1.1.2) and (1.1.4):

$$\begin{aligned} \vec{A} \pm \vec{B} &= (A_x \vec{i} + A_y \vec{j} + A_z \vec{k}) \pm (B_x \vec{i} + B_y \vec{j} + B_z \vec{k}) \\ &= (A_x \vec{i} \pm B_x \vec{i}) + (A_y \vec{j} \pm B_y \vec{j}) + (A_z \vec{k} \pm B_z \vec{k}), \end{aligned}$$

$$\vec{A} \pm \vec{B} = (A_x \pm B_x) \vec{i} + (A_y \pm B_y) \vec{j} + (A_z \pm B_z) \vec{k}. \quad (1.1.8)$$


There are two types of products of two vectors. The *dot product* is also known as the *scalar product* because it is a scalar result. It is defined in terms of the angle  $\phi$  between the vectors when they are placed tail to tail, according to

$$\vec{A} \cdot \vec{B} \equiv |\vec{A}| |\vec{B}| \cos \phi. \quad (1.1.9)$$

To avoid ambiguity, we limit the angle to  $0 \leq \phi \leq \pi$ . It is clear from this definition that the order in which a product is taken does not affect the result, so a dot product is commutative:

$$\vec{A} \cdot \vec{B} = \vec{B} \cdot \vec{A}. \quad (1.1.10)$$

One of the reasons why a dot product is useful is described by Fig. 1.3, where  $|\vec{B}| \cos \phi$  is shown to be the projection of  $\vec{B}$  in the direction of  $\vec{A}$ , in other words, the component of  $\vec{B}$  in the direction of  $\vec{A}$ . That figure also shows that  $|\vec{A}| \cos \phi$  is the component of  $\vec{A}$  in the direction of  $\vec{B}$ . Thus a dot product may be interpreted to be the magnitude of one vector multiplied by the parallel component of the other vector. In the event where they form an obtuse angle,  $\pi/2 < \phi \leq \pi$ , the dot product will be negative, meaning that the component is in the opposite sense from the vector on which it is projected.



**Figure 1.3.** Dot product of two vectors, showing the component of each vector parallel to the other.

A dot product can be proven to be distributive, which may be stated as

$$(\alpha \vec{A} + \beta \vec{B}) \cdot \vec{C} = \alpha \vec{A} \cdot \vec{C} + \beta \vec{B} \cdot \vec{C}. \quad (1.1.11)$$

The significance of this property is that it enables us to evaluate a dot product directly in terms of the components of each vector. This comes about from the fact that  $\vec{i}$ ,  $\vec{j}$ , and  $\vec{k}$  are mutually orthogonal unit vectors, so that

$$\begin{aligned} \vec{i} \cdot \vec{i} = \vec{j} \cdot \vec{j} = \vec{k} \cdot \vec{k} &= 1, \\ \vec{i} \cdot \vec{j} = \vec{j} \cdot \vec{i} = \vec{j} \cdot \vec{k} = \vec{k} \cdot \vec{j} &= \vec{k} \cdot \vec{i} = \vec{i} \cdot \vec{k} = 0. \end{aligned} \quad (1.1.12)$$

## 1.1 Vector Operations

5

Combining these fundamental dot products with Eq. (1.1.11) leads to evaluation of a dot product according to

$$\begin{aligned}\vec{A} \cdot \vec{B} &= (A_x \vec{i} + A_y \vec{j} + A_z \vec{k}) \cdot (B_x \vec{i} + B_y \vec{j} + B_z \vec{k}) \\ &= (A_x \vec{i}) \cdot (B_x \vec{i}) + (A_x \vec{i}) \cdot (B_y \vec{j}) + (A_x \vec{i}) \cdot (B_z \vec{k}) \\ &\quad + (A_y \vec{j}) \cdot (B_x \vec{i}) + (A_y \vec{j}) \cdot (B_y \vec{j}) + (A_y \vec{j}) \cdot (B_z \vec{k}) \\ &\quad + (A_z \vec{k}) \cdot (B_x \vec{i}) + (A_z \vec{k}) \cdot (B_y \vec{j}) + (A_z \vec{k}) \cdot (B_z \vec{k}),\end{aligned}$$

$$\vec{A} \cdot \vec{B} = A_x B_x + A_y B_y + A_z B_z.$$

(1.1.13)


A useful corollary of the preceding is that the length of a vector may be evaluated from a dot product,

$$|\vec{A}| = \sqrt{\vec{A} \cdot \vec{A}}. \quad (1.1.14)$$

The *cross product* of two vectors is also known as the *vector product*, because it is defined to be a vector in the direction perpendicular to the plane formed when the vectors are brought tail to tail. The magnitude of a cross product is defined as

$$|\vec{A} \times \vec{B}| = |\vec{A}| |\vec{B}| \sin \phi, \quad (1.1.15)$$

where  $\phi$  is the angle between the vectors, as it is for the dot product. As shown in Fig. 1.4,  $|\vec{B}| \sin \phi$  is the magnitude of the component of  $\vec{B}$  perpendicular to  $\vec{A}$ , and  $|\vec{A}| \sin \phi$  is the component of  $\vec{A}$  perpendicular to  $\vec{B}$ . Thus the magnitude of a cross product may be interpreted as the magnitude of one vector multiplied by the perpendicular component of the other vector. Figure 1.4 also shows that the sense of the cross-product direction is determined by the right-hand rule, in which the vectors are brought tail to tail, and the fingers of the right hand curl from the first vector to the second, as indicated by the curling arrow. The extended thumb then gives the orientation of the cross product, which would be out of the plane depicted by Fig. 1.4.



**Figure 1.4.** Construction of the cross product of two vectors showing the component of one vector perpendicular to the other. The curling arrow indicates the sense in which the fingers of the right hand should curl to form  $\vec{A} \times \vec{B}$ .

A cross product is not commutative because switching the sequence in which the product is formed reverses the sense of the curling arrow in Fig. 1.4. Thus,

$$\vec{B} \times \vec{A} = -\vec{A} \times \vec{B}. \quad (1.1.16)$$

The cross product does have the associative and distributive properties:

$$\begin{aligned}(\vec{A} \times \vec{B}) \times \vec{C} &= \vec{A} \times (\vec{B} \times \vec{C}), \\ (\alpha \vec{A} + \beta \vec{B}) \times \vec{C} &= \alpha \vec{A} \times \vec{C} + \beta \vec{B} \times \vec{C}.\end{aligned} \quad (1.1.17)$$

These properties lead to a rule for evaluating cross products in terms of vector components. We require that  $xyz$  be a right-handed coordinate system, so the fact that the unit vectors of the coordinate are mutually orthogonal gives

$$\begin{aligned}\bar{i} \times \bar{i} &= \bar{j} \times \bar{j} = \bar{k} \times \bar{k} = 0, \\ \bar{i} \times \bar{j} &= \bar{k}, \quad \bar{j} \times \bar{k} = \bar{i}, \quad \bar{k} \times \bar{i} = \bar{j}, \\ \bar{j} \times \bar{i} &= -\bar{k}, \quad \bar{k} \times \bar{j} = -\bar{i}, \quad \bar{i} \times \bar{k} = -\bar{j}.\end{aligned}\tag{1.1.18}$$

A mnemonic device for remembering these products is to consider positive alphabetical order to proceed as  $\bar{i}$  to  $\bar{j}$  to  $\bar{k}$ , then back to  $\bar{i}$ . Applying these cross products in conjunction with the distributive law in Eqs. (1.1.17) leads to

$$\begin{aligned}\bar{A} \times \bar{B} &= (A_x \bar{i} + A_y \bar{j} + A_z \bar{k}) \times (B_x \bar{i} + B_y \bar{j} + B_z \bar{k}) \\ &= (A_x \bar{i}) \times (B_y \bar{j}) + (A_x \bar{i}) \times (B_z \bar{k}) + (A_y \bar{j}) \times (B_x \bar{i}) + (A_y \bar{j}) \times (B_z \bar{k}) \\ &\quad + (A_z \bar{k}) \times (B_x \bar{i}) + (A_z \bar{k}) \times (B_y \bar{j}) \\ &= A_x B_y \bar{k} - A_x B_z \bar{j} - A_y B_x \bar{k} + A_y B_z \bar{i} + A_z B_x \bar{j} - A_z B_y \bar{i},\end{aligned}$$

$$\bar{A} \times \bar{B} = (A_y B_z - A_z B_y) \bar{i} + (A_z B_x - A_x B_z) \bar{j} + (A_x B_y - A_y B_x) \bar{k}.\tag{1.1.19}$$

Some individuals, rather than carrying out a cross product term by term, as in the preceding evaluation, use a mnemonic device based on a determinant, specifically,

$$\bar{A} \times \bar{B} = \begin{vmatrix} \bar{i} & \bar{j} & \bar{k} \\ A_x & A_y & A_z \\ B_x & B_y & B_z \end{vmatrix} = \begin{vmatrix} A_x & A_y & A_z \\ B_x & B_y & B_z \\ \bar{i} & \bar{j} & \bar{k} \end{vmatrix}.\tag{1.1.20}$$

A common analytical approach we will encounter entails describing a vector in different ways and then equating the different descriptions. A component description of vectors enables us to convert the vector equality to a set of scalar equations, based on the fact that if two vectors are equal their like components must be equal. Thus,

$$\bar{A} = \bar{B} \iff A_x = B_x, \quad A_y = B_y, \quad \text{and} \quad A_z = B_z.\tag{1.1.21}$$


Position vectors are the fundamental kinematical quantities. In Fig. 1.5 the position vector extending from origin  $O$  to point  $P$  is labeled  $\bar{r}_{P/O}$ , which should be read as *the position vector to  $P$  from  $O$* , or equivalently, *the position of  $P$  with respect to  $O$* . Similarly, the position of point  $P$  with respect to point  $A$  is  $\bar{r}_{P/A}$ . The tail of  $\bar{r}_{P/A}$  is situated at the head of  $\bar{r}_{A/O}$ , from which it follows that adding these vectors gives the position of point  $P$  with respect to point  $O$ :

$$\bar{r}_{P/O} = \bar{r}_{A/O} + \bar{r}_{P/A}.\tag{1.1.22}$$

This construction is fundamental to many operations in dynamics.

## 1.1 Vector Operations

7



**Figure 1.5.** Observation of a moving point  $P$  by observers at points  $O$  and  $A$ .

The issue of how one carries out algebraic operations with vectors requires consideration of mathematical software. Three-dimensional vectors may be represented as matrices, which is the preferred data format for such popular programs as Matlab and Mathcad. Both programs allow one to carry out all vector operations using matrix notation. In Mathcad one proceeds by writing all vectors in matrix form and then carrying out the operations as indicated. For example, if  $\vec{A} = 1\vec{i} + 2\vec{j} + 3\vec{k}$  and  $\vec{B} = 3\vec{i} - \vec{j} - 5\vec{k}$ , then the operation of constructing a unit vector parallel to  $\vec{A} \times \vec{B}$ , then verifying that this product is indeed perpendicular to  $\vec{A}$  and  $\vec{B}$ , could proceed as

$$A := \begin{Bmatrix} 1 \\ 2 \\ 3 \end{Bmatrix}, \quad B := \begin{Bmatrix} 3 \\ -1 \\ -5 \end{Bmatrix}, \quad C := A \times B, \quad e := \frac{C}{|C|}, \quad A_1 = A * e, \quad B_1 = B * e, \quad (1.1.23)$$

where  $:=$  denotes Mathcad's equality operator, which is obtained by pressing the colon key, and the cross-product operator is obtained from the Ctrl-8 key combination. The dot product in matrix notation is obtained from the product of a three-element row matrix and a three-element column matrix, so one could evaluate the dot product in Mathcad by writing  $A^T * B$ . An alternative is to simply multiply vectors to form a dot product, as was just done, which returns a scalar value.

Matlab proceeds similarly. The cross product is implemented with the "cross" function; a dot product can be obtained from the "dot" function, or more simply as a standard row-column product. Thus, the preceding example could be carried out in Matlab as

$$A=[1 \quad 2 \quad 3]; \quad B=[3 \quad -1 \quad -5]; \quad C=\text{cross}(A,B); \\ e=C/\text{norm}(C), \quad A_1=A * e'; \quad B_1=B * e';$$


Note that the "norm" without other arguments is Matlab's function for evaluating the (Euclidean) length of a vector. If one wishes, the preceding operations could be carried out with  $A$  and  $B$  defined to be three-element columns, for example,  $A = [1; 2; 3]$ . Other mathematical software programs have similar capabilities. Also, it is possible to implement these operations symbolically in some programs by use of matrix notation.

Ultimately, how one carries out computations is a matter of personal choice. The procedure used in this text generally will implement the operations term by term using the associative and distributive properties. One reason for this choice is that the notation is somewhat more compact. The second has to do with a common situation that will



frequently arise, in which it will be necessary to combine vectors that are defined in terms of components relative to different coordinate systems. It is awkward to indicate which coordinate system a matrix is associated with, whereas the symbols used for unit vectors display that information unambiguously.

**EXAMPLE 1.1** Robotic arm  $ABC$  induces a tensile force of 5000 N in cable  $CD$ . The orientation angles are  $\theta = 25^\circ$  for link  $AB$ , which lies in the horizontal plane, and  $\gamma = 40^\circ$  for rotation of arm  $BC$ . Pin  $B$  for this rotation is horizontal and perpendicular to arm  $AB$ , so  $AB$  and  $BC$  lie in a common vertical plane. Let  $\bar{F}$  denote the force the cable exerts on the robotic arm. Determine (a) the component of  $\bar{F}$  parallel to link  $BC$ , (b) the moment of  $\bar{F}$  about end  $A$ , (c) the moment of  $\bar{F}$  about the vertical  $z$  axis, and (d) the moment of  $\bar{F}$  about arm  $AB$ .



Example 1.1

**SOLUTION** This example reviews some basic evaluations of force properties, which call for most of the standard vector operations. The cable is in tension, so it pulls the robotic arm from point  $C$  to point  $D$ . We express this as  $\bar{F} = 5000\bar{e}_{D/C}$  N, where  $\bar{e}_{D/C}$  is the notation we use for the unit vector to  $D$  from  $C$ . The first task is to determine the coordinates of point  $C$ , which we can find by constructing position vectors along arms  $AB$  and  $BC$ . We project point  $B$  onto the  $x$  and  $y$  axes to evaluate  $\bar{r}_{B/A}$ . Similarly, we project point  $C$  onto the  $xy$  plane, and then project that point onto the  $x$  and  $y$  axes. This gives

$$\bar{r}_{B/A} = 2(\cos\theta\bar{i} + \sin\theta\bar{j}) = 1.8126\bar{i} + 0.8452\bar{j} \text{ m},$$

$$\bar{r}_{C/B} = 1.5\cos\gamma(\cos\theta\bar{i} + \sin\theta\bar{j}) + 1.5\sin\gamma\bar{k} = 1.0414\bar{i} + 0.4856\bar{j} + 0.9642\bar{k}.$$

The desired position vector is the sum of these vectors:

$$\begin{aligned}\bar{r}_{C/A} &= \bar{r}_{B/A} + \bar{r}_{C/B} = (1.8126 + 1.0414)\bar{i} + (0.8452 + 0.4856)\bar{j} + (0 + 0.9642)\bar{k} \\ &= 2.8540\bar{i} + 1.3309\bar{j} + 0.9642\bar{k} \text{ m}.\end{aligned}$$

Because  $\bar{r}_{C/A}$  and  $\bar{r}_{D/A} = 3.5\bar{i}$  m are tail to tail, it follows that  $\bar{r}_{D/C} = \bar{r}_{D/A} - \bar{r}_{C/A}$ , which leads to  $\bar{e}_{D/C}$  according to

$$\begin{aligned}\bar{e}_{D/C} &= \frac{\bar{r}_{D/A} - \bar{r}_{C/A}}{|\bar{r}_{D/A} - \bar{r}_{C/A}|} = \frac{0.6460\bar{i} - 1.3309\bar{j} - 0.9642\bar{k}}{(0.6460^2 + 1.3309^2 + 0.9642^2)^{1/2}} \\ &= 0.3658\bar{i} - 0.7537\bar{j} - 0.5460\bar{k}.\end{aligned}$$

## 1.1 Vector Operations

9

Thus the force applied to the arm is

$$\vec{F} = 5000\vec{e}_{D/C} = 1829\vec{i} - 3768\vec{j} - 2730\vec{k} \text{ N.}$$

The component of  $\vec{F}$  parallel to arm  $BC$  may be obtained from a dot product with the unit vector  $\vec{e}_{C/B}$ , which is readily constructed from  $\vec{r}_{C/B}$ , whose value has already been determined. Thus,

$$\begin{aligned} F_{BC} &= \vec{F} \cdot \vec{e}_{C/B} = \vec{F} \cdot \frac{\vec{r}_{C/B}}{|\vec{r}_{C/B}|} = \vec{F} \cdot (0.6943\vec{i} + 0.3237\vec{j} + 0.6428\vec{k}) \\ &= (1829)(0.6943) + (-3768)(0.3237) + (-2730)(0.6428) = -1705 \text{ N.} \end{aligned} \quad \triangleleft$$

Negative  $F_{BC}$  indicates that the projection of  $\vec{F}$  onto line  $BC$  is opposite the sense of  $\vec{e}_{C/B}$ .

The moment of a force may be evaluated from a cross product with a position vector from the reference point for the moment to the point where the force is applied. Hence,

$$\begin{aligned} \vec{M}_A &= \vec{r}_{C/A} \times \vec{F} = (2.8540\vec{i} + 1.3309\vec{j} + 0.9642\vec{k}) \times (1829\vec{i} - 3768\vec{j} - 2730\vec{k}) \\ &= (2.8540)(-3768)\vec{k} + (2.8540)(-2730)(-\vec{j}) + (1.3309)(1829)(-\vec{k}) \\ &\quad + (1.3309)(-2730)\vec{i} + (0.9642)(1829)\vec{j} + (0.9642)(-3768)(-\vec{i}) \\ &= 9555\vec{j} - 13189\vec{k} \text{ N-m.} \end{aligned} \quad \triangleleft$$

The moment of a force about an axis may be determined by forming the moment about any point on that axis, and then evaluating the component of that moment in the direction of the axis. Thus the moment of  $\vec{F}$  about the  $z$  axis is merely the  $\vec{k}$  component of  $\vec{M}_A$ ,

$$M_{Az} = \vec{M}_A \cdot \vec{k} = -13189 \text{ N-m.} \quad \triangleleft$$

A negative value indicates that the sense of this moment is determined by aligning the extended thumb of the right hand in the  $-\vec{k}$  direction. The same reasoning shows that the moment of  $\vec{F}$  about arm  $AB$  is obtained with a dot product involving  $\vec{e}_{B/A}$ ,

$$M_{AB} = \vec{M}_A \cdot \vec{e}_{B/A} = \vec{M}_A \cdot \frac{\vec{r}_{B/A}}{|\vec{r}_{B/A}|} = 4038 \text{ N-m.} \quad \triangleleft$$

### 1.1.2 Vector Calculus—Velocity and Acceleration

The primary kinematical variables for our initial studies are position, velocity, and acceleration. Velocity is defined to be the time derivative of position, and acceleration is the time derivative of velocity, so we need to establish how to handle derivatives of vectors. Because time derivatives are performed frequently, it is standard notation to use an overdot to denote each such operation. Overbars are used here to indicate that a quantity is a vector; the reader is encouraged to use the same notation.

Most of the laws for calculus operations are the same as those for scalar variables. Their adaptation requires that vector quantities be indicated unambiguously. In the following,  $\bar{A}$  and  $\bar{B}$  are time-dependent vector functions, and  $\alpha$  and  $\beta$  are scalar functions of time.

Definition of a derivative:

$$\frac{d\bar{A}}{dt} \equiv \dot{\bar{A}} \equiv \lim_{\Delta t \rightarrow 0} \frac{\bar{A}(t + \Delta t) - \bar{A}(t)}{\Delta t} = \lim_{\Delta t \rightarrow 0} \frac{\bar{A}(t) - \bar{A}(t - \Delta t)}{\Delta t}. \quad (1.1.24)$$

Definite integration:

$$\text{If } \dot{\bar{A}} = \bar{B}, \text{ then } \bar{B}(t) = \bar{B}(t_0) + \int_{t_0}^t \bar{A}(\tau) d\tau. \quad (1.1.25)$$

Derivative of a sum:

$$\frac{d}{dt} (\bar{A} + \bar{B}) = \dot{\bar{A}} + \dot{\bar{B}}. \quad (1.1.26)$$

Derivative of products:

$$\begin{aligned} \frac{d}{dt} (\alpha \bar{A}) &= \dot{\alpha} \bar{A} + \alpha \dot{\bar{A}}, \\ \frac{d}{dt} (\bar{A} \cdot \bar{B}) &= \dot{\bar{A}} \cdot \bar{B} + \bar{A} \cdot \dot{\bar{B}}, \\ \frac{d}{dt} (\bar{A} \times \bar{B}) &= \dot{\bar{A}} \times \bar{B} + \bar{A} \times \dot{\bar{B}}. \end{aligned} \quad (1.1.27)$$

As an immediate consequence of these properties, all calculus operations may be performed in terms of vector components. We consider here only situations in which  $xyz$  is a fixed coordinate system, so that  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  are constant vectors, which means that  $d\bar{i}/dt = d\bar{j}/dt = d\bar{k}/dt = 0$ . We then find that

$$\frac{d\bar{A}}{dt} = \frac{d}{dt} (A_x \bar{i} + A_y \bar{j} + A_z \bar{k}) = \dot{A}_x \bar{i} + \dot{A}_y \bar{j} + \dot{A}_z \bar{k}. \quad (1.1.28)$$

A common situation that arises in many phases of our study of kinematics involves a vector that depends on some parameter  $\alpha$ , which in turn varies with time. Differentiation of the vector with respect to time in this circumstance can be performed with the chain rule:

$$\frac{d\bar{A}}{dt} = \frac{d\bar{A}}{d\alpha} \frac{d\alpha}{dt} \equiv \dot{\alpha} \frac{d\bar{A}}{d\alpha}. \quad (1.1.29)$$

The chain rule may be extended by partial differentiation to situations in which the vector depends on two or more time-dependent parameters, according to

$$\frac{d\bar{A}}{dt} = \dot{\alpha} \frac{\partial \bar{A}}{\partial \alpha} + \dot{\beta} \frac{\partial \bar{A}}{\partial \beta} + \dots. \quad (1.1.30)$$

In the present notation, where  $\bar{r}_{P/O}$  denotes the position of point  $P$  with respect to the origin  $O$  of a fixed coordinate system, then the velocity and acceleration of that point are

$$\boxed{\bar{v} \equiv \dot{\bar{r}}_{P/O}, \quad \bar{a} \equiv \ddot{\bar{r}}_{P/O}.} \quad (1.1.31)$$

## 1.1 Vector Operations

11

It should be noted that no subscripts have been used to denote the velocity and acceleration vectors. If there is any ambiguity as to the point whose velocity is under consideration, the notation will be  $\bar{v}_P$  and  $\bar{a}_P$ , but even then there is no need to indicate in the velocity and acceleration what the origin is. This is so because different fixed observers all see the same motion. This may be proved from Fig. 1.5, where  $\bar{r}_{P/O}$  is the position seen by an observer at the origin, and  $\bar{r}_{P/A}$  is the position of point  $P$  as seen by an observer at point  $A$ . Equation (1.1.22) describes  $\bar{r}_{P/O}$  as the sum of the other two vectors. If point  $A$  is stationary, then  $\bar{r}_{A/O}$  is constant and  $d\bar{r}_{A/O}/dt = \bar{0}$ . It follows that


$$\bar{v}_P = \frac{d}{dt}\bar{r}_{P/O} = \frac{d}{dt}(\bar{r}_{A/O} + \bar{r}_{P/A}) = \frac{d}{dt}\bar{r}_{P/A}, \quad (1.1.32)$$

which shows that the velocity of a point is the derivative of the position vector to that point from any fixed point. The same must be true for acceleration because it is the derivative of the velocity.

In Chapter 3 we will treat situations in which the reference frame moves, in which case we will be interested in the motion relative to that reference frame. Equation (1.1.32) defines the *absolute velocity*, whereas the velocity seen by a moving observer is a *relative velocity*. The same terminology applies to the description of acceleration. If it is not specified otherwise, the words velocity and acceleration should be understood to mean absolute quantities.

Our initial studies are limited to situations in which the moving body may be considered to be a particle. By definition, a particle occupies only a single point in space. As time evolves, the particle will occupy a succession of positions. The locus of all positions occupied by the point is its *path*. One can obtain a visual representation of a path by illuminating the point and then taking a long-exposure photograph. Position, movement along a path, and velocity are inherently important because we can readily sense them. Acceleration is difficult for most individuals to observe without instrumentation. On the other hand, if we are subjected to an acceleration, our sensory system gives us an indication of its magnitude and direction primarily based on the internal forces that are generated. The time derivative of  $\bar{a}$ , which is called the *jerk*, primarily occurs in considerations of ride comfort for vehicles.

**EXAMPLE 1.2** A radar station on the ground at origin  $O$  tracks airplane  $A$  by measuring the distance  $r$ , the angle  $\theta$  in the horizontal  $xy$  plane, and the angle of elevation  $\beta$ . It is observed that these variables closely fit  $r(t) = 2000 + 100t$  m,  $\theta(t) = \pi/2[1 - \exp(-0.15t)]$  rad, and  $\beta = \pi/3 - 0.1\sqrt{t}$  rad, where  $t$  is measured in seconds. (a) Determine the velocity of the airplane at  $t = 2$  s according to a finite central difference approximation based on the change of the position vector  $\bar{r}$  during an interval of 1 ms. (b) Determine the velocity of the airplane at  $t = 2$  s by differentiating the  $xyz$  components of  $\bar{r}$ .



Example 1.2

**SOLUTION** The analysis brings to the fore many of the basic vector operations, but a more efficient evaluation of the velocity would use the spherical coordinate formulation we will develop in the next chapter. Both specified solution procedures require a description of the position vector. The projection of line  $OA$  onto the  $z$  axis is the length of the vertical dashed line. We obtain the  $x$  and  $y$  components by projecting line  $OA$  onto the  $xy$  plane and then projecting that line onto the  $x$  and  $y$  axes. The result is that

$$\vec{r}(t) = (r \cos \beta \cos \theta) \vec{i} + (r \cos \beta \sin \theta) \vec{j} + (r \sin \beta) \vec{k}. \quad (1)$$

A central difference at  $t = 2$  s covering a 1-ms interval is formed from  $t = 2 \pm 0.0005$  s, so the velocity in this approximation is

$$\begin{aligned} \vec{v}(t) &\approx \frac{\vec{r}(2 + 0.0005) - \vec{r}(2 - 0.0005)}{0.001} \\ &= 1000[(1246.61294\vec{i} + 537.68542\vec{j} + 1731.20494\vec{k}) \\ &\quad - (1246.59391\vec{i} + 537.41916\vec{j} + 1731.17425\vec{k})], \\ \vec{v}(t) &= 19.0\vec{i} + 266.3\vec{j} + 30.7\vec{k} \text{ m/s}. \end{aligned} \quad (2) \triangleleft$$

To differentiate the position analytically, we recognize that the representation of  $\vec{r}$  in Eq. (1) gives it as a function of  $r(t)$ ,  $\theta(t)$ , and  $\phi(t)$ . Thus we employ the chain rule, which gives

$$\begin{aligned} \vec{v}(t) &= \dot{r} \frac{\partial \vec{r}}{\partial r} + \dot{\theta} \frac{\partial \vec{r}}{\partial \theta} + \dot{\beta} \frac{\partial \vec{r}}{\partial \beta} \\ &= \dot{r} [(\cos \beta \cos \theta) \vec{i} + (\cos \beta \sin \theta) \vec{j} + (\sin \beta) \vec{k}] \\ &\quad + \dot{\theta} [-(r \cos \beta \sin \theta) \vec{i} + (r \cos \beta \cos \theta) \vec{j}] \\ &\quad + \dot{\beta} [-(r \sin \beta \cos \theta) \vec{i} - (r \sin \beta \sin \theta) \vec{j} + (r \cos \beta) \vec{k}]. \end{aligned} \quad (3)$$

At  $t = 2$  s we have

$$\begin{aligned} r &= 2200 \text{ m}, \quad \dot{r} = 100 \text{ m/s}, \\ \theta &= 0.40712 \text{ rad}, \quad \dot{\theta} = (\pi/2)(0.15) \exp(-0.15t) = 0.17455 \text{ rad/s}, \\ \beta &= 0.90578 \text{ rad}, \quad \dot{\beta} = -0.05/\sqrt{t} = -0.03536 \text{ rad/s}. \end{aligned}$$

## 1.2 Newtonian Mechanics

13

Substitution of these values into Eq. (3) gives the same result as that of Eqs. (2). The results of both analyses actually agree to within  $4 (10^{-7})$  % if intermediate results are not truncated as the computations proceeded.

In other cases, the degree to which the two analyses would agree would depend on the duration of the interval for the finite difference, as well as the nature of the functions describing  $r$ ,  $\theta$ , and  $\beta$ . Interestingly, modern data acquisition systems are digital, so the data taken by a radar station are sampled discrete values. Any functions representing  $r(t)$ ,  $\theta(t)$ , and  $\beta(t)$  are likely in that situation to be approximations based on curve-fitting procedures. In such situations, it would be incorrect to decide that the finite difference approximation gives a less precise result than one obtained by analytical differentiation.

## 1.2 NEWTONIAN MECHANICS

A fundamental aspect of any kinetics laws is the reference frame from which the motion is observed. A reference frame will be depicted as a set of coordinate axes, such as  $xyz$ , with an additional specification of the body to which the axes are attached. However, it is important to realize that coordinate axes are also often used to represent the directions for the component description of vectorial quantities. The two uses for a coordinate system are not necessarily related. Indeed, we frequently describe a kinematical quantity relative to a specified frame of reference in terms of its components along the coordinate axes associated with a different frame of reference.

### 1.2.1 Newton's Laws

The kinetics laws associated with Sir Isaac Newton are founded on the concept of an absolute reference frame, which implies that somewhere in the universe there is an object that is stationary. This concept is abandoned in relativity theory, but the notion of a fixed reference frame introduces negligible errors for objects that move slowly in comparison with the speed of light. The corollary of this concept is the dilemma of what object should be considered to be fixed. Once again, considering the Sun to be fixed usually is sufficiently accurate. However, in most engineering situations it is preferable to use the Earth as our reference frame. The primary effect of the Earth's motion in most cases is to modify the (in vacuo) free-fall acceleration  $g$  resulting from the gravitational attraction between an object and the Earth. Other than that effect, it is usually permissible to consider the Earth to be an absolute reference frame. (A more careful treatment of the effects of the Earth's motion will be part of our study in Chapter 3 of motion relative to a moving reference frame.)

A remarkable feature of Newton's Laws is that they address only objects that can be modeled as a particle. Kinetics laws governing a body having finite dimensions were derived from Newton's Laws by considering a body to be a collection of particles. Thus Newton's Laws are fundamental to all aspects of our work. At the same time, we should recognize that these are axiomatic to our studies, as they are based on experimental



observation without analytical proof. Indeed, relativity theory can be shown to reduce to Newton's Laws for bodies that move very slowly.

Newton's Laws have been translated in a variety of ways from their original statement in the *Principia* (1687), which was in Latin. We use the following version:

FIRST LAW: The velocity of a particle can only be changed by the application of a force.

SECOND LAW: The resultant force (that is, the sum of all forces) acting on a particle is proportional to the acceleration of the particle. The factor of proportionality is the mass.

$$\Sigma \vec{F} = m\vec{a}. \quad (1.2.1)$$

THIRD LAW: All forces acting on a body result from an interaction with another body, such that there is another force, called a *reaction*, applied to the other body. The action–reaction pair consists of forces having the same magnitude, and acting along the same line of action, but having opposite direction.

We realize that the First Law is included in the Second, but we retain it primarily because it treats systems in static equilibrium without the need to discuss acceleration. A number of individuals recognized this law prior to Newton. The Second Law is quite familiar, but it must be emphasized that it is a vector relation. Hence it can be decomposed into as many as three scalar laws, one for each component. The Third Law is very important to the modeling of systems. The models that are created in a kinetics study are free-body diagrams, in which the system is isolated from its surroundings. Careful application of the Third Law will assist identification of the forces exerted on the body.

The conceptualization of the First and Second Laws can be traced back to Galileo. Newton's revolutionary idea was the recognition of the Third Law and its implications for the first two. An interesting aspect of the Third Law is that it excludes the concept of an inertial force,  $-m\vec{a}$ , which is usually associated with d'Alembert, because there is no corresponding reactive body. We will address the inertial force concept in Chapter 7.

It is also worth noting that the class of forces described by the Third Law is limited – any force obeying this law is said to be a *central force*. An example of a noncentral force arises from the interaction between moving electric charges. Such forces have their origin in relativistic effects. Strictly speaking, the study of classical mechanics is concerned only with systems that fully satisfy all of Newton's laws. However, many of the principles and techniques are applicable either directly, or with comparatively minor modifications, to relativistic systems.

The acceleration employed in Newton's Second Law was stated to be observed from the hypothetical fixed reference frame. However, the same acceleration can also be observed from special moving reference frames. One may recognize this by returning to Fig. 1.5, in which the observer at point *A* is allowed to move. Differentiating twice the vector sum described by that figure gives

$$\vec{a}_P \equiv \frac{d^2}{dt^2} \vec{r}_{P/O} = \frac{d^2}{dt^2} \vec{r}_{A/O} + \frac{d^2}{dt^2} \vec{r}_{P/A}. \quad (1.2.2)$$

## 1.2 Newtonian Mechanics

15

If the observer at point  $A$  is to see  $\bar{a}_p$ , it must be that  $d^2\bar{r}_{A/O}/dt^2 = \bar{0}$ , which means that  $d\bar{r}_{A/O}/dt$  is constant. However,  $d\bar{r}_{A/O}/dt$  is defined to be  $\bar{v}_A$ . Thus Newton's Second Law can be formulated in terms of the acceleration seen by an observer moving at a constant velocity. However, there is a further restriction to this statement. If the coordinate axes of the reference frame do not point in fixed directions, changes in velocity will be associated with the variability of these directions, as well as changes in the velocity components. An *inertial reference frame* is one that translates at a constant velocity. The translation condition, by definition, means that the coordinate axes point in fixed directions, so that we may interpret velocity and acceleration in the same way as we do for a fixed reference frame. The constant-velocity condition requires that both the magnitude and direction of the moving observer's velocity be constant, which we will soon see can be true only if the observer follows a straight path. The fact that Newton's Laws are valid in any inertial reference frame is the principle of *Galilean invariance*, or the principle of *Newtonian relativity*.

### 1.2.2 Systems of Units

Newton's Second Law brings up the question of the units to be used for describing the force and motion variables. Related to that consideration is dimensionality, which refers to the basic measures that are used to form the quantity. In dynamics, the basic measures are time  $T$ , length  $L$ , mass  $M$ , and force  $F$ . The law of dimensional homogeneity requires that these four quantities be consistent with the Second Law. Thus

$$F = ML/T, \quad (1.2.3)$$

which means that only three of the four basic measures are independent. Measures for time and length are easily defined, so this leaves the question of whether mass or force is the third independent quantity. Whichever unit is not taken as the basic measure is obtained from Eq. (1.2.3). An *absolute set of units* is defined such that the unit of mass is fundamental, whereas a *gravitational set of units* defines force to be the fundamental unit. This latter set of units is said to be "gravitational" because of the relation among the weight  $w$ , the mass  $m$ , and the free-fall acceleration  $g$ .

The only system of units to be employed in this text are SI (Standard International), which is a metric MKS system with standardized prefixes for powers of 10 and standard names for derived units. Newton's law of gravitation states that the magnitude of the attractive force exerted between the Earth and a body of mass\*  $m$  is

$$F = \frac{GM_em}{r^2}, \quad (1.2.4)$$

\* It is implicit to this development that the inertial mass in Newton's Second Law is the same as the gravitational mass appearing in the law of gravitation. This fundamental assumption, which is known as the *principle of equivalence*, actually is owed to Galileo, who tested the hypothesis with his experiments on various pendulums. More refined experiments performed subsequently have continued to verify the principle.

where  $r$  is the distance between the centers of mass,  $G$  is the *universal gravitational constant*, and  $M_e$  is the mass of the Earth:

$$G = 6.6732(10^{-11}) \text{ m}^3/\text{kg}\cdot\text{s}^2, \quad M_e = 5.976(10^{24}) \text{ kg.} \quad (1.2.5)$$

The weight  $w$  of a body usually refers to gravity's pull when a body is near the Earth's surface. If a body near the Earth's surface falls freely in a vacuum, its acceleration is  $g$ , which according to the Second Law is the ratio of  $w$  and  $m$ . In view of Eq. (1.2.4), it must be that

$$g = \frac{GM_e}{r_e^2}, \quad (1.2.6)$$

where  $r_e = 6371 \text{ km}$  is the radius of the Earth.

The relationship between  $g$  and the gravitational pull of the Earth is actually far more complicated than Eq. (1.2.6). In fact,  $g$  depends on the location along the Earth's surface. One reason for such variation is the fact that the Earth is not perfectly homogeneous and spherical. In addition to these deviations of the gravitational force, the value of  $g$  is influenced by the motion of the Earth, because  $g$  is an acceleration measured relative to a noninertial reference frame. (This issue is explored in Section 3.6.) Consequently it is not exactly correct to employ Eq. (1.2.6).

The mass of a particle is constant (assuming no relativistic effects), so an absolute system of units is the same regardless of where they are measured. Prior to adoption of SI as a standard set of absolute units, many individuals used a gravitational metric system, in which grams or kilograms were used to specify the weight of a body. In SI units, where mass is basic, any body should be described in terms of its mass in kilograms. Its weight in newtons ( $1 \text{ N} \equiv 1 \text{ kg} \times 1 \text{ m/s} = 1 \text{ kg}\cdot\text{m/s}$ ) is  $mg$ . If an accurate measurement of  $g$  at the specific location on the Earth's surface is not available, one may use an average value

$$g = 9.807 \text{ m/s.} \quad (1.2.7)$$

The system now known as U.S. Customary is another gravitational system. Its basic unit is force, measured in pounds (lb). The body whose weight is defined as a pound must be at a specified location. If that body were to be moved to a different place, the gravitational force acting on it, and hence the unit of force, might be changed. The ambiguity as to a body's weight is one source of confusion in U.S. Customary units. Another stems from early usage of the pound as a mass unit. If one also employs a pound force unit, such that 1 lbf is the weight of a 1-lbm body at the surface of the Earth, then application of the law of dimensional homogeneity to  $\vec{F} = m\vec{a}$  requires that acceleration be measured in multiples of  $g$ . This is an unnecessary complication that has been abandoned in most scientific work.

Even when one recognizes that mass is a derived unit in the U.S. Customary units, the mass unit is complicated by the fact that two length units, feet and inches, are in common use. Practitioners working in U.S. Customary units use the standard values

$$g = 32.17 \text{ ft/s} \quad \text{or} \quad g = 386.0 \text{ in./s.} \quad (1.2.8)$$

## 1.2 Newtonian Mechanics

17

Hence, computing the mass as  $m = w/g$  will give a value for  $m$  that depends on the length unit in use. The *slug* is a standard name for the U.S. Customary mass unit, with

$$1 \text{ slug} = 1 \text{ lb}/(1\text{ft/s}^2) = 1 \text{ lb-s}^2/\text{ft}. \quad (1.2.9)$$

This mass unit is not applicable when inches is the length unit. To emphasize this matter, it is preferable for anyone using U.S. Customary units to make it a standard practice to give mass in terms of the basic units. For example, a mass might be listed as  $5.2 \text{ lb-s}^2/\text{ft}$ , or a moment of inertia might be  $125 \text{ lb-s}^2\text{-in}$ . The SI system avoids all of these ambiguities.

### 1.2.3 Energy and Momentum

A basic application of the calculus of vectors in dynamics is the derivation of energy and momentum principles, which are integrals of Newton's Second Law. These integrals represent standard relations between velocity parameters and the properties of the force system. We derive these laws for particle motion here; the corresponding derivations for a rigid body appear in Chapter 6.

Energy principles are useful when we know how the resultant force varies as a function of the particle's position, in other words, when  $\Sigma \bar{F}(\bar{r})$  is known. The displacement of a point is intimately associated with energy principles. The definition of a *displacement* is that it is the change in the position occupied by a point at two instants,

$$\Delta \bar{r} = \bar{r}(t + \Delta t) - \bar{r}(t). \quad (1.2.10)$$

To obtain a differential displacement  $d\bar{r}$ , we let  $\Delta t$  become an infinitesimal interval  $dt$ . A dot product of Newton's Second Law with a differential displacement of a particle yields

$$\Sigma \bar{F}(\bar{r}) \cdot d\bar{r} = m\bar{a} \cdot d\bar{r}. \quad (1.2.11)$$

The definition of velocity indicates that  $d\bar{r} = \bar{v}dt$ . Substitution of this and the definition of  $\bar{a}$  into the preceding leads to

$$\Sigma \bar{F}(\bar{r}) \cdot d\bar{r} = m \frac{d\bar{v}}{dt} \cdot \bar{v}dt. \quad (1.2.12)$$

A dot product is commutative, so  $(d\bar{v}/dt) \cdot \bar{v} \equiv \bar{v} \cdot (d\bar{v}/dt)$ , from which it follows that

$$\Sigma \bar{F}(\bar{r}) \cdot d\bar{r} = m \frac{1}{2} \left[ \frac{d}{dt} (\bar{v} \cdot \bar{v}) \right] dt \equiv d \left[ \frac{1}{2} m (\bar{v} \cdot \bar{v}) \right]. \quad (1.2.13)$$

The right side is a perfect differential, whereas the left side is a function of only the position because of the assumed dependence of the force resultant. Hence we may integrate the differential relation between the two positions. The evaluation of the integral of the left side must account for the variation of the resultant force as the position changes when the particle moves along its path; this is called a *path integral*. We therefore find that

$$\oint_1^2 \Sigma \bar{F}(\bar{r}) \cdot d\bar{r} = \frac{1}{2} m (\bar{v}_2 \cdot \bar{v}_2) - \frac{1}{2} m (\bar{v}_1 \cdot \bar{v}_1), \quad (1.2.14)$$

where “1” and “2” respectively denote the initial position and final position. The *kinetic energy* of a particle is

$$T \equiv \frac{1}{2}m(\vec{v} \cdot \vec{v}) = \frac{1}{2}m|\vec{v}|^2, \quad (1.2.15)$$

and the path integral is the *work* done by the resultant force in moving the particle from its initial to final position,


$$W_{1 \rightarrow 2} \equiv \oint_1^2 \Sigma \vec{F}(\vec{r}) \cdot d\vec{r}. \quad (1.2.16)$$

The subscript notation for  $W$  indicates that the work is done in going from the starting position 1 to the final position 2 along the particles's path. Correspondingly, Eq. (1.2.14) may be written as

$$T_2 = T_1 + W_{1 \rightarrow 2}, \quad (1.2.17)$$

which is the *work–energy principle*. It states that the increase in kinetic energy between two positions equals the work that is done.

The operation of evaluating the work is depicted in Fig. 1.6. The angle between the resultant force  $\Sigma \vec{F}$  and the infinitesimal displacement  $d\vec{r}$  is  $\theta$ . It follows from the definition of a dot product that the infinitesimal work done by  $\Sigma \vec{F}$  in this displacement is  $dW = \Sigma \vec{F} \cdot d\vec{r} = |\Sigma \vec{F}| |d\vec{r}| \cos \theta$ . The figure indicates that the infinitesimal work is the product of the differential distance the particle moves,  $|d\vec{r}|$ , and the component of the resultant force in the direction of movement,  $|\Sigma \vec{F}| \cos \theta$ , or equivalently, the product of the magnitude of the resultant force,  $|\Sigma \vec{F}|$ , and the projection of the displacement in the direction of the force,  $|d\vec{r}| \cos \theta$ . Only in the simple case in which the force has a constant component in the direction of the displacement does the work reduce to the simple expression “force multiplied by distance displaced.” Otherwise the work must be evaluated as a path integral, meaning that the value of  $\Sigma \vec{F} \cdot d\vec{r}$  must be described as a function of the position along the path. The evaluation of the work is a major part of a formulation of the work–energy principle. We will find in Chapter 6 that this task is alleviated by introducing the concept of potential energy.



**Figure 1.6.** Work done by a resultant force  $\Sigma \vec{F}$  in displacement  $d\vec{r}$  of a particle.

In contrast to the situation covered by the work–energy principle, which is based on knowing how the resultant force depends on the particle's position, momentum principles are intended to address situations in which the resultant force is known as a function

## 1.2 Newtonian Mechanics

19

of time. Two such principles may be derived from Newton's Second Law. The *linear impulse–momentum principle* is a direct integration of  $\Sigma \bar{F} = m\bar{a}$  with respect to time. Because  $\bar{a} = d\bar{v}/dt$ , multiplying the Second Law by  $dt$  and integrating over an interval  $t_1 \leq t \leq t_2$  leads to

$$\int_{t_1}^{t_2} \Sigma \bar{F} dt = m(\bar{v}_2 - \bar{v}_1). \quad (1.2.18)$$

The quantity  $m\bar{v}$  is the *momentum* of the particle, which we denote by the symbol  $\bar{P}$ . Thus we have

$$\bar{P} = m\bar{v}, \quad \bar{P}_2 = \bar{P}_1 + \int_{t_1}^{t_2} \Sigma \bar{F} dt. \quad (1.2.19)$$

The time integral of the resultant force is the *impulse*. Thus we have derived the *linear impulse–momentum principle*, where the word linear conveys the fact that the principle pertains to movement along a (possibly curved) line. Correspondingly, more precise names for the terms appearing in Eqs. (1.2.19) are the *linear impulse* and *linear momentum*.

This is a vector relation, so taking components in each of the coordinate directions will lead to three scalar equations, although some might be trivial, as in planar motion. There are few situations in which all forces acting on a body are known as functions solely of time, which is required if the impulse is to be evaluated. However, it might happen that the forces acting in a certain direction are known functions of time, in which case the linear impulse–momentum law may be invoked solely for that component.

A primary utility of the linear impulse–momentum principle is to treat systems excited by *impulsive forces*, that is, forces that impart a very large acceleration to a body over a very short time interval. We split the resultant force acting on a particle into two parts:  $\bar{F}_{\text{imp}}$  is the resultant of the impulsive forces, and  $\bar{F}_{\text{ord}}$  represents ordinary forces whose magnitude is not much larger than  $mg$ . The peak magnitude in the impulsive force,  $F_{\text{max}} = \max(\bar{F}_{\text{imp}})$ , must be much greater than the peak magnitude of the regular forces in order for it to qualify as an impulsive force. Because one of the regular forces is gravity, it follows that  $F_{\text{max}}/m$  must be much larger than  $g$  if a force is to be considered to be impulsive. The velocity at time  $t_2$ , when the impulsive force ceases, is related by the linear impulse–momentum principle to the velocity at  $t_1$ , when the force first began to act. Specifically,

$$m\bar{v}_2 = m\bar{v}_1 + \int_{t_1}^{t_2} \bar{F}_{\text{imp}} dt + \int_{t_1}^{t_2} \bar{F}_{\text{ord}} dt. \quad (1.2.20)$$

Because the impulsive forces are much bigger than the ordinary forces, we may ignore the impulse of the latter. Furthermore, in many situations, such as predicting the trajectory of an object after a collision, we are not very interested in specific manner in which the velocity changes between  $t_1$  and  $t_2$ . This is especially true because of the brevity of this time interval. Both observations lead to the idealized model of an impulsive force, in which it is considered to act over a zero time interval,  $t_2 = t_1$ , but to still have the same impulse  $\bar{G}$  as the actual force. The implication of a finite impulse

being obtained over a zero time interval is that the force is infinite. We represent such a force as

$$\bar{F}_{\text{imp}} = \bar{G}\delta(t - t_1), \quad (1.2.21)$$

where  $\delta(t - t_1)$  is a *Dirac delta function*, which is defined by two basic properties:

$$\delta(t - t_1) = 0 \text{ if } t \neq t_1, \quad \int_{t_0}^{t_2} \delta(t - t_1) dt = 1 \text{ if } t_0 < t_1 < t_2. \quad (1.2.22)$$

The consequences of using this model to analyze the motion of a particle is that (a) the acceleration is infinite for one instant, (b) the velocity changes instantaneously, and (c) the position changes continuously. (The latter feature follows from the facts that the velocity is integrated to find the position and the velocity is finite.) As was mentioned, this representation of an impulsive force is satisfactory for predicting the motion of the particle at any instant outside the brief interval when the impulsive force acts. At the same time, the fact that the model considers an impulsive force to have an infinite magnitude makes it inappropriate for any stress analysis task, such as designing a golf club.

In statics, we know that the resultant moment is as important as the resultant force. Thus, let us investigate how the moment  $\Sigma \bar{M}_O$  of the resultant force about origin  $O$  of a fixed reference frame is related to the acceleration. Application of the Second Law to the resultant moment leads to

$$\Sigma \bar{M}_O = \bar{r}_{P/O} \times \Sigma \bar{F} = \bar{r}_{P/O} \times m\bar{a} = \bar{r}_{P/O} \times m \frac{d\bar{v}}{dt}. \quad (1.2.23)$$

We now bring the time derivative outside the cross product by compensating the equation with an appropriate term to maintain the identity, specifically,

$$\Sigma \bar{M}_O = \frac{d}{dt} (\bar{r}_{P/O} \times m\bar{v}) - \frac{d\bar{r}_{P/O}}{dt} \times m\bar{v}. \quad (1.2.24)$$

However, the last term vanishes because  $d\bar{r}_{P/O}/dt \equiv \bar{v}$  and the velocity is parallel to the momentum  $m\bar{v}$ . The remaining term on the right side of the equation is the time derivative of the moment about origin  $O$  of the linear momentum of the particle. We refer to  $\bar{r}_{P/O} \times m\bar{v}$  as the *moment of momentum*. The more common name for this quantity is the *angular momentum*, which refers to the fact that a moment is associated with a rotational tendency. We use the symbol  $\bar{H}_O$  to denote it. Thus,

$$\bar{H}_O = \bar{r}_{P/O} \times m\bar{v}, \quad \Sigma \bar{M}_O = \dot{\bar{H}}_O, \quad (1.2.25)$$

which is the derivative form of the *angular impulse–momentum principle*. The integral form is obtained by integration over an arbitrary interval  $t_1 \leq t \leq t_2$ , which leads to

$$(\bar{H}_O)_2 = (\bar{H}_O)_1 + \int_{t_1}^{t_2} \Sigma \bar{M}_O dt. \quad (1.2.26)$$

The time integral of the moment is called the *angular impulse* of the resultant force.

Situations in which the angular impulse–momentum principle is needed to study the motion of a particle are few. As is the case for its linear analog, the angular momentum

### 1.3 Biographical Perspective

21

principle for a particle might be useful to treat an impulsive force. Also, when the moment of the resultant force about an axis is zero, the principle yields a conservation principle. Specifically, if the unit vector parallel to this axis is  $\bar{e}$ , then

$$\Sigma \bar{M}_O \cdot \bar{e} = \bar{0} \iff \bar{H}_O \cdot \bar{e} \text{ is constant.} \quad (1.2.27)$$

This conservation principle was recognized by Kepler for planetary motion, and it is a key part of the analysis of orbits. For us, the primary utility of the angular momentum principle lies in the application of the derivative form, Eq. (1.2.25), to a rigid body. We will find in Chapter 5 that the angular momentum of a body is directly related to its rotation.

### 1.3 BIOGRAPHICAL PERSPECTIVE

As we proceed through the various topics, the names of some early scientists and mathematicians will be encountered in a variety of contexts. The magnitude of the contribution of these pioneers cannot be overstated. Indeed, it is a testimonial to their ingenuity that we continue to use so much of their work. A view of the historical relationship among these researchers can greatly enhance our insight. The following discussion is an informal chronological survey of deceased individuals whose names are associated with concepts we will discuss. The goal here is to provide a brief overview of their life and their technical contributions. As in all scientific endeavors, many others made important contributions leading to those concepts. One objective of this survey is to introduce the notion that the laws of dynamics are a natural philosophy, as well as an engineering discipline. Another perspective to be gained from this survey is that some of these pioneers were active in a broad range of subjects, whereas others were specialists, but all were important to the advancement of dynamics. The reader is encouraged to examine the references for this chapter to fully appreciate how the subject evolved.

#### Galileo Galilei

Born 15 February 1564 in Pisa, Italy; died 8 January 1642. Galileo's family moved to Florence when he was 10 years old. His father forced him to enroll in the University of Pisa for a medical degree in 1581, but Galileo focused on mathematics and natural philosophy. He left the university without receiving a degree and began teaching mathematics in Siena in 1585. He worked there on the concept of center of gravity and unsuccessfully sought an appointment at the University of Bologna on the basis of that work. Galileo was named the Chair of Mathematics at the University of Pisa in 1589. He became a professor of mathematics at the University of Padua in 1590, where he was elevated to the post of Chief Mathematician in 1610.

Galileo is popularly known for experiments on gravity at the leaning tower of Pisa, but there is no conclusive evidence that those experiments actually occurred. From his measurements of the motion of pendulums, which led him to propose the use of a pendulum to provide the time base for a clock, he deduced that gravitational and inertial masses are identical. He refuted Aristotle's ancient statements by observing that the state of motion can be altered only by the presence of other bodies and that there is



no unique inertial reference frame. In astronomy, he developed the astronomical telescope, and used it for many pioneering observations. His last eight years were spent under house arrest for advocating the Copernican view of the solar system, which held that the Sun, rather than the Earth, is the center of the solar system.

### **Sir Isaac Newton**

Born 4 January 1643 in Lincolnshire, England; died 31 March 1727. Newton's father was wealthy, but illiterate, and Newton was raised by his grandparents. He entered Trinity College of Cambridge University in 1661 with the intent of earning a law degree, but became interested in mathematics and natural philosophy. He earned a bachelor's degree from Cambridge University in 1665, but his academic record there was not particularly distinguished. He returned to Lincolnshire shortly after graduation because of an outbreak of plague. His brilliance emerged there when he developed the fundamentals of calculus. Newton returned to Cambridge University in 1667, where he was named the Lucasian Chair in 1669. He was elected to Parliament in 1689 and retired from research in 1693. He became Warden of the Mint in 1696 and was knighted in 1705.

In addition to his contributions in developing calculus, Newton made important contributions to the refraction and diffraction of light. For us, his most important work is the monumental *Philosophiae naturalis principia mathematica*, which is usually referred to as the *Principia*. In it, he brought together the basic laws of motion, the universal law of gravitation, the study of projectile motion, and of celestial orbits. Equally important, it introduced the world to the scientific method by tying together mathematical hypothesis and experimental observation. The revolutionary nature of Newton's contributions causes many to regard him as one of the two most important figures in science, rivaled only by Albert Einstein.

### **Leonhard Euler**

Born 15 April 1707 in Basel, Switzerland; died 18 September 1783. Euler studied philosophy at the University of Basel, from which he earned a masters's degree in 1723. While there he became interested in mathematics, but much of his expertise in this subject was the result of self-instruction. He received an appointment at the University of St. Petersburg, Russia, at the age of 19, and served as a medical lieutenant in the Russian Navy from 1727 to 1730. In that year he was named a professor at the University of St. Petersburg, which enabled him to leave the navy. He was named the senior chair in 1733, but left to go to the University of Berlin in 1743 because of negative sentiment for foreigners in Russia. He became the Director of Mathematics when the Berlin Academy was created in 1744. Euler returned to St. Petersburg in 1763 because of disagreements with Frederick the Great. A failed operation led to his total blindness in 1771, but much of his technical contributions come from the subsequent period.

Euler was quite prolific, with more than 350 publications in such diverse areas as the calculus of variations, functional analysis, number theory, ordinary differential equations, differential geometry, cartography, orbital motion and trajectories, fluid mechanics, and solid mechanics. For the subject of dynamics, his primary contribution is the derivation of principles governing the kinematics and kinetics of rigid bodies. Euler was

### 1.3 Biographical Perspective

23

the most prolific mathematician of his century. By developing new mathematical principles in order to solve physically meaningful problems he fathered the discipline of mechanics. Unlike Newton, who created new concepts, much of Euler's work can be recognized as evolving from the efforts of his contemporaries.

#### Jean Le Rond d'Alembert

Born 17 November 1717 in Paris, France; died 29 October 1783. D'Alembert was abandoned by his unmarried mother on the steps of the Church of St. Jean Le Rond, which is the origin of his given name. He studied theology and mathematics at the Jansenist College of Quatre Nations, from which he graduated as a lawyer in 1735. He continued to study mathematics, with the result that he joined the Paris Académie des Sciences in 1741, where he remained. He wrote most of the mathematical sections of the *Encyclopédie*, published in 1754, which is the year he was appointed to the French Académie. D'Alembert's interests eventually turned to literature, philosophy, and music theory.

D'Alembert made significant contributions to the study of partial differential equations and their application to solid and fluid mechanics, as well as to functional analysis. Euler and d'Alembert initially held each other in high esteem, but the situation deteriorated in 1753. Nevertheless, many of Euler's works descended from d'Alembert's concepts. A notable aspect is that d'Alembert was uncomfortable with Newton's approach merging experiment and theory, with the result that the assumptions he made to initiate an analysis were often erroneous. D'Alembert is associated with the notion of an inertial force,  $-m\ddot{a}$ , which is a key concept for the development of analytical dynamics principles. However, this attribution, and hence d'Alembert's presence in this survey, is questionable, which is an issue we will address in Chapter 7.

#### Joseph-Louis Lagrange

Born 25 January 1736 in Turin, Italy; died 10 April 1813. Lagrange initially studied classical Latin at the College of Turin, but turned to mathematics and physics in order to pursue a financially sound career. Much of his knowledge in these subjects was the result of self-study, and his correspondences with Euler were very important for this effort. One consequence is that the works of Euler and Lagrange are intimately related. Lagrange became a professor of mathematics at the Royal Artillery School in Turin in 1755. He was elected to the Berlin Academy in 1755 on the recommendation of Euler and succeeded Euler as Director of Mathematics of that institution in 1766. Lagrange joined the Paris Académie des Sciences in 1787. The following year saw the publication of his treatise *Mécanique analytique*, in which he used differential equations as the framework for all of the primary developments in mechanics since Newton. Lagrange became the first professor of analysis at the École Polytechnique in Paris in 1794. He was named a Count of the Empire and awarded the Legion of Honor by Napoleon in 1808. Although Lagrange's heritage is Italian, the French consider him to be one of their own.

Lagrange's major contributions were to the calculus of variations and its applications to mechanics, the theory of equations, probability theory, number theory, ordinary differential equations, wave propagation, and celestial mechanics. His dynamical

equations of motion will be an essential element of our study here. Overall, Lagrange can be credited as being the individual who initiated the usage of applied mathematical tools to study dynamical systems.

### **Gaspard Gustave de Coriolis**

Born 21 May 1792 in Paris, France; died 19 September 1843. Coriolis' family fled to Nancy, France, shortly after his birth to escape punishment during the French Revolution. He attended the École Polytechnique, then the École des Ponts et Chaussées in Paris. His first position was an appointment in 1816 as a tutor in mathematical analysis at the École Polytechnique. In 1829 he became a professor of mechanics at the École Centrale des Artes et Manufactures, then returned to the École Polytechnique in 1832, where he became director of studies in 1838.

Coriolis' contributions to dynamics are less significant than those of the other researchers discussed here. His primary recognition stems from an explanation of the acceleration observed from the perspective of a rotating reference frame. In addition, he introduced the terms "work" and "energy" in their modern sense. He also contributed to the study of collisions of bodies, hydraulics, and machine design.

### **Sir William Rowan Hamilton**

Born 4 August 1805 in Dublin, Ireland; died 2 September 1865. Hamilton knew Latin, Greek, and Hebrew by the age of five. He entered Trinity College in Dublin in 1823, where he earned the ranking of "optime" in both science and classics, which was unprecedented. At age 21, while still an undergraduate, he was named a professor of astronomy, which was accompanied by the honorary title of Royal Astronomer of Ireland. He wrote poetry, which he exchanged with his friend Wordsworth, who advised Hamilton to remain a scientist. Hamilton remained at Trinity College for his whole career. He was knighted in 1835 and, shortly before his death, became the first foreign member of the U.S. National Academy of Sciences.

One of Hamilton's specialties was the ray theory of optics, especially the phenomenon of caustics. A primary contribution to dynamics was an alternative formulation of equations of motion, which apparently grew out of an effort to apply ray theory to dynamical systems. We also will encounter "Hamilton's Principle," which draws on concepts from the calculus of variations to capture the Newtonian and Lagrangian forms of the equations of motion. It has been invaluable for the development of finite element analysis, yet can be extended to relativistic systems. Hamilton also developed the algebra of quaternions, which has been employed in some areas of kinematics.

### **Edward John Routh**

Born 20 January 1831 in Quebec, Canada; died 7 June 1907. Routh's birth in Canada was a consequence of his father being posted there by the English army. Routh went to England in 1842 to enroll in University College, London, from which he earned a B.A. in 1849 and an M.A. in 1853. The latter was accompanied by gold medals in mathematics and natural philosophy. He received a B.A. from Cambridge University in 1854, at which time he was the Senior Wrangler in the Mathematics Tripos Exams. (The great

### 1.3 Biographical Perspective

25

physicist Maxwell came in second in that competition.) Routh was appointed to a lectureship at Cambridge in 1855, which was the position he held for his whole career. He became famous as a coach for the Tripos exams. For 22 years, starting in 1862, the Senior Wrangler was coached by him. Over a 30-year period, Routh coached 700 students, of whom 480 were named Wranglers out of a cohort of 900. Routh became a Fellow of the Cambridge Philosophical Society in 1854, of the Royal Astronomical Society in 1866, and of the Royal Society in 1872.

As a researcher, Routh contributed to geometry, astronomy, and wave propagation. His primary contribution for us is analysis of the dynamical behavior of rigid bodies. As part of that effort, he formulated general tools for analyzing dynamic stability, which proved also to be very useful for fluid mechanics.

#### Josiah Williard Gibbs

Born 11 February 1839 in New Haven, Connecticut; died 28 April 1903. Gibbs initially focused on mathematics and Latin when he entered Yale University, but switched to engineering. He received Yale's first doctorate in engineering in 1863. From 1866 to 1869 he studied in Europe, then became a professor of mathematical physics at Yale in 1871, where he remained.

In today's vernacular, he was a "late bloomer," in that his first published work appeared in 1873 when he was 34. His major contributions were in thermodynamics and statistical mechanics. He also worked on the electromagnetic theory of light. An alternative formulation of equations of motion, which is the aspect of his efforts that causes him to be included here, was part of his efforts to apply vector analysis to physical systems.

#### Paul Emile Appell

Born 27 September 1855 in Strasbourg, France; died 24 October 1930. Appell's family moved to Nancy, France, when he was 16 as a consequence of the German annexation of Alsace. There he became a lifelong friend of Poincaré. He entered in 1873 the École Normal Supérieure in Paris, and received a doctorate in mathematics in 1876. Appell became the Chair of Mathematics at the University of Sorbonne in Paris in 1885. He was ardently and actively patriotic for his whole life, as was manifested by his spying activities for France during his frequent visits to his family in Alsace. He was elected to the Académie des Sciences in 1892. He was dean of the Faculty of Science of the University of Paris from 1903 to 1920, then served as its rector from 1920 to 1923.

Appell's prolific research output emphasized the application of mathematical analysis to geometry and mechanics. His work tended to be refinements of existing concepts, rather than new ones. The contribution that brings him to our attention is the development of an alternative set of equations of motion, for which he shares attribution with Gibbs.

#### Walther Ritz

Born 22 February 1878 in Sion, Switzerland; died 7 July 1909. Ritz entered the Federal Polytechnic School in Zurich in 1897. His original intent was to study engineering, but he

soon transferred to mathematics, where one of his classmates was Einstein. He moved to Göttingen, Germany, where he did his thesis. Between 1901 and 1904 Ritz held positions in Leiden, Bonn, and Paris. Despite tuberculosis, which caused him to return to Switzerland in 1907, he took on positions in Tübingen, Germany, in 1907, and Göttingen, in 1908. Ritz's most productive period of research came in his last two years. His life span of 31 years is the shortest of the great physicists and mathematicians through the early 20th century. The only remorse he expressed as he was dying was that he would no longer be able to advance science.

Ritz's contributions to spectroscopy were vital to the development of quantum theory, and his work in the general theory of electrodynamics was important to the development of relativity theory. To explain the vibrations of elastic plates, Ritz applied an analytical technique based on Hamilton's Principle that he developed in his thesis on atomic spectra. This technique proved to be quite general, and now is widely used. It provides the foundation for finite element analysis. Interestingly, the only reason Ritz was interested in plate vibrations was the possibility of winning a mathematical competition. The rest of his research was in atomic physics.

Perhaps the most remarkable aspect of the foregoing survey is the time span over which these pioneers lived. The basic principles were essentially finalized more than a century ago. However, the subject of mechanics is mature from only a philosophical view. Developments since then have transferred the works of our predecessors from the realm of physics and mathematics to engineering, thereby converting their contributions from fundamentally straightforward principles and concepts to sophisticated analytical tools capable of describing complex systems. One objective of this text is to show how far we have come, but expanding the versatility of the analytical tools and their level of sophistication continues to be a research focus.

## SELECTED REFERENCES

- 
- Dugas, R., *A History of Mechanics*, Dover, New York (1988).  
 Gamow, G., *The Great Physicists from Galileo to Einstein*, Dover, New York (1988).  
 Ginsberg, J. H., and Genin, J., *Dynamics*, 2nd ed., Wiley, New York (1984).  
 Greenwood, D. T., *Principles of Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1965).  
 Hibbeler, R. C., *Engineering Mechanics – Combined*, 10th ed., Prentice-Hall, Englewood Cliffs, New Jersey (2003).  
 Lanczos, C., *The Variational Principles of Mechanics*, 4th ed., University of Toronto Press, Toronto (1970).  
 Lindsay, R. B., and Margenau, H., *Foundations of Physics*, Ox Bow Press, Woodbridge, Connecticut (1981).  
 Mach, E., *The Science of Mechanics*, 6th ed., Open Court Publishing, LaSalle, Illinois (1960).  
 Marion, J. B., *Classical Dynamics of Particles and Systems*, Academic, New York (1960).  
 Meirovitch, L., *Methods of Analytical Dynamics*, McGraw-Hill, New York (1970).


## Homework Problems

27

- Morse, P. M., and Feshbach, H., *Methods of Theoretical Physics*, Vol. 1., McGraw-Hill, New York (1953).
- Newton, I., *The Principia: Mathematical Principles of Natural Philosophy*, translated by B. Cohen and A. Whitman, University of California Press, Berkeley, California (1999).
- Ronald, L., and Huston, H. J., *Dynamics of Mechanical Systems*, CRC, Boca Raton, Florida (2002).
- Truesdell, C., *Essays in the History of Mechanics*, Springer-Verlag, New York (1960).
- Shames, I. H., *Engineering Mechanics: Statics and Dynamics*, 4th ed., Prentice-Hall, Englewood Cliffs, New Jersey (1996).
- Wills, A. P., *Vector Analysis With an Introduction to Tensor Analysis*, Dover, New York (1958).
- Wrede, W. R., *Introduction to Vector and Tensor Analysis*, Dover, New York (1972).

## HOMEWORK PROBLEMS

**EXERCISE 1.1** The rectangular plate is welded at corner  $A$  to the vertical shaft and braced by cable  $BC$ . The tension in the cable is 5 kN. (a) Determine the components parallel to the edges of the plate of the force the cable applies to the plate. (b) Determine the moment about corner  $A$  of the force applied by the cable. (c) Determine the moment about the axis of the shaft of the force applied by the cable.



Exercise 1.1

**EXERCISE 1.2** The study of the kinematics of rigid bodies in Chapter 3 will show that the accelerations of two points in a rigid body are related by  $\bar{a}_B = \bar{a}_A + \bar{\alpha} \times \bar{r}_{B/A} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{B/A})$ . At a certain instant  $\bar{r}_{A/O} = \bar{i} + \bar{j} + \bar{k}$  m,  $\bar{r}_{B/O} = 4\bar{i} + 2\bar{j} - 3\bar{k}$  m,  $\bar{a}_A = 4\bar{i} - 5\bar{j} + \bar{k}$  m/s<sup>2</sup>,  $\bar{\omega} = 5\bar{i} - 3\bar{j} + 2\bar{k}$  rad/s,  $\bar{\alpha} = -20\bar{i} + 10\bar{j} - 40\bar{k}$  rad/s<sup>2</sup>. Evaluate  $\bar{a}_B$  by carrying out the calculation manually, then verify the result using mathematical software.

**EXERCISE 1.3** The Gibbs–Appell function for a rigid body is related to the instantaneous angular velocity  $\bar{\omega}$  and angular acceleration  $\bar{\alpha}$  by

$$S = \frac{1}{2} \bar{\alpha} \cdot \frac{\partial \bar{H}_A}{\partial t} + \bar{\alpha} \cdot (\bar{\omega} \times \bar{H}_A),$$

$$\bar{H}_A = (I_{xx}\omega_x - I_{xy}\omega_y - I_{xz}\omega_z)\bar{i} + (I_{yy}\omega_y - I_{xy}\omega_x - I_{yz}\omega_z)\bar{j} \\ + (I_{zz}\omega_z - I_{xz}\omega_x - I_{yz}\omega_y)\bar{k},$$


$$\frac{\partial \bar{H}_A}{\partial t} = (I_{xx}\alpha_x - I_{xy}\alpha_y - I_{xz}\alpha_z)\bar{i} + (I_{yy}\alpha_y - I_{xy}\alpha_x - I_{yz}\alpha_z)\bar{j} \\ + (I_{zz}\alpha_z - I_{xz}\alpha_x - I_{yz}\alpha_y)\bar{k},$$

where  $I_{xx}$ ,  $I_{yy}$ , and  $I_{zz}$  are the moments of inertia and  $I_{xy}$ ,  $I_{yz}$ , and  $I_{xz}$  are products of inertia. Consider a situation in which  $\bar{\omega} = -50\bar{i} - 20\bar{k}$  rad/s,  $\bar{\alpha} = 1500\bar{i} - 500\bar{j} + 1000\bar{k}$  rad/s<sup>2</sup>. The nonzero inertia values are  $I_{xx} = 500$ ,  $I_{yy} = 800$ ,  $I_{zz} = 300$ , and  $I_{xz} = -200$  kg·m<sup>2</sup>. Evaluate  $S$  by carrying out the calculation manually, then verify the result using mathematical software.

**EXERCISE 1.4** Angular velocity  $\bar{\omega}$  is a fundamental property of the motion of rigid bodies. In the Eulerian angle description, see Chapter 3,  $\bar{\omega}$  is the sum of three contributions in directions defined by unit vectors  $\bar{e}_1$ ,  $\bar{e}_2$ , and  $\bar{e}_3 = \bar{k}$ , such that  $\bar{\omega} = c_1\bar{e}_1 + c_2\bar{e}_2 + c_3\bar{k}$ , with  $\bar{e}_2$  defined to be perpendicular to the plane containing  $\bar{e}_1$  and  $\bar{k}$ . Consider the situation in which the angular velocity is  $\bar{\omega} = 70\bar{i} + 110\bar{j} + 500\bar{k}$  rad/s and  $\bar{e}_1 = -0.4913\bar{i} - 0.7651\bar{j} - 0.4161\bar{k}$ . Determine the corresponding values of  $c_1$ ,  $c_2$ , and  $c_3$ .

**EXERCISE 1.5** The intersecting edges of a nonorthogonal parallelepiped are defined by the position vectors  $\bar{r}_{B/A} = -20\bar{i} + 30\bar{j} + 5\bar{k}$ ,  $\bar{r}_{C/A} = 8\bar{i} + 25\bar{j} + 10\bar{k}$ ,  $\bar{r}_{D/A} = 4\bar{i} - 2\bar{j} - 15\bar{k}$  mm. Determine the volume of this object.

**EXERCISE 1.6** An affine coordinate system has unit vectors that are not mutually orthogonal. The  $x$  and  $y$  axes in the sketch constitute such a system for a planar situation. A vector may be represented in terms of its *contravariant components* relative to  $xy$  by constructing lines parallel to the respective coordinate axes. Such a set of components are  $F^1$  and  $F^2$  for the force vector in the sketch. The unit vectors parallel to the  $x$  and  $y$  axes are  $\bar{e}_1$  and  $\bar{e}_2$ . This force can also be represented in term of its  $F_X$  and  $F_Y$  components relative to the Cartesian  $XY$  coordinate system whose  $X$  axis is coincident with  $x$ . Given that  $F_X = 500$  N,  $F_Y = 350$  N, and  $\beta = 65^\circ$ , use vector algebra to determine  $F^1$  and  $F^2$ .



Exercise 1.6

**EXERCISE 1.7** The mass flow rate per unit surface area is the product of the density and velocity at a point in space, and the mass flux per unit area is the component of the mass flow rate parallel to the unit vector  $\bar{e}$  that is normal to a surface. Consider a square surface whose sides are 200 mm and whose normal is  $\bar{e} = 0.6\bar{j} + 0.8\bar{k}$ . The velocity everywhere on this surface is  $\bar{v} = 80 \cos(5\pi t)\bar{i} - 20 \cos(10\pi t)\bar{j} + 40 \sin(10\pi t)\bar{k}$  m/s, where  $t$  has units of seconds, and the density is 950 kg/m<sup>3</sup>. Determine how much mass flows across the square in the interval  $50 < t < 100$  ms.

**EXERCISE 1.8** Polar coordinates in the  $xy$  plane are defined by the radial distance  $R$  and the polar angle  $\theta$  measured from the  $x$  axis. The corresponding representation of position is  $\bar{r}_{P/O} = R \cos \theta \bar{i} + R \sin \theta \bar{j}$ . Suppose that  $R = \rho + \varepsilon \sin(\alpha t)$  and  $\theta = \alpha t^2/2$ . Determine the velocity of point  $P$ , then evaluate the components of this velocity parallel and perpendicular to  $\bar{r}_{P/O}$ .


**EXERCISE 1.9** Polar coordinates in the  $xy$  plane are defined by the radial distance  $R$  and the polar angle  $\theta$  measured from the  $x$  axis. The corresponding representation of position is  $\bar{r}_{P/O} = R \cos \theta \bar{i} + R \sin \theta \bar{j}$ . Suppose that  $R$  and  $\theta$  are arbitrary functions of

### Homework Problems

29

time. Derive formulas for the velocity of point  $P$  in terms of  $xyz$  components, then evaluate the components of this velocity parallel and perpendicular to  $\vec{r}_{P/O}$ .

**EXERCISE 1.10** The collar slides to the left as the interconnected bars swing in the vertical plane. The position of the collar is  $x = 20 \sin(50t)$  mm, and the angles are  $\theta_1 = 0.2\pi \cos(50t)$ ,  $\theta_2 = 0.2\pi \sin(50t - \pi/3)$  rad. Determine the velocity of the lower end by differentiating its position in terms of horizontal and vertical components.



Exercise 1.10



## CHAPTER 2

# Particle Kinematics

This chapter develops some basic techniques for describing the motion of a point and therefore of a particle. The procedures we follow are driven not merely by how the point's motion is described, but also by the information we seek. Each formulation is based on describing vector quantities with respect to a different set of unit vectors. Which description is best suited to a particular situation depends on a variety of factors, but a primary consideration is whether the associated quantities, such as the coordinates, naturally fit the known aspects of the motion. Ultimately we will find that it might be beneficial to combine a variety of descriptions.

The various kinematical description that we use fall into two general classes. The one that might seem to be the most natural is *extrinsic coordinates*, which means that the description is extrinsic to knowledge of the path followed by the point. A simple case is rectangular Cartesian coordinates, for which the position is known in terms of distances measured along three mutually orthogonal straight lines representing reference directions. A variety of other extrinsic coordinate systems are in use. However, we begin by studying *intrinsic coordinates*, in which knowledge of the path is fundamental to the description of the motion. For example, the unit vectors for intrinsic coordinates are defined in terms of the properties of the path. For this reason, intrinsic coordinates are more commonly referred to as *path variables*.

## 2.1 PATH VARIABLES

The idea that the motion of a point should be described in terms of the properties of its path may seem to be counterintuitive, in that the nature of the motion defines the path. However, this is precisely the way in which one thinks when using a road map in conjunction with the speedometer and odometer of an automobile. Another name for this type of description is *tangent and normal components*, because those are the primary component directions, as we shall see.

We assume that the path is known. The fundamental variable for a specified path is the arc length  $s$  along this curve, measured from some starting point to the point of interest. As shown in Fig. 2.1, measurement of  $s$  requires definition of positive sense along the path. Negative  $s$  means that the point has receded, rather than advanced, along its path. It is quite obvious from Fig. 2.1 that the position  $\bar{r}_{P/O}$  is unambiguously defined by the value of  $s$ . Furthermore, because  $s$  changes with time, the position is an implicit function of time,  $\bar{r}_{P/O} = \bar{r}(s)$  and  $s = s(t)$ . (Mathematically, the preceding

## 2.1 Path Variables

31




Figure 2.1. Position as a function of arc length.

should be understood to indicate that the position is a vector function of the arc length, which in turn is a scalar function of time.) It follows that the derivation of formulas for velocity and acceleration will involve the chain rule for differentiation.

By definition, velocity is the rate of change of the position vector. Differentiating the implicit description of position leads to

$$\bar{v} = \frac{d\bar{r}}{dt} = \frac{d\bar{r}}{ds} \frac{ds}{dt} = \dot{s} \frac{d\bar{r}}{ds}. \quad (2.1.1)$$

(In the present context only one point is under consideration, so subscripts can be omitted from the notation.) The quantity  $d\bar{r}/ds$  occurring in Eq. (2.1.1) is determined solely by the nature of the dependence of the position vector on the path. Hence it is another of the path variables.

By definition, acceleration is the rate of change of the velocity, so

$$\bar{a} = \frac{d\bar{v}}{dt} = \dot{s} \frac{d\bar{r}}{ds} + \dot{s} \frac{d}{dt} \left( \frac{d\bar{r}}{ds} \right). \quad (2.1.2)$$

To differentiate the last term we recall that  $d\bar{r}/ds$  depends solely on  $s$ , so we invoke the chain rule to find

$$\bar{a} = \frac{d\bar{v}}{dt} = \dot{s} \frac{d\bar{r}}{ds} + \dot{s}^2 \left( \frac{d^2\bar{r}}{ds^2} \right). \quad (2.1.3)$$

The second derivative,  $d^2\bar{r}/ds^2$ , is another property of the path.

In the simple case of a straight path we can let the origin  $O$  be the starting point of the path without loss of generality. Let  $\bar{e}$  denote the constant orientation of the straight path, so that  $\bar{r} = s\bar{e}$ , and  $d\bar{r}/ds = \bar{e}$ . Because  $\bar{e}$  is invariant in this case,  $d^2\bar{r}/ds^2 = \bar{0}$ , from which it follows that  $\bar{v} = \dot{s}\bar{e}$  and  $\bar{a} = \ddot{s}\bar{e}$ . Thus the velocity and acceleration are oriented parallel to the straight path. The key point here is that acceleration will not be parallel to the velocity for a smooth curvilinear path, unless  $\dot{s} = 0$ . Failure to recognize this elementary fact is probably the most common mistake in the application of the path variable approach to kinematics.

### 2.1.1 Tangent and Normal Components

To understand  $d\bar{r}/ds$  for a curved path we consider Fig. 2.2, which shows the position vector at two locations that are separated by a small arc length  $\Delta s$ . The displacement  $\Delta\bar{r}$




Figure 2.2. Tangent vector.

is the change of the point's position as it moves from position  $s$  to  $s + \Delta s$ ,

$$\Delta \vec{r} = \vec{r}(s + \Delta s) - \vec{r}(s). \quad (2.1.4)$$

In the limit as  $\Delta s \rightarrow ds$ , the magnitude of  $\Delta \vec{r}$  equals  $ds$  because a chord progressively approaches the curve. For the same reason, the direction of  $\Delta \vec{r}$  approaches tangency to the curve, in the sense of increasing  $s$ . This *tangent direction* is described by the unit tangent vector  $\vec{e}_t$ . A unit vector has the dimensionless value 1 for magnitude, so

$$\frac{d\vec{r}}{ds} = \lim_{\Delta s \rightarrow 0} \frac{\Delta \vec{r}}{\Delta s} = \vec{e}_t. \quad (2.1.5)$$

The tangent vector is one of three unit vectors used to describe vectorial quantities in terms of path variables. We encountered an aspect of the second unit vector in Eq. (2.1.3), which featured  $d^2\vec{r}/ds^2 \equiv d\vec{e}_t/ds$ . One basic property that is readily apparent comes from the fact that  $\vec{e}_t$  is a unit vector, so  $\vec{e}_t \cdot \vec{e}_t = 1$ . Differentiation of this relation leads to

$$\vec{e}_t \cdot \frac{d\vec{e}_t}{ds} = 0. \quad (2.1.6)$$

In other words,  $d\vec{e}_t/ds$  is always perpendicular to  $\vec{e}_t$ . (Perpendicularity of a unit vector and its derivative is a general property that will arise frequently.) We define the *normal direction*, whose unit vector is denoted as  $\vec{e}_n$ , to be parallel to this derivative. Because parallelism of two vectors corresponds to their proportionality, this definition may be written as

$$\vec{e}_n = \rho \frac{d\vec{e}_t}{ds}. \quad (2.1.7)$$

Because  $\vec{e}_n$  is a dimensionless unit vector, the factor of proportionality,  $\rho$ , may be found from


$$\rho = \frac{1}{\left| \frac{d\vec{e}_t}{ds} \right|}. \quad (2.1.8)$$

Dimensional consistency of Eq. (2.1.7) requires that  $\rho$  be a length parameter. It is the *radius of curvature*.

There is a simple construction that explains Eq. (2.1.7) for a circular path having radius  $R$ . In Fig. 2.3(a) tangent and normal vectors are placed at adjacent positions on the circle. To construct the increment  $\Delta \vec{e}_t = \vec{e}_t(s + \Delta s) - \vec{e}_t(s)$ , the tails of the two

## 2.1 Path Variables

33



**Figure 2.3.** Relation between tangent and normal directions for a circular path.

tangent vectors are brought into coincidence in Fig. 2.3(b), so that  $\Delta\vec{e}_t$  extends from the head of  $\vec{e}_t(s)$  to  $\vec{e}_t(s+\Delta s)$ . The angle between  $\Delta\vec{e}_t$  and either tangent vector is  $\pi/2 - \Delta\theta/2$ . Because the triangle formed by the two unit vectors is isosceles with unit length, and  $\Delta\theta$  is small, the length of  $\Delta\vec{e}_t$  is essentially  $\Delta\theta$ . For a circular arc, the subtended angle is  $\Delta\theta = \Delta s/R$ , so  $|\Delta\vec{e}_t| \approx \Delta s/R$ . In the limit as  $\Delta s \rightarrow ds$ , the angle between  $\Delta\vec{e}_t$  and either  $\vec{e}_t$  approaches  $\pi/2$ . Multiplying the magnitude of  $d\vec{e}_t$  by the unit vector for its direction gives  $d\vec{e}_t = (ds/R)\vec{e}_n$ . Dividing this relation by  $ds$  leads to an equation that exemplifies Eq. (2.1.7). In general, a quick way of visualizing the direction in which a unit vector changes is to follow the tip of the unit vector as it moves when the parameter  $\theta$  changes.

In the case of an arbitrary path,  $\vec{e}_t$  and  $\vec{e}_n$  at any point along the curve form the *osculating plane*. The generalization of the center of a circle is the *center of curvature*, which is situated in the osculating plane at a distance  $\rho$  in the normal direction from the corresponding point on the curve. In some situations, such as one in which it is necessary to design a curve to meet a certain specification, the foregoing allows us to determine this location according to

$$\vec{r}_{\text{center}} = \vec{r}_{P/O}(s) + \rho\vec{e}_n. \quad (2.1.9)$$

When we substitute Eqs. (2.1.5) and (2.1.7) into the basic formulas for velocity and acceleration, we find that

$$\begin{aligned} \vec{v} &= v\vec{e}_t, & v &= \dot{s}, \\ \vec{a} &= \dot{v}\vec{e}_t + \frac{v^2}{\rho}\vec{e}_n. \end{aligned} \quad (2.1.10)$$

The scalar quantity  $v$  is the *speed* of the particle. These relations, which apply to all paths, contain much information. The first of Eqs. (2.1.10) indicates that the speed is the

magnitude of the velocity; the second equation states that it is the rate of increase of the distance traveled along the path. In the example of the automobile, the speedometer tells us the instantaneous speed of the vehicle. As noted,  $v$  is a scalar, and it is usually considered to be a positive number in common parlance. However, when we use  $v$  analytically, it can be either positive or negative. A negative value of  $v$  when  $s$  is positive indicates that the point is returning to the starting point after traveling a certain positive distance along the path. In contrast, a negative value of  $v$  when  $s$  is negative indicates that the point is receding farther from the starting point. The rate of change of the speed is readily obtained if  $v$  is known as a function of time, but in some situations, the speed might be known as a function of position,  $v(s)$ , in which case the chain rule for differentiation leads to

$$\dot{v} = \frac{dv}{ds} \frac{ds}{dt} = v \frac{dv}{ds}. \quad (2.1.11)$$

The velocity and acceleration always lie in the osculating plane formed by  $\bar{e}_t$  and  $\bar{e}_n$ , but that plane is constant only if the path is planar. Otherwise, the osculating plane twists around as the point moves along its path. There is only a tangential velocity component, whereas both acceleration components exist unless  $v$  is constant, or the path is straight, in which case  $\rho$  is infinite. Recall that a vector is constant only if its magnitude *and* direction are constant. The normal acceleration component is the consequence of the changing direction of the velocity vector. This component is always oriented toward the center of curvature because that is the direction in which the tip of the velocity vector moves. The tangential acceleration results from changing the speed. Increasing  $v$  when  $v$  is positive, or decreasing the magnitude of negative  $v$ , produces a positive tangential acceleration.

The development thus far might seem to be paradoxical in light of Newton's Second Law, for we know that forces can act on a particle in three directions, but there are only two acceleration components. However, buried in the path variable derivation is the fact that there is another direction, perpendicular to the osculating plane. This is the *binormal direction*, which is denoted as  $\bar{e}_b$ . We can determine this direction in any situation by a cross product of the tangent and normal unit vectors,

$$\bar{e}_b = \bar{e}_t \times \bar{e}_n. \quad (2.1.12)$$

One of the uses of the binormal direction arises when we apply Newton's Second Law to a particle. Because two vectors can be equal only when their respective components match, we find that

$$\begin{aligned} \Sigma F_t &\equiv \Sigma \bar{F} \cdot \bar{e}_t = m\dot{v}, \\ \Sigma F_n &\equiv \Sigma \bar{F} \cdot \bar{e}_n = m \frac{v^2}{\rho}, \\ \Sigma F_b &\equiv \Sigma \bar{F} \cdot \bar{e}_b = 0. \end{aligned} \quad (2.1.13)$$

## 2.1 Path Variables

35

The last of Eqs. (2.1.13) shows that there must be a force balance perpendicular to the osculating plane. Also note that, according to the second equation, there must be a net force pushing inward toward the center of curvature, because the changing direction of acceleration is always directed toward that point.

Equations (2.1.13) form a set of *equations of motion*. Each type of kinematical description leads to a different form of these equations. In general, there are three classes of problems involving equations of motion. In the simplest, all aspects of the motion are specified, so that the forces required for the motion may be found algebraically after the acceleration has been determined by use of the appropriate kinematical formulas. The second class of problems occurs when all forces acting on a system are known. The equations of motion then represent differential equations, which may be solved by analytical or numerical methods. The third class of problems is a mixture of the first two, in that some forces are known and some aspects of the motion are specified.

In most situations in which path variables are useful there will be forces acting in the normal and binormal directions whose role is to prevent the particle from moving off the designated path. Both forces have unknown magnitudes that adjust to provide the centripetal acceleration in the presence of the other forces. Such forces are sometimes referred to as *reactions*, but we usually will use the more descriptive term *constraint forces*. If  $v$  is specified, the tangential equation of motion may be solved for a force causing the particle to move along the path. The more interesting condition is that in which the tangential forces are known, in which case that equation of motion is an ordinary differential equation. The tangential resultant force might depend on  $t$ , which could characterize a force that we control. This resultant force might also depend on  $s$ , which would be the case for a spring force, or it might depend on  $v$ , as in the case of any frictional resistance. Thus  $\Sigma F_t = f(t, s, v)$  in the most general situation. The tangential equation of motion then is a second-order differential equation,  $m\ddot{s} = f(t, s, \dot{s})$ . This equation is readily solved if  $f$  is linear in  $s$  and  $\dot{s}$  and the dependence on  $t$  is not too complicated. Other situations might require numerical methods, such as Runge–Kutta integration.

If  $f$  depends on only one variable, then we may obtain  $v$  and  $s$  by separating variables. Specifically, if the resultant force depends solely on  $t$ , we replace  $\ddot{s}$  with  $dv/dt$ , so that separating variables leads to

$$m dv = f(t) dt. \quad (2.1.14)$$

A definite integration whose lower limits are the initial conditions yields the speed as a function of time,  $v = g(t)$ . Because  $v = ds/dt$ , separating variables here gives  $ds = g(t) dt$ , whose integration leads to  $s$  as a function of time. When the resultant force depends solely on  $s$ , we use Eq. (2.1.11) to replace  $\ddot{s}$ . The separated form of the tangential equation then is

$$m v dv = f(s) ds. \quad (2.1.15)$$


The definite integral of this differential form can be solved for  $v$  as a function of  $s$ ,  $v = g(s)$ . Separation of variables by use of  $v = ds/dt = g(s)$  leads to  $ds/g(s) = dt$ , which may be integrated to find the value of  $t$  for a specified  $s$ . The third case, in which

$\Sigma F_t = f(v)$ , may also be addressed by use of Eq. (2.1.11). The separated form of the equation of motion then is

$$m \frac{v dv}{f(v)} = ds. \quad (2.1.16)$$

Definite integration of this expression gives  $s$  as a function of  $v$ ,  $s = h(v)$ . Inversion gives  $v = h^{-1}(s)$ , which is the same type of dependency as the one obtained when  $\Sigma F_t = f(s)$ , so determination of  $s$  as a function of  $t$  can proceed as discussed for that case.

**EXAMPLE 2.1** At the instant when the 5-kg particle is at position  $A$ , it has a velocity of 500 m/s directed from point  $A$  to point  $B$  and an acceleration of  $10g$  directed from point  $A$  to point  $O$ . Determine the corresponding rate of change of the speed, the radius of curvature of the path, and the location of the center of curvature of the path. Also determine the tangent, normal, and binormal components of the resultant force acting on the particle.



Example 2.1

**SOLUTION** This example demonstrates how one can extract path variable information when the velocity and acceleration are known. The idea is to make the velocity and acceleration fit the fundamental formulas for path variables. The given vectors are

$$\vec{v} = 500 \vec{e}_{B/A} \text{ m/s}, \quad \vec{a} = 10(9.807) \vec{e}_{O/A} \text{ m/s}^2.$$

The unit vectors are defined by the positions of the end points, according to

$$\begin{aligned} \vec{r}_{A/O} &= 4 \cos 60^\circ (\cos 75^\circ \vec{i} + \sin 75^\circ \vec{j}) + 4 \sin 60^\circ \vec{k} \\ &= 0.5176 \vec{i} + 1.9319 \vec{j} + 3.464 \vec{k} \text{ m}, \end{aligned}$$

$$\vec{r}_{B/O} = 4 \vec{i},$$

$$\vec{e}_{B/A} = \frac{\vec{r}_{B/A}}{|\vec{r}_{B/A}|} = \frac{\vec{r}_{B/O} - \vec{r}_{A/O}}{|\vec{r}_{B/O} - \vec{r}_{A/O}|} = 0.6598 \vec{i} - 0.3660 \vec{j} - 0.6563 \vec{k},$$

$$\vec{e}_{O/A} = -\frac{\vec{r}_{A/O}}{|\vec{r}_{A/O}|} = -0.1294 \vec{i} - 0.4830 \vec{j} - 0.8660 \vec{k}.$$

In general,  $\vec{v} = v \vec{e}_t$ , from which it follows that

$$\vec{e}_t = \vec{e}_{B/A} = 0.6598 \vec{i} - 0.3660 \vec{j} - 0.6563 \vec{k}.$$

## 2.1 Path Variables

37

Then, because  $\dot{v}$  is the tangential component of acceleration, we find

$$\dot{v} = \bar{a} \cdot \bar{e}_t = 98.07\bar{e}_{O/A} \cdot \bar{e}_{B/A} = 64.70 \text{ m/s}^2. \quad \triangleleft$$

We may evaluate the normal acceleration by forming the difference between  $\bar{a}$  and  $\dot{v}\bar{e}_t$ , specifically,

$$\begin{aligned} \frac{v^2}{\rho}\bar{e}_n &= \bar{a} - \dot{v}\bar{e}_t = 98.07\bar{e}_{O/A} - 64.70\bar{e}_{B/A} \\ &= -55.38\bar{i} - 23.68\bar{j} - 42.47\bar{k} \text{ m/s}^2. \end{aligned}$$

The values of  $\rho$  and  $\bar{e}_n$  come from the magnitude and direction of the normal acceleration component,

$$\begin{aligned} \frac{v^2}{\rho} &= (55.38^2 + 23.69^2 + 42.47^2)^{1/2} = 73.70 \text{ m/s}^2, \\ \rho &= \frac{v^2}{73.70} = 3392 \text{ m}, \\ \bar{e}_n &= \frac{-55.38\bar{i} - 23.69\bar{j} - 42.47\bar{k}}{73.70} = -0.7515\bar{i} - 0.3213\bar{j} - 0.5762\bar{k}. \end{aligned} \quad \triangleleft$$

To locate the center of curvature  $C$  we recall Eq. (2.1.9):

$$\bar{r}_{C/O} = \bar{r}_{A/O} + \rho\bar{e}_n = -2549\bar{i} - 1088\bar{j} - 1951\bar{k} \text{ m}. \quad \triangleleft$$

In general, if a problem involves forces we should draw a free-body diagram. However, the forces in the present case are straightforward. The gravity force is  $mg$  in the negative  $\bar{k}$  direction. In addition, there is a force tangent to the path, which changes the speed, and there may be normal and binormal components of a contact force that prevent the particle from moving perpendicularly to the path. Thus Newton's Second Law is

$$\Sigma \bar{F} = -5(9.807)\bar{k} + F_t\bar{e}_t + F_n\bar{e}_n + F_b\bar{e}_b = 5\left(\dot{v}\bar{e}_t + \frac{v^2}{\rho}\bar{e}_n\right).$$

Expressions for  $\bar{e}_t$  and  $\bar{e}_n$  have been found. We evaluate  $\bar{e}_b$  from the cross product:

$$\bar{e}_b = \bar{e}_t \times \bar{e}_n = 0.8734\bar{j} - 0.4871\bar{k}.$$

To find the force components we use a dot product of the resultant force and each of the unit vectors,

$$\begin{aligned} \Sigma \bar{F} \cdot \bar{e}_t &= -49.035(-0.6563) + F_t = 5\dot{v}, \\ \Sigma \bar{F} \cdot \bar{e}_n &= -49.035(-0.5763) + F_n = 5\frac{v^2}{\rho}, \\ \Sigma \bar{F} \cdot \bar{e}_b &= -49.035(-0.4871) + F_b = 0, \end{aligned}$$

from which we obtain

$$F_t = 291.3, \quad F_n = 340.2, \quad F_b = -23.9 \text{ N}. \quad \triangleleft$$



## 2.1 Path Variables

41

In view of the fact that  $s' = [1 + (dy/dx)^2]^{1/2}$ , solving the preceding expression for  $\rho$  gives

$$\rho = \frac{\left[1 + \left(\frac{dy}{dx}\right)^2\right]^{3/2}}{\left|\frac{d^2y}{dx^2}\right|}, \quad (2.1.31)$$

which is the same as the formula derived in a course on calculus. Back substitution of  $\rho$  into the preceding expression for  $\bar{e}_n$  leads to

$$\bar{e}_n = \frac{\frac{d^2y}{dx^2}}{\left|\frac{d^2y}{dx^2}\right|} \frac{1}{s'} \left(-\frac{dy}{dx}\bar{i} + \bar{j}\right) = \text{sgn}\left(\frac{d^2y}{dx^2}\right) \frac{-\frac{dy}{dx}\bar{i} + \bar{j}}{\left[1 + \left(\frac{dy}{dx}\right)^2\right]^{1/2}}, \quad (2.1.32)$$

where  $\text{sgn}(\ )$  denotes the signum function, that is, the sign of the argument. It tells us the sense in which the normal vector is perpendicular to the tangent vector. If  $d^2y/dx^2$  is positive, which means that the slope increases with increasing  $x$ , then  $\bar{e}_n$  will have a positive  $\bar{e}_y$  component.

Two simple checks are available. The first verifies that both  $\bar{e}_t$  and  $\bar{e}_n$  have unit magnitudes, which may be done by comparing  $\bar{e}_t \cdot \bar{e}_t$  and  $\bar{e}_n \cdot \bar{e}_n$  to unity. The second check verifies that the unit vectors are orthogonal, which can be verified by ascertaining that  $\bar{e}_t \cdot \bar{e}_n = 0$ .

**EXAMPLE 2.3** A particle follows the path defined by  $x = 0.2\beta \cos(\beta)$ ,  $y = 0.2\beta \sin(\beta)$ , and  $z = 0.1\beta^2$ , where each coordinate is measured in meters. The speed depends on time  $t$  (in seconds) according to  $v = 20t$  m/s, and the particle was at the origin when  $t = 0$ . Determine the velocity and acceleration of the particle when  $t = 0.5$  s. Also describe the path.

**SOLUTION** This problem is quite intricate. It will serve to illustrate the application of most of the relevant relations and also to highlight the thought process needed to implement these relations. We begin by observing that the path is specified in parametric form, with  $\beta$  as the parameter. Furthermore, the value of  $\beta$  for the position of interest is not specified. To determine this value we need to follow an inverse process, in which we use the given function  $v(t)$  to determine  $s$  at  $t = 0.5$  s, then solve the relation for  $s$  in terms of  $\beta$  to determine the corresponding value of the parameter. After that, the remainder of the work reduces to straightforward calculations.

The speed increases at a constant rate and  $s = 0$  at  $t = 0$ , so we have

$$v = 20t \implies s = 10t^2, \quad \dot{v} = 20.$$

Setting  $t = 0.5$  s shows that the values at the position of interest are

$$s = 2.5 \text{ m}, \quad v = 10 \text{ m/s}, \quad \dot{v} = 20 \text{ m/s}^2.$$

The derivatives of the coordinate functions are

$$\begin{aligned} x' &= 0.2 [\cos(\beta) - \beta \sin(\beta)], & x'' &= 0.2 [-2 \sin(\beta) - \beta \cos(\beta)], \\ y' &= 0.2 [\sin(\beta) + \beta \cos(\beta)], & y'' &= 0.2 [2 \cos(\beta) - \beta \sin(\beta)], \\ z' &= 0.2\beta, & z'' &= 0.2. \end{aligned}$$


The first derivatives are the components of  $\bar{r}'$ , so

$$\begin{aligned} s' &= [(x')^2 + (y')^2 + (z')^2]^{1/2} \\ &= 0.2 (2\beta^2 + 1)^{1/2}. \end{aligned}$$

We find  $s$  as a function of  $\beta$  by integrating the preceding. Setting  $x = y = z = 0$  for the starting position reveals that  $\beta = 0$  there, so that is the lower limit for a definite integral. Thus,

$$s(\beta_P) = \int_0^{\beta_P} 0.2 (2\beta^2 + 1)^{1/2} d\beta = 0.1\beta (2\beta^2 + 1)^{1/2} + 0.05\sqrt{2} \sinh^{-1}(\sqrt{2}\beta_P).$$

The root-finding function of our mathematical software can be used to find the value of  $\beta_P$  for which  $s = 2.5$  m. To do so we need a starting value of  $\beta_P$ , which we can obtain by graphing  $s$  for a range of  $\beta_P$ . From the graph, we see that a good starting value is  $\beta_P = 4$ . The root finder then yields  $\beta_P = 4.026$ . (It should be mentioned that if one encounters a situation for which it is not possible to integrate  $s' d\beta$  analytically, numerical integration can be used to determine  $s$  at a set of  $\beta$  values.)



Graph of arc length as a function of the parameter  $\beta$ .

The values of  $\bar{r}'$  and  $\bar{r}''$  corresponding to this value of  $\beta_P$  are

$$\begin{aligned} \bar{r}' &= x'\bar{i} + y'\bar{j} + z'\bar{k} = 0.4962\bar{i} - 0.6650\bar{j} + 0.8052\bar{k}, \\ \bar{r}'' &= x''\bar{i} + y''\bar{j} + z''\bar{k} = 0.8197\bar{i} + 0.3995\bar{j} + 0.20\bar{k}, \end{aligned}$$

## 2.1 Path Variables

43

and  $s'(\beta_p) = 1.1489$ . Substitution of these values into Eqs. (2.1.18), (2.1.29), and (2.1.28) yields

$$\bar{e}_t = 0.4292\bar{i} - 0.5751\bar{j} + 0.6965\bar{k},$$

$$\bar{e}_n = 0.7975\bar{i} + 0.6033\bar{j} + 0.0068\bar{k},$$

$$\rho = 1.5226 \text{ m}.$$

The basic kinematical formulas, Eqs. (2.1.10), correspondingly give

$$\bar{v} = 4.292\bar{i} - 5.751\bar{j} + 6.965\bar{k} \text{ m/s},$$

$$\bar{a} = 60.96\bar{i} + 28.123\bar{j} + 14.38\bar{k} \text{ m/s}^2.$$

The last task is to describe the path. We observe that  $x$  and  $y$  are respectively proportional to  $\cos(\beta)$  and  $\sin(\beta)$ , and recall that  $(x^2 + y^2)^{1/2}$  is the distance to the  $z$  axis. This suggests that we consider polar coordinates, with the polar angle defined by  $\tan \theta = y/x = \tan \beta$ , so we take  $\theta = \beta$ . Thus the radial distance  $R = (x^2 + y^2)^{1/2} = 0.2\theta$ , which means that the projection of the path onto the  $xy$  plane is a linearly increasing spiral. The axial distance becomes  $z = 0.1\theta^2 = 2.5R^2$ , which tells us that the distance along the  $z$  axis increases as the square of the perpendicular distance from the  $z$  axis. In other words, the path seems to be a rapidly expanding helical-type path that wraps around the  $z$  axis.

### 2.1.3 Binormal Direction and Torsion of a Curve

The development thus far is adequate to determine the velocity and acceleration. However, additional study of the unit vectors will enhance our understanding of the properties of curves. Because  $\bar{e}_t$  and  $\bar{e}_n$  are situated in the osculating plane, the binormal direction  $\bar{e}_b$  was introduced to resolve an arbitrary vector, such as the resultant force acting on a particle. This direction was defined by use of a cross product,  $\bar{e}_b = \bar{e}_t \times \bar{e}_n$ . However, it also is possible to express  $\bar{e}_b$  in terms of derivatives of the other path variable unit vectors, which leads to an expression that parallels the definitions of  $\bar{e}_t$  and  $\bar{e}_n$ .

The component of an arbitrary vector in a specific direction may be obtained from a dot product with a unit vector in that direction. Multiplying each component by the corresponding unit vector and adding the individual contributions then reproduces the original vector. Applying this notion to the description of the derivative of  $\bar{e}_n$  gives

$$\frac{d\bar{e}_n}{ds} = \left( \frac{d\bar{e}_n}{ds} \cdot \bar{e}_t \right) \bar{e}_t + \left( \frac{d\bar{e}_n}{ds} \cdot \bar{e}_n \right) \bar{e}_n + \left( \frac{d\bar{e}_n}{ds} \cdot \bar{e}_b \right) \bar{e}_b. \quad (2.1.33)$$

We obtain the tangential component in Eq. (2.1.33) from the orthogonality of the unit vectors, which requires that  $\bar{e}_n \cdot \bar{e}_t = 0$ , so that

$$\frac{d\bar{e}_n}{ds} \cdot \bar{e}_t = -\bar{e}_n \cdot \frac{d\bar{e}_t}{ds} = -\bar{e}_n \cdot \left( \frac{1}{\rho} \bar{e}_n \right) = -\frac{1}{\rho}. \quad (2.1.34)$$

Similarly, because  $\bar{e}_n \cdot \bar{e}_n = 1$ , we find that

$$\frac{d\bar{e}_n}{ds} \cdot \bar{e}_n = 0. \quad (2.1.35)$$

The binormal component in Eq. (2.1.33) is generally nonzero; its value is defined to be the reciprocal of the path's *torsion*  $\tau$ :

$$\frac{d\bar{e}_n}{ds} \cdot \bar{e}_b \equiv \frac{1}{\tau}. \quad (2.1.36)$$

The reciprocal is used here for consistency with Eq. (2.1.7), such that  $\tau$  has the dimension of length. Substitution of Eqs. (2.1.34)–(2.1.36) into Eq. (2.1.33) results in

$$\boxed{\frac{d\bar{e}_n}{ds} = -\frac{1}{\rho}\bar{e}_t + \frac{1}{\tau}\bar{e}_b.} \quad (2.1.37)$$

The derivative of  $\bar{e}_b$  may be obtained by a similar approach. The decomposition of  $d\bar{e}_b/ds$  is

$$\frac{d\bar{e}_b}{ds} = \left(\frac{d\bar{e}_b}{ds} \cdot \bar{e}_t\right)\bar{e}_t + \left(\frac{d\bar{e}_b}{ds} \cdot \bar{e}_n\right)\bar{e}_n + \left(\frac{d\bar{e}_b}{ds} \cdot \bar{e}_b\right)\bar{e}_b. \quad (2.1.38)$$

The fact that  $\bar{e}_t$ ,  $\bar{e}_n$ , and  $\bar{e}_b$  are mutually orthogonal, in combination with Eqs. (2.1.7) and (2.1.37), yields

$$\begin{aligned} \bar{e}_b \cdot \bar{e}_t = 0 &\implies \frac{d\bar{e}_b}{ds} \cdot \bar{e}_t = -\bar{e}_b \cdot \frac{d\bar{e}_t}{ds} = -\bar{e}_b \cdot \frac{1}{\rho}\bar{e}_n = 0, \\ \bar{e}_b \cdot \bar{e}_n = 0 &\implies \frac{d\bar{e}_b}{ds} \cdot \bar{e}_n = -\bar{e}_b \cdot \frac{d\bar{e}_n}{ds} = -\bar{e}_b \cdot \left(-\frac{1}{\rho}\bar{e}_t + \frac{1}{\tau}\bar{e}_b\right) = -\frac{1}{\tau}, \\ \bar{e}_b \cdot \bar{e}_b = 1 &\implies \frac{d\bar{e}_b}{ds} \cdot \bar{e}_b = 0. \end{aligned} \quad (2.1.39)$$

It follows that

$$\boxed{\frac{d\bar{e}_b}{ds} = -\frac{1}{\tau}\bar{e}_n.} \quad (2.1.40)$$

Because  $\bar{e}_n$  is a unit vector, this relation provides an alternative to Eq. (2.1.36) for the torsion:

$$\frac{1}{\tau} = \left| \frac{d\bar{e}_b}{ds} \right|. \quad (2.1.41)$$

Equations (2.1.7), (2.1.37), and (2.1.40) are Frenet's formulas for a spatial curve. The first one shows that a small advancement along the path primarily changes the tangent vector in the normal direction. The osculating plane is formed from  $\bar{e}_t$  and  $\bar{e}_n$ . We therefore may consider this plane to be the tangent plane that most closely fits the curve at the position of interest. Equation (2.1.40) shows that small increments in  $s$  primarily change the binormal vector in the direction of  $\bar{e}_n$ . This is equivalent to a rotation of the osculating plane about the tangent direction, which is the source of the terminology "torsion." The osculating plane is constant for a planar curve, which corresponds to an infinite value of  $\tau$ . The greater the degree to which a curve is twisted in space, the smaller will be the value of  $\tau$ . In a similar vein,  $\rho$  measures the amount by which the curve bends in the osculating plane. A small value of  $\rho$  corresponds to a highly bent curve, and  $\rho$  is infinite for a straight line.

## 2.2 Rectangular Cartesian Coordinates

45

### 2.2 RECTANGULAR CARTESIAN COORDINATES

We now turn our attention to extrinsic coordinate systems, in which all properties are defined independently of knowledge of the path. The simplest set of extrinsic coordinates is rectangular Cartesian coordinates. These are associated with orthogonal  $xyz$  axes that are right-handed by convention. Situations in which such coordinates might be suitable are recognizable by the fact that vectors (position, velocity, force, etc.) are described in terms of components with respect to fixed directions, such as left–right and up–down. Figure 2.4 shows that the components of the position vector are merely the  $(x, y, z)$  coordinates. This may be established by either of two alternatives. The position of the point may be projected onto each of the three coordinate planes, after which each projection point is itself projected onto the coordinate axes of that plane. The projection lines form a box, for which the position vector  $\vec{r}$  is a main diagonal. The second construction drops a perpendicular from the point onto each of the coordinate axes. The perpendiculars form the diagonals of each face of the box formed in the first construction.




Figure 2.4. Rectangular Cartesian coordinates.

Each coordinate may be a function of time, so the position is given by

$$\vec{r}_{P/O} = x(t)\vec{i} + y(t)\vec{j} + z(t)\vec{k}. \quad (2.2.1)$$

Differentiating this expression is a simple matter because the unit vectors are constant. Thus, the velocity is given by

$$\begin{aligned} \vec{v} &= v_x\vec{i} + v_y\vec{j} + v_z\vec{k}, \\ v_x &= \dot{x}, \quad v_y = \dot{y}, \quad v_z = \dot{z}, \end{aligned} \quad (2.2.2)$$

from which it follows that the acceleration is

$$\begin{aligned} \vec{a} &= a_x\vec{i} + a_y\vec{j} + a_z\vec{k}, \\ a_x &= \dot{v}_x = \ddot{x}, \quad a_y = \dot{v}_y = \ddot{y}, \quad a_z = \dot{v}_z = \ddot{z}. \end{aligned} \quad (2.2.3)$$

A notable feature of these relations is that the motions in the  $x$ ,  $y$ , and  $z$  are *uncoupled inertially*. Specifically, the acceleration in one direction does not contain the other

coordinates. One way of regarding this result conceptually is to think of it as a superposition of rectilinear (i.e., straight line) motions in each of the coordinate directions. However, one should not infer from this observation that the motions in the three directions are independent. This becomes evident when we formulate Newton's Second Law in terms of components relative to the  $xyz$  axes:

$$\begin{aligned}\Sigma F_x &\equiv \Sigma \vec{F} \cdot \vec{i} = m\ddot{x}, \\ \Sigma F_y &\equiv \Sigma \vec{F} \cdot \vec{j} = m\ddot{y}, \\ \Sigma F_z &\equiv \Sigma \vec{F} \cdot \vec{k} = m\ddot{z}.\end{aligned}\tag{2.2.4}$$

The force components might be known as functions of time, but they also can depend on the  $x$ ,  $y$ , and/or  $z$  coordinates of the particle's location, as well as the  $\dot{x}$ ,  $\dot{y}$ , and/or  $\dot{z}$  velocity components. Thus, if these dependencies are known, Eqs. (2.2.4) can represent as many as three coupled ordinary differential equations whose solution is the position coordinates of the particle as a function of time.

In fully uncoupled situations the resultant force components depend solely on the corresponding position or velocity coordinate. For example, suppose  $\ddot{x} = f(x, v_x, t)$ . This constitutes a differential equation for  $x$  because  $v_x = \dot{x}$ . The techniques for separating variables that were described in the context of path variables, specifically Eqs. (2.1.14)–(2.1.16), are directly applicable here. If the force components couple motion in different directions, an analytical solution might be obtainable if all terms depend linearly on the position coordinates and their time derivatives. Of course, if analytical techniques do not seem promising, one can always solve the differential equations of motion numerically. Numerical solution techniques are discussed in Sections 7.6 and 8.2.


Not surprisingly, the simplicity of Cartesian coordinate formulation limits its usefulness. Practical situations in which the motion is given in terms of fixed directions are not abundant. The most common involves projectile motion near the Earth's surface. In that case the force of gravity is considered to act in the downward vertical direction, which means that the acceleration is always downward. Even this case breaks down when one wishes to treat the motion more accurately. For example, if it is desired to account for air resistance, the resistance force is always opposite the velocity. Such a force is readily described in path variables as  $-f\vec{e}_t$ . The description of projectile motion in terms of Cartesian coordinates also encounters difficulty when the motion covers a long range, as is the case for ballistic missiles. Then the gravitational force is always directed toward a fixed point, rather than having a fixed direction. A kinematical description using polar coordinates, see the next section, is more suitable to this type of consideration. The corresponding analysis is *orbital motion*.

**EXAMPLE 2.4** A 10-mg dust particle is injected into an electrostatic precipitator with an initial velocity of 20 m/s, as shown. The  $z$  axis is vertical and the attractive force on the particle is  $1.6 - 4y$  mN acting in the positive  $y$  direction, where  $y$  is

## 2.2 Rectangular Cartesian Coordinates

47

measured in meters. Determine the location and velocity at which the dust particle will strike a collector plate that is situated in the vertical plane defined by  $y = 400$  mm.



**Example 2.4**

**SOLUTION** In addition to showing how a decomposition of forces into a set of components can lead to differential equations governing the movement of a particle, a primary intent of this example is to emphasize that constant acceleration rates are the exceptional case. The forces acting on the particle are its weight and the electrostatic force, both of which act in fixed directions. It is for this reason that we employ Cartesian coordinates. Forming  $\Sigma \vec{F} = m\vec{a}$  in units of newtons gives

$$(1.6 - 4y)(10^{-3})\vec{j} - 10(10^{-6})(9.807)\vec{k} = 10(10^{-6})\vec{a}. \quad (1)$$

We proceed to take components of this equation in the three coordinate directions. We have an alternative here, depending on whether we consider  $\vec{a}$  to be the first derivative of velocity or the second derivative of position. In the former viewpoint we substitute  $\vec{a} = \dot{v}_x\vec{i} + \dot{v}_y\vec{j} + \dot{v}_z\vec{k}$ , which yields

$$\dot{v}_x = 0, \quad \dot{v}_y = 160 - 400y, \quad \dot{v}_z = -9.807. \quad (2)$$

These are first-order differential equations for the velocity components. The accelerations are constant in the first and third equations, so they may be integrated directly. In the second equation the acceleration rate depends on the corresponding distance, so we may solve this equation by changing  $s$  to  $y$  in Eq. (2.1.15). Note that integrating the equations in this manner yields solutions for the rate variables. Replacing each rate variable with its definition, that is,  $v_x = \dot{x}$ ,  $v_y = \dot{y}$ , and  $v_z = \dot{z}$ , leads to another set of differential equations for the position coordinates.

The second of the aforementioned approaches entails writing  $\vec{a} = \ddot{x}\vec{i} + \ddot{y}\vec{j} + \ddot{z}\vec{k}$ , which leads to

$$\ddot{x} = 0, \quad \ddot{y} = 160 - 400y, \quad \ddot{z} = -9.807. \quad (3)$$

We now have three second-order differential equations of motion. Either approach is suitable in this problem because analytical solutions are readily obtained. We shall follow the latter one here because it directly yields the position coordinates as functions of time. In other situations, the first-order approach might be easier to implement.

Equations (3) are linear and second order, with constant coefficients. We obtain the initial conditions by setting  $\vec{r}_0 = \vec{0}$  for launch at the origin, so the initial coordinates are  $x_0 = y_0 = z_0 = 0$ . Resolving the given initial velocity into components along the coordinate axes gives

$$\begin{aligned}\vec{v}_0 &= 20 \cos 45^\circ (\cos 20^\circ \vec{i} - \sin 20^\circ \vec{j}) + 20 \sin 45^\circ \vec{k} \\ &= 13.289\vec{i} - 4.837\vec{j} + 14.142\vec{k}.\end{aligned}\quad (4)$$

The components of this velocity are the scalar initial values:  $\dot{x}_0 = 13.289$  m/s,  $\dot{y}_0 = -4.837$  m/s,  $\dot{z}_0 = 14.142$  m/s at  $t = 0$ .

Integrating the first of Eqs. (3) twice gives

$$x = c_1 t + c_2.$$

This expression must match the initial values  $x_0$  and  $\dot{x}_0$ , which requires that  $c_1 = 13.289$ ,  $c_2 = 0$ . Integrating the third of Eqs. (3) twice gives

$$z = -\frac{1}{2}(9.807)t^2 + c_3 t + c_4.$$

We find the integration constants by matching this expression to the initial values  $z_0$  and  $\dot{z}_0$ , which gives  $c_3 = 14.142$ ,  $c_4 = 0$ . The second of Eqs. (3) is a standard differential equation,  $\ddot{y} + 400y = 160$ , whose general solution is

$$y = c_5 \cos(20t) + c_6 \sin(20t) + 0.4.$$

Equating  $y$  and  $\dot{y}$  from this relation to the initial conditions at  $t = 0$  yields  $c_5 = -0.4$ ,  $c_6 = -0.2418$ . Thus the Cartesian coordinates of the particle as functions of time are

$$\begin{aligned}x &= 13.289t, & y &= -0.4 \cos(20t) - 0.2418 \sin(20t) + 0.4, \\ z &= -4.9035t^2 + 14.142t \text{ m}.\end{aligned}\quad (5)$$

Now that we have determined the response as a function of time, we may study its properties. We find the instant  $t_f$  when the particle hits the collector plate by setting  $y = 0.4$  for  $t > 0$ , which occurs when

$$-0.4 \cos(20t_f) - 0.2418 \sin(20t_f) = 0 \implies \tan(20t_f) = -1.6543.$$

The smallest positive root corresponds to

$$\begin{aligned}20t_f &= \tan^{-1}(-1.6543) = -1.0270 + \pi, \\ t_f &= 0.10573 \text{ s}.\end{aligned}$$

Evaluating the position components for that instant yields

$$x = 1.4050, \quad y = 0.4, \quad z = 1.4404 \text{ m}.\quad \triangleleft$$

We obtain the final velocity components by differentiating Eqs. (5) and then evaluating the results at  $t_f$ . This gives

$$\dot{x} = 13.289, \quad \dot{y} = 9.348, \quad \dot{z} = 13.105 \text{ m/s}.\quad \triangleleft$$



## 2.2 Rectangular Cartesian Coordinates

49

**EXAMPLE 2.5** A right circular cone is defined by  $x^2 + y^2 = 9z^2$ , ( $x$ ,  $y$ , and  $z$  have units of millimeters). The vertical position of a block sliding along the interior of such a cone is observed to be  $z = 480 - 80t^2$ , and  $x = y^2/200$ . Also,  $y > 0$  throughout the motion. Determine the velocity and acceleration of the block when  $t = 2$  s.

**SOLUTION** In addition to demonstrating the application of the basic Cartesian coordinate formulas, this example shows how one can beneficially use implicit differentiation. Because the intersection of two functions relating  $x$ ,  $y$ , and  $z$  is a curve, the functions for the conical surface and for  $x$  in terms of  $y$  specify the path of the particle. In the present situation  $x = y^2/200$ , which is a parabola whose axis of symmetry is  $x$ , describes the projection of the path onto the  $xy$  plane. The equation for the cone then gives the  $z$  value corresponding to a specified  $x$ ,  $y$  pair. We elect to use Cartesian coordinates, rather than path variables, because the second of the given relations prescribes the movement in terms of the distance along the  $z$  axis. We could simplify the functional relationships by using the first and third equations to relate  $y$  solely to  $z$ , but this is not done in order to demonstrate how one could handle truly complicated functional relations.

The given position equations with  $x$ ,  $y$ , and  $z$  in meters are

$$z = 0.480 - 0.080t^2, \quad x = 5y^2, \quad x^2 + y^2 = 9z^2 \text{ m.} \quad (1)$$

Differentiation of these expressions yields relations governing  $\dot{x}$ ,  $\dot{y}$ , and  $\dot{z}$ :

$$\dot{z} = -0.16t, \quad \dot{x} = 10y\dot{y}, \quad x\dot{x} + y\dot{y} = 9z\dot{z}. \quad (2)$$

A second differentiation leads to

$$\begin{aligned} \ddot{z} &= -0.16, \quad \ddot{x} = 10(y\ddot{y} + \dot{y}^2), \\ x\ddot{x} + \dot{x}^2 + y\ddot{y} + \dot{y}^2 &= 9(z\ddot{z} + \dot{z}^2). \end{aligned} \quad (3)$$

We may solve Eqs. (1) for  $x$ ,  $y$ , and  $z$  at a specified  $t$ . Then Eqs. (2) become a set of linear equations for the corresponding first derivatives, which may be written in matrix form as

$$\begin{bmatrix} 0 & 0 & 1 \\ 1 & -10y & 0 \\ x & y & -9z \end{bmatrix} \begin{Bmatrix} \dot{x} \\ \dot{y} \\ \dot{z} \end{Bmatrix} = \begin{Bmatrix} -0.16t \\ 0 \\ 0 \end{Bmatrix}. \quad (4)$$

After these equations are satisfied, Eqs. (3) become simultaneous linear equations for the second derivatives, specifically,

$$\begin{bmatrix} 0 & 0 & 1 \\ 1 & -10y & 0 \\ x & y & -9z \end{bmatrix} \begin{Bmatrix} \ddot{x} \\ \ddot{y} \\ \ddot{z} \end{Bmatrix} = \begin{Bmatrix} -0.16 \\ 10\dot{y}^2 \\ 9\dot{z}^2 - \dot{x}^2 - \dot{y}^2 \end{Bmatrix}. \quad (5)$$

We begin by substituting the first and second of Eqs. (1) into the third equation, which yields  $25y^4 + y^2 = 9(0.08t^2)^2$ . We retain the real root of this equation at  $t = 2$  satisfying  $y > 0$ , and then evaluate the corresponding  $x$ ,

$$x = 0.3903, \quad y = 0.2794, \quad z = 0.160 \text{ m.} \quad (6)$$

These values are substituted into Eqs. (4), whose solution at  $t = 2$  is

$$\dot{x} = -0.9398, \quad \dot{y} = -0.3364, \quad \dot{z} = -0.32 \text{ m/s.} \quad (7)$$

Finally, we substitute Eqs. (6) and (7) into Eqs. (5), which yield

$$\ddot{x} = -0.3917, \quad \ddot{y} = -0.5452, \quad \ddot{z} = -0.160 \text{ m/s}^2.$$

The derivatives are the respective components of the velocity and acceleration, so

$$\begin{aligned} \bar{v} &= -0.9398\bar{i} - 0.3364\bar{j} - 0.320\bar{k} \text{ m/s,} \\ \bar{a} &= -0.3917\bar{i} - 0.5452\bar{j} - 0.160\bar{k} \text{ m/s}^2. \end{aligned} \quad \triangleleft$$

### 2.3 CURVILINEAR COORDINATES

Cartesian coordinates specify the location of a point by giving three numbers that are distances along the coordinate axes. Curvilinear coordinates also use a triad of parameters to locate a point, but they generalize the description by allowing the unit vectors associated with these parameters to be variable. Let  $\alpha$ ,  $\beta$ , and  $\gamma$  be the three parameters, such that there is a unique transformation between the  $(\alpha, \beta, \gamma)$  values and the  $(x, y, z)$  rectangular Cartesian coordinates. The general form of this transformation is

$$x = x(\alpha, \beta, \gamma), \quad y = y(\alpha, \beta, \gamma), \quad z = z(\alpha, \beta, \gamma). \quad (2.3.1)$$

Occasionally, we need the inverse transformation, whose form would be

$$\alpha = \alpha(x, y, z), \quad \beta = \beta(x, y, z), \quad \gamma = \gamma(x, y, z). \quad (2.3.2)$$

When two of the parameters  $(\alpha, \beta, \gamma)$  are held constant, and the third is given a range of values, Eqs. (2.3.1) specify a curve in space in parametric form. When the constant parameter pair is given an assortment of values, the result is a family of curves. Repeating this procedure with each of the other pairs of parameters held constant produces two more families of curves. These families of curves form a spatial mesh. The intersection of curves belonging to different families are orthogonal in the cases that we shall treat, in which case  $(\alpha, \beta, \gamma)$  are said to be *orthogonal curvilinear coordinates*. The name for each set of coordinates usually corresponds to one of the types of surfaces on which one of the curvilinear coordinates is constant. We begin by studying cylindrical and spherical coordinates as special cases prior to tackling an arbitrary set of coordinates.

## 2.3 Curvilinear Coordinates

51

### 2.3.1 Cylindrical and Polar Coordinates

The vast majority of situations we encounter are well described in terms of cylindrical and spherical coordinates, both of which have meshes that consist of circles and straight lines. In cylindrical coordinates, we select one of the Cartesian coordinate axes as a reference. We then locate a point by perpendicularly projecting its position onto the coordinate plane formed by the other two axes and onto the reference axis. Without loss of generality, let  $z$  be the reference axis. The corresponding construction is illustrated in Fig. 2.5. The distance from the point to the  $z$  axis is the *transverse distance*  $R$ , and the distance from the point to the  $xy$  plane is the *axial distance*  $z$ . It still remains to locate the plane formed by the axial and transverse lines, for which we use the angle  $\theta$  representing the rotation of the plane about the reference axis. Prior to the advent of inertial navigation, global positioning employed a sextant, which used a telescope on a swivel platform to locate the North Star. The angle the telescope was rotated about its platform was called the *azimuthal angle*. That is the name we shall use for  $\theta$ , but some individuals prefer to call it the *circumferential angle*. To avoid ambiguity when it is necessary to select a value of  $\theta$  corresponding to a specified position we shall limit the azimuthal angle range to  $-\pi < \theta \leq \pi$ . In Fig. 2.5,  $\theta = 0$  places the shaded plane at the  $xz$  plane, and  $\theta$  is measured counterclockwise looking down the  $z$  axis, but neither convention is mandatory.




Figure 2.5. Definition of the cylindrical coordinates.

The values of  $(R, \theta, z)$  are the *cylindrical coordinates*. By themselves,  $R$  and  $\theta$  are *polar coordinates*. They locate the point in the  $xy$  plane, whereas the value of  $z$  tells us how far the point is from that plane. Geometrical constructions show the transformation from  $(R, \theta, z)$  to  $(x, y, z)$  to be

$$\boxed{x = R \cos \theta, \quad y = R \sin \theta, \quad z = z.} \quad (2.3.3)$$

To construct the coordinate mesh, we observe that allowing  $R$  to change with  $\theta$  and  $z$  held constant moves the point along a radial line, perpendicular to the  $z$  axis, whereas allowing  $z$  to change with  $R$  and  $\theta$  held constant moves the point along a axial line, parallel to the  $z$  axis. The third coordinate curve is a circle parallel to the  $xy$  plane that is produced when  $\theta$  changes with  $R$  and  $z$  is held constant. The curvilinear coordinate mesh corresponds to various transverse lines (different fixed  $\theta$  and  $z$  values), axial lines (different fixed  $R$  and  $\theta$  values), and azimuthal circles (different fixed  $R$  and  $z$  values).

To define unit vectors for vector components, we observe that Cartesian coordinate directions  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  are the directions in which a point moves if two of the  $x$ ,  $y$ , and  $z$  values are held constant, and the other coordinate value is increased. We define the curvilinear coordinate unit vectors in an analogous manner. We use  $\bar{e}$  with the appropriate subscript to denote the unit vectors. Thus  $\bar{e}_R$  is the direction in which a point moves if  $R$  is increased with  $\theta$  and  $z$  constant; this is the *transverse direction*, which is outward along the transverse line from the  $z$  axis to the point. Increasing  $\theta$  with  $R$  and  $z$  constant moves the point tangentially along the azimuthal circle; this is the *azimuthal direction*  $\bar{e}_\theta$ . Finally, increasing  $z$  with  $R$  and  $\theta$  constant moves the point upward parallel to the  $z$  axis; this is the *axial direction*  $\bar{e}_z$ . The set of cylindrical coordinate unit vectors is depicted in Fig. 2.6. Avoidance of sign errors requires that we remember that the sense of the unit vectors is *always* defined according to the sense of increasing coordinate values. The unit vectors we have defined form a right-handed set according to

$$\bar{e}_R \times \bar{e}_\theta = \bar{e}_z. \quad (2.3.4)$$

However, if one needs to compute cross products, the foregoing should not be assumed because it is sometimes more convenient to define  $\theta$  to be in a clockwise sense relative to the axial direction, which would reverse the sense of  $\bar{e}_\theta$ . Also, although we selected  $z$  to be the axial direction, it may be convenient in some situation to select a different axis. This is the primary reason for using  $\bar{e}_z$  rather than  $\bar{k}$ . The unit vectors may be described in terms of  $\bar{i}$ ,  $\bar{j}$ ,  $\bar{k}$  components by projecting them onto the  $xy$  plane. Doing so yields

$$\bar{e}_R = (\cos \theta) \bar{i} + (\sin \theta) \bar{j}, \quad \bar{e}_\theta = -(\sin \theta) \bar{i} + (\cos \theta) \bar{j}, \quad \bar{e}_z = \bar{k}. \quad (2.3.5)$$




Figure 2.6. Definition of the unit vectors for cylindrical coordinates.

Figure 2.6 shows the instantaneous position  $\bar{r}$  of a point. Decomposing this vector into its components relative to the cylindrical coordinate unit vectors reveals that

$$\bar{r} = R\bar{e}_R + z\bar{e}_z. \quad (2.3.6)$$

At first glance, this expression seems to be inconsistent with the fact that  $\bar{r}$  depends on  $\theta$ . However, the value of  $\theta$  must be known in order to define the instantaneous orientation of  $\bar{e}_R$ . Differentiation of this expression to find the velocity leads to

$$\bar{v} = \dot{R}\bar{e}_R + R\frac{d\bar{e}_R}{dt} + \dot{z}\bar{e}_z. \quad (2.3.7)$$

Note that the radial unit vector is recognized as being a variable, because  $\bar{e}_R$  depends on  $\theta$ , and  $\theta$  may depend on time. Hence, evaluating the derivative of this unit vector

### 2.3 Curvilinear Coordinates

53

requires the chain rule,

$$\frac{d\bar{e}_R}{dt} = \dot{\theta} \frac{d\bar{e}_R}{d\theta} \quad (2.3.8)$$

We evaluate the preceding derivative by differentiating the first of Eqs. (2.3.5), which gives

$$\frac{d\bar{e}_R}{d\theta} = -(\sin \theta) \bar{i} + (\cos \theta) \bar{j} = \bar{e}_\theta. \quad (2.3.9)$$

We also will require the derivative of  $\bar{e}_\theta$ , which we obtain from the second of Eqs. (2.3.5):

$$\frac{d\bar{e}_\theta}{d\theta} = -(\cos \theta) \bar{i} - (\sin \theta) \bar{j} = -\bar{e}_R \quad (2.3.10)$$

Both derivatives could have been obtained pictorially. Recall that the derivative of a unit vector must be perpendicular to the vector. Figure 2.7(a) depicts the unit vectors at two close positions, and Fig. 2.7(b) places the vectors tail to tail. The angle between  $\bar{e}_R(\theta)$  and  $\bar{e}_R(\theta + \Delta\theta)$ , and between  $\bar{e}_\theta(\theta)$  and  $\bar{e}_\theta(\theta + \Delta\theta)$ , is  $\Delta\theta$ . The length of each unit vector is unity, so when  $\Delta\theta$  is very small, the length of  $\Delta\bar{e}_R$  is approximately  $\Delta\theta$ . The same is true for  $\Delta\bar{e}_\theta$ . In the limit as  $\Delta\theta$  approaches  $d\theta$ , the approximation becomes exact. Furthermore, in this limit  $d\bar{e}_R$  is parallel to  $\bar{e}_\theta(\theta)$ , so that  $d\bar{e}_R = d\theta \bar{e}_\theta$ . In the same limit,  $d\bar{e}_\theta$  is parallel to  $-\bar{e}_R(\theta)$ , which leads to  $d\bar{e}_\theta = -d\theta \bar{e}_R$ . Division of these descriptions of  $d\bar{e}_R$  and  $d\bar{e}_\theta$  by  $d\theta$  leads to Eqs. (2.3.9) and (2.3.10).




Figure 2.7. Differentiation of the radial and transverse unit vectors.

Substitution of Eqs. (2.3.9) and (2.3.8) into Eq. (2.3.7) gives the required expression for velocity:

$$\bar{v} = \dot{R}\bar{e}_R + R\dot{\theta}\bar{e}_\theta + \dot{z}\bar{e}_z. \quad (2.3.11)$$

The radial and axial velocity components have obvious meanings as rates of change of the corresponding distances. The second term tells us that the azimuthal velocity results from changing the azimuthal angle, with the effect growing in proportion to the radial distance. The latter matches our everyday experience, in that we rotate our head slowly when we track a faraway object moving at a high speed.

An expression for acceleration results from differentiating the velocity description. Let us start with the component representation of velocity  $\bar{v} = v_R\bar{e}_R + v_\theta\bar{e}_\theta + v_z\bar{e}_z$ .

We have already obtained  $d\bar{e}_R/dt$ , and the chain rule in conjunction with Eq. (2.3.10) gives  $d\bar{e}_\theta/dt = -\dot{\theta} \bar{e}_R$ , from which we find that

$$\bar{a} = (\dot{v}_R - v_\theta \dot{\theta}) \bar{e}_r + (\dot{v}_\theta + v_R \dot{\theta}) \bar{e}_\theta + \dot{v}_z \bar{e}_z. \quad (2.3.12)$$

This description explicitly describes the fact that acceleration results from variability of the directions in which the velocity components are measured, as well as if the components are not constant. This form is useful when the velocity components are known as functions of time, but the more usual circumstance is that in which the cylindrical coordinates are known. In that case we differentiate Eq. (2.3.11) directly, to obtain

$$\begin{aligned} \bar{a} &= \frac{d}{dt} [\dot{R} \bar{e}_R] + \frac{d}{dt} [R \dot{\theta} \bar{e}_\theta] + \frac{d}{dt} [\dot{z} \bar{e}_z] \\ &= [\ddot{R} \bar{e}_R + \dot{R} \dot{\theta} \bar{e}_\theta] + [\dot{R} \dot{\theta} \bar{e}_\theta + R \ddot{\theta} \bar{e}_\theta - R \dot{\theta}^2 \bar{e}_R] + \ddot{z} \bar{e}_z. \end{aligned} \quad (2.3.13)$$

The brackets in the preceding equation enable us to track which terms originate from the same velocity component. Both  $\ddot{R}$  and  $\ddot{z}$  are recognizable as acceleration rates in the respective directions, whereas  $R\ddot{\theta}$  is an azimuthal acceleration that arises because an unsteady value of  $\dot{\theta}$  will increase the transverse velocity component  $R\dot{\theta}$ . The fifth term,  $-R\dot{\theta}^2 \bar{e}_R$ , results from the changing direction of  $\bar{e}_\theta$ ; it occurs even if the azimuthal velocity  $R\dot{\theta}$  is constant. Although the second and third terms are both  $\dot{R}\dot{\theta} \bar{e}_\theta$ , the brackets indicate that they originate from different velocity components, and therefore represent different effects. The term in the first bracket stems from the fact that, even if the radial speed  $\dot{R}$  were constant, the radial direction is not constant. In contrast, the term in the second bracket is the rate at which the azimuthal speed,  $R\dot{\theta}$ , will change if  $R$  is not constant. Together, the two identical terms constitute the *Coriolis acceleration*, after G. Coriolis (1792–1843) who successfully explained the phenomenon. Grouping like terms leads to the desired acceleration expression.

$$\bar{a} = (\ddot{R} - R\dot{\theta}^2) \bar{e}_R + (R\ddot{\theta} + 2\dot{R}\dot{\theta}) \bar{e}_\theta + \ddot{z} \bar{e}_z. \quad (2.3.14)$$

The scalar form of Newton's Second Law that we obtain by decomposing it into the cylindrical coordinate directions is


$$\begin{aligned} \Sigma F_R &\equiv \Sigma \bar{F} \cdot \bar{e}_R = m (\ddot{R} - R\dot{\theta}^2), \\ \Sigma F_\theta &\equiv \Sigma \bar{F} \cdot \bar{e}_\theta = m (R\ddot{\theta} + 2\dot{R}\dot{\theta}), \\ \Sigma F_z &\equiv \Sigma \bar{F} \cdot \bar{e}_z = m \ddot{z}. \end{aligned} \quad (2.3.15)$$

In general, one can expect cylindrical coordinates to be useful if some aspect of the force system or motion is best described in terms of a direction that perpendicularly intersects a fixed line, or a fixed point in the case of planar motion. It is clear that in situations in which it is desired to determine  $R$  and  $\theta$  as functions of time resulting from application of a known force resultant, the preceding equation constitute nonlinear differential equations in which  $R$  and  $\theta$  are strongly coupled.

## 2.3 Curvilinear Coordinates


55

**EXAMPLE 2.6** An observer at point  $A$  watches automobile  $P$  follow the circular track. The angle between the diametral line to the observer and the radial line to the automobile is a measured function of time,  $\theta(t)$ . Derive expressions for the velocity and acceleration in terms of the radius  $\rho$  of the track and  $\theta$ .



Example 2.6

**SOLUTION** One of the primary purposes of this example, in addition to illustrating the basic use of the formulas, is to emphasize that there is a variety of descriptions that might be useful for motion along a circular path. We use polar coordinates here because the motion is defined by an angle in a plane measured relative to a fixed line. The polar coordinate variables and the associated unit vectors are defined in a sketch, with the origin placed at point  $A$ , where the observer is.



Polar coordinates and unit vectors corresponding to origin  $A$ .

It is known from geometry that triangle  $ABP$  is a right triangle, with side  $AB$  as the hypotenuse. Thus the transverse distance is given by

$$R = 2\rho \cos \theta.$$

This expression may be differentiated with respect to  $t$ , but in doing so we must recognize that  $\theta(t)$  is unspecified, so we cannot assume that  $\dot{\theta}$  is zero. Thus,

$$\dot{R} = (-2\rho \sin \theta) \dot{\theta}, \quad \ddot{R} = (-2\rho \cos \theta) \ddot{\theta}^2 + (-2\rho \sin \theta) \ddot{\theta}.$$


We substitute these expressions into Eqs. (2.3.11) and (2.3.14) to find

$$\vec{v} = -2\rho \dot{\theta} \sin \theta \vec{e}_R + 2\rho \dot{\theta} \cos \theta \vec{e}_\theta,$$

$$\vec{a} = -2\rho (2\dot{\theta}^2 \cos \theta + \ddot{\theta} \sin \theta) \vec{e}_R + 2\rho (\ddot{\theta} \cos \theta - 2\dot{\theta}^2 \sin \theta) \vec{e}_\theta.$$

There is no need to convert these results to  $\bar{i}$  and  $\bar{j}$  components because the sketch of the polar coordinates fully describes the directions of these components.


In closing, it is useful to observe that, if the observer following the automobile were situated at the center of the track, then the polar coordinate unit vectors would be as shown in the second sketch, with  $\bar{e}_\theta$  tangent to the circle in the sense of increasing  $\theta$  and  $\bar{e}_R$  radially outward.



Polar coordinate unit vectors when the center  $A$  is the origin.

In comparison, the tangent direction could be either parallel to, or opposite,  $\bar{e}_\theta$ , depending on how the arc length  $s$  is measured, and  $\bar{e}_n$  would be opposite  $\bar{e}_R$ , toward the center of curvature. Even though these alternative sets of directions are readily related here, the question of whether path variables or polar coordinates is more suitable depends on how movement along the path is defined. We use the former if we have information regarding  $s$  or  $v$ , whereas the latter should be selected if we have knowledge of  $R$  or  $\theta$  or their derivatives as functions of time.

**EXAMPLE 2.7** An airplane climbs at a constant speed  $v$  and constant climb angle  $\beta$ . The airplane is being tracked by a radar station at point  $A$  on the ground. Determine the radial velocity  $\dot{R}$  and the angular velocity  $\dot{\theta}$  as functions of the tracking angle  $\theta$ .



Example 2.7

**SOLUTION** One objective of this example is to emphasize once again that the type of path is not the issue when one decides which kinematical description should be employed. The situation here is very much like the one in the previous example, in that movement along a given path is prescribed in terms of the rotation of a line. We implement a trigonometric approach here, in which the rate variables are obtained from differentiation of geometrical relations. (A simpler solution to this problem may be found in Example 2.11, where the Cartesian and polar coordinate



### 2.3 Curvilinear Coordinates

57

descriptions of velocity and acceleration are compared.) First, we construct the distance  $vt$  the airplane has traveled after passing point  $B$  above the radar station. This forms one side of a triangle whose other sides are  $R$  and  $H$ . Then the law of sines yields

$$\frac{R}{\sin(\pi/2 + \beta)} = \frac{vt}{\sin(\pi/2 - \theta)} = \frac{H}{\sin(\theta - \beta)}.$$

For the purpose of differentiation it is preferable to write these two relations as

$$\begin{aligned} R \sin(\theta - \beta) &= H \sin(\pi/2 + \beta) \equiv H \cos(\beta), \\ vt \sin(\theta - \beta) &= H \sin(\pi/2 - \theta) \equiv H \cos(\theta). \end{aligned} \quad (1)$$

Differentiating each expression leads to

$$\begin{aligned} \dot{R} \sin(\theta - \beta) + R \dot{\theta} \cos(\theta - \beta) &= 0, \\ v \sin(\theta - \beta) + vt \dot{\theta} \cos(\theta - \beta) &= -H \dot{\theta} \sin(\theta) \end{aligned}$$

These are simultaneous equations for  $\dot{\theta}$  and  $\dot{R}$ , whose solutions are

$$\begin{aligned} \dot{\theta} &= -\frac{v \sin(\theta - \beta)}{vt \cos(\theta - \beta) + H \sin(\theta)}, \\ \dot{R} &= \frac{Rv \cos(\theta - \beta)}{vt \cos(\theta - \beta) + H \sin(\theta)}. \end{aligned} \quad (2)$$

The problem statement requested expressions for  $\dot{R}$  and  $\dot{\theta}$  as functions of  $\theta$ , but the preceding equations also contain the variables  $R$  and  $t$ . We therefore solve Eqs. (1) for  $R$  and  $vt$ ,

$$\begin{aligned} R &= \frac{H \cos(\beta)}{\sin(\theta - \beta)}, \\ vt &= \frac{H \cos(\theta)}{\sin(\theta - \beta)}, \end{aligned}$$

and then substitute those results into Eqs. (2), which leads to

$$\begin{aligned} \dot{\theta} &= -\frac{v \sin(\theta - \beta)}{H \cos(\theta) \cot(\theta - \beta) + \sin(\theta)}, \\ \dot{R} &= v \frac{\cos(\beta) \cot(\theta - \beta)}{\cos(\theta) \cot(\theta - \beta) + \sin(\theta)}. \end{aligned} \quad (3)$$

We may simplify these expressions by multiplying the numerator and denominator of each by  $\sin(\theta - \beta)$ , and then using the trigonometric identity that  $\cos(\theta) \cos(\theta - \beta) + \sin(\theta) \sin(\theta - \beta) \equiv \cos[\theta - (\theta - \beta)] \equiv \cos(\beta)$ , so that

$$\begin{aligned} \dot{\theta} &= -\frac{v \sin(\theta - \beta)^2}{H \cos(\beta)}, \\ \dot{R} &= v \cos(\theta - \beta). \end{aligned} \quad \triangleleft$$

Although not requested, it is useful to contemplate following the present approach to determine  $\dot{R}$  and  $\dot{\theta}$ . Clearly, differentiating the results for  $\dot{R}$  and  $\dot{\theta}$  would be tedious. The remarkable aspect of the approach described in Section 2.4 is that it will not require explicit differentiation of any term.

### 2.3.2 Spherical Coordinates

Spherical coordinates locate a point in terms of one length parameter and two angles. The *radial distance*  $r$ , which is the length of the position vector from a fixed point to the point of interest, is the hallmark of the formulation. The fixed point is taken to be the origin of an  $xyz$  coordinate system, as depicted in Fig. 2.8. In an application the  $z$  axis would be selected to coincide with a relevant fixed direction. The  $z$  axis and the moving point form the *meridional plane*. The instantaneous orientation of that plane is measured by the azimuthal angle  $\theta$ , just as it was in cylindrical coordinates. The second angle locating the point's position is the polar angle  $\phi$ . The triad  $(r, \phi, \theta)$  constitutes *spherical coordinates*. To avoid ambiguity, we limit the azimuthal angle to  $-\pi < \theta \leq \pi$  and the polar angle to  $0 \leq \phi \leq \pi$ . Note that motion in the  $xy$  plane corresponds to  $\phi = \pi/2$ , in which case  $(r, \theta)$  constitute polar coordinates. Polar coordinates are also formed by  $r$  and  $\phi$  for motion in any meridional plane defined by constant  $\theta$ .

A modified version of spherical coordinates occurs in geography. Within the spherical Earth approximation, the radial distance from the center of the Earth to a point on the surface is the radius  $R_e \approx 6370$  m. The fixed reference direction is the north-south polar axis. Position on the surface is specified by giving the longitude angle, which is the rotation angle of the radial line about the polar axis measured from the prime meridian at the Royal Observatory in Greenwich, England. The one difference is that, rather than measuring the polar angle from the North Pole, we use the latitude, which is measured from the equatorial plane. The latitude is the complement of the polar angle.




Figure 2.8. Definition of the spherical coordinates.

### 2.3 Curvilinear Coordinates

59

The transformation from  $(r, \phi, \theta)$  to  $(x, y, z)$  is found by dropping perpendiculars from the point onto the  $xy$  plane and onto the  $z$  axis. The distances from the origin to the projection points are  $r \sin \phi$  and  $r \cos \phi$ , respectively, from which it follows that

$$x = r \sin \phi \cos \theta, \quad y = r \sin \phi \sin \theta, \quad z = r \cos \phi. \quad (2.3.16)$$

The spherical coordinate mesh consists of radial lines, formed by allowing  $r$  to change with  $\phi$  and  $\theta$  constant, circles of radius  $r$  lying in a meridional, and circles of radius  $r \sin \phi$  parallel to the  $xy$  plane formed when  $\theta$  is varied with  $r$  and  $\phi$  constant. Different value combinations of the constant coordinate pairs associated with each type of curve produces the families of curves. Curves belonging to different families intersect perpendicularly.

The spherical coordinate unit vectors are formed by holding two of the three coordinates constant while the value of the third is increased. The unit vectors are tangent to the respective coordinate curves, as shown in Fig. 2.9. They are mutually orthogonal, with their sense being such that

$$\bar{e}_r \times \bar{e}_\phi = \bar{e}_\theta. \quad (2.3.17)$$

Note that the azimuthal angle is defined here to be positive according to the right-hand rule relative to the axial direction, that is, counterclockwise looking down the  $z$  axis. However, in some circumstances it might be convenient to define  $\theta$  in the opposite sense. In that case the sign of the preceding cross product would be reversed.




Figure 2.9. Unit vectors for spherical coordinates.

Projecting their unit length onto the respective coordinate axes shows the Cartesian components of the unit vectors to be

$$\begin{aligned} \bar{e}_r &= (\sin \phi \cos \theta) \bar{i} + (\sin \phi \sin \theta) \bar{j} + (\cos \phi) \bar{k}, \\ \bar{e}_\phi &= (\cos \phi \cos \theta) \bar{i} + (\cos \phi \sin \theta) \bar{j} - (\sin \phi) \bar{k}, \\ \bar{e}_\theta &= -(\sin \theta) \bar{i} + (\cos \theta) \bar{j}. \end{aligned} \quad (2.3.18)$$

Verification of this representation may be found in the fact that it satisfies Eq. (2.3.17). We see that the spherical coordinate unit vectors depend on both  $\phi$  and  $\theta$ . Derivation of formulas for velocity and acceleration from the position will require chain rule differentiation with respect to time, which in turn will require knowledge of the derivatives of

the unit vectors with respect to both spherical angles. Differentiating Eqs. (2.3.18) leads to

$$\begin{aligned}\frac{\partial \bar{e}_r}{\partial \phi} &= (\cos \phi \cos \theta) \bar{i} + (\cos \phi \sin \theta) \bar{j} - (\sin \phi) \bar{k}, \\ \frac{\partial \bar{e}_\phi}{\partial \phi} &= -(\sin \phi \cos \theta) \bar{i} - (\sin \phi \sin \theta) \bar{j} - (\cos \phi) \bar{k}, \\ \frac{\partial \bar{e}_\theta}{\partial \phi} &= 0, \\ \frac{\partial \bar{e}_r}{\partial \theta} &= -(\sin \phi \sin \theta) \bar{i} + (\sin \phi \cos \theta) \bar{j}, \\ \frac{\partial \bar{e}_\phi}{\partial \theta} &= -(\cos \phi \sin \theta) \bar{i} + (\cos \phi \cos \theta) \bar{j}, \\ \frac{\partial \bar{e}_\theta}{\partial \theta} &= -(\cos \theta) \bar{i} - (\sin \theta) \bar{j}.\end{aligned}\tag{2.3.19}$$

We wish to use these derivatives to obtain formulas for velocity and acceleration that depend on only the spherical coordinate variables. A comparison of the derivatives just listed with Eqs. (2.3.18) shows that

$$\begin{aligned}\frac{\partial \bar{e}_r}{\partial \phi} &= \bar{e}_\phi, \quad \frac{\partial \bar{e}_\phi}{\partial \phi} = -\bar{e}_r, \quad \frac{\partial \bar{e}_\theta}{\partial \phi} = 0, \\ \frac{\partial \bar{e}_r}{\partial \theta} &= (\sin \phi) \bar{e}_\theta, \quad \frac{\partial \bar{e}_\phi}{\partial \theta} = (\cos \phi) \bar{e}_\theta, \quad \frac{\partial \bar{e}_\theta}{\partial \theta} = -(\sin \phi) \bar{e}_r - (\cos \phi) \bar{e}_\phi.\end{aligned}\tag{2.3.20}$$

One could alternatively derive these derivatives by constructing diagrams resembling Fig. 2.7, but doing so would be a more complicated process requiring several views.

The position vector in spherical coordinates is aligned with the radial direction, so that

$$\bar{r} = r \bar{e}_r.\tag{2.3.21}$$

The dependence of  $\bar{r}$  on  $\phi$  and  $\theta$  is implicit, because the values of these coordinates must be known in order to locate  $\bar{e}_r$ . The chain rule for differentiation gives

$$\begin{aligned}\bar{v} &= \frac{d\bar{r}}{dt} = \dot{r} \bar{e}_r + r \frac{d\bar{e}_r}{dt} \\ &= \dot{r} \bar{e}_r + r \left( \dot{\phi} \frac{\partial \bar{e}_r}{\partial \phi} + \dot{\theta} \frac{\partial \bar{e}_r}{\partial \theta} \right).\end{aligned}\tag{2.3.22}$$

In view of Eqs. (2.3.20) this reduces to

$$\bar{v} = \dot{r} \bar{e}_r + r \dot{\phi} \bar{e}_\phi + r \dot{\theta} \sin(\phi) \bar{e}_\theta.\tag{2.3.23}$$

Each of these terms is readily explained as a superposition. If  $\phi$  and  $\theta$  were constant, there would be only a radial velocity component as a result of the changing radial distance. If  $r$  and  $\theta$  were constant, a point would follow a meridional circle of radius  $r$ . The rotation rate of the radial line is  $\dot{\phi}$ , giving a speed of  $r\dot{\phi}$ , and the unit vector tangent to

### 2.3 Curvilinear Coordinates

61

this circle is  $\bar{e}_\phi$ . The third component can be recognized by holding  $r$  and  $\phi$  constant, in which case the point follows an azimuthal circle of radius  $r \sin(\phi)$ . The transverse line rotates about the  $z$  axis at  $\dot{\theta}$ , giving a speed  $r\dot{\theta} \sin(\phi)$ , and  $\bar{e}_\theta$  is tangent to this circle.

The derivation of the formula for acceleration follows the same approach. For this, the time derivatives need to recognize that the unit vectors depend on  $\phi$  and  $\theta$ . As was done for cylindrical coordinates, brackets are used to track which acceleration terms originate from the same velocity component. Thus,

$$\begin{aligned}\bar{a} &= \frac{d}{dt} [\dot{r} \bar{e}_r] + \frac{d}{dt} [r \dot{\phi} \bar{e}_\phi] + \frac{d}{dt} [r \dot{\theta} \sin(\phi) \bar{e}_\theta] \\ &= \left[ \ddot{r} \bar{e}_r + \dot{r} \frac{d\bar{e}_r}{dt} \right] + \left[ \dot{r} \dot{\phi} \bar{e}_\phi + r \ddot{\phi} \bar{e}_\phi + r \dot{\phi} \frac{d\bar{e}_\phi}{dt} \right] \\ &\quad + \left[ \dot{r} \dot{\theta} \sin(\phi) \bar{e}_\theta + r \ddot{\theta} \sin(\phi) \bar{e}_\theta + r \dot{\theta} \dot{\phi} \cos(\phi) \bar{e}_\theta + r \dot{\theta} \sin(\phi) \frac{d\bar{e}_\theta}{dt} \right] \\ &= \left[ \ddot{r} \bar{e}_r + \dot{r} \left( \dot{\phi} \frac{\partial \bar{e}_r}{\partial \phi} + \dot{\theta} \frac{\partial \bar{e}_r}{\partial \theta} \right) \right] + \left[ \dot{r} \dot{\phi} \bar{e}_\phi + r \ddot{\phi} \bar{e}_\phi + r \dot{\phi} \bar{e}_r \left( \dot{\phi} \frac{\partial \bar{e}_\phi}{\partial \phi} + \dot{\theta} \frac{\partial \bar{e}_\phi}{\partial \theta} \right) \right] \\ &\quad + \left[ \dot{r} \dot{\theta} (\sin(\phi) \bar{e}_\theta + r \ddot{\theta} \sin(\phi) \bar{e}_\theta + r \dot{\theta} \dot{\phi} \cos(\phi) \bar{e}_\theta + r \dot{\theta} \sin(\phi) \left( \dot{\phi} \frac{\partial \bar{e}_\theta}{\partial \phi} + \dot{\theta} \frac{\partial \bar{e}_\theta}{\partial \theta} \right) \right].\end{aligned}\tag{2.3.24}$$

Substitution of Eqs. (2.3.20) leads to a profusion of terms:

$$\begin{aligned}\bar{a} &= [\ddot{r} \bar{e}_r + \dot{r} \dot{\phi} \bar{e}_\phi + \dot{r} \dot{\theta} \sin(\phi) \bar{e}_\theta] + [\dot{r} \dot{\phi} \bar{e}_\phi + r \ddot{\phi} \bar{e}_\phi - r \dot{\phi}^2 \bar{e}_r + r \dot{\phi} \dot{\theta} \cos(\phi) \bar{e}_\theta] \\ &\quad + [\dot{r} \dot{\theta} \sin(\phi) \bar{e}_\theta + r \ddot{\theta} \sin(\phi) \bar{e}_\theta + r \dot{\theta} \dot{\phi} \cos(\phi) \bar{e}_\theta \\ &\quad - r \dot{\theta}^2 \sin(\phi)^2 \bar{e}_r - r \dot{\theta}^2 \sin(\phi) \cos(\phi) \bar{e}_\phi].\end{aligned}\tag{2.3.25}$$

Although some terms are repeated, they originate from different effects. In general, one of the repeated terms results from the increase in a velocity component when one of the polar coordinates is increased, whereas the other results because acceleration occurs when the direction of a velocity component changes, even if the value of the component is constant. For example, the polar velocity is  $r\dot{\phi} \bar{e}_\phi$ . Changing the radial distance increases this velocity component, leading to an acceleration term  $\dot{r} \dot{\phi} \bar{e}_\phi$ . At the same time, the radial velocity is  $\dot{r} \bar{e}_r$ . Changing  $\phi$  moves the tip of  $\bar{e}_r$  in the direction of  $\bar{e}_\phi$ , so changing the direction of this velocity component also produces an acceleration term  $\dot{r} \dot{\phi} \bar{e}_\phi$ . Like cylindrical coordinates, the name given to this pair of equal acceleration terms, which lead to a factor of two in the formulas, is the Coriolis acceleration.

Other acceleration terms are either of two types. Some contain second derivatives of a spherical coordinate, such as  $r\ddot{\phi}$ . These arise when a rate variable increases. The others contain a product of  $r$  and the square of an angular rate. These correspond to centripetal acceleration effects. For example, moving along the polar circle of radius  $r$  at polar rate  $\dot{\phi}$  produces a centripetal acceleration  $r\dot{\phi}^2$ . Such an acceleration is directed inward toward the center of the circle, which is the negative radial direction. The latter two effects can be recognized individually and then superposed.

Collecting like components yields the formula we shall employ:

$$\begin{aligned} \bar{a} = & \left[ \ddot{r} - r\dot{\phi}^2 - r\dot{\theta}^2 \sin^2(\phi) \right] \bar{e}_r + \left[ r\ddot{\phi} + 2\dot{r}\dot{\phi} - r\dot{\theta}^2 \sin(\phi) \cos(\phi) \right] \bar{e}_\phi \\ & + \left[ r\ddot{\theta} \sin(\phi) + 2\dot{r}\dot{\theta} \sin(\phi) + 2r\dot{\phi}\dot{\theta} \cos(\phi) \right] \bar{e}_\theta. \end{aligned} \quad (2.3.26)$$

We obtain an equivalent form, which is useful when the velocity components are known, by differentiating  $\bar{v} = v_r \bar{e}_r + v_\phi \bar{e}_\phi + v_\theta \bar{e}_\theta$ , with Eqs. (2.3.20) used to describe the derivatives of the unit vectors. The result is


$$\begin{aligned} \bar{a} = & \dot{v}_r \bar{e}_r + v_r \left( \dot{\phi} \frac{\partial \bar{e}_r}{\partial \phi} + \dot{\theta} \frac{\partial \bar{e}_r}{\partial \theta} \right) + \dot{v}_\phi \bar{e}_\phi + v_\phi \left( \dot{\phi} \frac{\partial \bar{e}_\phi}{\partial \phi} + \dot{\theta} \frac{\partial \bar{e}_\phi}{\partial \theta} \right) \\ & + \dot{v}_\theta \bar{e}_\theta + v_\theta \left( \dot{\phi} \frac{\partial \bar{e}_\theta}{\partial \phi} + \dot{\theta} \frac{\partial \bar{e}_\theta}{\partial \theta} \right) \\ = & \left[ \dot{v}_r - v_\phi \dot{\phi} - v_\theta \dot{\theta} \sin(\phi) \right] \bar{e}_r + \left[ \dot{v}_\phi + v_r \dot{\phi} - v_\theta \dot{\theta} \cos(\phi) \right] \bar{e}_\phi \\ & + \left[ \dot{v}_\theta + v_r \dot{\theta} \sin(\phi) + v_\phi \dot{\theta} \cos(\phi) \right] \bar{e}_\theta. \end{aligned} \quad (2.3.27)$$

One criterion for deciding to use spherical coordinates is that some aspect of the motion or force system is best described in terms of a line from the moving point to a designated fixed point. Scalar equations of motion featuring the spherical coordinates  $r$ ,  $\phi$ , and  $\theta$  are obtained from Newton's Second Law when the force resultant is represented in terms of the spherical coordinate directions, specifically

$$\begin{aligned} \Sigma F_r \equiv \Sigma \bar{F} \cdot \bar{e}_r &= m \left[ \ddot{r} - r\dot{\phi}^2 - r\dot{\theta}^2 \sin^2(\phi) \right], \\ \Sigma F_\phi \equiv \Sigma \bar{F} \cdot \bar{e}_\phi &= m \left[ r\ddot{\phi} + 2\dot{r}\dot{\phi} - r\dot{\theta}^2 \sin(\phi) \cos(\phi) \right], \\ \Sigma F_\theta \equiv \Sigma \bar{F} \cdot \bar{e}_\theta &= m \left[ r\ddot{\theta} \sin(\phi) + 2\dot{r}\dot{\theta} \sin(\phi) + 2r\dot{\phi}\dot{\theta} \cos(\phi) \right]. \end{aligned} \quad (2.3.28)$$

When the force resultant is known, these are nonlinear differential equations for the spherical coordinates in which all variables are strongly coupled.

**EXAMPLE 2.8** The cable suspending a 400-g sphere is pulled in at a constant rate of 6 m/s. At the instant when the cable is 3 m long the angle of inclination is  $\phi = 30^\circ$ ,  $\Omega = 4$  rad/s, and  $\dot{\phi} = 5$  rad/s. Determine the values of  $\ddot{\phi}$  and  $\ddot{\Omega}$ , and the tensile force in the cable at this instant.




Example 2.8

### 2.3 Curvilinear Coordinates

63

**SOLUTION** This example illustrates the usage of spherical coordinates to formulate Newton's Second Law. It also will make it apparent that drawing a good free-body diagram is a vital step when forces are to be analyzed. In this situation the cable length is measured from a fixed point to the sphere, and the other position parameters are the angle from the fixed vertical axis and the rotation rate about that axis. The former is the polar angle  $\phi$ , and the latter corresponds to the azimuthal rotation rate  $\Omega = \dot{\theta}$ . These are spherical coordinates centered at the top of the post, with all motion parameters other than  $\dot{\phi}$  and  $\dot{\theta}$  given. Because it is required to evaluate a force acting on the particle, we draw a free-body diagram that also depicts the unit vectors of the spherical coordinate system we shall use.



Free-body diagram and spherical coordinates for the suspended sphere.

Each unit vector is defined to be positive in the sense of increasing values of the corresponding coordinate. Note that, because  $\dot{\theta}$  has been defined to be  $\Omega$ , we have  $\bar{e}_r \times \bar{e}_\phi = -\bar{e}_\theta$ , which is opposite the sign in Eq. (2.3.17). Also, the actual value of  $\theta$  is irrelevant because there is no special position in regard to rotation about the vertical axis.

Because the cable is being pulled in at a constant rate, the instantaneous values are  $r = 3$  m,  $\dot{r} = -6$  m/s, and  $\ddot{r} = 0$ . Substitution of these values and  $\phi = 30^\circ$ ,  $\dot{\phi} = 5$  rad/s., and  $\dot{\theta} = 4$  rad/s into Eq. (2.3.26) gives

$$\bar{a} = -87\bar{e}_r + (3\ddot{\phi} - 80.78)\bar{e}_\phi + (1.5\ddot{\theta} + 79.92)\bar{e}_\theta \text{ m/s}^2.$$

Newton's Second Law relates forces and acceleration variables, so we expect that it will yield the parameters we seek. We refer to the free-body diagram in order to describe the force components. The cable tension  $F$  pulls the sphere in the negative radial direction, and the weight,  $0.4g$  N, acts parallel to the polar axis, so the spherical coordinate equations of motion, Eqs. (2.3.28), require that

$$\Sigma \bar{F} \cdot \bar{e}_r = -F + 0.4(9.807) \cos(\phi) = ma_r = 0.4(-87),$$

$$\Sigma \bar{F} \cdot \bar{e}_\phi = -0.4(9.807) \sin(\phi) = ma_\phi = 0.4(3\ddot{\phi} - 80.78),$$

$$\Sigma \bar{F} \cdot \bar{e}_\theta = 0 = ma_\theta = 0.4(1.5\ddot{\theta} + 79.92).$$

The solution of these equations is

$$F = 38.72 \text{ N},$$

$$\ddot{\phi} = 25.29, \quad \ddot{\theta} = -53.28 \text{ rad/s}^2.$$

◁

### 2.3.3 Arbitrary Curvilinear Coordinates

Cylindrical and spherical coordinates are adequate for the majority of situations one might encounter. However, generalizing the formulation to handle any set of orthogonal curvilinear coordinates will vastly expand our capability. Doing so is also quite useful for topics in many related areas, including stress analysis, wave propagation, fluid mechanics, and acoustics. In the following subsection we consider a triad of curvilinear coordinates  $(\alpha, \beta, \gamma)$  that are related to the Cartesian coordinates  $(x, y, z)$  by an arbitrary transformation in the form of Eqs. (2.3.1).

#### Coordinates and Unit Vectors

It is difficult to depict a three-dimensional situation, so Fig. 2.10 shows a two-dimensional grid associated with various values of the curvilinear coordinates  $\alpha$  and  $\beta$ , with the third coordinate  $\gamma$  held constant. Each curve corresponds to constant values of two of the coordinates. We use the coordinate that varies to name the curve. For example, points on a specific  $\alpha$  curve correspond to a range of  $\alpha$  values with  $\beta$  and  $\gamma$  fixed. Neighboring curves for each family in the figure are separated by values of  $\alpha$  or  $\beta$  that differ by an infinitesimal value. We shall consider only coordinate systems for which the curves of different families intersect orthogonally. The distance between intersection points on the grid is not the same as the value of the increment in that coordinate. The ratio of the differential arc length along a coordinate curve between intersections, and the increment in the coordinate corresponding to the intersections is the *stretch ratio* for that coordinate, denoted  $h_\lambda$ , with  $\lambda = \alpha, \beta$ , or  $\gamma$ . The arc length along a  $\lambda$  coordinate curve is denoted as  $s_\lambda$ , so

$$ds_\lambda = h_\lambda d\lambda, \quad \lambda = \alpha, \beta, \text{ or } \gamma. \quad (2.3.29)$$

The relationship between the curvilinear coordinate transformation, Eqs. (2.3.1), and the stretch ratios will be established shortly.

Moving along any of the coordinate curves is very much like the situation in path variables. At any point, there are three unit vectors  $\bar{e}_\lambda$  tangent to the  $\alpha$ ,  $\beta$ , and  $\gamma$  curves passing through that point. Recall that the tangent direction is defined by  $\bar{e}_t = d\bar{r}/ds$ . We use Eq. (2.3.29) to describe the differential arc length. Incrementing one coordinate




Figure 2.10. Two-dimensional curvilinear coordinate mesh.



## 2.3 Curvilinear Coordinates

65

with the other two fixed is a process of partial differentiation, so the unit vectors may be obtained from

$$\bar{e}_\lambda = \frac{d\bar{r}}{ds_\lambda} = \frac{1}{h_\lambda} \frac{\partial \bar{r}}{\partial \lambda}, \quad \lambda = \alpha, \beta, \text{ or } \gamma. \quad (2.3.30)$$

It is conventional to employ a right-handed coordinate system in order to avoid sign errors in the evaluation of cross products. Consistency with this convention is obtained by ordering  $(\alpha, \beta, \gamma)$  such that

$$\bar{e}_\alpha \times \bar{e}_\beta = \bar{e}_\gamma. \quad (2.3.31)$$

Equations (2.3.1) define the components of  $\bar{r}$  with respect to  $xyz$  in terms of the curvilinear coordinates,

$$\bar{r} = x(\alpha, \beta, \gamma) \bar{i} + y(\alpha, \beta, \gamma) \bar{j} + z(\alpha, \beta, \gamma) \bar{k}. \quad (2.3.32)$$

Differentiation of this expression with respect to a specific curvilinear coordinate  $\lambda$  is straightforward because  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  are constant, so that

$$\frac{\partial \bar{r}}{\partial \lambda} = \left( \frac{\partial}{\partial \lambda} x(\alpha, \beta, \gamma) \right) \bar{i} + \left( \frac{\partial}{\partial \lambda} y(\alpha, \beta, \gamma) \right) \bar{j} + \left( \frac{\partial}{\partial \lambda} z(\alpha, \beta, \gamma) \right) \bar{k}. \quad (2.3.33)$$

Enforcement of the requirement that the unit vector defined by Eq. (2.3.30) actually have unit magnitude then yields an expression for the stretch ratio  $h_\lambda$ :

$$h_\lambda = \left| \frac{\partial \bar{r}}{\partial \lambda} \right| = \left[ \left( \frac{\partial}{\partial \lambda} x(\alpha, \beta, \gamma) \right)^2 + \left( \frac{\partial}{\partial \lambda} y(\alpha, \beta, \gamma) \right)^2 + \left( \frac{\partial}{\partial \lambda} z(\alpha, \beta, \gamma) \right)^2 \right]^{1/2}. \quad (2.3.34)$$

Substitution of this expression and Eq. (2.3.33) into Eq. (2.3.30) gives the  $xyz$  components of each of the curvilinear unit vectors in terms of the curvilinear coordinate values. In other words, the result has the general form

$$\bar{e}_\lambda = e_{\lambda\alpha}(\alpha, \beta, \gamma) \bar{i} + e_{\lambda\beta}(\alpha, \beta, \gamma) \bar{j} + e_{\lambda\gamma}(\alpha, \beta, \gamma) \bar{k}. \quad (2.3.35)$$

The derivation of the acceleration equation will require differentiation of the unit vectors. There are two ways in which we may proceed. The first is an extension of the manner in which we treated spherical coordinates. It is a direct differentiation procedure. Let  $\mu$  denote any of the curvilinear coordinates. Differentiation of Eq. (2.3.35) with respect to  $\mu$  gives

$$\begin{aligned} \frac{\partial \bar{e}_\lambda}{\partial \mu} &= \left[ \frac{\partial}{\partial \mu} e_{\lambda\alpha}(\alpha, \beta, \gamma) \right] \bar{i} + \left[ \frac{\partial}{\partial \mu} e_{\lambda\beta}(\alpha, \beta, \gamma) \right] \bar{j} \\ &\quad + \left[ \frac{\partial}{\partial \mu} e_{\lambda\gamma}(\alpha, \beta, \gamma) \right] \bar{k}, \quad \lambda, \mu = \alpha, \beta, \gamma. \end{aligned} \quad (2.3.36)$$

This expression describes the derivative in terms of  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  components, but we seek kinematical formulas that describe velocity and acceleration relative to the curvilinear

coordinate directions. In other words, we wish to represent the preceding derivative in the form of

$$\frac{\partial \bar{e}_\lambda}{\partial \mu} = \Gamma_{\lambda\mu\alpha} \bar{e}_\alpha + \Gamma_{\lambda\mu\beta} \bar{e}_\beta + \Gamma_{\lambda\mu\gamma} \bar{e}_\gamma. \quad (2.3.37)$$

The components in this expression may be found from a dot product with a specific curvilinear unit vector, from which we find that

$$\Gamma_{\lambda\mu\nu} = \frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_\nu, \quad \lambda, \mu, \nu = \alpha, \beta, \text{ or } \gamma. \quad (2.3.38)$$

Note that the result of implementing the preceding equation by use of Eqs. (2.3.35) and (2.3.36) will be expressions for the  $\Gamma_{\lambda\mu\nu}$  coefficients in terms of the curvilinear coordinate values. These coefficients are called *Christoffel symbols*. They play a prominent role in tensor analysis, which is a key mathematical tool for fields as diverse as solid mechanics and general relativity.

The shortcoming of Eq. (2.3.38) is that it does not shed any light on the fundamental nature of curvilinear coordinates in terms of recognizable parameters. Such information is obtained from the second derivation, which yields expressions in terms of stretch ratios. Although the derivation that follows is more circuitous, the result usually will be more efficient to evaluate, as we will see in an example.

We begin by observing that differentiation of a specified unit vector  $\bar{e}_\lambda$  leads to different cases depending on whether  $\mu$  and/or  $\nu$  in Eq. (2.3.38) are the same as  $\lambda$ . All cases in which the unit vectors  $\bar{e}_\lambda$  and  $\bar{e}_\nu$  are the same are covered by

$$\bar{e}_\lambda \cdot \bar{e}_\lambda = 1 \implies \frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_\lambda = \Gamma_{\lambda\mu\lambda} = 0. \quad (2.3.39)$$

Cases not covered by Eq. (2.3.39) correspond to  $\nu \neq \lambda$ , that is, the component of the derivative of a unit vector in the direction of a different unit vector. We may evaluate these with the aid of a sequence of identities. It follows from the orthogonality of the unit vectors that

$$\bar{e}_\lambda \cdot \bar{e}_\nu = 0 \implies \frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_\nu = \Gamma_{\lambda\mu\nu} = -\frac{\partial \bar{e}_\nu}{\partial \mu} \cdot \bar{e}_\lambda = -\Gamma_{\nu\mu\lambda}, \quad \nu \neq \lambda. \quad (2.3.40)$$

The following relation originates from Eq. (2.3.30):

$$\frac{\partial}{\partial \mu} (h_\lambda \bar{e}_\lambda) = \frac{\partial}{\partial \lambda} (h_\mu \bar{e}_\mu). \quad (2.3.41)$$

Carrying out the derivatives leads to

$$\frac{\partial h_\lambda}{\partial \mu} \bar{e}_\lambda + h_\lambda \frac{\partial \bar{e}_\lambda}{\partial \mu} = \frac{\partial h_\mu}{\partial \lambda} \bar{e}_\mu + h_\mu \frac{\partial \bar{e}_\mu}{\partial \lambda}. \quad (2.3.42)$$

We may now consider the various  $\Gamma_{\lambda\mu\nu}$  when  $\nu \neq \lambda$ . Because each of the symbols represents one of three possible coordinates, the only combinations fitting the restriction that  $\nu \neq \lambda$  are  $\mu = \nu \neq \lambda : \Gamma_{\lambda\mu\mu}$ ,  $\mu = \lambda \neq \nu : \Gamma_{\lambda\lambda\nu}$ , and  $\mu \neq \nu \neq \lambda$ . We begin by

### 2.3 Curvilinear Coordinates

67

considering the first case. Such terms are obtained from the dot product of Eq. (2.3.42) with  $\bar{e}_\mu$ . Because  $\bar{e}_\mu$  and  $\bar{e}_\lambda$  are different, it follows that

$$h_\lambda \frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_\mu = \frac{\partial h_\mu}{\partial \lambda} + h_\mu \frac{\partial \bar{e}_\mu}{\partial \lambda} \cdot \bar{e}_\mu. \quad (2.3.43)$$

We use Eq. (2.3.39) to simplify the preceding equation, with the result that

$$\frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_\mu = \Gamma_{\lambda\mu\mu} = \frac{1}{h_\lambda} \frac{\partial h_\mu}{\partial \lambda}, \quad \mu \neq \lambda. \quad (2.3.44)$$

We obtain an expression for  $\Gamma_{\lambda\lambda v} = (\partial \bar{e}_\lambda / \partial \lambda) \cdot \bar{e}_v$  when  $v \neq \lambda$  by applying Eq. (2.3.40), and then using Eq. (2.3.44) with  $\lambda$  changed to  $v$  and  $\mu$  changed to  $\lambda$ . This gives

$$\Gamma_{\lambda\lambda v} = -\frac{1}{h_v} \frac{\partial h_\lambda}{\partial v} = -\Gamma_{v\lambda\lambda}, \quad \lambda \neq v. \quad (2.3.45)$$

The only remaining case is that for which  $\lambda$ ,  $\mu$ , and  $v$  differ from each other. The dot product of Eq. (2.3.42) with  $\bar{e}_v$  in this case yields

$$\frac{1}{h_\mu} \frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_v = \frac{1}{h_\lambda} \frac{\partial \bar{e}_\mu}{\partial \lambda} \cdot \bar{e}_v, \quad \lambda, \mu, v \text{ distinct}. \quad (2.3.46)$$

The next steps involve an alternative application of permutations of the properties in Eqs. (2.3.40) and (2.3.46), with the labels interchanged appropriately, to the *right-hand side* of Eq. (2.3.46). This gives

$$\begin{aligned} \frac{1}{h_\mu} \frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_v &= \frac{1}{h_\lambda} \left( -\frac{\partial \bar{e}_v}{\partial \lambda} \cdot \bar{e}_\mu \right) = -\frac{1}{h_v} \frac{\partial \bar{e}_\lambda}{\partial v} \cdot \bar{e}_\mu \\ &= \frac{1}{h_v} \left( \frac{\partial \bar{e}_\mu}{\partial v} \cdot \bar{e}_\lambda \right) = \frac{1}{h_\mu} \frac{\partial \bar{e}_v}{\partial \mu} \cdot \bar{e}_\lambda \\ &= -\frac{1}{h_\mu} \frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_v. \end{aligned} \quad (2.3.47)$$

The foregoing is a contradiction unless both terms vanish, so that

$$\frac{\partial \bar{e}_\lambda}{\partial \mu} \cdot \bar{e}_v = \Gamma_{\lambda\mu v} = 0, \quad \lambda, \mu, v \text{ distinct}. \quad (2.3.48)$$

Equations (2.3.39), (2.3.44), and (2.3.48) are the properties we seek. They describe the Christoffel symbols in terms of the stretch ratios and their derivatives. There are nine combinations of  $\lambda$  and  $\mu$  values, whose individual components are evaluated by selecting the appropriate case from the identities. Only the results for  $\lambda = \alpha$  are listed. The others follow by permutation of the symbols.

$$\begin{aligned} \frac{\partial \bar{e}_\alpha}{\partial \alpha} &= -\frac{1}{h_\beta} \frac{\partial h_\alpha}{\partial \beta} \bar{e}_\beta - \frac{1}{h_\gamma} \frac{\partial h_\alpha}{\partial \gamma} \bar{e}_\gamma, \\ \frac{\partial \bar{e}_\alpha}{\partial \beta} &= \frac{1}{h_\alpha} \frac{\partial h_\beta}{\partial \alpha} \bar{e}_\beta, \quad \frac{\partial \bar{e}_\alpha}{\partial \gamma} = \frac{1}{h_\alpha} \frac{\partial h_\gamma}{\partial \alpha} \bar{e}_\gamma. \end{aligned} \quad (2.3.49)$$

**EXAMPLE 2.9** The two-dimensional hyperbolic–elliptic coordinate system is defined by

$$x = a \cosh(\alpha) \sin(\beta), \quad y = a \sinh(\alpha) \cos(\beta),$$

where  $a$  is a constant. Evaluate the unit vectors of this system in terms of components relative to the  $x$  and  $y$  axes, then describe the derivatives of the unit vectors.

**SOLUTION** This example illustrates the application of the basic curvilinear formulas to a coordinate system that is useful for some problems in acoustics, fluid mechanics, and electrodynamics. The name of this set of coordinates stems from the fact that lines of constant  $\alpha$  are ellipses,

$$\frac{x^2}{a^2 \cosh(\alpha)^2} + \frac{y^2}{a^2 \sinh(\alpha)^2} = 1,$$

where  $2a \cosh(\alpha)$  and  $2a \sinh(\alpha)$  are the lengths of the major and minor diameters. Also, lines of constant  $\beta$  are hyperbolas,

$$\frac{x^2}{a^2 \sin(\beta)^2} - \frac{y^2}{a^2 \cos(\beta)^2} = 1,$$

where  $x = \pm y \tan(\beta)$  are the asymptotes and  $x = \pm a \sin(\beta)$  are the intercepts on the  $x$  axis.

To evaluate the stretch ratios and unit vectors we need the partial derivatives of the position vectors:

$$\begin{aligned} \frac{\partial \bar{r}}{\partial \alpha} &= \frac{\partial x}{\partial \alpha} \bar{i} + \frac{\partial y}{\partial \alpha} \bar{j} = a \sinh(\alpha) \sin(\beta) \bar{i} + a \cosh(\alpha) \cos(\beta) \bar{j}, \\ \frac{\partial \bar{r}}{\partial \beta} &= \frac{\partial x}{\partial \beta} \bar{i} + \frac{\partial y}{\partial \beta} \bar{j} = a \cosh(\alpha) \cos(\beta) \bar{i} - a \sinh(\alpha) \sin(\beta) \bar{j}. \end{aligned} \quad (1)$$

According to Eq. (2.3.34), the stretch ratios are the magnitudes of the preceding, so

$$\begin{aligned} h_\alpha &= \left| \frac{\partial \bar{r}}{\partial \alpha} \right| = a \left[ \sinh(\alpha)^2 \sin(\beta)^2 + \cosh(\alpha)^2 \cos(\beta)^2 \right]^{1/2} \\ &= a \left[ (\cosh(\alpha)^2 - 1) \sin(\beta)^2 + \cosh(\alpha)^2 \cos(\beta)^2 \right]^{1/2} = ah, \\ h_\beta &= \left| \frac{\partial \bar{r}}{\partial \beta} \right| = ah, \end{aligned} \quad (2)$$

where

$$h = \left[ \cosh(\alpha)^2 - \sin(\beta)^2 \right]^{1/2}. \quad (3)$$

We find the corresponding unit vectors by substituting Eqs. (1) and (2) into Eqs. (2.3.30):

$$\begin{aligned} \bar{e}_\alpha &= \frac{1}{h} \left[ \sinh(\alpha) \sin(\beta) \bar{i} + \cosh(\alpha) \cos(\beta) \bar{j} \right], \\ \bar{e}_\beta &= \frac{1}{h} \left[ \cosh(\alpha) \cos(\beta) \bar{i} - \sinh(\alpha) \sin(\beta) \bar{j} \right]. \end{aligned} \quad (4) \triangleleft$$

### 2.3 Curvilinear Coordinates

69

The orthogonality of the mesh is confirmed by these unit vectors, because they show that  $\bar{e}_\alpha \cdot \bar{e}_\beta = 0$ .

The derivatives of the unit vectors involve partial derivatives of the stretch ratios, which we obtain by differentiating Eq. (3) to find

$$\begin{aligned}\frac{\partial h}{\partial \alpha} &= \frac{\cosh(\alpha) \sinh(\alpha)}{(\cosh(\alpha)^2 - \sin(\beta)^2)^{1/2}} = \frac{\cosh(\alpha) \sinh(\alpha)}{h}, \\ \frac{\partial h}{\partial \beta} &= \frac{-\sin(\beta) \cos(\beta)}{(\cosh(\alpha)^2 - \sin(\beta)^2)^{1/2}} = \frac{-\sin(\beta) \cos(\beta)}{h}.\end{aligned}$$

The corresponding expressions resulting from Eqs. (2.3.49), with  $\partial h / \partial \gamma = 0$  for a two-dimensional situation, are

$$\begin{aligned}\frac{\partial \bar{e}_\alpha}{\partial \alpha} &= -\frac{1}{h} \frac{\partial h}{\partial \beta} \bar{e}_\beta = \frac{\sin(\beta) \cos(\beta)}{h^2} \bar{e}_\beta, \\ \frac{\partial \bar{e}_\alpha}{\partial \beta} &= \frac{1}{h} \frac{\partial h}{\partial \alpha} \bar{e}_\beta = \frac{\cosh(\alpha) \sinh(\alpha)}{h^2} \bar{e}_\beta, \\ \frac{\partial \bar{e}_\beta}{\partial \alpha} &= \frac{1}{h} \frac{\partial h}{\partial \beta} \bar{e}_\alpha = -\frac{\sin(\beta) \cos(\beta)}{h^2} \bar{e}_\alpha, \\ \frac{\partial \bar{e}_\beta}{\partial \beta} &= -\frac{1}{h} \frac{\partial h}{\partial \alpha} \bar{e}_\alpha = -\frac{\cosh(\alpha) \sinh(\alpha)}{h^2} \bar{e}_\alpha.\end{aligned}$$

It is useful to compare this derivation to the steps that are entailed in direct evaluation of the Christoffel symbols according to Eq. (2.3.38). The first step would entail differentiation of each unit vector in Eqs. (4) with respect to  $\alpha$  and  $\beta$ . This would lead to four derivatives, each of whose form is somewhat lengthy because of the presence of  $h$ , which is a function of  $\alpha$  and  $\beta$ , in the denominator. Taking a dot product of each derivative with  $\bar{e}_\alpha$  and  $\bar{e}_\beta$  in accord with Eq. (2.3.38) would yield eight Christoffel symbols. It should be apparent that such a derivation is more difficult to implement than the approach we pursued.

### Kinematical Formulas

Our task in this subsection is to express the velocity and acceleration in terms of the parameters of a curvilinear coordinate system. For this development we consider the motion to be specified through the dependence of the curvilinear coordinates on time. The velocity is the time derivative of the position vector, which, in turn, is a function of the curvilinear coordinates  $(\alpha, \beta, \gamma)$ . Hence we employ the chain rule, in conjunction with the definition of the unit vectors in Eqs. (2.3.30), to differentiate  $\bar{r}$ :

$$\bar{v} = \dot{\alpha} \frac{\partial \bar{r}}{\partial \alpha} + \dot{\beta} \frac{\partial \bar{r}}{\partial \beta} + \dot{\gamma} \frac{\partial \bar{r}}{\partial \gamma} = h_\alpha \dot{\alpha} \bar{e}_\alpha + h_\beta \dot{\beta} \bar{e}_\beta + h_\gamma \dot{\gamma} \bar{e}_\gamma. \quad (2.3.50)$$

This expression may be written in summation form as

$$\vec{v} = \sum_{\lambda=\alpha,\beta,\gamma} h_{\lambda} \dot{\lambda} \vec{e}_{\lambda}. \quad (2.3.51)$$

We derive the acceleration by differentiating Eq. (2.3.51) with respect to time. Each of the factors inside the preceding summation may vary with time, so

$$\vec{a} = \sum_{\lambda=\alpha,\beta,\gamma} h_{\lambda} \ddot{\lambda} \vec{e}_{\lambda} + \sum_{\lambda=\alpha,\beta,\gamma} \dot{\lambda} \left( \frac{dh_{\lambda}}{dt} \vec{e}_{\lambda} + h_{\lambda} \frac{d\vec{e}_{\lambda}}{dt} \right). \quad (2.3.52)$$

We consider only the rates of change of the curvilinear coordinates  $\dot{\lambda}$  to depend explicitly on  $t$ , whereas the unit vectors  $\vec{e}_{\lambda}$  and the stretch ratios  $h_{\lambda}$  depend on  $t$  implicitly through their dependence on the curvilinear coordinates. Application of the chain rule for differentiation to the latter two sets of parameters then yields

$$\vec{a} = \sum_{\lambda=\alpha,\beta,\gamma} h_{\lambda} \ddot{\lambda} \vec{e}_{\lambda} + \sum_{\lambda=\alpha,\beta,\gamma} \sum_{\mu=\alpha,\beta,\gamma} \dot{\lambda} \dot{\mu} \left( \frac{\partial h_{\lambda}}{\partial \mu} \vec{e}_{\lambda} + h_{\lambda} \frac{\partial \vec{e}_{\lambda}}{\partial \mu} \right). \quad (2.3.53)$$


Explicit expressions for a specific set of curvilinear coordinates may be obtained from the preceding equation by evaluating the stretch ratios and the derivatives of the unit vectors according to Eqs. (2.3.34) and (2.3.49), respectively.

It is apparent that each acceleration component might consist of several terms in the most general case. The situation for many common sets of curvilinear coordinates is simplified by the fact that the stretch ratios and unit vectors usually do not depend on all of the curvilinear coordinates. For example, in the case of spherical coordinates, all of the unit vectors are independent of the radial distance  $r$  and the radial stretch ratio  $h_r = 1$ . In the most general case Eq. (2.3.53) gives 21 different terms: 3 from the single summation and 9 from each term in the double summation corresponding to different pairs of  $\lambda$  and  $\mu$ . Because there are only three curvilinear coordinate directions, it is clear that a variety of effects contributes to any acceleration component. Let us examine each type of effect.

The terms in the single summation of Eq. (2.3.53), that is,  $h_{\lambda} \ddot{\lambda} \vec{e}_{\lambda}$ , are intuitively obvious. They express an acceleration tangent to each  $\lambda$  coordinate curve that arises when  $\dot{\lambda}$  is not constant. To understand the terms in the double sum we categorize them as to whether the indices for each sum are associated with the same curvilinear coordinate. If  $\mu = \lambda$ , three terms correspond to  $\dot{\lambda}^2 (\partial h_{\lambda} / \partial \lambda) \vec{e}_{\lambda}$ . This is another acceleration effect tangent to a  $\lambda$  coordinate curve; it arises because constant  $\dot{\lambda}$  will not lead to a constant rate of movement along that curve if the stretch ratio  $h_{\lambda}$  changes along the curve. The other term corresponding to  $\mu = \lambda$  is  $\dot{\lambda}^2 h_{\lambda} (\partial \vec{e}_{\lambda} / \partial \lambda)$ . Because the derivative of a unit vector is always perpendicular to the unit vector, this is an acceleration component perpendicular to the  $\lambda$  coordinate curve that arises from the changing direction of the unit vector  $\vec{e}_{\lambda}$  as  $\lambda$  changes. Such a change is illustrated in Fig. 2.11 for the case in which  $\lambda = \alpha$ . Following the  $\alpha$  curve from the point associated with specific  $(\alpha, \beta, \gamma)$  values to an adjacent point at which the coordinates are  $(\alpha + d\alpha, \beta, \gamma)$  causes the tip of  $\vec{e}_{\alpha}$  to move perpendicularly to the original  $e_{\alpha}$ . The fact that  $\dot{\lambda} h_{\lambda}$  is the corresponding velocity component

### 2.3 Curvilinear Coordinates

71



**Figure 2.11.** Change of unit vector  $\bar{e}_\alpha$  along the  $\alpha$  and  $\beta$  coordinate curves.

suggests that this acceleration component is analogous to the centripetal acceleration in path variables.

Let us now turn our attention to those terms in the double sum of Eq. (2.3.53) that correspond to  $\mu \neq \gamma$ . There are three combinations fitting this description, corresponding to  $(\lambda, \mu) = (\alpha, \beta)$ ,  $(\beta, \gamma)$ , or  $(\alpha, \gamma)$  in either the listed or reversed order. Let us consider the combination  $(\lambda, \mu) = (\alpha, \beta)$  or  $(\beta, \alpha)$ . The first term in the double sum leads to two terms:  $[(\partial h_\alpha / \partial \beta) \bar{e}_\alpha + (\partial h_\beta / \partial \alpha) \bar{e}_\beta] \dot{\alpha} \dot{\beta}$ . The first of the preceding terms exists if  $\beta$  changes and the stretch ratio  $h_\alpha$  for the  $\alpha$  curve depends on  $\beta$ . Similarly, the second term exists if  $\alpha$  changes and the stretch ratio  $h_\beta$  depends on  $\alpha$ . Both are representative of acceleration components tangent to a generic coordinate curve  $\gamma$  that results because the rate of movement along the curve,  $\dot{\gamma} h_\gamma$ , changes as a consequence of the nonconstancy of the stretch ratio. The second term in the double sum also leads to two terms for  $(\lambda, \mu) = (\alpha, \beta)$  or  $(\beta, \alpha)$ :  $[h_\alpha \partial \bar{e}_\alpha / \partial \beta + h_\beta \partial \bar{e}_\beta / \partial \alpha] \dot{\alpha} \dot{\beta}$ . These are acceleration terms perpendicular to a  $\lambda$  coordinate curve ( $\lambda = \alpha$  for the first term and  $\lambda = \beta$  for the second) that occur when  $\bar{e}_\lambda$  depends on another curvilinear coordinate that is not constant in the motion. This is depicted in Fig. 2.11, where  $\bar{e}_\alpha$  changes as a point moves by an infinitesimal amount along the  $\beta$  coordinate line. Correspondingly, the mesh point coordinates change from  $(\alpha, \beta, \gamma)$  to  $(\alpha, \beta + d\beta, \gamma)$ . The tip of  $\bar{e}_\alpha$  moves perpendicularly to the original  $\bar{e}_\alpha$  direction, so the resulting acceleration effect is also perpendicular to  $\bar{e}_\alpha$ .

Let us focus on two terms that were just listed:  $(\partial h_\beta / \partial \alpha) \bar{e}_\beta \dot{\alpha} \dot{\beta}$ , which arose from the first term of the double sum, and  $h_\alpha (\partial \bar{e}_\alpha / \partial \beta) \dot{\alpha} \dot{\beta}$ , which arose from the second term of the double sum. According to Eqs. (2.3.49), the latter is the same as the former, which would lead to a factor of two in the ultimate acceleration formula. This is the general version of the Coriolis accelerations we encountered in the specific cases of cylindrical and spherical coordinates. Hence we have proven that, in general, Coriolis acceleration arises from two distinctly different effects associated with an interaction of motion along more than one coordinate curve.

To close this section it is emphasized that only in the special case of Cartesian coordinates does changing a single coordinate lead to velocity and acceleration solely in the direction associated with that coordinate. In the most general case of curvilinear coordinates, changing one coordinate can lead to acceleration tangentially to each coordinate curve. Furthermore, in Cartesian coordinates, acceleration results solely from nonconstancy of  $\dot{x}$ ,  $\dot{y}$ , or  $\dot{z}$ . In a curvilinear coordinate, there can be acceleration, even if  $\dot{\alpha}$ ,  $\dot{\beta}$ , and  $\dot{\gamma}$  are constant.

**EXAMPLE 2.10** Derive Eqs. (2.3.11) and (2.3.14) for velocity and acceleration in terms of cylindrical coordinates by using stretch ratios.

**SOLUTION** The intent of applying the basic kinematical formulas for curvilinear coordinates to a coordinate system that has been analyzed by a different technique is to enhance one's recognition of the significance of the basic parameters and operations. The first step is to evaluate the unit vectors and stretch ratios. For the coordinate transformation in Eq. (2.3.3), we have

$$\bar{\mathbf{r}} = R \cos(\theta) \bar{\mathbf{i}} + R \sin(\theta) \bar{\mathbf{j}} + z \bar{\mathbf{k}}.$$

Then

$$\begin{aligned} h_R \bar{\mathbf{e}}_R &= \frac{\partial \bar{\mathbf{r}}}{\partial R} = \cos(\theta) \bar{\mathbf{i}} + \sin(\theta) \bar{\mathbf{j}}, \\ h_\theta \bar{\mathbf{e}}_\theta &= \frac{\partial \bar{\mathbf{r}}}{\partial \theta} = -R \sin(\theta) \bar{\mathbf{i}} + R \cos(\theta) \bar{\mathbf{j}}, \\ h_z \bar{\mathbf{e}}_z &= \frac{\partial \bar{\mathbf{r}}}{\partial z} = \bar{\mathbf{k}}. \end{aligned}$$

Setting the magnitude of each unit vector to unity yields the stretch ratios,

$$\begin{aligned} h_R &= \left| \frac{\partial \bar{\mathbf{r}}}{\partial R} \right| = 1, \\ h_\theta &= \left| \frac{\partial \bar{\mathbf{r}}}{\partial \theta} \right| = R, \\ h_z &= \left| \frac{\partial \bar{\mathbf{r}}}{\partial z} \right| = 1, \end{aligned}$$

which correspond to

$$\begin{aligned} \bar{\mathbf{e}}_R &= \cos(\theta) \bar{\mathbf{i}} + \sin(\theta) \bar{\mathbf{j}}, \\ \bar{\mathbf{e}}_\theta &= -R \sin(\theta) \bar{\mathbf{i}} + R \cos(\theta) \bar{\mathbf{j}}, \\ \bar{\mathbf{e}}_z &= \bar{\mathbf{k}}. \end{aligned}$$

We refer to Eqs. (2.3.49) and its permutations to obtain the derivatives of the unit vectors:

$$\begin{aligned} \frac{\partial \bar{\mathbf{e}}_R}{\partial R} &= -\frac{1}{h_\theta} \frac{\partial h_R}{\partial \theta} \bar{\mathbf{e}}_\theta - \frac{1}{h_z} \frac{\partial h_R}{\partial z} \bar{\mathbf{e}}_z = 0, \\ \frac{\partial \bar{\mathbf{e}}_R}{\partial \theta} &= \frac{1}{h_R} \frac{\partial h_\theta}{\partial R} \bar{\mathbf{e}}_\theta = \bar{\mathbf{e}}_\theta, \quad \frac{\partial \bar{\mathbf{e}}_R}{\partial z} = \frac{1}{h_R} \frac{\partial h_z}{\partial R} \bar{\mathbf{e}}_z = 0, \\ \frac{\partial \bar{\mathbf{e}}_\theta}{\partial \theta} &= -\frac{1}{h_R} \frac{\partial h_\theta}{\partial R} \bar{\mathbf{e}}_R - \frac{1}{h_z} \frac{\partial h_\theta}{\partial z} \bar{\mathbf{e}}_z = -\bar{\mathbf{e}}_R, \\ \frac{\partial \bar{\mathbf{e}}_\theta}{\partial R} &= \frac{1}{h_\theta} \frac{\partial h_R}{\partial \theta} \bar{\mathbf{e}}_R = 0, \quad \frac{\partial \bar{\mathbf{e}}_\theta}{\partial z} = \frac{1}{h_\theta} \frac{\partial h_z}{\partial \theta} \bar{\mathbf{e}}_z = 0, \end{aligned}$$



## 2.4 Mixed Kinematical Descriptions

73

$$\begin{aligned}\frac{\partial \bar{e}_z}{\partial z} &= -\frac{1}{h_R} \frac{\partial h_z}{\partial R} \bar{e}_R - \frac{1}{h_\theta} \frac{\partial h_z}{\partial \theta} \bar{e}_\theta = 0, \\ \frac{\partial \bar{e}_z}{\partial R} &= \frac{1}{h_z} \frac{\partial h_R}{\partial z} \bar{e}_R = 0, \quad \frac{\partial \bar{e}_z}{\partial \theta} = \frac{1}{h_z} \frac{\partial h_\theta}{\partial z} \bar{e}_\theta.\end{aligned}$$

We obtain an expression for the velocity by expanding Eq. (2.3.51) and substituting the various terms. Thus,

$$\begin{aligned}\bar{v} &= h_R \dot{R} \bar{e}_R + h_\theta \dot{\theta} \bar{e}_\theta + h_z \dot{z} \bar{e}_z \\ &= \dot{R} \bar{e}_R + R \dot{\theta} \bar{e}_\theta + \dot{z} \bar{e}_z.\end{aligned}\quad \triangleleft$$


This is the same as Eq. (2.3.11). For acceleration, we expand Eq. (2.3.53) and omit terms that contain derivatives of stretch ratios or unit vectors that we have found to be zero. The remaining terms are

$$\begin{aligned}\bar{a} &= h_R \ddot{R} \bar{e}_R + h_\theta \ddot{\theta} \bar{e}_\theta + h_z \ddot{z} \bar{e}_z \\ &\quad + \dot{R} \dot{\theta} h_R \frac{\partial \bar{e}_R}{\partial \theta} + \dot{\theta} \dot{R} \frac{\partial h_\theta}{\partial R} \bar{e}_\theta + \dot{\theta}^2 h_\theta \frac{\partial \bar{e}_\theta}{\partial \theta} \\ &= \ddot{R} \bar{e}_R + R \ddot{\theta} \bar{e}_\theta + \ddot{z} \bar{e}_z + \dot{R} \dot{\theta} \bar{e}_\theta + \dot{\theta} \dot{R} \bar{e}_\theta + \dot{\theta}^2 R (-\bar{e}_R).\end{aligned}\quad \triangleleft$$

Collecting like components shows that this expression is the same as Eq. (2.3.14).

## 2.4 MIXED KINEMATICAL DESCRIPTIONS

Thus far there was little ambiguity as to which kinematical description, path variables, Cartesian, or one of the curvilinear coordinate systems, we should use. Here we consider situations in which no single description leads to an optimal solution. The key factor to be considered in this regard is which description fits the aspects of the motion that are known and which fits the parameters we seek. For example, suppose that the path of a particle is known to be as shown in Fig. 2.12. If the rate of movement along that path is specified in terms of the speed  $v$ , we would certainly want to employ a path variable description. Now further suppose that, with  $v$  known, it is desired to determine the rotation



**Figure 2.12.** Mixed usage of path variables and cylindrical coordinates.

rate  $\dot{\theta}$  of the azimuthal plane defined in the figure. Because  $\theta$  is one of the cylindrical coordinates, it would seem wise to use that description. We could consider the kinematical description that best matches the parameters of the actual system to be the “natural” one, but sometimes no single formulation is entirely natural, although more than one have elements that are suitable. It is almost axiomatic that if one of the kinematical descriptions has some aspect that suits a problem, it should be employed. Thus, the task that confronts us here is to simultaneously implement two different descriptions. A precursor to this task arose in Example 2.1, where the velocity and acceleration were given in Cartesian coordinates and we needed to evaluate path variable parameters.

The general concept is to match the velocity and acceleration vectors obtained from the relevant kinematical descriptions. This matching is implemented by resolving unit vectors for one formulation into components relative to the unit vectors of the other formulation. For this purpose it is assumed that the position is known, so that all geometric quantities, including the angles between unit vectors, are known. For simplicity, let us consider planar motion. Let  $\bar{e}_\alpha$  and  $\bar{e}_\beta$  be the orthogonal planar unit vectors for one kinematical description (for example,  $\bar{e}_\alpha$  and  $\bar{e}_\beta$  are the tangent and normal directions), and let  $\bar{e}_\lambda$  and  $\bar{e}_\mu$  be the orthogonal planar unit vectors for the other description. These unit vectors have been depicted with their tails coinciding in Fig. 2.13 in order to expedite resolving a unit vector into components.




Figure 2.13. Relation between two sets of orthogonal unit vectors in a plane.

As shown in the figure, the orientation of one set of unit vectors relative to the other is defined by the angle  $\psi$ . (The definition of this angle as that between  $\bar{e}_\alpha$  and  $\bar{e}_\lambda$  is arbitrary.) The components of  $\bar{e}_\lambda$  and  $\bar{e}_\mu$  relative to  $\bar{e}_\alpha$  and  $\bar{e}_\beta$  are found from this figure to be

$$\bar{e}_\lambda = \cos(\psi) \bar{e}_\alpha + \sin(\psi) \bar{e}_\beta, \quad \bar{e}_\mu = -\sin(\psi) \bar{e}_\alpha + \cos(\psi) \bar{e}_\beta. \quad (2.4.1)$$

The velocity may be expressed in terms of components relative to either set of unit vectors. Thus,

$$\bar{v} = v_\alpha \bar{e}_\alpha + v_\beta \bar{e}_\beta = v_\lambda \bar{e}_\lambda + v_\mu \bar{e}_\mu. \quad (2.4.2)$$

It is implicit to the preceding equation that each velocity component would be expressed in terms of the parameters associated with its unit vectors. For example, if  $\bar{e}_\alpha$  and  $\bar{e}_\beta$  represented the tangent and normal unit vectors, respectively, then we would set  $v_\alpha = v$  and  $v_\beta = 0$ .

Two vectors are equal if, and only if, their like components are equal. Thus Eqs. (2.4.2) constitute two scalar equations, which can be obtained by matching their components in two different coordinate directions. One approach for performing this

## 2.4 Mixed Kinematical Descriptions

75

operation is to substitute the unit vectors in Eqs. (2.4.1) into Eqs. (2.4.2), which yields

$$\begin{aligned}\bar{v} &= v_\alpha \bar{e}_\alpha + v_\beta \bar{e}_\beta = v_\lambda \bar{e}_\lambda + v_\mu \bar{e}_\mu \\ &= v_\lambda [\cos(\psi) \bar{e}_\alpha + \sin(\psi) \bar{e}_\beta] + v_\beta [-\sin(\psi) \bar{e}_\alpha + \cos(\psi) \bar{e}_\beta] \\ &= [v_\lambda \cos(\psi) - v_\beta \sin(\psi)] \bar{e}_\alpha + [v_\lambda \sin(\psi) + v_\beta \cos(\psi)] \bar{e}_\beta.\end{aligned}\quad (2.4.3)$$

Like components were grouped as the last operation in the preceding equation. Doing so assists equating like components on either side of the equality, with the result that

$$\begin{aligned}v_\alpha &= v_\lambda \cos(\psi) - v_\beta \sin(\psi), \\ v_\beta &= v_\lambda \sin(\psi) + v_\beta \cos(\psi).\end{aligned}\quad (2.4.4)$$

Each of the velocity components appearing in Eqs. (2.4.4) presumably has been represented in terms of the formula associated with its description. Furthermore, the position parameters are assumed to be known. Thus we have derived two scalar equations relating rate variables in either kinematical description.

An alternative way to obtain a component in a certain direction is to use a dot product. The dot product of the velocity in Eqs. (2.4.2) in the direction of two unit vectors gives two scalar equations representing the equality of the alternative component descriptions. The interesting aspect of this approach is that the selected unit vectors can be any pair. If we evaluate  $\bar{v} \cdot \bar{e}_\alpha$  and  $\bar{v} \cdot \bar{e}_\beta$ , we obtain Eqs. (2.4.4). However, the unit vectors can also belong to different descriptions. For example, we could evaluate  $\bar{v} \cdot \bar{e}_\beta$  and  $\bar{v} \cdot \bar{e}_\lambda$ , provided that  $\bar{e}_\beta$  and  $\bar{e}_\lambda$  are not parallel in the position of interest. This would give

$$\begin{aligned}\bar{v} \cdot \bar{e}_\beta &= v_\beta = v_\lambda \bar{e}_\lambda \cdot \bar{e}_\beta + v_\mu \bar{e}_\mu \cdot \bar{e}_\beta, \\ \bar{v} \cdot \bar{e}_\lambda &= v_\lambda = v_\alpha \bar{e}_\alpha \cdot \bar{e}_\lambda + v_\beta \bar{e}_\beta \cdot \bar{e}_\lambda.\end{aligned}\quad (2.4.5)$$

The dot products are readily described by referring to Fig. 2.13, which leads to

$$\begin{aligned}v_\beta &= v_\lambda \sin(\psi) + v_\mu \cos(\psi), \\ v_\lambda &= v_\alpha \cos(\psi) + v_\beta \sin(\psi).\end{aligned}\quad (2.4.6)$$

In practice, the procedure leading to Eqs. (2.4.6) is slightly more versatile, whereas following Eqs. (2.4.4) is somewhat less prone to computational errors. Either set represents two equations that may be used to solve for two unknown rate parameters. As an illustration of this procedure, suppose that  $(\alpha, \beta)$  represents path variables and  $(\lambda, \mu)$  represents polar coordinates. Substitution of the respective velocity components into Eqs. (2.4.4) then yields

$$\begin{aligned}v &= \dot{R} \cos(\psi) - R \dot{\theta} \sin(\psi), \\ 0 &= \dot{R} \sin(\psi) + R \dot{\theta} \cos(\psi).\end{aligned}\quad (2.4.7)$$

The values of the radial distance  $R$  and the angle of orientation  $\psi$  are known if the position is specified. Thus Eqs. (2.4.7) represent two relations among the three rate variables,  $v$ ,  $\dot{R}$ , and  $\dot{\theta}$ .


Equations derived by matching alternative velocity descriptions may be used in either of two general situations. It might be that the velocity is already known in terms of either the  $(\alpha, \beta)$  or the  $(\lambda, \mu)$  components. In that case, the equations provide the conversion to the parameters associated with the other set of components. The more interesting situation is that of a mixed description, that is, one in which the velocity is only partially known in terms of either of the two descriptions. In that case, the matching procedure provides the means to ascertain the velocity.

The same approach may be applied to treat acceleration. Specifically, the individual formulas for acceleration may be matched by employing either the unit vector transformation in Eqs. (2.4.1) or by taking dot products in the two different directions. The result will be two scalar equations for acceleration rate variables, such as  $\dot{v}$  or  $\dot{R}$ . Solving those equations requires that all velocity rate variables, such as  $v$  or  $\dot{R}$ , be evaluated first because they occur in the acceleration components. In other words, the velocity relations must be solved before accelerations can be addressed, which is not surprising because acceleration is the derivative of velocity. The remarkable aspect of the approach is there is no need to differentiate any quantity because the basic velocity and acceleration formulas represent standard derivatives.

The discussion treated the case of planar motion, but the same procedure also applies to three-dimensional motion. The kinematical formulas in that case have three components, so matching corresponding components will lead to three simultaneous equations. The primary difficulty that arises in this extension is the evaluation of the transformation of the unit vectors. The component representation in Eqs. (2.4.1) was derived by visual projections of one set of unit vector onto the other directions. The same procedure may be performed in a three-dimensional case if the geometry is not too complicated. An alternative approach for determining the unit vector components uses rotation transformation properties established in the next chapter.

**EXAMPLE 2.11** Use the concept of a Mixed kinematical description to determine  $\dot{R}$  and  $\dot{\theta}$  for the airplane in Example 2.7.

**SOLUTION** This example demonstrates that viewing a system from multiple kinematical perspectives often can greatly simplify the analysis. The path and speed of the airplane are given, both of which are path variable parameters. We must determine the rates of change of polar coordinates. Thus we draw a sketch that depicts the unit vectors for both formulations at an arbitrary  $\theta$ .



Example 2.11

## 2.4 Mixed Kinematical Descriptions

77

The velocity in terms of each set of unit vectors is

$$\bar{v} = v\bar{e}_t = \dot{R}\bar{e}_R + R\dot{\theta}\bar{e}_\theta.$$

The speed  $v$  is the given parameter, so we may obtain an equation for  $\dot{R}$  by forming

$$\bar{v} \cdot \bar{e}_R = v\bar{e}_t \cdot \bar{e}_R = \dot{R}.$$

From the sketch we see that the angle between  $\bar{e}_t$  and  $\bar{e}_R$  is  $\theta - \beta$ , so we find that

$$\dot{R} = v \cos(\theta - \beta). \quad \triangleleft$$

To find an expression for  $\dot{\theta}$ , we have

$$\bar{v} \cdot \bar{e}_\theta = v\bar{e}_t \cdot \bar{e}_\theta = R\dot{\theta}.$$

We evaluate the dot product by observing that the angle between  $\bar{e}_t$  and  $\bar{e}_\theta$  is  $\theta - \beta + \pi/2$ . Also, it was requested in the problem statement that the results be expressed in terms of the elevation angle  $\theta$ , on which  $R$  depends. From the law of sines, we have


$$\frac{R}{\sin(\beta + \pi/2)} = \frac{H}{\sin(\theta - \beta)} \implies R = H \frac{\cos(\beta)}{\sin(\theta - \beta)}.$$

Consequently, the equation for  $\bar{v} \cdot \bar{e}_\theta$  yields

$$\dot{\theta} = \frac{1}{R} v \cos(\theta - \beta + \pi/2) = -\frac{v}{H} \frac{\sin(\theta - \beta)^2}{\cos(\beta)}. \quad \triangleleft$$

There is no doubt that this solution is easier than the one in Example 2.7.


**EXAMPLE 2.12** Arm  $AB$  rotates clockwise at the constant rate of 40 rad/s as it pushes the slider along guide  $CD$ , which is described by  $y = x^2/200$  ( $x$  and  $y$  are in millimeters). Determine the velocity and acceleration of the slider when it is at the position  $x = 200$  mm.



Example 2.12

**SOLUTION** This example is a further demonstration that the concept of joint kinematical descriptions can make challenging problems quite tractable. The planar motion is specified by a rotation rate, but the path is not described in terms of polar

coordinates. Hence we follow an approach that employs path variables and polar coordinates. We begin by evaluating the position parameters for both kinematical descriptions. A sketch shows both sets of unit vectors at  $x = 200$  mm, which corresponds to  $y = x^2/200 = 200$  mm. In this sketch the sense of  $\bar{e}_t$  has been selected based on recognition that clockwise motion of bar  $AB$  will move the collar up and to the right. In more complicated situations, in which we are uncertain of the appropriate direction, we may guess the sense of  $\bar{e}_t$ . A wrong guess would lead to a negative value for  $v$ . Also, we have depicted  $\bar{e}_n$  as the perpendicular to  $\bar{e}_t$  that points toward the center of curvature.



The polar coordinates are found from a right triangle to be

$$R = (600^2 + 200^2)^{1/2} = 632.5 \text{ mm} = 0.6325 \text{ m},$$

$$\theta = \tan^{-1} \left( \frac{200}{600} \right) = 18.435^\circ.$$

The slope of the guide bar at this location yields the angle of orientation of the tangent vector:

$$\beta = \tan^{-1} \left( \frac{dy}{dx} \right) = \tan^{-1} \left( \frac{y}{100} \right) = 63.435^\circ.$$

Matching like velocity components in each formulation is the next step. The relevant velocity formulas are

$$\bar{v} = \dot{R}\bar{e}_R + R\dot{\theta}\bar{e}_\theta = v\bar{e}_t.$$

For the sake of variety, we use the approach in which one set of unit vectors is expressed in terms of components relative to the other set. Hence we write

$$\bar{e}_t = -\cos(\theta + \beta)\bar{e}_R + \sin(\theta + \beta)\bar{e}_\theta,$$

$$\bar{e}_n = \sin(\theta + \beta)\bar{e}_R + \cos(\theta + \beta)\bar{e}_\theta.$$

Note that, although  $\bar{e}_n$  is not needed to analyze the velocity, it has been described in anticipation of using it for acceleration. We substitute the expression for  $\bar{e}_t$  into the velocity equation, and match like components:

$$\bar{v} = \dot{R}\bar{e}_R + R\dot{\theta}\bar{e}_\theta = v[-\cos(\theta + \beta)\bar{e}_R + \sin(\theta + \beta)\bar{e}_\theta],$$

$$\bar{v} \cdot \bar{e}_R = \dot{R} = -v\cos(\theta + \beta), \quad \bar{v} \cdot \bar{e}_\theta = R\dot{\theta} = v\sin(\theta + \beta).$$

## 2.4 Mixed Kinematical Descriptions

79

The value of  $\dot{\theta}$  is given to be 40 rad/s, and  $R$ ,  $\theta$ , and  $\beta$  have been evaluated, so the preceding equations represent two equations for  $\dot{R}$  and  $v$ . Their solutions are

$$v = 25.56 \text{ m/s}, \quad \dot{R} = -3.614 \text{ m/s}.$$

Because we have evaluated all velocity parameters, we may now implement a similar procedure for acceleration. The relevant formulas are

$$\bar{a} = (\ddot{R} - R\dot{\theta}^2)\bar{e}_R + (R\ddot{\theta} + 2\dot{R}\dot{\theta})\bar{e}_\theta = \dot{v}\bar{e}_t + \frac{v^2}{\rho}\bar{e}_n.$$

Substitution of the earlier representations of  $\bar{e}_t$  and  $\bar{e}_n$  in terms of polar coordinates converts these equations to

$$\begin{aligned} \bar{a} &= (\ddot{R} - R\dot{\theta}^2)\bar{e}_R + (R\ddot{\theta} + 2\dot{R}\dot{\theta})\bar{e}_\theta \\ &= \dot{v}[-\cos(\theta + \beta)\bar{e}_R + \sin(\theta + \beta)\bar{e}_\theta] \\ &\quad + \frac{v^2}{\rho}[\sin(\theta + \beta)\bar{e}_R + \cos(\theta + \beta)\bar{e}_\theta]. \end{aligned}$$

The result of matching like acceleration components is

$$\begin{aligned} \bar{a} \cdot \bar{e}_R &= \ddot{R} - R\dot{\theta}^2 = -\dot{v}\cos(\theta + \beta) + \frac{v^2}{\rho}\sin(\theta + \beta), \\ \bar{a} \cdot \bar{e}_\theta &= R\ddot{\theta} + 2\dot{R}\dot{\theta} = \dot{v}\sin(\theta + \beta) + \frac{v^2}{\rho}\cos(\theta + \beta). \end{aligned}$$

We know that  $\dot{\theta}$  is constant at 40 rad/s, so  $\ddot{\theta} = 0$ . We evaluated  $R$ ,  $\theta$ , and  $\beta$  from the given position information. The radius of curvature, being a property of the path, also is a position parameter. We compute it from Eq. (2.1.31), which gives, for  $x = 200 \text{ mm}$ ,

$$\rho = \frac{\left[1 + \left(\frac{x}{100}\right)^2\right]^{3/2}}{\left|\frac{1}{100}\right|} = 1118.0 \text{ mm} = 1.1180 \text{ m}.$$

Substitution of all known quantities into the acceleration component equations gives

$$\begin{aligned} \bar{a} \cdot \bar{e}_R &= \ddot{R} - 1011.9 = -\dot{v}(0.14142) + \frac{25.56^2}{1.1180}(0.9899), \\ \bar{a} \cdot \bar{e}_\theta &= 2(-3.614)(40) = \dot{v}(0.9899) + \frac{25.56^2}{1.1180}(0.14142). \end{aligned}$$

We solve the second equation for  $\dot{v}$ , then use that solution to calculate  $\ddot{R}$ , which yields

$$\dot{v} = -375.5 \text{ m/s}^2, \quad \ddot{R} = 1643.3 \text{ m/s}^2.$$

The problem statement requested the velocity and acceleration, which may be expressed in terms of either path variable or polar coordinate components:

$$\begin{aligned}\bar{v} &= 25.56 \bar{e}_t \text{ m/s} \quad \text{or} \quad \bar{v} = -3.614 \bar{e}_R + 25.30 \bar{e}_\theta \text{ m/s}, \\ \bar{a} &= -375.5 \bar{e}_t + 584.1 \bar{e}_n \text{ m/s}^2, \quad \text{or} \quad \bar{a} = 631.4 \bar{e}_R - 289.1 \bar{e}_\theta \text{ m/s}^2.\end{aligned}$$

There usually is more than one way in which one may attack a problem, and sometimes the chosen path is not the most direct. This is the case here. The need to use polar coordinates was clearly indicated, but that description was matched to path variables primarily to give a full picture of the operations. The given information described the path in Cartesian coordinates, and there was no mention of speed. Thus it would have been more logical to match the polar and Cartesian coordinate descriptions of the slider's motion. Let us see how such a solution would evolve.

In units of meters the path is described by  $y = 5x^2$ . We do not know *a priori* how  $x$  or  $y$  depend on time, so the Cartesian coordinate descriptions of the slider's motion are

$$\begin{aligned}\bar{v} &= \dot{x}\bar{i} + \dot{y}\bar{j} = \dot{x}\bar{i} + 10x\dot{x}\bar{j}, \\ \bar{a} &= \frac{d\bar{v}}{dt} = \ddot{x}\bar{i} + 10(x\ddot{x} + \dot{x}^2)\bar{j}.\end{aligned}$$

At the position of interest  $x = 0.2$  m, and we earlier determined the corresponding polar coordinates to be  $R = 0.6325$  m,  $\theta = 18.435^\circ$ . From the earlier sketch of the unit vectors we know that

$$\begin{aligned}\bar{i} &= -\cos\theta\bar{e}_R + \sin\theta\bar{e}_\theta = -0.9487\bar{e}_R + 0.3162\bar{e}_\theta, \\ \bar{j} &= \sin\theta\bar{e}_R + \cos\theta\bar{e}_\theta = 0.3162\bar{e}_R + 0.9487\bar{e}_\theta.\end{aligned}$$

Equating the velocity descriptions leads to

$$\begin{aligned}\bar{v} &= \dot{x}\bar{i} + 10(0.2)\dot{x}\bar{j} = \dot{x}(-0.9487\bar{e}_R + 0.3162\bar{e}_\theta) + 2\dot{x}(0.3162\bar{e}_R + 0.9487\bar{e}_\theta) \\ &= \dot{R}\bar{e}_R + R\dot{\theta}\bar{e}_\theta = \dot{R}\bar{e}_R + (0.6325)(40)\bar{e}_\theta.\end{aligned}$$

The algebraic equations obtained by matching like components are

$$\begin{aligned}\bar{v} \cdot \bar{e}_R &= [-0.9487 + 2(0.3162)]\dot{x} = \dot{R}, \\ \bar{v} \cdot \bar{e}_\theta &= [0.3162 + 2(0.9487)]\dot{x} = 25.30,\end{aligned}$$

from which we find that

$$\dot{x} = 11.429 \text{ m/s}, \quad \dot{R} = -3.6145 \text{ m/s}.$$

These values are required to evaluate the acceleration. Equating the Cartesian description of acceleration written earlier to the polar coordinate expression gives

$$\begin{aligned}\bar{a} &= \ddot{x}\bar{i} + 10(x\ddot{x} + \dot{x}^2)\bar{j} \\ &= \ddot{x}(-0.9487\bar{e}_R + 0.3162\bar{e}_\theta) + 10\left[(0.2)\ddot{x} + (11.429)^2\right](0.3162\bar{e}_R + 0.9487\bar{e}_\theta) \\ &= (\ddot{R} - R\dot{\theta}^2)\bar{e}_R + (R\ddot{\theta} + 2\dot{R}\dot{\theta})\bar{e}_\theta = \left[\ddot{R} - (0.6325)(40)^2\right]\bar{e}_R + 2(-3.6145)(40)\bar{e}_\theta,\end{aligned}$$



## Selected References

81

from which we have

$$\bar{a} \cdot \bar{e}_R = [-0.9487 + 2(0.3162)]\ddot{x} + 10(11.429)^2(0.3162) = \ddot{R} - (0.6325)(40)^2,$$

$$\bar{a} \cdot \bar{e}_\theta = [0.3162 + 2(0.9487)]\ddot{x} + 10(11.429)^2(0.9487) = 2(-3.6145)(40).$$

These equations give

$$\ddot{x} = -690.4 \text{ m/s}^2, \quad \ddot{R} = 1643.3 \text{ m/s}^2.$$

The values of  $\dot{R}$  and  $\ddot{R}$  determined here are the same as those found previously, so the expression for  $\bar{v}$  and  $\bar{a}$  in terms of polar coordinate components would be unchanged. Using  $\dot{x}$  and  $\ddot{x}$  to form the Cartesian coordinate representation gives

$$\bar{v} = 11.429\bar{i} + 22.86\bar{j} \text{ m/s}, \quad \bar{a} = -690.4\bar{i} - 74.71\bar{j} \text{ m/s}^2 \quad \triangleleft$$


This solution is more direct than the preceding one, but which approach will be more direct might not be apparent *a priori* in other situations.

## SELECTED REFERENCES

- D'Souza, A. F., and Garg, V. K., *Advanced Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1984).
- Ginsberg, J. H., and Genin, J., *Dynamics*, 2nd ed., Wiley, New York (1984).
- Hibbeler, R. C., *Engineering Mechanics—Combined*, 10th ed., Prentice-Hall, Englewood Cliffs, New Jersey (2003).
- Kreyszig, E. "Formulae of Frenet," Chapter 15 in *Differential Geometry*, Dover, New York (1991).
- Marion, J. B., *Classical Dynamics of Particles and Systems*, Academic, New York (1960).
- Morse, P. M., and Feshbach, H., *Methods of Theoretical Physics*, McGraw-Hill, New York (1953).
- Pestel, E. C., and Thomson, W. T., *Dynamics*, McGraw-Hill, New York (1968).
- Shames, I. H., *Engineering Mechanics: Statics and Dynamics*, 4th ed., Prentice-Hall, Englewood Cliffs, New Jersey (1996).
- Smith, C. E., *Applied Mechanics: Dynamics*, Wiley, New York (1982).
- Stroud, K. A., and Booth, D. J., *Advanced Engineering Mathematics*, Industrial Press, New York (2005).
- Torby, B. J., *Advanced Dynamics for Engineers*, CBS College Publishing, New York (1984).
- Wills, A. P., *Vector Analysis With an Introduction to Tensor Analysis*, Dover, New York (1958).
- Wrede, W. R., *Introduction to Vector and Tensor Analysis*, Dover, New York (1972).

## HOMEWORK PROBLEMS

**EXERCISE 2.1** A small block slides in the interior of a smooth semicircular cylinder after being released from rest at the upper corner  $A$ . Because friction is negligible, the speed of the block is given by  $v^2 = 2gh$ , where  $h$  is the vertical distance the block has fallen. Determine the velocity and acceleration of the block as a function of  $h$ . Then sketch the acceleration when  $h = R/2$ .




Exercise 2.1

**EXERCISE 2.2** An automobile follows a circular road whose radius is 50 m. Let  $x$  and  $y$  respectively denote the eastern and northern directions, with origin at the center of the circle. Suppose the vehicle starts from rest at  $x = 50$  m heading north, and its speed depends on the distance  $s$  it travels according to  $v = 0.5s - 0.0025s^2$ , where  $s$  is measured in meters and  $v$  is in meters per second. It is known that the tires will begin to skid when the total acceleration of the vehicle is  $0.6g$ . Where will the automobile be and how fast will it be going when it begins to skid? Describe the position in terms of the angle of the radial line relative to the  $x$  axis.

**EXERCISE 2.3** A locomotive follows a circular track of radius  $R$  such that its speed depends on the distance it travels according to  $v = v_0 \sin(\pi s/s_0)$ , where  $s_0$  is the maximum distance. (a) What value of  $s$  corresponds to the maximum tangential acceleration? (b) What value of  $s$  corresponds to the maximum normal acceleration? (c) What value of the radius of the track will lead to the maximum normal and tangential accelerations being equal? (d) If the radius is the value in Part (c), at what value of  $s$  is the magnitude of the acceleration a maximum?

**EXERCISE 2.4** The collar slides over the stationary guide defined by  $x = ky^2$  in the vertical plane. The speed of the collar is the constant value  $v$ . This motion is implemented by application of a force  $\vec{F}$  of variable magnitude parallel to the  $x$  axis. Derive expressions for the magnitude of  $\vec{F}$  and of the reaction exerted by the guide as functions of the  $y$  coordinate of the collar.



Exercise 2.4

**EXERCISE 2.5** An old 5000-kg truck is traveling down a  $5^\circ$  incline at 20 km/h when its brakes and engine simultaneously fail. It is known that the air resistance is proportional to the square of the truck's speed and that the maximum speed the truck would obtain if the incline were sufficiently long and the truck did not become unstable is 160 km/h. Rolling resistance is negligible. Determine the truck's speed after it has traveled 1 km from the point of failure. How long does it take for the truck to arrive at this location?

**EXERCISE 2.6** A particle follows a planar path defined by  $x = k\xi$ ,  $y = 2k[1 - \exp(\xi)]$ , such that its speed is  $v = \beta\xi$ , where  $k$  and  $\beta$  are constants. Determine the velocity and acceleration at  $\xi = 0.5$ .

## Homework Problems

83

**EXERCISE 2.7** An ellipse is defined by  $(x/\alpha)^2 + (y/\beta)^2 = 1$ ,  $z = 0$ . Derive expressions for the tangent and normal unit vectors and the radius of curvature as functions of  $x$ .

**EXERCISE 2.8** A helix is defined by  $x = c\psi$ ,  $y = L\sin(k\psi)$ ,  $z = -L\cos(k\psi)$ , where  $c$ ,  $L$ , and  $k$  are constants. Determine the path variable unit vectors, the radius of curvature, and the torsion of this curve as functions of  $\psi$ .

**EXERCISE 2.9** A slider moves over a curved guide whose shape in the vertical plane is given by  $x = \beta\eta$ ,  $y = \beta \cosh \eta$ . Starting from  $x = 0$ , the speed is observed to vary as  $v = v_0(1 - ks)$ , where  $s$  is the distance traveled and  $k$  is a constant. Derive expressions for the velocity and acceleration of the slider as functions of  $x$ .

**EXERCISE 2.10** A particle moves along the paraboloid of revolution  $y = (x^2 + z^2)/L$ , such that  $x = L\sinh(k\xi)$ ,  $z = -L\cosh(k\xi)$ , where  $\xi$  is a parameter and  $L$  and  $k$  are constants. At the position where  $\xi = 1/k$ , its speed is  $5Lk$  and its speed is decreasing at the rate  $2Lk^2$ . Determine the velocity and acceleration at this position.

**EXERCISE 2.11** A particle slides along the hyperbolic paraboloidal surface  $z = xy/2$  such that  $x = 6\cos(ku)$ ,  $y = -6\sin(ku)$ , where  $x$ ,  $y$ , and  $z$  are in meters and  $u$  is a parameter. Determine the path variable unit vectors, the radius of curvature, and the torsion of the path at the position where  $ku = 2\pi/3$ .

**EXERCISE 2.12** A roller coaster track is laid out by giving the Cartesian coordinates of its centerline, with  $x$ ,  $y$ , and  $z$  respectively measured eastward, northward, and vertically relative to a reference point on the ground. For the track of interest  $y = x^2/100$  and  $z = 20[\cos(\pi x/50) + 1]$ , where  $x$ ,  $y$ , and  $z$  are in units of meters and  $-50 < x < 50$ . Determine and plot as functions of  $x$  the  $xyz$  components of the tangent, normal, and binormal unit vectors, as well as the dependence on  $x$  of the radius of curvature and torsion of the track.

**EXERCISE 2.13** In Exercise 2.12 the speed of a car as it travels along the track is known to be  $v = [2g(60 - z)]^{1/2}$  m/s. Determine and graph as a function of  $x$  the corresponding tangential and normal accelerations of a car.

**EXERCISE 2.14** Derive expressions for the binormal unit vector and torsion when a curve is described in parametric form by  $\bar{r}(\alpha)$ .


**EXERCISE 2.15** The specification for laying out the transition from a straight to curved segment of a train track stipulates that the radius of curvature must change gradually from an infinite value according to  $\rho = \rho_0 s_0/s$ , where  $0 < s < s_0$  is arc length from the beginning of the curve, after which the radius of curvature should be the constant value  $\rho_0$ . Consider a high-speed train that moves at a constant speed of 240 km/h. At the end of the curve, where  $s = s_0 = 1$  km, the normal acceleration should be  $0.5g$ . Let  $x$  measure distance in the direction of the tangent to the track at  $x = 0$ , and let  $y$  be the offset distance. Use computer software to determine how  $y$  must depend on  $x$  in order to meet this specification. Also plot the acceleration of a car as a function of  $x$ . *Hint:* Use a parametric description of the path with  $s$  as the parameter, so that  $s' = 1$  and

$y' = [1 - (x')^2]^{1/2}$ . Equating the expression for  $\rho$  in this representation to the specified dependence of  $\rho$  will lead to a differential equation for  $x(s)$  that can be solved numerically.

**EXERCISE 2.16** A particle moves along the surface  $z = (x^2 - y^2)/L$  such that  $x = L \cos(\beta\xi)$ ,  $y = L \sin(\beta\xi)$ , where  $\beta$  and  $L$  are constants and  $\xi$  is a parameter. Consider the case in which  $\xi = t$ . Derive expressions for the velocity and acceleration.

**EXERCISE 2.17** A particle slides along the hyperbolic paraboloidal surface  $z = xy/2b$  such that  $x = -(b^2 - y^2)^{1/2}$ ,  $y = b \sin(kt^2)$ , where  $h$ ,  $b$ , and  $k$  are constants. Derive expressions for the velocity and acceleration as functions of elapsed time  $t$ .


**EXERCISE 2.18** A ball is thrown down an incline whose angle of elevation is  $\theta$ . The initial velocity is  $u$  at an angle of elevation  $\beta$ . Derive an expression for the distance  $D$  measured along the incline at which the ball will return to the incline. Also determine the maximum height  $H$ , measured perpendicularly to the incline, of the trajectory, and the corresponding velocity of the ball at that position.



Exercise 2.18


**EXERCISE 2.19** A 200-g ball is thrown from the ground with the initial velocity  $v_0 = 20$  m/s at an angle of elevation  $\beta$ . In addition to its weight, there is a headwind that generates a horizontal resistance of 0.5 N. (a) For the case in which  $\beta = 30^\circ$  find the horizontal distance at which the ball returns to the elevation from which it was thrown. Also find the velocity of the ball at that location. (b) Find the value of  $\beta$  that maximizes the range for a specified value of  $v_0$ .

**EXERCISE 2.20** Pin  $P$ , whose mass is 10 g, moves in the horizontal plane within a groove defined by  $xy = 2$ , where  $x$  and  $y$  are in meters. The motion is actuated by arm  $ABC$ , which translates to the right at the constant speed of 30 m/s. (a) Determine the velocity and acceleration of the collar when  $x = 2$  m. (b) Determine the forces exerted on the pin by the groove and arm  $ABC$  when  $x = 2$  m.



Exercise 2.20

**EXERCISE 2.21** Gravity causes a steel ball of mass  $m$  that is situated between positive and negative magnetic plates to fall as it is attracted toward one of the plates. The magnetic force acting on the ball is horizontal with a magnitude that increases as the square of the distance from the midplane between the plates. In the sketch the  $xz$  plane coincides with this midplane, so this force is  $F = \alpha x^2 \text{sgn}(x)$ , where  $\text{sgn}(x)$  is the *signum* function. Suppose the ball is injected at the right plate,  $x = H/2$ ,  $y = 0$ , with an initial horizontal velocity  $v_0$  to the left. Derive an expression for the minimum  $v$  for



Exercise 2.21

## Homework Problems


85

which the ball will hit the left plate. Where will the ball hit the right plate if  $v$  is half this minimum value?

**EXERCISE 2.22** For laminar flow at low Reynolds number, the air resistance on an object is  $-c\bar{v}$ , where  $c$  is a constant and  $\bar{v}$  is the velocity of the object. A sphere of mass  $m$  is thrown from the ground with an initial speed  $v_0$  at an angle of elevation  $\beta$  in the (vertical)  $xy$  plane. Derive algebraic expressions for the position and velocity of the sphere as a function of time. Then use mathematical software to evaluate the distance the sphere travels, i.e., the value of  $x > 0$  at which  $y = 0$ , for the following sets of initial conditions: (a) initial velocity is 60 m/s at  $45^\circ$  angle of elevation, (b) initial velocity is 60 m/s at  $30^\circ$  angle of elevation. Compare the result in each case with what would be obtained if air resistance were neglected. The mass of the sphere is  $m = 4.6$  g, and the value of the viscosity coefficient  $c$  is such that the maximum speed of the sphere in a vertical free fall is 60 m/s. (This condition is called the terminal velocity.)

**EXERCISE 2.23** Solve Exercise 2.22 in the situation in which there is a steady headwind  $v_h = 10$  m/s blowing horizontally. The air resistance in that case is proportional to the velocity of the sphere relative to the air, so that  $\bar{f} = -c(\bar{v} + v_h\bar{i})$ .

**EXERCISE 2.24** The diagram shows a small ball that is pushed in the vertical plane along a hill whose elevation is  $y = H \sin(\pi x/L)$ . The motion is actuated by an angle arm that translates horizontally at constant speed  $u$ . It may be assumed that the ball remains in contact with the hill.



Exercise 2.24

(a) Derive expressions for the velocity and acceleration of the ball as functions of its horizontal distance  $x$  from the origin. (b) Determine the maximum speed  $v$  of the ball and the value(s) of  $x$  at which it occurs. (c) Determine the maximum acceleration magnitude of the ball and the value(s) of  $x$  at which it occurs. (d) What is the largest value of  $u$  for which the ball will remain in contact with the hill when  $x = L/2$ ? Friction is negligible, but gravity is not.

**EXERCISE 2.25** For the system in Exercise 2.24 determine as a function of  $x$  the forces exerted on the sphere by the arm and the hill.

**EXERCISE 2.26** The current flowing through the coiled wire sets up a magnetic field  $\bar{B}$  that is essentially constant in magnitude and parallel to the axis of the coil, so  $\bar{B} = B\bar{k}$ . The force acting on a charged particle moving through this field at velocity  $\bar{v}$  is given by  $F = \beta\bar{v} \times \bar{B}$ , where  $\beta$  is a constant. Suppose such a particle is injected into this field at the origin, with an arbitrary initial velocity. Derive an expression for the position of this particle as a function of time, and identify the corresponding path. Gravity is negligible.


**EXERCISE 2.27** Use the formula for velocity in cylindrical coordinates to solve Exercise 1.8.

**EXERCISE 2.28** A ball rolls on the interior of a paraboloid of revolution given by  $x^2 + y^2 = cz$ . The angle of rotation about the  $z$  axis is  $\theta = \gamma \sin(\lambda t)$ , and the elevation

of the ball is  $z = \beta\lambda^2 t^2$ , where  $\beta$ ,  $\gamma$ , and  $\lambda$  are constants. Determine the velocity and acceleration when  $t = 4\pi/3\lambda$ .


**EXERCISE 2.29** In an Eulerian description of fluid flow, particle velocity components are described as functions of the current position of a particle. The polar velocity components of fluid particles in a certain flow are known to be  $v_R = (A/R)\cos\theta$ ,  $v_\theta = (A/R)\sin\theta$ , where  $R, \theta$  are the polar coordinates of the particle. Determine the corresponding expressions for the acceleration.

**EXERCISE 2.30** The device in the sketch rotates about the vertical axis at  $\omega = 1800$  rev/min, and the angle locating the arms relative to the vertical is known to vary as  $\theta = (\pi/3)\sin(120t)$  rad, where  $t$  is in units of seconds. Determine the velocity and the acceleration of sphere  $A$  as a function of time. Then evaluate these expressions for the instants when the elevation of the sphere is a maximum and a minimum.




Exercise 2.30

**EXERCISE 2.31** The vertical shaft rotates at the constant rate  $\Omega$ , and the elevation of pin  $A$  is constant. End  $B$  of the bar slides over the base table, which translates upward at the constant speed  $u$ . Describe the velocity and acceleration of end  $B$  of the bar in terms of  $u, \Omega, L$ , and  $\theta$ .




Exercise 2.31

**EXERCISE 2.32** The device in the sketch is a flyball governor, which has been used to control the rotation rate of an engine. The concept is that increasing the rotation rate causes the spheres to move outward, thereby causing the vertical rod to move downward, which may be sensed magnetically. Consider a situation in which the angular speed  $\omega$  is unsteady and the vertical velocity of the rod,  $u$ , is constant. Describe the acceleration of a ball in terms of  $\omega, \dot{\omega}, \theta$ , and  $u$ .



Exercise 2.32

**EXERCISE 2.33** A small block whose mass is 400 g slides inside a right circular cone whose axis is vertical. At a certain instant the block is at  $r = 200$  m, with  $\dot{r} = -10$  m/s and  $\ddot{r} = 0$ . The block's rotation rate about the cone's axis is observed to be constant at 40 rad/s. Determine the components of the force tangent and normal to the surface required to obtain this motion.




Exercise 2.33

## Homework Problems

87

**EXERCISE 2.34** The cable, whose length is 300 mm, is fastened to the 500-g block. Clockwise rotation of the arm at a constant angular speed of 5 rad/s causes the block to slide outward. The motion occurs in the vertical plane, and the coefficient of sliding friction is 0.4. Determine the tensile force in the cable and the force exerted by the block on the walls of the groove when  $\theta = 53.1301^\circ$ .




Exercise 2.34

**EXERCISE 2.35** Derive the formulas for velocity and acceleration in spherical coordinates by following the formulation using stretch ratios.


**EXERCISE 2.36** Example 2.9 derived the unit vectors for hyperbolic-elliptic coordinates. Derive the corresponding formulas for velocity and acceleration.

**EXERCISE 2.37** Toroidal coordinates  $(\rho, \theta, \psi)$  are useful in situations in which it is desired to describe movement relative to a reference circle, which is the case for magnetohydrodynamic studies in the fusion reactor known as a tokamak. Let  $R$  be the radius of this reference circle. Then the transformation to Cartesian coordinates is  $x = (R + \rho \cos \psi) \cos \theta$ ,  $y = (R + \rho \cos \psi) \sin \theta$ ,  $z = \rho \sin \psi$ . Derive expressions for the unit vectors for this coordinate system and for the derivatives of the unit vectors with respect to each toroidal coordinate. Then obtain the toroidal coordinate expressions for velocity and acceleration.



Exercise 2.37

**EXERCISE 2.38** A small block slides inside a cone whose apex angle is  $\beta = 53.13^\circ$ . Because angular momentum about the vertical axis of the cone is conserved, the block spins about the  $z$  axis such that  $R^2\dot{\theta} = 5 \text{ m}^2/\text{s}$ , and the vertical motion is observed to be a constant acceleration given by  $z = 0.99 - 3t^2 \text{ m}$ . For the instant when  $z = 0.24 \text{ m}$ , determine the velocity and acceleration of the block.



Exercise 2.38

**EXERCISE 2.39** The instantaneous velocity of a point is  $\vec{v} = 10\vec{i} - 4\vec{j} + 6\vec{k} \text{ m/s}$ , and the acceleration is  $\vec{a} = -30\vec{i} - 25\vec{j} + 15\vec{k} \text{ m/s}^2$ . Determine the corresponding speed, rate of change of the speed, and the radius of curvature of the path.

**EXERCISE 2.40** The elevation of the center of mass of an automobile following an extremely bumpy road is observed to be  $y = 0.1 \sin(\pi x/3)$ , where  $x$  and  $y$  are the horizontal and vertical coordinates in meters. At  $x = 1 \text{ m}$  the vehicle's speed is 20 m/s, and

the speed at that position is decreasing at  $5 \text{ m/s}^2$ . Determine the horizontal and vertical components of the acceleration at that instant.


**EXERCISE 2.41** Polar coordinates in the  $XY$  plane are defined by the radial distance  $R$  and the polar angle  $\theta$  measured from the  $x$  axis. Derive expressions for the velocity and acceleration in terms of components relative to  $xyz$  by considering  $\vec{r}_{P/O} = R\cos\theta\vec{i} + R\sin\theta\vec{j}$  to be a parametric description of the path based on knowing  $R(\theta)$  and  $\theta(t)$ . Then obtain the polar coordinate representations of velocity and acceleration by transforming the  $xyz$  representation.

**EXERCISE 2.42** At a certain instant, the position, velocity, and acceleration of a point are observed to be

$$\vec{r} = 2000\vec{i} - 1000\vec{j} + 2000\vec{k} \text{ m}, \quad \vec{v} = 100\vec{i} + 150\vec{j} + 200\vec{k} \text{ m/s}, \quad \vec{a} = 30\vec{j} - 50\vec{k} \text{ m/s}^2.$$

Cylindrical coordinates for the system are  $(R, \theta, z)$  with  $\theta$  defined as the azimuthal angle in the  $xy$  plane, measured relative to the  $x$  axis. (a) For this instant determine the speed, the rate at which the speed is changing, and the direction of the normal vector pointing toward the path's center of curvature. (b) Determine the values of  $\theta$ ,  $\dot{\theta}$ , and  $\ddot{\theta}$  at this instant.


**EXERCISE 2.43** A satellite is in an orbit about the Earth. The magnitude of the acceleration of this body is  $g(R_e/R)^2$ , where  $R$  is the distance from the body to the center of the Earth,  $R_e = 6370 \text{ km}$  is the radius of the Earth, and  $g = 9.807 \text{ m/s}^2$ . At the position shown, the speed of the body is  $v = 27\,000 \text{ km/h}$ . (a) Determine the rate of change of the speed and the radius of curvature of the orbit at this position. (b) Determine  $\dot{R}$ ,  $\ddot{R}$ ,  $\dot{\theta}$ , and  $\ddot{\theta}$  at this position.



Exercise 2.43

**EXERCISE 2.44** Observation of a small mass attached to the end of the flexible bar reveals that the path of the particle is essentially an ellipse in the horizontal plane. The Cartesian coordinates for this motion are measured as  $x = A\sin(\theta)$ ,  $y = 2A\cos(\theta)$ ,  $\theta = \omega t$ , where  $A$  and  $\omega$  are constants. Determine the speed, the rate of change of the speed, and the normal acceleration at the instants when  $\omega t = 0, \pi/3$ , and  $\pi/2$ .

**EXERCISE 2.45** Pin  $P$  slides inside the 400-mm-radius groove at a constant rate of  $8 \text{ m/s}$ . This motion is actuated by arm  $AB$ . Determine the rotation rate of this arm and the rate of change of that rate when (a)  $\theta = 90^\circ$ , (b)  $\theta = 135^\circ$ .




Exercise 2.45



## Homework Problems

89

**EXERCISE 2.46** A radar station at the origin measures the azimuth angle  $\theta$ , the elevation angle  $\lambda$ , and the radial distance  $r$  to a target. At the instant when a high-performance aircraft is at point  $B$  it has a velocity of 500 m/s directed from point  $B$  to point  $A$  and an acceleration of  $8g$  directed upward. Determine the values of  $\dot{r}$ ,  $\ddot{r}$ ,  $\dot{\lambda}$ ,  $\ddot{\lambda}$ ,  $\dot{\theta}$ , and  $\ddot{\theta}$  that are observed at this location.




Exercises 2.46 and 2.47

**EXERCISE 2.47** A radar station at the origin measures the azimuth angle  $\theta$ , the elevation angle  $\lambda$ , and the radial distance  $r$  to a target, as shown in the sketch. At the instant when an aircraft is at location  $B$ , it is observed that  $\dot{r} = -400$  m/s,  $\ddot{r} = 20$  m/s<sup>2</sup>,  $\dot{\lambda} = 0.2$  rad/s,  $\ddot{\lambda} = 0$ ,  $\dot{\theta} = -0.1$  rad/s, and  $\ddot{\theta} = 0$ . Determine the corresponding speed, rate of change of the speed, and normal acceleration at this instant.

**EXERCISE 2.48** An airplane heading eastward is observed to be in a  $20^\circ$  climb at a speed of 2400 km/h. At this instant its acceleration components are  $2g$  eastward,  $5g$  northward, and  $1.5g$  downward. Determine the rate of change of the speed, as well as the radius of curvature and the location relative to the airplane of the center of curvature of the path.


**EXERCISE 2.49** A particle follows a planar path such that the azimuthal dependence of the radial distance from a fixed reference point is a known function  $R(\theta)$ . It is observed that  $\dot{\theta}$  is constant. Derive expressions for the velocity and acceleration of the particle. Then use those results to derive an expression for the radius of curvature of a path in polar coordinates.

**EXERCISE 2.50** A wheel, whose radius is  $r$ , rolls without slipping. A point on the perimeter of the wheel follows a cycloidal path, described in parametric form by  $x = r(\xi - \sin \xi)$ ,  $y = -r \cos \xi$ . The parameter  $\xi$  is observed to depend on time according to  $\xi = ct$ . Derive expressions for the speed and rate of change of the speed of this point as functions of  $\xi$ . Also determine the radius of curvature of the cycloid as a function of  $\xi$ .




Exercise 2.50

**EXERCISE 2.51** A cable that passes through a hole at point  $A$  is pulled inward at the constant rate of 25 m/s, thereby causing the 0.2-kg collar to move along the circular guide bar. The system is situated in the vertical plane. (a) Determine the speed and the rate of change of the speed of the slider at the instant shown in the sketch. (b) If the coefficient of sliding friction is  $\mu = 0.4$ , evaluate the corresponding tension in the cable.




Exercise 2.51

**EXERCISE 2.52** A collar slides along a guide bar that is bent to the shape of a parabola,  $y = 8x^2$ , where  $x$  and  $y$  are measured in meters. The system lies in the horizontal plane. The motion is actuated by pulling on a cable attached to the collar and passing through a slot. The rate at which the cable is pulled inward is a constant speed  $u$ . (a) For the position  $x = 1/4$  m determine the velocity and acceleration of the collar in terms of  $u$ . (b) Determine the tensile force in the cable at  $x = 1/4$  m.




Exercise 2.52

**EXERCISE 2.53** Collar  $C$  is pushed along the guide bar defined by  $y = 2(1 - 0.25x^2)$ , where  $x$  and  $y$  have units of meters. The angular speed of arm  $AB$  that actuates the motion is the constant value  $\omega = 20$  rad/s, so  $\theta = \omega t$ . Determine the forces exerted on the collar by arm  $AB$  and the guide bar at  $x = 1$  m. The mass of the collar is 2 kg, and gravitational effects are ignorable.



Exercise 2.53

**EXERCISE 2.54** A hydraulic piston in arm  $AB$  controls the arm's length, thereby moving the collar. Guide bar  $CDE$  is circular, and it lies in the vertical plane. At the highest position  $D$  it is known that  $\dot{L} = 10$  m/s and  $\ddot{L} = 0$ . Determine the speed of the collar and the rate of change of the speed at that location.



Exercise 2.54

## CHAPTER 3

# Relative Motion

When we ride in an automobile or airplane, the reference frame for our observations is moving. If we wish to use such observations to formulate Newton's Laws, we need to convert them to an inertial reference frame. More fundamentally, the basic fact that the points in a moving rigid body are stationary as viewed from that body is a vital aspect. In this chapter we develop the ability to correlate observations of position, velocity, and acceleration from fixed and moving reference frames.


### 3.1 COORDINATE TRANSFORMATIONS

It is standard terminology to refer to any quantity that is measured relative to a fixed reference frame as *absolute*, whereas quantities measured with respect to any moving reference frame are *relative*. Figure 3.1 depicts a general situation in which point  $P$  is being observed from a moving reference frame  $xyz$  whose motion we presumably know, whereas  $XYZ$  is a fixed reference frame. It is apparent from Fig. 3.1 that one can arrive at the absolute position  $\vec{r}_{P/O}$  by proceeding first to the  $xyz$  origin along  $\vec{r}_{O'/O}$ , then following the relative position  $\vec{r}_{P/O'}$ , so that

$$\vec{r}_{P/O} = \vec{r}_{O'/O} + \vec{r}_{P/O'}. \quad (3.1.1)$$

Despite the simple appearance of this relation, it embodies many of the issues that we generally encounter. Both  $\vec{r}_{P/O}$  and  $\vec{r}_{P/O'}$  describe position as seen from a specific reference frame. Each vector could be represented in terms of components relative to the coordinate axes of its associated reference frame. However, if we are to evaluate the sum by adding like components, rather than by a graphically based procedure, then the components of each vector must be described with respect to a common set of unit vectors. In other words, although a vector might describe the perspective of an observer on a specific reference frame, that vector may be described in terms of components relative to the axes of any reference frame.

As an aid to representing each of the vectors in Eq. (3.1.1), we introduce the  $x'y'z'$  reference frame in Fig. 3.1, whose origin always coincides with point  $O'$ , but whose axes always remain parallel to the respective fixed axes of  $XYZ$ . Such a reference frame executes a *translational motion*. The  $x'y'z'$  coordinates of point  $P$  are  $(x'_P, y'_P, z'_P)$ , and the



**Figure 3.1.** Fixed and moving reference frames for observing the position of a point.

$XYZ$  coordinates of point  $O'$  are  $(X_{O'}, Y_{O'}, Z_{O'})$ . The corresponding position vectors therefore are

$$\bar{r}_{O'/O} = X_{O'}\bar{I} + Y_{O'}\bar{J} + Z_{O'}\bar{K}, \quad \bar{r}_{P/O'} = x'_P\bar{i}' + y'_P\bar{j}' + z'_P\bar{k}'. \quad (3.1.2)$$

Because of the parallelism of the  $\bar{I}\bar{J}\bar{K}$  and  $\bar{i}'\bar{j}'\bar{k}'$  directions, a component description of Eq. (3.1.1) leads to

$$X_P = X_{O'} + x'_P, \quad Y_P = Y_{O'} + y'_P, \quad Z = Z_{O'} + z'_P. \quad (3.1.3)$$

This conversion between coordinates is referred to as a *translation transformation*.

This transformation is useful if we know the coordinates of point  $P$  relative to the translating  $x'y'z'$  reference frame. However, the more likely circumstance is that we would know the position coordinates  $(x_P, y_P, z_P)$  relative to the rotating axes of the  $xyz$  reference frame. Such would be the case when we describe position in terms of forward/back, left/right, and up/down relative to the cabin of an airplane, or when we locate a point in a piece of machinery by referring to the engineering drawings. This complicates the task of adding  $\bar{r}_{O'/O}$  and  $\bar{r}_{P/O'}$ , because the directions used to represent the vectors are not parallel. Determining the  $x'y'z'$  coordinates of point  $P$  corresponding to known  $xyz$  coordinates requires a rotation transformation.

### 3.1.1 Rotation Transformations

We consider a general situation in which a vector is described in terms of components relative to the axes of two coordinate systems,  $xyz$  and  $x'y'z'$ , that have a common origin. Figure 3.2 depicts the *direction angles*  $\alpha, \beta, \gamma$  between the  $x'$  axis and each of the  $xyz$  axes. An examination of Fig. 3.2 shows that the values of the direction angles should be limited to the range  $0 \leq \alpha, \beta, \gamma \leq \pi$  to avoid ambiguity. The components of  $\bar{i}'$  are its projections onto  $\bar{i}, \bar{j}$ , and  $\bar{k}$ , which are determined from the direction angles according to

$$\begin{aligned} \bar{i}' &= (\bar{i}' \cdot \bar{i})\bar{i} + (\bar{i}' \cdot \bar{j})\bar{j} + (\bar{i}' \cdot \bar{k})\bar{k} \\ &= (\cos \alpha)\bar{i} + (\cos \beta)\bar{j} + (\cos \gamma)\bar{k}. \end{aligned} \quad (3.1.4)$$

### 3.1 Coordinate Transformations

93




Figure 3.2. Direction angles  $\alpha$ ,  $\beta$ , and  $\gamma$  for a line.

This expression indicates that the cosines of the direction angles are more significant to our analysis: They are the *direction cosines*. We obviously are equally interested in all unit vectors, so we

Define  $\ell_{p'q}$  to be the cosine of the angle between axis  $p'$  and axis  $q$ , with  $p$  and  $q$  representing  $x$ ,  $y$ , or  $z$ .

Extending Eq. (3.1.4) to the other unit vectors then yields

$$\begin{aligned}\bar{i}' &= \ell_{x'x}\bar{i} + \ell_{x'y}\bar{j} + \ell_{x'z}\bar{k}, \\ \bar{j}' &= \ell_{y'x}\bar{i} + \ell_{y'y}\bar{j} + \ell_{y'z}\bar{k}, \\ \bar{k}' &= \ell_{z'x}\bar{i} + \ell_{z'y}\bar{j} + \ell_{z'z}\bar{k}.\end{aligned}\tag{3.1.5}$$

It is convenient to rewrite these equations in matrix form as

$$\begin{bmatrix} \bar{i}' & \bar{j}' & \bar{k}' \end{bmatrix}^T = [R] \begin{bmatrix} \bar{i} & \bar{j} & \bar{k} \end{bmatrix}^T,\tag{3.1.6}$$

where

$$[R] = \begin{bmatrix} \ell_{x'x} & \ell_{x'y} & \ell_{x'z} \\ \ell_{y'x} & \ell_{y'y} & \ell_{y'z} \\ \ell_{z'x} & \ell_{z'y} & \ell_{z'z} \end{bmatrix}.\tag{3.1.7}$$

The matrix  $[R]$  is the *rotation transformation*. It is a generalization of the conversion between coplanar pairs of unit vectors that we employed to discuss mixed kinematical descriptions in Section 2.4.

Several important properties of  $[R]$  follow from the fact that  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  are an orthogonal set of unit vectors, as are  $\bar{i}'$ ,  $\bar{j}'$ , and  $\bar{k}'$ . Suppose that we were to follow parallel steps to the preceding in order to establish the transformation  $[R']$  describing the unit vectors  $\bar{i}$ ,  $\bar{j}$ ,  $\bar{k}$  in terms of their components with respect to  $\bar{i}'$ ,  $\bar{j}'$ ,  $\bar{k}'$ . By direct analogy with Eqs. (3.1.6) and (3.1.7) we find that the inverse transformation  $[R']$  is described by

$$\begin{bmatrix} \bar{i} & \bar{j} & \bar{k} \end{bmatrix}^T = [R'] \begin{bmatrix} \bar{i}' & \bar{j}' & \bar{k}' \end{bmatrix}^T,\tag{3.1.8}$$

where the elements of  $[R']$  are the corresponding direction cosines between  $\bar{i}$ ,  $\bar{j}$ , or  $\bar{k}$  and  $\bar{i}'$ ,  $\bar{j}'$ , or  $\bar{k}'$ . For example,  $R'_{1,2} = \ell_{xy'}$ . Because  $\ell_{xy'} \equiv \ell_{y'z}$ , it follows that  $R'_{1,2} = R_{2,1}$ . More generally, the definition of the direction cosines leads to  $R'_{m,n} = R_{n,m}$ , so that  $[R'] = [R]^T$ .

A different description of  $[R']$  results from solving Eq. (3.1.6) for  $\bar{i}$ ,  $\bar{j}$ ,  $\bar{k}$ , which gives

$$[\bar{i} \ \bar{j} \ \bar{k}]^T = [R]^{-1} [\bar{i}' \ \bar{j}' \ \bar{k}']^T. \quad (3.1.9)$$

A comparison of Eqs. (3.1.8) and (3.1.9) shows that  $[R'] = [R]^{-1}$ . Thus we find that

*The transformation matrix  $[R']$  converting  $\bar{i}'$ ,  $\bar{j}'$ , and  $\bar{k}'$  to  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  is the inverse of the matrix  $[R]$  converting  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  to  $\bar{i}'$ ,  $\bar{j}'$ , and  $\bar{k}'$ . This inverse transformation may be evaluated by taking the transpose of the original transformation,*

$$[R'] = [R]^{-1} = [R]^T. \quad (3.1.10)$$

Equation (3.1.7) defines the rows of  $[R]$  to be the direction cosines of one of the primed unit vectors relative to the unprimed set. Similarly, the columns of  $[R]$  consist of the direction cosines of an unprimed unit vector with respect to each of the primed set. Let  $\{i\}$ ,  $\{j\}$ , etc., denote columns holding the direction cosines of the associated unit vector with respect to the other set of directions. Then we may write  $[R]$  in partition form in either of two ways,

$$[R] = \begin{bmatrix} \{i'\}^T \\ \{j'\}^T \\ \{k'\}^T \end{bmatrix} = \begin{bmatrix} \{i\} & \{j\} & \{k\} \end{bmatrix}. \quad (3.1.11)$$

The rules for products of partitioned matrices indicate that the partitions behave like single elements if the partitions are conformable (that is, consistently dimensioned). According to the first of Eqs. (3.1.11), it must be that

$$\begin{aligned} [R][R]^T &= \begin{bmatrix} \{i'\}^T \\ \{j'\}^T \\ \{k'\}^T \end{bmatrix} \begin{bmatrix} \{i\} & \{j\} & \{k\} \end{bmatrix} \\ &= \begin{bmatrix} \{i'\}^T \{i\} & \{i'\}^T \{j\} & \{i'\}^T \{k\} \\ \{j'\}^T \{i\} & \{j'\}^T \{j\} & \{j'\}^T \{k\} \\ \{k'\}^T \{i\} & \{k'\}^T \{j\} & \{k'\}^T \{k\} \end{bmatrix} = [U], \end{aligned} \quad (3.1.12)$$

where  $[U]$  is the identity (unit) matrix. The final result stems from the fact that each element of the product matrix is the matrix representation of a dot product, and the

### 3.1 Coordinate Transformations

95

unprimed unit vectors are mutually orthogonal. A similar expression results if we use the second form in Eq. (3.1.11) to form  $[R]^T [R]$ , specifically

$$[R]^T [R] = \begin{bmatrix} \{i\}^T \{i\} & \{i\}^T \{j\} & \{i\}^T \{k\} \\ \{j\}^T \{i\} & \{j\}^T \{j\} & \{j\}^T \{k\} \\ \{k\}^T \{i\} & \{k\}^T \{j\} & \{k\}^T \{k\} \end{bmatrix} = [U], \quad (3.1.13)$$

where the final form is a consequence of the mutual orthogonality of the unprimed unit vectors. Thus a matrix having the property that  $[R]^{-1} = [R]^T$  is said to be *orthonormal*.

The fact that  $[R][R]^T = [U]$  gives rise to a useful property. Recall from matrix algebra that the determinant of a product of matrices is identical to the product of the individual determinants. Furthermore, the determinant of  $[R]$  is identical to the determinant of  $[R]^T$ . Simultaneous satisfaction of both properties, in combination with the requirement that both  $xyz$  and  $x'y'z'$  are right-handed coordinate systems,\* leads to the conclusion that

$$|[R]| = 1. \quad (3.1.14)$$

One use of this property is to check computations.

Because a dot product is independent of the order in which the product is formed, Eq. (3.1.12) consists of six independent elements, whose specific form is

$$\ell_{p'x}\ell_{q'x} + \ell_{p'y}\ell_{q'y} + \ell_{p'z}\ell_{q'z} = \delta_{pq}, \quad p, q = x, y, \text{ or } z, \quad (3.1.15)$$

where  $\delta_{pq}$  denotes the Kronecker delta;  $\delta_{pq} = 1$  if  $p = q$  and  $\delta_{pq} = 0$  otherwise. Because there are six independent combinations of  $p$  and  $q$  in the preceding, it follows that there are six equations relating the nine direction cosines. Consequently, there are only three independent direction angles. However, the selection of which angles are independent is not entirely arbitrary. For example, the values of  $\alpha$ ,  $\beta$ , and  $\gamma$  in Fig. 3.2 are not independent because  $\cos^2 \alpha + \cos^2 \beta + \cos^2 \gamma = 1$ . This restriction arises because these three angles locate only one axis.

In Eqs. (3.1.6) the unit vectors of one coordinate system are described in terms of the unit vectors of another. However,  $[R]$  also transforms the components of vectors. To see this we consider an arbitrary vector  $\bar{A}$ , which may be described in terms of its components with respect to either set of unit vectors,

$$\bar{A} = A_{x'}\bar{i}' + A_{y'}\bar{j}' + A_{z'}\bar{k}' = A_x\bar{i} + A_y\bar{j} + A_z\bar{k}. \quad (3.1.16)$$

A matrix representation of this expression is

$$\bar{A} = \begin{bmatrix} \bar{i}' & \bar{j}' & \bar{k}' \end{bmatrix} \begin{Bmatrix} A_{x'} \\ A_{y'} \\ A_{z'} \end{Bmatrix} = \begin{bmatrix} \bar{i} & \bar{j} & \bar{k} \end{bmatrix} \begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix}. \quad (3.1.17)$$

\* Equation (3.1.14) is also correct if both coordinate systems are left-handed, whereas  $[R] = -1$  if  $xyz$  and  $x'y'z'$  have different parities.

To eliminate the primed unit vectors, we substitute Eq. (3.1.9) into the right side of Eq. (3.1.17). To do so we must use the property that the transpose of a matrix product is the reversed product of the transpose of each matrix. According to the orthonormal property,  $[R]^{-1}]^T = [R]$ , so we have

$$\begin{bmatrix} \bar{i}' & \bar{j}' & \bar{k}' \end{bmatrix} \begin{Bmatrix} A_{x'} \\ A_{y'} \\ A_{z'} \end{Bmatrix} = \begin{bmatrix} \bar{i}' & \bar{j}' & \bar{k}' \end{bmatrix} [R] \begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix}. \quad (3.1.18)$$

This must be true for an arbitrary  $\bar{A}$ , which permits us to cancel the row of unit vectors. Thus,

$$\begin{Bmatrix} A_{x'} \\ A_{y'} \\ A_{z'} \end{Bmatrix} = [R] \begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix}. \quad (3.1.19)$$

Kinematically, the position of a point with respect to the origin is of primary importance, in which case the vector components are the Cartesian coordinates of the point with respect to either the fixed  $XYZ$  or the moving  $xyz$ . In some situations we wish to follow a certain point  $P$  on the body, as we would when we monitor the motion of a point in a piece of machinery. In that case the  $(x_P, y_P, z_P)$  values with respect to the body-fixed axes remain constant, and the  $(X_P, Y_P, Z_P)$  coordinates change. In other situations it is necessary to determine how a point  $P$  that does not move is seen from the perspective of the moving body. Then it is  $(X_P, Y_P, Z_P)$  that remain constant, and  $(x_P, y_P, z_P)$  change. Either situation can be addressed once we have determined the transformation matrix  $[R]$  that converts  $\bar{I}\bar{J}\bar{K}$  components to  $\bar{i}\bar{j}\bar{k}$  components.


We have seen that knowledge of  $[R]$  enables us to fully characterize a vector in terms of alternative sets of components. The following example determines a transformation directly from the orthonormal properties. Sometimes there are simpler procedures for such a determination, which we will take up in the following sections.

**EXAMPLE 3.1** The positions of two points are known to be  $\bar{r}_A = -250\bar{i} + 400\bar{j} - 500\bar{k}$  mm relative to the  $xyz$  coordinate system described in the sketch and  $\bar{r}_B = 400\bar{I} - 600\bar{J} + 200\bar{K}$  mm relative to the  $XYZ$  coordinate system. Determine the position coordinates of each point relative to the coordinate system not given, and also determine the distance between the points.



### 3.1 Coordinate Transformations

97



Example 3.1

**SOLUTION** This example illustrates most of the basic operations associated with rotation transformations. According to the sketch the  $y$  axis lies in the  $XZ$  plane such that

$$\bar{j} = \cos 30^\circ \bar{i} + \sin 30^\circ \bar{k}.$$

The only other piece of information conveyed by the sketch is that the  $z$  axis is depressed  $20^\circ$  below the  $XY$  plane. Thus the  $Z$  component of  $\bar{k}$  is  $-\sin 20^\circ$ . Let  $\theta$  denote the angle between the  $Y$  axis and the projection of the  $z$  axis onto the  $XY$  plane. Because  $\bar{k}$  has unit magnitude, the length of its projection onto this plane is  $\cos 20^\circ$ , from which it follows that

$$\bar{k} = \cos 20^\circ (\sin \theta \bar{i} + \cos \theta \bar{j}) - \sin 20^\circ \bar{k}.$$

The angle  $\theta$  is set by the condition that  $\bar{j}$  and  $\bar{k}$  are orthogonal, so that their dot product is zero,

$$\bar{j} \cdot \bar{k} = \cos 30^\circ \cos 20^\circ \sin \theta - \sin 30^\circ \sin 20^\circ = 0,$$

from which we find

$$\theta = \sin^{-1}(\tan 30^\circ \tan 20^\circ) = 0.2117 \text{ rad} = 12.131^\circ.$$

The preceding description of  $\bar{k}$  correspondingly gives

$$\bar{k} = 0.19747 \bar{i} + 0.91871 \bar{j} - 0.34202 \bar{k}.$$

The fact that  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  are a set of orthonormal unit vectors enables us to directly determine  $\bar{i}$  from a cross product:

$$\bar{i} = \bar{j} \times \bar{k} = -0.45936 \bar{i} + 0.39493 \bar{j} + 0.79563 \bar{k}.$$

The rows of the transformation from  $XYZ$  to  $xyz$  are the components of the unit vectors of  $xyz$  relative to  $XYZ$ , so we have found that

$$[R] = \begin{bmatrix} -0.45936 & 0.39493 & 0.79563 \\ 0.86603 & 0 & 0.500 \\ 0.19747 & 0.91871 & -0.34202 \end{bmatrix}.$$

We use  $[R]^T$  to transform the  $xyz$  coordinates of point  $A$ , and  $[R]$  to transform the  $XYZ$  coordinates of point  $B$ :

$$\begin{aligned} \begin{Bmatrix} X_A \\ Y_A \\ Z_A \end{Bmatrix} &= [R]^T \begin{Bmatrix} -250 \\ 400 \\ -500 \end{Bmatrix} = \begin{Bmatrix} 362.52 \\ -558.09 \\ 172.10 \end{Bmatrix} \text{ mm}, \\ \begin{Bmatrix} x_B \\ y_B \\ z_B \end{Bmatrix} &= [R] \begin{Bmatrix} 400 \\ -600 \\ 200 \end{Bmatrix} = \begin{Bmatrix} -261.58 \\ 446.41 \\ -540.64 \end{Bmatrix} \text{ mm}. \end{aligned} \quad \triangleleft$$

The distance between the points is the magnitude of the position vector between them, which may be constructed from  $\bar{r}_{B/A} = \bar{r}_{B/O} - \bar{r}_{A/O}$ . We calculate this difference by taking the difference of components with respect to the  $XYZ$  coordinate system:

$$\{r_{B/A}\} = \begin{Bmatrix} X_B - X_A \\ Y_B - Y_A \\ Z_B - Z_A \end{Bmatrix} = \begin{Bmatrix} 37.48 \\ -41.91 \\ 27.90 \end{Bmatrix}.$$

The distance  $|\bar{r}_{B/A}|$  may be determined from the matrix implementation of a dot product, which gives

$$\begin{aligned} |\bar{r}_{B/A}|^2 &= [37.48 \quad -41.91 \quad 27.90] \begin{Bmatrix} 37.48 \\ -41.91 \\ 27.90 \end{Bmatrix}, \\ |\bar{r}_{B/A}| &= 62.77 \text{ mm}. \end{aligned} \quad \triangleleft$$

This result should be the same as what would be obtained if we described  $\bar{r}_{B/A}$  in terms of  $xyz$  components. Doing so would have given

$$\begin{aligned} \{r'_{B/A}\} &= \begin{Bmatrix} x_B - x_A \\ y_B - y_A \\ z_B - z_A \end{Bmatrix} = \begin{Bmatrix} -11.58 \\ 46.41 \\ -40.64 \end{Bmatrix}, \\ |\bar{r}'_{B/A}|^2 &= [-11.58 \quad 46.41 \quad -40.64] \begin{Bmatrix} -11.58 \\ 46.41 \\ -40.64 \end{Bmatrix}, \\ |\bar{r}'_{B/A}| &= 62.77 \text{ mm}. \end{aligned} \quad \triangleleft$$

### 3.1 Coordinate Transformations

99

#### 3.1.2 Rotation Sequences

One use of a moving reference frame is to represent a rigid body in motion. A set of axes  $xyz$  that are attached to the body is said to be *body fixed*. To follow the rotation of the axes we designate  $XYZ$  as the orientation of the body-fixed axes prior to the initiation of motion. Because a translation transformation accounts for the motion of the origin of  $xyz$ , we temporarily consider the origins of  $XYZ$  and  $xyz$  to coincide. Our objective here is to characterize the transformation from  $XYZ$  to the current orientation of  $xyz$  in terms of rotations that the body undergoes. We do this by following successively more complicated types of rotations.

#### Simple Rotations

In a *simple rotation* one of the body-fixed coordinate axes remains stationary. We may picture such a rotation by looking down the stationary axis, because all points move in the plane perpendicular to that axis. To avoid ambiguity, we use the right-hand rule to define the positive sense of rotation. Specifically, one curls the fingers of the right hand in the sense of the rotation. If the extended thumb of that hand points in the positive sense of the rotation axis, then the rotation angle is positive. The three possibilities, involving positive rotation about the  $x$ ,  $y$ , or  $z$  axis, are depicted in Fig. 3.3. We use a subscript to denote the axis for the simple rotation. Inspection of Fig. 3.3 gives the direction angles of  $xyz$  relative to  $XYZ$ , which leads to

$$\begin{aligned} [R_x] &= \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \theta_x & \sin \theta_x \\ 0 & -\sin \theta_x & \cos \theta_x \end{bmatrix}, & [R_y] &= \begin{bmatrix} \cos \theta_y & 0 & -\sin \theta_y \\ 0 & 1 & 0 \\ \sin \theta_y & 0 & \cos \theta_y \end{bmatrix}, \\ [R_z] &= \begin{bmatrix} \cos \theta_z & \sin \theta_z & 0 \\ -\sin \theta_z & \cos \theta_z & 0 \\ 0 & 0 & 1 \end{bmatrix}. \end{aligned} \quad (3.1.20)$$




Figure 3.3. Simple rotations about each of the coordinate axes.

Note that a rotation that is opposite the sense of the right-hand rule corresponds to a negative value of the respective angle in the preceding equations. This leads to an interesting observation. Each transformation for the negative angle is the transpose of the transformation of the positive angle, that is


$$[R_x(-\theta_x)] = [R_x(+\theta_x)]^T, \quad [R_y(-\theta_y)] = [R_y(+\theta_y)]^T, \quad [R_z(-\theta_z)] = [R_z(+\theta_z)]^T. \quad (3.1.21)$$

This demonstrates that the inverse transformation for a simple rotation merely corresponds to the opposite rotation, which is a fact that is apparent from Fig. 3.3.

### Body-Fixed Rotations

A *spatial rotation* is one in which a new orientation does not result from rotation about a single coordinate axis. The first situation we treat is that in which the overall rotation can be pictured as a sequence of simple rotations. The ultimate orientation of a coordinate system that undergoes such a rotation clearly will depend on the orientation of each of the simple rotation axes, and the amount of rotation about each axis. It is less apparent that the final alignment of the coordinate axes also is dependent on the sequence in which the individual rotations occur. Two situations commonly arise. The simpler case to describe in words is a *space-fixed* rotation sequence, in which the simple rotation axes have fixed orientations in space. The contrasting situation is a *body-fixed* rotation sequence, in which each simple rotation is about one of the body-fixed axes at the preceding step in the sequence. For example, a body-fixed sequence  $\theta_y, \theta_z, \theta_x$  occurs first about the initial position of the  $y$  axis, then about the  $z$  axis in its new orientation, then about the  $x$  axis in its orientation after the second rotation. Although a body-fixed rotation is more difficult than a space-fixed rotation to describe in words, the transformation for body-fixed rotations is easier to derive.

We begin by following a specific sequence of body-fixed rotations, after which we generalize the result. The first rotation  $\theta_x$  occurs about the original orientation of the  $x$  axis, and the second rotation  $\theta_z$  occurs about the position of the  $z$  axis after the first rotation. In Fig. 3.4(a), the stationary  $XYZ$  system marks the initial orientation of  $xyz$ .



**Figure 3.4.** Body-fixed rotations: (a) rotation by  $\theta_x$  about the original  $x$  axis, followed by (b) rotation by  $\theta_z$  about the  $z$  axis resulting from the first rotation.

### 3.1 Coordinate Transformations

101

We mark the orientation of  $xyz$  after the  $\theta_x$  rotation as  $x_1y_1z_1$ . The transformation describing the first rotation is given by

$$\begin{Bmatrix} A_{x_1} \\ A_{y_1} \\ A_{z_1} \end{Bmatrix} = [R_x] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix}, \quad (3.1.22)$$

where we may readily construct  $[R_x]$  because it describes a simple rotation.

The result of the second rotation is depicted in Fig. 3.4(b). The  $\theta_z$  rotation moves  $xyz$  from its intermediate orientation coincident with  $x_1y_1z_1$  to its final orientation. Because this corresponds to a single axis rotation about the  $z_1$  axis, we have

$$\begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix} = [R_z] \begin{Bmatrix} A_{x_1} \\ A_{y_1} \\ A_{z_1} \end{Bmatrix}. \quad (3.1.23)$$

Substitution of Eq. (3.1.22) into Eq. (3.1.23) leads to the overall transformation matrix  $[R]$ ,

$$\begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix} = [R] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix}, \quad [R] = [R_z][R_x]. \quad (3.1.24)$$

Additional rotations about any of the  $xyz$  axes will merely extend the preceding by inserting additional premultiplication factors. Furthermore, we observe that the details of the individual transformations were not used, so the result is valid for any sequence of rotations, rather than being limited to simple rotations. We let  $[R_i]$  denote the transformation describing the  $i$ th rotation. This enables us to conclude that

*If  $xyz$  is a coordinate system that undergoes a sequence of rotations about body-fixed axes, and  $XYZ$  marks the initial orientation of  $xyz$ , then the transformation from  $\bar{I}\bar{J}\bar{K}$  components to the final  $\bar{i}\bar{j}\bar{k}$  components is obtained by premultiplying (from right to left) the sequence of transformation matrices for the individual rotations. For  $n$  rotations:*

$$[R] = [R_n] \cdots [R_2][R_1]. \quad (3.1.25)$$

It should be noted that although the preceding is valid for any type of body-fixed rotation, in practice, we usually apply it to simple rotations, that is, rotations about the axes of  $xyz$ . Doing so simplifies the description of the individual transformations.

**EXAMPLE 3.2** Consider the coordinate systems in Example 3.1. The final orientation of  $xyz$  may be obtained from a set of body-fixed rotations, starting from an initial orientation in which  $xyz$  coincides with  $XYZ$ . Describe the axis and angle for each rotation.


**SOLUTION** In addition to illustrating some basic operations, this example demonstrates the versatility provided by decomposing a transformation into a set of simple rotations. Initially  $xyz$  coincides with  $XYZ$ . Because we fully know the final orientation of the  $y$  axis, we begin by imparting a set of rotations that move this axis to where it should be. One way of doing this is first to rotate  $xyz$  about the negative  $Z$  axis by  $90^\circ$  in order to make the  $y$  axis align with the  $X$  axis. This leaves the  $z$  and  $Z$  axes coincident and the  $x$  axis aligned oppositely from the  $Y$  axis. Thus the first transformation is

$$[R_1] = \begin{bmatrix} 0 & -1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 1 \end{bmatrix}.$$

Next we rotate by  $30^\circ$  about the current  $x$  axis, which places the  $y$  axis where it should be. This is a simple rotation transformation given by

$$[R_2] = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos 30^\circ & \sin 30^\circ \\ 0 & -\sin 30^\circ & \cos 30^\circ \end{bmatrix}.$$

It is helpful to sketch the orientation of  $xyz$  after the second rotation.



$x, y, z$  after notation of  $-90^\circ$  about the original  $z$  axis, followed by rotation of  $30^\circ$  about the new  $x$  axis.

Any further rotation should keep the  $y$  axis in place, so we rotate  $xyz$  about its current  $y$  axis. Because the amount of this rotation cannot be ascertained by inspection, we let  $\phi$  denote the angle. The associated simple rotation transformation is

$$[R_3] = \begin{bmatrix} \cos \phi & 0 & -\sin \phi \\ 0 & 1 & 0 \\ \sin \phi & 0 & \cos \phi \end{bmatrix}.$$

### 3.1 Coordinate Transformations

103

The transformation corresponding to these three body-fixed rotations is

$$[R] = [R_3][R_2][R_1] = \begin{bmatrix} 0.5 \sin \phi & -\cos \phi & -0.8660 \sin \phi \\ 0.8660 & 0 & 0.5 \\ -0.5 \cos \phi & -\sin \phi & 0.8660 \cos \phi \end{bmatrix}.$$

The final orientation of the  $z$  axis is such that the angle between it and the  $Z$  axis is  $110^\circ$ , so that  $\ell_{zZ} = \cos 110^\circ$ . Equating this to the (3,3) element of  $[R]$  gives

$$\cos \phi = \frac{\cos 110^\circ}{0.8660} = -0.3949.$$


There are two roots of the preceding in the range  $-180^\circ < \phi \leq 180^\circ$ . To select the appropriate one we observe that the sketch accompanying Example 3.1 indicates that the direction angles from the  $X$  and  $Y$  axes to the  $z$  axis are both acute, which requires that both  $\ell_{zX}$  and  $\ell_{zY}$  be positive. Because these direction cosines are the (3,1) and (3,2) elements of  $[R]$ , the desired root must be such that  $\cos \phi$  and  $\sin \phi$  are both negative, so  $\phi = -113.26^\circ$  is the appropriate root. Evaluation of  $[R]$  corresponding to this value of  $\phi$  shows the result to be the same as  $[R]$  derived in Example 3.1. Thus  $[R]$  may be obtained by a sequence of three body-fixed rotations:  $-90^\circ$  about the  $z$  axis, followed by  $30^\circ$  about the  $x$  axis, concluding with  $-113.26^\circ$  about the  $y$  axis.  $\triangleleft$

#### Space-Fixed Rotations

The derivation of the transformation matrix for a sequence of space-fixed rotations follows a course that parallels the development in the previous section, in that we begin by considering a specific pair of rotations and then generalize the result. The rotations now occur about the axes of the stationary  $XYZ$  coordinate system. In the first rotation,  $\theta_X$ , the  $x$  axis remains coincident with the  $X$  axis. In Fig. 3.5(a)  $x_1y_1z_1$  marks the position of  $xyz$  after the first rotation. Thus the transformation from  $\bar{i}\bar{j}\bar{k}$  components to  $\bar{i}_1\bar{j}_1\bar{k}_1$  components is described by the simple rotation transformation  $[R_X]$  corresponding to angle  $\theta_X$  about the  $X$  axis, so that

$$\begin{Bmatrix} A_{x_1} \\ A_{y_1} \\ A_{z_1} \end{Bmatrix} = [R_X] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix}. \quad (3.1.26)$$

The second rotation, which consists of  $\theta_Z$  about the (fixed)  $Z$  axis, rotates  $x_1y_1z_1$  to  $xyz$ . This movement is difficult to visualize because it does not occur about an axis of either  $x_1y_1z_1$  or  $xyz$ . As an aid to following the rotation, Fig. 3.5(a) shows construction lines  $Ay_1$  and  $Bz_1$ , which are formed by dropping perpendiculars from the tips of the respective axes to the  $Z$  axis. Coordinate system  $x_2y_2z_2$  in Fig. 3.5(b) is defined to coincide with  $XYZ$  prior to the second rotation. The  $Z$  and  $z_2$  axes remain coincident,



**Figure 3.5.** Space-fixed rotations: (a)  $\theta_x$  about the fixed  $X$  axis, followed by (b)  $\theta_z$  about the fixed  $Z$  axis.

so  $\bar{i}_2 \bar{j}_2 \bar{k}_2$  components are related to  $\bar{I} \bar{J} \bar{K}$  components by the simple rotation transformation  $[R_z]$ :

$$\begin{Bmatrix} A_{x_2} \\ A_{y_2} \\ A_{z_2} \end{Bmatrix} = [R_z] \begin{Bmatrix} A_{x_1} \\ A_{y_1} \\ A_{z_1} \end{Bmatrix}. \quad (3.1.27)$$

Now comes the crucial observation: Because  $x_1 y_1 z_1$  and  $x_2 y_2 z_2$  undergo the second rotation in unison, their relative orientation is invariant. Before this rotation  $xyz$  coincided with  $x_1 y_1 z_1$  and  $x_2 y_2 z_2$  coincided with  $XYZ$ . Equation (3.1.26) gives the transformation from  $XYZ$  to  $x_1 y_1 z_1$ , so it also describes the transformation from  $x_2 y_2 z_2$  to  $xyz$ :

$$\begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix} = [R_x] \begin{Bmatrix} A_{x_2} \\ A_{y_2} \\ A_{z_2} \end{Bmatrix}. \quad (3.1.28)$$

To eliminate the components relative to  $x_2 y_2 z_2$ , we substitute Eq. (3.1.27), with the result that

$$\begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix} = [R_x][R_z] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix} = [R] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix}. \quad (3.1.29)$$

We now observe that we never specifically treated  $[R_x]$  and  $[R_z]$  as simple rotations. Furthermore, the pattern would repeat if we were to consider another space-fixed rotation. Consequently, the preceding is generally valid, provided that we use  $[R_j]$  to denote the  $j$ th rotation about a space-fixed axis. We therefore conclude that

*If  $xyz$  is a reference frame that undergoes a sequence of rotations about a set of axes that are fixed in space, and  $xyz$  is initially coincident with  $XYZ$ , then the transformation from  $\bar{I} \bar{J} \bar{K}$  components to  $\bar{i} \bar{j} \bar{k}$  components is obtained by postmultiplying*




### 3.1 Coordinate Transformations

105

(from left to right) the sequence of transformation matrices for the individual rotations. For  $n$  rotations,

$$[R] = [R_1][R_2] \cdots [R_n]. \quad (3.1.30)$$

The similarity of Eqs. (3.1.25) and (3.1.30) is significant. We see that the result of a sequence of body-fixed rotations leads to the same orientation as the reverse sequence of space-fixed rotations, and vice versa. For example, the transformation in Eq. (3.1.29), which was obtained by consideration of a pair of space-fixed rotations  $\theta_X$  followed by  $\theta_Z$ , can be obtained alternatively by a pair of body-fixed rotations. The first such rotation would be  $\theta_Z$  about the  $Z$  axis, and the second rotation would be  $\theta_X$  about the  $x$  axis in its orientation following the first rotation. Both situations are depicted in Fig. 3.6. In this sketch  $x_1y_1z_1$  marks the position of  $xyz$  after the first rotation in each case. It can be seen that, in both cases, the  $x$  axis is situated in the  $XY$  plane at an angle  $\theta_Z$  from the  $X$  axis, the direction angle from the  $Z$  axis to the  $y$  axis is  $\pi/2 - \theta_X$ , and the direction angle from the  $Z$  axis to the  $z$  axis is  $\theta_X$ . These properties lead to the conclusion that the orientation of  $xyz$  relative to  $XYZ$  is the same for each rotation case.



**Figure 3.6.** A pair of rotations about (a) space-fixed rotations  $\theta_X$  followed by  $\theta_Z$ , compared to (b) the body-fixed rotations  $\theta_Z$  followed by  $\theta_X$ .

For a given sequence of simple rotations, the order of multiplication in which  $[R]$  is formed from the individual matrices must be consistent with the type of rotation: pre-multiplication for body-fixed rotations and postmultiplication for space-fixed rotations. In a situation in which the overall rotation involves both types of rotations, we may follow Eqs. (3.1.25) and (3.1.30) by premultiplying for the body-fixed rotations and postmultiplying for the space-fixed rotations. For example, a sequence described by  $[R_1]$  and  $[R_2]$  about body-fixed axes, followed by  $[R_3]$  about a space-fixed axis, then  $[R_4]$  about a body-fixed axis would lead to  $[R] = [R_4][R_2][R_1][R_3]$ . A fundamental property of vectors is that their sum is independent of the order of addition. Because the final rotation transformation depends on the sequence in which the rotations occur, *spatial rotations cannot be represented as vectors*.

**EXAMPLE 3.3** An  $xyz$  coordinate system, which initially coincided with a stationary  $XYZ$  coordinate system, first undergoes a rotation  $\theta_1 = 65^\circ$  about the  $Y$  axis, followed by  $\theta_2 = -145^\circ$  about the  $Z$  axis. Determine (a) the coordinates relative to  $xyz$  in its final orientation of a stationary point at  $X = 2$ ,  $Y = -4$ ,  $Z = 3$  m; (b) the coordinates relative to  $XYZ$  of the point that remains at  $x = 2$ ,  $y = -4$ ,  $z = 3$  m throughout the motion.

**SOLUTION** In addition to illustrating the basic operations associated with space-fixed rotations, this example serves to emphasize the difference between points that are fixed in space and those that are stationary with respect to a moving reference frame. The transformation matrix for this pair of space-fixed rotations is  $[R] = [R_1][R_2]$ , where  $[R_1]$  describes a simple rotation about the  $Y$  axis and  $[R_2]$  is a simple rotation about the  $Z$  axis. Thus

$$\begin{aligned} [R] &= \begin{bmatrix} \cos 65^\circ & 0 & -\sin 65^\circ \\ 0 & 1 & 0 \\ \sin 65^\circ & 0 & \cos 65^\circ \end{bmatrix} \begin{bmatrix} \cos(-145^\circ) & \sin(-145^\circ) & 0 \\ -\sin(-145^\circ) & \cos(-145^\circ) & 0 \\ 0 & 0 & 1 \end{bmatrix} \\ &= \begin{bmatrix} -0.3462 & -0.2424 & -0.9063 \\ 0.5736 & -0.8192 & 0 \\ -0.7424 & -0.5198 & 0.4226 \end{bmatrix}. \end{aligned}$$

For the first question, we know the position coordinates with respect to  $XYZ$ , and  $[R]$  transforms from  $\bar{i}\bar{j}\bar{k}$  components to  $\bar{i}\bar{j}\bar{k}$  components, so we apply the direct transformation:

$$\begin{Bmatrix} x_a \\ y_a \\ z_a \end{Bmatrix} = [R] \begin{Bmatrix} 2 \\ -3 \\ 4 \end{Bmatrix} = \begin{Bmatrix} -2.442 \\ 4.424 \\ 1.862 \end{Bmatrix} \text{ m.} \quad \triangleleft$$

In the second situation the coordinates of the point with respect to the  $xyz$  coordinate system are invariant, and we need to determine the  $XYZ$  coordinates. This is the inverse of the transformation described by  $[R]$ . In accord with the orthonormal property, we use  $[R]^T$  to find


$$\begin{Bmatrix} X_b \\ Y_b \\ Z_b \end{Bmatrix} = [R]^T \begin{Bmatrix} 2 \\ -3 \\ 4 \end{Bmatrix} = \begin{Bmatrix} -5.214 \\ 1.232 \\ -0.545 \end{Bmatrix} \text{ m.} \quad \triangleleft$$

### Rotation About an Arbitrary Axis

We have seen that a sequence of simple rotations about various coordinate axes leads to a general rotation transformation. The question now is this: What should one do if

### 3.1 Coordinate Transformations

107



**Figure 3.7.** Rotation by angle  $\phi$  about line  $Z'$  that does not coincide with one of the original coordinate axes.

there is a rotation about an axis that is not one of the coordinate axes? To address this question we follow the approach we employed to analyze space-fixed rotations. Such a situation appears in Fig. 3.7, where we have defined two fixed coordinate systems:  $XYZ$ , which is the one of interest, and  $X'Y'Z'$ , which is defined to have its  $Z'$  axis align with the rotation axis, but otherwise is arbitrary. The direction cosines  $\ell_{Z'X}$ ,  $\ell_{Z'Y}$ , and  $\ell_{Z'Z}$  define the orientation of the  $Z'$  axis.

The angle of rotation is  $\phi$ . We denote as  $[R']$  the transformation from  $XYZ$  components to  $X'Y'Z'$  components. We seek to determine the transformation  $[R]$  from  $\bar{i}\bar{j}\bar{k}$  components to  $\bar{i}'\bar{j}'\bar{k}'$  components, where coordinate system  $xyz$  coincided with  $XYZ$  prior to the rotation. To assist in that determination we define another coordinate system  $x'y'z'$  that also undergoes the rotation, with the property that its axes coincided with  $X'Y'Z'$  prior to the rotation. Because  $xyz$  and  $x'y'z'$  experience the same rotation, and therefore maintain their relative orientation,  $[R']$  also describes the relation between these coordinate systems. Thus we have

$$\begin{Bmatrix} A_{X'} \\ A_{Y'} \\ A_{Z'} \end{Bmatrix} = [R'] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix}, \quad \begin{Bmatrix} A_{x'} \\ A_{y'} \\ A_{z'} \end{Bmatrix} = [R'] \begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix}. \quad (3.1.31)$$

Let  $\phi$  denote the angle of rotation about the  $Z'$  axis. This is a simple rotation from the perspective of  $X'Y'Z'$  and  $x'y'z'$ , so

$$\begin{Bmatrix} A_{x'} \\ A_{y'} \\ A_{z'} \end{Bmatrix} = [R_\phi] \begin{Bmatrix} A_{X'} \\ A_{Y'} \\ A_{Z'} \end{Bmatrix}, \quad [R_\phi] = \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix}. \quad (3.1.32)$$

Using Eqs. (3.1.31) to eliminate the primed components in the preceding equation leads to

$$[R'] \begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix} = [R_\phi][R'] \begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix}. \quad (3.1.33)$$

The transformation from  $XYZ$  to  $xyz$  is readily obtained from the orthonormal property, which leads to an interesting conceptual picture:

*The transformation matrix corresponding to rotation of a coordinate system about an arbitrary axis is equivalent to a sequence of body-fixed rotations. The first rotation,*

corresponding to  $[R']$ , brings one of the coordinate system's axes into coincidence with the rotation axis. This is followed by a simple rotation  $[R_\phi]$  about the designated rotation axis, after which the inverse of the first rotation is executed, so that

$$\begin{bmatrix} A_x \\ A_y \\ A_z \end{bmatrix} = [R] \begin{bmatrix} A_X \\ A_Y \\ A_Z \end{bmatrix}, \quad [R] = [R']^T [R_\phi] [R']. \quad (3.1.34)$$

The converse of the preceding is *Euler's theorem*, which states that any rotation is equivalent to a single rotation about an axis. Let us consider the task of finding the angle and axis of such a rotation given  $[R]$ . In the analysis leading to Eq. (3.1.34) we saw that the  $Z'$  axis has a constant orientation relative to  $xyz$ . Hence, the direction cosines of  $Z'$  with respect to  $xyz$  after the rotation are the same as its direction cosines with respect to  $XYZ$ . However, the direction cosines of any vector with respect to  $xyz$  and  $XYZ$  are related by  $[R]$ . Consequently, we have

$$\begin{bmatrix} \ell_{Z'X} \\ \ell_{Z'Y} \\ \ell_{Z'Z} \end{bmatrix} = \begin{bmatrix} \ell_{Z'x} \\ \ell_{Z'y} \\ \ell_{Z'z} \end{bmatrix} = [R] \begin{bmatrix} \ell_{Z'X} \\ \ell_{Z'Y} \\ \ell_{Z'Z} \end{bmatrix}. \quad (3.1.35)$$

Thus we obtain a set of simultaneous equations for the direction cosines of  $\bar{K}'$ :

$$[[R] - [U]] \{K'\} = \{0\}, \quad \{K'\} = \begin{bmatrix} \ell_{Z'X} \\ \ell_{Z'Y} \\ \ell_{Z'Z} \end{bmatrix}. \quad (3.1.36)$$

There must be a nontrivial solution for the direction cosines, which will be true only if  $|[R] - [U]| = 0$ . In other words,  $[R] - [U]$  is rank deficient, which means that one or more of the elements of  $\{K'\}$  is arbitrary. We can solve Eqs. (3.1.36) for two direction cosines in terms of the arbitrary one. Then all three values may be determined from the fact that  $\bar{K}'$  is a unit vector, so that  $\ell_{Z'X}^2 + \ell_{Z'Y}^2 + \ell_{Z'Z}^2 = 1$ .

An alternative procedure for determining the direction cosines comes from solving the matrix eigenvalue problem described by

$$[[R] - \lambda [U]] \{\xi\} = \{0\}, \quad (3.1.37)$$

which gives nontrivial solutions if  $|[R] - \lambda [U]| = 0$ . Because  $|[R] - [U]| = 0$ , it follows that one of the eigenvalues must be unity. The eigenvector corresponding to  $\lambda = 1$  and having a unit Euclidean norm will be  $\{K'\}$ . In other words

$$[[R] - \lambda_j [U]] \{\xi_j\} = \{0\} \text{ gives } \{\xi_j\} = \{K'\} \text{ if } \lambda_j = 1 \text{ and } \{\xi_j\}^T \{\xi_j\} = 1. \quad (3.1.38)$$

Because  $[R]$  is a  $3 \times 3$  matrix, there are three eigenvalues. However, only one axis remains stationary in the rotation. This is manifested by the other two eigenvalues being complex, and therefore irrelevant, although their magnitude is unity. The primary virtue

### 3.1 Coordinate Transformations

109

of Eqs. (3.1.38) as compared with Eq. (3.1.36) is that the former are readily implemented with mathematical software.


It still remains to determine the angle of rotation  $\phi$  corresponding to  $[R]$ . A theorem of matrix algebra leads to an equation that  $\phi$  must satisfy. The relation between  $[R]$  and  $[R_\phi]$  given by Eq. (3.1.34) is an orthogonal similarity transformation. (We will encounter this matter in greater detail in Chapter 5 when we discuss the inertia properties of rigid bodies.) An important property of such a transformation is constancy of the trace of the matrix, which is the sum of the diagonal terms. Thus  $\text{tr}[R] = \text{tr}[R_\phi]$ . In view of the definition of  $[R_\phi]$ , it follows that the angle of rotation must satisfy

$$1 + 2 \cos \phi = \text{tr}[R], \quad (3.1.39)$$

which is a relation that was derived by Euler.

The difficulty with Eq. (3.1.39) is that it does not uniquely determine  $\phi$  because  $\cos \phi = \cos(-\phi)$ . This ambiguity in the sign of  $\phi$  is associated with the fact that Eqs. (3.1.38) are satisfied by  $-\{K'\}$ , as well as by  $+\{K'\}$ . Physically, the same transformation will result from  $\phi$  in the sense of  $\bar{K}'$  and  $-\phi$  in the sense of  $-\bar{K}'$ .

One way to determine  $\phi$  involves first determining the transformation  $[R']$  in Eq. (3.1.34). The direction cosines  $\{K'\}$  are taken to be known from Eqs. (3.1.36) or (3.1.38). The orientation of the  $X'$  and  $Y'$  axes was unspecified in the development leading to Eq. (3.1.34). Let us impose the condition that the  $Y'$  axis should lie in the  $XY$  plane. This is the situation in Fig. 3.8, where  $\psi$  is the angle between the  $Y$  and  $Y'$  axes and  $\theta$  is the angle between the  $Z$  and  $Z'$  axes. It is evident from the figure that all possible orientations of the  $Y'$  axis in the  $XY$  plane are covered by  $-\pi < \psi \leq \pi$ , whereas any  $Z'$  axis is described by  $0 \leq \theta < \pi$ .



**Figure 3.8.** Sequence of rotations leading to a coordinate system whose  $Z'$  axis coincides with an arbitrary rotation axis.

It is possible to construct  $[R']$  in terms of  $\psi$  and  $\theta$  by use of Fig. 3.8 to project  $\bar{I}'$ ,  $\bar{J}$ , and  $\bar{K}'$  onto the  $XYZ$  axes. Alternatively, one can consider  $[R']$  to be the result of a pair of body-fixed rotations:  $\psi$  about the  $Z'$  axis, followed by  $\theta$  about the  $Y'$  axis. (This viewpoint will be used in Chapter 4, where  $\psi$  and  $\theta$  will be identified as two of the Eulerian angles used to standardize the description of motion. The third Eulerian angle will be  $\phi$ .) Either construction leads to

$$[R'] = \begin{bmatrix} \cos \psi \cos \theta & \sin \psi \cos \theta & -\sin \theta \\ -\sin \psi & \cos \psi & 0 \\ \cos \psi \sin \theta & \sin \psi \sin \theta & \cos \theta \end{bmatrix}. \quad (3.1.40)$$

The last row consists of the direction cosines of the  $Z'$  axis. Equating these to the corresponding elements of  $\{K'\}$  leads to

$$\begin{aligned}\ell_{Z'Z} &= \cos \theta, \\ \ell_{Z'Y} &= \sin \psi \sin \theta, \\ \ell_{Z'X} &= \cos \psi \sin \theta.\end{aligned}\tag{3.1.41}$$

These relations may be solved for the values of  $\theta$  and  $\psi$ . Only values  $0 \leq \theta \leq \pi$  are meaningful, and the quadrant of  $\psi$  must be consistent with the last two relations.

Knowledge of  $\psi$  and  $\theta$  allows us to fill in the missing elements of  $[R']$  in Eq. (3.1.40). The corresponding  $[R_\phi]$  obtained by solving Eq. (3.1.34) with the aid of the orthonormal property is

$$[R_\phi] = [R'] [R] [R']^T.\tag{3.1.42}$$

Matching the result of this calculation to Eqs. (3.1.32) leads to values of  $\cos \phi$  and  $\sin \phi$ , which together enable us to place  $\phi$  in the proper quadrant.

**EXAMPLE 3.4** Construct  $[R]$  corresponding to angles  $\psi = -30^\circ$  and  $\theta = 125^\circ$  in Fig. 3.8, with  $\phi = -143.13^\circ$  being the angle of rotation about the  $Z'$  axis. Then test the procedure for ascertaining the angle and axis of rotation by extracting the values of  $\phi$ ,  $\theta$ , and  $\psi$  from the resulting  $[R]$ .

**SOLUTION** This example entails application of all the concepts associated with rotation about an arbitrary axis. We begin by evaluating Eqs. (3.1.40) and (3.1.32) for the given angles,

$$\begin{aligned}[R'] &= \begin{bmatrix} -0.4967 & 0.2868 & -0.8192 \\ 0.5 & 0.866 & 0 \\ 0.7094 & -0.4096 & -0.5736 \end{bmatrix}, \\ [R_\phi] &= \begin{bmatrix} -0.8 & -0.6 & 0 \\ 0.6 & -0.8 & 0 \\ 0 & 0 & 1 \end{bmatrix}.\end{aligned}$$

The overall transformation is found from Eq. (3.1.34) to be

$$[R] = \begin{bmatrix} 0.1059 & -0.1789 & -0.9782 \\ -0.8671 & -0.4980 & -0.0028 \\ -0.4867 & 0.8485 & -0.2078 \end{bmatrix}.\tag{3.1.43}$$

We now wish to work backwards to determine the angles associated with this transformation. We could determine  $\{K'\}$  by solving Eqs. (3.1.38) with the aid of Matlab's *eigen* or Mathcad's *eigenvec* function. Instead we shall follow Eqs. (3.1.36).

### 3.1 Coordinate Transformations

111

We subtract the identity matrix from  $[R]$  and recognize that only two of the rows are linearly independent because  $|[R] - [U]| = 0$ . Using the first two rows leads to

$$\begin{bmatrix} 0.1059 & -0.1789 & -0.9782 \\ -0.8671 & -0.4980 & -0.0028 \end{bmatrix} \begin{Bmatrix} \ell_{Z'X} \\ \ell_{Z'Y} \\ \ell_{Z'Z} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \end{Bmatrix}.$$

We have two equations for three unknowns, so we take  $\ell_{Z'Z}$  to be arbitrary, and solve for the other direction cosines:

$$\begin{bmatrix} 0.8941 & -0.1789 \\ -0.8671 & -1.4980 \end{bmatrix} \begin{Bmatrix} \ell_{Z'X} \\ \ell_{Z'Y} \end{Bmatrix} = \begin{Bmatrix} 0.9782\ell_{Z'Z} \\ 0.0028\ell_{Z'Z} \end{Bmatrix},$$

$$\ell_{Z'X} = -1.2368\ell_{Z'Z}, \quad \ell_{Z'Y} = 0.7141\ell_{Z'Z}.$$

We find  $\ell_{Z'Z}$  from the fact that  $\bar{K}'$  is a unit vector, so that

$$\ell_{Z'X}^2 + \ell_{Z'Y}^2 + \ell_{Z'Z}^2 = (1.2368^2 + 0.7141^2 + 1) \ell_{Z'Z}^2 = 1.$$

The sign of  $\ell_{Z'Z}$  is not defined by this relation. Because we require that  $0 \leq \theta < \pi$ , setting  $\ell_{Z'Z} = \cos \theta$  would lead to two alternative values for  $\theta$ . Let us use the positive root, so that  $\theta$  will be acute, specifically,

$$\ell_{Z'Z} = \frac{1}{(1.2368^2 + 0.7141^2 + 1)^{1/2}} = 0.5736 = \cos \theta,$$

$$\theta = 55^\circ. \quad \triangleleft$$

The second and third of Eqs. (3.1.41) then lead to

$$\ell_{Z'Y} = \sin \psi \sin \theta = 0.4096, \quad \ell_{Z'X} = \cos \psi \sin \theta = -0.7094.$$

These relations place  $\psi$  in the second quadrant:

$$\psi = 150^\circ. \quad \triangleleft$$

Equation (3.1.40) indicates that the transformation  $[R']$  corresponding to the calculated  $\psi$  and  $\theta$  is

$$[R'] = \begin{bmatrix} -0.4967 & 0.2868 & -0.8192 \\ -0.5 & -0.866 & 0 \\ -0.7094 & 0.4096 & 0.5736 \end{bmatrix}.$$

We use Eq. (3.1.42) to find the value of  $[R_\phi]$  corresponding to the preceding, and match the result to the standard expression in Eqs. (3.1.32), which leads to

$$\begin{aligned} [R_\phi] &= [R'] [R] [R']^T = \begin{bmatrix} -0.8 & 0.6 & 0 \\ -0.6 & -0.8 & 0 \\ 0 & 0 & 1 \end{bmatrix}, \\ &= \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix}, \\ \phi &= 143.13^\circ. \end{aligned}$$

◁

The values of  $\psi$  and  $\theta$  are  $180^\circ$  greater than the given values, which means that the identified  $Z'$  axis is oriented oppositely from the rotation axis that was specified in the problem statement. Correspondingly, the value of  $\phi$  that was found is the negative of the specified value. In other words, we have identified the opposite rotation about the opposing axis. This situation is a consequence of using a positive sign for the square root leading to  $\ell_{Z'Z}$ .

### 3.2 DISPLACEMENT

The rotation transformation relates the components of a vector with respect to two coordinate systems having different orientation. For many vectors, such as force or velocity, only their direction angles relative to the reference directions are significant. This observation enabled us to develop the rotation transformation by depicting the coordinate systems as having a common origin, with the tail of the vector situated at that origin. The situation is different for position vectors. Figure 3.1 described the position of an arbitrary point  $P$  as it is observed from two different reference frames. The position with respect to the fixed reference frame is  $\bar{r}_{P/O}$ , whose components with respect to the stationary  $XYZ$  coordinate system can be designated as  $X_P$ ,  $Y_P$ , and  $Z_P$ . The position with respect to a moving reference frame is  $\bar{r}_{P/O'}$ . Because the moving  $xyz$  coordinate system provides the viewpoint for this vector, we use the associated coordinates  $x_P$ ,  $y_P$ , and  $z_P$  to describe  $\bar{r}_{P/O'}$ .

To implement Eq. (3.1.1) by adding like components, we need to describe all vectors in terms of components relative to the same coordinate directions. We may use a rotation transformation for this task by observing in Fig. 3.1 that  $x'y'z'$  is parallel to  $XYZ$ . If the former coordinate system is to be useful, it must be that we know where its origin is, which means that we know  $X_{O'}$ ,  $Y_{O'}$ , and  $Z_{O'}$ . To represent the components of  $\bar{r}_{P/O'}$  with respect to  $XYZ$ , we use the rotation transformation  $[R]$  between  $x'y'z'$  and  $xyz$ .



### 3.2 Displacement

113

This leads to the *general positional transformation*, which is described by

$$\begin{bmatrix} X_P & Y_P & Z_P \end{bmatrix}^T = \begin{bmatrix} X_{O'} & Y_{O'} & Z_{O'} \end{bmatrix}^T + [R]^T \begin{bmatrix} x_P & y_P & z_P \end{bmatrix}^T. \quad (3.2.1)$$

Proper application of this relation requires that we be cognizant of the fact that  $[R]$  is defined to give components relative to  $xyz$ , given  $x'y'z'$  components, and that  $x'y'z'$  is parallel to  $XYZ$ . Obviously, when  $xyz$  coincides with  $x'y'z'$ , so that  $[R]$  is the identity matrix, the preceding reduces to the translational transformation, Eq. (3.1.3).

A key aspect of the description of motion is evaluation of the *displacement* of a point, which is the position shift from an initial reference location to the current location,


$$\Delta \bar{r}_P = (\bar{r}_{P/O})_f - (\bar{r}_{P/O})_o, \quad (3.2.2)$$

where the subscripts “o” and “f” are shorthand for original and final. Note that the origin  $O$  does not need to be indicated in the notation for  $\Delta \bar{r}_P$  because the displacement vector merely extends from the initial to the final position, for which the location of the origin  $O$  is irrelevant.

The simplest evaluation of displacement is encountered when both positions are known in terms of their coordinates relative to a stationary  $XYZ$  reference frame. In that case, the displacement components are merely the difference of like coordinates. In matrix form, we have

$$\begin{Bmatrix} \Delta r_{PX} \\ \Delta r_{PY} \\ \Delta r_{PZ} \end{Bmatrix} \equiv \begin{Bmatrix} \Delta X_P \\ \Delta Y_P \\ \Delta Z_P \end{Bmatrix} = \begin{Bmatrix} (X_P)_f \\ (Y_P)_f \\ (Z_P)_f \end{Bmatrix} - \begin{Bmatrix} (X_P)_o \\ (Y_P)_o \\ (Z_P)_o \end{Bmatrix}. \quad (3.2.3)$$

The more usual case involves observation of some aspects of motion from a moving reference frame. This would be the case if we were in an airplane observing the displacement of another airplane. Consider the situation in Fig. 3.9, in which the position of point  $P$  is described by a position vector from the origin of a coordinate system  $xyz$  that executes a known motion. In this viewpoint, the original and final positions are each



**Figure 3.9.** Displacement of a point as viewed from a moving reference frame. Points  $(P)_o$  and  $(P)_f$  are the original and final positions, respectively.

described by Eq. (3.2.1), with subscripts “o” and “f” used to designate the original and final states. Taking the difference of these expressions yields the displacement:

$$\begin{aligned} \begin{Bmatrix} \Delta r_{PX} \\ \Delta r_{PY} \\ \Delta r_{PZ} \end{Bmatrix} &= \begin{Bmatrix} \Delta r_{O'X} \\ \Delta r_{O'Y} \\ \Delta r_{O'Z} \end{Bmatrix} + [R]_f^T \begin{Bmatrix} (x_P)_f \\ (y_P)_f \\ (z_P)_f \end{Bmatrix} \\ &\quad - [R]_o^T \begin{Bmatrix} (x_P)_o \\ (y_P)_o \\ (z_P)_o \end{Bmatrix}. \end{aligned} \quad (3.2.4)$$

The *relative displacement*  $(\Delta \bar{r}_P)_{xyz}$  is the displacement that an observer moving in unison with  $xyz$  would see. Such an observer would consider the orientation of  $xyz$  to be invariant, so only the change in the values of  $(x_P, y_P, z_P)$  would be seen. Thus,

$$(\Delta \bar{r}_P)_{xyz} = [(x_P)_f - (x_P)_o] \bar{i} + [(y_P)_f - (y_P)_o] \bar{j} + [(z_P)_f - (z_P)_o] \bar{k}. \quad (3.2.5)$$

To emphasize the difference between  $(\Delta \bar{r}_P)_{xyz}$  and  $\Delta \bar{r}_P$ , the latter is sometimes called an *absolute displacement*. [Consistency of the notation suggests that the absolute displacement should be denoted as  $(\Delta \bar{r}_P)_{XYZ}$ , but we shall not do so for brevity. Instead, the absence of a subscript denoting a reference frame should be understood to mean that a displacement, and later, a velocity or acceleration, is relative to the stationary reference frame.] The matrix representation of Eq. (3.2.5) is

$$\begin{Bmatrix} (x_P)_f \\ (y_P)_f \\ (z_P)_f \end{Bmatrix} = \begin{Bmatrix} (x_P)_o \\ (y_P)_o \\ (z_P)_o \end{Bmatrix} + \begin{Bmatrix} (\Delta \bar{r}_P)_{xyz} \cdot \bar{i} \\ (\Delta \bar{r}_P)_{xyz} \cdot \bar{j} \\ (\Delta \bar{r}_P)_{xyz} \cdot \bar{k} \end{Bmatrix}. \quad (3.2.6)$$

Note that a dot product is used to denote which set of displacement components are under consideration in order to avoid later confusion. Substitution of the preceding equation into Eq. (3.2.4) leads to a useful expression for the  $\bar{I}\bar{J}\bar{K}$  displacement components:

$$\begin{aligned} \begin{Bmatrix} \Delta \bar{r}_P \cdot \bar{I} \\ \Delta \bar{r}_P \cdot \bar{J} \\ \Delta \bar{r}_P \cdot \bar{K} \end{Bmatrix} &= \begin{Bmatrix} \Delta \bar{r}_{O'} \cdot \bar{I} \\ \Delta \bar{r}_{O'} \cdot \bar{J} \\ \Delta \bar{r}_{O'} \cdot \bar{K} \end{Bmatrix} + [R]_f^T \begin{Bmatrix} (\Delta \bar{r}_P)_{xyz} \cdot \bar{i} \\ (\Delta \bar{r}_P)_{xyz} \cdot \bar{j} \\ (\Delta \bar{r}_P)_{xyz} \cdot \bar{k} \end{Bmatrix} \\ &\quad + \left[ [R]_f^T - [R]_o^T \right] \begin{Bmatrix} (x_P)_o \\ (y_P)_o \\ (z_P)_o \end{Bmatrix}. \end{aligned} \quad (3.2.7)$$

### 3.2 Displacement

115

Equation (3.2.7) highlights that when motion is described in terms of a moving reference frame, three effects combine to give the displacement relative to a stationary reference frame. If  $xyz$  were to translate, so that  $[R]_f \equiv [R]_o$ , and if the coordinates of point  $P$  relative to  $xyz$  were constant, so that  $(\Delta \bar{r}_P)_{xyz} \equiv \bar{0}$ , then only the displacement of the origin of  $xyz$  would matter. Thus  $(\Delta \bar{r}_{O'})_{XYZ}$  is called the *translational displacement*. If  $xyz$  translates, but the position of point  $P$  relative to  $xyz$  is not constant, then the relative displacement is superposed onto the translational displacement. Finally, if  $xyz$  rotates, so that  $[R]$  is no longer constant, then the last term, representing the *rotational displacement* expressed in terms of  $\bar{I}\bar{J}\bar{K}$  components, superposes onto the other contributions. These three influences also will be encountered when we use a moving reference frame to describe velocity.


There are many situations in which it is more desirable to use the moving reference frame to describe vector components. For example, such a description corresponds to the position of another airplane from a pilot's perspective. Another general situation is one in which displacement is used to define strain in order to perform a stress analysis. Such a study is most relevant if viewed relative to favored directions defined with respect to the body. Equation (3.2.7) describes displacement in terms of  $\bar{I}\bar{J}\bar{K}$  components. Multiplying that expression by  $[R]_f$  converts it to components relative to the final  $xyz$  orientation. We then use Eq. (3.2.6) to eliminate the original coordinates, with the result that

$$\begin{aligned} \begin{Bmatrix} \Delta \bar{r}_P \cdot \bar{i} \\ \Delta \bar{r}_P \cdot \bar{j} \\ \Delta \bar{r}_P \cdot \bar{k} \end{Bmatrix} &= \begin{Bmatrix} \Delta \bar{r}_{O'} \cdot \bar{i} \\ \Delta \bar{r}_{O'} \cdot \bar{j} \\ \Delta \bar{r}_{O'} \cdot \bar{k} \end{Bmatrix} + [R]_f [R]_o^T \begin{Bmatrix} (\Delta \bar{r}_P)_{xyz} \cdot \bar{i} \\ (\Delta \bar{r}_P)_{xyz} \cdot \bar{j} \\ (\Delta \bar{r}_P)_{xyz} \cdot \bar{k} \end{Bmatrix} \\ &+ \left[ [U] - [R]_f [R]_o^T \right] \begin{Bmatrix} (x_P)_f \\ (y_P)_f \\ (z_P)_f \end{Bmatrix}. \end{aligned} \quad (3.2.8)$$

A common source of error in the application of Eqs. (3.2.7) and (3.2.8) is confusion regarding the definition of  $[R]$ , which is that it converts  $\bar{I}\bar{J}\bar{K}$  components to  $\bar{i}\bar{j}\bar{k}$  components.

It is imperative to realize that this expression and Eq. (3.2.7) describe the same (absolute) displacement. Equation (3.2.7) gives displacement components relative to the axes of the fixed  $XYZ$  coordinate system in terms of the original coordinates of the point. This description, which is referred to as a *Lagrangian* description, represents the perspective of a fixed observer. In contrast, Eq. (3.2.8) is an *Eulerian* description giving displacement components relative to the axes of the moving  $xyz$  coordinate system in terms of the final coordinates. This is the perspective of an observer who moves in unison with  $xyz$ . Which is most suitable depends on the situation to be analyzed. The study of solid mechanics usually begins with an Lagrangian description, whereas fluid mechanics analyses are usually most easily carried out with an Eulerian description.

**EXAMPLE 3.5** The sketch shows the initial position of a box, in which its edges coincided with fixed reference frame  $XYZ$ . The box is rotated  $30^\circ$  about axis  $OA$ , counterclockwise when viewed from  $O$  to  $A$ . Determine the displacement of point  $B$  in terms of components relative to  $xyz$ , and relative to  $XYZ$ .



Example 3.5

**SOLUTION** This example consolidates many of the developments for rotation transformations. To follow corner  $B$  as it moves, we attach the  $xyz$  coordinate system to the box, such that the axes coincide with  $XYZ$  prior to rotation. Thus the initial transformation is  $[R]_o = [U]$ , and the initial coordinates of point  $B$  with respect to  $xyz$  are

$$\begin{Bmatrix} (x_B)_o \\ (y_B)_o \\ (z_B)_o \end{Bmatrix} = \begin{Bmatrix} 1.5 \\ 2 \\ 1 \end{Bmatrix}.$$

We need to establish  $[R]_f$ , which transforms  $XYZ$  to  $xyz$  components in the final position. The rotation takes place about an axis that does not coincide with either set of axes, so we define an  $X'Y'Z'$  coordinate system whose  $Z'$  axis coincides with the diagonal  $OA$ . This system may be obtained by a simple rotation about the negative  $X$  axis by  $\theta_X = \tan^{-1}(2/1)$ . The corresponding transformation from  $\bar{I}\bar{J}\bar{K}$  to  $\bar{I}'\bar{J}'\bar{K}'$  components is

$$[R'] = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \theta_X & -\sin \theta_X \\ 0 & \sin \theta_X & \cos \theta_X \end{bmatrix}.$$

The specified rotation about the  $Z'$  axis is  $\phi = -30^\circ$ , so

$$[R_\phi] = \begin{bmatrix} \cos 30^\circ & -\sin 30^\circ & 0 \\ \sin 30^\circ & \cos 30^\circ & 0 \\ 0 & 0 & 1 \end{bmatrix}.$$

### 3.2 Displacement

117

From Eq. (3.1.34) we find that

$$[R]_f = [R']^T [R_\phi] [R'] = \begin{bmatrix} 0.8660 & -0.2236 & 0.4472 \\ 0.2236 & 0.9732 & 0.0536 \\ -0.4472 & 0.0536 & 0.8928 \end{bmatrix}.$$


The origin  $O'$  was placed at a fixed point, so there is no translational displacement,  $\Delta \bar{r}_{O'} = \bar{0}$ . Point  $B$  is a part of the box, so it does not move relative to  $xyz$ . Thus its coordinates relative to  $xyz$  are constant and its relative displacement is  $(\Delta \bar{r}_B)_{xyz} = \bar{0}$ . We may directly employ either Eq. (3.2.7) or Eq. (3.2.8). Setting  $[R]_o = [U]$  in the latter shows that the displacement of point  $B$  in terms of  $xyz$  components is

$$\begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{i} \\ \Delta \bar{r}_B \cdot \bar{j} \\ \Delta \bar{r}_B \cdot \bar{k} \end{Bmatrix} = [[U] - [R]_f] \begin{Bmatrix} (x_B)_f \\ (y_B)_f \\ (z_B)_f \end{Bmatrix} = \begin{Bmatrix} 0.2010 \\ -0.3354 \\ 0.6708 \end{Bmatrix} \text{ m.} \quad \triangleleft$$

We could use Eq. (3.2.7) to find the  $XYZ$  displacement components, but here it is simpler to use the rotation transformation  $[R]_f^T$  to transform to  $XYZ$  components:

$$\begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{I} \\ \Delta \bar{r}_B \cdot \bar{J} \\ \Delta \bar{r}_B \cdot \bar{K} \end{Bmatrix} = [R]_f^T \begin{Bmatrix} 0.2010 \\ -0.3354 \\ 0.6708 \end{Bmatrix} = \begin{Bmatrix} 0.5490 \\ -0.2455 \\ 0.4911 \end{Bmatrix} \text{ m.} \quad \triangleleft$$


**EXAMPLE 3.6** The robotic linkage is reconfigured by rotating arm  $AB$  by angle  $\theta$  about the vertical  $Z$  axis, and by angle  $\beta$  about its longitudinal axis. Link  $BC$  rotates about the pin at junction  $B$  through angle  $\gamma$ . The pin is horizontal when  $\beta = 0$ . The system is given a set of rotations consisting of  $\theta = 50^\circ$ ,  $\beta = 30^\circ$ ,  $\gamma = 60^\circ$ . The length  $L$  of link  $BC$  changes from 0.5 m to 1.5 m in the course of this motion. Determine the coordinates of end  $C$  with respect to the fixed  $XYZ$  coordinate after these rotations.



Example 3.6

**SOLUTION** This example serves to illustrate the versatility of the general procedure for evaluating displacements, and the ease with which it may be extended. It should

be noted that the sequence in which the rotations are applied is not specified. It will become apparent in the course of the solution that such information is irrelevant for this system. We define reference frames  $x_1y_1z_1$  fixed to arm  $AB$ , and  $x_2y_2z_2$  fixed to arm  $BC$ , with the  $x$  axis for each aligned with the corresponding arm. The  $z_1$  axis is vertical when  $\beta = 0$  and the  $y_2$  axis is aligned with the pin at connection  $B$ , so that all rotations occur about coordinate axes.



The general approach is to use Eq. (3.2.7) to express the displacement of point  $B$  in terms of the rotation of  $x_1y_1z_1$  and then to describe the displacement of point  $C$  in terms of the displacement of point  $B$  and the rotation of  $x_2y_2z_2$ . We use  $\bar{I}\bar{J}\bar{K}$  components to facilitate relating vector quantities for each body. Thus,

$$\begin{aligned} \begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{I} \\ \Delta \bar{r}_B \cdot \bar{J} \\ \Delta \bar{r}_B \cdot \bar{K} \end{Bmatrix} &= \begin{Bmatrix} \Delta \bar{r}_A \cdot \bar{I} \\ \Delta \bar{r}_A \cdot \bar{J} \\ \Delta \bar{r}_A \cdot \bar{K} \end{Bmatrix} + [R_1]_f^T \begin{Bmatrix} (\Delta \bar{r}_B)_{x_1y_1z_1} \cdot \bar{i} \\ (\Delta \bar{r}_B)_{x_1y_1z_1} \cdot \bar{j} \\ (\Delta \bar{r}_B)_{x_1y_1z_1} \cdot \bar{k} \end{Bmatrix} \\ &\quad + \left[ [R_1]_f^T - [R_1]_o^T \right] \begin{Bmatrix} (x_{1B})_o \\ (y_{1B})_o \\ (z_{1B})_o \end{Bmatrix}, \\ \begin{Bmatrix} \Delta \bar{r}_C \cdot \bar{I} \\ \Delta \bar{r}_C \cdot \bar{J} \\ \Delta \bar{r}_C \cdot \bar{K} \end{Bmatrix} &= \begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{I} \\ \Delta \bar{r}_B \cdot \bar{J} \\ \Delta \bar{r}_B \cdot \bar{K} \end{Bmatrix} + [R_2]_f^T \begin{Bmatrix} (\Delta \bar{r}_C)_{x_2y_2z_2} \cdot \bar{i} \\ (\Delta \bar{r}_C)_{x_2y_2z_2} \cdot \bar{j} \\ (\Delta \bar{r}_C)_{x_2y_2z_2} \cdot \bar{k} \end{Bmatrix} \\ &\quad + \left[ [R_2]_f^T - [R_2]_o^T \right] \begin{Bmatrix} (x_{2C})_o \\ (y_{2C})_o \\ (z_{2C})_o \end{Bmatrix}. \end{aligned}$$

We derive the required rotation transformations as a sequence of simple rotations. In the initial state, like axes were parallel, so

$$[R_1]_o = [R_2]_o = [U].$$

### 3.3 Time Derivatives

119

For the transformation from  $XYZ$  to the final orientation of  $x_1y_1z_1$  we may consider arm  $AB$  to rotate first about the  $Z$  axis by  $\theta$ , followed by the  $\beta$  rotation about the  $x_1$  axis, which corresponds to a sequence of body-fixed rotations. Alternatively, we may consider the  $\beta$  rotation to occur about the  $X$  axis, followed by the  $\theta$  rotation about the  $Z$  axis, which is a space-fixed sequence. Either way, we find that

$$[R_1]_f = [R_\beta][R_\theta] = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \beta & \sin \beta \\ 0 & -\sin \beta & \cos \beta \end{bmatrix} \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}.$$

When  $\gamma = 0$ , like axes of  $x_1y_1z_1$  and  $x_2y_2z_2$  are parallel. Thus the final orientation of  $x_2y_2z_2$  may be considered to be attained by rotating it about the negative  $y_2$  axis by  $\gamma$  relative to  $x_1y_1z_1$ . This is a body-fixed rotation, so that

$$[R_2]_f = [R_\gamma][R_1]_f = \begin{bmatrix} \cos \gamma & 0 & \sin \gamma \\ 0 & 1 & 0 \\ -\sin \gamma & 0 & \cos \gamma \end{bmatrix} [R_1]_f.$$

Next we describe the relative positions and displacements. Because point  $A$  is stationary,  $\Delta \bar{r}_A = \bar{0}$ . Also, because point  $B$  remains at 2 m along the  $x_1$  axis throughout the motion,  $(\bar{r}_{B/A})_0 = 2\bar{i}_1$  and  $(\Delta \bar{r}_B)_{x_1y_1z_1} = \bar{0}$ . In contrast, point  $C$  remains on the  $x_2$  axis, but its distance to the origin of  $x_2y_2z_2$  increases from 0.5 m to 1.5 m, so it displaces 1 m in the  $x_2$  direction relative to  $x_2y_2z_2$ . Thus  $(\bar{r}_{C/B})_0 = 0.5\bar{i}_2$  and  $(\Delta \bar{r}_C)_{x_2y_2z_2} = 1\bar{i}_2$ . Substituting the given values of  $\theta$ ,  $\beta$ , and  $\gamma$  into the earlier expressions for  $\Delta \bar{r}_B$  and  $\Delta \bar{r}_C$  leads to

$$\begin{aligned} \begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{I} \\ \Delta \bar{r}_B \cdot \bar{J} \\ \Delta \bar{r}_B \cdot \bar{K} \end{Bmatrix} &= \begin{Bmatrix} -0.7144 \\ 1.5321 \\ 0 \end{Bmatrix} \text{ m}, \\ \begin{Bmatrix} \Delta \bar{r}_C \cdot \bar{I} \\ \Delta \bar{r}_C \cdot \bar{J} \\ \Delta \bar{r}_C \cdot \bar{K} \end{Bmatrix} &= \begin{Bmatrix} -0.2348 \\ 1.6891 \\ 1.1250 \end{Bmatrix} \text{ m}. \end{aligned}$$

<

### 3.3 TIME DERIVATIVES

When we observe a movement over a reasonably long time interval, the change in position coordinates is measurable and the rotations about various axes are finite. Consequently, there is substantial change in a system's geometrical configuration. In contrast, the definition of velocity is that it is the ratio of the infinitesimal displacement to

the infinitesimal time over which the displacement occurs. The change from finite to infinitesimal quantities actually simplifies many aspects of a kinematical analysis, essentially because the changing geometry will not be an issue.

We consider initial and final positions that are infinitesimally different and use Eq. (3.2.8) to describe the associated displacement in terms of components relative to the final orientation of  $xyz$ . The absolute displacements of the origin  $O'$  and of the observed point  $P$  are differential quantities,  $d\bar{r}_{O'}$  and  $d\bar{r}_P$ , and the relative displacement is  $(d\bar{r}_P)_{xyz}$ . The orientation of  $xyz$  relative to  $XYZ$  in the initial position is described by  $[R]_o$ , which is considered to be known.

To obtain  $[R]_f$  we recall that any transformation matrix has only three independent direction cosines and corresponding angles. This allows us to consider  $xyz$  to move from its initial to final orientation by executing infinitesimal rotations about each of its axes,  $d\theta_x$ ,  $d\theta_y$ ,  $d\theta_z$ , in the listed sequence. Because this is a sequence of body-fixed rotations, we have

$$[R]_f = [R_z][R_y][R_x][R]_o. \quad (3.3.1)$$

For a differential angle  $d\theta$ , we have  $\cos d\theta = 1$  and  $\sin d\theta = d\theta$ , so the simple rotation transformations are

$$[R_x] = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & d\theta_x \\ 0 & -d\theta_x & 1 \end{bmatrix}, \quad [R_y] = \begin{bmatrix} 1 & 0 & -d\theta_y \\ 0 & 1 & 0 \\ d\theta_y & 0 & 1 \end{bmatrix}, \quad [R_z] = \begin{bmatrix} 1 & d\theta_z & 0 \\ -d\theta_z & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}. \quad (3.3.2)$$

Evaluating the products in Eq. (3.3.1) yields

$$[R]_f = \begin{bmatrix} 1 & d\theta_z + d\theta_y d\theta_x & -d\theta_y + d\theta_z d\theta_x \\ -d\theta_z & 1 - d\theta_z d\theta_y d\theta_x & d\theta_x + d\theta_z d\theta_y \\ d\theta_y & -d\theta_x & 1 \end{bmatrix} [R]_o. \quad (3.3.3)$$

The second-order differential quantities in the preceding equation are unimportant to the evaluation of a derivative. Thus substituting Eq. (3.3.3) into Eq. (3.2.8) for the case of differential displacements gives

$$\begin{aligned} \begin{Bmatrix} d\bar{r}_P \cdot \bar{i} \\ d\bar{r}_P \cdot \bar{j} \\ d\bar{r}_P \cdot \bar{k} \end{Bmatrix} &= \begin{Bmatrix} d\bar{r}_{O'} \cdot \bar{i} \\ d\bar{r}_{O'} \cdot \bar{j} \\ d\bar{r}_{O'} \cdot \bar{k} \end{Bmatrix} + \begin{bmatrix} 1 & d\theta_z & -d\theta_y \\ -d\theta_z & 1 & d\theta_x \\ d\theta_y & -d\theta_x & 1 \end{bmatrix} \begin{Bmatrix} (d\bar{r}_P)_{xyz} \cdot \bar{i} \\ (d\bar{r}_P)_{xyz} \cdot \bar{j} \\ (d\bar{r}_P)_{xyz} \cdot \bar{k} \end{Bmatrix} \\ &+ \begin{bmatrix} 0 & -d\theta_z & d\theta_y \\ d\theta_z & 0 & -d\theta_x \\ -d\theta_y & d\theta_x & 0 \end{bmatrix} \begin{Bmatrix} (x_P)_f \\ (y_P)_f \\ (z_P)_f \end{Bmatrix}. \end{aligned} \quad (3.3.4)$$

The second term on the right side also contains second-order differentials, which are unimportant. Another simplification is that because all displacements and rotations are infinitesimal, there is no significant difference between using the initial or final position



### 3.3 Time Derivatives

121

coordinates in the last term. This allows us to denote the position of point  $P$  as  $\bar{r}_{P/O'} = x_P \bar{i} + y_P \bar{j} + z_P \bar{k}$ . Thus

$$\begin{aligned} \begin{Bmatrix} d\bar{r}_P \cdot \bar{i} \\ d\bar{r}_P \cdot \bar{j} \\ d\bar{r}_P \cdot \bar{k} \end{Bmatrix} &= \begin{Bmatrix} d\bar{r}_{O'} \cdot \bar{i} \\ d\bar{r}_{O'} \cdot \bar{j} \\ d\bar{r}_{O'} \cdot \bar{k} \end{Bmatrix} + \begin{Bmatrix} (d\bar{r}_P)_{xyz} \cdot \bar{i} \\ (d\bar{r}_P)_{xyz} \cdot \bar{j} \\ (d\bar{r}_P)_{xyz} \cdot \bar{k} \end{Bmatrix} \\ &+ \begin{bmatrix} 0 & -d\theta_z & d\theta_y \\ d\theta_z & 0 & -d\theta_x \\ -d\theta_y & d\theta_x & 0 \end{bmatrix} \begin{Bmatrix} x_P \\ y_P \\ z_P \end{Bmatrix}. \end{aligned} \quad (3.3.5)$$

The important features of the preceding equation emerge when we recognize that it is the matrix representation of a vector equation, specifically,

$$d\bar{r}_P = d\bar{r}_{O'} + (d\bar{r}_P)_{xyz} + \overline{d\theta} \times \bar{r}_{P/O'}, \quad (3.3.6)$$

where

$$\overline{d\theta} = d\theta_x \bar{i} + d\theta_y \bar{j} + d\theta_z \bar{k} \quad (3.3.7)$$

is the *infinitesimal rotation* vector. It is evident from Eq. (3.3.6) that the only significant feature of an infinitesimal rotation is its vector sum, defined by Eq. (3.3.8). This would seem to conflict with the earlier observation that rotations cannot be represented as vectors, because the rotation transformation depends on the sequence in which rotations occur. To understand the difference between finite and infinitesimal rotations, consider altering the sequence in which the infinitesimal rotations were applied in Eq. (3.3.1), for example by performing  $d\theta_z$ , followed by  $d\theta_y$ , then  $d\theta_x$ . Regardless of the sequence, only the second-order differentials in Eq. (3.3.3) would be different, and such terms are dropped. Furthermore, the transformations for space-fixed and body-fixed axes differ only by the sequence in which the individual rotation transformations are multiplied. Consequently, the same transformation is obtained if a set of infinitesimal rotations are imparted about body fixed or space fixed axes. Geometrically, the fact that an infinitesimal displacement depends on neither the type of rotation, body fixed or space fixed, nor the sequence of the rotations has a simple explanation: When rotations are infinitesimal, the difference between the initial and final orientation of any rotation axis is negligible.

A corollary of the fact that infinitesimal rotation is a vector is that the additive property applies, even if the individual rotations are not about coordinate axes. Specifically, when there are several rotations  $d\theta_n$  about directions  $\bar{e}_n$  that are parallel to the respective rotation axes in the sense of the right-hand rule (curl the fingers of the right hand about the axis in the sense of the rotation; the extended thumb gives the sense of the vector), then

$$\overline{d\theta} = \sum_n d\theta_n \bar{e}_n. \quad (3.3.8)$$

It should be noted that the overbar is placed above the entire symbol  $\overline{d\theta}$  denoting the infinitesimal rotation in order to emphasize that there is no finite rotation vector from

which the differential is formed. A principal advantage of Eq. (3.3.6) over Eq. (3.3.5) is that the vector form is independent of how the vectors are described—one can use whichever set of components is most suitable to the task of describing each quantity, then transform each set of components as necessary to sum the terms.

The underlying reason for studying differential displacement is that velocity is  $\bar{v} = d\bar{r}/dt$ . Thus dividing Eq. (3.3.6) by the time interval  $dt$  over which the displacement occurs gives us an expression for velocity of point  $P$ :

$$\bar{v}_P = \bar{v}_{O'} + (\bar{v}_P)_{xyz} + \bar{\omega} \times \bar{r}_{P/O'}, \quad (3.3.9)$$

where  $\bar{\omega}$  is the *angular velocity* of  $xyz$ , which is defined as

$$\bar{\omega} \equiv \frac{d\bar{\theta}}{dt}. \quad (3.3.10)$$

To explain  $(\bar{v}_P)_{xyz}$  we recall the definition of relative displacement, Eq. (3.2.5), according to which the components of  $(d\bar{r}_P)_{xyz}$  are the infinitesimal increments of the  $xyz$  coordinates of point  $P$ . Thus the components of  $(\bar{v}_P)_{xyz}$  are the rates of change of those coordinates, that is,

$$(\bar{v}_P)_{xyz} = \dot{x}_P \bar{i} + \dot{y}_P \bar{j} + \dot{z}_P \bar{k}. \quad (3.3.11)$$

Because an observer on  $xyz$  would not see the coordinate axes' orientation change, we say that  $(\bar{v}_P)_{xyz}$  is the *velocity relative to  $xyz$* , or more simply, the *relative velocity*.

We will develop a consistent methodology for analyzing velocity and acceleration with the aid of moving reference frames, but one basic relation still remains to be derived. An alternative description of  $\bar{v}_P$  in terms of the velocity of the origin comes about when we differentiate the description of position given by Eq. (3.1.1), which gives

$$\bar{v}_P = \bar{v}_{O'} + \frac{d}{dt}(\bar{r}_{P/O'}). \quad (3.3.12)$$

A comparison of this and Eq. (3.3.9) shows that

$$\frac{d}{dt}(\bar{r}_{P/O'}) = (\bar{v}_P)_{xyz} + \bar{\omega} \times \bar{r}_{P/O'}. \quad (3.3.13)$$

We arrive at an important generalization when we recall that Eq. (3.3.11) defines the  $\bar{i}\bar{j}\bar{k}$  components of  $(\bar{v}_P)_{xyz}$  to be the rates of change of the  $xyz$  coordinates of point  $P$ , which are, in turn, the  $\bar{i}\bar{j}\bar{k}$  components of  $\bar{r}_{P/O'}$ . Thus  $(\bar{v}_P)_{xyz}$  is like a partial time derivative of  $\bar{r}_{P/O'}$  in which account is taken of the variability of the components of  $\bar{r}_{P/O'}$ , but the orientation of the  $\bar{i}$ ,  $\bar{j}$ ,  $\bar{k}$  unit vectors is held constant. We shall generally use a partial derivative to denote such an operation. Specifically, if  $\bar{A}$  is any vector, then

$$\bar{A} = A_x \bar{i} + A_y \bar{j} + A_z \bar{k} \implies \frac{\partial \bar{A}}{\partial t} \equiv \dot{A}_x \bar{i} + \dot{A}_y \bar{j} + \dot{A}_z \bar{k}, \quad (3.3.14)$$

in which viewpoint,  $(\bar{v}_P)_{xyz} = \partial(\bar{r}_{P/O'})/\partial t$ . We refer to the result of differentiating the components of a vector, without regard to the changing orientation of these components, as a *relative derivative*. (Many other texts, including earlier versions of this one,

### 3.3 Time Derivatives

123

denoted this operation as  $\delta/\delta t$ . The  $\delta$  symbol is reserved here for operations that will be encountered in Chapter 7 on analytical mechanics.) The analogy between  $\bar{r}_{P/O'}$  and any other vector allows us to conclude from Eq. (3.3.13) that


*The time rate of change of any vector  $\bar{A}$  described in terms of components relative to reference frame  $xyz$  having angular velocity  $\bar{\omega}$  is*

$$\dot{\bar{A}} = \frac{\partial \bar{A}}{\partial t} + \bar{\omega} \times \bar{A}. \quad (3.3.15)$$

A less general case is that in which  $\bar{A}$  is one of the unit vectors of  $xyz$ , which we denote by the generic symbol  $\bar{e}$ . Clearly,  $\partial \bar{e}/\partial t = \bar{0}$ , so we find that

$$\bar{e} = \bar{i}, \bar{j}, \text{ or } \bar{k} \implies \dot{\bar{e}} = \bar{\omega} \times \bar{e}. \quad (3.3.16)$$

We will invoke this relation frequently as part of the methodology for analyzing angular acceleration. Figure 3.10(a) shows a typical unit vector  $\bar{e}$  before and after an infinitesimal rotation. The axis of rotation is parallel to  $\bar{\omega}$ . The amount by which  $\bar{e}$  changes is the difference  $d\bar{e}$  between the final vector  $(\bar{e})_f$  and original vector  $(\bar{e})_o$ . This difference is depicted in Fig. 3.10(b), where the tails of  $(\bar{e})_f$  and  $(\bar{e})_o$  have been brought to the axis represented by  $d\bar{\theta}$ . The sketch shows that only the portion of  $\bar{e}$  that is perpendicular to the rotation axis changes; call this component  $\bar{e}_\perp$ . The line in Fig. 3.10(b) representing  $\bar{e}_\perp$  rotates through the angle  $|d\bar{\theta}|$ . Hence the arc that represents  $d\bar{e}$  has a length  $|\bar{e}_\perp| d\theta$ , and the direction of  $d\bar{e}$  is perpendicular to both  $\bar{e}$  and  $d\bar{\theta}$ . The magnitude of a cross product is defined to be the product of the magnitude of one vector and the perpendicular component of the other vector, and the direction of the product is perpendicular to the individual vectors in the sense of the right-hand rule. It follows that the pictorial analysis fully agrees with Eq. (3.3.16). The fact that the change of  $\bar{e}$  is perpendicular to  $\bar{e}$  is another manifestation of the general property derived in the study of tangent and normal components, as well as curvilinear coordinates.



**Figure 3.10.** The change of a unit vector resulting from an infinitesimal rotation: (a) movement of the unit vector, (b) construction of the difference between the new and original unit vectors.

**EXAMPLE 3.7** Consider the linkage in Example 3.6 when the final position specified there is the starting configuration, so that  $L_o = 1.5$  m,  $\theta_o = 50^\circ$ ,  $\beta_o = 30^\circ$ ,  $\gamma_o = 60^\circ$ . From that position the following increments are applied:  $\Delta L = 12$  mm,  $\Delta\theta = 0.5^\circ$ ,  $\Delta\beta = -0.5^\circ$ ,  $\Delta\gamma = -1^\circ$ . Determine the associated displacement using the exact matrix transformation technique, and compare it with the approximate value obtained by considering the rotation to be infinitesimal.

**SOLUTION** An objective of this example is to demonstrate the simplifications encountered in the transition from finite displacement to velocity. To apply the developments in the previous example here, we recognize that the final configuration obtained there is now the initial, so we have

$$[R_1]_o = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \beta_o & \sin \beta_o \\ 0 & -\sin \beta_o & \cos \beta_o \end{bmatrix} \begin{bmatrix} \cos \theta_o & \sin \theta_o & 0 \\ -\sin \theta_o & \cos \theta_o & 0 \\ 0 & 0 & 1 \end{bmatrix},$$

$$[R_2]_o = \begin{bmatrix} \cos \gamma_o & 0 & \sin \gamma_o \\ 0 & 1 & 0 \\ -\sin \gamma_o & 0 & \cos \gamma_o \end{bmatrix} [R_1]_o.$$

The transformations  $[R_1]_f$  and  $[R_2]_f$  for the final location are obtained by replacing the angles in the preceding by  $\theta_o + \Delta\theta$ ,  $\beta_o + \Delta\beta$ , and  $\gamma_o + \Delta\gamma$ . Relative to  $x_2y_2z_2$ , which is attached to arm  $BC$ , the position and displacement are  $(\bar{r}_{C/B})_o = 1.5\bar{i}_2$  and  $(\Delta\bar{r}_C)_{x_2y_2z_2} = (\Delta L)\bar{i}_2$ . It still is true that  $\bar{r}_{B/A} = 2\bar{i}$  and  $\Delta\bar{r}_A = (\Delta\bar{r}_B)_{x_1y_1z_1} = \bar{0}$ . Substitution of these terms into Eq. (3.2.7) to evaluate  $\Delta\bar{r}_B$ , and then  $\Delta\bar{r}_C$ , leads to

$$\begin{Bmatrix} \Delta\bar{r}_B \cdot \bar{I} \\ \Delta\bar{r}_B \cdot \bar{J} \\ \Delta\bar{r}_B \cdot \bar{K} \end{Bmatrix} = \begin{Bmatrix} 13.42 \\ 11.16 \\ 0 \end{Bmatrix} \text{ mm},$$

$$\begin{Bmatrix} \Delta\bar{r}_C \cdot \bar{I} \\ \Delta\bar{r}_C \cdot \bar{J} \\ \Delta\bar{r}_C \cdot \bar{K} \end{Bmatrix} = \begin{Bmatrix} -5.28 \\ 49.08 \\ 3.01 \end{Bmatrix} \text{ mm}.$$

To perform the analysis based on the infinitesimal approximation we use Eq. (3.3.6) to relate the displacements of points  $A$ ,  $B$ , and  $C$ . The rotation angles from the initial to final positions are small, but finite, so these relations are approximate. We let  $\overline{\Delta\theta}_1$  and  $\overline{\Delta\theta}_2$  denote small rotation vectors for the respective reference frames. Because  $\Delta\bar{r}_A = (\Delta\bar{r}_B)_{x_1y_1z_1} = \bar{0}$ , we have

$$\Delta\bar{r}_B \approx \overline{\Delta\theta}_1 \times \bar{r}_{B/A}, \quad \Delta\bar{r}_C \approx \Delta\bar{r}_B + (\Delta\bar{r}_C)_{x_2y_2z_2} + \overline{\Delta\theta}_2 \times \bar{r}_{C/B}.$$

### 3.3 Time Derivatives

125

Each small rotation vector is the vector sum of the scalar angles in the directions of the respective axes. The rotation of  $x_1 y_1 z_1$  consists of  $\Delta\theta$  about the  $Z$  axis, followed by  $\Delta\beta$  about the  $x_1$  axis. (Because  $\beta$  is not zero, the  $z_1$  axis is not vertical, so we cannot say that  $\Delta\theta$  is about the  $z_1$  axis.) The vector sum of these rotations is

$$\overline{\Delta\theta}_1 = \Delta\theta \bar{K} + \Delta\beta \bar{i}_1.$$

Because  $x_2 y_2 z_2$  rotates by  $\beta$  about the negative  $y_2$  axis relative to  $x_1 y_1 z_1$ , its rotation vector is the sum of the rotation of  $x_1 y_1 z_1$  and  $\Delta\gamma$  in the direction of  $-\bar{j}_2$ :

$$\overline{\Delta\theta}_2 = \Delta\theta \bar{K} + \Delta\beta \bar{i}_1 - \Delta\gamma \bar{j}_2.$$

Note that the rotation angles must be expressed in units of radians.

To form the sums we need to express all quantities in terms of components relative to the same set of coordinate axes. We could use  $\bar{I}\bar{J}\bar{K}$  components for this with the aid of rotation transformations. However, if we use  $\bar{i}_1\bar{j}_1\bar{k}_1$  components we can find the required vectors by inspection. We refer back to the sketch of the coordinate axes in Example 3.6. Because  $\bar{k}_1$  remains coincident with  $\bar{K}$  in the  $\theta$  rotation,  $\bar{K}$  is situated in the  $y_1 z_1$  plane, such that  $\bar{K} = \sin\beta_o \bar{j}_1 + \cos\beta_o \bar{k}_1$ . (Note that, because  $\beta$  changes little, we may use the initial geometrical arrangement to describe components.) The  $y_1$  and  $y_2$  axes are parallel, so  $\bar{j}_2 = \bar{j}_1$ . Thus we find that

$$\overline{\Delta\theta}_1 = \Delta\theta (\sin\beta_o \bar{j}_1 + \cos\beta_o \bar{k}_1) + \Delta\beta \bar{i}_1,$$

$$\overline{\Delta\theta}_2 = \Delta\theta (\sin\beta_o \bar{j}_1 + \cos\beta_o \bar{k}_1) + \Delta\beta \bar{i}_1 - \Delta\gamma \bar{j}_1.$$

The positions and relative displacements were described earlier as  $\bar{r}_{B/A} = 2\bar{i}_1$ ,  $\bar{r}_{C/B} = 1.5\bar{i}_2$ ,  $(\Delta\bar{r}_C)_{x_2 y_2 z_2} = (\Delta L)\bar{i}_2$ . We convert the last two to  $\bar{i}_1\bar{j}_1\bar{k}_1$  components by observing that the  $\gamma$  rotation leaves  $\bar{i}_2$  in the  $x_1 z_1$  plane, so that  $\bar{i}_2 = \cos\gamma_o \bar{i}_1 + \sin\gamma_o \bar{k}_1$ . The result of substitution of the various terms corresponding to the given values of the angles and their increments into the earlier vector expressions for  $\bar{u}_B$  and  $\bar{u}_C$  is

$$\Delta\bar{r}_B = 0.01511 \bar{j}_1 - 0.00873 \bar{k}_1 \text{ m},$$

$$\Delta\bar{r}_C = 0.03434 \bar{i}_1 + 0.03212 \bar{j}_1 - 0.01470 \bar{k}_1 \text{ m}.$$

The first evaluation of  $\Delta\bar{r}_C$  gave the result in terms of components relative to  $XYZ$ . There is little difference between the initial and the final orientation of  $xyz$  in the present situation, so we may use either the initial or final  $[R_1]$  to convert the preceding approximate displacement to those components. Using the initial transformation gives

$$\begin{Bmatrix} \Delta\bar{r}_C \cdot \bar{I} \\ \Delta\bar{r}_C \cdot \bar{J} \\ \Delta\bar{r}_C \cdot \bar{K} \end{Bmatrix} = [R_1]_0^T \begin{Bmatrix} 0.03434 \\ 0.03212 \\ -0.01470 \end{Bmatrix} = \begin{Bmatrix} -4.86 \\ 48.91 \\ 3.33 \end{Bmatrix} \text{ mm.} \quad \triangleleft$$

These values are quite close to the previous; decreasing the values of  $\Delta\theta$ ,  $\Delta\beta$ ,  $\Delta\gamma$ , and  $\Delta L$  would improve the agreement.

An interesting aspect of the analysis based on the infinitesimal displacement approximation is that the only place where a rotation transformation matrix was required was to convert the displacement to the components found from the exact transformation procedure. The steps we followed to carry out the approximate analysis are like those by which we will analyze velocity and acceleration.

**EXAMPLE 3.8** The Frenet formulas give the derivatives of the path variable unit vectors with respect to the arc length  $s$  along an arbitrary curve. Because  $\dot{s} = v$ , these derivatives may be converted to time rates of change of the unit vectors. Furthermore, the orthonormal directions represented by these unit vectors form a moving reference frame. Determine the angular velocity of the  $\bar{e}_t \bar{e}_n \bar{e}_b$  reference frame in terms of the path variable parameters.

**SOLUTION** It is useful to begin by recalling the Frenet formulas, which are

$$\frac{d\bar{e}_t}{ds} = \frac{1}{\rho} \bar{e}_n, \quad \frac{d\bar{e}_n}{ds} = -\frac{1}{\rho} \bar{e}_t + \frac{1}{\tau} \bar{e}_b, \quad \frac{d\bar{e}_b}{ds} = -\frac{1}{\tau} \bar{e}_n. \quad (1)$$

To convert these to time derivatives, we observe that, if  $\bar{e}$  is a unit vector that depends on the arc length  $s$  locating a point, and  $s = s(t)$ , then the chain rule gives

$$\frac{d\bar{e}}{dt} = \frac{ds}{dt} \frac{d\bar{e}}{ds} = v \frac{d\bar{e}}{ds}.$$

Hence, multiplying each of Eqs. (1) by  $v$  gives

$$\frac{d\bar{e}_t}{dt} = \frac{v}{\rho} \bar{e}_n, \quad \frac{d\bar{e}_n}{dt} = -\frac{v}{\rho} \bar{e}_t + \frac{v}{\tau} \bar{e}_b, \quad \frac{d\bar{e}_b}{dt} = -\frac{v}{\tau} \bar{e}_n. \quad (2)$$

Now let  $\bar{\omega} = \omega_t \bar{e}_t + \omega_n \bar{e}_n + \omega_b \bar{e}_b$  be the angular velocity of  $\bar{e}_t \bar{e}_n \bar{e}_b$ . Each unit vector has constant components relative to the reference frame, so Eq. (3.3.16) applies. Thus,

$$\begin{aligned} \frac{d\bar{e}_t}{dt} &= \bar{\omega} \times \bar{e}_t = \omega_b \bar{e}_n - \omega_n \bar{e}_b, \\ \frac{d\bar{e}_n}{dt} &= \bar{\omega} \times \bar{e}_n = -\omega_b \bar{e}_t + \omega_t \bar{e}_b, \\ \frac{d\bar{e}_b}{dt} &= \bar{\omega} \times \bar{e}_b = \omega_b \bar{e}_t - \omega_t \bar{e}_n. \end{aligned} \quad (3)$$

Matching like components in Eqs. (2) and (3) leads to

$$\omega_b = \frac{v}{\rho}, \quad \omega_n = 0, \quad \omega_t = \frac{v}{\tau} \implies \bar{\omega} = \frac{v}{\tau} \bar{e}_t + \frac{v}{\rho} \bar{e}_b. \quad \triangleleft$$

We see from this result that a sharp bend in the curve (small  $\rho$ ) causes a rapid rotation about the binormal direction, which is perpendicular to the osculating plane. Similarly, a sharp twist (small  $\tau$ ) causes a rapid rotation about the tangent direction. There is no rotation about the normal direction because the curve locally lies in the osculating plane.

### 3.4 Angular Velocity and Acceleration

127

#### 3.4 ANGULAR VELOCITY AND ACCELERATION

We have seen that analysis of velocity by using a moving reference frame requires the current value of  $\bar{\omega}$ . A comparable analysis of acceleration requires knowledge of the *angular acceleration*, which is defined to be the rate of change of the angular velocity. The need to differentiate  $\bar{\omega}$  requires that we describe this quantity in general terms, rather than merely ascertaining its instantaneous value.

##### 3.4.1 Analytical Description

We always designate the angular velocity of the  $xyz$  reference frame as  $\bar{\omega}$ . The way in which we form this crucial quantity is a direct result of substituting Eq. (3.3.8), which adds infinitesimal rotations about various axes, into the definition of  $\bar{\omega}$ , Eq. (3.3.10). This leads to the recognition that

*An angular velocity  $\bar{\omega}$  is the sum of simple rotations described by angular velocities  $\omega_n \bar{e}_n$ , where  $\bar{e}_n$  is a unit vector parallel to the respective rotation axis, in accord with the right-hand rule,*

$$\bar{\omega} = \sum_n \omega_n \bar{e}_n. \quad (3.4.1)$$

Note that there is no rule as to how the rotations are numbered, because sequence is irrelevant to angular velocity.

The angular acceleration  $\bar{\alpha}$  of  $xyz$  is the rate of change of the angular velocity:

$$\bar{\alpha} \equiv \frac{d\bar{\omega}}{dt}. \quad (3.4.2)$$

Because Eq. (3.4.1) is a general description of  $\bar{\omega}$ , it may be differentiated to obtain  $\bar{\alpha}$ . This operation requires that we evaluate the rate of change of the unit vectors  $\bar{e}_n$ . We use Eq. (3.3.16) for this purpose, but doing so requires a definition of the reference frame associated with each  $\bar{e}_n$ . Specifically,

*For each simple rotation, define an auxiliary moving reference frame  $x_n y_n z_n$ , such that one of the axes of  $x_n y_n z_n$  always coincides with that rotation axis. Hence,  $\bar{e}_n$  is either  $\bar{i}_n$ ,  $\bar{j}_n$ , or  $\bar{k}_n$ . Let  $\bar{\Omega}_n$  denote the angular velocity of  $x_n y_n z_n$ .*

Note that these auxiliary reference frames are quite unrestricted, other than the requirement that one of their coordinate axes should always align with a simple rotation axis. Any of them may actually be the  $xyz$  coordinate system, in which case the corresponding  $\bar{\Omega}_n \equiv \bar{\omega}$ . In general, a single auxiliary reference frame may be associated with more than

one simple rotation. Also, if an axis of rotation is stationary, we may let the corresponding reference frame be  $XYZ$ , corresponding to  $\bar{\Omega}_n = \bar{0}$ .

We apply the standard rules for derivatives to Eq. (3.4.1) According to Eq. (3.3.16), the time derivative of the axis directions is  $d\bar{e}_n/dt = \bar{\Omega}_n \times \bar{e}_n$ , so we find that

$$\bar{\alpha} = \sum_n (\dot{\omega}_n \bar{e}_n + \bar{\Omega}_n \times \omega_n \bar{e}_n). \quad (3.4.3)$$

An interesting aspect of this description of  $\bar{\alpha}$  is that the only derivatives we need to determine explicitly are the  $\dot{\omega}_n$  values.

It is imperative to understand the meaning of the terms in Eq. (3.4.3). Two types of contributions are associated with each simple rotation. An unsteady rotation rate,  $\dot{\omega}_n \neq 0$ , gives rise to an angular acceleration  $\dot{\omega}_n \bar{e}_n$  that is parallel to the rotation axis. In addition, even if all rotation rates are constant, there will be an angular acceleration term if the orientation of any rotation axis is not constant, corresponding to  $\bar{\Omega}_n \times \omega_n \bar{e}_n \neq \bar{0}$ . This type of angular acceleration is perpendicular to the rotation axis, as well as the angular velocity of that axis. Planar motion consists of a single simple rotation about an axis perpendicular to the plane. Because the orientation of this axis is constant, the angular acceleration in planar motion does not feature any effect associated with non-stationary rotation axes. This is one of the primary reasons why intuitive judgements based on experiences with planar motion are often incorrect.

After the individual terms in Eqs. (3.4.1) and (3.4.3) have been characterized, all vector quantities should be expressed in terms of a common set of components. This is necessary so that we may sum the terms by adding like components. The directions used for this purpose constitute the *global coordinate system*. One could use the stationary  $XYZ$  axes as the global system, but components relative to the  $xyz$  axes, whose angular motion is described by  $\bar{\omega}$  and  $\bar{\alpha}$ , often are more meaningful. Another possibility is to use one of the auxiliary reference frames  $x_n y_n z_n$  to describe components. A primary reason for the last choice is that expressing components relative to either  $XYZ$  or  $xyz$  might require evaluation of a rotation transformation matrix, whereas it might be possible to use visual inspection to construct the components relative to one of the auxiliary coordinate systems. This is especially so because, after we align one axis of  $x_n y_n z_n$  with its associated rotation axis, we are free to align its other axes in a manner that expedites the description of all vector components.

### 3.4.2 Procedure

Correct evaluation of  $\bar{\omega}$  and  $\bar{\alpha}$  for a moving  $xyz$  reference frame is of primary importance in several contexts. For that reason, it is appropriate to formalize the concepts and developments thus far into a sequence of steps that will address most situations.

1. Examine the overall rotation of the body of interest, which is defined as reference frame  $xyz$ . Conceptually decompose it into a sequence of simple rotations  $\omega_n$ ,



### 3.4 Angular Velocity and Acceleration

129

- $n = 1, 2, \dots$ , where the units of  $\omega_n$  are radians per second. (These simple rotations are typically the rotation of one part of the system with respect to another part.)
- For each rotation  $\omega_n$ , define a reference frame  $x_n y_n z_n$  such that one of its unit vectors  $\bar{i}_n$ ,  $\bar{j}_n$ , or  $\bar{k}_n$  always coincides with the corresponding rotation direction  $\bar{e}_n$ . Note that these reference frames may be fixed, or else execute some or all of the rotations associated with  $xyz$ , but they will never execute more rotations than  $xyz$ . Denote as  $\bar{e}_n$  the unit vector that is aligned with the axis  $\omega_n$  rotation axis.
  - Select a global coordinate system to be used for evaluating all vector components. The orientation of this coordinate system should facilitate describing all rotation directions  $\bar{e}_n$  based on the manner in which linear and angular dimensions of the system are described. It usually is convenient to use as the global system one of the set of reference frame axes already defined.
  - Construct the angular velocity vector  $\bar{\omega}$  of  $xyz$  by vectorially adding the simple rotation rates according to

$$\bar{\omega} = \omega_1 \bar{e}_1 + \omega_2 \bar{e}_2 + \dots \quad (3.4.4)$$

- Vectorially add the simple rotation rates of each  $x_n y_n z_n$  to construct the angular velocity vector  $\bar{\Omega}_n$ . The form of the superposition sum will be similar to Eq. (3.4.4).
- Form the angular acceleration  $\bar{\alpha}$  of  $xyz$  by differentiating  $\bar{\omega}$  in Eq. (3.4.4). For this differentiation, use the fact that  $\bar{e}_n$  is one of the unit vectors of  $x_n y_n z_n$ , so that  $d\bar{e}_n/dt = \bar{\Omega}_n \times \bar{e}_n$ . Thus this step gives

$$\bar{\alpha} = \dot{\omega}_1 \bar{e}_1 + \omega_1 (\bar{\Omega}_1 \times \bar{e}_1) + \dot{\omega}_2 \bar{e}_2 + \omega_2 (\bar{\Omega}_2 \times \bar{e}_2) + \dots \quad (3.4.5)$$


- Express each unit vector  $\bar{e}_n$  in terms of its components relative to the global coordinate system, in the form

$$\bar{e}_n = \ell_{nx} \hat{i} + \ell_{ny} \hat{j} + \ell_{nz} \hat{k} \quad (3.4.6)$$

where  $\hat{i}$ ,  $\hat{j}$ , and  $\hat{k}$  are the unit vectors of whichever coordinate system was selected as the global one.


- Substitute the component descriptions of the unit vectors given by Eq. (3.4.6) into the angular velocity of  $xyz$  described by Eq. (3.4.4), and collect like components. This gives  $\bar{\omega}$  in terms of components with respect to the global coordinate system.
- Substitute the component descriptions of the unit vectors given by Eq. (3.4.6) into each angular velocity  $\bar{\Omega}_n$  formed in Step 5, and collect like components. This gives each  $\bar{\Omega}_n$  in terms of components with respect to the global coordinate system.
- Substitute the component descriptions of the unit vectors given by Eq. (3.4.6), and of each  $\bar{\Omega}_n$  obtained in Step 9, into the angular acceleration given by Eq. (3.4.5). Collect like components. This gives  $\bar{\alpha}$  in terms of components with respect to the global coordinate system.

**EXAMPLE 3.9** The disk rotates about shaft  $AB$  at 3600 rev/min as the system rotates about the vertical axis at 20 rad/s. Determine the angular velocity and angular acceleration of the disk.



Example 3.9

**SOLUTION** This straightforward example illustrates the procedural steps leading to  $\bar{\omega}$  and  $\bar{\alpha}$ . We attach  $xyz$  to the disk, so that  $\bar{\omega}$  describes the angular velocity of that body. There are two rotations:  $\omega_1 = 20$  rad/s, with  $\bar{e}_1$  vertically upward by the right-hand rule, and  $\omega_2 = 3600 (2\pi/60)$  rad/s with  $\bar{e}_2$  directed from center  $B$  to junction  $A$ . To describe the first rotation we select the fixed  $XYZ$  as the first auxiliary reference frame, with  $Z$  defined to be vertical, so that  $\bar{e}_1 = \bar{K}$  and  $\bar{\Omega}_1 = \bar{0}$ . Because there are only two rotations, we may use  $xyz$  as  $x_2y_2z_2$ . Although  $xyz$  must be attached to the disk, we are free to orient it in a manner that expedites description of the second rotation axis. With this in mind, we observe that shaft  $AB$  has a constant orientation relative to the disk, which enables us to align the  $z$  axis with this shaft. Then  $\bar{e}_2 = \bar{k}$  and  $\bar{\Omega}_2 = \bar{\omega}$ . We show the rotation direction vectors in a simple sketch as an aid to the task of evaluating components.



Coordinate systems for describing the angular motion of the disk.

Several features of this sketch should be noted. First, the location of the origin of each coordinate system is irrelevant to the task of evaluating the angular motion. Second, the orientations of the fixed  $X$  and  $Y$  axes are unimportant from the viewpoint of the disk, so these axes have been omitted from the sketch. Third, the only

### 3.4 Angular Velocity and Acceleration

131

aspect of the orientation of  $xyz$  requiring specification is that the  $z$  axis coincide with shaft  $AB$ . The sketch depicts an arbitrary instant, so the  $z$  axis is aligned with shaft  $AB$ , but the  $x$  and  $y$  axes lie in neither the horizontal nor the vertical plane. The arbitrariness of these axes will be useful for later developments.

For a global coordinate system we define  $\hat{x}\hat{y}\hat{z}$  to be attached to shaft  $AB$  such that the  $\hat{z}$  axis is always aligned with the  $z$  axis, and the  $\hat{x}$  axis is the horizontal diameter of the disk. This choice for the global system simultaneously facilitates describing  $\bar{e}_1$  and  $\bar{e}_2$ . The sketch also depicts the  $\hat{x}\hat{y}\hat{z}$  axes.

The general description of the angular velocity of  $xyz$  is

$$\bar{\omega} = \omega_1 \bar{e}_1 + \omega_2 \bar{e}_2 = \omega_1 \bar{K} + \omega_2 \bar{k}. \quad (1)$$

Because the first auxiliary reference frame is stationary, and the second one is  $xyz$ , we have

$$\bar{\Omega}_1 = \bar{0}, \quad \bar{\Omega}_2 = \bar{\omega}.$$

The rotation rates are constant, so the corresponding description of the angular acceleration of  $xyz$  is

$$\bar{\alpha} = \omega_1 \bar{\Omega}_1 \times \bar{K} + \omega_2 \bar{\Omega}_2 \times \bar{k} = \omega_2 \bar{\omega} \times \bar{k}. \quad (2)$$

We find the global components of the unit vectors by inspection of the sketch, which leads to

$$\bar{K} = \sin 60^\circ \hat{j} + \cos 60^\circ \hat{k}, \quad \bar{k} = \hat{k}. \quad (3)$$

Substitution of these unit vectors into Eqs. (1) and (2) yields


$$\begin{aligned} \bar{\omega} &= 0.866\omega_1 \hat{j} + (0.5\omega_1 + \omega_2) \hat{k}, \\ \bar{\alpha} &= \omega_2 [0.866\omega_1 \hat{j} + (0.5\omega_1 + \omega_2) \hat{k}] \times \hat{k} = 0.866\omega_1 \omega_2 \hat{i}. \end{aligned}$$

Evaluation of these expressions at the specified rotation rates gives

$$\begin{aligned} \bar{\omega} &= 17.32 \hat{j} + 387.00 \hat{k} \text{ rad/s}, \\ \bar{\alpha} &= 6530 \hat{i} \text{ rad/s}^2. \end{aligned} \quad \triangleleft$$


There is a ready explanation for the sense of the angular acceleration. The general expression for  $\bar{\omega}$  shows that it is the sum of two terms:  $\omega_1 \bar{K}$ , which is constant, and  $\omega_2 \bar{k}$ , which rotates about the vertical axis. The rate of change of a vector that is due to its rotation is in the sense of the movement of the vector's tip when its tail is considered to be stationary. The tip of the  $z$  axis moves horizontally in the rotation about the  $Z$  axis, so the angular acceleration is horizontal in the sense of positive  $\hat{i}$ . In general, considering whether the result for  $\bar{\alpha}$  makes sense is an excellent way to check one's work.

**EXAMPLE 3.10** The gyroscopic turn indicator consists of a flywheel that spins about its axis of symmetry at the constant rate  $\omega_1$  relative to the gimbal, as the assembly rotates about the fixed horizontal shaft at the variable rate  $\omega_2$ . The angle  $\beta$  locating the plane of the gimbal relative to the horizontal shaft is an arbitrary function of time. Determine the angular acceleration of the flywheel at an arbitrary instant.



Example 3.10

**SOLUTION** The angular motion is more complicated here than it was in the previous example, so this analysis will provide a more complete picture of the procedure. Let  $xyz$  be attached to the flywheel, so that its angular motion is identical to that of the flywheel. We begin by identifying the constituent simple rotations and draw a sketch depicting the rotation unit vectors and associated coordinate axes.



Coordinate systems for the turn indicator.

The  $\omega_2$  rotation is about the fixed horizontal shaft. Correspondingly, we let  $x_2y_2z_2$  be the fixed reference frame  $XYZ$  defined such that  $\bar{e}_2 = \bar{I}$ . The  $\omega_1$  rotation is about the axis of the flywheel. This direction is fixed relative to the flywheel. We therefore select  $x_1y_1z_1$  as  $xyz$ , with the specification that the  $x$  axis coincides with the flywheel's axis of symmetry, so that  $\bar{e}_1 = \bar{i}$ . The fact that  $\beta$  is variable means

### 3.4 Angular Velocity and Acceleration

133

that there is a third rotation,  $\dot{\beta}$ , about an axis that is always perpendicular to the horizontal shaft. To describe it, we attach reference frame  $x_3y_3z_3$  to the gimbal supporting the flywheel, with the  $z_3$  axis defined such that  $\bar{e}_3 = \bar{k}_3$ . In the sketch the  $x_3$  axis has been aligned with the gimbal's shaft, because doing so makes  $x_3y_3z_3$  a convenient global coordinate system. (In fact, because  $\bar{e}_1$  is parallel to the  $x_3$  axis, this  $x_3y_3z_3$  reference frame could also have been used to describe the  $\omega_1$  rotation.) To develop procedures suitable to later developments we observe that because  $xyz$  rotates at  $\omega_1$  relative to the gimbal, at the arbitrary instant depicted in the sketch the  $y$  and  $z$  axes have rotated away from  $y_3$  and  $z_3$ , respectively.

The angular velocity of the flywheel is the sum of the simple rotations, so

$$\bar{\omega} = \omega_1 \bar{e}_1 + \omega_2 \bar{e}_2 + \dot{\beta} \bar{e}_3 = \omega_1 \bar{i} + \omega_2 \bar{I} + \dot{\beta} \bar{k}_3.$$

The auxiliary reference frame for  $\bar{e}_2$  is  $XYZ$ , the frame for  $\bar{e}_1$  is  $xyz$ , and the frame for  $\bar{e}_3$  is  $x_3y_3z_3$ , which executes the  $\omega_2$  and  $\dot{\beta}$  rotations. Thus we have

$$\bar{\Omega}_1 = \bar{\omega}, \quad \bar{\Omega}_2 = \bar{0}, \quad \bar{\Omega}_3 = \omega_2 \bar{I} + \dot{\beta} \bar{k}_3.$$

The only rotation rate that is specified to be constant is  $\omega_1$ , so the general description of  $\bar{\alpha}$  corresponding to the preceding expression for  $\bar{\omega}$  is

$$\begin{aligned} \bar{\alpha} &= \omega_1 (\bar{\Omega}_1 \times \bar{i}) + \dot{\omega}_2 \bar{I} + \omega_2 (\bar{\Omega}_2 \times \bar{I}) + \ddot{\beta} \bar{k}_3 + \dot{\beta} (\bar{\Omega}_3 \times \bar{k}_3) \\ &= \omega_1 \bar{\omega} \times \bar{i} + \dot{\omega}_2 \bar{I} + \ddot{\beta} \bar{k}_3 + \dot{\beta} (\omega_2 \bar{I} + \dot{\beta} \bar{k}_3) \times \bar{k}_3. \end{aligned}$$

We use geometrical projections to describe the global  $\bar{i}_3 \bar{j}_3 \bar{k}_3$  components of the unit vectors. This gives

$$\bar{i} = \bar{i}_3, \quad \bar{I} = \cos \beta \bar{i}_3 - \sin \beta \bar{j}_3.$$

Substitution of these representations into the expressions for  $\bar{\omega}$  and  $\bar{\alpha}$  gives

$$\begin{aligned} \bar{\omega} &= (\omega_1 + \omega_2 \cos \beta) \bar{i}_3 - \omega_2 \sin \beta \bar{j}_3 + \dot{\beta} \bar{k}_3, \\ \bar{\alpha} &= (\dot{\omega}_2 \cos \beta - \dot{\beta} \omega_2 \sin \beta) \bar{i}_3 + (-\dot{\omega}_2 \sin \beta + \omega_1 \dot{\beta} - \dot{\beta} \omega_2 \cos \beta) \bar{j}_3 \\ &\quad + (\ddot{\beta} + \omega_1 \omega_2 \sin \beta) \bar{k}_3. \end{aligned} \quad \triangleleft$$

Each term in  $\bar{\alpha}$  can be explained physically. Unsteady values of  $\omega_2$  and  $\dot{\beta}$  give rise to angular accelerations that are parallel to the respective rotation axes. Terms that are the products of two rotation rates, and therefore exist even if the rates are constant, represent angular acceleration effects that are perpendicular to the simple rotation axes. For example, the terms containing  $\dot{\beta} \omega_2$  are a consequence of  $\bar{e}_3$  rotating at  $\omega_2 \bar{e}_2$ , which makes the tip of  $\bar{e}_3$  moves perpendicularly to the  $X$  axis in the  $\hat{x}_3 \hat{y}_3$  plane. In contrast,  $\bar{e}_1$  rotates at  $\dot{\beta} \bar{e}_3$  and  $\omega_2 \bar{e}_2$ . The  $\dot{\beta} \bar{e}_3$  rotation makes the tip of  $\bar{e}_1$  move in the  $\hat{j}_3$  direction, which is the direction of the  $\omega_1 \dot{\beta}$  term in  $\bar{\alpha}$ . The term  $\omega_1 \omega_2 \sin \beta$  in the  $\bar{k}_3$  component of  $\bar{\alpha}$  arises because the  $\omega_2 \bar{e}_2$  rotation makes the tip of  $\bar{e}_1$  move in the  $\hat{k}_3$  direction. The  $\sin \beta$  coefficient in this term arises because only the component of  $\bar{e}_1$  perpendicular to the  $\bar{I}$  axis changes in this rotation.

### 3.5 VELOCITY AND ACCELERATION ANALYSIS USING A MOVING REFERENCE FRAME

This chapter began with the introduction of a moving reference frame as an aid to describing displacement. Specializing the relations to the case of infinitesimal movements led us to Eq. (3.3.9) for velocity. Application of that formula required evaluation of angular velocity, and we anticipated later developments by also considering angular acceleration. We now return to the study of point motion by deriving a formula for the acceleration of a point whose movement is observed from a moving reference frame.

Equation (3.3.9) provides a general description of velocity, so it may be differentiated. The time derivative of the origin's velocity  $\bar{v}_{O'}$  is its acceleration  $\bar{a}_{O'}$ . The relative velocity  $(\bar{v}_P)_{xyz}$  is defined by Eq. (3.3.11) in terms of components relative to the moving reference frame. Equation (3.3.15) gives the derivative of a vector described in such a manner, where the  $\partial/\partial t$  operator defined in Eq. (3.3.14) denotes a time derivative that ignores the fact that the direction of the unit vectors is not constant. Because the relative velocity components are the derivatives of the position coordinates, the relative acceleration is given by

$$(\bar{a}_P)_{xyz} \equiv \frac{\partial}{\partial t} (\bar{v}_P)_{xyz} = \ddot{x}_P \bar{i} + \ddot{y}_P \bar{j} + \ddot{z}_P \bar{k}. \quad (3.5.1)$$

Correspondingly, we find from Eq. (3.3.15) that

$$\frac{d}{dt} (\bar{v}_P)_{xyz} = (\bar{a}_P)_{xyz} + \bar{\omega} \times (\bar{v}_P)_{xyz}. \quad (3.5.2)$$

Now consider the last term in Eq. (3.3.9). The time derivative of  $\bar{\omega}$  is  $\bar{\alpha}$ , and Eq. (3.3.13) gives the time derivative of  $\bar{r}_{P/O'}$ . We therefore have

$$\frac{d}{dt} (\bar{\omega} \times \bar{r}_{P/O'}) = \bar{\alpha} \times \bar{r}_{P/O'} + \bar{\omega} \times [(\bar{v}_P)_{xyz} + \bar{\omega} \times \bar{r}_{P/O'}]. \quad (3.5.3)$$


We obtain the acceleration formula by adding Eqs. (3.5.2) and (3.5.3) to  $\bar{a}_{O'}$ . For later use the result is accompanied by the previously derived expression for velocity:

$$\begin{aligned} \bar{v}_P &= \bar{v}_{O'} + (\bar{v}_P)_{xyz} + \bar{\omega} \times \bar{r}_{P/O'}, \\ \bar{a}_P &= \bar{a}_{O'} + (\bar{a}_P)_{xyz} + \bar{\alpha} \times \bar{r}_{P/O'} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/O'}) + 2\bar{\omega} \times (\bar{v}_P)_{xyz}. \end{aligned} \quad (3.5.4)$$

With one exception, the terms in these expressions could have been anticipated as a simple superposition of motion of the origin and motion relative to  $xyz$ . The velocity term  $\bar{\omega} \times \bar{r}_{P/O'}$  and the acceleration term  $\bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/O'})$  are described in Fig. 3.11. By definition,  $\bar{\omega} \times \bar{r}_{P/O'}$  is perpendicular to the plane formed by  $\bar{\omega}$  and  $\bar{r}_{P/O'}$ , and its magnitude is  $|\bar{\omega}| r_\perp$ , where  $r_\perp$  is the component of  $\bar{r}_{P/O'}$  perpendicular to  $\bar{\omega}$ . Thus this term is like the azimuthal velocity  $R\dot{\theta}$  that occurred in cylindrical coordinates. Furthermore, it follows that the magnitude of  $\bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/O'})$  is  $|\bar{\omega}|^2 r_\perp$  and that it is directed along the perpendicular line from point  $P$  toward the rotation axis. Thus this term is a centripetal acceleration, like the term  $R\dot{\theta}^2$  in cylindrical coordinates. Another acceleration term associated with the rotational motion is  $\bar{\alpha} \times \bar{r}_{P/O'}$ . Although it appears to be analogous to the velocity term  $\bar{\omega} \times \bar{r}_{P/O'}$ , in spatial motion the angular acceleration is nonzero and

### 3.5 Velocity and Acceleration Analysis Using a Moving Reference Frame

135



**Figure 3.11.** Construction of the centripetal acceleration of a point.

not parallel to the angular velocity, even if all rotation rates are constant. As a result, the direction of the corresponding acceleration term will generally not be perpendicular to the plane formed by the rotation axis and  $\bar{r}_{P/O'}$ .

The acceleration term  $2\bar{\omega} \times (\bar{v}_P)_{xyz}$  is not intuitively obvious, but it is readily explained. As might be guessed from the two factor, it is the Coriolis acceleration that was encountered in the study of curvilinear coordinates, for example,  $2\dot{R}\dot{\theta}$  in cylindrical coordinates. In fact, as we saw in the study of curvilinear coordinates, Coriolis acceleration actually arises from two distinct effects that have equal importance. Equation (3.5.2) indicates that half the Coriolis acceleration stems from the fact that the components of relative velocity have a variable orientation that is due to rotation of the  $xyz$  axes. The other half appears in Eq. (3.5.3), where it is associated with the fact that the transverse velocity  $\bar{\omega} \times \bar{r}_{P/O'}$  is not constant if the coordinates of point  $P$  with respect to  $xyz$  are not constant. Thus it is to some extent a misnomer to use a single name to refer to  $2\bar{\omega} \times (\bar{v}_P)_{xyz}$ .

One aspect of the relative velocity  $(\bar{v}_P)_{xyz}$  and relative acceleration  $(\bar{a}_P)_{xyz}$  greatly facilitates their evaluation. These terms may be visualized as the effects that would remain if the reference frame were held stationary. They were described in Eqs. (3.3.11) and (3.5.1), respectively, in terms of a Cartesian coordinate description. However, other kinematical descriptions, such as path variables or curvilinear coordinates, might be more appropriate in some situations. If such an approach is employed, it is necessary to convert those components to the global set of components used to represent all vectors.

It is instructive to close this discussion by considering two special cases. The situation in which the  $xyz$  frame translates corresponds to  $\bar{\omega}$  being identically zero. Hence,  $\bar{\alpha}$  also is zero. The relative motion equations then reduce to

$$\begin{aligned}\bar{v}_P &= \bar{v}_{O'} + (\bar{v}_P)_{xyz}, \\ \bar{a}_P &= \bar{a}_{O'} + (\bar{a}_P)_{xyz}.\end{aligned}\tag{3.5.5}$$

The motion of the origin and of the point relative to the translating reference frame are additive—there are no corrections for direction changes that are due to rotation. If  $xyz$ , as well as  $XYZ$ , is fixed, so that  $\bar{v}_{O'} = \bar{0}$  and  $\bar{a}_{O'} = \bar{0}$ , then the preceding relations show that the velocity and acceleration are the same, regardless of which fixed reference frame is selected. A more important observation arises when  $xyz$  is translating at a constant velocity, so that  $\bar{a}_{O'} = \bar{0}$ . (Note that this condition requires that the origin  $O'$  follow a

straight path.) The second of Eqs. (3.5.5) shows that  $\bar{a}_P = (\bar{a}_P)_{xyz}$  in this case. A reference frame translating at constant velocity is said to be an *inertial* or *Galilean reference frame*. The terminology arises from the fact that the absolute acceleration is observable from the reference frame, so the frame may be employed to formulate Newton's Laws.

The second special case arises when point  $P$  is fixed with respect to the moving reference frame. Because the position coordinates then are constant,  $(\bar{v}_P)_{xyz}$  and  $(\bar{a}_P)_{xyz}$  are both identically zero. This simplifies the velocity and acceleration relations to

$$\begin{aligned}\bar{v}_P &= \bar{v}_{O'} + \bar{\omega} \times \bar{r}_{P/O'}, \\ \bar{a}_P &= \bar{a}_{O'} + \bar{\alpha} \times \bar{r}_{P/O'} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/O'}).\end{aligned}\tag{3.5.6}$$

A primary reason for highlighting this situation is that it is descriptive of the motion of a rigid body. If  $xyz$  is attached to the body, then the position vectors between points in the body have constant components relative to the moving reference frame. Also, the angular motion of the body and of  $xyz$  are synonymous in this case. The motion of rigid bodies is the focus of the next chapter.

General equations (3.5.4) exemplify the notion that using a moving reference frame allows us to decompose a complicated motion into a set of simpler kinematical analyses associated with the individual terms in those equations. Application of these formulas requires definition of  $xyz$ . If it is required that  $\bar{\omega}$  and  $\bar{\alpha}$  of a body be determined, then  $xyz$  should be attached to that body. Otherwise,  $xyz$  seldom is specified *a priori*. Its selection affects the individual terms, although the ultimate results for velocity and acceleration will be unaffected. Depending on how  $xyz$  is defined, some terms will be easier to determine, whereas others will be more difficult. Some general criteria can be identified. The choice of the body to which  $xyz$  is attached dictates which simple rotations combine to form  $\bar{\omega}$ . Selecting  $xyz$  to execute many rotations complicates the analysis of  $\bar{\omega}$  and  $\bar{\alpha}$ . However, the methodology laid out in the previous section is reasonably robust, so no selection is likely to be completely overwhelming. Furthermore, letting  $xyz$  execute many of the rotations is likely to simplify analysis of the relative motion terms  $(\bar{v}_P)_{xyz}$  and  $(\bar{a}_P)_{xyz}$ . Thus, a guideline for selecting the attachment of  $xyz$  is that it should execute as many rotations as possible, provided that one can evaluate the corresponding  $\bar{\omega}$  and  $\bar{\alpha}$ . (Once again, the exception is that if  $\bar{\omega}$  and  $\bar{\alpha}$  of a certain body must be determined, then  $xyz$  must be attached to that body.)

The selection of the origin  $O'$  affects the terms  $\bar{v}_{O'}$  and  $\bar{a}_{O'}$ , as well as  $\bar{r}_{P/O'}$  in Eqs. (3.2.4) and (3.2.7) for displacement. This selection is restricted by the requirement that point  $O'$  be one of the points of the body to which  $xyz$  is attached. Thus an optimal approach is to select the body to which  $xyz$  is attached by considering the difficulty entailed in describing  $\bar{\omega}$  and  $\bar{\alpha}$ , simultaneously with considering whether some point in the body follows a relatively simple path so that the description of  $\bar{v}_{O'}$  and  $\bar{a}_{O'}$  will be manageable. (In complicated systems, evaluation of  $\bar{v}_{O'}$  and  $\bar{a}_{O'}$  might require a separate analysis with a different moving reference frame.)

As we did for the analysis of  $\bar{\omega}$  and  $\bar{\alpha}$ , we use a global coordinate system to represent the components of all vectors, so that the various terms may be combined. The previous section stated a criterion that the orientation of these axes should be selected




### 3.5 Velocity and Acceleration Analysis Using a Moving Reference Frame

137

to facilitate representation of the unit vectors  $\bar{e}_n$  for the rotations. Because other terms, notably  $(\bar{v}_P)_{xyz}$  and  $(\bar{a}_P)_{xyz}$ , must now be represented in component form, it is best that the global system be selected to facilitate describing all terms. This requires striking a balance. For example, a certain selection might be ideal for describing the relative motion terms while simultaneously complicating the component description of the  $\bar{e}_j$  rotation directions. If necessary, one can always employ rotation transformation matrices to describe the components of any troublesome vectors.

**EXAMPLE 3.11** Bar  $BC$  is pinned to the T-bar, which is rotating about the vertical axis at constant rate  $\Omega$ . Angle  $\theta$  is an arbitrary function of time. Determine the velocity and acceleration of point  $C$  using the following alternative approaches: (a) attach the  $xyz$  reference frame to the T-bar; (b) attach the  $xyz$  reference frame to bar  $BC$ .




Example 3.11

**SOLUTION** By employing two different approaches, this example provides insight into the decisions one must make. In the first approach, attaching  $xyz$  to the T-bar means that the sole rotation of  $xyz$  is  $\Omega$  about the fixed vertical axis. Thus we define the  $Z$  axis such that  $\bar{e}_1 = \bar{K}$ . Because  $\Omega$  is specified to be constant, the general descriptions of angular motion are

$$\bar{\omega} = \Omega \bar{e}_1 = \Omega \bar{K}, \quad \bar{\Omega}_1 = \bar{0}, \quad \bar{\alpha} = \bar{\Omega}_1 \times \bar{K} = \bar{0}.$$

Any point on the vertical axis of rotation is stationary. Selecting the origin  $O'$  to be point  $A$  simplifies the description of  $\bar{r}_{P/O'}$  and gives  $\bar{v}_{O'} = \bar{a}_{O'} = \bar{0}$ . We orient  $xyz$  consistently with the way in which the configuration of the system is specified and show our choice in a line sketch.



Kinematical analysis with  $xyz$  as a reference frame that is attached to the T-bar.

To analyze the relative motion we visualize bringing  $xyz$  to rest by setting  $\Omega = 0$ . Bar  $BC$  would still move in the vertical plane as it pivots about pin  $B$ . Thus end  $C$  moves in a circular path at angular speed  $\dot{\theta}$  relative to  $xyz$ . Polar coordinates having origin at point  $B$  are suitable for describing this relative motion, with the radial distance  $R = L_2$  and  $\theta$  being the polar angle. The associated unit vectors are shown in the sketch. The corresponding descriptions of the relative velocity and acceleration are

$$(\bar{v}_C)_{xyz} = L_2 \dot{\theta} \bar{e}_\theta, \quad (\bar{a}_C)_{xyz} = -L_2 \dot{\theta}^2 \bar{e}_R + L_2 \ddot{\theta} \bar{e}_\theta.$$

The axes of  $xyz$  are convenient directions for representing vectors, so we use them as the global directions. (An alternative definition would align the  $\hat{x}$  axis with bar  $BC$ , and place the  $\hat{z}$  axis in the vertical plane. This would simplify the description of  $\bar{e}_R$  and  $\bar{e}_\theta$ , but slightly complicate  $\bar{K}$ .) The global descriptions of the unit vectors are

$$\bar{K} = -\bar{k}, \quad \bar{e}_R = \cos \theta \bar{i} - \sin \theta \bar{k}, \quad \bar{e}_\theta = -\sin \theta \bar{i} - \cos \theta \bar{k}.$$

The corresponding relative position is

$$\bar{r}_{C/O'} = (L_1 + L_2 \cos \theta) \bar{i} - L_2 \sin \theta \bar{k}.$$

We may now assemble the individual terms. For velocity we have

$$\begin{aligned} \bar{v}_C &= (\bar{v}_C)_{xyz} + \bar{\omega} \times \bar{r}_{C/O'} \\ &= L_2 \dot{\theta} (-\sin \theta \bar{i} - \cos \theta \bar{k}) + (-\Omega \bar{k}) \times [(L_1 + L_2 \cos \theta) \bar{i} - L_2 \sin \theta \bar{k}], \\ \bar{v}_C &= -L_2 \dot{\theta} \sin \theta \bar{i} - (L_1 + L_2 \cos \theta) \Omega \bar{j} - L_2 \dot{\theta} \cos \theta \bar{k}. \end{aligned} \quad \triangleleft$$


A shortcut for the evaluation of  $\bar{\omega} \times (\bar{\omega} \times \bar{r}_{C/O'})$  is to retain  $\bar{\omega} \times \bar{r}_{C/O'}$  from the velocity analysis. Thus we have

$$\begin{aligned} \bar{a}_C &= (\bar{a}_C)_{xyz} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{C/O'}) + 2\bar{\omega} \times (\bar{v}_C)_{xyz} \\ &= -L_2 \dot{\theta}^2 (\cos \theta \bar{i} - \sin \theta \bar{k}) + L \ddot{\theta} (-\sin \theta \bar{i} - \cos \theta \bar{k}) + (-\Omega \bar{k}) \\ &\quad \times [-(L_1 + L_2 \cos \theta) \Omega \bar{j}] + 2(-\Omega \bar{k}) \times [L_2 \dot{\theta} (-\sin \theta \bar{i} - \cos \theta \bar{k})] \quad \triangleleft \\ &= [-L_2 \dot{\theta}^2 \cos \theta - L \ddot{\theta} \sin \theta - (L_1 + L_2 \cos \theta) \Omega^2] \bar{i} + 2L \Omega \dot{\theta} \sin \theta \bar{j} \\ &\quad + (L_2 \dot{\theta}^2 \sin \theta - L \ddot{\theta} \cos \theta) \bar{k}. \end{aligned}$$

Obviously, changing the selection of the moving reference frame should not alter the result. To avoid confusion with the preceding analysis, let  $x'y'z'$  denote the moving reference frame that is attached to bar  $BC$ . The angular velocity of this bar is the sum of  $\Omega$  about the vertical axis and  $\dot{\theta}$  about an axis that is perpendicular to the plane of the T-bar. Both simple rotations are shown in a new sketch.

### 3.5 Velocity and Acceleration Analysis Using a Moving Reference Frame

139



Kinematical analysis using  $x'y'z'$  as a reference frame that is attached to the swinging bar  $BC$ .

As was done in the previous analysis, fixed  $XYZ$  can be used to describe  $\bar{e}_1$ . To describe the  $\dot{\theta}$  rotation we attach  $x_2y_2z_2$  to the T-bar, with the  $y_2$  axis outward from the plane of the sketch, so that  $\bar{e}_2 = \bar{j}_2$ . The angular velocity  $\bar{\Omega}_2$  then consists solely of the rotation about the vertical axis. Thus

$$\bar{\omega} = \Omega \bar{e}_1 + \dot{\theta} \bar{e}_2 = \Omega \bar{K} + \dot{\theta} \bar{j}_2, \quad \bar{\Omega}_1 = \bar{0}, \quad \bar{\Omega}_2 = \Omega \bar{K}.$$

The angular acceleration corresponding to constant  $\Omega$  and variable  $\dot{\theta}$  is

$$\bar{\alpha} = \ddot{\theta} \bar{j}_2 + \dot{\theta} (\bar{\Omega}_2 \times \bar{j}_2) = \ddot{\theta} \bar{j}_2 + \dot{\theta} \Omega (\bar{K} \times \bar{j}_2).$$

The guideline for the selection of the origin  $O'$  requires that it be a point in bar  $BC$ , which is the body to which  $x'y'z'$  is attached. The only such point executing a simple motion is end  $B$ , which follows a circular path in the horizontal plane at constant angular speed  $\Omega$ . We may describe this motion in cylindrical coordinates whose axis is  $z_2$ , with the  $x_2$  axis parallel to arm  $AB$ , which is the  $\bar{e}_R$  direction. Then the  $y_2$  axis is opposite to  $\bar{e}_\theta$ . Correspondingly, the motion of the origin is given by

$$\bar{v}_{O'} = -L_1 \Omega \bar{j}_2, \quad \bar{a}_{O'} = -L_1 \Omega^2 \bar{i}_2.$$

Because  $xyz$  has been defined to be attached to bar  $BC$ , point  $C$  remains fixed from the viewpoint of this reference frame. Thus,

$$(\bar{v}_C)_{xyz} = (\bar{a}_C)_{xyz} = \bar{0}.$$

Orienting  $x'y'z'$  as depicted in the sketch facilitates the description of relative position. We correspondingly find that

$$\bar{K} = \sin \theta \bar{i}' - \cos \theta \bar{k}', \quad \bar{j}_2 = \bar{j}', \quad \bar{i}_2 = \cos \theta \bar{i}' + \sin \theta \bar{k}', \quad \bar{r}_{C/O'} = L_2 \bar{i}'.$$

The global descriptions of the angular motion variables are

$$\bar{\omega} = \Omega (\sin \theta \bar{i}' - \cos \theta \bar{k}') + \dot{\theta} \bar{j}',$$

$$\bar{\alpha} = \ddot{\theta} \bar{j}' + \dot{\theta} \Omega [(\sin \theta \bar{i}' - \cos \theta \bar{k}') \times \bar{j}'] = \ddot{\theta} \bar{j}' + \dot{\theta} \Omega (\cos \theta \bar{i}' + \sin \theta \bar{k}').$$

The nonzero terms in the general velocity equation are

$$\begin{aligned} \bar{v}_C &= \bar{v}_{O'} + \bar{\omega} \times \bar{r}_{C/O'} \\ &= -L_1 \Omega \bar{j}' + [\Omega (\sin \theta \bar{i}' - \cos \theta \bar{k}') + \dot{\theta} \bar{j}'] \times L_2 \bar{i}' \\ &= -(L_1 + L_2 \cos \theta) \Omega \bar{j}' - L_2 \dot{\theta} \bar{k}'. \end{aligned}$$


◁

The nonzero terms in the general acceleration equation are

$$\begin{aligned}\bar{a}_C &= \bar{a}_{O'} + \bar{\alpha} \times \bar{r}_{C/O'} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{C/O'}) \\ &= -L_1 \Omega^2 (\cos \theta \bar{i}' + \sin \theta \bar{k}') + [\ddot{\theta} \bar{j}' + \dot{\theta} \Omega (\cos \theta \bar{i}' + \sin \theta \bar{k}')] \times L_2 \bar{i}' \\ &\quad + [\Omega (\sin \theta \bar{i}' - \cos \theta \bar{k}') + \dot{\theta} \bar{j}'] \times (-L_2 \Omega \cos \theta \bar{j}' - L_2 \dot{\theta} \bar{k}') \\ &= [-(L_1 + L_2 \cos \theta) \Omega^2 \cos \theta - L_2 \dot{\theta}^2] \bar{i}' + 2L_2 \Omega \dot{\theta} \sin \theta \bar{j}' \\ &\quad + [-(L_1 + L_2 \cos \theta) \Omega^2 \sin \theta - L_2 \ddot{\theta}] \bar{k}'.\end{aligned}$$

Different global coordinate systems were used to represent each set of results, so the components of  $\bar{v}_C$  and  $\bar{a}_C$  are not identical. One check that the vectors are consistent lies in the fact that the  $y'$  axis for the second analysis coincides with the  $\hat{y}$  axis for the first. Correspondingly, we see that those velocity and acceleration components match. Another way to verify that both sets of results represent the same vectors is to apply the rotation transformation between  $x'y'z'$  and  $\hat{x}\hat{y}\hat{z}$  to transform one set of components to the other. A third approach is to sketch the vector resultant of similar terms. For example, the  $(L_1 + L_2 \cos \theta) \Omega^2$  terms obtained in either analysis represent a centripetal acceleration that is perpendicular to the vertical axis directed from point  $B$  to point  $A$ .

**EXAMPLE 3.12** The turntable rotates at angular speed  $\omega_1$ , and the disk rotates at angular speed  $\omega_2$  relative to the turntable. Both rates are constant. Determine the velocity and acceleration of point  $C$  on the perimeter of the disk using (a) a moving coordinate system that is attached to the turntable; (b) a moving coordinate system that is attached to the disk.




Example 3.12

**SOLUTION** As in the previous example, the intent here is to illustrate the decisions and trade-offs involved in using various moving reference frames. In the first analysis, we place the origin of  $xyz$  at the center of rotation of the turntable, point  $A$ . The reference frame for the second analysis is  $x'y'z'$ . We place its origin at the

### 3.5 Velocity and Acceleration Analysis Using a Moving Reference Frame

141

pivot point  $B$ , because this is the only point on the disk that follows a simple path. The system is in planar motion, so we orient the  $z$  and  $z'$  axes normal to the plane. We use  $xyz$  as the global directions for both analyses to track the differences between the two solutions. The alignments depicted in the sketch are consistent with the manner in which the system is described.



Analysis of the motion of point  $C$  using coordinate systems  $xyz$  attached to the turntable and  $x'y'z'$  attached to the disk.

When  $xyz$  is attached to the turntable, it rotates at angular speed  $\omega_1$  about the  $z$  axis. This direction is constant, as is the rotation rate, so

$$\bar{\omega} = \omega_1 \bar{k}, \quad \bar{\alpha} = \bar{0}.$$

The origin is stationary, so  $\bar{v}_A = \bar{a}_A = \bar{0}$ . We could use polar coordinates to formulate the relative velocity and acceleration, but we employ the relative motion equations for this task as a way of emphasizing their utility. We visualize the motion that would remain if the turntable were stationary. The disk would then solely rotate at angular speed  $\omega_2$  about point  $B$ , which would be stationary. Points  $B$  and  $C$  have fixed positions when viewed from the disk, so we may employ Eqs. (3.5.6) with the angular motion being that of the disk in the relative motion,  $\bar{\omega}_{\text{rel}} = \omega_2 (-\bar{k})$ ,  $\bar{\alpha}_{\text{rel}} = \dot{\omega}_2 (-\bar{k}) = \bar{0}$ . Correspondingly, we have

$$(\bar{v}_C)_{xyz} = \bar{\omega}_{\text{rel}} \times \bar{r}_{C/B}, \quad (\bar{a}_C)_{xyz} = \bar{\omega}_{\text{rel}} \times (\bar{\omega}_{\text{rel}} \times \bar{r}_{C/B}).$$

The nonzero terms in Eqs. (3.5.4) for the motion of point  $C$  are

$$\bar{v}_C = (\bar{v}_C)_{xyz} + \bar{\omega} \times \bar{r}_{C/A},$$

$$\bar{a}_C = (\bar{a}_C)_{xyz} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{C/A}) + 2\bar{\omega} \times (\bar{v}_C)_{xyz}.$$

The  $xyz$  coordinate axes serve as a convenient global system. Evaluation of the velocity proceeds as follows:

$$\begin{aligned} (\bar{v}_C)_{xyz} &= (-\omega_2 \bar{k}) \times (R \cos \theta \bar{i} - R \sin \theta \bar{j}) = \omega_2 R (-\sin \theta \bar{i} - \cos \theta \bar{j}), \\ \bar{v}_C &= \omega_2 R (-\sin \theta \bar{i} - \cos \theta \bar{j}) + (\omega_1 \bar{k}) \times [(L + R \cos \theta) \bar{i} - R \sin \theta \bar{j}] \\ &= (\omega_1 - \omega_2) R \sin \theta \bar{i} + [(\omega_1 - \omega_2) R \cos \theta + \omega_1 L] \bar{j}. \end{aligned}$$

◁

The corresponding evaluation of acceleration gives

$$\begin{aligned}
 (\bar{a}_C)_{xyz} &= (-\omega_2 \bar{k}) \times (-\omega_2 R \sin \theta \bar{i} - \omega_2 R \cos \theta \bar{j}) = \omega_2^2 R (-\cos \theta \bar{i} + \sin \theta \bar{j}), \\
 \bar{a}_c &= \omega_2^2 R (-\cos \theta \bar{i} + \sin \theta \bar{j}) + \omega_1 \bar{k} \times [\omega_1 R \sin \theta \bar{i} + (\omega_1 R \cos \theta + \omega_1 L) \bar{j}] \\
 &\quad + 2\omega_1 \bar{k} \times \omega_2 R (-\sin \theta \bar{i} - \cos \theta \bar{j}) \\
 &= [-(\omega_1^2 + \omega_2^2) R \cos \theta - \omega_1^2 L + 2\omega_1 \omega_2 R \cos \theta] \bar{i} \\
 &\quad + [(\omega_1^2 + \omega_2^2) R \sin \theta - 2\omega_1 \omega_2 R \sin \theta] \bar{j}. \quad \triangleleft
 \end{aligned}$$

The second analysis uses  $x'y'z'$  attached to the disk as the moving reference frame. A key aspect of this selection is recognizing that  $\omega_2$  is measured relative to the turntable, so the angular velocity of the disk is the vector sum of the two rotations,  $\bar{\omega} = (\omega_1 + \omega_2) \bar{k}$ . The rotation rates are constant, as is  $\bar{k}$ , so  $\bar{\alpha} = \bar{0}$ . Fixing reference frame  $x'y'z'$  to the disk eliminates the relative velocity and relative acceleration,  $(\bar{v}_C)_{x'y'z'} = (\bar{a}_C)_{x'y'z'} = \bar{0}$ . This is balanced by the need to evaluate the velocity and acceleration of the origin  $B$ . We find these quantities by recognizing that points  $A$  and  $B$  are two points in the turntable, so we may employ Eqs. (3.5.6), with  $\omega_1 \bar{k}$  as the rotational velocity of the turntable, and  $\bar{v}_A = \bar{a}_A = \bar{0}$ . Thus,

$$\bar{v}_B = \omega_1 \bar{k} \times \bar{r}_{B/A}, \quad \bar{a}_B = \omega_1 \bar{k} \times (\omega_1 \bar{k} \times \bar{r}_{B/A}).$$

The nonzero terms in the relative motion equations (3.5.4) for point  $C$  are

$$\bar{v}_C = \bar{v}_B + \bar{\omega} \times \bar{r}_{C/B}, \quad \bar{a}_C = \bar{a}_B + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{C/B}).$$

As mentioned earlier, we use  $xyz$  as the global coordinate system. Evaluation of the relations for velocity yields

$$\begin{aligned}
 \bar{v}_B &= \omega_1 \bar{k} \times L \bar{i} = \omega_1 L \bar{j}, \\
 \bar{v}_C &= \omega_1 L \bar{j} + \omega_1 \bar{k} \times (R \cos \theta \bar{i} - R \sin \theta \bar{j}) \\
 &= (\omega_1 - \omega_2) R \sin \theta \bar{i} + [\omega_1 L + (\omega_1 - \omega_2) R \cos \theta] \bar{j}. \quad \triangleleft
 \end{aligned}$$

Evaluation of the acceleration terms leads to


$$\begin{aligned}
 \bar{a}_B &= \omega_1 \bar{k} \times (\omega_1 \bar{k} \times L \bar{i}) = -\omega_1^2 L \bar{i}, \\
 \bar{a}_C &= -\omega_1^2 L \bar{i} + (\omega_1 - \omega_2) \bar{k} \times [(\omega_1 - \omega_2) R \sin \theta \bar{i} + (\omega_1 - \omega_2) R \cos \theta \bar{j}] \\
 &= [-\omega_1^2 L - (\omega_1 - \omega_2)^2 R \cos \theta] \bar{i} + (\omega_1 - \omega_2)^2 R \sin \theta \bar{j}. \quad \triangleleft
 \end{aligned}$$

Because the global system is the same for both analyses, the resulting component representations should be the same, as they are. Overall, the second analysis is somewhat easier, but it requires recognizing that there are two contributions to the angular velocity of the disk.

### 3.5 Velocity and Acceleration Analysis Using a Moving Reference Frame

143

**EXAMPLE 3.13** Let  $\omega_x$ ,  $\omega_y$ , and  $\omega_z$  denote the pitch, roll, and yaw rates, respectively, of a ship about  $xyz$  axes that are attached to the ship with the orientations shown. All of these rotation rates are variable quantities. The origin of  $xyz$  coincides with the center of mass  $G$  of the ship. Consider an elevator car whose path perpendicularly intersects the centerline at a distance  $L$  forward from the center of mass. Let  $h(t)$  denote the height of the car above the centerline. The velocity and acceleration of the center of mass at this instant are  $\bar{v}_G$  and  $\bar{a}_G$ . Determine the corresponding velocity and acceleration of the car.



Example 3.13

**SOLUTION** This example brings to the fore an important feature of a body-fixed reference frame whose rotation about its own axes is known. We use  $xyz$  as the moving reference frame, as well as the global coordinate system. The given rotations are about body-fixed axes, so we have  $\bar{e}_1 = \bar{i}$ ,  $\bar{e}_2 = \bar{j}$ ,  $\bar{e}_3 = \bar{k}$  corresponding to the rates  $\omega_x$ ,  $\omega_y$ , and  $\omega_z$ , respectively. Thus, the angular velocity of the ship is

$$\bar{\omega} = \omega_x \bar{i} + \omega_y \bar{j} + \omega_z \bar{k}.$$

Because the rotation directions are the unit vectors of  $xyz$ , their angular velocity is  $\bar{\omega}$ , that is,  $\bar{\Omega}_1 = \bar{\Omega}_2 = \bar{\Omega}_3 = \bar{\omega}$ . The general description of the angular acceleration corresponding to variable rotation rates therefore is

$$\begin{aligned} \bar{\alpha} &= \dot{\omega}_x \bar{i} + \omega_x (\bar{\omega} \times \bar{i}) + \dot{\omega}_y \bar{j} + \omega_y (\bar{\omega} \times \bar{j}) + \dot{\omega}_z \bar{k} + \omega_z (\bar{\omega} \times \bar{k}) \\ &= \dot{\omega}_x \bar{i} + \dot{\omega}_y \bar{j} + \dot{\omega}_z \bar{k} + \bar{\omega} \times (\omega_x \bar{i}) + \bar{\omega} \times (\omega_y \bar{j}) + \bar{\omega} \times (\omega_z \bar{k}) \\ &= \dot{\omega}_x \bar{i} + \dot{\omega}_y \bar{j} + \dot{\omega}_z \bar{k} + \bar{\omega} \times \bar{\omega} = \dot{\omega}_x \bar{i} + \dot{\omega}_y \bar{j} + \dot{\omega}_z \bar{k}. \end{aligned}$$

This result for  $\bar{\alpha}$  indicates that the angular acceleration components are always the time derivatives of the angular velocity components, provided that those components are relative to body-fixed axes. This observation is a key aspect to the development of kinetics principles in Chapter 5.

The elevator follows a straight path relative to the ship, so the relative motion is

$$\bar{r}_{P/G} = L\bar{i} + h\bar{k}, \quad (\bar{v}_P)_{xyz} = \dot{h}\bar{k} = u\bar{k}, \quad (\bar{a}_P)_{xyz} = \dot{u}\bar{k}.$$

We have described all the terms in Eqs. (3.5.4), so we find the velocity to be


$$\begin{aligned}\bar{v}_P &= \bar{v}_G + (\bar{v}_P)_{xyz} + \bar{\omega} \times \bar{r}_{P/G} \\ &= \bar{v}_G + (\omega_y h - \omega_z L) \bar{i} - \omega_x h \bar{j} + (u + \omega_x L) \bar{k},\end{aligned}\quad \triangleleft$$

and the acceleration is

$$\begin{aligned}\bar{a}_P &= \bar{a}_G + (\bar{a}_P)_{xyz} + \bar{\alpha} \times \bar{r}_{P/G} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/G}) + 2\bar{\omega} \times (\bar{v}_P)_{xyz} \\ &= \bar{a}_G + \dot{u} \bar{k} + (\dot{\omega}_x \bar{i} + \dot{\omega}_y \bar{j} + \dot{\omega}_z \bar{k}) \times (L \bar{j} + h \bar{k}) + (\omega_x \bar{i} + \omega_y \bar{j} + \omega_z \bar{k}) \\ &\quad \times [(\omega_y h - \omega_z L) \bar{i} - \omega_x h \bar{j} + \omega_x L \bar{k}] + 2(\omega_x \bar{i} + \omega_y \bar{j} + \omega_z \bar{k}) \times u \bar{k} \\ &= \bar{a}_G + [\dot{\omega}_y h - \dot{\omega}_z L + \omega_x \omega_y L + \omega_x \omega_z h + 2\omega_y u] \bar{i} + [-\dot{\omega}_x h + \omega_y \omega_z h \\ &\quad - (\omega_x^2 + \omega_z^2) L - 2\omega_x u] \bar{j} + [\dot{u} + \dot{\omega}_x L - (\omega_x^2 + \omega_y^2) h + \omega_y \omega_z L] \bar{k}.\end{aligned}\quad \triangleleft$$

Some of the terms in the acceleration were foreseeable. The acceleration of the elevator relative to the ship is represented by the  $\dot{u}$  term, and the angular acceleration effects are contained in the  $\dot{\omega}_x$ ,  $\dot{\omega}_y$ , and  $\dot{\omega}_z$  terms. In the same vein, the  $\omega_x^2$ ,  $\omega_y^2$ , and  $\omega_z^2$  terms represent centripetal accelerations about the respective axes associated with each rotation being the only one present. The terms that are not intuitive are those containing products of rotation rates about different axes, as well as the Coriolis acceleration terms.

**EXAMPLE 3.14** The cooling fan consists of a shaft that rotates about the vertical axis at angular speed  $\Omega$  as the blades rotate around the shaft at angular rate  $\dot{\phi}$ , where  $\phi$  is the angle of rotation of one of the blades from the top-center position. Both rotation rates are constant. Derive expressions for the velocity and acceleration of the blade tip  $P$  in terms of components relative to the body-fixed  $xyz$  reference system.



Example 3.14

**SOLUTION** This example synthesizes many of the concepts developed in this chapter, including rotation transformations. The problem statement requires that  $xyz$  be used as the global coordinate system. We also use it as the reference frame for the relative motion, as a precursor for the kinetics principles in Chapter 5, which require the usage of body-fixed axes. The rotation of  $xyz$  is the sum of the rotation  $\Omega$



### 3.5 Velocity and Acceleration Analysis Using a Moving Reference Frame

145

about the vertical axis and the rotation  $\dot{\phi}$  about shaft  $AB$ . To define the first rotation, we attach reference frame  $x_1 y_1 z_1$  to the vertical shaft, with the  $z_1$  axis vertically upward. The only meaningful horizontal direction is the one that lies in the vertical plane containing shaft  $AB$ , so we define the  $x_1$  axis to lie in that plane, to the right for the given diagram. Then  $y_1$  is inward relative to the plane of the diagram. The  $x$  axis always coincides with shaft  $AB$ , so we set  $\bar{e}_2 = \bar{i}$ . Thus general descriptions of the angular velocities of the reference frames are

$$\bar{\omega} = \Omega \bar{k}_1 + \dot{\phi} \bar{i}, \quad \bar{\Omega}_1 = \Omega \bar{k}_1, \quad \bar{\Omega}_2 = \bar{\omega}. \quad (1)$$

The rotation rates are constant, so the angular acceleration of  $xyz$  is

$$\bar{\alpha} = \Omega (\bar{\Omega}_1 \times \bar{k}_1) + \dot{\phi} (\bar{\Omega}_2 \times \bar{i}) = \dot{\phi} (\bar{\omega} \times \bar{i}). \quad (2)$$

Several approaches for expressing  $\bar{k}_1$  in terms of global  $xyz$  components are available; we shall evaluate the rotation transformation from  $x_1 y_1 z_1$  to  $xyz$ . The transformation may be visualized as the result of a pair of body-fixed rotations. The first is a rotation of  $\pi/2 - \beta$  about the  $y'$  axis. This transforms  $x_1 y_1 z_1$  to  $x' y' z'$ , where the  $x'$  axis is aligned with the  $x$  axis and the  $z'$  axis is the upward reference line in view C-C. A rotation by angle  $\phi$  about the  $x'$  axis moves  $z'$  into alignment with the  $z$  axis without disturbing the  $x'$  axis. Thus the transformation is

$$\begin{aligned} \{\bar{i} \quad \bar{j} \quad \bar{k}\}^T &= [R] \{\bar{i}_1 \quad \bar{j}_1 \quad \bar{k}_1\}^T, \\ [R] &= [R_x][R_y] = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \phi & \sin \phi \\ 0 & -\sin \phi & \cos \phi \end{bmatrix} \begin{bmatrix} \cos(\frac{\pi}{2} - \beta) & 0 & -\sin(\frac{\pi}{2} - \beta) \\ 0 & 1 & 0 \\ \sin(\frac{\pi}{2} - \beta) & 0 & \cos(\frac{\pi}{2} - \beta) \end{bmatrix} \\ &= \begin{bmatrix} \sin \beta & 0 & -\cos \beta \\ \sin \phi \cos \beta & \cos \phi & \sin \phi \sin \beta \\ \cos \phi \cos \beta & -\sin \phi & \cos \phi \sin \beta \end{bmatrix}. \end{aligned}$$

The inverse transformation gives the unit vectors of  $x_1 y_1 z_1$  in terms of the  $xyz$  unit vectors, so the last row of  $[R]^T$ , which is the last column of  $[R]$ , gives the global components of the rotation direction  $\bar{e}_1 = \bar{k}_1$ ,

$$\bar{k}_1 = -\cos \beta \bar{i} + \sin \phi \sin \beta \bar{j} + \cos \phi \sin \beta \bar{k}. \quad (3)$$

This enables us to evaluate the global components of  $\bar{\omega}$  and  $\bar{\alpha}$ :

$$\bar{\omega} = (\dot{\phi} - \Omega \cos \beta) \bar{i} + \Omega \sin \phi \sin \beta \bar{j} + \Omega \cos \phi \sin \beta \bar{k}, \quad (4a)$$

$$\begin{aligned} \bar{\alpha} &= [(\dot{\phi} - \Omega \cos \beta) \bar{i} + \Omega \sin \phi \sin \beta \bar{j} + \Omega \cos \phi \sin \beta \bar{k}] \times \bar{i} \\ &= \Omega \dot{\phi} (\cos \phi \sin \beta \bar{j} - \sin \phi \sin \beta \bar{k}). \end{aligned} \quad (4b)$$

We may construct the velocity and acceleration of origin  $B$  by recognizing that this point follows a circular path in the horizontal plane. However, using an alternative approach based on its being a point on shaft  $AB$  is more suitable to expressing the results in terms of components relative to  $xyz$ . The angular velocity of shaft  $AB$  is  $\bar{\Omega}_1$ , which is constant, and point  $A$  is stationary, so we have

$$\bar{v}_B = \Omega \bar{k}_1 \times \bar{r}_{B/A}, \quad \bar{a}_B = \Omega \bar{k}_1 \times (\Omega \bar{k}_1 \times \bar{r}_{B/A}).$$

The global components of  $\bar{k}_1$  are given by Eq. (3), whose substitution into the preceding yields

$$\begin{aligned} \bar{v}_B &= \Omega (-\cos \beta \bar{i} + \sin \phi \sin \beta \bar{j} + \cos \phi \sin \beta \bar{k}) \times L \bar{i} \\ &= \Omega L (\cos \phi \sin \beta \bar{j} - \sin \phi \sin \beta \bar{k}), \end{aligned} \quad (5a)$$

$$\begin{aligned} \bar{a}_B &= \Omega (-\cos \beta \bar{i} + \sin \phi \sin \beta \bar{j} + \cos \phi \sin \beta \bar{k}) \times \Omega L (\cos \phi \sin \beta \bar{j} - \sin \phi \sin \beta \bar{k}) \\ &= \Omega^2 L [-(\sin \beta)^2 \bar{i} - \sin \phi \sin \beta \cos \beta \bar{j} - \cos \phi \sin \beta \cos \beta \bar{k}] \end{aligned} \quad (5b)$$

Because  $xyz$  is attached to the propeller, there is no relative velocity or acceleration. Hence  $\bar{v}_P$  and  $\bar{a}_P$  also are described by Eqs. (3.5.6), which indicate that

$$\bar{v}_P = \bar{v}_B + \bar{\omega} \times \bar{r}_{P/B}, \quad \bar{a}_P = \bar{a}_B + \bar{\alpha} \times \bar{r}_{P/B} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/B}).$$

Substitution of the global descriptions in Eqs. (4) and (5) yields

$$\begin{aligned} \bar{v}_P &= \Omega L (\cos \phi \sin \beta \bar{j} - \sin \phi \sin \beta \bar{k}) + [(\dot{\phi} - \Omega \cos \beta) \bar{i} + \Omega \sin \phi \sin \beta \bar{j} \\ &\quad + \Omega \cos \phi \sin \beta \bar{k}] \times R \bar{k} \\ &= \Omega [R \sin \phi \sin \beta \bar{i} + (L \cos \phi \sin \beta + R \cos \beta) \bar{j} - L \sin \phi \sin \beta \bar{k}]. \end{aligned} \quad \triangleleft$$

The corresponding evaluation of acceleration gives

$$\begin{aligned} \bar{a}_P &= \Omega^2 L [-(\sin \beta)^2 \bar{i} - \sin \phi \sin \beta \cos \beta \bar{j} - \cos \phi \sin \beta \cos \beta \bar{k}] \\ &\quad + \Omega \dot{\phi} (\cos \phi \sin \beta \bar{j} - \sin \phi \sin \beta \bar{k}) \times R \bar{k} \\ &\quad + [(\dot{\phi} - \Omega \cos \beta) \bar{i} + \Omega \sin \phi \sin \beta \bar{j} + \Omega \cos \phi \sin \beta \bar{k}] \\ &\quad \times \Omega R (\sin \phi \sin \beta \bar{i} + \cos \beta \bar{j}) \\ &= \Omega^2 \{ -\sin \beta (L \sin \beta + R \cos \phi \cos \beta) \bar{i} + \sin \phi \sin \beta (-L \cos \beta + R \cos \phi \sin \beta) \bar{j} \\ &\quad + [-L \cos \phi \sin \beta \cos \beta - R (\cos \beta)^2 - R (\sin \phi)^2 (\sin \beta)^2] \bar{k} \} - \dot{\phi}^2 R \bar{k} \\ &\quad + 2\Omega \dot{\phi} R (\cos \phi \sin \beta \bar{i} + \cos \beta \bar{j}). \end{aligned} \quad \triangleleft$$

These results are displayed in groups of like coefficients of the rate variables to highlight that the underlying physical phenomena are a superposition of effects. The terms in  $\bar{v}_P$  that contain  $\Omega$  and those in  $\bar{a}_P$  that contain  $\Omega^2$  represent the motion that would be present if  $\phi$  were constant, giving  $\dot{\phi} \equiv 0$ . In that case, point  $P$  would follow

### 3.6 Observations from a Moving Reference Frame

147

a circular path in the horizontal plane. Similarly, the terms in  $\bar{v}_P$  that contain  $\dot{\phi}$  and those in  $\bar{a}_P$  that contain  $\dot{\phi}^2$  correspond to a pure rotation about the  $x$  axis, in which case point  $P$  would follow a circular path of radius  $R$ . The effect that has no obvious description as a superposition is represented by the acceleration term that has the factor  $2\Omega\dot{\phi}$ . The two factor identifies it as a Coriolis acceleration that exists only if both rotation rates are nonzero. This physical Coriolis acceleration arises, even though the Coriolis acceleration term  $2\bar{\omega} \times (\bar{v}_P)_{xyz}$  in relative acceleration equations (3.5.4) was identically zero in our analysis.

### 3.6 OBSERVATIONS FROM A MOVING REFERENCE FRAME

Thus far, our concern has been with situations in which the motion of some point could be more readily described in terms of a moving reference frame. However, sometimes the absolute motion is known, and the relative motion must be evaluated. For example, it might be necessary to ensure that one part of a machine merge with another part in a smooth manner, as in the case of gears. The influence of the Earth's motion on the dynamic behavior of a system is an important situation in which aspects of the absolute motion are known.

One approach is to interchange the absolute and relative reference frames, based on the fact that the kinematical relationships do not actually require that one of the reference frames be stationary. Thus in this viewpoint, if the angular velocity of  $xyz$  relative to  $XYZ$  is  $\bar{\omega}$ , then the angular velocity of  $XYZ$  as viewed from  $xyz$  is  $-\bar{\omega}$ . The difficulty with this approach is that it is prone to errors, particularly in signs, because of the need to change the observer's viewpoint for the formulation. The more reliable approach, which does not require redefinition of the basic quantities, manipulates the earlier relations.

The concept is quite straightforward. When the absolute velocity  $\bar{v}_P$  and the absolute acceleration  $\bar{a}_P$  are known, Eqs. (3.5.4) may be solved for the relative motion parameters. Specifically,

$$\begin{aligned} (\bar{v}_P)_{xyz} &= \bar{v}_P - \bar{v}_{O'} - \bar{\omega} \times \bar{r}_{P/O'}, \\ (\bar{a}_P)_{xyz} &= \bar{a}_P - \bar{a}_{O'} - \bar{\alpha} \times \bar{r}_{P/O'} - \bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/O'}) - 2\bar{\omega} \times (\bar{v}_P)_{xyz}. \end{aligned} \quad (3.6.1)$$

If it is appropriate, the relative velocity may be removed from the acceleration relation by substitution of the velocity relation. The result is

$$(\bar{a}_P)_{xyz} = \bar{a}_P - \bar{a}_{O'} - \bar{\alpha} \times \bar{r}_{P/O'} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/O'}) - 2\bar{\omega} \times (\bar{v}_P - \bar{v}_{O'}).$$

The steps required for applying these relations are like those already established, because  $\bar{\omega}$  and  $\bar{\alpha}$  still describe the rotation of  $xyz$  relative to a fixed reference frame.

These relations are particularly useful when the rotation of the Earth must be considered. Newton's Second Law relates the forces acting on a particle to the acceleration

relative to some hypothetical inertial reference frame. However, we commonly observe the motion with Earth-based instruments. We use the relative motion relations to reconcile Newton's Law with the motion we observe. Consider an observer at point  $O'$  on the Earth's surface. A natural definition for the reference frame employed by this observer is east–west and north–south for position along the surface and vertical for measurements off the surface. Such a reference frame is depicted in Fig. 3.12, where the  $x$  axis is northward and the  $y$  axis is westward. The observation point  $O'$  in the figure is located by the latitude angle  $\lambda$  measured from the equator and the longitude angle  $\phi$  measured from some reference location, such as the prime meridian (the longitude of the Royal Observatory at Greenwich, England).




Figure 3.12. The Earth as a reference frame.

For the present purposes, it is adequate to employ an approximate model of the Earth. The Earth spins at one revolution about its polar axis in 23 h, 56 min, 4.06 s, which converts to  $\omega_e = 2\pi \text{ rad}/23.934 \text{ h} = 7.292(10^{-5}) \text{ rad/s}$ . For comparison, the orbital rate of rotation of the Earth about the Sun,  $\omega_O$ , is smaller by an approximate factor of 365, because one such revolution requires a full year. To assess the relative importance of the two, let us consider the associated centripetal acceleration. The maximum that is due to the Earth's rotation occurs at the equator, where the distance from the polar axis is the Earth's radius,  $R_e = 6370 \text{ km}$ . The centripetal acceleration at this location associated with the Earth's rotation is  $\omega_e^2 R_e \approx 0.034 \text{ m/s}^2$ . The mean radius of the Earth's orbit is  $R_O = 149.6(10^6) \text{ km}$ , so the associated centripetal acceleration is  $\omega_O^2 R_O \approx 0.0059 \text{ m/s}^2$ , which is 17.5% of the acceleration that is due to the Earth's spin, which is itself quite feeble in comparison with the free-fall acceleration  $g$ . Furthermore, the centripetal acceleration associated with the Earth's orbital motion is essentially balanced by the effect of the Sun's gravitational attraction because that balance produces the orbit. For these reasons, it is reasonable to consider the center of the Earth to be stationary and to ignore the Sun's gravitational attraction. If we also ignore the relatively minor wobble of the polar axis, our model of the Earth reduces to a sphere that rotates about the (fixed) polar axis at the constant rate  $\omega_e$ .

### 3.6 Observations from a Moving Reference Frame

149

Newton's Second Law gives the acceleration of a particle relative to a fixed reference frame corresponding to the resultant force. We decompose this force into two parts:  $\bar{F}_g$  represents the gravitational attraction of the Earth, and  $\bar{F}_a$  consists of all other forces, including applied loads and reactions. The angular acceleration of the Earth in our simple model is zero. Thus application of Eqs. (3.6.1) leads to a relation for the acceleration relative to the Earth-based  $xyz$  reference frame corresponding to a specified set of forces acting on a particle:

$$(\bar{a}_P)_{xyz} = \frac{\bar{F}_a + \bar{F}_g}{m} - \bar{a}_{O'} - \bar{\omega}_e \times (\bar{\omega}_e \times \bar{r}_{P/O'}) - 2\bar{\omega}_e \times (\bar{v}_P)_{xyz}. \quad (3.6.2)$$

Now consider a particle in free fall near the Earth's surface. Let point  $O'$  be close to the particle, so that  $\bar{r}_{P/O'} \approx \bar{0}$ . If air resistance is negligible, there are no applied forces,  $\bar{F}_a \approx \bar{0}$ . The definition of  $g$  is that it is the magnitude of the free-fall acceleration observed from the Earth. Furthermore, we interpret the direction of the free-fall acceleration as being vertically downward. Recall that the definition of the  $z$  axis in Fig. 3.12 was that it is the upward vertical, which now means that the observed free-fall acceleration is  $(\bar{a}_P)_{xyz} = -g\bar{k}$ . The magnitude of the actual gravitational force is given by the inverse square law, and this force is directed oppositely to the radial line from the center of the Earth to the particle. We use the position vector  $\bar{r}_{O'/O}$  to construct the radial unit vector, so the gravitational force is described by

$$\bar{F}_g = \frac{GM_em}{r_e^2} \left( -\frac{\bar{r}_{O'/O}}{|\bar{r}_{O'/O}|} \right) = -\frac{GM_em}{r_e^3} \bar{r}_{O'/O}. \quad (3.6.3)$$

The origin  $O'$  follows a circular path parallel to the equatorial plane. The radius of this path is  $R_e \cos \lambda$ , and the rotation rate of a radial line is  $\omega_e$ . The corresponding centripetal acceleration is  $\bar{a}_{O'} = r_e \omega_e^2 (\cos \lambda) (-\bar{e}_\perp)$ , where  $\bar{e}_\perp$  is the radial unit vector perpendicular to the polar axis intersecting point  $O'$ . Unless the free fall occurs over a long time, the velocity relative to the Earth is small, which makes it permissible to neglect Coriolis acceleration effects. In this case Eq. (3.6.2) reduces to

$$g\bar{k} = \frac{GM_e}{r_e^3} \bar{r}_{O'/O} - r_e \omega_e^2 (\cos \lambda) \bar{e}_\perp. \quad (3.6.4)$$

There are two primary aspects of interest in this relation. The centripetal acceleration term is parallel to  $\bar{r}_{O'/O}$  only at the equator,  $\lambda = 0$ , and at the poles,  $\lambda = 0, \pi$ , where it is zero. Hence, the vertical direction defined by  $\bar{k}$  does not generally intersect the center of the Earth. However, it does lie in the meridional plane because that plane contains both  $\bar{r}_{O'/O}$  and  $\bar{e}_\perp$ . Equally significant is the effect of the centripetal acceleration on the value of  $g$  that is obtained from measurements. This effect is largest at the equator, where  $\bar{e}_\perp$  is parallel to  $\bar{r}_{O'/O}$  and  $\cos \lambda = 1$ .

We may quantify both effects by resolving  $\bar{r}_{O'/O}$  and  $\bar{e}_\perp$  into components parallel and perpendicular to  $\bar{k}$ . Let the angle from  $\bar{k}$  to  $\bar{r}_{O'/O}$  be  $\beta$ , such that the angle from  $\bar{k}$  to the equatorial plane is  $\lambda + \beta$ . Because all vectors are situated in the same meridional plane, this resolution is

$$\bar{r}_{O'/O} = r_e (\cos \beta \bar{k} - \sin \beta \bar{i}), \quad \bar{e}_\perp = \cos(\lambda + \beta) \bar{k} - \sin(\lambda + \beta) \bar{i}. \quad (3.6.5)$$

Substitution of these expressions into Eq. (3.6.4) followed by equating like components leads to two equations for the values of  $g$  and  $\lambda$ :

$$\begin{aligned} g &= \frac{GM_e}{r_e^2} \cos \beta - r_e \omega_e^2 (\cos \lambda) \cos (\lambda + \beta), \\ 0 &= -\frac{GM_e}{r_e^2} \sin \beta + r_e \omega_e^2 (\cos \lambda) \sin (\lambda + \beta). \end{aligned} \quad (3.6.6)$$

It is apparent that  $\beta$  is very small, so we may obtain the value of  $g$  by setting  $\beta = 0$  in the first of Eqs. (3.6.6):

$$g = \frac{GM_e}{r_e^2} - r_e \omega_e^2 (\cos \lambda)^2. \quad (3.6.7)$$

Thus we see that  $g$  decreases from the value associated with gravity at the poles to a minimum that is reduced by  $r_e \omega_e^2 = 0.034 \text{ m/s}^2$  at the equator. The value  $g = 9.807 \text{ m/s}^2$  represents a reasonable average value when the latitude is not specified. Smallness of  $\beta$  allows us to approximate  $\cos (\lambda + \beta) \approx \cos \lambda$  in the second of Eqs. (3.6.6). We also approximate  $GM_e/r_e^2$  as  $g$ , which leads to

$$\beta = \sin^{-1} \left( \frac{r_e \omega_e^2 \sin (2\lambda)}{2g} \right). \quad (3.6.8)$$

The maximum deviation angle  $\beta$  occurs at a latitude of  $45^\circ$ , where  $\beta = 0.099^\circ$ .

The definition of  $g\bar{k}$ , Eq. (3.6.4), allows us to simplify Eq. (3.6.2) slightly. The centripetal acceleration term  $\bar{\omega}_e \times (\bar{\omega}_e \times \bar{r}_{P/O'})$  may be neglected, unless the magnitude of  $\bar{r}_{P/O'}$  is a large fraction of the Earth's radius. [In fact, if this acceleration term is significant, we should not use Eq. (3.6.4).] Thus we have

$$(\bar{a}_P)_{xyz} = \frac{\bar{F}_a}{m} - g\bar{k} - 2\bar{\omega}_e \times (\bar{v}_P)_{xyz}, \quad (3.6.9)$$

which shows that the primary difference between the acceleration we observe from the Earth and the absolute acceleration associated with Newton's Second Law is the Coriolis term. We use the Earth-based  $xyz$  coordinate system to describe the preceding. The components of relative velocity and acceleration are respectively the first and second time derivatives of the Cartesian coordinates  $(x, y, z)$ . Because the angular velocity of the Earth is parallel to the polar axis, and the deviation of the  $z$  axis from the line to the center of the Earth is small, the angular velocity is essentially


$$\bar{\omega}_e = \omega_e (\cos \lambda \bar{i} + \sin \lambda \bar{k}). \quad (3.6.10)$$

Correspondingly, Eq. (3.6.9) becomes

$$\begin{aligned} \ddot{x} - (2\omega_e \sin \lambda) \dot{y} &= \frac{\bar{F}_a \cdot \bar{i}}{m}, \\ \ddot{y} + (2\omega_e \sin \lambda) \dot{x} - (2\omega_e \cos \lambda) \dot{z} &= \frac{\bar{F}_a \cdot \bar{j}}{m}, \\ \ddot{z} + (2\omega_e \cos \lambda) \dot{y} &= \frac{\bar{F}_a \cdot \bar{k}}{m} - g. \end{aligned} \quad (3.6.11)$$

### 3.6 Observations from a Moving Reference Frame

151



**Figure 3.13.** Coriolis acceleration associated with motion in the horizontal plane relative to the Earth.

These equations may be solved for the forces required to have a specified motion relative to the Earth. Alternatively, they may be regarded as a set of coupled differential equations for the relative position in situations in which the forces are specified.


The fact that the Coriolis term is perpendicular to the velocity as seen by an observer on the Earth leads to some interesting anomalies. In the Northern Hemisphere, the component of  $\bar{\omega}_e$  perpendicular to the Earth's surface is outward. If a particle is constrained to follow a horizontal path relative to the Earth in the Northern Hemisphere, the Coriolis term  $2\bar{\omega}_e \times (\bar{v}_P)_{xyz}$  is as shown in Fig. 3.13. It follows that a horizontal force pushing to the left of the direction of motion is required if that direction is to be maintained.

A story that has been passed down from professor to student over the years, without substantiation, states that a railroad line had two sets of north–south tracks along which trains ran in only one direction. For the track along which trains ran northward, the inner surface of the east rail was supposedly more shiny, because of the westward Coriolis force it had to exert on the flange of the wheels. Correspondingly, the track for trains running south was more shiny on the inner surface of the west rail. The veracity of this statement is questionable, owing to the smallness of the force in comparison with other effects, such as the wind and elevation changes.

If a transverse force is not present to maintain a particle in a straight path relative to the Earth, as required by Eqs. (3.65), then the particle will deviate to the right. This observation leads to a qualitative explanation of the swirling of a liquid that is drained through the centered hole of a perfectly symmetrical cylindrical tank. As the fluid rushes to the hole, the tendency in the Northern Hemisphere to deviate to the right along any inward radial line induces a counterclockwise spiraling flow when viewed from above. (The flow will be clockwise in the Southern Hemisphere.) The same phenomenon acts on a much larger scale to set up the flow patterns in hurricanes and typhoons. Goldstein (1980) offers an excellent discussion of these effects. Meteorological models used to predict general weather patterns must account for the Coriolis acceleration effect.

**EXAMPLE 3.15** Leah is standing stationary on a turntable rotating about the vertical axis at the constant rate  $\omega$ . A ball traveling in the radial direction has constant speed  $v$  horizontally. It is timed to arrive at Leah's position so that she may catch it. Let  $xyz$  be Leah's reference frame with the  $x$  axis radially outward, as shown. Determine the horizontal components of position, velocity, and acceleration of the

ball as seen by Leah as a function of time. Perform the analysis by (a) constructing the relative position vector geometrically, (b) using the relative motion formulas.



Example 3.15

**SOLUTION** This problem illustrates the application of the basic relations, as well as providing a further demonstration that there often is more than one way to perform a kinematical analysis. For both analyses we let  $t = 0$  be the instant when Leah catches the ball, so  $t < 0$  characterizes an arbitrary instant before the ball is caught. Correspondingly, the angle locating her relative to the path of the ball is  $\theta = \omega(-t)$  and the radial distance  $R$  to the ball from the center of the turntable is  $R = r + v(-t)$ .


The first analysis involves geometrically constructing the  $xyz$  components of the ball's position relative to the child,  $\vec{r}_{B/A}$ . Projecting the radial line from the center of the turntable to the ball onto the  $x$  and  $y$  axes gives

$$\begin{aligned}\vec{r}_{B/A} &= x\vec{i} + y\vec{j} = (R\cos\theta - r)\vec{i} + R\sin\theta\vec{j} \\ &= [(r - vt)\cos(\omega t) - r]\vec{i} - (r - vt)\sin(\omega t)\vec{j}.\end{aligned}$$

We may find the path of the ball in the  $xy$  plane as seen by Leah by plotting the  $x$  and  $y$  components at various  $t$ . Let  $\tau = \omega t$  be a nondimensional time parameter. Then a nondimensional description of the relative path coordinates is

$$\frac{x}{r} = \left(1 - \frac{v}{r\omega}\tau\right)\cos\tau - 1, \quad \frac{y}{r} = -\left(1 - \frac{v}{r\omega}\tau\right)\sin\tau.$$

These expressions show that the relative path, scaled by  $r$ , depends solely on the ratio  $v/r\omega$ . Plots for several values of this ratio for the interval  $-4\pi \leq \tau \leq 0$ , corresponding to two revolutions of the turntable, show that the path is an inward spiral.



Path of the ball in the horizontal plane as seen by the child on the turntable



### 3.6 Observations from a Moving Reference Frame

153

By definition, we may obtain the relative velocity by differentiating the components of the relative position:

$$(\bar{v}_B)_{xyz} \equiv \frac{\partial}{\partial t} \bar{r}_{B/A} = -[v \cos(\omega t) - (r - vt)\omega \sin(\omega t)] \bar{i} + [v \sin(\omega t) - (r - vt)\omega \cos(\omega t)] \bar{j}. \quad \triangleleft$$

Similarly, we may obtain the relative acceleration by differentiating the relative velocity components:

$$(\bar{a}_B)_{xyz} \equiv \frac{\partial}{\partial t} (\bar{v}_B)_{xyz} = [2v\omega \sin(\omega t) - (r - vt)\omega^2 \cos(\omega t)] \bar{i} + [2v\omega \cos(\omega t) + (r - vt)\omega^2 \sin(\omega t)] \bar{j}. \quad \triangleleft$$

The solution obtained with the moving reference formulation barely resembles the operations in the previous solution. The position as seen by Leah is

$$\bar{r}_{B/A} = \bar{r}_{B/O} - \bar{r}_{A/O}.$$

We know that the ball is at distance  $R = r - vt$  in the fixed radial direction, which we define to be the direction of the stationary  $X$  axis. Thus  $\bar{r}_{B/O} = (r - vt) \bar{I}$ . The child is at distance  $r$  in the radial direction along which the  $x$  axis is aligned, so  $\bar{r}_{A/O} = r \bar{i}$ . We use these descriptions to form  $\bar{r}_{B/A}$  in terms of components relative to the  $xyz$  axes, which is Leah's viewpoint. This requires that we express  $\bar{r}_{B/O}$  in terms of  $\bar{i} \bar{j} \bar{k}$  components. A visual inspection shows that  $\bar{I} = \cos \theta \bar{i} - \sin \theta \bar{j}$ , which leads to

$$\bar{r}_{B/A} = (r - vt) (\cos \theta \bar{i} + \sin \theta \bar{j}) - r \bar{i}. \quad \triangleleft$$

Because  $\theta = \omega(-t)$ , this is the same description as that derived in the first analysis.

To analyze velocity and acceleration, we begin with the angular motion of the  $xyz$  reference frame. This is a simple rotation about the vertical axis at constant rate, so  $\bar{\omega} = \omega \bar{k}$ ,  $\bar{\alpha} = \bar{0}$ . The origin of  $xyz$  is point  $A$ , which follows a circular path relative to the fixed reference frame. Thus  $\bar{v}_A = r\omega \bar{j}$ ,  $\bar{a}_A = -r\omega^2 \bar{i}$ . We also know that the ball's motion in the horizontal plane is a straight path at constant speed  $v$ , so  $\bar{v}_B = -v \bar{I}$ ,  $\bar{a}_B = \bar{0}$ , where  $\bar{I}$  was previously described in terms of  $\bar{i} \bar{j} \bar{k}$  components. Substitution of these expressions into the first of Eqs. (3.6.1) yields the relative velocity:

$$\begin{aligned} (\bar{v}_B)_{xyz} &= \bar{v}_B - \bar{v}_A - \bar{\omega} \times \bar{r}_{B/A} \\ &= -v (\cos \theta \bar{i} + \sin \theta \bar{j}) - r\omega \bar{j} - \omega \bar{k} \times [(r - vt) (\cos \theta \bar{i} + \sin \theta \bar{j}) - r \bar{i}], \\ (\bar{v}_B)_{xyz} &= [-v \cos \theta + \omega (r - vt) \sin \theta] \bar{i} + [-v \sin \theta - \omega (r - vt) \cos \theta] \bar{j}. \quad \triangleleft \end{aligned}$$


Using this last expression to form the second of Eqs. (3.6.1) gives the relative acceleration:

$$\begin{aligned} (\bar{a}_B)_{xyz} &= \bar{a}_B - \bar{a}_A - \bar{\alpha} \times \bar{r}_{B/A} - \bar{\omega} \times (\bar{\omega} \times \bar{r}_{B/A}) - 2\bar{\omega} \times (\bar{v}_B)_{xyz} \\ &= -(-r\omega^2\bar{i}) - \omega\bar{k} \times \{\omega\bar{k} \times [(r - vt)(\cos\theta\bar{i} + \sin\theta\bar{j}) - r\bar{i}]\} \\ &\quad - 2\omega\bar{k} \times \{[-v\cos\theta + \omega(r - vt)\sin\theta]\bar{i} + [-v\sin\theta - \omega(r - vt)\cos\theta]\bar{j}\}, \\ (\bar{a}_B)_{xyz} &= [-\omega^2(r - vt)\cos\theta - 2\omega v\sin\theta]\bar{i} + [-\omega^2(r - vt)\sin\theta + 2\omega v\cos\theta]\bar{j}. \quad \triangleleft \end{aligned}$$

Substitution of  $\theta = -\omega t$  into the second set of results would show that they are identical to the results of the first analysis. We could employ either approach with equal ease in this problem because the motion is planar. The relative motion formulation becomes increasingly advantageous as the rotation of the reference frame becomes more complicated.

**EXAMPLE 3.16** When a small ball is suspended by a stiff cable from an ideal swivel joint that permits three-dimensional motion, the system is called a spherical pendulum. Suppose such a pendulum, whose cable length is  $\ell$ , is released from rest relative to the Earth with the ball at a distance  $b \ll \ell$  north of the point below the pivot. Analyze the effect of the Earth's rotation on the motion. It may be assumed that the angle between the suspending cable and the vertical is always very small.

**SOLUTION** In addition to demonstrating the solution of the coupled equations of motion, Eqs. (3.6.11), this example explains an interesting phenomenon regarding motion relative to the Earth. A free-body diagram of the ball shows the weight  $mg$  and the tensile force  $\bar{F}$  exerted by the cable.



Example 3.16

In terms of the  $xyz$  coordinates sketch defined in the diagram, we have

$$\bar{F} = F \frac{\bar{r}_{O'/B}}{|\bar{r}_{O'/B}|} = F \left( -\frac{x}{\ell}\bar{i} - \frac{y}{\ell}\bar{j} + \frac{z}{\ell}\bar{k} \right). \quad (1)$$

### 3.6 Observations from a Moving Reference Frame

155

When the values of  $x$  and  $y$  are known, the value of  $z$  is given by

$$z = -(\ell^2 - x^2 - y^2)^{1/2}. \quad (2)$$

Because  $\ell$  is constant, differentiating the preceding gives

$$\dot{z} = \frac{x\dot{x} + y\dot{y}}{(\ell^2 - x^2 - y^2)^{1/2}}.$$

The specification that the angle with the vertical is small means that  $|x| \ll \ell$  and  $|y| \ll \ell$ . Introducing this approximation above yields

$$\dot{z} \approx \frac{x\dot{x} + y\dot{y}}{\ell}, \quad \ddot{z} \approx \frac{x\ddot{x} + \dot{x}^2 + y\ddot{y} + \dot{y}^2}{\ell} \approx \frac{\dot{x}^2 + \dot{y}^2}{\ell}. \quad (3)$$

The preceding indicates that  $\dot{z}$  is much less than  $\dot{x}$  and  $\dot{y}$ . Furthermore, smallness of  $\dot{z}$  means that the speed of the ball is essentially  $\dot{x}^2 + \dot{y}^2$ . This leads to the interpretation of  $\ddot{z}$  as the centripetal acceleration associated with motion in a circle of radius  $\ell$ . The result of substituting the preceding descriptions of  $\ddot{F}$  and  $\ddot{z}$  into the general equations of motion, Eqs. (3.6.11), is

$$\ddot{x} - (2\omega_e \sin \lambda) \dot{y} = -\frac{F}{m\ell}x, \quad (4)$$

$$\ddot{y} + (2\omega_e \sin \lambda) \dot{x} = -\frac{F}{m\ell}y, \quad (5)$$

$$\frac{\dot{x}^2 + \dot{y}^2}{\ell} + (2\omega_e \cos \lambda) \dot{y} = \frac{F}{m\ell}(\ell^2 - x^2 - y^2)^{1/2} - g, \quad (6)$$

where the Coriolis acceleration term containing  $\dot{z}$  in Eq. (5) has been dropped because  $\dot{z}$  is small compared with  $\dot{x}$  and  $\dot{y}$ .

There are three variables in Eqs. (4)–(6). Elimination of  $F$  from these equations leads to a pair of ordinary differential equations governing  $x$  and  $y$ . We use Eq. (6) for that purpose. To estimate the order of magnitude of the first term in Eq. (6) we recall that  $\dot{x}^2 + \dot{y}^2 \approx v^2$ . Because the Coriolis effect is quite small, the motion should be essentially like the result for a simple pendulum whose pivot is stationary, so we may employ the principle of conservation of energy to estimate  $v^2$ . Let the elevation of the pivot be the datum, so the gravitational potential energy is  $mgz$ . At the lowest position,  $z = -\ell$  and  $v = v_{\max}$ , whereas at the highest position,  $z = z_{\max}$ , and  $v = 0$ . It follows that

$$\frac{1}{2}mv_{\max}^2 - mg\ell \approx mgz_{\max}. \quad (7)$$

The value of  $z_{\max}$  is related to the other coordinates by Eq. (2), to which we apply a binomial series expansion to find

$$z_{\max} = -(\ell^2 - x_{\max}^2 - y_{\max}^2)^{1/2} \approx -\ell + \frac{x_{\max}^2 + y_{\max}^2}{2\ell}.$$

Substitution of this expression into Eq. (7) gives

$$\frac{v_{\max}^2}{\ell} \approx g \frac{x_{\max}^2 + y_{\max}^2}{\ell^2}.$$

Because  $x$  and  $y$  are stated to remain small compared with  $\ell$  throughout the motion, it follows that  $v^2/\ell$  is always small compared with  $g$ . Accordingly, we may neglect the first term in Eq. (6). Furthermore, the Coriolis acceleration is a small effect. Thus Eq. (6) indicates that the cable tension is well approximated as the ball's weight,  $F/m = g$ . This approximation reduces Eqs. (4) and (5) to

$$\begin{aligned} \ddot{x} - 2p\dot{y} + \Omega^2 x &= 0, \\ \ddot{y} + 2p\dot{x} + \Omega^2 y &= 0, \end{aligned} \quad (8)$$

where

$$\Omega = \left(\frac{g}{\ell}\right)^{1/2}, \quad p = \omega_e \sin \lambda.$$

Evaluating the motion requires that we solve this pair of linear, coupled, ordinary differential equations. We could use the method of characteristic exponents, but an examination of the equations leads to a much briefer solution. We observe that if the Coriolis effect were not present,  $p = 0$ , then the equations for  $x$  and  $y$  would be uncoupled, and the fundamental solutions for both variables would be combinations of  $\sin(\Omega t)$  and  $\cos(\Omega t)$ . Furthermore, in either equation with  $p \neq 0$ , the order of the derivatives of  $y$  is one different from the order of the derivatives of  $x$ . The combination of these two features suggests that both  $x$  and  $y$  vary sinusoidally at some frequency  $\mu$ , with a  $90^\circ$  phase difference between them. We therefore consider a trial solution whose form is

$$x = A \cos(\mu t + \phi), \quad y = B \sin(\mu t + \phi). \quad (9)$$

We obtain relations for the amplitudes  $A$  and  $B$ , the frequency  $\mu$ , and the phase angle  $\phi$  by substituting the trial forms into Eqs. (8), which leads to

$$\begin{aligned} (\Omega^2 - \mu^2) A - 2p\mu B &= 0, \\ -2p\mu A + (\Omega^2 - \mu^2) B &= 0. \end{aligned} \quad (10)$$

For  $A$  and  $B$  to be nonzero, the determinant of this pair of homogeneous equations must vanish. This leads to a characteristic equation:

$$(\Omega^2 - \mu^2)^2 - (2p\mu)^2 = 0 \implies \Omega^2 - \mu^2 = \pm 2p\mu.$$

This pair of quadratic equations for  $\mu$  has a total of four roots, but we need only the positive values, which are

$$\mu_1 = (\Omega^2 + p^2)^{1/2} - p, \quad \mu_2 = (\Omega^2 + p^2)^{1/2} + p. \quad (11a)$$

### 3.6 Observations from a Moving Reference Frame

157

In view of the smallness of  $\omega_e$ , any conceivable value of  $\ell$  will lead to  $\Omega \gg p$ , so the characteristic roots are well approximated as

$$\mu_1 \approx \Omega - p, \quad \mu_2 \approx \Omega + p. \quad (11b)$$

There is a solution of Eqs. (10) for each characteristic root. Because the determinant vanishes when  $\mu = \mu_1$  or  $\mu = \mu_2$ , only one of those equations is independent. This means that both equations will be satisfied if  $A$  is arbitrarily set to some value  $A_j$ , provided that we then obtain  $B_j$  by solving either of Eqs. (10). The second of these equations gives

$$B_j = \frac{2p\mu_j}{(\Omega^2 - \mu_j^2)} A_j.$$

Substitution of the respective values of  $\mu_j$  from Eqs. (11a) leads to  $B_1 = A_1$  and  $B_2 = -A_2$ . The corresponding general solution of the equations of motion therefore is

$$\begin{aligned} x &= A_1 \cos(\mu_1 t + \phi_1) + A_2 \cos(\mu_2 t + \phi_2), \\ y &= A_1 \sin(\mu_1 t + \phi_1) - A_2 \sin(\mu_2 t + \phi_2). \end{aligned} \quad (12)$$

The coefficients  $A_1$ ,  $A_2$ ,  $\phi_1$ , and  $\phi_2$  must satisfy initial conditions. It was given in the problem statement that the ball was released from rest relative to  $xyz$  at a distance  $b$  to the north of the pivot. Thus the initial conditions are  $x = b$ ,  $\dot{x} = \dot{y} = \dot{y} = 0$  at  $t = 0$ . We match these values to the result of evaluating the general solution, from which we find that

$$A_1 = b \frac{\mu_2}{\mu_1 + \mu_2} \approx \frac{b}{2}, \quad A_2 = b \frac{\mu_1}{\mu_1 + \mu_2} \approx \frac{b}{2}.$$

The general solution corresponding to the preceding when approximations (11b) are used for the characteristic exponents is

$$\begin{aligned} x &= \frac{b}{2} \{ \cos[(\Omega - p)t] + \cos[(\Omega + p)t] \}, \\ y &= \frac{b}{2} \{ \sin[(\Omega - p)t] - \sin[(\Omega + p)t] \}. \end{aligned} \quad (13)$$

Trigonometric identities simplify this to


$$x = b \cos(pt) \cos(\Omega t), \quad y = -b \sin(pt) \cos(\Omega t). \quad \triangleleft$$

The nature of the path becomes obvious when we observe that  $\sin(pt)$  and  $\cos(pt)$  vary much more slowly than  $\cos(\Omega t)$  because  $p \ll \Omega$ . Hence we may consider  $x$  and  $y$  to oscillate at frequency  $\Omega$  with an amplitude that slowly oscillates at frequency  $p$ . The preceding solution satisfies

$$y = -x \tan(pt),$$

which is the equation of a straight line whose slope is  $-\tan(pt)$ , if we neglect the variation in the value of  $pt$ . As shown in the diagram, the path seems to lie in a

vertical plane that is situated at angle  $pt$  relative to the  $xz$  plane, measured clockwise when viewed downward.



The vertical plane in which the cable lies therefore seems to an observer on the Earth to rotate about the upward vertical axis at angular speed  $-p = -\omega_e \sin \lambda$ . This is exactly opposite the vertical component of the angular velocity of the Earth.

It is interesting to consider the movement of the local plane of the Foucault pendulum's path from the perspective of an observer in outer space who is not experiencing the Earth's rotation. The angular velocity of this plane is the sum of the Earth's rotation  $\bar{\omega}_e$  and the rotation  $-\omega_e \sin \lambda$  about the  $-z$  axis seen by an Earth-based observer. Because the latter cancels the vertical component of  $\bar{\omega}_e$ , the angular velocity that is seen from outer space at any instant is  $\omega_e \cos \lambda$  about the  $x$  axis, which points northward along the Earth's surface.

The movement of the plane of a spherical pendulum relative to the Earth was used in 1851 by the French physicist Jean Louis Foucault (1819–1869) to demonstrate the Earth's rotation. The most famous Foucault pendulum may be found in the General Assembly building at United Nations headquarters in New York City.

In closing, we should note that the spherical pendulum for arbitrary, small initial values of  $x$ ,  $\dot{x}$ ,  $y$ , and  $\dot{y}$  would seem to follow an elliptical path in the  $xy$  plane. The major and minor axes of the ellipse would rotate about the  $z$  axis relative to the Earth at angular speed  $-\omega_e \sin \lambda$ .

## SELECTED REFERENCES

- Baruh, H. *Analytical Dynamics*, McGraw-Hill, New York (1999).  
D'Souza, A. F., and Garg, V. K., *Advanced Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1985).  
Frazer, R. A., Duncan, W. J., and Collar, A. R., *Elementary Matrices*, Cambridge University Press, New York (1960).  
Ginsberg, J. H., and Genin, J., *Dynamics*, 2nd ed., Wiley, New York (1984).


## Homework Problems

159

- Goldstein, H., *Classical Mechanics*, 2nd ed., Addison-Wesley, Reading, Massachusetts, (1980).
- Goodman, L. E., and Warner, W. H., *Dynamics*, Dover, New York (2001).
- Greenwood, D. T., *Principles of Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1965).
- Haug, E. J., *Intermediate Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1992).
- Kraus, A. D., *Matrices for Engineers*, Hemisphere, Washington, D.C. (1987).
- Marion, J. B., *Classical Dynamics of Particles and Systems*, Academic, New York (1960).
- Meirovitch, L., *Methods of Analytical Dynamics*, McGraw-Hill, New York (1970).
- Shabana, A. A., *Computational Dynamics*, Wiley, New York (2001).
- Shames, I. H., *Engineering Mechanics: Statics and Dynamics*, 4th Ed., Prentice-Hall, Englewood Cliffs, New Jersey (1996).
- Smith, C. E., *Applied Mechanics: Dynamics*, Wiley, New York (1982).
- Thomson, W. T., *Introduction to Space Dynamics*, Dover, New York (1986).
- Torby, B. J., *Advanced Dynamics for Engineers*, CBS College Publishing, New York (1984).

## HOMEWORK PROBLEMS

**EXERCISE 3.1** The  $XYZ$  coordinate system coincides with the edges of the box, the  $y$  axis coincides with the main diagonal for the box, and the  $x$  axis coincides with face  $ABCD$ . Use the orthonormal properties to determine the transformation that converts vector components relative to  $XYZ$  to components relative to  $xyz$ . Then use this transformation to determine the  $xyz$  coordinates of corner  $C$ .




Exercise 3.1

**EXERCISE 3.2** Solve Exercise 3.1 by considering the transformation from  $XYZ$  to  $xyz$  to be the result of a sequence of body-fixed rotations.


**EXERCISE 3.3** At a certain instant gyrosensors on an airplane report that it is heading  $40^\circ$  west of north, climbing at  $20^\circ$  and that its wings are banked at an angle of  $10^\circ$  clockwise as viewed looking forward. At this instant, the aircraft's accelerometers indicate that the center of mass has acceleration components relative to the aircraft of  $2g$  downward and  $0.5g$  forward. What are the acceleration components in terms of north-south, east-west, and vertical?

**EXERCISE 3.4** The corners of triangular plate  $ABC$  are situated along the axes of coordinate system  $XYZ$  as shown. Another coordinate system, whose origin is at corner  $A$ , is defined such that  $\bar{i} = \bar{e}_{B/A}$  and  $\bar{k}$  is perpendicular to plane  $ABC$  with a positive component in the direction of  $\bar{J}$ . Determine the rotation transformation from  $XYZ$  to  $xyz$ . Then determine the coordinates of the origin  $O$  with respect to  $xyz$ . *Hint:* Define a coordinate system parallel to  $XYZ$  with its origin at point  $A$ .



Exercise 3.4


**EXERCISE 3.5** The  $xyz$  coordinate system is attached to the box, and  $XYZ$  is a parallel stationary coordinate system. The box undergoes a pair of rotations: First,  $\theta_1 = 65^\circ$  about the  $y$  axis, followed by  $\theta_2 = -145^\circ$  about the  $z$  axis. For this rotation determine (a) the coordinates relative to  $xyz$  in its final orientation of the stationary point that was at the location of point  $E$  prior to the rotations, (b) the coordinates relative to  $XYZ$  of corner  $E$  of the box after both rotations.



Exercise 3.5

**EXERCISE 3.6** Solve Exercise 3.5 if the rotations are  $\theta_1 = 65^\circ$  about the  $Y$  axis, followed by  $\theta_2 = -145^\circ$  about the  $Z$  axis.

**EXERCISE 3.7** The sketch shows an electric fan that may rotate about three axes. In this sketch  $XYZ$  constitute a set of fixed axes, and  $xyz$  are attached to the fan blades. The rotations are defined as follows. When the rotation angle  $\beta$  about the fixed vertical  $Z$  axis is zero, the pin's axis aligns with the fixed horizontal  $Y$  axis. When the rotation angle  $\gamma$  about the pin is zero, the shaft about which the fan blades spin is horizontal. When the spin angle  $\delta$  is zero, the  $x$  axis is aligned with the axis of the pin. Consider a sequence of rotations in which  $\gamma$  occurs first, followed by  $\beta$ , then  $\delta$ . Describe the transformation matrix  $[R]$  for which  $[\bar{i} \ \bar{j} \ \bar{k}]^T = [R][\bar{I} \ \bar{J} \ \bar{K}]^T$  as a set of simple rotation transformations about specific axes. Then identify an alternative sequence in which the rotations  $\beta$ ,  $\gamma$ ,  $\delta$  may be executed and still arrive at the same final orientation of  $xyz$  relative to  $XYZ$ .




Exercise 3.7



# Homework Problems

161


**EXERCISE 3.8** Motor  $A$  in the sketch can be rotated through angle  $\theta_1$  about the vertical shaft, as well as through angle  $\theta_2$  about shaft  $OA$ . The rotation of the flywheel relative to the motor housing is  $\theta_3$ . In this diagram  $xyz$  is attached to the flywheel, and  $x'y'z'$  is attached to shaft  $OA$ , such that the  $y'$  axis always coincides  $OA$  and the  $z'$  axis is always vertical. (a) What is the transformation by which vector components defined with respect to  $x'y'z'$  may be expressed in terms of  $xyz$  components?



Exercise 3.8


(b) One may obtain the rotated position of  $xyz$  with respect to  $x'y'z'$  by rotating first by  $\theta_2$ , and then by  $\theta_3$ , or else by applying  $\theta_3$ , followed by  $\theta_2$ . Prove that the transformation in Part (a) is independent of the sequence in which these rotations are performed. (c) Consider point  $B$ , which is located on the  $z$  axis at the perimeter of the flywheel. The flywheel's radius is  $\rho$ . Use the transformation in Part (a) to describe the displacement of this point relative to  $x'y'z'$ . (You may express this result in terms of any convenient set of coordinate directions, but state what your choice is.)

**EXERCISE 3.9** Rod  $ABC$  is such that segment  $BC$  is perpendicular to segment  $AB$ . The brackets align segment  $AB$  at  $20^\circ$  from the vertical  $Z$  axis, as shown. The rod rotates by angle  $\theta$  about axis  $AB$ , which is defined such that segment  $BC$  is situated in the vertical plane formed by segment  $AB$  and the  $Z$  axis when  $\theta = 0$ . Determine and graph the angle between the centerline of segment  $BC$  and the  $X$  axis as a function of  $\theta$ .



Exercise 3.9


**EXERCISE 3.10** The three-axis gyroscope consists of an outer gimbal that may rotate by angle  $\psi$  about the  $AB$  axis relative to a fixed reference frame  $XYZ$  and an inner gimbal that may rotate by angle  $\theta$  about the  $CD$  axis relative to the outer gimbal. The spin of the flywheel relative to the inner gimbal is the angle  $\phi$ . (These are, respectively, the Eulerian angles of precession, nutation, and spin, which will be discussed in Chapter 4.) When these angles are zero, the body-fixed  $xyz$  system coincides with the respective axes of  $XYZ$ . There are six possible sequences in which the



Exercise 3.10

rotations may take place. Prove that the transformation from  $XYZ$  to  $xyz$  components depends on only the values of these angles, but not the sequence in which the rotations occur.


**EXERCISE 3.11** Starting from the position shown, the box is rotated by  $40^\circ$  about face diagonal  $AB$ , clockwise as viewed from corner  $B$  toward corner  $A$ . Determine the coordinates of corner  $C$  relative to the fixed reference frame after this rotation.



Exercises 3.11 and 3.12

**EXERCISE 3.12** Starting from the position shown, the box is rotated by angle  $\theta$  about main diagonal  $AC$ , counterclockwise as viewed from corner  $C$  toward corner  $A$ . The angle between the fixed  $Y$  axis and the unit vector  $\bar{e}_{E/A}$  after the rotation is  $110^\circ$ . Determine  $\theta$ .

**EXERCISE 3.13** The bent rod is given a pair of rotations, first by  $60^\circ$  about line  $AB$ , and then  $30^\circ$  about line  $AC$ , with the sense of each rotation as shown in the sketch. Let  $xyz$  be a coordinate system fixed to the rod that initially aligned with the fixed  $XYZ$  system shown. Determine the transformation by which vector components with respect to  $XYZ$  may be converted to components with respect to  $xyz$ .




Exercise 3.13

**EXERCISE 3.14** Consider the rotation of the bent rod in Exercise 3.13. Determine the orientation of the axis and the angle of rotation of the single rotation that would be equivalent to the pair of rotations specified there.

**EXERCISE 3.15** It is desired to impart to the box in Exercise 3.5 a rotation about a single axis that is equivalent to the rotations specified there. Determine the orientation of that axis and the angle of rotation about that axis.

**EXERCISE 3.16** Collar  $A$  is welded to the vertical shaft, so  $\theta$  is constant. The rectangular plate is welded to this shaft, and  $xyz$  is a coordinate system that is attached to the plate. Splines prevent shaft  $BC$  from rotating relative to the collar, so  $\phi = 0$ , in which case the  $yz$  plane is always situated in the vertical plane. The system is rotated by  $\psi = 75^\circ$  about the vertical axis; the value of  $\theta$  is  $30^\circ$ . Determine the rotation transformation from relating components relative to the initial and final  $xyz$  coordinate system. From this result determine the angle between the initial and final orientations of the  $y$  axis.



Exercises 3.16 and 3.17


**EXERCISE 3.17** Collar  $A$  is welded to the vertical shaft, so  $\theta$  is constant. The rectangular plate is welded to this shaft, and  $xyz$  is a coordinate system that is attached to the plate. Shaft  $BC$  may rotate relative to the collar by angle  $\phi$ , with  $\phi = 0$  when the  $yz$  plane coincides with the vertical plane, as depicted in the sketch. Starting from the illustrated

# Homework Problems

163

position the system is rotated by  $\psi = 75^\circ$  about the vertical axis, and  $\phi = 115^\circ$ , with  $\theta = 30^\circ$ . Determine the rotation transformation from relating components relative to the initial and final  $xyz$  coordinate system. From this result determine the angle between the initial and final orientations of the  $y$  axis.


**EXERCISE 3.18** A hydraulic cylinder allows the length of arm  $AB$  to vary, and servomotors control the rotation angles  $\theta$  about the vertical,  $\beta$  about pin  $A$ , and  $\gamma$  about axis  $AB$ , with  $\gamma = 0$  corresponding to bar  $BC$  being situated in the vertical plane as shown. In the initial position  $L = 250$  mm,  $\theta = 0$ ,  $\beta = 90^\circ$ , and  $\gamma = 0$ . In the final position,  $\theta = \beta = 120^\circ$ ,  $\gamma = -90^\circ$ , and  $L = 500$  mm. Determine the corresponding displacement of end  $C$ .



Exercise 3.18


**EXERCISE 3.19** Solve Exercise 3.18 for the case the initial state is such that  $L = 250$  mm,  $\theta = 0$ ,  $\beta = 30^\circ$ , and  $\gamma = 50^\circ$ . The final position is as specified there.

**EXERCISE 3.20** Bar  $ABC$  rotates through angle  $\theta$  about the fixed  $X$  axis, and collar  $C$  enables bar  $CD$  to rotate by angle  $\phi$  about segment  $BC$  of bar  $ABC$ . When  $\theta = \phi = 0$ , both bars are situated in the  $XY$  plane. Determine the displacement of end  $D$  from this reference position to one where  $\phi = -70^\circ$  and  $\theta = 120^\circ$ .




Exercise 3.20

**EXERCISE 3.21** Flexure of a cantilevered shaft supporting a rotating flywheel causes the center  $C$  of the flywheel to undergo transverse displacement  $w$ , and the centerline of the flywheel to rotate relative to the bearing axis, which is marked as  $Z$  in the diagram. The rotation of the plane formed by the bearing axis and center  $C$  is  $\psi$ , and the flywheel's centerline lies in this rotated plane. The disk is welded to the shaft, so the angle  $\theta$  between this centerline and the bearing axis is the flexural angle by which the tangent to the shaft rotates because of deformation. Torsional deformation of the shaft is described by the rotation  $\phi$  of diametral line  $ACB$ ; when  $\phi = 0$ , this line lies in the plane containing the flywheel's centerline and the bearing axis. In the initial position  $w = \psi = \theta = \phi = 0$ , whereas  $w = 50$  mm,  $\psi = 460^\circ$ ,  $\theta = 10^\circ$ , and  $\phi = 8^\circ$  in the final position. Determine the corresponding displacement of points  $A$  and  $B$  on the perimeter of the flywheel.



Exercise 3.21

**EXERCISE 3.22** The disk centered at point  $B$  is an optical mirror that is positioned by servo-controlled arms. Angle  $\theta_1$  is the rotation about the stationary horizontal shaft,  $\theta_2$  is the rotation of the motor housing about shaft  $OA$ , and  $\theta_3$  is the rotation of the flywheel relative to the motor housing. When  $\theta_1 = \theta_2 = \theta_3 = 0$  shaft  $OA$  is horizontal, shaft  $AB$  is vertical, and the line from center  $B$  to point  $C$  on the perimeter of the flywheel is parallel to the shaft for the  $\theta_1$  rotation. In the position of interest the angles are  $\theta_1 = 75^\circ$ ,  $\theta_2 = -120^\circ$ , and  $\theta_3 = 210^\circ$ . Determine the displacement of point  $C$  relative to its location when  $\theta_1 = \theta_2 = \theta_3 = 0$ . The length dimensions are  $H = 300$  mm,  $L = 500$  mm,  $R = 100$  mm.



Exercise 3.22


**EXERCISE 3.23** In Exercise 3.16 collar  $A$ , which is welded to the vertical shaft, allows shaft  $BC$  to slide rotate relative to it, so the distance  $L$  and rotation angle  $\phi$  are not constant. The rectangular plate is welded to this shaft, and it is situated in the vertical plane when  $\phi = 0$ . In the initial state  $L = 3H$  and  $\psi = \phi = 0$ . In the final position  $\psi = 60^\circ$ ,  $\phi = -75^\circ$ , and  $L = 5H$ . Determine the displacement of corner  $D$  in terms of components relative to the final orientation of the body-fixed  $xyz$  coordinate system.

**EXERCISE 3.24** In Exercise 3.18 the rates are  $\dot{L} = 5$  m/s,  $\dot{\theta} = 40$  rad/s,  $\dot{\beta} = 0$  rad/s, and  $\dot{\gamma} = 10$  rad/s. At  $t = 0$  it is known that  $L = 200$  mm,  $\theta = 0$ ,  $\beta = 75^\circ$ , and  $\gamma = -30^\circ$ . Determine the displacement of end  $C$  in the interval from  $t = 0$  to  $t = 10$  ms. Compare that result with the approximate value obtained by considering the angular velocity to be constant over the interval.

**EXERCISE 3.25** Consider the linkage in Exercise 3.20 when the initial position corresponds to  $\theta = 30^\circ$  and  $\phi = 50^\circ$ , and  $\theta = 28^\circ$  and  $\phi = 47^\circ$  in the final position. Compare the displacement of end  $D$  obtained by considering these rotations to be infinitesimal with the result obtained from an analysis based on rotation transformations.

**EXERCISE 3.26** The bladed disk of a gas turbine in an aircraft is spinning at the constant rate of 30 000 rev/min while the aircraft travels at 1200 km/h in a 2-km radius turn to the left. Determine the angular velocity and angular acceleration of the disk.

**EXERCISE 3.27** The rotation rates  $\omega_1$  of the bracket supporting the spinning disk are constant. The spin rate of the disk is increasing linearly with elapsed time, so that  $\omega_2 = \xi t$ . (a) Describe the angular velocity of the disk in terms of a superposition of simple rotations. (b) Solely from an examination of the description in Part (a), predict the direction(s) in which the angular acceleration of the disk will be situated relative to the  $xyz$  axes defined in the sketch, which rotates in unison with the support




Exercise 3.27

## Homework Problems

165

bracket. Briefly explain your answer. (c) Describe the angular velocity and angular acceleration of the disk in terms of components relative to  $xyz$  coordinate system.

**EXERCISE 3.28** The entire system rotates about the vertical axis at constant angular speed  $\omega_1$ , and the rotation rate  $\omega_2$  of the rotor relative to bar  $BC$  also is constant. (a) Describe the angular velocity of the rotor in terms of a superposition of simple rotations. (b) Solely from an examination of the description in Part (a), predict the direction(s) in which the angular acceleration of the rotor will be situated relative to the  $xyz$  axes defined in the sketch. Briefly explain your answer. (c) Describe the angular velocity and angular acceleration of the rotor in terms of components relative to  $xyz$ .



Exercise 3.28


**EXERCISE 3.29** The flywheel of the gyroscope in Exercise 3.10 rotates about its own axis at  $\dot{\phi} = 50\,000$  rev/min, and the outer gimbal is rotating about the horizontal axis at  $\dot{\psi} = 20$  rad/s, with  $\ddot{\psi} = -100$  rad/s<sup>2</sup>. Determine the angular velocity and angular acceleration of the flywheel if the orientation of the inner gimbal relative to the outer one is constant at (a)  $\theta = 90^\circ$ , (b)  $\theta = 60^\circ$ .

**EXERCISE 3.30** The flywheel of the gyroscope in Exercise 3.10 rotates about its own axis at  $\dot{\phi} = 50\,000$  rev/min, and the outer gimbal is rotating about the horizontal axis at  $\dot{\psi} = 20$  rad/s, with  $\ddot{\psi} = -100$  rad/s<sup>2</sup>. At the instant when the angle  $\theta$  locating the inner gimbal relative to the outer one is  $\theta = 75^\circ$ , it is changing at  $\dot{\theta} = -2$  rad/s,  $\ddot{\theta} = 50$  rad/s<sup>2</sup>. Determine the angular velocity and angular acceleration of the flywheel at this instant.

**EXERCISE 3.31** The orientation angles  $\theta$ ,  $\beta$ , and  $\gamma$  in Exercise 3.18 each change at a constant rate. At the instant of interest,  $\beta = 90^\circ$  and  $\gamma = 0$ . Determine the angular velocity and angular acceleration of arm  $BC$  at this instant in terms of components relative to a coordinate system that is attached to the vertical shaft.


**EXERCISE 3.32** The orientation angles  $\theta$ ,  $\beta$ , and  $\gamma$  in Exercise 3.18 each change at a constant rate. At the instant of interest,  $\beta = 60^\circ$  and  $\gamma = 30^\circ$ . Determine the angular velocity and angular acceleration of arm  $BC$  at this instant in terms of components relative to a coordinate system that is attached to this arm with  $\bar{k} = \bar{e}_{C/B}$ .

**EXERCISE 3.33** The collar moves at the constant speed  $u$  relative to the guide bar, which rotates in the horizontal plane at the constant rate  $\Omega$ . Derive expressions for the velocity and acceleration of the collar as functions of the angle  $\theta$ , locating where the collar is situated along its guide. Describe the results in terms of components relative to the  $xyz$  coordinate system appearing in the sketch.




Exercise 3.33

**EXERCISE 3.34** A servomotor maintains the angle of bar  $BC$  relative to bar  $AB$  at  $\phi = 2\theta$ , where  $\theta$  is the angle of inclination of bar  $AB$ . Determine the acceleration of end  $C$  corresponding to arbitrary values of  $\theta$ ,  $\dot{\theta}$ , and  $\ddot{\theta}$ .




Exercise 3.34

**EXERCISE 3.35** A speed governor consists of a block of mass  $m$  that slides within a smooth groove in a turntable that rotates about its center point  $O$  at angular speed  $\Omega$ . The identical opposing springs, whose stiffness is  $k$ , are precompressed. Consequently the springs maintain their contact with the block regardless of the displacement  $s$ . The system lies in the horizontal plane. Derive an expression for the normal force exerted by the groove wall on the block and the differential equation governing  $s$  as a function of time in the case where  $\Omega$  is an arbitrary function of time. Then determine the natural frequency of vibratory motion of the block within the groove for the case in which  $\Omega$  is constant, and explain how that result can be used to monitor when  $\Omega$  exceeds a critical value.




Exercise 3.35

**EXERCISE 3.36** The disk rotates at  $\omega_2$  about its axis, and the rotation rate of the forked shaft is  $\omega_1$ . Both rates are constant. It is desired to determine the velocity and acceleration of point  $P$  in the perimeter of the disk, which is oriented on the radial line that has rotated by  $\theta$  relative to the upward vertical. Perform this analysis using a reference frame attached to the forked shaft; then compare that analysis with one that uses a reference frame attached to the disk. Describe the results in terms of components relative to the  $xyz$  axes in the sketch.



Exercise 3.36

**EXERCISE 3.37** The angle  $\theta$  describing the rotation of a reconnaissance satellite's solar panels about the body-fixed  $x$  axis is an arbitrary function of time. The satellite spins about the  $z$  axis at the constant rate  $\Omega$ . Derive expressions for the absolute velocity and acceleration of point  $B$  relative to the origin of  $xyz$ .




Exercise 3.37

**EXERCISE 3.38** The disk spins about its axis  $CD$  at 1200 rev/min as the system rotates about the vertical axis at 20 rev/min. Both rates are constant. It is desired to determine the velocity and acceleration of point  $E$ , which is the lowest point on the perimeter of the disk, in the situation in which  $\beta$  is constant at  $60^\circ$ . (a) Carry out the analysis by using

# Homework Problems

167


a moving reference frame attached to gimbal  $BCD$ . (b) Carry out the analysis by using a moving reference frame attached to the disk.



Exercises 3.38 and 3.39

**EXERCISE 3.39** The disk spins about its axis  $CD$  at 1200 rev/min as the system rotates about the vertical axis at 20 rev/min. Both rates are constant. The angle of elevation of the arm supporting the disk is such that  $\dot{\beta} = 10 \text{ rad/s}$  and  $\ddot{\beta} = -500 \text{ rad/s}^2$  when  $\beta = 36.87^\circ$ . Determine the velocity and acceleration of point  $E$ , which is the lowest point on the perimeter of the disk.

**EXERCISE 3.40** Collar  $C$  slides relative to the curved rod at a constant speed  $u$ . The rotation rate about bearing axis  $AB$  is constant at  $\Omega$ . Determine the acceleration of the collar in terms of the angle  $\theta$  locating the collar. Also derive expressions for the dynamic forces exerted on the collar by the rod and the tangential force required to hold  $u$  constant. Gravity may be assumed to be unimportant.




Exercise 3.40

**EXERCISE 3.41** The following questions pertain to the application of the relative motion formulas:

$$\vec{v}_B = \vec{v}_{O'} + (\vec{v}_B)_{xyz} + \vec{\omega} \times \vec{r}_{B/O'}$$

$$\vec{a}_B = \vec{a}_{O'} + (\vec{a}_B)_{xyz} + \vec{\alpha} \times \vec{r}_{B/O'} + \vec{\omega} \times (\vec{\omega} \times \vec{r}_{B/O'}) + 2\vec{\omega} \times (\vec{v}_B)_{xyz}$$

In each question,  $xyz$  in these formulas is equated to one of the coordinate systems in the diagram, and you are to describe one of the corresponding relative motion terms. Each answer should be expressed in component form relative to any of the three coordinate systems, but a different coordinate system may be used to describe each answer. (a) If  $xyz = x'''y'''z'''$ , what is  $\vec{\omega}$ ? (b) If  $xyz = x''y''z''$ , what is  $\vec{\alpha}$ ? (c) If  $xyz = x'''y'''z'''$ , what is  $\vec{\alpha}$ ? (d) If  $xyz = x''y''z''$ , what is  $(\vec{v}_B)_{xyz}$ ? (e) If  $xyz = x''y''z''$ , what is  $(\vec{a}_B)_{xyz}$ ? (f) If  $xyz = x'''y'''z'''$ , what is  $\vec{v}_{O'}$ ? (g) If  $xyz = x'y'z'$ , what is  $\vec{r}_{B/O'}$ ?




Exercise 3.41

**EXERCISE 3.42** The rotation rates of the bars in Exercise 3.20 are constant at  $\dot{\theta} = 20$  rad/s,  $\dot{\phi} = 30$  rad/s. For the instant when  $\theta = 120^\circ$  and  $\phi = 50^\circ$ , determine the velocity and acceleration of end  $D$  of the bar.


**EXERCISE 3.43** Use the concepts of relative motion to derive the formulas for velocity and acceleration of a point in terms of a set of spherical coordinates.

**EXERCISE 3.44** The sketch defines an orthogonal curvilinear coordinate system  $\rho, \theta, \phi$  known as toroidal coordinates. The radius  $R$  is a constant parameter on which these coordinates are based. Use the concepts of relative motion to derive the corresponding formulas for velocity and acceleration of point  $P$  in terms of the unit vectors of this coordinate system.



Exercise 3.44


**EXERCISE 3.45** The track of a roller coaster is described in terms of a reference centerline that is defined in parametric form by a function  $\bar{r}(s)$  locating points along it, with  $s$  being the arc length from the start. In turn this defines a set of path variable unit vectors  $\bar{e}_t, \bar{e}_n, \bar{e}_b$  at each point. These unit vectors depend on the location, so they define a moving reference frame  $x'y'z'$ . As shown in the diagram, the track is laid out by defining a line that is rotated by angle  $\beta$ , which can depend on  $s$ , about  $\bar{e}_t$ . This line is used to situate the tracks at a fixed distance  $d$  on either side of the reference centerline. Thus coordinate system  $xyz$  is a moving reference frame whose  $x$  axis is  $\bar{e}_t$  and whose  $y$  axis indicates the orientation of an axle of a car as it moves along the track, with  $\bar{\omega}_{xyz} = \bar{\omega}_{x'y'z'} + \dot{\beta}\bar{e}$ .



Exercise 3.45

(a) Suppose a car moves along the track at a speed  $v$  that depends on  $s$ . Based on the approximation that the longitudinal axis of the car is parallel to  $\bar{e}_t$ , derive an expression for the angular velocity and angular acceleration of the car in terms of the radius of curvature  $\rho(s)$  and torsion  $\tau(s)$  of the path. (b) Consider a point at distance  $h$  above the axle,  $\bar{r}_{P/O} = h\bar{j}$ . Determine the velocity and acceleration of such a point corresponding to the expressions derived in Part (a). *Hint:* Use the Frenet formulas and the fact that  $ds/dt \equiv v$  to describe the rate of change of the path variable unit vectors, then equate these derivatives to the general property that  $d\bar{e}/dt = \bar{\omega} \times \bar{e}$ .

**EXERCISE 3.46** The blades of a centrifugal flow pump are attached to the central hub such that their tangent at their outer radius is at angle  $\beta$  relative to the radial line at that location. The radius of curvature of the blades at the tip is  $\rho$ . Suppose water flows outward along a blade at a constant relative speed  $u$  and the rotation rate  $\Omega$  is constant. Determine the velocity and acceleration of a water particle immediately



Exercise 3.46




## Homework Problems

169


before it flows off a blade. Also determine the exit angle  $\theta$  at which the water is directed as it leaves the blade.

**EXERCISE 3.47** A pellet of mass  $m$  moves through the smooth barrel. At the instant before the pellet emerges, its speed relative to the barrel is  $u$ . At that instant, the magnitude of the propulsive force  $F$ , which acts parallel to the barrel, is a factor of 50 times greater than the weight of the pellet. The barrel rotates about the vertical axis at angular speed  $\Omega$  as the angle of elevation of the barrel is increased at the rate  $\dot{\theta}$ . Both rates are constant. Derive expressions for the acceleration term  $\ddot{u}$  and the force the pellet exerts on the walls of the barrel at this instant.




Exercise 3.47

**EXERCISE 3.48** While the tank is moving forward at a constant speed  $v_c = 30$  km/h, the turret is rotating at the constant rate  $\omega_1 = 0.3$  rad/s and the barrel is being raised at the constant rate  $\dot{\theta} = 0.5$  rad/s. At a certain instant the barrel is facing forward and  $\theta = 15^\circ$ . At this instant a shell whose mass is 80 kg is about to emerge from the barrel with a muzzle velocity  $v_{\text{rel}} = 5500$  km/h that has reached a maximum because the internal propulsive pressure within the barrel has been dissipated. Determine the force exerted by the shell on the wall of barrel at this instant.




Exercise 3.48

**EXERCISE 3.49** A shipping container is suspended from a crane by an inextensible cable. The crane rotates in the vertical plane at the constant angular speed  $\Omega$ . It may be assumed that the cable remains taut, so its orientation is describable in terms of the angle  $\theta$  locating the vertical plane in which it is situated relative to the plane of the crane and the angle of elevation  $\phi$  from a vertical line. Based on a model of the container as a small particle, derive differential equations of motion in which the only unknowns are  $\theta$  and  $\phi$ .




Exercise 3.49

**EXERCISE 3.50** The vertical shaft rotates at the constant rate  $\Omega$ . Collar  $C$  is attached to this shaft by a fork-and-clevis, so the angle of inclination  $\theta$  of bar  $AB$  is an unknown time function. The bar is free to slide through the collar, so the distance  $\xi$  from the pivot point to end  $B$  is an arbitrary function of  $t$ . Derive expressions for the velocity and acceleration of point  $B$  in terms of  $\xi$ ,  $\theta$ , and their derivatives, as well as  $\Omega$ .




Exercise 3.50

**EXERCISE 3.51** The disk, whose radius is  $R$ , spins about axis  $AB$  relative to the bent shaft. The angle of rotation of a radial line to point  $P$  on the perimeter of the disk about this axis is  $\theta$ , so  $\dot{\theta}$  is the spin rate. This angle is defined such that line  $OP$  is situated in the plane containing the bearing axis and axis  $AB$  when  $\theta = 0$ . The whole assembly precesses at angular speed  $\Omega$  about the bearing axis, with the disk's center situated on the bearing axis. Derive expressions for the velocity and acceleration of point  $P$  on the perimeter of the disk. Describe the results in terms of components relative to an  $xyz$  system that is attached to the disk, with  $\bar{i}$  aligned from the disk's center to point  $P$ .



Exercise 3.51

**EXERCISE 3.52** Bent shaft  $ABC$  is welded to the vertical shaft, which rotates at constant speed  $\Omega$ . The angle of rotation of the square plate about axis  $BC$  is  $\phi$ , which is an arbitrary function of time. The configuration depicted in the sketch, in which the plate is situated in the vertical plane, corresponds to  $\phi = 0$ . The  $xyz$  coordinate system is attached to the plate. (a) Derive expressions for the angular velocity and angular acceleration of the plate, valid for arbitrary  $\phi$ , in terms of components with respect to  $xyz$ . (b) Derive expressions for the velocity and acceleration of the center of the plate in terms of  $xyz$  components.




Exercise 3.52

**EXERCISE 3.53** Instantaneous parameters for the robotic linkage in Example 3.6 are  $\theta = 40^\circ$ ,  $\dot{\theta} = 5 \text{ rad/s}$ ,  $\ddot{\theta} = -200 \text{ rad/s}^2$ ,  $\beta = 0$ ,  $\dot{\beta} = -3 \text{ rad/s}$ ,  $\ddot{\beta} = 0$ ,  $\gamma = 20^\circ$ ,  $\dot{\gamma} = 10 \text{ rad/s}$ ,  $\ddot{\gamma} = 0$ , and  $L$  is constant at  $0.8 \text{ m}$ . Determine the velocity and acceleration of end  $C$  at this instant.

**EXERCISE 3.54** Instantaneous parameters for the robotic linkage in Example 3.6 are  $\theta = 70^\circ$ ,  $\dot{\theta} = 5 \text{ rad/s}$ ,  $\ddot{\theta} = -200 \text{ rad/s}^2$ ,  $\beta = -60^\circ$ ,  $\dot{\beta} = 4 \text{ rad/s}$ ,  $\ddot{\beta} = 40 \text{ rad/s}^2$ ,  $\gamma = 20^\circ$ ,  $\dot{\gamma} = 10 \text{ rad/s}$ ,  $\ddot{\gamma} = 0$ ,  $L = 0.8 \text{ m}$ ,  $\dot{L} = 20 \text{ m/s}$ ,  $\ddot{L} = 100 \text{ m/s}^2$ . Determine the velocity and acceleration of end  $C$  at this instant.

**EXERCISE 3.55** The larger gear rotates at half the angular speed of the smaller gear, which is rotating clockwise at a constant rate of  $4800 \text{ rev/min}$ . Points  $A$  and  $B$  are corners of gear teeth that will mesh. At a certain instant  $\theta_1 = 85^\circ$  and  $\theta_2 = 42^\circ$ . For this instant determine the velocity and acceleration of corner  $B$  with respect to corner  $A$  as seen from a reference frame that is attached to the smaller gear.




Exercise 3.55

## Homework Problems

171


**EXERCISE 3.56** Airplane  $A$  travels eastward at constant speed  $v_B = 560$  km/h, while airplane  $A$  executes a constant-radius turn,  $\rho = 3.2$  km, in the horizontal plane at constant speed  $v_A = 1440$  km/h. At  $t = 0$  the angle  $\theta$  locating airplane  $A$  was zero, and  $s_A$  at that instant was 5.2 km. Radar equipment on aircraft  $A$  can measure the separation distance  $r$  and the angle  $\phi$  relative to the aircraft's longitudinal axis, as well as the rates of change of these parameters. Derive expressions for  $r$ ,  $\dot{r}$ ,  $\phi$ , and  $\dot{\phi}$ . Graph these parameters as functions of time.



Exercise 3.56

**EXERCISE 3.57** At a certain instant the absolute velocity and acceleration of an aircraft's center of mass in terms of a body-fixed coordinate system are  $\vec{v} = 900\vec{i}$  km/h,  $\vec{a} = 5\vec{j}$  m/s<sup>2</sup>, where  $\vec{i}$  is the longitudinal forward direction and  $\vec{k}$  is the direction perceived to be upward. The longitudinal axis is pitched upward at  $10^\circ$  from horizontal. The airplane has rolled to  $25^\circ$  in order to execute a left turn and the roll rate at this instant is 2 rad/s about the positive  $x$  axis. The corresponding yaw rate is 0.5 rad/s about the positive  $z$  axis, and both the roll and yaw rates are constant. At this instant an attendant drops a beverage container from a height of 800 mm above a passenger. Determine the acceleration of the container as seen by the passenger at the instant of release.

**EXERCISE 3.58** A test chamber for astronauts rotates about its centerline at constant angular speed  $\omega_1$  as the entire assembly rotates about the bearing axis at angular speed  $\omega_2$ , which also is constant. An astronaut is seated securely in the chamber at center point  $O$ , which is collinear with both axes of rotation. At a certain instant a ball that was thrown toward the astronaut is at position  $B$ , which is at distance  $X$  along the fixed rotation axis. Its speed at this instant is  $v_B$ , and  $\dot{v}_B = 0$ . Derive expressions for the velocity and acceleration of the ball as seen by the astronaut at this instant.



Exercises 3.58 and 3.59

**EXERCISE 3.59** A test chamber for astronauts rotates about its centerline at constant angular speed  $\omega_1$  as the entire assembly rotates about the bearing axis at angular speed  $\omega_2$ , which also is constant. An astronaut is seated securely in the chamber at center point  $O$ , which is collinear with both axes of rotation. Ball  $C$  falls freely after being released at  $t = 0$  from height  $H$ , so the vertical distance from the observer to the ball is  $Z = H - gt^2/2$ . At  $t = 0$  the plane containing the two rotation axes is horizontal. Determine as a function of elapsed time  $t$  the velocity and acceleration of the ball as seen by the astronaut.


**EXERCISE 3.60** A small disk slides with negligible friction on a horizontal sheet of ice. The initial velocity of the disk was  $u$  in the southerly direction. Determine the distance and sense of the east–west shift  $s$  in the position after the disk has traveled distance  $d$

southward. How would this result have changed if the initial velocity was northward or eastward?

**EXERCISE 3.61** A ball is thrown vertically from the ground at speed  $v$ . Assuming that air resistance is negligible and that the distance the ball travels is sufficiently small to consider the gravitational force to be  $mg$  downward, derive an expression for the shift that is due to the Coriolis effect in the position where it returns to the ground. Evaluate the result for  $v = 4000$  m/s at a latitude of  $45^\circ$ .

**EXERCISE 3.62** An object falls in a vacuum after being released at a distance  $H$  above the surface of the Earth. The line extending from the center of the Earth to this object is at latitude  $\lambda$ , and point  $O'$  on the Earth's surface is concurrent with this line. Determine the location (east–west and north–south relative to point  $O'$ ) at which the object strikes the ground in each of the following cases: (a) The object is initially at rest relative to the Earth, (b) the object was initially at rest relative to a reference frame that translates with the center of the Earth but does not execute the Earth's spinning rotation. For the sake of simplicity, the gravitational attraction may be considered to be constant at  $mg$ . Explain the difference between the results in cases (a) and (b).

**EXERCISE 3.63** A small disk of mass  $m$  is attached to a horizontal turntable by two pairs of opposing springs having stiffnesses  $k_x$  and  $k_y$  that are unstretched length when the block coincides with the axis of the turntable. The  $(x, y)$  coordinates of the block relative to the turntable are much less than the radius of the turntable, which means that the force exerted by each spring on the disk may be taken to be  $k_x x$  or  $k_y y$  opposite the direction of the respective displacement. Derive differential equations for  $x$  and  $y$  for the case in which the turntable's rotation rate  $\Omega$  is an arbitrary function of time. Then solve those equations for the case in which  $\Omega$  is constant. The initial state for this solution is one in which the block is released from rest relative to the turntable at  $x = b$ ,  $y = 0$ . Discuss how this system is analogous to the Foucault pendulum.



Exercise 3.63

## CHAPTER 4

# Kinematics of Constrained Rigid Bodies

The concept of a rigid body is an artificial one, in that all materials deform when forces are applied to them. Nevertheless, this artifice is very useful when we are concerned with an object whose shape changes little in the course of its motion. In addition, it often is convenient to decompose the motion of a flexible body into rigid-body and deformational contributions.

Most engineering systems feature bodies that are interconnected. Each body must move consistently with the restrictions imposed on it by the other bodies. We refer to these restrictions as *constraints*. Constraint conditions are the kinematical manifestations of the reaction forces. Indeed, a synonym for reactions is constraint forces. A keystone of analytical dynamics, whose treatment begins in Chapter 7, is the duality of constraint forces and constraint conditions, which enable us to describe one if we know the other. However, in a kinematics analysis one is not concerned with the forces required to attain a specified state of motion.

### 4.1 GENERAL EQUATIONS

When an object is modeled as a *rigid body*, the distance separating any pair of points in that object is considered to be invariant. This approximation is quite useful because it leads to greatly simplified kinematical and kinetic analyses. Because the distance between points cannot change, any set of coordinate axes  $xyz$  that is scribed in the body will maintain its orientation relative to the body. Such a coordinate system forms a body-fixed reference frame. The orientation of  $xyz$  relative to the body and the location of its origin are arbitrary. A typical situation is depicted in Fig. 4.1, where points  $O'$ ,  $A$ , and  $B$  are arbitrarily selected points in the body.

A corollary of the rigidity of the body is that no point in the body can displace relative to  $xyz$ , so  $(x_A, y_A, z_A)$  are both the initial and final  $xyz$  coordinates of point  $A$  and there is no displacement relative to  $xyz$ ,  $(\Delta \bar{r}_A)_{xyz} = \bar{0}$ . Correspondingly, Eq. (3.2.7) shows that the  $\bar{I}\bar{J}\bar{K}$  displacement components of points  $A$  are related to those of point  $O'$  by

$$\begin{Bmatrix} \Delta \bar{r}_A \cdot \bar{I} \\ \Delta \bar{r}_A \cdot \bar{J} \\ \Delta \bar{r}_A \cdot \bar{K} \end{Bmatrix} = \begin{Bmatrix} \Delta \bar{r}_{O'} \cdot \bar{I} \\ \Delta \bar{r}_{O'} \cdot \bar{J} \\ \Delta \bar{r}_{O'} \cdot \bar{K} \end{Bmatrix} + \left[ [R]_f^T - [R]_o^T \right] \begin{Bmatrix} x_A \\ y_A \\ z_A \end{Bmatrix}, \quad (4.1.1)$$




Figure 4.1. Relating the motion of three points in a rigid body.

where  $[R]_o$  and  $[R]_f$  are the rotation transformations of  $xyz$  with respect to  $XYZ$  in the original and final locations, respectively. The fact that points in the body cannot move relative to the body-fixed reference frame also simplifies the velocity and acceleration relations. Because  $(\bar{v}_A)_{xyz} = \bar{0}$  and  $(\bar{a}_A)_{xyz} = \bar{0}$ , we have

$$\begin{aligned}\bar{v}_A &= \bar{v}_{O'} + \bar{\omega} \times \bar{r}_{A/O'}, \\ \bar{a}_A &= \bar{a}_{O'} + \bar{\alpha} \times \bar{r}_{A/O'} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{A/O'}).\end{aligned}\quad (4.1.2)$$

Although we placed the origin of  $xyz$  at point  $O'$ , there is nothing special about the choice of points. Thus, relations like Eqs. (4.1.1) and (4.1.2) exist, relating the motion of any pair of points. However, all such relations are not independent. In the case of displacement we observe by analogy to Eq. (4.1.1) that the displacement of point  $B$  is related to that of point  $O'$  by

$$\begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{I} \\ \Delta \bar{r}_B \cdot \bar{J} \\ \Delta \bar{r}_B \cdot \bar{K} \end{Bmatrix} = \begin{Bmatrix} \Delta \bar{r}_{O'} \cdot \bar{I} \\ \Delta \bar{r}_{O'} \cdot \bar{J} \\ \Delta \bar{r}_{O'} \cdot \bar{K} \end{Bmatrix} + \left[ [R]_f^T - [R]_o^T \right] \begin{Bmatrix} x_B \\ y_B \\ z_B \end{Bmatrix}.\quad (4.1.3)$$

On the other hand, we could use an  $x'y'z'$  coordinate system that is parallel to  $xyz$  with origin at point  $A$ . Because  $\bar{r}_{B/A} = \bar{r}_{B/O'} - \bar{r}_{A/O'}$ , the coordinates of the points are related by a translation transformation, such that

$$x'_B = x_B - x_A, \quad y'_B = y_B - y_A, \quad z'_B = z_B - z_A.\quad (4.1.4)$$

Because  $x'y'z'$  is specified to always be parallel to  $xyz$ ,  $[R]_f$  and  $[R]_o$  also are the transformations from  $\bar{I}\bar{J}\bar{K}$  to  $\bar{i}'\bar{j}'\bar{k}'$  components. Thus the analog to Eq. (4.1.1) relating the displacements of points  $A$  and  $B$  is

$$\begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{I} \\ \Delta \bar{r}_B \cdot \bar{J} \\ \Delta \bar{r}_B \cdot \bar{K} \end{Bmatrix} = \begin{Bmatrix} \Delta \bar{r}_A \cdot \bar{I} \\ \Delta \bar{r}_A \cdot \bar{J} \\ \Delta \bar{r}_A \cdot \bar{K} \end{Bmatrix} + \left[ [R]_f^T - [R]_o^T \right] \begin{Bmatrix} x_B - x_A \\ y_B - y_A \\ z_B - z_A \end{Bmatrix}.\quad (4.1.5)$$

The significant aspect of this relation is that it is the same as the result of subtracting Eq. (4.1.1) from Eq. (4.1.3). Thus we deduce that the displacements of three points in a rigid body are related by two independent equations. We would arrive at a similar conclusion if we were to follow similar steps to relate the velocity or acceleration

#### 4.1 General Equations

175

of points  $O'$ ,  $A$ , and  $B$  by using Eqs. (4.1.2). For example, for velocity we would have

$$\begin{aligned}\bar{\mathbf{v}}_A &= \bar{\mathbf{v}}_{O'} + \bar{\boldsymbol{\omega}} \times \bar{\mathbf{r}}_{A/O'}, \\ \bar{\mathbf{v}}_B &= \bar{\mathbf{v}}_{O'} + \bar{\boldsymbol{\omega}} \times \bar{\mathbf{r}}_{B/O'}, \\ \bar{\mathbf{v}}_B &= \bar{\mathbf{v}}_A + \bar{\boldsymbol{\omega}} \times \bar{\mathbf{r}}_{B/A}.\end{aligned}\tag{4.1.6}$$

Because  $\bar{\mathbf{r}}_{B/A} = \bar{\mathbf{r}}_{B/O'} - \bar{\mathbf{r}}_{A/O'}$ , the third of the preceding equations is the same as the difference between the second and first equations. If we consider relating additional points, we come to the realization that only one additional equation for displacement, velocity, or acceleration exists for each point added. This leads us to a general conclusion:

Given a set of  $n$  points in a rigid body, there are  $n - 1$  independent equations relating their displacement, velocity, or acceleration. We may obtain these equations by selecting one point as the reference for the description of the other  $n - 1$  points. Let  $A$  designate the reference point and  $P$  denote any of the other points. Then the displacement components relative to the fixed reference frame are related by

$$\begin{Bmatrix} \Delta \bar{\mathbf{r}}_P \cdot \bar{\mathbf{I}} \\ \Delta \bar{\mathbf{r}}_P \cdot \bar{\mathbf{J}} \\ \Delta \bar{\mathbf{r}}_P \cdot \bar{\mathbf{K}} \end{Bmatrix} = \begin{Bmatrix} \Delta \bar{\mathbf{r}}_A \cdot \bar{\mathbf{I}} \\ \Delta \bar{\mathbf{r}}_A \cdot \bar{\mathbf{J}} \\ \Delta \bar{\mathbf{r}}_A \cdot \bar{\mathbf{K}} \end{Bmatrix} + \left[ [\mathbf{R}]_f^T - [\mathbf{R}]_o^T \right] \begin{Bmatrix} x_P - x_A \\ y_P - y_A \\ z_P - z_A \end{Bmatrix}.\tag{4.1.7}$$

The velocities of these points are related by

$$\bar{\mathbf{v}}_P = \bar{\mathbf{v}}_A + \bar{\boldsymbol{\omega}} \times \bar{\mathbf{r}}_{P/A},\tag{4.1.8}$$

and the accelerations are related by

$$\bar{\mathbf{a}}_P = \bar{\mathbf{a}}_A + \bar{\boldsymbol{\alpha}} \times \bar{\mathbf{r}}_{P/A} + \bar{\boldsymbol{\omega}} \times (\bar{\boldsymbol{\omega}} \times \bar{\mathbf{r}}_{P/A}).\tag{4.1.9}$$

It is important to realize that the preceding expressions for displacement, velocity, and acceleration, being vectorial in nature, each represent three scalar equations associated with the respective components. It follows that if one relates the motion of  $n$  points in a body,  $3(n - 1)$  scalar equations will result. Such equations will be solved in the following sections to perform kinematical analyses of the motion of systems of rigid bodies.

Equations (4.1.7)–(4.1.9) show that the velocity and the acceleration of any point in a rigid body are the superposition of the movement of an arbitrarily selected reference point  $A$  and a rotational motion about point  $A$ . These observations are manifestations of Chasle's theorem:

The *general motion* of a rigid body is a superposition of a translation and a pure rotation. In the *translation*, all points follow the movement of an arbitrary point  $A$  in the body, and the orientation of any line scribed in the body remains constant. In the rotation the selected point  $A$  is at rest.

As a consequence of the arbitrariness of the point selected for the translation, changing the reference point changes the translational part of the motion, except for the case of pure translational motion. This means that the only global property of a rigid

body's motion is its rotation, as described by the current orientation of a set of  $xyz$  axes scribed in it, its angular velocity, and its angular acceleration. Various methods for locating a point by means of intrinsic and extrinsic coordinates were discussed in Chapter 2. The next section presents a standardized way for describing orientation.

A basic tool in the analysis of velocity for a body in planar motion is the instant center method. In essence, this technique is based on considering a body in general motion (translation plus rotation) to be rotating about a rest point, which is called the instantaneous center of zero velocity, or more briefly, the *instant center*. If there is a point  $C$  in a body for which  $\bar{v}_C = \bar{0}$  at some instant, then Eq. (4.1.8) indicates that  $\bar{v}_P = \bar{\omega} \times \bar{r}_{P/C}$ . This means that point  $C$  must be along a line perpendicular to  $\bar{v}_P$  and intersecting point  $P$ . If the direction of the velocity of two points in a body is known at some instant, the instant center, if it exists, will be at the intersection of the two perpendiculars that are constructed according to this specification. (In the case of a translating body, the perpendiculars to the velocity of all points will be parallel, which leads to  $\bar{r}_{P/C}$  being infinite. This is consistent with  $\omega$  being zero.)

The instant center for planar motion leads to a simplified visualization of the velocity of points. Each point's velocity is like what would be obtained if the point were following a circular path whose radius is the perpendicular distance to the axis of rotation intersecting the instant center. However, the usefulness of the instant center concept is quite narrow. The condition that  $\bar{v}_P = \bar{\omega} \times \bar{r}_{P/C}$  for all points in a body requires that the velocity of all points be perpendicular to  $\bar{\omega}$ , which is not true for general spatial motion. In addition, the instant center concept is not valid for acceleration analysis because the instant center will have an acceleration unless the body is in pure rotation. Also,  $\bar{a}$  is not parallel to  $\bar{\omega}$  in a spatial motion. Thus, for the purpose of analyzing acceleration, we cannot visualize points as following a circular path about a stationary center. For these reasons we shall not invoke instant center concept as an analytical tool, but it might be useful for explaining some feature.


Chasle's theorem could be used to represent the velocity as the superposition of a translation that follows a special point  $C$  and a pure rotation about point  $C$  at angular speed  $\bar{\omega}$ . Point  $C$  has the property that its velocity is parallel to  $\bar{\omega}$ . This is a *screw motion*, whose terminology stems from an analogy with the movement of a screw with a right-handed thread, which is to advance in the direction of the outstretched thumb of the right hand when the fingers of that hand are curled in the sense that the screw turns. We shall not pursue such a representation because it does little to improve our ability to perform a kinematical analysis. However, some people do find it to be a useful way to visualize spatial motion.

**EXAMPLE 4.1** Observation of the motion of the block reveals that at a certain instant the velocity of corner  $B$  is parallel to the diagonal  $BE$ . At this instant components relative to the body-fixed  $xyz$  coordinate system of the velocities of the other corners are believed to be  $(v_A)_y = 10$ ,  $(v_C)_y = 20$ ,  $(v_D)_z = 10$ ,  $(v_E)_x = 5$  m/s. Determine whether these values are possible, and if so, evaluate the velocity of corner  $F$ .



#### 4.1 General Equations

177



#### Example 4.1

**SOLUTION** In addition to illustrating application of the basic equation relating the velocity of points in a rigid body, the objective here is to emphasize that Chasle's theorem is embedded in any motion. It is given that  $\bar{v}_B = v_B \bar{e}_{E/B}$ ,  $\bar{v}_A \cdot \bar{j} = 10$ ,  $\bar{v}_C \cdot \bar{j} = 20$ ,  $\bar{v}_D \cdot \bar{k} = 10$ , and  $\bar{v}_E \cdot \bar{i} = 5$  m/s. There are four independent equations in the form of Eq. (4.1.8) relating the five corner points. Decomposing each into components would yield 12 scalar equations. The associated unknown scalar quantities are the speed of point  $B$ , the two unspecified components of the velocities of points  $A$ ,  $C$ ,  $D$ , and  $E$ , and the three components of  $\bar{\omega}$ , which are a set of 12 values. This reasoning suggests that the number of equations and unknowns will match in the contemplated analysis, so we proceed.

We select point  $B$  as the reference point for the translational motion, because the only unknown aspect of its velocity is the speed, that is,

$$\bar{v}_B = v_B \bar{e}_{E/B} = v_B \frac{1.5\bar{i} + 2\bar{j} - 1\bar{k}}{(1.5^2 + 2^2 + 1^2)^{1/2}} = v_B (0.5571\bar{i} + 0.7428\bar{j} - 0.3714\bar{k}).$$

The angular velocity is unknown, so we let  $\bar{\omega} = \omega_x \bar{i} + \omega_y \bar{j} + \omega_z \bar{k}$ . The velocity equations relating point  $B$  to the other points are

$$\begin{aligned}\bar{v}_A &= \bar{v}_B + \bar{\omega} \times \bar{r}_{A/B}, & \bar{r}_{A/B} &= -1\bar{k}, \\ \bar{v}_C &= \bar{v}_B + \bar{\omega} \times \bar{r}_{C/B}, & \bar{r}_{C/B} &= 2\bar{j}, \\ \bar{v}_D &= \bar{v}_B + \bar{\omega} \times \bar{r}_{D/B}, & \bar{r}_{D/B} &= 2\bar{j} - 1\bar{k}, \\ \bar{v}_E &= \bar{v}_B + \bar{\omega} \times \bar{r}_{E/B}, & \bar{r}_{E/B} &= 1.5\bar{i} + 2\bar{j} - 1\bar{k}.\end{aligned}$$

Rather than forming the full set of scalar equations resulting from matching like components in each of the preceding vector equations, focusing on those velocity components that are specified lessens the number of equations to be solved. Thus we have

$$\begin{aligned}\bar{v}_A \cdot \bar{j} &= 10 = 0.7428v_B + \omega_x(1), \\ \bar{v}_C \cdot \bar{j} &= 20 = 0.7428v_B, \\ \bar{v}_D \cdot \bar{k} &= 10 = -0.3714v_B + \omega_x(2), \\ \bar{v}_E \cdot \bar{i} &= 5 = 0.5571v_B - \omega_y(1) - \omega_z(2).\end{aligned}$$

Although these are four equations for the four unknown parameters, the equations are not solvable. The first three equations contain only two unknowns:  $\omega_x$  and  $v_B$ . If we solve the second equation for  $v_B$ , the value of  $\omega_x$  obtained from the first equation differs from the value obtained from the third equation. This means that the motion is *overconstrained*. In the exceptional situation in which the velocity components  $\bar{v}_A \cdot \bar{j}$ ,  $\bar{v}_C \cdot \bar{j}$ , and  $\bar{v}_D \cdot \bar{k}$  are selected such that there is a consistent solution for  $\omega_x$  and  $v_B$ , we would still be unable to solve the problem because the fourth equation would be the sole relation for the two remaining unknowns:  $\omega_y$  and  $\omega_z$ .  $\triangleleft$

## 4.2 EULERIAN ANGLES

Three independent direction angles define the orientation of a set of  $xyz$  axes. Because there are a total of nine direction angles locating  $xyz$  with respect to an absolute reference frame  $XYZ$ , an independent set of angles may be selected in a variety of ways. Eulerian angles treat this matter as a specific sequence of rotations.

Let us follow the intermediate orientations of a moving reference frame as it is rotated away from its initial alignment with  $XYZ$ . The first rotation, called the *precession*, is about the fixed  $Z$  axis. The angle of rotation in the precession is denoted  $\psi$ , as depicted in Fig. 4.2. The orientation of the moving reference frame after it has undergone only the precession is denoted as  $x'y'z'$ . The transformation from  $\bar{I}\bar{J}\bar{K}$  components to  $\bar{i}'\bar{j}'\bar{k}'$  components is that of a single axis rotation about the  $Z$  (or  $z'$ ) axis, specifically

$$\begin{Bmatrix} A_{x'} \\ A_{y'} \\ A_{z'} \end{Bmatrix} = [R_\psi] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix}, \quad (4.2.1)$$

where

$$[R_\psi] = \begin{bmatrix} \cos \psi & \sin \psi & 0 \\ -\sin \psi & \cos \psi & 0 \\ 0 & 0 & 1 \end{bmatrix}. \quad (4.2.2)$$




Figure 4.2. Definition of the Eulerian angles.

## 4.2 Eulerian Angles

179

The second rotation is the *nutation*, and the nutation angle is  $\theta$ . It is defined to be about an axis that is perpendicular to the precession axis. We label the nutation axis as  $y'$ . The orientation of the moving reference frame after the nutation is denoted  $x''y''z''$  in Fig. 4.2. The second transformation, from  $\bar{i}'\bar{j}'\bar{k}'$  components to  $\bar{i}''\bar{j}''\bar{k}''$  components, is that of a simple rotation about the  $y'$  (or  $y''$ ) axis, so

$$\begin{Bmatrix} A_{x''} \\ A_{y''} \\ A_{z''} \end{Bmatrix} = [R_\theta] \begin{Bmatrix} A_{x'} \\ A_{y'} \\ A_{z'} \end{Bmatrix}, \quad (4.2.3)$$

where

$$[R_\theta] = \begin{bmatrix} \cos \theta & 0 & -\sin \theta \\ 0 & 1 & 0 \\ \sin \theta & 0 & \cos \theta \end{bmatrix}. \quad (4.2.4)$$

The last rotation is the *spin*  $\phi$ , which moves the reference frame from  $x''y''z''$  to its final orientation  $xyz$ . It is executed about the  $z''$  (or  $z$ ) axis, so this is a simple rotation transformation from  $\bar{i}''\bar{j}''\bar{k}''$  components to  $\bar{i}\bar{j}\bar{k}$  components given by

$$\begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix} = [R_\phi] \begin{Bmatrix} A_{x''} \\ A_{y''} \\ A_{z''} \end{Bmatrix}, \quad (4.2.5)$$

where

$$[R_\phi] = \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix}. \quad (4.2.6)$$

The sequence of rotations, precession, nutation, then spin, constitute a set of body-fixed rotations. Consequently, we can use the transformation properties of such a sequence to relate any two sets of unit vectors. For example, the overall transformation from  $\bar{I}\bar{J}\bar{K}$  components to  $\bar{i}\bar{j}\bar{k}$  components is obtained by postmultiplication, according to

$$\begin{Bmatrix} A_x \\ A_y \\ A_z \end{Bmatrix} = [R] \begin{Bmatrix} A_X \\ A_Y \\ A_Z \end{Bmatrix}, \quad [R] = [R_\phi][R_\theta][R_\psi]. \quad (4.2.7)$$

The angular velocity and angular acceleration are readily expressed by adding the precession, nutation, and spin rates about the respective axes. The precession is about the  $Z$  axis, so the first rotation rate is  $\dot{\psi}$ , the direction is  $\bar{e}_1 = \bar{K}$ , and the angular velocity of  $XYZ$  is  $\bar{\Omega}_1 = \bar{0}$ . The nutation occurs about the  $y'$  axis. (The term *line of nodes* is sometimes used to refer to the  $y'$  axis because points on this axis do not move in the

nutations.) The nutation rate is  $\dot{\theta}$ , the direction is  $\bar{e}_2 = \bar{j}' \equiv \bar{j}''$ , and the angular velocity of  $x'y'z'$  is  $\bar{\Omega}_2 = \dot{\psi} \bar{K}$ . Finally, the spin rate is  $\dot{\phi}$  about the  $z''$  axis, so the third rotation direction is  $\bar{e}_3 = \bar{k}''$ , and the angular velocity of  $x''y''z''$  is  $\bar{\Omega}_3 = \dot{\psi} \bar{K} + \dot{\theta} \bar{j}''$ . The angular velocity of  $xyz$  is the vector sum of the individual rotation rates, so

$$\bar{\omega} = \dot{\psi} \bar{K} + \dot{\theta} \bar{j}'' + \dot{\phi} \bar{k}'' . \quad (4.2.8)$$

The general expression for angular acceleration obtained by using each angular velocity  $\bar{\Omega}_j$  to differentiate the corresponding rotation direction  $\bar{e}_j$  is

$$\begin{aligned} \bar{\alpha} &= \ddot{\psi} \bar{K} + \ddot{\theta} \bar{j}'' + \dot{\theta} (\bar{\Omega}_2 \times \bar{j}'') + \ddot{\phi} \bar{k}'' + \dot{\phi} (\bar{\Omega}_3 \times \bar{k}'') \\ &= \ddot{\psi} \bar{K} + \ddot{\theta} \bar{j}'' + \dot{\psi} \dot{\theta} (\bar{K} \times \bar{j}'') + \ddot{\phi} \bar{k}'' + \dot{\psi} \dot{\phi} (\bar{K} \times \bar{k}'') + \dot{\theta} \dot{\phi} (\bar{j}'' \times \bar{k}'') . \end{aligned} \quad (4.2.9)$$

To use these expressions in computations, they must be transformed to a common set of components. Many situations involve bodies that have an axisymmetric shape, with the  $z$  axis defined to be the axis of symmetry. In such cases there is no special orientation of the  $x$  and  $y$  axes relative to the body, so using  $x''y''z''$  as the global coordinate system will yield a description of vector quantities from the viewpoint of the body that is generally descriptive. Inspection of Fig. 4.2 shows that  $\bar{K}$  lies in the  $x''z''$  plane, such that

$$\bar{K} = -\sin \theta \bar{i}'' + \cos \theta \bar{k}'' . \quad (4.2.10)$$

We thereby find that

When the angular velocity  $\bar{\omega}$  and angular acceleration  $\bar{\alpha}$  of reference frame  $xyz$  are described in terms of the Eulerian angles of precession  $\psi$ , nutation  $\theta$ , and spin  $\phi$ , then

$$\begin{aligned} \bar{\omega} &= -\dot{\psi} \sin \theta \bar{i}'' + \dot{\theta} \bar{j}'' + (\dot{\psi} \cos \theta + \dot{\phi}) \bar{k}'' , \\ \bar{\alpha} &= (-\ddot{\psi} \sin \theta - \dot{\psi} \dot{\theta} \cos \theta + \dot{\theta} \dot{\phi}) \bar{i}'' + (\ddot{\theta} + \dot{\psi} \dot{\phi} \sin \theta) \bar{j}'' \\ &\quad + (\ddot{\psi} \cos \theta + \ddot{\phi} - \dot{\psi} \dot{\theta} \sin \theta) \bar{k}'' , \end{aligned} \quad (4.2.11)$$

where  $x''y''z''$  is a reference frame that executes only the precession and nutation. If appropriate, the preceding expressions may be transformed to  $\bar{i} \bar{j} \bar{k}$  components by applying Eq. (4.2.5). This operation yields

$$\begin{aligned} \bar{\omega} &= (-\dot{\psi} \sin \theta \cos \phi + \dot{\theta} \sin \phi) \bar{i} + (\dot{\psi} \sin \theta \sin \phi + \dot{\theta} \cos \phi) \bar{j} + (\dot{\psi} \cos \theta + \dot{\phi}) \bar{k} , \\ \bar{\alpha} &= (-\ddot{\psi} \sin \theta \cos \phi + \ddot{\theta} \sin \phi - \dot{\psi} \dot{\theta} \cos \theta \cos \phi + \dot{\psi} \dot{\phi} \sin \theta \sin \phi + \dot{\theta} \dot{\phi} \cos \phi) \bar{i} \\ &\quad + (\ddot{\psi} \sin \theta \sin \phi + \ddot{\theta} \cos \phi + \dot{\psi} \dot{\theta} \cos \theta \sin \phi + \dot{\psi} \dot{\phi} \sin \theta \cos \phi - \dot{\theta} \dot{\phi} \sin \phi) \bar{j} \\ &\quad + (\ddot{\psi} \cos \theta + \ddot{\phi} - \dot{\psi} \dot{\theta} \sin \theta) \bar{k} . \end{aligned} \quad (4.2.12)$$


## 4.2 Eulerian Angles

181

Utilization of Eulerian angles requires recognition of the appropriate axes of rotation. This involves identifying a fixed axis of rotation as the precession axis. Then the nutation axis precesses orthogonally to the precession axis. Finally, the spin axis precesses and nutates while it remains perpendicular to the nutation axis. In many cases, the nutation or spin rates may be zero, in which case either of the respective angles is constant. This results in a degree of arbitrariness in the selection of the axes. Indeed, a simple rotation can be considered to be solely precession, nutation, or spin, as one wishes.

From one perspective it is sufficient to rely on Eqs. (4.2.12) because they reduce to Eqs. (4.2.11) when  $\phi = 0$ , which corresponds to  $xyz$  being coincident with  $x''y''z''$ . On the other hand, the raw expressions in Eqs. (4.2.8) and (4.2.9) are readily adapted to a variety of situations. This is especially true if the axes are labeled differently from the convention used here. For example, some texts define the  $x'$  axis to be the line of nodes for nutation. Also, a different definition of the Eulerian angles often is used by aerodynamicists. (This is the topic of Exercise 4.6.) Another consideration is that the Eulerian angle formulas may not be directly applicable. For example, the representation addresses a motion featuring no more than three rotations, so one set of Eulerian angles cannot describe a situation that features more than three rotations. Such situations could be treated by defining multiple sets of transformations. Another case in which the Eulerian angle formulation is inadequate by itself arises when a motion consists of three rotations in which no two rotation axes are orthogonal. No line of nodes is evident in that case. This is another situation that can be treated with more than one set of Eulerian angles.

**EXAMPLE 4.2** A free gyroscope consists of a flywheel that rotates relative to the inner gimbal at the constant angular speed of 8000 rev/min, and the rotation of the inner gimbal relative to the outer gimbal is  $\gamma = 0.2 \sin(100\pi t)$  rad. The rotation of the outer gimbal is  $\beta = 0.5 \sin(50\pi t)$  rad. Use the Eulerian angle formulas to determine the angular velocity and angular acceleration of the flywheel at  $t = 4$  ms. Express the results in terms of components relative to the body-fixed  $xyz$  and space-fixed  $XYZ$  reference frames, where the  $x$  axis was directed from bearing  $D$  to bearing  $C$  at  $t = 0$ .



Example 4.2

**SOLUTION** This example explains how one can apply the Eulerian angle formulas when none of the rotations are explicitly stated to be those parameters. The primary task in applying the formulas is identification of the precession, nutation, and spin. The angle  $\beta$  is the rotation about a fixed axis, so it is the precession. Thus we set  $\psi = \beta = 0.5 \sin(50\pi t)$  in the formulas. By definition, the nutation axis is perpendicular to the precession axis. This matches the characteristic of line  $CD$  for the  $\gamma$  rotation, so we identify  $\bar{e}_{C/D}$  as the line of nodes, and set  $\theta = \gamma = 0.2 \sin(100\pi t)$  in the formulas. The 8000 rev/min rotation occurs in the direction of  $\bar{e}_{F/E}$ , which is perpendicular to the line of nodes, so it fits the spinning rotation. Furthermore, it is specified that the  $x$  axis was aligned with  $\bar{e}_{C/D}$  at  $t = 0$ , so we set  $\phi = 8000 (2\pi/60) t$  rad. The Eulerian angles and their derivatives at  $t = 0.004$  are

$$\begin{aligned}\psi &= 0.2939 \text{ rad}, \quad \dot{\psi} = 63.54 \text{ rad/s}, \quad \ddot{\psi} = -7\,252 \text{ rad/s}^2, \\ \theta &= 0.19021 \text{ rad}, \quad \dot{\theta} = 19.416 \text{ rad/s}, \quad \ddot{\theta} = -18\,773 \text{ rad/s}^2, \\ \phi &= 3.351 \text{ rad}, \quad \dot{\phi} = 837.8 \text{ rad/s}, \quad \ddot{\phi} = 0.\end{aligned}\tag{1}$$

To avoid confusing the  $xyz$  coordinate system in the definition of Eulerian angles with the coordinate system defined here, let us use a subscript  $f$  to denote the unit vectors in the formulas, Eqs. (4.2.12). Then the result of substituting the values in Eqs. (1) into those formulas is

$$\begin{aligned}\bar{\omega} &= 7.71\bar{i}_f - 21.49\bar{j}_f + 900.15\bar{k}_f \text{ rad/s}, \\ \bar{\alpha} &= -14256\bar{i}_f + 11934\bar{j}_f - 7354\bar{k}_f \text{ rad/s}^2.\end{aligned}\tag{2}$$

The rotation transformation  $[R]$  in Eq. (4.2.7) relates vector components in the body-fixed system to the standard fixed reference frame  $X_f Y_f Z_f$ . For the angles in Eqs. (1), this transformation is

$$\begin{aligned}[\bar{i}_f \quad \bar{j}_f \quad \bar{k}_f]^T &= [R][\bar{I}_f \quad \bar{J}_f \quad \bar{K}_f]^T, \\ [R] &= \begin{bmatrix} -0.85909 & -0.47723 & 0.18494 \\ 0.47876 & -0.87707 & -0.03931 \\ 0.18096 & 0.05477 & 0.98196 \end{bmatrix}.\end{aligned}$$

We use the inverse transformation to obtain the fixed coordinate system components of  $\bar{\omega}$  and  $\bar{\alpha}$ , as follows:

$$\begin{aligned}\{\omega\}_f &= [R]^T \begin{Bmatrix} 7.71 \\ -21.49 \\ 900.15 \end{Bmatrix} = \begin{Bmatrix} 145.98 \\ 64.47 \\ 886.19 \end{Bmatrix}, \\ \{\alpha\}_f &= [R]^T \begin{Bmatrix} -14256 \\ 11934 \\ -7354 \end{Bmatrix} = \begin{Bmatrix} 16\,630 \\ -4\,066 \\ -10\,327 \end{Bmatrix}.\end{aligned}\tag{3}$$

### 4.3 Interconnections and Linkages

183

It still remains to identify the components corresponding to the coordinate systems that were defined in the problem statement. Toward that end we observe that the spin occurs about the  $y$  axis, so it must be that  $\bar{k}_f = \bar{j}$ . We also observe that the  $x$  axis aligned with  $\bar{e}_{C/D}$  at  $t = 0$ , which is the line of nodes. In the Eulerian definition the  $y_f$  axis lines up with the line of nodes when  $\phi = 0$ , which matches the alignment of the  $x$  axis here. Thus we set  $\bar{j}_f = \bar{i}$ . Then, because  $\bar{j}_f \times \bar{k}_f \equiv \bar{i} \times \bar{j}$ , it must be that  $\bar{i}_f = \bar{k}$ . Substitution of these equivalencies into Eqs. (2) yields

$$\begin{aligned}\bar{\omega} &= -21.49\bar{i} + 900.2\bar{j} + 7.71\bar{k} \text{ rad/s}, \\ \bar{\alpha} &= 11934\bar{i} - 7354\bar{j} - 14256\bar{k} \text{ rad/s}^2.\end{aligned}\tag{4} \triangleleft$$

In regard to the fixed coordinate components, we observe in the present situation that  $\bar{j} = \bar{J}$  and  $\bar{i} = \bar{I}$  when all of the Eulerian angles are zero. Hence it must be that the fixed unit vectors are permuted in the same way as the moving unit vectors. In other words,  $\bar{K}_f = \bar{J}$ ,  $\bar{J}_f = \bar{I}$ , and  $\bar{I}_f = \bar{K}$ . Selecting the elements in Eqs. (3) accordingly then leads to

$$\begin{aligned}\bar{\omega} &= 64.47\bar{I} + 886.19\bar{J} + 145.98\bar{K} \text{ rad/s}, \\ \bar{\alpha} &= -4\,066\bar{I} - 10\,327\bar{J} + 16\,630\bar{K} \text{ rad/s}^2.\end{aligned}\triangleleft$$

As an aside, it should be mentioned that if one is confronted in practice with the situation posed here, an approach based on returning to the basic formulation might be easier, and less prone to error, than one that relies on formulaic substitutions.

### 4.3 INTERCONNECTIONS AND LINKAGES

According to Eq. (4.1.7), the displacement of any point in a rigid body from a known initial state can be evaluated if the displacement of a reference point and the rotation transformation in the final state are known. Point displacement is a three-component vector, and a rotation transformation is defined completely by three angles, such as the Eulerian angles. Thus a rigid body in free motion has six degrees of freedom.


Most bodies are restricted in their movement because they are connected to adjoining bodies. These connections give rise to *kinematical constraint equations*, which are mathematical statements of conditions that are imposed on the motion of a point or on the angular motion of a body. Such equations are relations between kinematical variables that must be satisfied under any circumstance, regardless of the nature of the forces that actuate the motion. The kinematical constraints are imposed by *constraint forces* (and couples), which are more commonly known as *reactions*. The role of constraint forces and their relation to the kinematical conditions they impose will be treated in the chapters on kinetics.

A simple, though common, constraint condition arises when a body is permitted to execute only a planar motion. By definition, planar motion means that all points in the body move in parallel planes, which can only happen if the angular velocity is always perpendicular to these planes. Let the  $XY$  plane of the fixed reference frame and the

$xy$  plane of the body fixed reference frame be coincident planes of motion. Points that differ only in their  $z$  coordinate execute the same motion in this case, so they may be considered to be situated in the  $xy$  plane. Hence the kinematical equations for planar motion are


$$\begin{aligned}\bar{\omega} &= \omega \bar{k} = \dot{\omega} \bar{K}, \quad \bar{\alpha} = \dot{\omega} \bar{k} = \dot{\omega} \bar{K}, \\ r_{P/A} &= x\bar{i} + y\bar{j} = X\bar{I} + Y\bar{J}, \\ \bar{v}_P &= \bar{v}_A + \bar{\omega} \times \bar{r}_{P/A}, \\ \bar{a}_P &= \bar{a}_A + \bar{\alpha} \times \bar{r}_{P/A} - \omega^2 \bar{r}_{P/A},\end{aligned}\tag{4.3.1}$$

where point  $P$  is an arbitrary point in the body and point  $A$  is any convenient reference point in the same body. Note that the preceding centripetal acceleration term is simplified from  $\bar{\omega} \times (\bar{\omega} \times \bar{r}_{P/A})$  to  $-\omega^2 \bar{r}_{P/A}$  by an identity that is valid only when  $\bar{r}_{P/A}$  is perpendicular to  $\bar{\omega}$ . These relations are depicted in Fig. 4.3.



**Figure 4.3.** Relation of the velocity and acceleration of two points in a rigid body undergoing planar motion.

The restriction to planar motion contains an implicit assumption that the connections to other bodies permit rotation only about an axis perpendicular to the plane. An analysis of spatial motion requires explicit consideration of the constraint conditions arising from connections. These may be identified by characterizing the nature of the connection using the fundamental concepts developed thus far. For example, the *ball-and-socket joint* connecting bodies 1 and 2 in Fig. 4.4 allows each body to rotate freely about its center point  $B$ , so it does not impose a constraint on the orientation of either



**Figure 4.4.** Ball-and-socket joint.



### 4.3 Interconnections and Linkages

185

body. However, the center  $B$  of the ball is common to both bodies, so the bodies must move in unison at this junction. This means that the displacement, velocity, and acceleration of point  $B$  on each body must match, so that

$$(\Delta \bar{r}_B)_1 = (\Delta \bar{r}_B)_2, \quad (\bar{v}_B)_1 = (\bar{v}_B)_2, \quad (\bar{a}_B)_1 = (\bar{a}_B)_2 \quad (4.3.2)$$

The case of a *pin connection* between bodies, depicted in Fig. 4.5, has some elements in common with a ball-and-socket joint. In the figure,  $x_1 y_1 z_1$  and  $x_2 y_2 z_2$  represent reference frames attached to each of the joined bodies, with their shared  $z$  axis aligned along the axis of the pin. We define each  $x$  axis to align with a convenient reference line in the respective body, such as the centerline for a bar. The direction of the pin's axis may be evaluated from a cross product:

$$\bar{e}_{\text{pin}} = \bar{k}_1 = \bar{k}_2 = \frac{\bar{i}_1 \times \bar{i}_2}{|\bar{i}_1 \times \bar{i}_2|} \quad (4.3.3)$$

As is true of the ball-and-socket joint, both bodies have the same motion at their point of commonality. Consequently, Eqs. (4.3.2) must be satisfied. However, the pin also introduces a constraint on rotation. The only rotation of body 2 relative to body 1 permitted by the pin connection is a spin about the  $z_1$  or  $z_2$  axis. We denote the spin angle as  $\phi$ , with  $\phi = 0$  defined as the configuration in which  $x_1 y_1 z_1$  and  $x_2 y_2 z_2$  coincide. A simple rotation transformation about the  $z$  axis gives  $\bar{i}_2 \bar{j}_2 \bar{k}_2$  components in terms of  $\bar{i}_1 \bar{j}_1 \bar{k}_1$  components:

$$\begin{Bmatrix} A_{x_2} \\ A_{y_2} \\ A_{z_2} \end{Bmatrix} = [R_\phi] \begin{Bmatrix} A_{x_1} \\ A_{y_1} \\ A_{z_1} \end{Bmatrix}, \quad [R_\phi] = \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix} \quad (4.3.4)$$

The constraints introduced by a pin connection on the angular velocity and angular acceleration may be expressed in vector form. Because  $x_2 y_2 z_2$  spins at  $\dot{\phi}$  about the  $\bar{k}_1 = \bar{k}_2$  axis, the respective angular velocities are related by

$$\bar{\omega}_2 = \bar{\omega}_1 + \dot{\phi} \bar{k}_1. \quad (4.3.5)$$

The angular velocity of  $x_1 y_1 z_1$  is  $\bar{\omega}_1$ , so the time derivative of the preceding is

$$\bar{\alpha}_2 = \bar{\alpha}_1 + \ddot{\phi} \bar{k}_1 + \dot{\phi} (\bar{\omega}_1 \times \bar{k}_1). \quad (4.3.6)$$




Figure 4.5. Pin connection.

Equations (4.3.4)–(4.3.6) are constraint equations on the angular motion that must be satisfied in addition to Eqs. (4.3.2) for the connecting points. Each of these relations may be transformed to any convenient global set of components. It is interesting to observe that, if a system is arranged such that all pin connections are parallel, then the rotational constraint equations lead to the conclusion that the  $z$  axis of each pin is invariant. In other words, using pins aligned perpendicular to a fixed plane will lead to planar motion of a system in that plane.

Another common method for connecting bodies consists of a *collar* that slides over a bar, as depicted in Fig. 4.6. (This connection is also known as a *slider*.) Similar to the treatment of a ball-and-socket joint, point  $C$  in the figure denotes the center of the ball. For most purposes, the distance to the adjacent point  $B$  on the centerline of bar 1 is small relative to the overall dimensions of a system. We take this distance to be zero for the sake of simplicity. (The modifications required to account for the finiteness of this distance are the topic of Exercise 4.7.) The collar is free to slide over bar 1. We characterize the constraint condition in this case by attaching reference frame  $x_1y_1z_1$  to bar 1, with the  $x_1$  axis aligned with the centerline of that bar. With respect to this reference frame, the collar can move along only the  $x_1$  axis. We let  $u$  denote the amount of this relative displacement, so  $(\Delta \bar{r}_C)_{x_1y_1z_1} = u\bar{i}_1$ , and approximate  $\bar{r}_{C/B}$  to be zero. Taking point  $O'$  in Eq. (3.2.8) to be point  $B$  in the present situation leads to the conclusion that the collar's displacement in terms of components relative to the axes of  $x_1y_1z_1$  is given by

$$\begin{Bmatrix} \Delta \bar{r}_C \cdot \bar{i} \\ \Delta \bar{r}_C \cdot \bar{j} \\ \Delta \bar{r}_C \cdot \bar{k} \end{Bmatrix} = \begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{i} \\ \Delta \bar{r}_B \cdot \bar{j} \\ \Delta \bar{r}_B \cdot \bar{k} \end{Bmatrix} + \begin{Bmatrix} u \\ 0 \\ 0 \end{Bmatrix}.$$

Alternatively, the general description in Eq. (3.2.7) may be used to describe the absolute displacement, which leads to

$$\begin{Bmatrix} \Delta \bar{r}_C \cdot \bar{I} \\ \Delta \bar{r}_C \cdot \bar{J} \\ \Delta \bar{r}_C \cdot \bar{K} \end{Bmatrix} = \begin{Bmatrix} \Delta \bar{r}_B \cdot \bar{I} \\ \Delta \bar{r}_B \cdot \bar{J} \\ \Delta \bar{r}_B \cdot \bar{K} \end{Bmatrix} + [R]_{\text{f}}^{\text{T}} \begin{Bmatrix} u \\ 0 \\ 0 \end{Bmatrix},$$

where  $[R]$  describes the orientation of  $x_1y_1z_1$ . The velocity of point  $C$  relative to  $x_1y_1z_1$  is  $\dot{u}\bar{k}_1$ , so we have

$$\bar{v}_C = \bar{v}_B + \dot{u}\bar{i}_1, \quad \bar{a}_C = \bar{a}_B + \ddot{u}\bar{i}_1 + 2\bar{\omega}_1 \times \dot{u}\bar{i}_1, \quad (4.3.7)$$

where the sign of  $u$  and its derivatives gives the sense of the sliding motion.





Figure 4.6. Collar with a ball-and-socket joint.

### 4.3 Interconnections and Linkages

187

It should be noted that the analyses of the collar's displacement, velocity, and acceleration assumed that bar 1 is straight. If this bar were curved, it would be necessary to augment the relative acceleration with the centripetal acceleration term  $(\dot{u}^2/\rho)\bar{e}_n$ , where  $\rho$  is the radius of curvature of bar 1 at point  $B$  and  $\bar{e}_n$  is the normal direction (pointing toward the center of curvature) for the segment at point  $B$ .

The collar in Fig. 4.6 introduces no angular motion restrictions because bar 2 is connected to the collar by a ball-and-socket joint. However, a common connection method is a pin, Fig. 4.7(a), or a *fork-and-clevis* joint, Fig. 4.7(b). If the cross section of bar 1 is not circular, interference prevents the collar from spinning about that bar. In that case the constraints on angular motion are the same as Eqs. (4.3.4)–(4.3.6) for a pin connection. However, if the cross section of bar 1 is circular, then bar 1 acts as a pin that permits rotation about its axis. We treat the angular motion constraints for this connection by attaching  $x_2y_2z_2$  to bar 2; the  $z_2$  axis is chosen to align with the axis of the pin connecting bar 2 and the collar, and the  $x_2$  axis coincides with a convenient reference line of bar 2.



**Figure 4.7.** Collar connections that impose rotational constraints: (a) collar with a pin connection, (b) collar with a fork-and-clevis joint.

Let  $\psi$  denote the angle by which the collar rotates relative to bar 1 about the  $x_1$  axis, and let  $\theta$  be the rotation of bar 2 about the pin relative to the collar. (As implied by their labels,  $\psi$  represents precession of bar 2 relative to bar 1, and  $\theta$  represents a relative spin.) Define these angles such that  $\psi = \theta = 0$  corresponds to  $x_1y_1z_1$  and  $x_2y_2z_2$  being parallel. These are a pair of body-fixed rotations, so the rotation transformation from  $\bar{i}_1\bar{j}_1\bar{k}_1$  to  $\bar{i}_2\bar{j}_2\bar{k}_2$  is given by

$$\begin{Bmatrix} A_{x_2} \\ A_{y_2} \\ A_{z_2} \end{Bmatrix} = [R_\theta][R_\psi] \begin{Bmatrix} A_{x_1} \\ A_{y_1} \\ A_{z_1} \end{Bmatrix}, \quad (4.3.8)$$

where  $[R_\psi]$  and  $[R_\theta]$  are simple rotation transformations for  $\psi$  about the  $x_1$  axis and by  $\theta$  about the  $z_2$  axis, respectively. The rotation rates of bar 2 relative to bar 1 are  $\dot{\psi}$  about the  $x_1$  axis, and by  $\dot{\theta}$  about the  $z_2$  axis, so

$$\bar{\omega}_2 = \bar{\omega}_1 + \dot{\psi}\bar{i}_1 + \dot{\theta}\bar{k}_2. \quad (4.3.9)$$

Using the angular velocities of each reference frame to describe the time derivative of the respective unit vectors leads to

$$\bar{\alpha}_2 = \bar{\alpha}_1 + \dot{\psi} \bar{i}_1 + \dot{\psi} (\bar{\omega}_1 \times \bar{i}_1) + \dot{\theta} \bar{k}_2 + \dot{\theta} (\bar{\omega}_2 \times \bar{k}_2). \quad (4.3.10)$$

Equations (4.3.7)–(4.3.10) constitute the constraint equations for a collar sliding over bar 1 whose cross section is circular. As always, these conditions may be represented in terms of any convenient global coordinate system.

It should be obvious from the discussion thus far that the connections need to be examined in detail to identify all constraints on the motion. If all of the permutations and novel features of various types of connections were to be tabulated, it would not aid our understanding. It is preferable to consider each connection on a case-by-case basis, and then to employ the type of reasoning developed thus far to identify the constraint equations.

As noted at the outset, it follows from Chasle's theorem that a rigid body in free motion has six degrees of freedom. If a system is composed of  $N$  bodies, its movement could be described by as many as  $6N$  kinematical variables. However, the constraint equations for the appropriate types of connection and the fact that some connections are part of the same body reduce the number of free variables. The overall approach is to use the rotational constraints, if any exist, to characterize the angular motion of the body, simultaneously with employing kinematical equations (4.1.7)–(4.1.9) to relate the motion of constrained points in a body. When such relations are broken down into components, one obtains simultaneous equations for the kinematical variables describing the motion of each body.

If the motion of the system is *fully constrained*, then this system of equations will be solvable such that, for each body, the linear motion of a point and the angular motion may be evaluated. The system is only *partially constrained* if the number of kinematical variables exceeds the number of kinematical equations. The simultaneous equations may then be solved for a set of excess variables in terms of the other. The excess variables in this case depend on the nature of the force system, so their evaluation requires a kinetics study. The number of excess kinematical variables is the system's *number of degrees of freedom*. Another possibility is that the kinematical equations are not solvable. In that case, there are too many constraints on the motion of the system. This means that no motion is possible – such a system is rigid.

In principle, it is possible to analyze the constrained motion of a system in terms of its displacements and angles of rotation. However, the occurrence of these angles as sines and cosines in component descriptions and in rotation transformations, as well as the complicated nature of the spatial geometry in many situations, combine to make it quite difficult to formulate and solve the associated kinematical equations. Furthermore, we will see in our later studies, beginning in Chapter 7, that some motion constraints restrict velocity, without any associated positional restrictions. For both reasons, our efforts here focus on the kinematical analysis of velocity and acceleration when the system is at a given position. In Chapter 8 we will see that such an analysis can be used to obtain differential equations whose solution will be the position variables as a function of time.

### 4.3 Interconnections and Linkages

189




Figure 4.8. Spatial motion of a bar subject to constraints.

To demonstrate these matters, consider bar  $AB$  in Fig. 4.8, which is constrained by collars that follow noncoplanar guide bars  $CD$  and  $EF$ . The connection at collar  $A$  is a ball-and-socket joint, whereas the one at collar  $B$  is a pin. Because points  $A$  and  $B$  are part of the same rigid body, their velocities are related by

$$\bar{v}_A = \bar{v}_B + \bar{\omega} \times \bar{r}_{A/B}. \quad (4.3.11)$$

We next address the constraint conditions associated with the connections. Because the guide bars are fixed, velocity constraint equations (4.3.7) state that

$$\bar{v}_A = v_A \bar{e}_{E/F}, \quad \bar{v}_B = v_B \bar{e}_{D/C}, \quad (4.3.12)$$

where positive values of  $v_A$  and  $v_B$  indicate that the respective velocities are taken to be downward and to the right. (If the actual sense of each motion is contrary to the assumed one, then the associated rate will be negative.) Let us for the moment ignore the constraint on the rotation of bar  $AB$  that is introduced by the pin on collar  $B$ . Then the angular velocity of the bar is an unknown  $\bar{\omega}_{AB}$  having three components. Equation (4.3.11) reduces to three scalar equations, one for each component, and there are five unknowns:  $v_A$ ,  $v_B$ , and the three components of  $\bar{\omega}_{AB}$ . (It is assumed that we have worked out whatever geometrical relations are required to describe distances and angles, so there are no unknown positional parameters.)

To further characterize the system, we need to account for the rotational constraint on  $\bar{\omega}_{AB}$  imposed by having a pin at collar  $B$ , which is described by Eq. (4.3.9). (This assumes that guide bar  $CD$  has a round cross section.) The guide bar is fixed, so it serves as the precession axis for rotation  $\psi$ , which equivalently is the angle by which plane  $ABC$  has rotated away from vertical. Thus the precession direction is  $\bar{k}_1 \equiv \bar{e}_{C/D}$ , based on the sense with which  $\psi$  is depicted in Fig. 4.8. In addition, the angle  $\theta$  between bar  $AB$  and guide bar  $CD$  is equivalent to the angle of rotation about the axis of the pin, which is assumed to be perpendicular to the plane containing  $AB$  and  $CD$ . We represent this direction with a cross product, with the sequence of terms based on the right-hand rule for when  $\theta$  increases:

$$\bar{j}_2 = \frac{\bar{e}_{C/D} \times \bar{r}_{A/B}}{|\bar{e}_{C/D} \times \bar{r}_{A/B}|}. \quad (4.3.13)$$

When we use Eq. (4.3.9) to describe the angular velocity of bar  $AB$ , we find that

$$\bar{\omega}_{AB} = \dot{\psi} \bar{e}_{C/D} + \dot{\theta} \frac{\bar{e}_{C/D} \times \bar{r}_{A/B}}{|\bar{e}_{C/D} \times \bar{r}_{A/B}|}. \quad (4.3.14)$$

This reduces the number of unknown scalars in  $\bar{\omega}_{AB}$  from three to two, thereby reducing the number of unknowns in the system to four:  $v_A$ ,  $v_B$ ,  $\dot{\psi}$ , and  $\dot{\theta}$ . Two possibilities arise now. In a fully constrained situation, the overall motion will be defined through some kinematical input, such as a specification of  $v_B$ , which removes the corresponding velocity parameter from the list of unknowns. In contrast, if the motion is induced by a given set of forces, so that none of the four kinematical parameters are specified, then the system is partially constrained. In that case, the three scalar equations obtained from Eq. (4.3.11) can be used to describe three of the unknowns in terms of the fourth. The system then has one degree of freedom, and kinetics principles would relate the remaining unknown to the force system.

A different condition of partial constraint is obtained when bar  $AB$  is connected to both collars by ball-and-socket joints, because Eq. (4.3.14) then does not apply. The lack of constraint in such a case is associated with the ability of bar  $AB$  to spin about its own axis. Such a rotation does not affect the motion of either collar. The kinematical equations therefore can be solved for a relation between  $v_A$  and  $v_B$ , although there will be no unique solution for  $\bar{\omega}_{AB}$ . If it is desired that the number of equations and unknowns match, one could consider the spin of bar  $AB$  about its own axis to be zero, in which case one may invoke Eq. (4.3.14).

Other conditions are possible. Suppose that bar  $AB$  was connected to both collars by pins. That would introduce another constraint on  $\bar{\omega}_{AB}$  having similar form to that of Eq. (4.3.14). It would not be possible to satisfy simultaneously both angular motion constraints, which would mean that the system is rigid. (The exception to this condition occurs if both guide bars are coplanar and the pins are perpendicular to that plane, in which case motion in that plane is possible.)

Thus far the discussion has only addressed the analysis of velocities. The treatment of acceleration follows a parallel development with the same logic as that by which the velocity was analyzed. It is essential to recognize that the velocities must be analyzed before accelerations can be addressed. One reason for this is that the angular velocities occur in the acceleration relation between two points in a body, Eq. (4.1.9). Also, angular accelerations in spatial motion contain terms that are the products of rotation rates. A third place where velocity parameters arise in an acceleration analysis is the characterization of the acceleration of a collar sliding along a curved bar, as was noted following Eqs. (4.3.7).


An area of special interest in kinematics is concerned with *linkages*, in which bars are interconnected sequentially in order to convert an input motion to a different output motion. From the standpoint of our general approach to rigid-body motion, the treatment of linkages presents no special problems. The constrained points in the system are the ends of the linkage, the connection points, and any point whose motion is specified. The velocity analysis is performed by using Eq. (4.1.8) to relate different connection points on each link. The linear velocity constraint equation appropriate to each connection is introduced into these relations between the velocity of points. Simultaneously, the angular velocity constraint equation associated with each connection is used to characterize the angular velocity of each link. In the special case of a robot, it is likely that the rotations about some or all of pins are controlled by servomotors, which remove these

### 4.3 Interconnections and Linkages

191


rotations from the list of unknowns. After the velocity analysis has been completed, one may carry out an acceleration analysis by following the same logic using the analogous acceleration equations. In comparison with the system in Fig. 4.8, the primary complication encountered in analyzing linkages is that the description of the position vectors and vector components is likely to be more difficult.

**EXAMPLE 4.3** Collar  $B$  is pinned to arm  $AB$  as it slides over a circular guide bar. The guide bar translates to the left such that the distance from pivot  $A$  to the center  $C$  is an arbitrary function of time  $u(t)$ . Derive expressions for the angular velocity and angular acceleration of arm  $AB$  in terms of  $u$ .



Example 4.3

**SOLUTION** Although we have focused on three-dimensional motion, this example demonstrates that the procedures work equally well for planar problems. We begin with a sketch depicting the global  $XYZ$  coordinate system and the basic features of the geometrical configuration.



Coordinate systems and unit vectors for the planar linkage

The law of cosines gives expressions for the angles locating collar  $B$ :

$$\theta = \cos^{-1} \left( \frac{u^2 + R^2 - L^2}{2uR} \right), \quad \beta = \cos^{-1} \left( \frac{u^2 + L^2 - R^2}{2uL} \right) \quad (1)$$

These relations are valid at any instant so we could differentiate them to obtain relations for  $\dot{\theta}$  and  $\dot{\beta}$ , and then  $\ddot{\theta}$  and  $\ddot{\beta}$ . Such a procedure exemplifies a procedure for analyzing linkages based on describing the position of constrained points at an arbitrary instant and then differentiating such expressions. The geometrical complexity of many linkages often makes such an approach too difficult to implement.

Our general approach does not require differentiation of position vectors, because it recognizes that the kinematical relations for velocity and acceleration

represent standard derivatives of position. Guide bar  $CD$  forms a translating reference frame for the collar's motion whose translational velocity is  $\dot{u}$  to the left. The vectors  $\bar{e}_t$  and  $\bar{e}_n$  in the sketch are the path variable unit vectors for the motion of the collar relative to this reference frame, and we let  $v_{\text{rel}}$  denote the speed of this relative motion. We also know that the collar is pinned to bar  $AB$ . These two views of the velocity of the collar must match, so that

$$\bar{v}_B = \bar{v}_{CD} + v_{\text{rel}}\bar{e}_t = \bar{\omega}_{AB} \times \bar{r}_{B/A}.$$

Resolving the vectors into global components relative to  $XYZ$  leads to

$$\bar{v}_B = \dot{u}\bar{I} + v_{\text{rel}}(\sin\theta\bar{I} - \cos\theta\bar{J}) = (-\dot{\beta}\bar{K}) \times L(\cos\beta\bar{I} - \sin\beta\bar{J}). \quad (2)$$

We match like components:

$$\begin{aligned} \bar{v}_B \cdot \bar{I} &= \dot{u} + v_{\text{rel}}\sin\theta = -\dot{\beta}L\sin\beta, \\ \bar{v}_B \cdot \bar{J} &= -v_{\text{rel}}\cos\theta = -\dot{\beta}L\cos\beta. \end{aligned}$$

The solution of these component equations is

$$\begin{aligned} \dot{\beta} &= -\frac{\dot{u}\cos\theta}{L(\sin\beta\cos\theta + \cos\beta\sin\theta)} \equiv -\frac{\dot{u}}{L}\frac{\cos\theta}{\sin(\beta+\theta)}, \\ v_{\text{rel}} &= -\dot{u}\frac{\cos\beta}{\sin(\beta+\theta)}. \end{aligned} \quad (3)$$

Solution of Eqs. (1) gives the values of  $\beta$  and  $\theta$  as functions of  $u$ , so the first of Eqs. (3) gives the angular velocity of bar  $AB$  as an implicit function of  $u$  and  $\dot{u}$ .

The analysis of acceleration follows the same logical outline. We match the acceleration of the collar from the viewpoint of the translating bar  $CD$  to the acceleration based on the collar being attached to rotating bar  $AB$ . The translational acceleration is  $\ddot{u}\bar{I}$ , and the collar follows a circular path of radius  $R$  relative to bar  $CD$ , so we have

$$\bar{a}_B = \ddot{u}\bar{I} + \dot{v}_{\text{rel}}\bar{e}_t + \frac{v_{\text{rel}}^2}{R}\bar{e}_n = \bar{\alpha}_{AB} \times \bar{r}_{B/A} - \omega_{AB}^2\bar{r}_{B/A}.$$

We resolve all vectors into  $\bar{I}$  and  $\bar{J}$  components:

$$\begin{aligned} \bar{a}_B &= \ddot{u}\bar{I} + \dot{v}_{\text{rel}}(\sin\theta\bar{I} - \cos\theta\bar{J}) + \frac{v_{\text{rel}}^2}{R}(\cos\theta\bar{I} + \sin\theta\bar{J}) \\ &= (-\ddot{\beta}\bar{K}) \times L(\cos\beta\bar{I} - \sin\beta\bar{J}) - \dot{\beta}^2L(\cos\beta\bar{I} - \sin\beta\bar{J}). \end{aligned} \quad (4)$$

The component form of this relation is

$$\begin{aligned} \bar{a}_B \cdot \bar{I} &= \ddot{u} + \dot{v}_{\text{rel}}\sin\theta + \frac{v_{\text{rel}}^2}{R}\cos\theta = -\ddot{\beta}L\sin\beta - \dot{\beta}^2L\cos\beta, \\ \bar{a}_B \cdot \bar{J} &= -\dot{v}_{\text{rel}}\cos\theta + \frac{v_{\text{rel}}^2}{R}\sin\theta = -\ddot{\beta}L\cos\beta + \dot{\beta}^2L\sin\beta. \end{aligned} \quad (5)$$



### 4.3 Interconnections and Linkages

193

We eliminate  $\dot{v}_{\text{rel}}$  from these equations, which gives

$$\ddot{u} \cos \theta + \frac{v_{\text{rel}}^2}{R} = -\ddot{\beta} L (\sin \beta \cos \theta + \cos \beta \sin \theta) - \dot{\beta}^2 L (\cos \beta \cos \theta - \sin \beta \sin \theta).$$

The identities for the sine and cosine of the sum of two angles simplify this to

$$\ddot{\beta} = -\frac{\ddot{u} \cos \theta}{L \sin (\beta + \theta)} - \dot{\beta}^2 \cot (\beta + \theta) - \frac{v_{\text{rel}}^2}{RL \sin (\beta + \theta)}.$$


Equations (3) give the values of  $v_{\text{rel}}$  and  $\dot{\beta}$ , so the preceding becomes

$$\ddot{\beta} = -\frac{\ddot{u} \cos \theta}{L \sin (\beta + \theta)} - \frac{\dot{u}^2 (\cos \theta)^2 \cos (\beta + \theta)}{L^2 [\sin (\beta + \theta)]^3} - \frac{\dot{u}^2 (\cos \beta)^2}{RL [\sin (\beta + \theta)]^3}. \quad \triangleleft$$

Once again, because Eqs. (1) give  $\beta$  and  $\theta$  as functions of  $u$ , this result describes the angular acceleration of bar  $AB$  as an implicit function of  $u$ ,  $\dot{u}$ , and  $\ddot{u}$ .

Before we leave this example, it is useful to observe that the primary complication for the preceding analysis was the need to carry out algebraic and trigonometric manipulations. The analysis would have been much simpler if a specific value of  $u$  had been specified, because numerical values would have occurred instead.

**EXAMPLE 4.4** Arm  $AB$  is turned by a motor at a constant rate of 1800 rev/min. Cap  $B$  connects this bar to bar  $BC$  with a fork-and-clevis joint, and the cap is free to rotate about the  $AB$  axis. The connection between bar  $BC$  and collar  $C$  is a ball-and-socket joint. Determine the velocity and acceleration of collar  $C$  and the angular velocity and angular acceleration of bar  $BC$  when the system is in the position shown.



Example 4.4

**SOLUTION** This example applies the general procedures to a system that is sometimes referred to as a four-bar linkage: rotating arm  $AB$ , connecting rod  $BC$ , slider  $C$ , and the fixed guide bar for the slider. The process is readily extended to multiple links. The global coordinate system we use has a vertical  $Z$  axis, and  $Y$  is aligned

with the rotation axis of arm  $AB$ , with  $\bar{J}$  pointing rightward. We begin by expressing the constraints on the motion of the connection points. Point  $A$  is stationary, collar  $C$  follows a straight path parallel to the  $X$  axis at an unknown speed  $v_C$ , and cap  $B$  is attached to both arm  $AB$  and connecting rod  $CD$ . Thus we have

$$\begin{aligned}\bar{v}_B &= \bar{\omega}_{AB} \times \bar{r}_{B/A} = v_C \bar{I} + \bar{\omega}_{BC} \times \bar{r}_{B/C}, \\ \bar{a}_B &= \bar{\alpha}_{AB} \times \bar{r}_{B/A} + \bar{\omega}_{AB} \times (\bar{\omega}_{AB} \times \bar{r}_{B/A}) \\ &= \dot{v}_C \bar{I} + \bar{\alpha}_{BC} \times \bar{r}_{B/C} + \bar{\omega}_{BC} \times (\bar{\omega}_{BC} \times \bar{r}_{B/C}).\end{aligned}\quad (1)$$

The position vectors at the instant depicted in the diagram are

$$\begin{aligned}\bar{r}_{B/A} &= 0.3(-\sin 30^\circ \bar{I} + \cos 30^\circ \bar{K}) = -0.15 \bar{I} + 0.2598 \bar{K} \text{ m}, \\ \bar{r}_{B/C} &= -\left[0.75^2 - 0.4^2 - (0.3 \cos 30^\circ)^2\right]^{1/2} \bar{I} - 0.4 \bar{J} + 0.3 \cos 30^\circ \bar{K} \\ &= -0.5788 \bar{I} - 0.4 \bar{J} + 0.2598 \bar{K} \text{ m}.\end{aligned}\quad (2)$$

Next, we describe the constraints on angular motion. It is given that

$$\bar{\omega}_{AB} = 1800 \left( \frac{2\pi}{60} \right) (-\bar{J}) \text{ rad/s}, \quad \bar{\alpha}_{AB} = \bar{0}. \quad (3)$$

Cap  $C$  rotates at an unknown rate  $\dot{\psi}$  about axis  $AB$  relative to arm  $AB$ . Relative to the cap, the fork-and-clevis joint allows bar  $BC$  only to rotate at an unknown rate  $\dot{\theta}$  about the axis of that joint's pin. Thus we have

$$\bar{\omega}_{\text{cap}} = \bar{\omega}_{AB} + \dot{\psi} \bar{e}_{B/A}, \quad \bar{\omega}_{BC} = \bar{\omega}_{\text{cap}} + \dot{\theta} \bar{e}_{\text{pin}} = \bar{\omega}_{AB} + \dot{\psi} \bar{e}_{B/A} + \dot{\theta} \bar{e}_{\text{pin}}. \quad (4)$$

To describe the angular acceleration we observe that  $\bar{e}_{B/A}$  rotates at  $\bar{\omega}_{AB}$  while  $\bar{e}_{\text{pin}}$  rotates at  $\bar{\omega}_{\text{cap}}$ . Because  $\bar{\alpha}_{AB} = \bar{0}$ , we have

$$\bar{\alpha}_{BC} = \dot{\psi} \bar{e}_{B/A} + \dot{\psi} (\bar{\omega}_{AB} \times \bar{e}_{B/A}) + \ddot{\theta} \bar{e}_{\text{pin}} + \dot{\theta} (\bar{\omega}_{\text{cap}} \times \bar{e}_{\text{pin}}). \quad (5)$$

We obtain  $\bar{e}_{B/A}$  from  $\bar{r}_{B/A}$  and evaluate  $\bar{e}_{\text{pin}}$  as the normal to the plane formed by  $\bar{r}_{B/A}$  and  $\bar{r}_{B/C}$ , where both position vectors are given by Eqs. (2). Thus,

$$\begin{aligned}\bar{e}_{B/A} &= \frac{\bar{r}_{B/A}}{|\bar{r}_{B/A}|} = -0.5 \bar{I} + 0.866 \bar{K}, \\ \bar{e}_{\text{pin}} &= \frac{\bar{r}_{B/A} \times \bar{r}_{B/C}}{|\bar{r}_{B/A} \times \bar{r}_{B/C}|} = 0.6347 \bar{I} - 0.6804 \bar{J} + 0.3664 \bar{K}.\end{aligned}\quad (6)$$

Now that we have characterized the constraint conditions, we proceed to analyze the velocities. This will yield the unknown rotation rates, which we will need to know in order to evaluate the angular acceleration. The first of Eqs. (1) gives

$$\begin{aligned}\bar{v}_B &= (-60\pi \bar{J}) \times (-0.15 \bar{I} + 0.2598 \bar{K}) \\ &= v_C \bar{I} + [-60\pi \bar{J} + \dot{\psi} (-0.5 \bar{I} + 0.866 \bar{K}) + \dot{\theta} (0.6347 \bar{I} - 0.6804 \bar{J} \\ &\quad + 0.3664 \bar{K})] \times (-0.5788 \bar{I} - 0.4 \bar{J} + 0.2598 \bar{K}).\end{aligned}$$

### 4.3 Interconnections and Linkages

195

The component equations obtained from this vector equation are

$$\begin{aligned}\bar{v}_B \cdot \bar{I} &= -48.97 = v_C + 0.3464\dot{\psi} - 0.0302\dot{\theta} - 48.97, \\ \bar{v}_B \cdot \bar{J} &= 0 = -0.3713\dot{\psi} - 0.3770\dot{\theta}, \\ \bar{v}_B \cdot \bar{K} &= -28.27 = 0.200\dot{\psi} - 0.6477\dot{\theta} - 109.10.\end{aligned}$$

The solution of this set of linear equations is

$$v_C = -36.28 \text{ m/s}, \quad \dot{\psi} = 96.46 \text{ rad/s}, \quad \dot{\theta} = -95.01 \text{ rad/s}. \quad (7) \triangleleft$$

The corresponding angular velocity obtained from the second of Eqs. (4) is

$$\bar{\omega}_{BC} = -108.53\bar{I} - 123.86\bar{J} + 48.72\bar{K} \text{ rad/s}. \quad (8)$$

We may now proceed to analyze the acceleration. We begin by using the parameters obtained thus far to form  $\bar{\alpha}_{BC}$ . From the value of  $\dot{\psi}$  we know that

$$\bar{\omega}_{\text{cap}} = \bar{\omega}_{AB} + 96.45\bar{e}_{B/A} = -48.23\bar{I} - 188.50\bar{J} + 83.53\bar{K}.$$

We substitute into Eq. (5) this expression, the unit vectors in Eqs. (6), and the results for  $\dot{\psi}$  and  $\dot{\theta}$ , which gives

$$\begin{aligned}\bar{\alpha}_{BC} &= \ddot{\psi}\bar{e}_{B/A} + 96.45(\bar{\omega}_{AB} \times \bar{e}_{B/A}) + \ddot{\theta}\bar{e}_{\text{pin}} - 95.01(\bar{\omega}_{\text{cap}} \times \bar{e}_{\text{pin}}) \\ &= (-0.50\ddot{\psi} + 0.6347\ddot{\theta} - 14582)\bar{I} + (-0.6804\ddot{\theta} - 6716)\bar{J} \\ &\quad + (0.8660\ddot{\psi} + 0.3664\ddot{\theta} - 23575)\bar{K} \text{ rad/s}^2.\end{aligned} \quad (9)$$

Substitution of Eqs. (8) and (9), as well as the position vectors in Eqs. (2), into the second of Eqs. (1) governing the acceleration of cap  $B$  gives

$$\begin{aligned}\bar{a}_B &= (-60\pi\bar{J}) \times [(-60\pi\bar{J}) \times (-0.15\bar{I} + 0.2598\bar{K})] \\ &= \dot{v}_C\bar{I} + [(-0.50\ddot{\psi} + 0.6347\ddot{\theta} - 14582)\bar{I} + (-0.6804\ddot{\theta} - 6716)\bar{J} \\ &\quad + (0.8660\ddot{\psi} + 0.3664\ddot{\theta} - 23575)\bar{K}] \times (-0.5788\bar{I} - 0.4\bar{J} + 0.2598\bar{K}) \\ &\quad + (-108.53\bar{I} - 123.86\bar{J} + 48.72\bar{K}) \times [(-108.53\bar{I} - 123.86\bar{J} \\ &\quad + 48.72\bar{K}) \times (-0.5788\bar{I} - 0.4\bar{J} + 0.2598\bar{K})].\end{aligned}$$

The corresponding component equations are

$$\begin{aligned}\bar{a}_B \cdot \bar{I} &= 5330 = \dot{v}_C + 0.3464\ddot{\psi} - 0.0302\ddot{\theta} - 7673, \\ \bar{a}_B \cdot \bar{J} &= 0 = -0.3713\ddot{\psi} - 0.3770\ddot{\theta} + 13747, \\ \bar{a}_B \cdot \bar{K} &= -9231 = 0.200\ddot{\psi} - 0.6477\ddot{\theta} + 373.6,\end{aligned} \quad (10)$$

whose solution is


$$\dot{v}_C = 7813 \text{ m/s}, \quad \ddot{\psi} = 16722 \text{ rad/s}^2, \quad \ddot{\theta} = 19994 \text{ rad/s}^2. \quad \triangleleft$$

The angular acceleration corresponding to these acceleration rates is

$$\bar{\alpha}_{BC} = (-10.253\bar{I} + 20.319\bar{J} - 1.77\bar{K}) (10^3) \text{ rad/s}^2. \quad \triangleleft$$

In closing, it should be noted that the operations we performed are readily implemented in mathematical software.

**EXAMPLE 4.5** The *cardan joint* depicted in the sketch is used to connect shafts that intersect, but are not collinear. The angle between the shafts is  $\beta$ , and the respective rotation rates are  $\dot{\phi}_1$  and  $\dot{\phi}_2$ . The cross-link  $OABCD$  connecting the shafts is able to rotate about axis  $CD$  relative to shaft 1, and about axis  $AB$  relative to shaft 2. In effect, each shaft is terminated by a fork-and-clevis joint, with the cross-link being the clevis for both forks. Derive an expression for the rotation rate  $\dot{\phi}_2$  in terms of the instantaneous values of  $\phi_1$  and  $\dot{\phi}_1$ . Also determine the corresponding angular velocity of the cross-link.



Example 4.5

**SOLUTION** The analysis of this seemingly simple device actually will bring to the fore many of the concepts in both this chapter and the previous one. Thus this example will give a broader perspective of the procedures for characterizing the kinematics of connections. There are a variety of approaches for establishing the relation between  $\phi_2$  and  $\phi_1$ . The first is quite direct. It is founded on the fact that arm  $AB$  is perpendicular to arm  $CD$ , so that  $\bar{e}_{B/A} \cdot \bar{e}_{D/C} = 0$ .

The  $X_j$  axes depicted in the sketch are aligned with the respective shafts, and both  $Z_j$  axes are perpendicular to the plane containing the shafts. At an arbitrary instant  $\bar{e}_{D/C}$  lies in the  $Y_1 Z_1$  plane at angle  $\phi_1$  below the  $Y_1$  axis, and  $\bar{e}_{B/A}$  is in the

### 4.3 Interconnections and Linkages

197

$Y_2Z_2$  plane at angle  $\phi_2$  from the  $Z_2$  axis. Thus,

$$\bar{e}_{D/C} = \cos \phi_1 \bar{J}_1 - \sin \phi_1 \bar{K}_1, \quad \bar{e}_{B/A} = \sin \phi_2 \bar{J}_2 + \cos \phi_2 \bar{K}_2. \quad (1)$$

Because both coordinate systems share the same  $Z$  axis it must be that  $Y_2$  lies in the  $X_1Y_1$  plane so that

$$\bar{J}_2 = \sin \beta \bar{I} + \cos \beta \bar{J}.$$

It follows that

$$\bar{e}_{B/A} = \sin \phi_2 (\sin \beta \bar{I}_1 + \cos \beta \bar{J}_1) + \cos \phi_2 \bar{K}_1. \quad (2)$$

Setting the dot product of the unit vectors to zero yields

$$\bar{e}_{B/A} \cdot \bar{e}_{D/C} = \sin \phi_2 \cos \beta \cos \phi_1 - \cos \phi_2 \sin \phi_1 = 0,$$

which may be rewritten as

$$\tan \phi_2 = \frac{\tan \phi_1}{\cos \beta}. \quad (3)$$

Because this is a general relation between the angles, it may be differentiated with respect to time to obtain a relation between the rotation rates. Thus

$$\dot{\phi}_2 \frac{1}{(\cos \phi_2)^2} = \dot{\phi}_1 \frac{1}{\cos \beta (\cos \phi_1)^2}.$$

To remove the dependence on  $\phi_2$ , we employ Eq. (3) in conjunction with the identity that  $(\cos \phi_2)^2 = 1 / [1 + (\tan \phi_2)^2]$ . The result is

$$\dot{\phi}_2 = \dot{\phi}_1 \frac{\cos \beta}{(\sin \phi_1)^2 + (\cos \beta \cos \phi_1)^2}. \quad (4) <$$

This derivation does not examine the nature of the constraints imposed on the rotation of the cross-link, and therefore does not address the angular velocity of the cross-link. To determine that quantity we pursue an alternative analysis, which also will lead to Eqs. (3) and (4). If we consider the cross-link to be connected to the first shaft, we would say that the cross-link rotates through angle  $\phi_1$  together with that shaft about the negative  $X_1$  axis, and it also rotates relative to that shaft about  $\bar{e}_{D/C}$  by an unknown angle  $\theta_1$ . The  $\phi_1$  rotation is a precession (rotation about a fixed axis), whereas  $\theta_2$  is a nutation, with  $\bar{e}_{D/C}$  being the line of nodes. Similarly, from the perspective of shaft 2,  $\phi_2$  is the precession about the negative  $X_2$  axis, and unknown angle  $\theta_2$  is the nutation about the line of nodes defined by  $\bar{e}_{B/A}$ .

Because the legs of the cross-link are orthogonal, we may consider them to represent a rotating coordinate system. Let  $\bar{e}_{D/C} = \bar{j}$  and  $\bar{e}_{B/A} = \bar{k}$ . The alternative viewpoints enables us to derive two rotation transformations from components

relative to the fixed directions to  $\bar{i}\bar{j}\bar{k}$  components. For shaft 1 we have a pair of body-fixed rotations  $-\phi_1$  about the  $X_1$  axis, followed by  $\theta_1$  about the  $y$  axis, so that

$$\begin{aligned} \begin{Bmatrix} \bar{i} \\ \bar{j} \\ \bar{k} \end{Bmatrix} &= \begin{bmatrix} \cos \theta_1 & 0 & -\sin \theta_1 \\ 0 & 1 & 0 \\ \sin \theta_1 & 0 & \cos \theta_1 \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \phi_1 & -\sin \phi_1 \\ 0 & \sin \phi_1 & \cos \phi_1 \end{bmatrix} \begin{Bmatrix} \bar{I}_1 \\ \bar{J}_1 \\ \bar{K}_1 \end{Bmatrix} \\ &= \begin{bmatrix} \cos \theta_1 & -\sin \theta_1 \sin \phi_1 & -\sin \theta_1 \cos \phi_1 \\ 0 & \cos \phi_1 & -\sin \phi_1 \\ \sin \theta_1 & \cos \theta_1 \sin \phi_1 & \cos \theta_1 \cos \phi_1 \end{bmatrix} \begin{Bmatrix} \bar{I}_1 \\ \bar{J}_1 \\ \bar{K}_1 \end{Bmatrix}. \end{aligned} \quad (5)$$

From the perspective of shaft 2, the body-fixed rotations are  $-\phi_2$  about the  $X_2$  axis, followed by  $\theta_2$  about the  $z$  axis, so

$$\begin{aligned} \begin{Bmatrix} \bar{i} \\ \bar{j} \\ \bar{k} \end{Bmatrix} &= \begin{bmatrix} \cos \theta_2 & \sin \theta_2 & 0 \\ -\sin \theta_2 & \cos \theta_2 & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \phi_2 & -\sin \phi_2 \\ 0 & \sin \phi_2 & \cos \phi_2 \end{bmatrix} \begin{Bmatrix} \bar{I}_2 \\ \bar{J}_2 \\ \bar{K}_2 \end{Bmatrix} \\ &= \begin{bmatrix} \cos \theta_2 & \sin \theta_2 \cos \phi_2 & -\sin \theta_2 \sin \phi_2 \\ -\sin \theta_2 & \cos \theta_2 \cos \phi_2 & -\cos \theta_2 \sin \phi_2 \\ 0 & \sin \phi_2 & \cos \phi_2 \end{bmatrix} \begin{Bmatrix} \bar{I}_2 \\ \bar{J}_2 \\ \bar{K}_2 \end{Bmatrix}. \end{aligned} \quad (6)$$

Because the  $Z_1$  and  $Z_2$  axes coincide, the rotation transformation between the fixed coordinate systems is

$$\begin{Bmatrix} \bar{I}_2 \\ \bar{J}_2 \\ \bar{K}_2 \end{Bmatrix} = \begin{bmatrix} \cos \beta & -\sin \beta & 0 \\ \sin \beta & \cos \beta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{Bmatrix} \bar{I}_1 \\ \bar{J}_1 \\ \bar{K}_1 \end{Bmatrix}. \quad (7)$$

Substituting this transformation into Eq. (6) leads to a transformation from  $\bar{I}_1\bar{J}_1\bar{K}_1$  components to  $\bar{i}\bar{j}\bar{k}$  components. Matching it to Eq. (5) requires that

$$\begin{aligned} \begin{bmatrix} \cos \theta_2 & \sin \theta_2 \cos \phi_2 & -\sin \theta_2 \sin \phi_2 \\ -\sin \theta_2 & \cos \theta_2 \cos \phi_2 & -\cos \theta_2 \sin \phi_2 \\ 0 & \sin \phi_2 & \cos \phi_2 \end{bmatrix} \begin{bmatrix} \cos \beta & -\sin \beta & 0 \\ \sin \beta & \cos \beta & 0 \\ 0 & 0 & 1 \end{bmatrix} \\ = \begin{bmatrix} \cos \theta_1 & -\sin \theta_1 \sin \phi_1 & -\sin \theta_1 \cos \phi_1 \\ 0 & \cos \phi_1 & -\sin \phi_1 \\ \sin \theta_1 & \cos \theta_1 \sin \phi_1 & \cos \theta_1 \cos \phi_1 \end{bmatrix}. \end{aligned}$$

### 4.3 Interconnections and Linkages

199

Although there are nine elements to match in the preceding equation, the orthonormal property leads to six identities, so only three elements are independent. The simplest equations come from the last row, specifically

$$\begin{aligned} (3, 1) : \sin \phi_2 \sin \beta &= \sin \theta_1, \\ (3, 2) : \sin \phi_2 \cos \beta &= \cos \theta_1 \sin \phi_1, \\ (3, 3) : \cos \phi_2 &= \cos \theta_1 \cos \phi_1. \end{aligned} \quad (8)$$

These are three equations for  $\theta_1$ ,  $\theta_2$ , and  $\phi_2$  in terms of  $\phi_1$ . The ratio of the second to the third gives

$$\tan \phi_2 \cos \beta = \tan \phi_1, \quad (3')$$

which is the same as the relation obtained in the first derivation.

The analysis leading to this relation was less direct than the procedure by which it was derived in the first analysis. However, pursuing it enables us to recognize how the cross-link rotates. In fact, once we have evaluated  $\phi_2$  corresponding to a specified value of  $\phi_1$ , the first two of Eqs. (8) can be solved for  $\theta_1$  and  $\theta_2$ .

Just as there are two viewpoints for the orientation of the cross-link, the angular velocity can be formulated from alternative perspectives. For shaft 1 the precession rate is  $-\dot{\phi}_1$  about the  $X_1$  axis and the nutation rate is  $\dot{\theta}_1$  in the direction of  $\bar{e}_{D/C}$ , so the angular velocity of the cross-link is

$$\bar{\omega} = -\dot{\phi}_1 \bar{I}_1 + \dot{\theta}_1 \bar{e}_{D/C}. \quad (9)$$

For shaft 2 the precession rate is  $-\dot{\phi}_2$  about the  $X_2$  axis and the nutation rate is  $\dot{\theta}_2$  in the direction  $\bar{e}_{B/A}$ . This leads to a description of the angular velocity as

$$\bar{\omega} = -\dot{\phi}_2 \bar{I}_2 + \dot{\theta}_2 \bar{e}_{B/A}. \quad (10)$$

Matching Eqs. (9) and (10) leads to three scalar component equations for the values of  $\dot{\theta}_1$ ,  $\dot{\theta}_2$ , and  $\dot{\phi}_2$  in terms of  $\dot{\phi}_1$ . The most direct set of equations for further manipulation is obtained by taking components in the mutually orthogonal directions  $\bar{e}_{D/C}$ ,  $\bar{e}_{B/A}$ , and  $\bar{e}_{D/C} \times \bar{e}_{B/A}$ . Because  $\bar{e}_{D/C}$  is perpendicular to the  $X_1$  axis and  $\bar{e}_{B/A}$  is perpendicular to the  $X_2$  axis, we have

$$\begin{aligned} \bar{\omega} \cdot \bar{e}_{D/C} &= \dot{\theta}_1 = -\dot{\phi}_2 \bar{I}_2 \cdot \bar{e}_{D/C}, \\ \bar{\omega} \cdot \bar{e}_{B/A} &= -\dot{\phi}_1 \bar{I}_1 \cdot \bar{e}_{B/A} = \dot{\theta}_2, \end{aligned} \quad (11)$$

$$\bar{\omega} \cdot (\bar{e}_{D/C} \times \bar{e}_{B/A}) = -\dot{\phi}_1 \bar{I}_1 \cdot (\bar{e}_{D/C} \times \bar{e}_{B/A}) = -\dot{\phi}_2 \bar{I}_2 \cdot (\bar{e}_{D/C} \times \bar{e}_{B/A}).$$

To evaluate these terms we express the unit vectors in  $\bar{I}_1 \bar{J}_1 \bar{K}_1$  components. Equations (1) and (2) describe  $\bar{e}_{D/C}$  and  $\bar{e}_{B/A}$ , and the first row of the rotation transformation in Eq. (7) shows that  $\bar{I}_2$  is

$$\bar{I}_2 = \cos \beta \bar{I}_1 - \sin \beta \bar{J}_1.$$

The result of substitution of these representations of the unit vectors into Eqs. (11) is

$$\begin{aligned}
 \dot{\theta}_1 &= -\dot{\phi}_2 \cos \beta \cos \phi_1, \\
 -\dot{\phi}_1 \sin \phi_2 \sin \beta &= \dot{\theta}_2, \\
 -\dot{\phi}_1 (\cos \phi_1 \cos \phi_2 + \sin \phi_1 \sin \phi_2 \cos \beta) \\
 &= -\dot{\phi}_2 [\cos \beta (\cos \phi_1 \cos \phi_2 + \sin \phi_1 \sin \phi_2 \cos \beta) \\
 &\quad - \sin \beta (-\sin \phi_1 \sin \phi_2 \sin \beta)] \\
 &\equiv -\dot{\phi}_2 (\cos \beta \cos \phi_1 \cos \phi_2 + \sin \phi_1 \sin \phi_2).
 \end{aligned} \tag{12}$$

Dividing the last of these equations by  $\cos \phi_1 \cos \phi_2$  gives

$$\dot{\phi}_2 (\cos \beta + \tan \phi_1 \tan \phi_2) = \dot{\phi}_1 (1 + \tan \phi_1 \tan \phi_2 \cos \beta).$$


We can eliminate the dependence on  $\phi_2$  by using Eq. (3'). Further manipulation by use of  $\tan \phi_1 \equiv \sin \phi_1 / \cos \phi_1$  shows that this relation for  $\dot{\phi}_2$  is identical to Eq. (4). Once the value of  $\dot{\phi}_2$  has been determined, the first of Eqs. (12) gives the corresponding value of  $\dot{\theta}_1$ . Substitution of that result and Eqs. (1) into Eq. (9) gives

$$\bar{\omega} = -\dot{\phi}_1 \left[ \bar{I}_1 + \frac{(\cos \beta)^2 \cos \phi_1}{(\sin \phi_1)^2 + (\cos \beta \cos \phi_1)^2} (\cos \phi_1 \bar{J}_1 - \sin \phi_1 \bar{K}_1) \right]. \quad \triangleleft$$

It is interesting to observe that the maximum value of  $\dot{\phi}_2$  is  $\dot{\phi}_1 / \cos \beta$  at  $\phi_1 = 0$  and  $\pi$ , whereas the minimum value of  $\dot{\phi}_2$  is  $\dot{\phi}_1 \cos \beta$  at  $\phi_2 = 0$  and  $3\pi/2$ . This oscillation relative to the input speed  $\dot{\phi}_1$  makes the cardan joint by itself unsuitable as a constant-velocity joint. In conventional front-engine, rear-wheel-drive automobiles, two cardan joints are employed in the drive train in opposition. The reciprocal arrangement produces a final speed that matches the input.

#### 4.4 ROLLING

When two bodies contact each other, one kinematical condition is that they not penetrate each other. In rolling motion, the contacting surfaces have no corners, so the surfaces share an identifiable tangential contact plane. Figure 4.9 shows two surfaces in contact, as viewed edgewise along their plane of contact. The  $z$  axis in the figure is



**Figure 4.9.** Equal-arc-length rule for rolling without slipping.



#### 4.4 Rolling

201

defined to be normal to the plane of contact. Because the surface of each body is impenetrable, the velocity components normal to the contact plane must match. Let  $C1$  and  $C2$  be contacting points on each body. Then

$$\bar{v}_{C1} \cdot \bar{k} = \bar{v}_{C2} \cdot \bar{k}. \quad (4.4.1)$$

The special case of *rolling without slipping* imposes an additional constraint associated with the condition that the contacting surfaces have no relative motion parallel to the contact plane. One way of characterizing this condition is to consider arc lengths on the perimeter of each body. In Fig. 4.9 points  $B1$  and  $B2$  were the points of contact at an earlier instant. The absence of slipping means that the arc length  $s_1$  along the perimeter of body 1 between points  $B1$  and  $C1$  is the same as the arc length  $s_2$  along body 2 between points  $B2$  and  $C2$ .

We restrict our attention to situations in which the rolling bodies are circular, because the round shape makes it substantially simpler to perform a kinematical analysis. For example, arc lengths are measured along circles or flat surfaces. Describing the arc-length constraint imposed by the absence of slippage leads to a description of the position of points in the rolling bodies. The most common application of this approach is a wheel rolling along the ground. The path followed by a point on the circumference of the wheel is a *cycloid*. The geometrical parameters needed to characterize this path are depicted in Fig. 4.10.




Figure 4.10. Rolling of a wheel on a flat surface.

Point  $A$  on the cylinder contacted the ground initially, at which position the center of the wheel was at the origin  $O$  of the fixed  $XYZ$  reference frame. Point  $B$  is the current contact point, so the horizontal distance  $x$  from point  $O$  to the center of the wheel equals the arc length along the ground between the initial and the current contact points. When there is no slippage, the arc length between points  $A$  and  $B$  on the wheel is the same as  $x$ , which gives a relation for the angle by which the wheel rotates:


$$x = R\theta. \quad (4.4.2)$$

Thus the position of point  $A$  is described in parametric form as a function of  $\theta$  according to

$$\bar{r}_{A/O} = X\bar{i} + Y\bar{j}, \quad X = R(\theta - \sin \theta), \quad Y = -R\cos \theta, \quad (4.4.3)$$

which is the parametric description of a cycloid depicted in Fig. 4.11.

In addition to enabling us to describe the path followed by a point on the perimeter of the wheel, the circular shape makes it easy to describe the motion of the wheel's



**Figure 4.11.** Cycloidal path followed by a point on the perimeter of a wheel rolling without slipping over a flat surface.

center. Such knowledge may be used to obtain expressions for the velocity and acceleration of a point on the wheel's perimeter. The center point in Fig. 4.10 follows a straight path, and  $x$  is the distance traveled. Thus the speed of the center is  $v = \dot{x} = R\dot{\theta}$ . We use this expression to eliminate the angular velocity when we take the time derivative of Eqs. (4.4.3), which leads to expressions for the velocity and acceleration of an arbitrary point on the perimeter of a wheel:

$$\begin{aligned}\bar{v}_A &= v(1 - \cos \theta)\bar{i} + v \sin \theta \bar{j}, \\ \bar{a}_A &= \left[ \dot{v}(1 - \cos \theta) + \frac{v^2}{R} \sin \theta \right] \bar{i} + \left( \dot{v} \sin \theta + \frac{v^2}{R} \cos \theta \right) \bar{j}.\end{aligned}\quad (4.4.4)$$

An aspect of the velocity and acceleration of particular relevance to further developments arises at  $\theta = 0$ , at which position  $\bar{v}_A = \bar{0}$  and  $\bar{a}_A = (v^2/R)\bar{j}$ . In other words, a point on the perimeter of a wheel comes to rest when it comes in contact with the ground, and its acceleration is upward at that instant. This corresponds to the cusp in the cycloidal path.

One difficulty with a formulation in terms of arc lengths is that it becomes increasingly difficult to use as the complexity of the motion increases. This is particularly true for spatial motion. We therefore develop an alternative method in which constraint conditions on velocity and acceleration are formulated. Consider the limiting situation in which the points of contact  $B_i$  and  $C_i$  in Fig. 4.9 correspond to instants that are very close. The points of contact on each body then seem to have the same displacement along the contact plane. Dividing this displacement by the small time interval shows that the tangential velocity components must be the same. Because the contact condition between the bodies requires that the normal velocity components are equal, it must be that


The velocities of contacting points of bodies that roll over each other without slipping must match in all directions. The constraint condition is

$$\bar{v}_{C1} = \bar{v}_{C2} \text{ for no slipping.} \quad (4.4.5)$$

Acceleration is more complicated because the contacting points on each body come together and then separate. This means that they have different accelerations in the normal direction. A common misconception arises from the case of the rolling wheel in Fig. 4.10, as well as other planar situations. As was noted after Eqs. (4.4.4), the acceleration of a point on the perimeter of a wheel in planar motion is upward when the

#### 4.4 Rolling

203




**Figure 4.12.** Acceleration of contact points on two spheres that have no relative slip as they rotate about fixed axes.

point comes in contact with the ground. This is often incorrectly interpreted to mean that, in all situations of rolling without slipping, the contact points may accelerate relative to each other only perpendicularly to the contact plane. This cannot be assumed to be true in spatial motion, as may be recognized by considering a simple case. In Fig. 4.12, two spheres rotate at constant rates  $\omega_1$  and  $\omega_2$  about fixed parallel axes, such that there is no slipping between the contacting points  $A$  and  $B$ . The plane of contact is  $xy$ . Points on each sphere follow circular paths in the horizontal plane whose radii are  $\rho_1 = r_1 d / (r_1 + r_2)$  and  $\rho_2 = r_2 d / (r_1 + r_2)$ . The tangent direction of the paths followed by points  $A$  and  $B$  at the contact location are  $(\bar{e}_t)_A = (\bar{e}_t)_B = -\bar{j}$ , so the no-slip velocity condition that  $\bar{v}_A = \bar{v}_B$  is satisfied if  $\omega_2 / \omega_1 = r_1 / r_2$ . For constant rotation rate, each point's acceleration is solely centripetal, being  $a_A = \rho_1 \omega_1^2$  and  $a_B = \rho_2 \omega_2^2$  in the horizontal directions displayed in the figure. It is apparent that  $\bar{a}_A \cdot \bar{i} \neq \bar{a}_B \cdot \bar{i}$ , so the acceleration components parallel to the  $xy$  plane do not match. This demonstrates that contact points on rolling bodies can have different accelerations parallel to the contact plane, as well as perpendicularly to it.

The lack of a direct constraint condition for the acceleration presents a dilemma. We remedy it by recalling that we have limited our attention to rolling bodies that are round in some sense. For such bodies the distance from the center to the point of contact on each rolling body is constant. This constancy leads to a velocity constraint condition that may be differentiated, thereby yielding to the additional kinematical conditions required for analyzing acceleration. In effect, in addition to considering kinematical conditions at the points of contact, we *consider the center point to be subject to a kinematical constraint that must be identified.*

To explore this idea, consider the planar situation of a planetary gear rolling over a sun gear. In Fig. 4.13,  $\omega_2$  is the angular speed of the sun gear,  $v_A$  is the speed of the center of the planetary gear, and  $\omega_1$  is the angular speed of that gear. Because the distance from the center  $A$  of the planetary gear to the point of contact  $C$  is constant, point  $A$  follows a circular path of radius  $r_1 + r_2$ . Thus, for the  $xyz$  coordinate system depicted in the figure, the velocity and acceleration of point  $A$  are described according to path variables as

$$\bar{v}_A = v_A \bar{i}, \quad \bar{a}_A = \dot{v}_A \bar{i} - \frac{v_A^2}{r_1 + r_2} \bar{j} \quad (4.4.6)$$



**Figure 4.13.** Rolling without slipping of a planetary gear over a fixed inner gear.

In addition, for planar motion we know that  $\bar{\omega}_1 = -\omega_1 \bar{k}$  and  $\bar{\omega}_2 = -\omega_2 \bar{k}$ . Because there is no slipping at point  $C$ , the velocity constraint requires that  $\bar{v}_C = \omega_2 r_2 \bar{i}$  be the same for both gears. Using this to construct the velocity of center  $A$  gives

$$\bar{v}_A = \bar{v}_C + \bar{\omega}_1 \times \bar{r}_{A/C} = (\omega_2 r_2 + \omega_1 r_1) \bar{i}. \quad (4.4.7)$$

The descriptions of  $\bar{v}_A$  in Eqs. (4.4.6) and (4.4.7) agree in direction. Matching the speeds in these two equations leads to


$$v_A = \omega_2 r_2 + \omega_1 r_1. \quad (4.4.8)$$

To obtain a kinematical constraint on acceleration, we recognize that the round shape of the gears and the fact that the path followed by point  $A$  is circular make the preceding relation valid at any instant. Consequently, we may differentiate it with respect to time. Doing so yields

$$\dot{v}_A = \dot{\omega}_2 r_2 + \dot{\omega}_1 r_1. \quad (4.4.9)$$

Equations (4.4.8) and (4.4.9) are constraint equations relating the three rate variables. This enables us to describe the velocity and acceleration of the center point  $A$ , as well as the angular velocity and angular acceleration of the planetary gear, in terms of the two rate variables we choose to retain. From such knowledge we can determine the velocity and acceleration of any other point on the planetary gear in terms of those variables.

The same approach may be extended directly to cases of spatial motion. A relative simple situation is that of steady precession of a disk that rolls along the ground, as depicted by the side view in Fig. 4.14. The inclination angle  $\beta$  is constant, as is the



**Figure 4.14.** Steady precession of a rolling disk.

#### 4.4 Rolling

205

precession rate  $\dot{\psi}$ . In this case the center point follows a circular path of radius  $\rho$ , so the velocity and acceleration of the center of the disk are

$$\bar{v}_A = \rho \dot{\psi} \bar{j}', \quad \bar{a}_A = \rho \dot{\psi}^2 (-\cos \beta \bar{i}' + \sin \beta \bar{k}'), \quad (4.4.10)$$

where  $x'y'z'$  is a coordinate system that precesses with its origin at the center of the disk. The angular velocity and acceleration of the disk are given by

$$\begin{aligned} \bar{\omega} &= \dot{\psi} \bar{e}_1 + \dot{\phi} \bar{e}_2 = (\dot{\psi} \sin \beta - \dot{\phi}) \bar{i}' + \dot{\psi} \cos \beta \bar{k}', \\ \bar{\alpha} &= \dot{\phi} (\bar{\omega} \times \bar{e}_2) = -\dot{\psi} \dot{\phi} \cos \beta \bar{j}'. \end{aligned} \quad (4.4.11)$$

The preceding assumes that  $\dot{\phi}$  is constant, which is something we will verify. This rate is not yet known, but we have not imposed the condition that there is no slippage at the contact point  $C$ . Because  $\bar{v}_C = \bar{0}$ , the velocity of the center of the disk is  $\bar{\omega} \times \bar{r}_{A/C}$ . Equating this to the expression for  $\bar{v}_A$  corresponding to circular motion leads to

$$\bar{v}_A = \rho \dot{\psi} \bar{j}' = \bar{\omega} \times R \bar{k}' = (\dot{\psi} \sin \beta - \dot{\phi}) R \bar{j}'. \quad (4.4.12)$$


Matching the  $\bar{j}'$  components yields

$$\dot{\phi} = \left( \sin \beta - \frac{\rho}{R} \right) \dot{\psi}. \quad (4.4.13)$$

Because  $\beta$  and  $\rho$  are constant, this expression shows that  $\dot{\phi}$  is proportional to  $\dot{\psi}$ , which confirms our assumption that  $\ddot{\phi}$  is zero. Substitution of  $\dot{\phi}$  into Eqs. (4.4.11) gives

$$\bar{\omega} = \dot{\psi} \left( \frac{\rho}{R} \bar{i}' + \cos \beta \bar{k}' \right), \quad \bar{\alpha} = -\dot{\psi}^2 \left( \sin \beta - \frac{\rho}{R} \right) \cos \beta \bar{j}'. \quad (4.4.14)$$

Equations (4.4.10) and (4.4.14) show that knowledge of the Eulerian angles is sufficient to characterize the motion of the center, as well as the angular motion, of a rolling disk in the steady precession case. The same is true for unsteady motion, in which the spin rate is not proportional to the precession rate. The analysis is more difficult, but it still uses the basic concept that the center is a constrained point whose velocity may be described in a general manner by relating it to the contact point on the disk. Figure 4.15 depicts a disk that is rolling without slipping over a flat surface in a wobbly manner. We use Eulerian angles to represent the orientation of the disk, with precession angle  $\psi$  measured about the upward vertical  $\bar{e}_1$  and nutation  $\theta$  measured from the vertical to the center line of the disk. The line of nodes is the  $y'$  axis, which is defined to be the



**Figure 4.15.** Unsteady rolling without slipping of a disk on a flat surface.

horizontal diameter of the disk. Body-fixed  $xyz$  axes execute a spin  $\phi$  about the  $z'$  axis relative to  $x'y'z'$ .

The importance of the round shape in this case is that, if all other quantities are held fixed, the motion of the system will not be altered by changing  $\phi$ . As a consequence of this invariance, a description of the velocity of the center of disk in terms of  $\bar{i}'\bar{j}'\bar{k}'$  components, with the Eulerian angles represented algebraically, will be valid at any instant. Such a representation may be differentiated to analyze acceleration. In terms of the Eulerian angles the angular velocities  $\bar{\Omega}'$  of  $x'y'z'$  and  $\bar{\omega}$  of  $xyz$  are

$$\begin{aligned}\bar{\Omega}' &= \dot{\psi}\bar{e}_1 + \dot{\theta}\bar{j}' = -\dot{\psi}\sin\theta\bar{i}' + \dot{\theta}\bar{j}' + \dot{\psi}\cos\theta\bar{k}', \\ \bar{\omega} &= \bar{\Omega}' + \dot{\phi}\bar{k}' = -\dot{\psi}\sin\theta\bar{i}' + \dot{\theta}\bar{j}' + (\dot{\phi} + \dot{\psi}\cos\theta)\bar{k}'.\end{aligned}\quad (4.4.15)$$

At point  $C$ , where the disk comes in contact with the ground, the no-slip condition requires that  $\bar{v}_C = \bar{0}$ . Thus the velocity of the center  $A$  must be

$$\bar{v}_A = \bar{\omega} \times \bar{r}_{A/C} = -R(\dot{\phi} + \dot{\psi}\cos\theta)\bar{j}' + R\dot{\theta}\bar{k}'. \quad (4.4.16)$$

This is a general relation for  $\bar{v}_A$  in terms of the Eulerian angles. It therefore may be differentiated to determine  $\bar{a}_A$ . The relative derivative concept described by Eq. (3.3.15) is appropriate to this task. Equation (4.4.16) gives the  $\bar{i}'\bar{j}'\bar{k}'$  components of  $\bar{v}_A$ , and the first of Eqs. (4.4.15) is the angular velocity of  $x'y'z'$ . We thereby find that

$$\begin{aligned}\bar{a}_A &= \frac{\partial}{\partial t} \left[ -R(\dot{\phi} + \dot{\psi}\cos\theta)\bar{j}' + R\dot{\theta}\bar{k}' \right] + \bar{\Omega}' \times \left[ -R(\dot{\phi} + \dot{\psi}\cos\theta)\bar{j}' + R\dot{\theta}\bar{k}' \right] \\ &= R[\dot{\theta}^2 + (\dot{\phi} + \dot{\psi}\cos\theta)\dot{\psi}\cos\theta]\bar{i}' + R[-\ddot{\phi} - \ddot{\psi}\cos\theta + 2\dot{\psi}\dot{\theta}\sin\theta]\bar{j}' \\ &\quad + R[\ddot{\theta} + (\dot{\phi} + \dot{\psi}\cos\theta)\dot{\psi}\sin\theta]\bar{k}'.\end{aligned}\quad (4.4.17)$$

The angular acceleration is found by differentiating the second of Eqs. (4.2.11):

$$\begin{aligned}\bar{\alpha} &= (-\ddot{\psi}\sin\theta - \dot{\psi}\dot{\theta}\cos\theta + \dot{\theta}\dot{\phi})\bar{i}' + (\ddot{\theta} + \dot{\psi}\dot{\phi}\sin\theta)\bar{j}' \\ &\quad + (\dot{\psi}\cos\theta + \ddot{\phi} - \dot{\psi}\dot{\theta}\sin\theta)\bar{k}'.\end{aligned}\quad (4.4.18)$$

Equations (4.4.15)–(4.4.18) describe the motion of the center point and the angular motion of the rolling disk in terms of the Eulerian angles. The velocity and acceleration of any other point in the disk may be determined through the kinematical formulas relating points in a rigid body.

Although Eqs. (4.4.16) and (4.4.17) contain a variety of effects, one is readily identifiable. The vertical unit vector in Fig. 4.15 is  $\bar{e}_1 = -\sin\theta\bar{i}' + \cos\theta\bar{k}'$ . Correspondingly, we find that the components of  $\bar{v}_A$  and  $\bar{a}_A$  perpendicular to the contact plane are

$$\bar{v}_A \cdot \bar{e}_1 = R\dot{\theta}\cos\theta, \quad \bar{a}_A \cdot \bar{e}_1 = R(\ddot{\theta}\cos\theta - \dot{\theta}^2\sin\theta). \quad (4.4.19)$$

We now observe from Fig. 4.15 that the elevation of point  $A$  above the ground is  $h = R\sin\theta$ . Successive differentiation of  $h$  shows that  $\dot{h} \equiv \bar{v}_A \cdot \bar{e}_1$  and  $\ddot{h} \equiv \bar{a}_A \cdot \bar{e}_1$ . In other words, the procedure we followed implicitly recognized a fundamental geometric property stemming from the fact that the distance from the contact point to the center is always  $R$ .


Although the roundness of the disk played a less obvious role in this motion, it was crucial. If the disk were elliptical, it would have been necessary to describe the velocity

#### 4.4 Rolling

207

of the center point as a function of the spin angle and the properties of the ellipse. Differentiating such a representation would have been substantially more difficult than the corresponding tasks in the case of a circular disk.

**EXAMPLE 4.6** Piston  $A$  has constant velocity  $v$  to the right. The wheel, which is connected to the piston by connecting rod  $AB$ , rolls without slipping over the ground. Determine the velocity and acceleration of the center of the wheel for the position shown in the sketch.



Example 4.6

**SOLUTION** This example is intended to reinforce our ability to analyze a planar linkage while simultaneously accounting for the special features of a rolling body. It is imperative to realize that, even though the input speed  $v$  is constant, none of the other acceleration parameters can be assumed to be zero because the geometrical configuration changes when connecting pin  $B$  moves. Also, we could analyze this system when pin  $B$  is at an arbitrary position, but doing so would merely complicate the geometrical description of position variables without modifying the basic operations.

For a global coordinate system, let the  $x$  axis be horizontal to the right and the  $y$  axis be vertically upward. The angular velocity of each body is perpendicular to the plane, with unknown rates, so we have

$$\bar{\omega}_{AB} = \omega_{AB}\bar{k}, \quad \bar{\omega}_w = \omega_w\bar{k}.$$

We next account for the fact that both points  $A$  and  $C$  follow straight paths, so that

$$\bar{v}_A = v\bar{i}, \quad \bar{a}_A = \bar{0}, \quad \bar{v}_C = v_C\bar{i}, \quad \bar{a}_C = \dot{v}_C\bar{i}. \quad (1)$$

Because there is no slippage between the wheel and the stationary ground, relating the velocity of center  $C$  to that of the contact point yields

$$\bar{v}_C = v_C\bar{i} = \omega_w\bar{k} \times R\bar{j} \implies v_C = -R\omega_w. \quad (2)$$

This relation is true at any instant, so differentiating it with respect to  $t$  gives

$$\dot{v}_C = -R\dot{\omega}_w. \quad (3)$$

From this juncture, the analysis proceeds like that for any other planar linkage. We describe the velocity of the connecting pin  $B$  in terms of the parameters for bar  $AB$  and for the wheel. Thus,

$$\bar{v}_B = \bar{v}_A + \omega_{AB}\bar{k} \times \bar{r}_{B/A} = \bar{v}_C + \omega_w\bar{k} \times \bar{r}_{B/C}. \quad (4)$$

The instantaneous positions are

$$\bar{r}_{B/A} = \sqrt{3}R\bar{i} + R\bar{j}, \quad \bar{r}_{B/C} = -R\bar{i}. \quad (5)$$

Substitution of Eqs. (1), (2), and (5) into Eqs. (4) results in

$$\bar{v}_B = v\bar{i} + \omega_{AB}\bar{k} \times (\sqrt{3}R\bar{i} + R\bar{j}) = -R\omega_w\bar{i} + \omega_w\bar{k} \times (-R\bar{i}). \quad (6)$$

Matching like components yields two simultaneous equations for  $\omega_{AB}$  and  $\omega_w$  in terms of  $v$ ,

$$\begin{aligned} \bar{v}_B \cdot \bar{i} &= v - R\omega_{AB} = -R\omega_w, \\ \bar{v}_B \cdot \bar{j} &= \sqrt{3}R\omega_{AB} = -R\omega_w, \end{aligned}$$

from which we find that the instantaneous rotation rates are

$$\omega_{AB} = 0.3660 \frac{v}{R}, \quad \omega_w = -0.6340 \frac{v}{R}. \quad (7)$$

The corresponding velocity of center  $C$  is

$$\bar{v}_C = -R\omega_w\bar{i} = 0.6340v\bar{i}. \quad \triangleleft$$

Now that the velocity has been fully analyzed, we may proceed to acceleration. We begin by writing the acceleration analogs to Eqs. (4):

$$\begin{aligned} \bar{a}_B &= \bar{a}_A + \dot{\omega}_{AB}\bar{k} \times \bar{r}_{B/A} - \omega_{AB}^2 \bar{r}_{B/A} \\ &= \bar{a}_C + \dot{\omega}_w\bar{k} \times \bar{r}_{B/C} - \omega_w^2 \bar{r}_{B/C}. \end{aligned} \quad (8)$$

From Eqs. (1) and (3), we know that  $\bar{a}_A = \bar{0}$  and  $\bar{a}_C = -R\dot{\omega}_w\bar{i}$ . The current rotation rates are given by Eqs. (7), and Eqs. (5) give the instantaneous position vectors. Substitution of these values into the preceding results in

$$\begin{aligned} \bar{a}_B &= \dot{\omega}_{AB}\bar{k} \times (\sqrt{3}R\bar{i} + R\bar{j}) - \left(0.3660 \frac{v}{R}\right)^2 (\sqrt{3}R\bar{i} + R\bar{j}) \\ &= -R\dot{\omega}_w\bar{i} + \dot{\omega}_w\bar{k} \times (-R\bar{i}) - \left(-0.6340 \frac{v}{R}\right)^2 (-R\bar{i}). \end{aligned}$$

The simultaneous equations obtained from matching like components of  $\bar{a}_B$  are

$$\begin{aligned} \bar{a}_B \cdot \bar{i} &= -R\dot{\omega}_{AB} - 0.2321 \frac{v^2}{R} = -R\dot{\omega}_w + 0.4019 \frac{v^2}{R}, \\ \bar{a}_B \cdot \bar{j} &= \sqrt{3}R\dot{\omega}_{AB} - 0.1340 \frac{v^2}{R} = -R\dot{\omega}_w. \end{aligned}$$

The angular acceleration rates obtained from these equations are

$$\dot{\omega}_{AB} = -0.1830 \frac{v^2}{R^2}, \quad \dot{\omega}_w = 0.4510 \frac{v^2}{R^2}.$$

The corresponding acceleration of center  $C$  is


$$\bar{a}_C = -R\dot{\omega}_w\bar{i} = -0.4510 \frac{v^2}{R}\bar{i}. \quad \triangleleft$$



#### 4.4 Rolling


209

**EXAMPLE 4.7** Rack  $CD$  pivots about pin  $D$  such that the angle of elevation  $\theta$  is a known function of time. Rack  $B$  translates to the right in order to keep gear  $A$  in contact with rack  $CD$ . Determine the required velocity  $v$ , the corresponding angular velocity of gear  $A$ , and the velocity of the gear's center. Express all results in terms of the instantaneous values of  $\theta$  and  $\dot{\theta}$ .



Example 4.7

**SOLUTION** This example concerns a situation in which contacting surfaces involved in rolling have a normal velocity component, so its analysis will generalize our understanding of rolling in planar motion. Our approach treats the system as a linkage, in which some of the constrained points are subject to the no-slip condition. The sketch shows the global  $xyz$  coordinate system we shall use, as well as the geometrical parameters we will need to describe position vectors.



Global coordinate system and geometrical parameters for analyzing the rolling motion of the gear.

The constrained points are the center  $A$ , which follows a straight horizontal path, point  $B$ , at which there can be no slipping between gear  $A$  and the horizontal rack, point  $E$ , at which there can be no slipping between gear  $A$  and rack  $CD$ , and point  $C$ , which is stationary. We set  $\vec{v}_A = -v_A \vec{i}$ ,  $\vec{v}_C = \vec{0}$ , and equate the velocities of point  $E$  obtained by considering it to be a point on rack  $CD$ , or on gear  $A$ . Thus,

$$\vec{v}_E = \dot{\theta} \vec{k} \times \vec{r}_{E/C} = -v_A \vec{i} + \omega_A \vec{k} \times \vec{r}_{E/A}. \quad (1)$$

Matching the velocity descriptions of contact point  $B$  based on considering it to be a point in the rack or in the gear gives

$$\vec{v}_B = -v \vec{i} = -v_A \vec{i} + \omega_A \vec{k} \times \vec{r}_{B/A}. \quad (2)$$

The length  $L$  from the pivot is related to the angle  $\theta$  by

$$L = R \cot\left(\frac{\theta}{2}\right), \quad (3)$$

so that

$$\bar{r}_{E/C} = R \cot\left(\frac{\theta}{2}\right) (\cos \theta \bar{i} + \sin \theta \bar{j}), \quad \bar{r}_{E/A} = R(-\sin \theta \bar{i} + \cos \theta \bar{j}), \quad \bar{r}_{B/A} = -R \bar{j}.$$

Substitution of these position vectors into Eqs. (1) and (2) gives

$$\begin{aligned} \bar{v}_E &= R\dot{\theta} \cot\left(\frac{\theta}{2}\right) (-\sin \theta \bar{i} + \cos \theta \bar{j}) = -v_A \bar{i} + \omega_A R(-\cos \theta \bar{i} - \sin \theta \bar{j}), \\ \bar{v}_B &= -v \bar{i} = \dot{v}_A \bar{i} + \omega_A R \bar{i}. \end{aligned} \quad (4)$$

Matching like components in each of these equations leads to

$$\begin{aligned} \bar{v}_B \cdot \bar{i} &= -v = -v_A + \omega_A R, \\ \bar{v}_E \cdot \bar{i} &= -R\dot{\theta} \cot\left(\frac{\theta}{2}\right) \sin \theta = -v_A - \omega_A R \cos \theta, \\ \bar{v}_E \cdot \bar{j} &= R\dot{\theta} \cot\left(\frac{\theta}{2}\right) \cos \theta = -\omega_A R \sin \theta. \end{aligned}$$

The solution of these equations is

$$\begin{aligned} \omega_A &= -\dot{\theta} \cot\left(\frac{\theta}{2}\right) \cot \theta \equiv -\dot{\theta} \frac{\cos \theta}{(1 - \cos \theta)}, \\ v_A &= -\frac{\omega_A R}{\cos \theta} = R\dot{\theta} \frac{1}{(1 - \cos \theta)}, \\ v &= -\omega_A R \left( \frac{1}{\cos \theta} + 1 \right) = R\dot{\theta} \frac{(1 + \cos \theta)}{(1 - \cos \theta)}. \end{aligned} \quad (5)$$

An interesting aspect of the result for  $v_A$  is that it could have been obtained much more simply by a different approach. A geometrical analysis shows that  $L$  also is the distance from pivot  $C$  to the point of contact  $B$ . Because this point is always directly below the center  $A$ , we have  $\bar{r}_{A/C} = L \bar{i} + R \bar{j}$ . Differentiating this vector, with  $L$  given by Eq. (3), leads to

$$\bar{v}_A = \dot{L} \bar{i} = \frac{dL}{d\theta} \dot{\theta} \bar{i} = -R\dot{\theta} \frac{1}{2(\sin(\theta/2))^2}. \quad (6)$$

Because  $2(\sin(\theta/2))^2 \equiv 1 - \cos \theta$ , this result is the same as the second of Eqs. (5). Clearly the second approach represents a more direct route for analyzing  $\bar{v}_A$ , but it gives neither the angular velocity of gear  $A$  nor the velocity of rack  $B$ .


Suppose it had been requested to determine the accelerations of rack  $B$  and center  $A$  and the angular acceleration of the gear. As a consequence of the circular geometry, the derived expressions for  $\omega_A$ ,  $v_A$ , and  $v$  are valid at any  $\theta$ . Thus expressions for  $\dot{\omega}_A$ ,  $\dot{v}_A$ , and  $\dot{v}$  can be obtained by direct differentiation. For example,

$$\begin{aligned} \dot{\omega}_A &= -\ddot{\theta} \frac{\cos \theta}{(1 - \cos \theta)} - \dot{\theta}^2 \frac{d}{d\theta} \left[ \frac{\cos \theta}{(1 - \cos \theta)} \right] \\ &= -\ddot{\theta} \frac{\cos \theta}{(1 - \cos \theta)} + \dot{\theta}^2 \frac{\sin \theta}{(1 - \cos \theta)^2}. \end{aligned}$$

#### 4.4 Rolling


211

**EXAMPLE 4.8** The disk rotates freely about its shaft, as the shaft rotates about the vertical axis at the constant rate  $\Omega$ . There is no slippage at the point where the disk contacts the inner wall of the stationary cylindrical tank. Determine the angular velocity and angular acceleration of the disk, and the acceleration of the point on the disk that is in contact with the cylinder.



Example 4.8

**SOLUTION** A key objective of this example of rolling in spatial motion is to clarify some misconceptions that individuals have as a result of using intuition, rather than the formal analytical concepts. We begin by treating this system like any other in which it is necessary to evaluate the angular velocity and angular acceleration. Thus we draw a sketch of the system as a side view that shows both rotation axes in true view. Reference frame  $xyz$  is fixed to the disk, so only its  $z$  axis lies in the plane of the sketch at all instants, whereas the  $x_2y_2z_2$  is attached to the shaft so both the  $x_2$  and  $z_2$  axes are always situated in the vertical plane. We define the  $Z$  axis of the fixed reference frame to coincide with the axis for the  $\Omega$  rotation. The unknown spin rate is denoted as  $\dot{\phi}$ , consistent with the notation for Eulerian angles.



Coordinate systems for analyzing the spatial rolling motion of the disk

A general expression for the angular velocity of the disk is

$$\bar{\omega} = \Omega \bar{e}_1 + \dot{\phi} \bar{e}_2, \quad \bar{e}_1 = -\bar{K}, \quad \bar{e}_2 = \bar{k}_2.$$

Because  $XYZ$  is fixed and  $x_2y_2z_2$  rotates about the vertical axis, we have

$$\bar{\Omega}_1 = \bar{0}, \quad \bar{\Omega}_2 = \Omega \bar{e}_1.$$

It will turn out that there is a constant ratio between  $\Omega$  and  $\dot{\phi}$ , which means that  $\ddot{\phi}$  will be zero because  $\Omega$  is constant. However, that might not be true in other situations, so we carry out the analysis of angular acceleration allowing for the possibility that  $\ddot{\phi} \neq 0$ . Thus differentiating  $\bar{\omega}$  leads to

$$\bar{\alpha} = \ddot{\phi} \bar{e}_2 + \dot{\phi} (\bar{\Omega}_2 \times \bar{e}_2).$$

The axes of  $x_2 y_2 z_2$  form a convenient global coordinate system, so that  $\bar{e}_1 = \sin \beta \bar{i}_2 - \cos \beta \bar{k}_2$ . Correspondingly, we find that

$$\bar{\omega} = \Omega \sin \beta \bar{i}_2 + (\dot{\phi} - \Omega \cos \beta) \bar{k}_2,$$

$$\bar{\Omega}_2 = \Omega \sin \beta \bar{i}_2 - \Omega \cos \beta \bar{k}_2,$$

$$\bar{\alpha} = -\Omega \dot{\phi} \sin \beta \bar{j}_2 + \ddot{\phi} \bar{k}_2.$$

At this juncture, we have not addressed the constraint imposed by the no-slip condition at the wall, which requires that the instantaneous velocity at the contact point  $C$  be zero. The center point  $B$  follows a horizontal circular path of radius  $L \sin \beta$ , and it is moving inward relative to the plane of the sketch, so  $\bar{v}_B = -L\Omega \sin \beta \bar{j}_2$ . The kinematical relation between the velocities of these points based on both belonging to the disk then requires that

$$\bar{v}_B = -L\Omega \sin \beta \bar{j}_2 = \bar{\omega} \times \bar{r}_{B/C} = [\Omega \sin \beta \bar{i}_2 + (\dot{\phi} - \Omega \cos \beta) \bar{k}_2] \times (-R \bar{i}_2).$$

The only nonzero component of the preceding is

$$\bar{v}_B \cdot \bar{j}_2 = -L\Omega \sin \beta = -R(\dot{\phi} - \Omega \cos \beta),$$

from which we find that

$$\dot{\phi} = \left( \frac{L}{R} \sin \beta + \cos \beta \right) \Omega.$$

Because the analysis has been carried out for an arbitrary instant, this relation is generally valid. It shows that  $\dot{\phi}$  is proportional to  $\Omega$ , so we have  $\ddot{\phi} = 0$ , as was anticipated earlier. Substitution of the spin rate into the general expressions for  $\bar{\omega}$  and  $\bar{\alpha}$  yields

$$\bar{\omega} = \Omega \sin \beta \left( \bar{i}_2 + \frac{L}{R} \bar{k}_2 \right), \quad \bar{\alpha} = -\Omega^2 \left[ \frac{L}{R} (\sin \beta)^2 + \sin \beta \cos \beta \right] \bar{j}_2. \quad \triangleleft$$

A key aspect of the rotation is the fact that both  $\dot{\phi}$  and  $\Omega$  are responsible for the rotation about the  $z$  axis. Failure to recognize the contribution of  $\Omega$  leads to a common error for novices, who state that as a result of the no-slip condition the

#### 4.4 Rolling

213

speed of point  $B$  is  $\dot{\phi} R$ . As we have seen, the angular velocity component about the  $z$  axis actually is  $\dot{\phi} - \Omega \cos \beta$ , which led to  $v_B = (\dot{\phi} - \Omega \cos \beta) R$ .

Now that we have described the angular motion we can proceed to evaluate the acceleration of the contact point. We do this by relating  $\bar{a}_C$  to the acceleration of a reference point in the disk, for which the center  $B$  is convenient. Because this point follows a horizontal circular path, we have

$$\bar{a}_B = (L \sin \beta) \Omega^2 \bar{e}_n = (L \sin \beta) \Omega^2 (-\cos \beta \bar{i}_2 - \sin \beta \bar{k}_2).$$

[An alternative to using path variables to describe  $\bar{a}_B$  is to recognize that point  $B$  is also a point on the shaft, whose angular velocity is the constant  $\bar{\Omega}_1$  and whose point  $A$  is stationary, so that  $\bar{a}_B = \bar{\Omega}_1 \times (\bar{\Omega}_1 \times \bar{r}_{B/A})$ .] With  $\bar{a}_B$ ,  $\bar{\omega}$ , and  $\bar{\alpha}$  established, we evaluate

$$\begin{aligned} \bar{a}_C &= \bar{a}_B + \bar{\alpha} \times \bar{r}_{C/B} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{C/B}) \\ &= \Omega^2 \left[ \frac{L}{R} (\sin \beta)^2 + \sin \beta \cos \beta \right] (-L \bar{i}_2 + R \bar{k}_2). \end{aligned} \quad \triangleleft$$


An interesting interpretation of these results follows from the observation that  $\bar{r}_{C/A} = R \bar{i}_2 + L \bar{k}_2$ . The expressions we have derived indicate that  $\bar{\omega}$  is parallel to  $\bar{r}_{C/A}$  and  $\bar{a}_C$  is perpendicular to  $\bar{r}_{C/A}$ . Both features would have been apparent if we had slightly altered our analysis based on the observation that point  $A$  is always at distance  $L$  along the disk's centerline. Consequently, we can consider point  $A$  to belong to the disk, which allows us to use point  $A$  as the reference point for describing the motion of the contact point. Because point  $A$  is stationary, we could have written

$$\bar{v}_C = \bar{0} = \bar{\omega} \times \bar{r}_{C/A}, \quad \bar{a}_C = \bar{\alpha} \times \bar{r}_{C/A} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{C/A}).$$

The first equation establishes the parallelism of  $\bar{\omega}$  and  $\bar{r}_{C/A}$ , and it simplifies the second equation to  $\bar{a}_C = \bar{\alpha} \times \bar{r}_{C/A}$ , from which it follows that  $\bar{a}_C \cdot \bar{r}_{C/A} = 0$ .


This leads to a visual model for the motion of the disk. Regardless of the angles of rotation about the  $Z$  and  $z$  axes, the line connecting points  $A$  and  $C$  is always situated at a constant angle from the vertical. The sketch shows that this angle is  $\beta + \tan^{-1}(R/L)$ . Thus the locus of this line is a cone. Because it represents the view of line  $AC$  from the perspective of a fixed observer, it is called the *space cone*. On the other hand, from the perspective of an observer on the disk, who considers  $xyz$  to be stationary, the angle from the  $x$  axis to line  $AC$  is always  $\tan^{-1}(L/R)$ . However, line  $AC$  may be situated arbitrarily relative to the  $xz$  plane. Thus the locus of line  $AC$  relative to an observer on  $xyz$  is the *body cone*. The last sketch depicts both cones. The motion of the disk is equivalent to the body cone rolling without slipping over the space cone. The instantaneous axis of rotation is the line of contact between the cones. The acceleration of any point on the body cone that is on this line of contact is normal to the rotation axis. The concept of space and body cones is particularly

useful for the treatment of the rotation of bodies in free flight, which is a topic in Chapter 10.




Body and space cones for the disk that rolls without slipping over the interior of the cylinder.

**EXAMPLE 4.9** A disk rolls without slipping on the  $XY$  plane. At the instant shown, the horizontal diameter  $ACB$  is parallel to the  $X$  axis. Also, at this instant, the horizontal components of the velocity of the center  $C$  are known to be 5 m/s in the  $X$  direction and 3 m/s in the  $Y$  direction, and the  $Y$  component of the velocity of point  $B$  is 6 m/s. Determine the precession, nutation, and spin rates for the Eulerian angles in Fig. 4.15.



Example 4.9

**SOLUTION** We begin with a sketch that is like Fig. 4.15, except that the nutation angle exceeds  $\pi/2$  because the disk is tilted to the right. The  $y'$  axis coincides with the horizontal diameter  $AB$ , which is the line of nodes. Because an increase of  $\theta$  is defined to correspond to rotation about the positive  $y'$  axis, we have  $\bar{j}' = -\bar{l}$  at the given instant.



Eulerian angles and coordinate systems for analyzing arbitrary rolling motion of a disk

The axes and angle defined here match those in Fig. 4.15, so we may directly employ the description of  $\bar{\omega}$  in Eqs. (4.2.12). We set  $\theta = 110^\circ$  for the instant of interest, which yields

$$\bar{\omega} = -0.9397\dot{\psi}\bar{i}' + \dot{\theta}\bar{j}' + (\dot{\phi} - 0.3420\dot{\psi})\bar{k}'.$$

There is no slipping at the contact point  $D$ , so  $\bar{v}_D = \bar{0}$ . When we refer the velocities of points  $B$  and  $C$  to this point, we find that

$$\begin{aligned}\bar{v}_C &= \bar{\omega} \times (-0.08\bar{i}') = -0.08(\dot{\phi} - 0.3420\dot{\psi})\bar{j}' + 0.08\dot{\theta}\bar{k}', \\ \bar{v}_B &= \bar{\omega} \times (-0.08\bar{i}' + 0.08\bar{j}') \\ &= -0.08(\dot{\phi} - 0.3420\dot{\psi})(\bar{i}' + \bar{j}') + 0.08(\dot{\theta} - 0.9397\dot{\psi})\bar{k}'.\end{aligned}$$

These velocities must match the given components. The fact that  $\bar{j}' = -\bar{I}$  at this instant substantially expedites the evaluation of dot products, which we find to be

$$\begin{aligned}\bar{v}_C \cdot \bar{I} = 5 &= -0.08(\dot{\phi} - 0.3420\dot{\psi})(\bar{j}' \cdot \bar{I}) + 0.08\dot{\theta}(\bar{k}' \cdot \bar{I}) = 0.08(\dot{\phi} - 0.3420\dot{\psi}), \\ \bar{v}_C \cdot \bar{J} = 3 &= -0.08(\dot{\phi} - 0.3420\dot{\psi})(\bar{j}' \cdot \bar{J}) + 0.08\dot{\theta}(\bar{k}' \cdot \bar{J}) = 0.08\dot{\theta} \cos 20^\circ, \\ \bar{v}_B \cdot \bar{J} = 6 &= -0.08(\dot{\phi} - 0.3420\dot{\psi})(\bar{i}' \cdot \bar{J} + \bar{j}' \cdot \bar{J}) + 0.08(\dot{\theta} - 0.9397\dot{\psi})\bar{k}' \cdot \bar{J} \\ &= -0.08(\dot{\phi} - 0.3420\dot{\psi})(-\sin 20^\circ) + 0.08(\dot{\theta} - 0.9397\dot{\psi}) \cos 20^\circ.\end{aligned}$$

The solution of these simultaneous equations is

$$\dot{\psi} = -18.260, \quad \dot{\theta} = 39.907, \quad \dot{\phi} = 56.255 \text{ rad/s.} \quad \triangleleft$$


## SELECTED REFERENCES

- Arnold, R. N., and Maunder, M., *Gyrostatics and Its Engineering Applications*, Academic, New York (1961).  
Ginsberg, J. H., and Genin, J., *Dynamics*, 2nd ed., Wiley, New York (1984).

- Goldstein, H., *Classical Mechanics*, 2nd ed., Addison-Wesley, Reading, Massachusetts (1980).
- Greenwood, D. T., *Principles of Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1965).
- Haug, E. J., *Intermediate Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1992).
- Josephs, H., and Huston, R. L., *Dynamics of Mechanical Systems*, CRC Press, Boca Raton, Florida (2002).
- Kane, T. R., and Levinson, D. A., *Dynamics: Theory and Applications*, McGraw-Hill, New York (1985).
- Marion, J. B., *Classical Dynamics of Particles and Systems*, Academic, New York (1960).
- O'Reilly, O. M., *Engineering Dynamics*, Springer-Verlag, New York (2001).
- Shabana, A. A., *Computational Dynamics*, Wiley, New York (2001).
- Smith, C. E., *Applied Mechanics: Dynamics*, Wiley, New York (1982).
- Uicker, J. J., Pennock, G. P., and Shigley, J. E., *Theory of Machines and Mechanisms*, Oxford University Press, New York (2003).
- Vinogradov, O., *Fundamentals of Kinematics and Dynamics of Machines and Mechanisms*, CRC Press, Boca Raton, Florida (2000).

## HOMEWORK PROBLEMS


**EXERCISE 4.1** A gyropendulum consists of a flywheel that rotates at constant angular speed  $\omega_1$  relative to shaft  $BC$ . This shaft is pinned to the vertical shaft, which rotates at constant angular speed  $\omega_2$ . The angle  $\beta$  measuring the inclination of shaft  $BC$  is an arbitrary function of time. Use the Eulerian angle formulas for angular velocity and angular acceleration to derive expressions for the velocity and acceleration of point  $D$ , which coincides with the horizontal diameter at the instant of interest.



Exercise 4.1

**EXERCISE 4.2** Consider a body whose orientation is described by Eulerian angles. Derive the transformation from space-fixed to body-fixed axes for a sequence beginning with precession  $\psi = 20^\circ$ , followed by nutation  $\theta = -60^\circ$ , then spin  $\phi = 140^\circ$ . Is it possible to obtain the same transformation with a different sequence beginning with nutation  $\theta'$ , followed by spin  $\phi'$ , then precession  $\psi'$ ? If so, determine the values of  $\theta'$ ,  $\phi'$ , and  $\psi'$ .

**EXERCISE 4.3** A rigid disk is welded to the end of a flexible shaft that rotates about bearing  $A$ . The bending deformation of the shaft is such that its centerline forms a curve in a plane that always contains the bearing's axis. The rotation of this plane about the bearing's axis is the precession  $\psi$ . The tangent to this curve at end  $B$  is the axis of symmetry of the disk, and



Exercise 4.3



## Homework Problems

217

the angle between the bearing's axis and the disk's axis is the nutation angle  $\theta$ . Torsional deformation of the shaft produces a spin  $\phi$  about the disk's axis. Let  $xyz$  be a set of axes attached to the disk, and let  $x'y'z'$  be a set of axes that undergo only the precessional motion. The  $z'$  axis is coincident with the bearing axis, and the curved centerline of the shaft is always situated in the  $x'z'$  plane. It is observed that at some instant  $\theta = 10^\circ$ ,  $\phi = -5^\circ$ , and the angular velocity of the disk is  $\omega = 17\bar{i}' - 20\bar{j}' + 48\bar{k}'$  rad/s. Determine the corresponding precession, nutation, and spin rates. Then express the angular velocity in terms of components relative to  $xyz$ .


**EXERCISE 4.4** Measurements of the rotational motion of an orbiting satellite indicate that, at a certain instant, the angular velocity with respect to body-fixed coordinate system  $xyz$  is  $\bar{\omega} = 19.24\bar{i} + 6.68\bar{j} + 303.21\bar{k}$  rad/s. The laws for free rotation of a body, developed in Chapter 10, indicate that  $\bar{k}$  is the spin axis and the precession axis is  $\bar{K} = -0.3830\bar{i} - 0.6634\bar{j} + 0.6428\bar{k}$ . Determine  $\dot{\psi}$ ,  $\theta$ ,  $\dot{\theta}$ ,  $\phi$ , and  $\dot{\phi}$  at this instant.

**EXERCISE 4.5** Measurements of the rotational motion of an orbiting satellite indicate that, at a certain instant, the angular velocity with respect to body-fixed coordinate system  $xyz$  is  $\bar{\omega} = -34.64\bar{i} + 10\bar{j} - 820\bar{k}$  rad/s and the angular acceleration is  $\bar{\alpha} = -7800\bar{i} - 28713\bar{j} - 346\bar{k}$  rad/s<sup>2</sup>. The laws for free rotation of a body, developed in Chapter 10, indicate that  $\bar{k}$  is the spin axis and the precession axis is  $\bar{K} = -0.8660\bar{i} + 0.50\bar{k}$ . Determine  $\dot{\psi}$ ,  $\dot{\psi}$ ,  $\theta$ ,  $\dot{\theta}$ ,  $\phi$ ,  $\dot{\phi}$ , and  $\ddot{\phi}$  at this instant.

**EXERCISE 4.6** An alternative set of Eulerian angles is often employed to describe the rotation of aircraft and spacecraft. Let  $xyz$  be a reference frame that is attached to the vehicle, with the  $x$  axis aligned with the longitudinal axis of the vehicle and  $z$  aligned in a meaningful orthogonal direction, such as the direction of the aerodynamic lift for an aircraft. The fixed  $XYZ$  reference frame is defined such that its axes coincide with the orientation of the respective axes of  $xyz$  when the vehicle is in its nominal operational condition. The *yaw* angle  $\psi$  takes place about the  $Z$  axis, followed by the *pitch* angle  $\theta$  about the new  $y$  axis, followed by the *roll* angle  $\phi$  about the final  $x$  axis. (a) Derive the rotation transformation that converts  $\bar{I}\bar{J}\bar{K}$  components to  $\bar{i}\bar{j}\bar{k}$  components. (b) Describe the angular velocity and angular acceleration of the airplane in terms of body-fixed  $\bar{i}\bar{j}\bar{k}$  components.


**EXERCISE 4.7** Let the distance between points  $B$  and  $C$  in Fig. 4.6 be  $h$ , and let the  $y_1$  axis coincide with the line connecting these points. Let  $\psi$  denote the angle that the collar rotates relative to bar 1. Describe the constraint equations relating the displacements, velocities, and accelerations of points  $B$  and  $C$ .

**EXERCISE 4.8** Pin  $B$  slides through groove  $CD$  in a plate that translates upward at speed  $v$ . The groove forms the parabolic curve  $y = 300 - x^2/400$ , where  $x$  and  $y$  have units of millimeters. In the position shown, bar  $AB$  is rotating clockwise at 40 rad/s, and that rate is decreasing at 160 rad/s<sup>2</sup>. Determine the corresponding values of  $v$  and  $\dot{v}$ .




Exercise 4.8

**EXERCISE 4.9** A collar slides in the horizontal plane over a curved rod defined in polar coordinates by  $R = 0.1 \sin(2\theta)$  m. The motion is actuated by the translating arm, which contains a groove that pushes a pin in the collar. The speed of the arm is constant at 20 m/s. Determine the velocity and acceleration of the collar in the position where  $\theta = 1$  rad.




Exercise 4.9

**EXERCISE 4.10** Bar  $AB$  rotates at the constant rate  $\omega$ , which causes collar  $B$  to slide along curved bar  $CD$ . For the instant depicted in the diagram, determine the angular velocity and angular acceleration of bar  $CD$  and velocity and acceleration of the collar.



Exercise 4.10

**EXERCISE 4.11** The cubic box slides along the wall and floor. The motion of the box is fully specified if the angle  $\theta$  is determined as a function of time. Derive expressions for the velocity and acceleration of corners  $A$  and  $B$  and of the central point  $G$  in terms of  $\theta$ ,  $\dot{\theta}$ , and  $\ddot{\theta}$ .




Exercise 4.11

# Homework Problems


219

**EXERCISE 4.12** Collar  $C$  slides over bar  $AB$ . When the system is in the position shown, slider  $A$  is moving downward at 600 mm/s and its speed is decreasing at 15 m/s<sup>2</sup>. Determine the corresponding angular velocity and angular acceleration of each bar.




Exercise 4.12

**EXERCISE 4.13** The rotation rate  $\dot{\theta}$  of crank  $AB$  is constant. Determine the angular velocity and angular acceleration of bar  $BC$  and the velocity and acceleration of end  $C$  when  $\theta = 60^\circ$  and when  $\theta = 120^\circ$ .




Exercise 4.13

**EXERCISE 4.14** The slotted disk rotates at a constant angular speed  $\omega_A$ . Determine the angular velocity and angular acceleration of connecting rod  $BC$  in the illustrated position.




Exercise 4.14

**EXERCISE 4.15** Holes bored through block  $E$  maintain the angle between bars  $AB$  and  $CD$  at  $45^\circ$ . At the instant when bar  $CD$  is in the upright position shown, bar  $AB$  is rotating counterclockwise at 10 rad/s and that rate is decreasing at 50 rad/s<sup>2</sup>. For this instant determine the velocity and acceleration of the point on block  $E$  at which the centerlines of the bars intersect.




Exercise 4.15

**EXERCISE 4.16** Bar  $AB$  rotates clockwise at the constant angular speed  $\omega_1$ . Determine the angular velocity and angular acceleration of the other bars when the linkage is at the position shown in the sketch.




Exercise 4.16

**EXERCISE 4.17** Starting from  $s_A = 0$  at  $t = 0$ , collar  $A$  is given a constant upward acceleration  $\dot{v}_A$ . The rotation rate  $\Omega$  about the vertical axis is constant. Derive expressions for the angular velocity and acceleration of connecting rod  $AB$  as functions of the elapsed time  $t$ . Also derive expressions for the time dependence of the velocity and acceleration of collar  $B$ . Describe all results in terms of components relative to a coordinate system that rotates in unison with the T-bar.



Exercise 4.17


**EXERCISE 4.18** Collar  $A$  is pushed downward at speed  $v$ , while the entire system precesses about the vertical axis at constant angular speed  $\Omega$ . Determine the velocity of collar  $B$  and of the midpoint of bar  $AB$  at the instant depicted in the sketch.



Exercises 4.18 and 4.19


**EXERCISE 4.19** Collar  $A$  is pushed downward at speed  $v$ , while the entire system precesses about the vertical axis at angular speed  $\Omega$ . Determine the velocity and acceleration of collar  $B$  and of the midpoint of bar  $AB$  at the instant depicted in the sketch.

**EXERCISE 4.20** Bar  $BC$  is pinned to the T-bar, which rotates at constant rate  $\Omega$  about the vertical axis. The bottom of this bar contacts the platform, which translates upward at constant speed  $v$ . Determine the angular velocity and angular acceleration of bar  $BC$  as functions of the angle of elevation  $\theta$  and the value of  $\Omega$  and  $\xi$ .



Exercise 4.20

**EXERCISE 4.21** Bead  $C$  slides relative to the curved guide bar  $AB$ , which rotates about the vertical axis at the constant rate  $\Omega$ . The movement of the slider is actuated by arm  $DE$ , which pushes the collar outward from the vertical axis at a constant rate  $v$ . Determine the velocity and acceleration of the slider as a function of  $\theta$ .




Exercise 4.21

# Homework Problems


221

**EXERCISE 4.22** The spin rate  $\dot{\psi}$  of sphere  $C$  is constant, as is the precession rate  $\dot{\phi}$  and the speed  $v$  of collar  $A$ . Derive expressions for the angular velocity and angular acceleration of the sphere as functions of  $\theta$ ,  $v$ ,  $\dot{\psi}$ , and  $\dot{\phi}$ .




Exercise 4.22

**EXERCISE 4.23** Crankshaft  $ABC$  rotates at the constant rate of 900 rev/min. The connecting rod  $CD$  is pinned to cap  $C$ , which is free to rotate about axis  $BC$ . The connection at collar  $D$  is a ball-and-socket joint. For the instant depicted in the sketch, determine the velocity and acceleration of collar  $D$ , and the corresponding angular velocity and angular acceleration of the connecting rod.




Exercise 4.23

**EXERCISE 4.24** Collar  $A$  is connected to bar  $AB$  by a ball-and-socket joint, whereas the connection between collar  $B$  and bar  $AB$  is a fork-and-clevis. The speed of collar  $B$  is  $v = 30$  m/s and  $\dot{v} = -500$  m/s<sup>2</sup> at the position shown. (a) Determine the velocity of slider  $A$  and the value of  $\dot{\beta}$  at this position, where  $\beta$  is the angle between bar  $AB$  and the horizontal guide. (b) Determine the acceleration of slider  $A$  and the value of  $\ddot{\beta}$  at this position.




Exercise 4.24

**EXERCISE 4.25** The axes of bearings  $A$  and  $D$  lie in the same horizontal plane, and intersect orthogonally. Connections  $B$  and  $C$  are ball-and-socket joints, and bars  $AB$  and  $CD$  are welded to collars  $A$  and  $D$ , respectively. Bar  $AB$  rotates at the constant rate of 200 rev/min. Determine the velocity and acceleration of joint  $C$  at the instant shown.




Exercise 4.25

**EXERCISE 4.26** Bar  $CD$  is connected to collar  $D$  by a clevis joint, and all other connections are ball-and-socket joints. Collar  $A$  moves toward point  $C$  at constant speed  $v$ . Determine the angular velocity of both bars at the instant depicted in the sketch in the case in which bar  $AB$  has a circular cross section. Then repeat the analysis for the case in which the cross section of bar  $AB$  is square and there is a close sliding fit between collar  $D$  and this bar.




Exercise 4.26

**EXERCISE 4.27** Bar  $DE$  is attached to collar  $E$  by a ball-and-socket joint, and its connection to collar  $D$  is a fork-and-clevis joint. The cross section of crankshaft  $ABC$  is circular, so collar  $D$  may rotate about axis  $BC$  relative to the crankshaft. The crankshaft rotates at constant angular speed  $\Omega$ , so specification of the position of all parts of the linkage at a specified instant requires knowledge of the distance  $s$  locating collar  $D$ . Derive expressions for the angular velocity of bar  $DE$  and the speed of collar  $E$  in terms of  $s$  and  $\dot{s}$  for the instant at which  $\Omega t = \pi/3$ . The horizontal distance  $H = 0.3L$ .




Exercise 4.27

**EXERCISE 4.28** A cylinder of radius  $r$  rolls without slipping inside a semicylindrical cavity. Point  $P$  is collinear with the vertical centerline when the vertical angle  $\theta$  locating the cylinder's center  $C$  is zero. Derive expressions for the velocity and acceleration of point  $P$  in terms of  $\theta$ ,  $\dot{\theta}$ , and  $\ddot{\theta}$ .



Exercise 4.28

**EXERCISE 4.29** A disk rolls without slipping over the exterior of a large drum. The rotation rate  $\Omega$  of the drum is constant. In the position shown the center of the disk has a speed  $v$ , which is increasing at the rate  $\dot{v}$ . Derive expressions for the velocity and acceleration of point  $P$ , which is situated at an arbitrary angle  $\beta$  relative to the line of centers.




Exercise 4.29

# Homework Problems


223

**EXERCISE 4.30** The angular velocities of the inner and outer gears are counterclockwise at the constant values  $\omega_1$  and  $\omega_2$ , respectively. Determine the velocity and acceleration of point  $C$  on the perimeter of the planetary gear as a function of the angle  $\theta$  locating the instantaneous position of point  $C$  relative to the radial line.




Exercise 4.30

**EXERCISE 4.31** The collar has a constant speed  $v$  to the right, and the rack is stationary. Determine the angular velocity and angular acceleration of the gear at the instant depicted in the sketch.




Exercise 4.31

**EXERCISE 4.32** The wheel rolls without slipping over the ground as the collar slides at constant speed  $u$  over the curved guide bar. Determine the velocity and acceleration of the center of the wheel in terms of  $u$  when the linkage is in the position shown.




Exercise 4.32

**EXERCISE 4.33** Movement of the actuating rod  $AB$  at constant speed  $v$  pushes the connecting pin through the groove in the wheel, thereby causing the wheel to roll over the ground. Determine the angular velocity and angular acceleration of the gear as a function of  $\theta$  if there is no slippage in the rolling motion.




Exercise 4.33

**EXERCISE 4.34** Rack  $CD$ , which meshes with gear  $A$ , is actuated by moving collar  $D$  upward at the constant speed  $v_D$ . Rack  $B$ , over which gear  $A$  rolls, is stationary. Derive expressions for the velocity and acceleration of the center of gear  $A$  as functions of the current values of  $s$  and  $\theta$ .




Exercise 4.34

**EXERCISE 4.35** The body cone rolls without slipping over the stationary space cone. It is observed that the axis of the body cone requires 200 ms to complete one revolution. Determine the angular velocity and angular acceleration of the body cone.




Exercise 4.35

**EXERCISE 4.36** A sphere of radius  $R$  rolls without slipping in the interior of a cone such that  $R$  also is the distance from the axis of the cone to the center of the sphere. The speed of the center of the sphere is the constant value  $v$ . The rotation of the sphere is observed to consist of a precession about a vertical axis and a spin about an axis parallel to the cone generator. Derive expressions for the angular velocity and angular acceleration of the sphere in terms of  $v$ ,  $R$ , and the apex angle  $\theta$ .




Exercise 4.36

**EXERCISE 4.37** The sphere rolls without slipping over the interior wall of a hollow cylinder that rotates about its axis at  $\Omega_2$ . The angular speed of the vertical shaft driving the sphere is  $\Omega_1$ . Both rotation rates are constant. Determine the angular velocity and angular acceleration of the sphere.



Exercise 4.37

**EXERCISE 4.38** The sketch shows the cross section of a cone whose axis is vertical and whose vertex angle is  $2\beta$ . This cone rotates about its axis at the constant angular speed  $\Omega$ . The sphere spins freely at angular speed  $\phi$  about the shaft that intersects its center. This shaft precesses about the vertical axis at the variable angular speed  $\psi$ , so  $\dot{\psi} \neq 0$ . (a) Determine the ratio  $\phi/\Omega$  for which there is no slippage between the sphere and the cone. (b) Determine the angular velocity and angular acceleration of the sphere when there is no slippage.




Exercise 4.38



## Homework Problems


225

**EXERCISE 4.39** Gear  $A$  spins relative to its shaft, which rotates at variable rate  $\Omega_1$  about the horizontal axis. Gear  $B$  rotates at the variable rate  $\Omega_2$ . Determine the angular velocity and angular acceleration of gear  $A$ .




Exercise 4.39

**EXERCISE 4.40** The sketch shows a reduction gear assembly that converts an input angular speed  $\Omega_1$  to an output speed  $\Omega_2$ . Gear  $A$  is welded to the stationary housing, gears  $B$  and  $C$  are welded to their respective shafts, and spider arm  $D$  rotates about the horizontal axis at a different angular speed. Gears  $E$  and  $F$  are a single planetary body that spins about its axis of symmetry relative to the angled arm of the spider. (a) Derive an expression for the gear ratio  $\Omega_2/\Omega_1$  in terms of the length dimensions and the angle  $\beta$ . (b) Derive expressions for the angular velocity and angular acceleration of planetary gear  $EF$ . *Hint:* The intersection  $O$  of the axis of the planetary gear and of the drive shaft is stationary.




Exercise 4.40

**EXERCISE 4.41** The cylindrical drum rotates about the vertical axis at the constant rate  $\Omega_2$ , and the conical floor of the tank rotates at the constant rate  $\Omega_1$ . In the situation of interest the radial line to the center of the sphere also rotates at  $\Omega_1$ . There is no slip-page between either the interior wall of the tank or the spinning conical floor in the rolling motion. Determine the angular velocity and acceleration of the sphere.




Exercise 4.41

**EXERCISE 4.42** The diagram shows the cross section of a differential gear of radius  $R$  that spins relative to the bent shaft at angular speed  $\omega_2$ . The rotation rate of this shaft about the vertical axis is  $\omega_1$ . The cylindrical drum rotates at constant angular speed  $\Omega_1$  about the vertical axis, and the base gear rotates at constant angular speed  $\Omega_2$ . The differential gear rotates without slipping relative to both the base and the cylinder. (a) Derive expressions for  $\omega_1$  and  $\omega_2$  corresponding to specified values of  $\Omega_1$  and  $\Omega_2$ . (b) Determine the angular velocity and angular acceleration of the differential gear.




Exercise 4.42

**EXERCISE 4.43** The system in the sketch is analogous to a roulette wheel, in that a sphere of radius  $R$  rolls without slipping over the interior of a hemispherical shell of radius  $b$  that rotates about the vertical axis at constant rate  $\Omega$ . The polar and azimuth angles locating the center of the sphere are  $\phi$  and  $\theta$ , defined with respect to the fixed  $XYZ$  coordinate system. Both angles are arbitrary functions of time. Derive expressions for the angular velocity and angular acceleration of the sphere in terms of  $\phi$ ,  $\theta$ , and their derivatives.



Exercise 4.43

**EXERCISE 4.44** The disk rolls without slipping over the horizontal  $XY$  plane. At the instant when  $\beta = 36.87^\circ$ , the  $X$  and  $Y$  components of the velocity of point  $B$  on the horizontal diameter of the disk are 8 m/s and  $-4$  m/s, respectively, and the corresponding velocity components of center  $A$  at this instant are 4 m/s and 2 m/s. Determine the precession angle  $\psi$  between the horizontal diameter  $BAC$  and the  $X$  axis, and also evaluate the precession, nutation, and spin rates.



Exercises 4.44 and 4.45

**EXERCISE 4.45** The disk is rolling without slipping over the horizontal  $XY$  plane. At the instant when the angle of inclination is  $\beta = 30^\circ$ , the disk is observed to be spinning at  $\dot{\phi} = 5$  rad/s. At this instant, the speed of points  $B$  and  $C$  on its horizontal diameter are 1 and 2 m/s, respectively. Determine the corresponding precession and nutation rates.

## CHAPTER 5

# Inertial Effects for a Rigid Body

Chasle's theorem states that the general motion of a rigid body can be represented as a superposition of a translation following any point in a body and a pure rotation about that point. The kinematics tools we have developed provide the capability to describe these motions in terms of a few parameters. In this chapter we begin to characterize the relationship between forces acting on a rigid body and kinematical parameters for that body. The resultant of a set of forces may be regarded intuitively as the net tendency of the force system to push a body, so one should expect it to be related to the translational effect. Similarly, it is reasonable to expect that the resultant moment of a set of forces represents the rotational influence. We shall confirm and quantify these expectations.

From a philosophical perspective, the shift from statics, in which one equilibrates forces, to kinetics, in which the forces must match an inertial effect, is rather drastic. For a particle, Newton's Second and Third Laws are readily understood in this regard. However, the corresponding shift for the rotational effect will lead to effects associated with the angular momentum of a rigid body that sometimes are counterintuitive. This is especially true for those who try to examine spatial motion from a planar motion viewpoint. This chapter focuses on the determination and evaluation of angular momentum. In the course of the development we derive basic laws governing the relationship between a body's motion and the forces that act on the body. The development will be the extension to rigid bodies of Newton's Laws for particles, following concepts associated with Euler. Hence we refer to the resulting kinetics principles as the Newton–Euler equations of motion. The application of those principles will be addressed in Chapter 6.

## 5.1 LINEAR AND ANGULAR MOMENTUM

We begin by considering an arbitrary system of particles, which can represent anything from a region within a fluid to a deformable solid body. After we derive some general principles, we will specialize them to the particular case of a rigid body. Because we are cognizant of the type of information required by Chasle's theorem, our focus in all cases will be on using some point  $A$  in the system as a reference for the motion. Identification of criteria for selecting this point is one of the issues to be addressed. The fundamental axioms for the development are Newton's Second Law, which governs the motion of each particle in the system, and the Third Law, which tells us how each particle interacts with its surroundings.

## 5.1 Linear and Angular Momentum

229




Figure 5.1. External and internal forces acting on a two-particle system.

### 5.1.1 System of Particles

Figure 5.1 shows a system of two particles, numbered  $j$  and  $k$ . Two types of forces are described there. Both  $\vec{F}_j$  and  $\vec{F}_k$  are *external forces*, that is, the forces exerted on the respective particles by anything other than those particles that constitute the system of interest. Both  $\vec{f}_{j,k}$  and  $\vec{f}_{k,j}$  are the *interaction forces*, where the first subscript denotes the particle to which the force is applied and the second subscript indicates which particle exerted the force. According to Newton's Third Law, a pair of interaction forces such as these are equal in magnitude and oppositely directed:

$$\vec{f}_{k,j} = -\vec{f}_{j,k}. \quad (5.1.1)$$

Furthermore, the Third Law states that the interaction forces are collinear, meaning that they have the same line of action. The significance of this feature becomes apparent when we consider the moment exerted by each interaction force about origin  $A$ , that is,  $\vec{r}_{j/A} \times \vec{f}_{j,k}$  and  $\vec{r}_{k/A} \times \vec{f}_{k,j}$ . Because the forces act along a common line, the perpendicular distance from point  $A$  to their line of action is identical. In combination with Eq. (5.1.1), we conclude that the moment these forces exert about the origin are equal in magnitude, but directed oppositely:

$$\vec{r}_{k/A} \times \vec{f}_{k,j} = -\vec{r}_{j/A} \times \vec{f}_{j,k}. \quad (5.1.2)$$

Now let us consider Newton's Second Law for each particle. The resultant force acting on each is the sum of the external and internal contributions, so

$$\vec{F}_j + \vec{f}_{j,k} = m_j \vec{a}_j, \quad \vec{F}_k + \vec{f}_{k,j} = m_k \vec{a}_k. \quad (5.1.3)$$

Our interest here is the role of the force system on the ensemble of particles. To find the resultant of all forces, which we denote as  $\Sigma \vec{F}$ , we add the preceding equations. In view of Eq. (5.1.1), the internal forces cancel in this sum, so we have

$$\Sigma \vec{F} = \vec{F}_j + \vec{F}_k = m_j \vec{a}_j + m_k \vec{a}_k. \quad (5.1.4)$$

A similar result arises when we consider the total moment  $\Sigma \vec{M}_A$  exerted by all forces about origin  $A$ . We use the position vector from the origin to each particle to evaluate this moment, and use Eqs. (5.1.3) to characterize the forces. This leads to

$$\Sigma \vec{M}_A = \vec{r}_{j/A} \times (\vec{F}_j + \vec{f}_{j,k}) + \vec{r}_{k/A} \times (\vec{F}_k + \vec{f}_{k,j}) = \vec{r}_{j/A} \times m_j \vec{a}_j + \vec{r}_{k/A} \times m_k \vec{a}_k. \quad (5.1.5)$$

Equation (5.1.2) simplifies this to

$$\Sigma \bar{M}_A = \bar{r}_{j/A} \times \bar{F}_j + \bar{r}_{k/A} \times \bar{F}_k = \bar{r}_{j/A} \times m_j \bar{a}_j + \bar{r}_{k/A} \times m_k \bar{a}_k. \quad (5.1.6)$$

This shows that only the external forces contribute to the resultant force and to the resultant moment about point  $A$ .

If we were to add a third particle to the system addressed thus far, there would be additional internal forces exerted between this particle and each of particles in the original system. Each additional pair of interaction forces would give no net contribution to the resultant force and the moment about point  $A$ . Thus the extension of the system from two particles to an arbitrary collection of particles does not alter the fact that *only the external forces contribute to the resultant force and to the resultant moment about point  $A$* . To quantify this fact we let  $N$  denote the number of particles contained in the system and number the particles consecutively from  $j = 1$  to  $j = N$ . The forms analogous to Eqs. (5.1.4) and (5.1.6) are

$$\begin{aligned} \Sigma \bar{F} &= \sum_{j=1}^N \bar{F}_j = \sum_{j=1}^N m_j \bar{a}_j, \\ \Sigma \bar{M}_A &= \sum_{j=1}^N \bar{r}_{j/A} \times \bar{F}_j = \sum_{j=1}^N (\bar{r}_{j/A} \times m_j \bar{a}_j). \end{aligned} \quad (5.1.7)$$

We now turn our attention to the inertial effects described by the right-hand side of the preceding equations. For the resultant force we replace the acceleration with the second derivative of position. Because the mass of each particle is constant, we may form the sum before differentiating, specifically,

$$\Sigma \bar{F} = \sum_{j=1}^N \bar{F}_j = \sum_{j=1}^N m_j \frac{d^2}{dt^2} \bar{r}_{j/O} = \frac{d^2}{dt^2} \left( \sum_{j=1}^N m_j \bar{r}_{j/O} \right). \quad (5.1.8)$$

The term in parentheses is the *first moment of mass*. To understand it consider a set of particles near the surface of the Earth, with gravity acting in the negative  $Z$  direction, as depicted in Fig. 5.2. The gravitational attraction force on all particles may be replaced with a single resultant  $\bar{F}$  acting parallel to the individual forces. The magnitude of this result is the sum of the individual forces,


$$F = m_{\text{system}} g, \quad m_{\text{system}} = \sum_{j=1}^N m_j. \quad (5.1.9)$$

The point through which the resultant force acts is the *center of mass*, which is denoted as point  $G$ . To locate the  $X$  and  $Y$  coordinates of this point we equate the total moment of the gravitational forces acting on all particles to the moment of the resultant. After cancellation of a common  $g$  factor, the moments about the  $Y$  and  $X$  axes reduce to

$$m_{\text{system}} X_G = \sum_{j=1}^N m_j X_j, \quad m_{\text{system}} Y_G = \sum_{j=1}^N m_j Y_j. \quad (5.1.10)$$

## 5.1 Linear and Angular Momentum

231



**Figure 5.2.** Resultant of a the gravity forces acting on a set of particles close to the Earth.

These are first moments of mass with respect to the  $X$  and  $Y$  coordinates. A similar form featuring  $Z$  coordinates would result if gravity were to act parallel to the  $X$  or  $Y$  axes. In view of the fact that  $\bar{\mathbf{r}}_{G/O} = X_G\bar{\mathbf{i}} + Y_G\bar{\mathbf{j}} + Z_G\bar{\mathbf{k}}$ , the vector form of the first moment of mass is

$$m_{\text{system}}\bar{\mathbf{r}}_{G/O} = \sum_{j=1}^N m_j (X_j\bar{\mathbf{i}} + Y_j\bar{\mathbf{j}} + Z_j\bar{\mathbf{k}}) = \sum_{j=1}^N m_j\bar{\mathbf{r}}_{j/O}. \quad (5.1.11)$$

Substitution of this relation into Eq. (5.1.8) leads to

$$\Sigma \bar{\mathbf{F}} = \frac{d^2}{dt^2} (m_{\text{system}}\bar{\mathbf{r}}_{G/O}). \quad (5.1.12)$$

The system's mass is constant, so the preceding reduces to

$$\Sigma \bar{\mathbf{F}} = m_{\text{system}}\bar{\mathbf{a}}_G. \quad (5.1.13)$$

From this expression, we recognize that, although he posed the Second Law for a particle, Newton actually captured the behavior of the center of mass of any system of particles. If the particles move independently, it is one of many equations of motion for the various particles. The primary value of this relation lies in its application to the collection of particles forming a rigid body, in which case it addresses the portion of Chasle's theorem that requires description of the motion of one point in a body.

There are several formulations of the kinetic moment equation; they differ by the reference point that is selected. We now specify that the reference point for the kinematical description of velocity and acceleration should be the same as the point  $A$  about which we evaluate the moment sum. At this juncture, the collection of particles can move without kinematical constraints, so there is no overall rotational motion to consider. Thus we define the reference point  $A$  to be the origin of a translating reference

frame  $xyz$ . For shorthand we designate the relative velocity and acceleration of point  $P$  with respect to the moving origin  $A$  as  $\bar{v}_{P/A}$  and  $\bar{a}_{P/A}$ , respectively, where

$$\begin{aligned}\bar{v}_{P/A} &= (\bar{v}_{P/A})_{xyz} = \bar{v}_P - \bar{v}_A, \\ \bar{a}_{P/A} &= (\bar{a}_{P/A})_{xyz} = \bar{a}_P - \bar{a}_A.\end{aligned}\quad (5.1.14)$$

The second of Eqs. (5.1.7) describes the moment exerted by all forces acting on the system. In that relation we use the preceding to relate the acceleration of each particle to the acceleration of point  $A$ , which leads to

$$\Sigma \bar{M}_A = \sum_{j=1}^N \bar{r}_{j/A} \times m_j (\bar{a}_A + \bar{a}_{j/A}). \quad (5.1.15)$$

The sum may be broken into two parts. The first contains  $\bar{a}_A$  as a common factor. When it is taken out of the summation, what remains is the first moment of mass relative to origin  $A$ . In view of Eq. (5.1.11), the expression becomes

$$\Sigma \bar{M}_A = m_{\text{system}} \bar{r}_{G/A} \times \bar{a}_A + \sum_{j=1}^N [\bar{r}_{j/A} \times m_j \bar{a}_{j/A}]. \quad (5.1.16)$$

To convert the remaining sum to a more useful form, we make the time derivative entailed in acceleration explicit, and then invoke the rule for differentiating a cross product:

$$\begin{aligned}\Sigma \bar{M}_A &= m_{\text{system}} \bar{r}_{G/A} \times \bar{a}_A + \sum_{j=1}^N \bar{r}_{j/A} \times m_j \frac{d}{dt} (\bar{v}_{j/A}) \\ &\equiv m_{\text{system}} \bar{r}_{G/A} \times \bar{a}_A + \sum_{j=1}^N \left[ \frac{d}{dt} (\bar{r}_{j/A} \times m_j \bar{v}_{j/A}) - \frac{d}{dt} (\bar{r}_{j/A}) \times m_j \bar{v}_{j/A} \right].\end{aligned}\quad (5.1.17)$$

By definition,  $d(\bar{r}_{j/A})/dt = \bar{v}_{j/A}$ , so the last term vanishes. Taking the remaining time derivative outside the sum then gives

$$\Sigma \bar{M}_A = m_{\text{system}} \bar{r}_{G/A} \times \bar{a}_A + \frac{d}{dt} \bar{H}_A, \quad (5.1.18)$$

where  $\bar{H}_A$  is the *angular momentum* of the system about point  $A$ :

$$\bar{H}_A = \sum_{j=1}^N (\bar{r}_{j/A} \times m_j \bar{v}_{j/A}). \quad (5.1.19)$$

Note that  $m_j \bar{v}_{j/A}$  is the (linear) momentum of particle  $i$  relative to the translating  $xyz$  reference frame whose origin is point  $A$ . Hence a more descriptive name for  $\bar{H}_A$  is *moment of momentum* relative to point  $A$ . In the special case where point  $A$  is stationary, these equations reduce to the sum of the angular impulse–momentum equations for each particle relative to an inertial reference point, as described by Eqs. (1.2.25).

Equations (5.1.13) and (5.1.18) can be considered to govern respectively the average translation and rotation of any system of particles. The details of the interaction forces

## 5.1 Linear and Angular Momentum

233

affect how each particle in the system moves relative to these averages. For example, if our concern were with the effects of deformation of an elastic body, the internal forces would be stress resultants, and we would need to characterize how those quantities are related to the positions of the various particles. In the case of a rigid body, the kinematical condition of rigidity, which led to Chasle's theorem, is such that knowledge of the "average" motions is all that is required.

### 5.1.2 Rigid Body—Basic Equations

In the absence of deformation, the center of mass has a stationary position relative to a body. Thus, application of the extended version of Newton's Second Law, Eq. (5.1.13), governs the acceleration of a point in that body. Integrating this equation would enable us to determine the velocity and position of a point in the body, which is the first part of the information required according to Chasle's theorem.

Up to now, point  $A$  could be any that we wish. Now we require that point  $A$  have a fixed position relative to the body. The difference between the velocities of any two points in a rigid body is solely due to the body's angular velocity  $\bar{\omega}$ , so this restriction enables us to assert that

$$\bar{v}_{j/A} = \bar{\omega} \times \bar{r}_{j/A}. \quad (5.1.20)$$

Correspondingly, the angular momentum becomes

$$\bar{H}_A = \sum_{j=1}^N m_j [\bar{r}_{j/A} \times (\bar{\omega} \times \bar{r}_{j/A})]. \quad (5.1.21)$$

It is important to observe at this juncture that the mass and position of each particle relative to a body-fixed reference frame are constant for a specified rigid body. It follows that, after the preceding terms are summed over all particles, the resulting  $\bar{H}_A$  will depend solely on the angular velocity  $\bar{\omega}$  of the body. Because Eq. (5.1.18) features the rate of change of  $\bar{H}_A$ , this equation will lead to an equation governing the rotation of the body. From this perspective, the fact that Eq. (5.1.18) also contains  $\bar{a}_A$  is a complication, because the analysis of rotational motion requires simultaneous consideration of point motion. We avoid this complication in our initial studies by foregoing the freedom we have in a statics study to select a point for summing moments in favor of a restricted choice having the virtue of simplifying the kinetics terms. We refer to such points as "allowable" for forming the moment equation, which indicates that the simplified version of the moment equation is applicable. At the closure of the next chapter, we will reassert our freedom to sum moments about any point.

There are three possibilities for selecting point  $A$  such that the term  $\bar{r}_{G/A} \times \bar{a}_A$  coupling the translational and rotational effects in Eq. (5.1.18) will vanish:

1. Select point  $A$  to be the center of mass  $G$ , so that  $\bar{r}_{G/A} \equiv \bar{0}$ . The center of mass is always an allowable point. This is the point we shall use whenever the body of interest executes a general motion or a translation.



2. Select point  $A$  such that  $\bar{a}_A = \bar{0}$ . By definition, a body in pure rotation has some point that is stationary. Thus *the pivot point for a pure rotation is always an allowable point.*
3. Select point  $A$  to be the point that is accelerating directly toward or away from the center of mass, in which case  $\bar{a}_A$  is parallel to  $\bar{r}_{G/A}$ , so that  $\bar{r}_{G/A} \times \bar{a}_A = \bar{0}$ . This is a highly specialized case, so we will not employ such a point to formulate the equations governing rotation.

Formulation of the force equation of motion requires that we identify the center of mass. Thus, selecting the center of mass as the focal point for the moment equation would lead to a general procedure. However, there is an important reason why the second selection is preferable for pure rotation. Preventing the pivot point from moving requires that reaction forces be exerted at that point. For example, a ball-and-socket joint exerts an arbitrary reaction force having three components. By definition, reactions are not known in advance, so summing moments about the pivot avoids the occurrence of these unknowns in the rotational equations of motion.

In contrast to the first two possibilities, there seldom is any point in a body that is accelerating directly toward or away from the center of mass. Even if there were, locating it would be difficult. One exception occurs in planar motion, when a disk rolls without slipping over a stationary surface. The contact point's acceleration in that case is normal to the contact plane, and therefore directed toward the center of the disk. Thus the contact point would fit the allowability specification, but only if the wheel were balanced, so that the center of mass and geometric centroid coincide. Furthermore, if we wish to study the effect of slippage, the contact point would no longer be acceptable.

Translational motion is interesting because it is sometimes mistaken for a static situation. Because  $\bar{\omega} \equiv \bar{0}$  for pure translation, Eq. (5.1.21) indicates that  $\bar{H}_A \equiv \bar{0}$ . Thus the moment equation for a translating body reduces to  $\Sigma \bar{M}_A = m_{\text{system}} \bar{r}_{G/A} \times \bar{a}_A$ . If point  $A$  is not selected to be the center of mass, the resultant moment vanishes only if  $\bar{a}_A = \bar{0}$ . However, all points in a translating body experience the same acceleration. Hence the condition  $\bar{a}_A = \bar{0}$  here corresponds to rectilinear translation at a constant speed. A body executing such a motion represents an inertial reference frame, so the laws of statics apply. *If points in a translating body do not move along a straight path, or their speed is not constant, then the center of mass is the only allowable point for formulating the simplified moment equation of motion.*

When point  $A$  is allowable, the moment equation reduces to

$$\Sigma \bar{M}_A = \frac{d}{dt} \bar{H}_A. \quad (5.1.22)$$

This form is analogous to the equation for the motion of the center of mass. To recognize this we differentiate the first moment of mass, Eq. (5.1.11), which shows that the total linear momentum of any system is

$$\bar{P} = \sum_{j=1}^N m_j \bar{v}_j = \sum_{j=1}^N \frac{d}{dt} (m_j \bar{r}_{j/O}) = \frac{d}{dt} (m_{\text{system}} \bar{r}_{G/O}) = m_{\text{system}} \bar{v}_G. \quad (5.1.23)$$

## 5.1 Linear and Angular Momentum

235

Thus Eq. (5.1.13) is equivalent to

$$\Sigma \bar{F} = \frac{d}{dt} \bar{P}. \quad (5.1.24)$$

In other words, the linear or angular effect of the external force system equals the rate of change of the corresponding type of momentum for the body. Thus, the equations of motion described by this chapter are said to be momentum based. An alternative energy-based procedure for formulating equations of motion will be addressed in Chapter 7.

### 5.1.3 Kinetic Energy

In addition to being the fundamental kinetic quantity for our studies in the later chapters, kinetic energy appears in work–energy principles that are sometimes a useful adjunct to the momentum-based equations of motion. Also, kinetic energy will play a prominent role for one aspect of the evaluation of inertia properties of a rigid body. We begin by describing the kinetic energy of a system of independently moving particles.

Because kinetic energy is a scalar, we obtain the total energy  $T$  of the system by adding the values for each particle:

$$T = \sum_{j=1}^N \frac{1}{2} m_j \bar{v}_j \cdot \bar{v}_j. \quad (5.1.25)$$

Let  $B$  denote an arbitrary reference point to which the velocity of all particles is referred, so that  $\bar{v}_j = \bar{v}_B + \bar{v}_{j/B}$ . The corresponding form for the system's kinetic energy is

$$\begin{aligned} T &= \sum_{j=1}^N \frac{1}{2} m_j (\bar{v}_B + \bar{v}_{j/B}) \cdot (\bar{v}_B + \bar{v}_{j/B}) \\ &= \sum_{j=1}^N \frac{1}{2} m_j (\bar{v}_B \cdot \bar{v}_B + 2\bar{v}_B \cdot \bar{v}_{j/B} + \bar{v}_{j/B} \cdot \bar{v}_{j/B}). \end{aligned} \quad (5.1.26)$$

We factor out of each sum terms that are independent of the particle number, which yields

$$T = \frac{1}{2} m_{\text{system}} \bar{v}_B \cdot \bar{v}_B + \bar{v}_B \cdot \sum_{j=1}^N \frac{d}{dt} (m_j \bar{r}_{j/B}) + \frac{1}{2} \sum_{j=1}^N m_j \bar{v}_{j/B} \cdot \bar{v}_{j/B}. \quad (5.1.27)$$

We recognize the first sum as the time derivative of the first moment of mass relative to point  $B$ . In view of Eq. (5.1.11), we find that

$$T = \frac{1}{2} m_{\text{system}} \bar{v}_B \cdot \bar{v}_B + m_{\text{system}} \bar{v}_B \cdot \bar{v}_{G/B} + \frac{1}{2} \sum_{j=1}^N m_j \bar{v}_{j/B} \cdot \bar{v}_{j/B}. \quad (5.1.28)$$

One viewpoint of this expression is that the kinetic energy of any system of particles is associated with three effects: translation of all particles following the reference point (the first term above), motion of the particles relative to the reference point (the third

term), and a coupling of the motions of the reference point and of the center of mass relative to the reference point.

Our interest is the kinetic energy of a rigid body. We restrict point  $B$  to be stationary relative to the body, so that the relative velocity of any material point is  $\bar{v}_{j/B} = \bar{\omega} \times \bar{r}_{j/B}$ . The kinetic energy correspondingly becomes

$$T = \frac{1}{2} m \bar{v}_B \cdot \bar{v}_B + m \bar{v}_B \cdot (\bar{\omega} \times \bar{r}_{G/B}) + \frac{1}{2} \sum_{j=1}^N m_j (\bar{\omega} \times \bar{r}_{j/B}) \cdot (\bar{\omega} \times \bar{r}_{j/B}). \quad (5.1.29)$$

The sum may be written in a more recognizable form by use of an identity for the scalar triple product:

$$(\bar{a} \times \bar{b}) \cdot \bar{c} \equiv \bar{a} \cdot (\bar{b} \times \bar{c}). \quad (5.1.30)$$

We employ this identity with  $\bar{a} = \bar{\omega}$ ,  $\bar{b} = \bar{r}_{j/B}$ , and  $\bar{c} = \bar{\omega} \times \bar{r}_{j/B}$ , which yields

$$T = \frac{1}{2} m \bar{v}_B \cdot \bar{v}_B + m \bar{v}_B \cdot (\bar{\omega} \times \bar{r}_{G/B}) + \frac{1}{2} \sum_{j=1}^N m_j \bar{\omega} \cdot [\bar{r}_{j/B} \times (\bar{\omega} \times \bar{r}_{j/B})]. \quad (5.1.31)$$

Because  $\bar{\omega}$  is an overall property of the motion, it may be factored out of the sum. The terms that remain are recognizable from Eq. (5.1.21) as the angular momentum relative to point  $B$ , so that

$$T = \frac{1}{2} m \bar{v}_B \cdot \bar{v}_B + m \bar{v}_B \cdot (\bar{\omega} \times \bar{r}_{G/B}) + \frac{1}{2} \bar{\omega} \cdot \bar{H}_B. \quad (5.1.32)$$

To simplify this expression we restrict point  $B$  to fit either of the first two criteria for an allowable point, that is, the center of mass or the pivot point for a body in pure rotation. Either choice cancels the second term. (Other choices for point  $B$  would achieve the same simplification, such as selecting it to be the instant center for a general planar motion, but there is little need to consider them.) Thus the alternatives we employ to evaluate the kinetic energy of a rigid body are

$$\boxed{\begin{aligned} T &= \frac{1}{2} m \bar{v}_G \cdot \bar{v}_G + \frac{1}{2} \bar{\omega} \cdot \bar{H}_G: \text{any type of motion,} \\ T &= \frac{1}{2} \bar{\omega} \cdot \bar{H}_O: \text{pure rotation about point } O. \end{aligned}} \quad (5.1.33)$$

The fact that there are two ways to describe the kinetic energy of a body in pure rotation leads to a relation whereby the angular momentum may be transferred between points. Suppose we were to hold some point  $P$  in a body stationary, in which case the velocity of the center of mass would be  $\bar{\omega} \times \bar{r}_{G/P}$ . The alternative descriptions of the kinetic energy in that case would require that

$$T = \frac{1}{2} \bar{\omega} \cdot \bar{H}_P = \frac{1}{2} m (\bar{\omega} \times \bar{r}_{G/P}) \cdot (\bar{\omega} \times \bar{r}_{G/P}) + \frac{1}{2} \bar{\omega} \cdot \bar{H}_G. \quad (5.1.34)$$

## 5.1 Linear and Angular Momentum

237

A rearrangement of terms based on Eq. (5.1.30) leads to


$$T = \frac{1}{2} \bar{\omega} \cdot \bar{H}_P = \frac{1}{2} m \bar{\omega} \cdot [\bar{r}_{G/P} \times (\bar{\omega} \times \bar{r}_{G/P})] + \frac{1}{2} \bar{\omega} \cdot \bar{H}_G. \quad (5.1.35)$$

This relation must be true for any angular velocity, so the factor of  $\bar{\omega}$  in the dot product on either side of the equality sign must match. It is useful for later work to use  $\bar{r}_{P/G} = -\bar{r}_{G/P}$ , from which it follows that

$$\bar{H}_P = \bar{H}_G + m \bar{r}_{P/G} \times (\bar{\omega} \times \bar{r}_{P/G}). \quad (5.1.36)$$

There seldom is need to transfer angular momentum between points. However, Eq. (5.1.36) will soon prove to be useful for our exploration of inertial properties.

**EXAMPLE 5.1** Identical small spheres having mass  $m$  are welded to the ends of a rigid bar that spins about the axis of the motor at angular speed  $\omega_1$ . The motor is mounted on the horizontal turntable, which rotates at angular speed  $\omega_2$ . Determine the angular momentum of this pair of particles about point  $C$  where the connecting bar is welded to the motor's shaft. Then use the angular momentum to characterize the force system exerted on the connecting bar at point  $C$ , as well as the kinetic energy of these spheres. Express the result in terms of the angle  $\theta$  from the bar's centerline to vertical.



Example 5.1

**SOLUTION** The intent of this problem is to provide visualizations that will lessen the abstract nature of the development thus far, and also bring to the fore aspects that distinguish the kinetics of spatial motion from the simpler case of planar motion. Both spheres, being small, are treated as particles. They are fastened to the massless rigid body formed by the connecting bar and the motor's shaft. Point  $O$  is also a point in this body, and  $\bar{v}_O \equiv \bar{0}$ . Thus point  $O$  is an allowable point for the moment equation. The center of mass  $G$  of the pair of particles is halfway between them, which is the attachment point of the bar to the motor's shaft. This is always an allowable point.

The angular velocity of the bar/shaft system is

$$\bar{\omega} = \omega_1 \bar{e}_1 + \omega_2 \bar{e}_2.$$

To describe the unit vector for each rotation, we let  $x'y'z'$  be a coordinate system attached to the turntable with its origin  $O$  at the center of the turntable. The  $z'$  axis

is vertical and the  $x'$  axis is aligned with the shaft, such that  $\bar{e}_1 = -\bar{i}'$  and  $\bar{e}_2 = \bar{k}'$ . The angular velocity of the connecting bar is then given by

$$\bar{\omega} = -\omega_1 \bar{i}' + \omega_2 \bar{k}'. \quad (1)$$

To evaluate the angular momentum with respect to point  $C$ , we form the position vector to each sphere. In terms of components relative to  $x'y'z'$ , these are

$$\bar{r}_{1/C} = R \sin \theta \bar{j}' + R \cos \theta \bar{k}' = -\bar{r}_{2/C}. \quad (2)$$

Equation (5.1.21) for this two-particle system is

$$\bar{H}_C = 2m_1 [\bar{r}_{1/C} \times (\bar{\omega} \times \bar{r}_{1/C})].$$

The result of substituting Eqs. (1) and (2) into this expression is

$$\bar{H}_C = -2m R^2 \omega_1 \bar{i}' - 2m R^2 \omega_2 (\sin \theta) (\cos \theta) \bar{j}' + 2m R^2 \omega_2 (\sin \theta)^2 \bar{k}'. \quad (3) \triangleleft$$

The first feature to note is that some components of  $\bar{H}_C$  are not constant, even though  $\bar{\omega}$  has constant components relative to  $x'y'z'$ . Furthermore, the orientations of both  $\bar{i}'$  and  $\bar{j}'$  are variable. This feature typifies the fundamental fact that, even though the rotation rates in spatial motion might be constant, the angular momentum will not be a constant vector. Moments are required to change the angular momentum, regardless of whether the change of the angular momentum is a result of components having a variable direction or magnitude. It follows that the shaft must exert a moment on the connecting bar in order to produce the specified motion.

To evaluate the force system that the motor's shaft must apply, we consider a rigid body consisting of the two spheres and the connecting bar. If the rotation rates are sufficiently high, the gravitational forces will be negligible, in which case the only significant forces acting on this body are exerted by the motor's shaft. Point  $C$  is the body's center of mass, and this point follows a circular path of radius  $L$ , so the resultant force exerted by the shaft is found from Eq. (5.1.13) to be

$$\bar{F}_{\text{shaft}} = m_{\text{body}} \bar{a}_C = 2m (-L \omega_2^2 \bar{i}'). \quad (4) \triangleleft$$

Similar reasoning indicates that the only significant moment acting on the two-sphere rigid body is a couple exerted by the shaft. According to Eq. (5.1.22), this couple must equal the rate at which  $\bar{H}_C$  changes. To differentiate the components of the angular momentum in Eq. (3) we observe that  $\dot{\theta} = \omega_1$ , whereas the derivatives of the unit vectors follow from the fact that the angular velocity of  $x_1 y_1 z_1$  is  $\omega_2 \bar{k}'$ , so that

$$\begin{aligned} \bar{M}_{\text{shaft}} = \frac{d\bar{H}_C}{dt} &= \omega_1 \frac{\partial}{\partial \theta} \left[ -2m R^2 \omega_2 (\sin \theta) (\cos \theta) \bar{j}' + 2m R^2 \omega_2 (\sin \theta)^2 \bar{k}' \right] \\ &\quad - 2m R^2 \omega_1 (\omega_2 \bar{k}' \times \bar{i}') - 2m R^2 \omega_2 (\sin \theta) (\cos \theta) (\omega_2 \bar{k}' \times \bar{j}') \\ &\quad + 2m R^2 \omega_2 (\sin \theta)^2 (\omega_2 \bar{k}' \times \bar{k}'). \end{aligned}$$

## 5.1 Linear and Angular Momentum

239

Carrying out these operations yields

$$\begin{aligned}\bar{M}_{\text{shaft}} &= 2mR^2\omega_2^2 \sin\theta \cos\theta \bar{i} - 4mR^2\omega_1\omega_2 (\cos\theta)^2 \bar{j}' \\ &\quad + 4mR^2\omega_1\omega_2 (\sin\theta) (\cos\theta) \bar{k}'.\end{aligned}\quad (5)$$

The kinetic energy of the two-particle rigid body may be evaluated from Eq. (5.1.33). Point  $C$  is the center of mass, and we already have  $\bar{\omega}$  and  $\bar{H}_C$ . The speed of the center of mass is  $L\omega_2$ , so we find that

$$\begin{aligned}T &= \frac{1}{2}(2m)(L\omega_2)^2 + \frac{1}{2}(-\omega_1\bar{i}' + \omega_2\bar{k}') \cdot \bar{H}_C \\ &= mR^2\omega_1^2 + m\omega_2^2 \left[ L^2 + R^2(\sin\theta)^2 \right].\end{aligned}\quad (6)$$

It is not necessary to introduce angular momentum to derive these results. Instead, we can consider each sphere individually. We use point  $C$  as the reference for the kinematical analysis. Because  $\bar{r}_{1/C} = -\bar{r}_{1/C}$ , the velocities are

$$\begin{aligned}\bar{v}_1 &= \bar{v}_C + \bar{\omega} \times \bar{r}_{1/C} \\ &= -R\omega_2 \sin\theta \bar{i}' + (\omega_1 R \cos\theta + L\omega_2) \bar{j}' - \omega_1 R \sin\theta \bar{k}', \\ \bar{v}_2 &= \bar{v}_C + \bar{\omega} \times \bar{r}_{2/C} \\ &= R\omega_2 \sin\theta \bar{i}' + (-\omega_1 R \cos\theta + L\omega_2) \bar{j}' + \omega_1 R \sin\theta \bar{k}'.\end{aligned}$$

The result of using these expressions to evaluate the kinetic energy according to  $\frac{1}{2}m\bar{v}_1 \cdot \bar{v}_1 + \frac{1}{2}m\bar{v}_2 \cdot \bar{v}_2$  would be identical to Eq. (6).

To examine the force system exerted by the shaft we describe each sphere's acceleration relative to point  $C$ , according to

$$\begin{aligned}\bar{a}_1 &= \bar{a}_C + \bar{a}_{1/C}, \quad \bar{a}_2 = \bar{a}_C + \bar{a}_{2/C}, \\ \bar{a}_{1/C} &= -\bar{a}_{2/C} = \bar{\alpha} \times \bar{r}_{1/C} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{1/C}).\end{aligned}\quad (7)$$

The angular velocity is given in Eq. (1), and the angular acceleration is

$$\bar{\alpha} = -\omega_1 (\omega_2 \bar{k}' \times \bar{i}') = -\omega_1 \omega_2 \bar{j}',$$

which leads to

$$\bar{a}_{1/C} = -2R\omega_1\omega_2 \cos\theta \bar{i}' - R(\omega_1^2 + \omega_2^2) \sin\theta \bar{j}' - \omega_1^2 R \cos\theta \bar{k}'. \quad (8)$$

We use these expressions to form the force and moment sums for the system consisting of the two spheres and the connecting bar. Specifically, we apply  $\Sigma \bar{F}_n = m\bar{a}_n$  to each particle and use Eqs. (7) to describe each acceleration. Because the force exerted by the connecting bar on each sphere is internal to this system, the result is


$$\Sigma \bar{F} = \bar{F}_{\text{shaft}} = m_1\bar{a}_1 + m_2\bar{a}_2 = 2m\bar{a}_C.$$

This is the same as the force described by Eq. (4).

The forces exerted by the connecting bar also disappear from a moment sum for the system. Application of Eqs. (7) in conjunction with  $\bar{r}_{2/C} = -\bar{r}_{1/C}$  leads to

$$\Sigma \bar{M}_C = \bar{M}_{\text{shaft}} = \bar{r}_{1/C} \times m_1 \bar{a}_1 + \bar{r}_{2/C} \times m_2 \bar{a}_2 = m \bar{r}_{1/C} \times \bar{a}_{1/C} + m \bar{r}_{2/C} \times \bar{a}_{2/C}.$$

The sketch shows the acceleration of each sphere relative to point C, which when multiplied by  $m$  become the forces that contribute to the moment sum. Inspection of this diagram shows that for each particle the sum of the  $z'$  component and the portion of the  $y'$  component that is due to  $\omega_1$  is a vector that acts from each sphere toward point C. It follows that these forces do not contribute to the moment sum. Consequently, the moment exerted by the shaft is formed from two couples. The  $x'$  components form a couple that is  $(2m R \omega_1 \omega_2 \cos \theta) (2R)$  acting perpendicular to the connecting bar. The unit vector for this couple is  $-\cos \theta \bar{j}' + \sin \theta \bar{k}'$ . The other couple, which is formed from the remaining portion of the  $y'$  components of relative acceleration, is  $(m R \omega_2^2 \sin \theta) (2R \cos \theta)$ . This couple acts about the  $x'$  axis. The sum of these couples is the same as Eq. (5).



Position and acceleration components of each sphere relative to point C at which the connecting rod is joined to the motor's shaft

This discussion explains in fundamental terms why moments are required to sustain a spatial motion in which all rotation rates are constant. Because particles have acceleration components that do not lie in a common plane, the forces required to accelerate these particles exert moments about several axes. For the system of two interconnected spheres the analysis using angular momentum was merely an alternative approach, but it will be the only viable one for bodies whose size is not negligible.

## 5.2 INERTIA PROPERTIES

It is inconceivable to evaluate the angular momentum of a rigid body by adding the contribution of each of its atomic particles. Our approach is to model the rigid body


## 5.2 Inertia Properties

241

as a continuous distribution of mass, which will permit us to apply the principles of calculus. The result will be an expression for the angular momentum that features a set of numbers characterizing the manner in which mass is distributed in the body.

### 5.2.1 Moments and Products of Inertia

In a continuum model of a rigid body the particles are differential elements of mass  $dm$  having infinitesimal dimensions. These elements fill the region occupied by the body. In this viewpoint, any summation over the particles forming the body becomes an integral over the body's domain. In Fig. 5.3,  $xyz$  is a global coordinate system whose origin  $A$  is an allowable point for the moment equation of motion.



**Figure 5.3.** Differential element of mass  $dm$  relative to a body-fixed  $xyz$  reference frame.

In terms of components relative to  $xyz$  the position vector  $\bar{r}_{i/A}$  and angular velocity  $\bar{\omega}$  are

$$\bar{r}_{i/A} = x\bar{i} + y\bar{j} + z\bar{k}, \quad \bar{\omega} = \omega_x\bar{i} + \omega_y\bar{j} + \omega_z\bar{k}. \quad (5.2.1)$$

We substitute these expressions into Eq. (5.1.21) for the angular momentum and convert the summation to an integral. This transforms the general relation to

$$\bar{H}_A = \iiint (x\bar{i} + y\bar{j} + z\bar{k}) \times [(\omega_x\bar{i} + \omega_y\bar{j} + \omega_z\bar{k}) \times (x\bar{i} + y\bar{j} + z\bar{k})] dm. \quad (5.2.2)$$

The result of evaluating the cross products is an integrand that consists of  $\bar{i}$ ,  $\bar{j}$ , and  $\bar{k}$  components. Each component may be integrated individually. Furthermore, the rotation rates are overall properties of the motion, rather than functions of the position within the body. Consequently,  $\omega_x$ ,  $\omega_y$ , and  $\omega_z$  may be factored out of each integral. The result is

$$\begin{aligned} \bar{H}_A = & (I_{xx}\omega_x - I_{xy}\omega_y - I_{xz}\omega_z)\bar{i} + (I_{yy}\omega_y - I_{yx}\omega_x - I_{yz}\omega_z)\bar{j} \\ & + (I_{zz}\omega_z - I_{zx}\omega_x - I_{zy}\omega_y)\bar{k}, \end{aligned} \quad (5.2.3)$$

where

$$\begin{aligned} I_{xx} = \iiint (y^2 + z^2) dm, \quad I_{yy} = \iiint (x^2 + z^2) dm, \quad I_{zz} = \iiint (x^2 + y^2) dm, \\ I_{xy} = I_{yx} = \iiint xy dm, \quad I_{xz} = I_{zx} = \iiint xz dm, \quad I_{yz} = I_{zy} = \iiint yz dm. \end{aligned} \quad (5.2.4)$$



The terms  $I_{pp}$  (repeated subscripts) are *moments of inertia* about the three coordinate axes, and the terms  $I_{pq}$  (nonrepeated subscripts) are *products of inertia*. The vector description of  $\bar{H}_A$  may be written alternatively in matrix form as


$$\{H_A\} = [I] \{\omega\}, \quad (5.2.5)$$

where  $\{H_A\}$  and  $\{\omega\}$  are formed from the components of  $\bar{H}_A$  and  $\bar{\omega}$ , respectively, and  $[I]$  is the *inertia matrix*:

$$[I] = \begin{bmatrix} I_{xx} & -I_{xy} & -I_{xz} \\ -I_{yx} & I_{yy} & -I_{yz} \\ -I_{zx} & -I_{zy} & I_{zz} \end{bmatrix}. \quad (5.2.6)$$

The matrix representation will be seen to be quite useful in conjunction with mathematical software. The inertia matrix, combined with the mass and the location of the center of mass, fully characterizes the inertia properties of a rigid body.\*

The moments of inertia are properties encountered in planar motion. The similarity of any  $I_{pp}$  to the parameter for planar motion may be realized by looking down the  $p$  axis. Such a view for  $I_{zz}$  is shown in Fig. 5.4. The distance  $R = (x^2 + y^2)^{1/2}$  is the perpendicular distance from the  $z$  axis to the mass element  $dm$ . Thus  $I_{zz}$  is the sum for all mass elements of the  $R^2$  values weighted by  $dm$ .



**Figure 5.4.** Contribution of an element of mass to the moment of inertia about the  $z$  axis.

A common way to prescribe a moment of inertia is to give its *radius of gyration*,


$$\kappa_p = \left( \frac{I_{pp}}{m} \right)^{1/2}. \quad (5.2.7)$$

Consider a thin ring whose mass is situated on a circle of radius  $\kappa_p$ , with  $p$  being the axis perpendicular to the plane of the ring and intersecting the center. The distance from this axis to any mass element is  $\kappa_p$ , so the integral of  $R^2 dm$  reduces to  $\kappa_p^2$  multiplied by the integral of the mass, in other words,  $I_{pp} = m\kappa_p^2$ . Thus a radius of gyration describes a circular ring whose mass is the same as the body of interest and whose moment of inertia about its axis of symmetry  $p$  is identical to  $I_{pp}$  for the body. Because  $I_{pp}$  is the sum of the  $R^2 dm$  values, the radius of gyration cannot exceed the largest distance from axis  $p$  to

\* The definitions of products of inertia in Eqs. (5.2.4) are opposite in sign to those used by some individuals. The present definitions are based on indicating quadrants in which mass is dominant. The alternative definition gives an inertia matrix whose off-diagonal elements equal the products of inertia.

## 5.2 Inertia Properties

243



**Figure 5.5.** The significance of a product of inertia as a measure of deviation from symmetry.

a mass point in the body. This knowledge can be quite useful when one wishes to make an order-of-magnitude estimate of the moments of inertia of a given body.

In contrast to the moments of inertia, which depend on how far mass is situated from each coordinate axis, the products of inertia describe the degree to which mass is distributed symmetrically relative to the three coordinate planes. Figure 5.5 shows the cross section of a body at an arbitrary value of  $z$ . The dotted region is the mirror image of the cross section, which one obtains by flipping it about the  $y$  axis. The shaded area is the union of the cross section and its mirror image. Two mass elements on either side of the  $yz$  plane are depicted in Fig. 5.5. The  $x$  coordinate for the left element is the negative of the  $x$  coordinate for the right element, whereas their  $y$  and  $z$  coordinates are the same. If the density is the same for both elements, then they have the same mass  $dm$ . In that case the values of  $xy\,dm$  and  $xz\,dm$  for the left element are the negative of the corresponding values for the right element, so their combined contributions to  $I_{xy}$  and  $I_{xz}$  are zero. It follows that the total contribution to  $I_{xy}$  and  $I_{xz}$  of all mass elements situated in the shaded region of Fig. 5.5 is zero. The unshaded portions of the cross section have no mirror image on the other side of the  $yz$  plane. The sign marking each such region indicates whether the product  $xy$  is positive or negative within that region. The situation in the figure is one in which the unbalanced regions correspond mostly to positive  $xy$ . Thus, if the density is constant over the cross section, the net contribution of this cross section to  $I_{xy}$  would be positive. Similar reasoning applies for  $I_{xz}$ . One should note, however, that the actual values of  $I_{xy}$  and  $I_{xz}$  for this body cannot be judged solely from the figure, because they depend on the combined contribution of all cross sections.

From the preceding considerations, we conclude that a positive value of  $I_{pq}$  indicates that the mass of the body is predominantly situated in either or both of the quadrants where the  $p$  and  $q$  coordinates have the same sign, whereas negative  $I_{pq}$  means that mass is predominant in the quadrants where  $p$  and  $q$  have opposite sign. We obtain an important corollary of the discussion by considering a situation in which the shaded region in Fig. 5.5 is the actual cross section and the density at the mirror image points is the same. In that case the contributions to  $I_{xy}$  and  $I_{xz}$  of this cross section will vanish. If the same is true for all cross sections, then the body is symmetric with respect to the  $yz$  plane, and  $I_{xy} = 0$  and  $I_{xz} = 0$ . Similar conclusions would result if we were to consider symmetry with respect to the  $xz$  or  $xy$  plane. The fact that the  $z$  axis is normal to the plane of symmetry for the situation in the figure leads to this generalization:

If two coordinate axes form a plane of symmetry for a body, then all products of inertia involving the coordinate normal to that plane are zero.

A further corollary is

If at least two of the three coordinate planes are planes of symmetry for a body, then all products of inertia are zero.

The condition of perpendicular planes of symmetry is attained for any body of revolution if the axis of symmetry coincides with a coordinate axis. Whenever the coordinate axes correspond to vanishing values of all products of inertia, they are said to be *principal axes*. We will soon see that it is possible to identify principal axes for any body, regardless of its symmetry properties.

**EXAMPLE 5.2** Evaluate the inertia properties of the pair of particles in Example 5.1 relative to the  $x'y'z'$  coordinate system defined there. Then use those properties to determine  $\bar{H}_A$ .

**SOLUTION** This example uses a simple system to illustrate the significance of the inertia properties. It also provides some insight that will be useful to later developments concerning the rate of change of  $\bar{H}_A$ . The two particles and their massless connecting rod form the rigid body of interest here. Each particle may be considered to be an element of mass. Correspondingly, the integral reduces to a single term for each particle. The  $z'$  axis in Example 5.1 was defined to be vertical, and the  $x'$  axis is aligned with the motor's rotation axis. The position of the particles in terms of components relative to  $x'y'z'$  was found previously to be

$$\bar{r}_{1/O} = L\bar{i}' + R\sin\theta\bar{j}' + R\cos\theta\bar{k}', \quad \bar{r}_{2/O} = L\bar{i}' - R\sin\theta\bar{j}' - R\cos\theta\bar{k}'.$$

Because the components are the respective values of  $x'$ ,  $y'$ , and  $z'$  for each particle, Eqs. (5.2.4) for the present situation reduce to

$$\begin{aligned} I_{x'x'} &= m(y_1^2 + z_1^2) + m(y_2^2 + z_2^2) = 2mR^2, \\ I_{y'y'} &= m(x_1^2 + z_1^2) + m(x_2^2 + z_2^2) = 2mL^2 + 2mR^2(\cos\theta)^2, \\ I_{z'z'} &= m(x_1^2 + y_1^2) + m(x_2^2 + y_2^2) = 2mL^2 + 2mR^2(\sin\theta)^2, \\ I_{x'y'} &= I_{y'x'} = mx_1y_1 + mx_2y_2 = 0, \\ I_{x'z'} &= I_{z'x'} = mx_1z_1 + mx_2z_2 = 0, \\ I_{y'z'} &= I_{z'y'} = my_1z_1 + my_2z_2 = 2mR^2\sin\theta\cos\theta = mR^2\sin(2\theta). \end{aligned}$$

The products of inertia indicate that there is a balanced mass distribution relative to the  $x'y'$  and  $x'z'$  quadrants, and the mass is situated in the two quadrants where  $y'z'$  are positive whenever  $\sin(2\theta)$  is positive, that is,  $0 < \theta < \pi/2$  and  $\pi < \theta < 3\pi/2$ .

To evaluate  $\bar{H}_A$  we recall from the previous example that the angular velocity of the assembly of the two particles and the connecting rod is the sum of the rotation rates  $\omega_2$  about the vertical and  $\omega_1$  of the motor. We previously found that

$$\bar{\omega} = -\omega_1\bar{i}' + \omega_2\bar{k}'.$$

## 5.2 Inertia Properties

245

The components are  $\omega_{x'} = -\omega_1$ ,  $\omega_{y'} = 0$ ,  $\omega_{z'} = \omega_2$ . Correspondingly, Eq. (5.2.3) gives


$$\begin{aligned}\bar{H}_A &= [2mR^2(-\omega_1) - 0(0) - 0(\omega_2)]\bar{i}' \\ &+ \left\{ [2mL^2 + 2mR^2(\cos\theta)^2](0) - 0(-\omega_1) - (2mR^2\sin\theta\cos\theta)(\omega_2) \right\}\bar{j}' \\ &+ \left\{ [2mL^2 + 2mR^2(\sin\theta)^2](\omega_2) - 0 - (2mR^2\sin\theta\cos\theta)(0) \right\}\bar{k}'.\end{aligned}$$

The preceding exemplifies a general observation that many terms in the standard formula for angular momentum usually vanish because either a product of inertia or a component of  $\bar{\omega}$  is zero. The present result reduces to

$$\bar{H}_A = -2mR^2\omega_1\bar{i}' - 2mR^2\omega_2\sin\theta\cos\theta\bar{j}' + 2m[L^2 + R^2(\sin\theta)^2]\omega_2\bar{k}'. \quad \triangleleft$$

This is the same as the expression we derived in Example 5.1 by actually evaluating moments of the relative momenta.

**EXAMPLE 5.3** Derive the inertia matrix of the quarter-sphere about the  $xyz$  axes; then use that result to obtain the inertia matrix for a quarter-spherical shell whose skin thickness is  $d \ll a$ . Express each result in terms of the mass  $m$  of that body.



Example 5.3

**SOLUTION** Although we usually use other techniques to evaluate the inertia matrix, integration is a basic tool. This example illustrates some procedures that were used to derive the properties tabulated in the Appendix. Spherical coordinates with an origin at the center are ideal here because the quarter-sphere's surfaces correspond to constant values of one of these coordinates. Any coordinate axis may be employed as the reference for the polar angle  $\phi$ ; we select the  $y$  axis, so the azimuthal angle  $\theta$  is measured in the  $xz$  plane relative to the  $x$  axis. The coordinate transformation is

$$y = r \cos \phi, \quad x = r \sin \phi \cos \theta, \quad z = r \sin \phi \sin \theta.$$

The body occupies the domain  $0 \leq r \leq a$ ,  $0 \leq \phi \leq \pi/2$ ,  $0 \leq \theta \leq \pi$ , and a differential element of mass is  $dm = \rho(dr)(rd\phi)(rd\theta \sin \phi)$ . The body is symmetric with

respect to the  $yz$  plane, so the two products of inertia containing  $x$  as the subscript are zero:

$$I_{xy} = I_{xz} = 0. \quad \triangleleft$$

Also, the symmetry of the quarter-sphere is such that mass is situated in the same manner relative to the  $y$  and  $z$  axes, so  $I_{zz} = I_{yy}$ . Thus it is necessary to compute only  $I_{xx}$ ,  $I_{yy}$ , and  $I_{yz}$ .

The integral definitions, Eqs. (5.2.4), give

$$\begin{aligned} I_{xx} &= \int_0^a \int_0^{\pi/2} \int_0^\pi (y^2 + z^2) \rho r^2 \sin \phi \, d\theta \, d\phi \, dr \\ &= \rho \int_0^a \int_0^{\pi/2} \int_0^\pi \left[ (r \cos \phi)^2 + (r \sin \phi \sin \theta)^2 \right] r^2 \sin \phi \, d\theta \, d\phi \, dr, \\ I_{yy} &= \int_0^a \int_0^{\pi/2} \int_0^\pi \left[ (r \sin \phi \cos \theta)^2 + (r \sin \phi \sin \theta)^2 \right] \rho r^2 \sin \phi \, d\theta \, d\phi \, dr, \\ I_{zz} &= \int_0^a \int_0^{\pi/2} \int_0^\pi \left[ (r \sin \phi \cos \theta)^2 + (r \cos \phi)^2 \right] \rho r^2 \sin \phi \, d\theta \, d\phi \, dr, \\ I_{yz} &= \int_0^a \int_0^{\pi/2} \int_0^\pi yz \rho r^2 \sin \phi \, d\theta \, d\phi \, dr \\ &= \rho \int_0^a \int_0^{\pi/2} \int_0^\pi (\cos \phi) (\sin \phi \sin \theta) r^4 \sin \phi \, d\theta \, d\phi \, dr. \end{aligned}$$

The results are

$$I_{xx} = I_{yy} = I_{zz} = \frac{2\pi}{15} \rho a^5, \quad I_{yz} = \frac{2}{15} \rho a^5.$$

To express the inertia properties in terms of the mass  $m$ , the density is expressed as the ratio of the mass to the volume of a quarter-sphere:

$$\rho = \frac{m}{V} = \frac{m}{\frac{1}{4} \left( \frac{4\pi a^3}{3} \right)} = \frac{3m}{\pi a^3}.$$

We substitute for  $\rho$  in each of the inertia properties and recall from Eq. (5.2.6) that the off-diagonal terms of the inertia matrix are the negative of the products of inertia. The result is

$$[I] = \frac{2}{5} m a^2 \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & -1/\pi \\ 0 & -1/\pi & 1 \end{bmatrix}. \quad \triangleleft$$

A shell is a body whose mass is concentrated at its surface. There are two procedures for obtaining the inertia properties of the quarter-spherical shell. The general one specializes the differential element of mass. Let  $\sigma$  be the mass per

## 5.2 Inertia Properties

247

unit surface area. A differential element of surface area in spherical coordinates is  $dS = (a d\phi)(a \sin \phi d\theta)$ . The surface is defined by  $0 \leq \phi \leq \pi/2$ ,  $0 \leq \theta \leq \pi$ . We modify the integrals for the quarter-sphere, with  $r = a$  for points on the surface and  $dm = \sigma dS$ , which leads to

$$\begin{aligned} I_{xx} &= \int_0^{\pi/2} \int_0^{\pi} \left[ (a \cos \phi)^2 + (a \sin \phi \sin \theta)^2 \right] \sigma a^2 \sin \phi d\theta d\phi = \frac{2}{3} \pi \sigma a^4, \\ I_{yy} &= \int_0^{\pi/2} \int_0^{\pi} \left[ (a \sin \phi \cos \theta)^2 + (a \sin \phi \sin \theta)^2 \right] \sigma a^2 \sin \phi d\theta d\phi = \frac{2}{3} \pi \sigma a^4, \\ I_{zz} &= \int_0^{\pi/2} \int_0^{\pi} \left[ (a \sin \phi \cos \theta)^2 + (a \cos \phi)^2 \right] \sigma a^2 \sin \phi d\theta d\phi = \frac{2}{3} \pi \sigma a^4, \\ I_{yz} &= \int_0^{\pi/2} \int_0^{\pi} (a \cos \phi)(a \sin \phi \sin \theta) \sigma a^3 \sin \phi d\theta d\phi = \frac{2}{3} \sigma a^4. \end{aligned}$$

The surface area of a sphere is  $4\pi a^2$ , so the mass per unit surface area is related to the mass of the quarter-spherical shell by

$$\sigma = \frac{m_{\text{shell}}}{\frac{1}{4}(4\pi a^2)}.$$

Substitution of this expression into the inertia values leads to

$$[I] = \frac{2}{3} m_{\text{shell}} a^2 \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & -1/\pi \\ 0 & -1/\pi & 1 \end{bmatrix}. \quad \triangleleft$$

An alternative is to derive the properties of the shell from those of the full body. We may obtain the shell by removing from the quarter-sphere a concentric quarter-sphere whose radius is  $a - h$ , where  $h$  is the thickness of the shell. Because the origins of  $xyz$  for both the original and removed bodies coincide, the inertia properties of the shell are the difference of the values for the two full bodies. We form the differences by using the original forms, which featured the density, so that

$$\begin{aligned} I_{xx} = I_{yy} = I_{zz} &= \frac{2}{15} \pi \rho a^5 - \frac{2}{15} \pi \rho (a - h)^5 = \frac{2}{15} \pi \rho (5a^4 h + \dots), \\ I_{yz} &= \frac{2}{15} \rho a^5 - \frac{2}{15} \rho (a - h)^5 = \frac{2}{15} \rho (5a^4 h + \dots). \end{aligned}$$

Higher powers of  $h$  are omitted because the definition of a shell is that its thickness is very small compared with the overall dimensions. The density is the ratio of the shell's mass to its volume:

$$\rho = \frac{m_{\text{shell}}}{V} = \frac{m_{\text{shell}}}{\frac{1}{4} \left[ \frac{4\pi a^3}{3} - \frac{4\pi (a - h)^3}{3} \right]} = \frac{m_{\text{shell}}}{\pi (a^2 h + \dots)}.$$

Substitution of this description of  $\rho$  into the last set of expressions for the inertia properties would yield the same results as those obtained by integration.

**EXAMPLE 5.4** A first-order correction for the mass distribution of the Earth is to take it to be an oblate spheroid with the polar axis as the axis of symmetry. A consequence of this deviation from sphericity, combined with the tilt of the polar axis relative to the Earth's orbital plane about the Sun, and the Moon's orbital plane about the Earth, is that the forces exerted by those bodies do not exactly act at the Earth's center. The task here is to characterize the gravitational attraction of the Sun and the Moon as force–couple systems acting at the Earth's center.

**SOLUTION** This example will lead to a different perspective to the meaning of “center of mass,” as well as recognition that the inertia properties can occur in contexts other than evaluation of angular momentum. The usage of the first moment of mass to locate the point at which the resultant gravitational force acts originates from considering the force of gravity to be constant. The analysis we carry out here, in which the inverse square law is used to describe the force exerted by the Sun on each of particle of the Earth's mass, is required to explain some features of the Earth's rotation. In particular, the result will be a crucial piece of our analysis in Chapter 10 of *precession of the equinoxes*, which is manifested by variability in the dates when the seasons change.

We begin by recalling the inverse square law for gravitational force exerted by a large spherical body on a particle:

$$\bar{F} = \frac{Gm_s m}{r^2} \bar{e}_r,$$


where  $m$  and  $m_s$  are the masses of the particle and the attracting body,  $r$  is the distance from the particle to the center of the other body,  $\bar{e}_r$  is the unit vector from the particle to the center of the attracting body, and  $G$  is the universal gravitational constant. The Earth's diameter is much smaller than the distance to either the Sun or the Moon, so the Earth appears to be a dot when viewed from either body, especially the Sun. If we were to set  $r$  equal to the distance  $R$  between the respective centers and take  $\bar{e}_r$  to be constant at  $\bar{e}_R$ , which is the unit vector from the center of the Earth to the center of the other body, we would obtain the conventional representation of the effect of gravity, in which the Earth's center of gravity, at which the gravitational attraction acts, coincides with its center of mass, which is essentially the center of the Earth.

We perform the analysis for the case of the interaction between the Earth and the Sun, then consider what modifications are required to describe the role of the Moon. Let  $xyz$  be a coordinate system whose origin is at the center of the Earth such that the  $z$  axis is the polar axis; this axis is inclined by angle  $\theta$  relative to the normal to the Earth's orbital plane. The  $y$  axis is defined to coincide with the diametral line

## 5.2 Inertia Properties

249

at the Earth's equator that lies in the orbital plane. To describe how the Earth is oriented relative to the Sun define  $x'y'z'$  whose origin also is at the Earth's center. The  $z'$  axis is defined to be normal to the Earth's orbital plane, and  $x'$  is aligned with the unit vector from the center of the Earth to the center of the Sun, so that  $\bar{e}_R = \bar{i}'$ .



This arrangement is depicted in the sketch. The transformation between these coordinates systems is

$$[x \ y \ z]^T = [R][x' \ y' \ z']^T,$$

$$[R] = \begin{bmatrix} \cos \theta & 0 & -\sin \theta \\ 0 & 1 & 0 \\ \sin \theta & 0 & \cos \theta \end{bmatrix} \begin{bmatrix} \cos \beta & \sin \beta & 0 \\ -\sin \beta & \cos \beta & 0 \\ 0 & 0 & 1 \end{bmatrix},$$


where  $\beta$  is the angle between the  $y$  and  $y'$  axes. The first row of  $[R]^T$  consists of the direction cosines of the  $x'$  axis with respect to  $xyz$ , which enables us to describe the direction of the Sun's center in terms of  $xyz$  components,

$$\bar{e}_R = \ell_{x'x}\bar{i} + \ell_{x'y}\bar{j} + \ell_{x'z}\bar{k},$$

where the direction cosines are

$$\ell_{x'x} = \cos \theta \cos \beta, \quad \ell_{x'y} = -\sin \beta, \quad \ell_{x'z} = \sin \theta \cos \beta.$$

The near parallelism of the lines from all particles to the Sun's center assists us in describing the distance and direction of the line from a particle of the Earth to the Sun. In the second sketch, which shows the plane containing a mass particle  $P$ , the center  $O$  of the Earth, and the center  $O'$  of the Sun,  $r$  is the distance from the center of the Sun to the particle and  $\bar{e}_r$  is the direction to point  $O'$ .





It is evident that

$$r\bar{e}_r = R\bar{e}_R - \bar{r}_{P/O}, \quad (1)$$

so the distance is

$$r \equiv (r\bar{e}_r \cdot r\bar{e}_r)^{1/2} = (R^2 + \bar{r}_{P/O} \cdot \bar{r}_{P/O} - 2R\bar{r}_{P/O} \cdot \bar{e}_R)^{1/2}.$$

Because  $|\bar{r}_{P/O}|$  is much smaller than  $R$ , a binomial series expansion of the preceding gives

$$r \approx R - \bar{r}_{P/O} \cdot \bar{e}_R. \quad (2)$$

In turn, substituting this expression into Eq. (1) yields

$$\begin{aligned} \bar{e}_r &= \frac{R\bar{e}_R - \bar{r}_{P/O}}{r} \approx \frac{R}{R - \bar{r}_{P/O} \cdot \bar{e}_R} \bar{e}_R - \frac{\bar{r}_{P/O}}{R} \\ &\approx \left(1 + \frac{\bar{r}_{P/O} \cdot \bar{e}_R}{R}\right) \bar{e}_R - \frac{\bar{r}_{P/O}}{R}. \end{aligned} \quad (3)$$

Equation (2) is used to express the distance in the inverse square law for the gravitational force  $d\bar{F}$  acting on a differential element of mass situated at point  $P$ , and Eq. (3) gives the direction of that force. Application of a binomial series expansion then leads to

$$\begin{aligned} d\bar{F} &= \frac{Gm_s dm}{(R - \bar{r}_{P/O} \cdot \bar{e}_R)^2} \bar{e}_r \\ &\approx \frac{Gm_s dm}{R^2} \left(1 + 2\frac{\bar{r}_{P/O} \cdot \bar{e}_R}{R}\right) \left[\left(1 + \frac{\bar{r}_{P/O} \cdot \bar{e}_R}{R}\right) \bar{e}_R - \frac{\bar{r}_{P/O}}{R}\right] \\ &\approx Gm_s dm \left(\frac{1}{R^2} \bar{e}_R + 3\frac{\bar{r}_{P/O} \cdot \bar{e}_R}{R^3} \bar{e}_R - \frac{\bar{r}_{P/O}}{R^3}\right). \end{aligned} \quad (4)$$

We obtain the resultant force by integrating the contribution associated with each mass element. For this integration, we observe that the only quantity in Eq. (3) that depends on the position of the mass element is  $\bar{r}_{P/O}$ . The integral of  $\bar{r}_{P/O} dm$  is identically zero because it is the first moment of mass and point  $O$  is the center of mass. Thus the resultant force is

$$\bar{F} = \iiint d\bar{F} = \iiint \frac{Gm_s dm}{R^2} \bar{e}_R = \frac{Gm_s m_e}{R^2} \bar{e}_R, \quad (5)$$

where  $m_e$  is the Earth's total mass. The preceding expression is the same as the force derived from an approximation that considers the gravitational field to be constant across the Earth.

The equivalent couple must have the same moment as the resultant moment of the gravitational forces about point  $O$ , so we set

$$\bar{M} = \iiint \bar{r}_{P/O} \times d\bar{F}.$$

## 5.2 Inertia Properties

251

Using the approximation of  $d\bar{F}$  in Eq. (4) leads to

$$\begin{aligned}\bar{M} &= Gm_s \iiint \bar{r}_{P/O} \times \left( \frac{1}{R^2} \bar{e}_R + 3 \frac{\bar{r}_{P/O} \cdot \bar{e}_R}{R^3} \bar{e}_R - \frac{\bar{r}_{P/O}}{R^3} \right) dm \\ &\approx \frac{Gm_s}{R^2} \iiint \bar{r}_{P/O} \times \bar{e}_R dm + 3 \frac{Gm_s}{R^3} \iiint (\bar{r}_{P/O} \times \bar{e}_R) (\bar{r}_{P/O} \cdot \bar{e}_R) dm.\end{aligned}$$

The first integral vanishes because  $\bar{e}_R$  is independent of the position of the mass element, so the integral is proportional to the first moment of mass relative to the center of mass. Therefore the gravitational couple is described by

$$\bar{M} = 3 \frac{Gm_s}{R^3} \iiint (\bar{e}_R \cdot \bar{r}_{P/O}) (\bar{r}_{P/O} \times \bar{e}_R) dm. \quad (6)$$

To understand this integral we represent the position vector in terms of the position coordinates of the mass element,  $\bar{r}_{P/O} = x\bar{i} + y\bar{j} + z\bar{k}$ . The corresponding representation of the integrand is

$$(\bar{e}_R \cdot \bar{r}_{P/O}) (\bar{r}_{P/O} \times \bar{e}_R) = (\ell_{x'y}x + \ell_{x'z}y + \ell_{x'z}z) [(\ell_{x'z}y - \ell_{x'y}z)\bar{i} + \dots],$$

where only the  $x$  component is listed because the others can be obtained by permuting the symbols. Carrying out the product shows that the integrand contains various quadratic products of the point coordinates, so the integral may be expressed in terms of the moments and products of inertia. The result is simplified if  $xyz$  are principal axes because the terms in the integrand that contain mixed products,  $xy$ ,  $xz$ , or  $yz$ , vanish in the integration. The nonzero terms are

$$\begin{aligned}(\bar{e}_R \cdot \bar{r}_{P/O}) (\bar{r}_{P/O} \times \bar{e}_R) &= \ell_{x'y}\ell_{x'z}(y^2 - z^2)\bar{i} + \ell_{x'x}\ell_{x'z}(z^2 - x^2)\bar{j} \\ &\quad + \ell_{x'x}\ell_{x'y}(x^2 - y^2)\bar{k} + \dots.\end{aligned}$$

Substitution of this representation of the integrand into Eq. (6) leads to

$$\begin{aligned}M &= 3 \frac{Gm_s}{R^3} \left[ \ell_{x'y}\ell_{x'z} \iiint (x^2 + y^2 - x^2 - z^2) dm \bar{i} \right. \\ &\quad + \ell_{x'x}\ell_{x'z} \iiint (y^2 + z^2 - x^2 - y^2) dm \bar{j} \\ &\quad \left. + \ell_{x'x}\ell_{x'y} \iiint (x^2 + z^2 - y^2 - z^2) dm \bar{k} \right] \\ &= 3 \frac{Gm_s}{R^3} [\ell_{x'y}\ell_{x'z} (I_{zz} - I_{yy})\bar{i} + \ell_{x'x}\ell_{x'z} (I_{xx} - I_{zz})\bar{j} + \ell_{x'x}\ell_{x'y} (I_{yy} - I_{xx})\bar{k}]. \quad (7)\end{aligned}$$

Equations (5) and (7) are valid for the gravitational force–couple system exerted on any large body when  $xyz$  are principal axes. Axisymmetry of the present approximation of the Earth's shape further simplifies the couple expression because  $I_{xx} = I_{yy}$ . When we use Eq. (4) for  $\bar{F}$  to describe the coefficient of the bracketed term and recognize that  $\ell_{x'z}$  is the direction cosine between the radial line to the

Sun and the polar axis, we find that

$$\begin{aligned}\bar{F} &= F\bar{e}_R, \quad \bar{M} = 3 \frac{F(I_{zz} - I_{xx})}{m_e R} (\bar{e}_R \cdot \bar{k}) (\bar{e}_R \times \bar{k}), \\ F &= \frac{Gm_s m_e}{R^2}, \quad \bar{e}_R = \ell_{x'x}\bar{i} + \ell_{x'y}\bar{j} + \ell_{x'z}\bar{k}.\end{aligned}\tag{7}$$

These expressions indicate that the moment acts about an axis that is perpendicular to the plane formed by the radial line to the Sun and the polar axis. To get a sense of the scale of  $\bar{M}$ , consider a pair of forces  $\bar{F}$  and  $-\bar{F}$  whose couple moment  $Fh$  equals  $|\bar{M}|$ . The corresponding separation distance is

$$h = \frac{3(I_{zz} - I_{xx})}{m_e R} (\bar{e}_R \cdot \bar{k}) |\bar{e}_R \times \bar{k}|.$$

The ratio of a moment of inertia to the mass is the square of the corresponding radius of gyration,  $\kappa_z$  and  $\kappa_x$ . Because both  $\bar{e}_R$  and  $\bar{k}$  are unit vectors, it must be that

$$h < \frac{3|\kappa_z^2 - \kappa_x^2|}{R}.\tag{8}$$

The Earth is nearly spherical, so  $\kappa_x \approx \kappa_z$ . Furthermore, both radii of gyration are smaller than the radius  $R_e$  of the Earth, so  $|\kappa_z^2 - \kappa_x^2| \ll R_e^2$ , which leads to the conclusion that  $h/R_e \ll R_e/R$ .

A significant aspect of the derivation is that it is readily adapted to treat the role of the Moon. Obviously,  $R$  must be interpreted as the distance between the centers of the Earth and the Moon, and  $m_s$  must be changed to the mass of the Moon. We also must define  $x'y'z'$  to lie in the Moon's orbital plane relative to the Earth. An interesting aspect of the fact that the Moon is much smaller but much closer than the Sun is that their relative significance for the gravitational moment is opposite their significance for the attractive force. Their respective masses are  $m_s = 1.98892(10^{30})$  kg and  $m_{\text{moon}} = 7.348(10^{22})$  kg, whereas the average orbital distances are  $R_s = 1.4960(10^{11})$  m and  $R_{\text{moon}} = 3.844(10^8)$  m. Thus, the relative magnitudes are

$$\begin{aligned}\frac{F_{\text{moon}}}{F_s} &= \frac{m_{\text{moon}}}{m_s} \left( \frac{R_s}{R_{\text{moon}}} \right)^2 = 0.56\%, \\ \frac{|M_{\text{moon}}|}{|M_s|} &= \frac{m_{\text{moon}}}{m_s} \left( \frac{R_s}{R_{\text{moon}}} \right)^3 = 218\%.\end{aligned}$$

In other words, a first-order analysis of the movement of the Earth's center of mass is well justified in neglecting the role of the Moon, but understanding the rotational motion of the Earth requires that the effect of both bodies be considered. Although both moments are relatively small, they are ever present. This leads to precession of the tilted Earth's polar axis that has a period of many millennia, as well as a wobble of the polar axis, as we will see in Chapter 10. [The variability of the gravitational attraction of the moon also is a large part of the cause of oceanic tides. The text by Sverdrup *et al.* (2005) is a good entry to this topic.]

## 5.2 Inertia Properties

253

### 5.2.2 Transformations

Several resources, including the Appendix, tabulate the inertia properties of homogeneous bodies having common shapes. The formulas appearing in the Appendix were obtained by carrying out the integrals in Eqs. (5.2.4). The inertia properties of shapes could be evaluated from the integral definitions, but it often is easier to consider a body to be a composite of tabulated shapes. Integrals over different domains are additive. This makes it possible to decompose the moments and products of inertia of a composite shape into contributions of the constituents, that is,

$$I_{\xi\eta} = (I_{\xi\eta})_1 + (I_{\xi\eta})_2 + \cdots, \quad \xi, \eta = x, y, \text{ or } z. \quad (5.2.8)$$

The same decomposition applies to the mass and first moment of mass, from which we can locate the center of mass  $G$  of the composite shape:


$$\begin{aligned} m &= m_1 + m_2 + \cdots, \\ m\xi_G &= m_1(\xi_G)_1 + m_2(\xi_G)_2 + \cdots, \quad \xi = x, y, \text{ or } z. \end{aligned} \quad (5.2.9)$$

Although these relations for the properties of the composite shape appear to be straightforward, one aspect substantially complicates the task. In particular, applying Eq. (5.2.8) requires that the inertia properties of the constituent bodies all be relative to the desired  $xyz$  coordinate system. All inertia properties in the Appendix are for centroidal axes, whereas the constituent parts of most composite shapes seldom have coincident centroids. It also is possible that the orientation of coordinate systems for the basic shapes will be different. A rotation transformation of the inertial properties will allow us to bring the coordinate axes for each shape into parallel alignment with the coordinate system of interest. Then the parallel axis transformation of inertia properties will allow us to bring the origin of the coordinate system for each shape into coincidence with the desired origin. Only after such transformations are evaluated may the individual inertia properties be combined according to Eq. (5.2.8).

Composite shapes are not the only reason for studying transformations of the inertia properties. If a body is in pure rotation about a noncentroidal point, it is desirable to sum moments about the pivot point. This would require knowing the inertia properties for a set of axes whose origin is at the pivot, rather than the center of mass. A situation requiring a rotation transformation might arise if the coordinate system we use is selected to facilitate description of the components of  $\bar{\omega}$ , without considering which coordinate system is used to describe the tabulated inertia properties.

#### Parallel Axis Transformation

There are several ways in which we may transfer the inertia properties between points. The approach we will use is based on Eq. (5.1.36). In Fig. 5.6  $xyz$  are a set of centroidal coordinate axes for which the inertia properties are known, and  $x'y'z'$  is a parallel coordinate system having origin  $B$  for which we wish to determine the properties. The distances  $x_B$ ,  $y_B$ , and  $z_B$  are the coordinates of origin  $B$  with respect to the centroidal



**Figure 5.6.** Parallel coordinate axes for transforming inertia properties.

coordinate system. Writing the position of origin  $B$  with respect to  $xyz$  is one way to ensure that the signs of these coordinates are correctly identified:

$$\bar{r}_{B/G} = x_B \bar{i} + y_B \bar{j} + z_B \bar{k}. \quad (5.2.10)$$

We use this expression together with a component representation of  $\bar{\omega}$  to evaluate  $\bar{r}_{B/G} \times (\bar{\omega} \times \bar{r}_{B/G})$ , which changes Eq. (5.1.36) to

$$\begin{aligned} \bar{H}_B = & \bar{H}_G + m[(y_B^2 + z_B^2)\omega_x - x_By_B\omega_y - x_Bz_B\omega_z]\bar{i} \\ & + m[(x_B^2 + z_B^2)\omega_y - x_By_B\omega_x - y_Bz_B\omega_z]\bar{j} \\ & + m[(x_B^2 + y_B^2)\omega_z - x_Bz_B\omega_x - y_Bz_B\omega_y]\bar{k}. \end{aligned}$$

Let the inertia properties with respect to the parallel coordinate systems  $xyz$  and  $x'y'z$  be  $[I_G]$  and  $[I_B]$ , respectively. Then the preceding may be written as

$$[I_B]\{\omega\} = [I_G]\{\omega\} + m \begin{bmatrix} (y_B^2 + z_B^2) & -x_By_B & -x_Bz_B \\ -x_By_B & (x_B^2 + z_B^2) & -y_Bz_B \\ -x_Bz_B & -y_Bz_B & (x_B^2 + y_B^2) \end{bmatrix} \{\omega\}. \quad (5.2.11)$$

This relation must apply for any  $\{\omega\}$ , so the factor of  $\{\omega\}$  on each side of the equality must match. The result is the *parallel axis transformation of inertia properties*:

$$[I_B] = [I_G] + m \begin{bmatrix} (y_B^2 + z_B^2) & -x_By_B & -x_Bz_B \\ -x_By_B & (x_B^2 + z_B^2) & -y_Bz_B \\ -x_Bz_B & -y_Bz_B & (x_B^2 + y_B^2) \end{bmatrix}. \quad (5.2.12)$$

Matching like elements in this relation leads to the scalar form of this parallel axis transformation. The diagonal terms transform moments of inertia,

$$\begin{aligned} I_{x'x'} &= I_{xx} + m(y_B^2 + z_B^2), \\ I_{y'y'} &= I_{yy} + m(x_B^2 + z_B^2), \\ I_{z'z'} &= I_{zz} + m(x_B^2 + y_B^2), \end{aligned} \quad (5.2.13)$$

## 5.2 Inertia Properties

255

whereas products of inertia transform according to


$$\begin{aligned} I_{x'y'} &= I_{yx} = I_{xy} + m x_B y_B, \\ I_{x'z'} &= I_{zx} = I_{xz} + m x_B z_B, \\ I_{y'z'} &= I_{zy} = I_{yz} + m y_B z_B. \end{aligned} \quad (5.2.14)$$

Equations (5.2.13) add a positive quantity to the centroidal values, which means that the moments of inertia for centroidal axes are smaller than those about any parallel noncentroidal axes. Also, it is not necessary to actually implement the transformation to obtain any product of inertia that can be recognized as being zero because of symmetry.

It is imperative to remember that the preceding transformations apply *only if*  $xyz$  are centroidal axes, which is the condition under which Eq. (5.1.36) is valid. Otherwise, additional terms featuring first moments of mass would arise. Another common error is failure to remember that  $x_B$ ,  $y_B$ , and  $z_B$  are the coordinates of the origin  $B$  of the noncentroidal coordinate system. One can avoid the latter error by locating this point vectorially, as in Eq. (5.2.10). Also, if it is desired to transform between two parallel noncentroidal coordinate systems, one can convert from the set of known inertia properties to centroidal values by solving the aforementioned equations, and then transfer from the latter values to the coordinate system for which the properties are desired.


An interesting interpretation of the parallel axis transformation results from considering the case of a single particle. The particle model considers a body's dimensions to be negligible, so that the centroidal inertia properties vanish,  $[I] = [0]$ . The moments of inertia for noncentroidal axes are then simply the particle's mass multiplied by the square of its distance from the respective coordinate axes, and the products of inertia are the mass multiplied by the products of the respective coordinates of the noncentroidal coordinate system. Thus the general parallel axis theorems indicate that transferring from centroidal to noncentroidal axes increments the inertia properties as though all of the body's mass were situated at its center of mass.

**EXAMPLE 5.5** Locate the center of mass of the trapezoidal parallelepiped. Then determine the moments and products of inertia corresponding to centroidal coordinate system  $xyz$  whose axes are parallel to  $XYZ$  defined in the sketch.



Example 5.5

**SOLUTION** This is an illustration of the procedures for evaluating the inertia properties of a body that is a composite of basic shapes. The decomposition we use is a rectangular parallelepiped and a rectangular prism, both of whose properties are described in the Appendix. We begin with a sketch that shows the location of the center of mass for each constituent shape.



The first moment of mass is used to locate the center of mass. We may perform this calculation in one step by writing the positions of the respective centers of mass vectorially. The masses are

$$m_1 = \rho (1.5) (2) (1.2), \quad m_2 = \rho \frac{1}{2} (1.5) (2) (1.2), \quad m = m_1 + m_2 = 5.4\rho.$$

Relative to  $XYZ$  the centers of mass are located at

$$\bar{r}_{G1/O} = 0.75\bar{i} + 1\bar{j} + 0.6\bar{k}, \quad \bar{r}_{G2/O} = 2\bar{i} + 1\bar{j} + 0.4\bar{k} \text{ m.}$$

The corresponding moment of mass is

$$m\bar{r}_{G/O} = m_1\bar{r}_{G1/O} + m_2\bar{r}_{G2/O},$$

$$5.4\rho\bar{r}_{G/O} = 3.6\rho (0.75\bar{i} + 1\bar{j} + 0.6\bar{k}) + 1.8\rho (2\bar{i} + 1\bar{j} + 0.4\bar{k}),$$

from which we find that

$$\bar{r}_{G/O} = 1.1667\bar{i} + 1\bar{j} + 0.5333\bar{k} \text{ m.} \quad \triangleleft$$

Obviously we could have identified the  $Y$  coordinate of the center of mass by symmetry.

Let  $xyz$  be the coordinate system that is parallel to  $XYZ$  with origin at point  $G$ . The  $xz$  plane cuts the body in half, so it is a plane of symmetry. Because  $y$  is the axis perpendicular to this plane, we have

$$I_{xy} = I_{yz} = 0. \quad \triangleleft$$

Thus we need to evaluate each moment of inertia, as well as  $I_{xz}$ .

## 5.2 Inertia Properties

257

For each basic shape let  $x_j y_j z_j$  denote the centroidal axis that is aligned parallel to  $XYZ$ . For body 1 we find from the Appendix that

$$(I_{x_1 x_1})_1 = \frac{1}{12} m_1 (2^2 + 1.2^2) = 1.6320\rho,$$

$$(I_{y_1 y_1})_1 = \frac{1}{12} m_1 (1.5^2 + 1.2^2) = 1.1070\rho,$$

$$(I_{z_1 z_1})_1 = \frac{1}{12} m_1 (1.5^2 + 2^2) = 1.8750\rho,$$

$$(I_{x_1 z_1})_1 = 0.$$

The coordinates of point  $G$  with respect to  $x_1 y_1 z_1$  are the components of the position of the relative position vector,

$$\bar{r}_{G/G1} = \bar{r}_{G/O} - \bar{r}_{G1/O} = 0.4167\bar{I} - 0.0667\bar{K}.$$

The parallel axis transformation for shape 1 therefore is

$$(I_{xx})_1 = (I_{x_1 x_1})_1 + m_1 (-0.0667)^2 = 1.6480\rho,$$

$$(I_{yy})_1 = (I_{y_1 y_1})_1 + m_1 [(0.4167)^2 + (-0.0667)^2] = 1.7481\rho,$$

$$(I_{zz})_1 = (I_{z_1 z_1})_1 + m_1 (0.4167)^2 = 2.500\rho,$$

$$(I_{xz})_1 = (I_{x_1 z_1})_1 + m_1 (0.4167)(-0.0667) = -0.100\rho.$$

For shape 2 care must be taken to properly permute the axis labels from those depicted in the Appendix. The centroidal inertia properties of shape 2 are thereby found to be

$$(I_{x_2 x_2})_2 = \frac{1}{36} m_2 [3(2^2) + 2(1.2^2)] = 0.7440\rho,$$

$$(I_{y_2 y_2})_2 = \frac{1}{18} m_2 (1.5^2 + 1.2^2) = 0.3690\rho,$$

$$(I_{z_2 z_2})_2 = \frac{1}{36} m_2 [3(2^2) + 2(1.5^2)] = 0.8250\rho,$$

$$(I_{x_2 z_2})_2 = -\frac{1}{36} m_2 (1.5)(1.2) = -0.0900\rho.$$

The position vector for point  $G$  relative to the centroid of shape 2 is

$$\bar{r}_{G/G2} = \bar{r}_{G/O} - \bar{r}_{G2/O} = -0.8333\bar{I} + 0.1333\bar{K}.$$

The corresponding parallel axis transformation is

$$(I_{xx})_2 = (I_{x_2 x_2})_2 + m_2 (0.1333)^2 = 0.7760\rho,$$

$$(I_{yy})_2 = (I_{y_2 y_2})_2 + m_2 [(-0.8333)^2 + (0.1333)^2] = 1.6510\rho,$$

$$(I_{zz})_2 = (I_{z_2 z_2})_2 + m_2 (-0.8333)^2 = 2.0750\rho,$$

$$(I_{xz})_2 = (I_{x_2 z_2})_2 + m_2 (-0.8333)(0.1333) = -0.2900\rho.$$



Now that the inertia properties of each shape are known with respect to  $xyz$  their contributions may be added. Thus,

$$\begin{aligned} I_{xx} &= (I_{xx})_1 + (I_{xx})_2 = 2.4240\rho, \\ I_{yy} &= (I_{yy})_1 + (I_{yy})_2 = 3.3990\rho, \\ I_{zz} &= (I_{zz})_1 + (I_{zz})_2 = 4.5750\rho, \\ I_{xz} &= (I_{xz})_1 + (I_{xz})_2 = -0.3900\rho. \end{aligned} \quad \triangleleft$$

### Rotational Transformation

Our concern here is with a situation in which we know  $[I]$  relative to  $xyz$ , and we wish to determine  $[I']$  corresponding to coordinate system  $x'y'z'$  whose origin coincides with the origin of  $xyz$ . From the rotation transformation we have

$$\{\omega'\} = [R]\{\omega\}, \quad (5.2.15)$$

where  $\{\omega\}$  and  $\{\omega'\}$  consist of the components of the respective vectors.

The derivation of the parallel axis transformations was based on a property of the kinetic energy. Similarly, the rotational transformation will employ the rotational contribution to the kinetic energy of a body. Energy is a scalar quantity, so formulating it in terms of angular velocity components with respect to either coordinate system must yield the same result.

Either of Eqs. (5.1.33) indicates that the kinetic energy associated with rotation about point  $A$  is

$$T_{\text{rot}} = \frac{1}{2} \bar{\omega} \cdot \bar{H}_A. \quad (5.2.16)$$

The components of the angular momentum  $\bar{H}_A$  of a rigid body relative to the designated point are described in matrix form in Eq. (5.2.5), which leads to

$$T_{\text{rot}} = \frac{1}{2} \{\omega\}^T [I] \{\omega\}. \quad (5.2.17)$$

The same value of  $T_{\text{rot}}$  should result if the angular velocity and the inertia properties are referred to the  $x'y'z'$  axes, so

$$T_{\text{rot}} = \frac{1}{2} \{\omega'\}^T [I'] \{\omega'\}. \quad (5.2.18)$$

Equation (5.2.15) allows us to replace the  $x'y'z'$  components of  $\bar{\omega}$  in the preceding with those relative to  $xyz$ , with the result that

$$T_{\text{rot}} = \frac{1}{2} \{\omega\}^T [R]^T [I'] [R] \{\omega\}. \quad (5.2.19)$$

## 5.2 Inertia Properties

259

The value of  $T_{\text{rot}}$  obtained from this equation must match the result of Eq. (5.2.17), regardless of what the angular velocity actually is. The only way this equivalence can be attained is if the inner product matches  $[I]$ , that is,

$$[I] = [R]^T [I'] [R]. \quad (5.2.20)$$

In the scenario of interest we presumably know  $[I]$ . To solve for  $[I']$  we recall the orthonormal property,  $[R][R]^T = [R]^T [R] = [U]$ . Thus we find that

$$[I'] = [R][I][R]^T. \quad (5.2.21)$$

Any quantity transforming in the manner described by this relation is said to be a tensor of the second rank. In this viewpoint, vectors, whose components transform according to Eq. (5.2.15), are tensors of the first rank. Note that transforming a vector involves premultiplication by the matrix  $[R]$  that transforms from the known to unknown components. Transformation of a second-rank tensor involves premultiplication by  $[R]$  and postmultiplication by  $[R]^T$ . In the case of the symmetric second-rank tensors like the inertia properties, such a transformation preserves the symmetry of the tensor.

The transformation in Eq. (5.2.21) may be decomposed into individual inertia values. Toward that end we recall Eq. (3.1.11), which expresses  $[R]$  as a sequence of row partitions consisting of the direction cosines of an axis of  $x'y'z'$  relative to  $xyz$ , according to

$$[R] = \begin{bmatrix} \{e_{x'}\}^T \\ \{e_{y'}\}^T \\ \{e_{z'}\}^T \end{bmatrix}. \quad (5.2.22)$$

The rows of  $[R]$  are denoted as  $\{e_{\xi'}\}^T$ ,  $\xi' = x', y', \text{ or } z'$ , because each column vector consists of the components of a unit vector  $\bar{e}_{\xi'}$  relative to  $xyz$ , that is,

$$\{e_{\xi'}\}^T = \begin{bmatrix} \ell_{\xi'x} & \ell_{\xi'y} & \ell_{\xi'z} \end{bmatrix}. \quad (5.2.23)$$

The utility of the partitioned form of  $[R]$  is that it enables us to condense the operations, because each partition may be treated as a single element. The columns of  $[R]^T$  are rows of  $[R]$ , so

$$[R]^T = \begin{bmatrix} \{e_{x'}\} & \{e_{y'}\} & \{e_{z'}\} \end{bmatrix}. \quad (5.2.24)$$

Thus, substituting the partitioned form of  $[R]$  into the rotation transformation, Eq. (5.2.21), leads to


$$\begin{aligned} [I'] &= \begin{bmatrix} \{e_{x'}\}^T \\ \{e_{y'}\}^T \\ \{e_{z'}\}^T \end{bmatrix} [I] \begin{bmatrix} \{e_{x'}\} & \{e_{y'}\} & \{e_{z'}\} \end{bmatrix} \\ &= \begin{bmatrix} \{e_{x'}\}^T \\ \{e_{y'}\}^T \\ \{e_{z'}\}^T \end{bmatrix} \begin{bmatrix} [I]\{e_{x'}\} & [I]\{e_{y'}\} & [I]\{e_{z'}\} \end{bmatrix} \\ &= \begin{bmatrix} \{e_{x'}\}^T [I]\{e_{x'}\} & \{e_{x'}\}^T [I]\{e_{y'}\} & \{e_{x'}\}^T [I]\{e_{z'}\} \\ \{e_{y'}\}^T [I]\{e_{x'}\} & \{e_{y'}\}^T [I]\{e_{y'}\} & \{e_{y'}\}^T [I]\{e_{z'}\} \\ \{e_{z'}\}^T [I]\{e_{x'}\} & \{e_{z'}\}^T [I]\{e_{y'}\} & \{e_{z'}\}^T [I]\{e_{z'}\} \end{bmatrix}. \end{aligned} \quad (5.2.25)$$

The diagonal elements of the product are the moments of inertia, whereas the off-diagonal terms are the negative of the products of inertia. Thus we find that

$$\left. \begin{aligned} I_{\xi'\xi'} &= \{e_{\xi'}\}^T [I] \{e_{\xi'}\} \\ I_{\xi'\eta'} &= -\{e_{\xi'}\}^T [I] \{e_{\eta'}\} \end{aligned} \right\}, \quad \xi', \eta' = x, y, \text{ or } z, \quad \xi \neq \eta. \quad (5.2.26)$$

The purpose of deriving these relations is to understand how a specific inertia property is altered by a rotation. In most situations we would need all of the transformed inertia properties. In that case it is much simpler to evaluate Eq. (5.2.21) directly.

**EXAMPLE 5.6** The 5-kg homogeneous box rotates through angle  $\theta$  about the  $Y$  axis of the stationary  $XYZ$  coordinate system. Edge  $AB$  coincides with the  $Z$  axis when  $\theta = 0$ . Determine the moments and products of inertia with respect to  $XYZ$  as functions of  $\theta$ .




**Example 5.6**

**SOLUTION** This problem has the obvious purpose of illustrating the transformation of inertia properties, but the results also help us understand some general aspects. In the second drawing  $x'y'z'$  is a body-fixed coordinate system having origin  $A$  whose

## 5.2 Inertia Properties

261

axes are aligned with the edges of the box. It is parallel to the centroidal system of a rectangular parallelepiped described in the Appendix.



Coordinate systems used to derive the rotation transformation

The coordinates of corner  $A$  relative to the parallel centroidal coordinate system are the components of the relative position vector,

$$\bar{\mathbf{r}}_{A/G} = -0.75\bar{i}' - 1\bar{j}' - 0.5\bar{k}' \text{ m.}$$

Applying the parallel axis transformation to the tabulated properties gives

$$I_{x'x'} = \frac{1}{12} (5) (2^2 + 1^2) + 5 [(-1)^2 + (-0.5)^2] = 8.3333,$$

$$I_{y'y'} = \frac{1}{12} (5) (1.5^2 + 1^2) + 5 [(-0.75)^2 + (-0.5)^2] = 5.4167,$$

$$I_{z'z'} = \frac{1}{12} (5) (1.5^2 + 2^2) + 5 [(-0.75)^2 + (-1)^2] = 10.4167,$$

$$I_{x'y'} = I_{y'x'} = 0 + 5(-0.75)(-1) = 3.7500,$$

$$I_{x'z'} = I_{z'x'} = 0 + 5(-0.75)(-0.5) = 1.8750,$$

$$I_{y'z'} = I_{z'y'} = 0 + 5(-1)(-0.5) = 2.5 \text{ kg}\cdot\text{m}^2.$$

The rotation transformation from  $x'y'z'$  to  $XYZ$  is a simple rotation by  $\beta = \tan^{-1}(1.5/2) = 36.87^\circ$  about the negative  $z'$  axis:

$$\begin{Bmatrix} X \\ Y \\ Z \end{Bmatrix} = [R_1] \begin{Bmatrix} x' \\ y' \\ z' \end{Bmatrix}, \quad [R_1] = \begin{bmatrix} 0.8 & -0.6 & 0 \\ 0.6 & 0.8 & 0 \\ 0 & 0 & 1 \end{bmatrix}.$$

Let us define the body-fixed coordinate system  $xyz$  such that it coincides with  $XYZ$  when  $\theta = 0$ . Thus, transforming the inertia matrix from  $x'y'z'$  to  $XYZ$  gives the

constant properties relative to  $xyz$ . We designate this as  $[I_{\theta=0}]$ . Using the preceding rotation matrix gives

$$\begin{aligned} [I_{\theta=0}] &= [R_1] \begin{bmatrix} 8.3333 & -3.7500 & -1.8750 \\ -3.7500 & 5.4167 & -2.5 \\ -1.8750 & -2.5 & 10.4167 \end{bmatrix} [R_1]^T \\ &= \begin{bmatrix} 10.8833 & 0.3500 & 0 \\ 0.3500 & 2.8667 & -3.1250 \\ 0 & -3.1250 & 10.4167 \end{bmatrix}. \end{aligned}$$

Another rotation transformation is needed to find the properties relative to space-fixed  $XYZ$  axes when  $\theta$  is not zero. Because  $xyz$  rotates about the  $Y$  axis relative to  $XYZ$ , the transformation from  $XYZ$  to  $xyz$  is

$$\begin{Bmatrix} x \\ y \\ z \end{Bmatrix} = [R_2] \begin{Bmatrix} X \\ Y \\ Z \end{Bmatrix}, \quad [R_2] = \begin{bmatrix} \cos \theta & 0 & -\sin \theta \\ 0 & 1 & 0 \\ \sin \theta & 0 & \cos \theta \end{bmatrix}.$$

The transformation from  $xyz$  to  $XYZ$  is described by  $[R_2]^T$ , so the inertia matrix for the  $XYZ$  axes is given by

$$[I] = [R_2]^T [I_{\theta=0}] [R_2].$$

The diagonal elements are the moments of inertia relative to  $XYZ$ , and the off-diagonal elements are the negative of the products of inertia:

$$I_{XX} = 0.4667 (\cos \theta)^2 + 10.4167, \quad I_{ZZ} = 0.4667 (\sin \theta)^2 + 10.4167,$$

$$I_{YY} = 2.8667,$$

$$I_{XY} = I_{YX} = -0.3500 \cos \theta + 3.1250 \sin \theta, \quad \triangleleft$$

$$I_{XZ} = I_{ZX} = 0.4667 (\sin \theta) (\cos \theta),$$

$$I_{YZ} = I_{ZY} = 0.3500 \sin \theta + 3.1250 \cos \theta.$$

The moment of inertia about the  $Y$  axis does not depend on  $\theta$  because the distance from this axis to each mass point is unaffected by the rotation. Both  $I_{XX}$  and  $I_{ZZ}$  are periodic in  $\Delta\theta = \pi$ , but they vary little as  $\theta$  changes, essentially because the dimensions of the box in both directions transverse to the  $Y$  axis are comparable. The products of inertia  $I_{XY}$  and  $I_{YZ}$  are periodic in  $\Delta\theta = 2\pi$ , whereas  $I_{XZ}$  is periodic in  $\Delta\theta = \pi$ . The periodic nature of the inertia properties stems from the fact that a rotation by  $\Delta\theta = \pi$  changes the sign of the  $X$  and  $Z$  coordinates of each mass element, whereas the  $Y$  coordinate remains constant. An important observation is that there are values of  $\theta$  for which each product of inertia vanishes, but the angle is different for each term.

## 5.2 Inertia Properties

263

### 5.2.3 Inertia Ellipsoid

Equation (5.2.17) for the rotational kinetic energy and Eq. (5.2.26) for the moment of inertia about an arbitrary axis have similar forms. We exploit that similarity here to develop a pictorial representation of the dependence of moments of inertia on the orientation of the associated axis. In the present context the construction is primarily of qualitative interest, but it will be quite useful in Chapter 10 for a detailed study of the rotation of a body in free motion.

Suppose a body is made to rotate at angular speed  $\omega$  about a specified axis  $p' = x', y',$  or  $z'$  whose direction is  $\bar{e}_{p'}$ . The matrix representation of the angular velocity is

$$\{\omega\} = \omega \{e_{p'}\}, \quad (5.2.27)$$

where  $\{e_{p'}\}$  contains the components of one of the unit vectors of  $x'y'z'$  relative to  $xyz$ . The construction we seek considers a situation in which the angular speed is adjusted such that, regardless of how the rotation axis is oriented relative to body-fixed coordinates  $xyz$ , the rotational kinetic energy is always  $T_{\text{rot}} = 1/2$ . Let  $\bar{\rho}$  denote a vector extending from the origin of  $xyz$  to a point whose coordinates are the components of this special  $\bar{\omega}$ . In matrix notation we have

$$\{\rho\} = [x \ y \ z]^T = \rho \{e_{p'}\}, \quad \rho = (x^2 + y^2 + z^2)^{1/2}. \quad (5.2.28)$$

Let  $[I]$  denote the inertia matrix relative to  $xyz$ . Setting  $T_{\text{rot}} = 1/2$  in Eq. (5.2.17) shows that these coordinates satisfy

$$[x \ y \ z][I][x \ y \ z]^T = 1. \quad (5.2.29)$$

Expansion of this product yields

$$I_{xx}x^2 + I_{yy}y^2 + I_{zz}z^2 - 2I_{xy}xy - 2I_{xz}xz - 2I_{yz}yz = 1. \quad (5.2.30)$$


This is the equation for an ellipsoidal surface whose centroid coincides with the origin of the  $xyz$  set of axes. This surface is called the *ellipsoid of inertia*.

One interpretation of the ellipsoid of inertia is associated with its construction, that is, it is the locus of points for which an angular velocity equal to the vector from the origin to any point gives  $T_{\text{rot}} = 1/2$ . A more useful interpretation is obtained by using Eq. (5.2.28) to eliminate the position coordinates in Eq. (5.2.29). In view of the first of Eqs. (5.2.26), this operation yields

$$\rho^2 \{e_{p'}\}^T [I] \{e_{p'}\} = \rho^2 I_{p'p'} = 1. \quad (5.2.31)$$

Thus the distance  $\rho$  from the origin to a point on the ellipsoid of inertia is the reciprocal of the square root of the moment of inertia about the axis intersecting the origin and that point. In other words, the distance is inversely proportional to the radius of gyration about that axis.

If we know  $[I]$ , we can construct the inertia ellipsoid according to Eq. (5.2.30), as depicted in Fig. 5.7. The major, minor, and intermediate axes of this ellipsoid of inertia, along which the distance from the origin is an extreme value, are mutually orthogonal.



**Figure 5.7.** A typical ellipsoid of inertia, whose major, intermediate, and minor axes align with  $\xi_1$ ,  $\xi_2$ , and  $\xi_3$ , respectively.

However, they do not necessarily coincide with the  $xyz$  axes. In the figure  $\xi_1\xi_2\xi_3$  is a coordinate system whose axes coincide respectively with the major, intermediate, and minor axes of the ellipsoid of inertia. The canonical equation for an ellipsoidal surface relative to such a coordinate system is

$$I_1\xi_1^2 + I_2\xi_2^2 + I_3\xi_3^2 = 1, \quad (5.2.32)$$


where  $I_1 \leq I_2 \leq I_3$  when  $\xi_1$  aligns with the major axis and  $\xi_3$  align with the minor axis. The semidiameters of the ellipsoid are  $1/\sqrt{I_1}$ ,  $1/\sqrt{I_2}$ , and  $1/\sqrt{I_3}$ , respectively, as shown in the figure. Equation (5.2.32) is like Eq. (5.2.30), except that there are no terms associated with products of inertia. It follows that  $I_1$ ,  $I_2$ , and  $I_3$  are the principal moments of inertia and the  $\xi_1\xi_2\xi_3$  coordinate system is a set of principal axes.

This discussion proves that, for a specified origin, there always is a set of principal axes. We could contemplate locating these axes by evaluating  $[I]$  for nonprincipal axes and then constructing the inertia ellipsoid. The principal axes would then be located by graphically identifying the major, intermediate, and minor axes. However, such a procedure would be imprecise, as well as challenging to implement. The following example shows how mathematical analysis of the inertia ellipsoid can locate the principal axes in a two-dimensional situation.

**EXAMPLE 5.7** In the sketch  $xyz$  and  $x'y'z'$  are centroidal coordinate systems for the right triangular plate, with the former aligned parallel to the parallel edges and the latter rotated about the  $z$  axis through angle  $\theta$ . The mass of the plate is 400 kg. Because the plate is bisected by the  $x'y'$  plane,  $I_{x'z'} = I_{y'z'} = 0$ . There are values of  $\theta$  for which  $I_{x'y'} = 0$ , thereby making  $x'y'z'$  principal axes for the plate. Determine  $\theta$  and the corresponding principal moments of inertia by using a rotation transformation. Then perform the same evaluation by using the properties of the inertia ellipsoid.

## 5.2 Inertia Properties

265



Example 5.7

**SOLUTION** The primary intent here is to lessen the abstract nature of the ellipsoid of inertia by seeing its features for an actual body. We may find the inertia properties relative to  $xyz$  by letting the length  $a$  of the right triangular prism in the Appendix approach zero. The  $z$  and  $x$  axes are swapped with the corresponding axes in the tabulation, but the  $y$  axis here is reversed from the sense described there. This means that we should interchange the subscripts of the inertia properties to match the present definitions and also set  $I_{xy}$  and  $I_{yz}$  equal to the negative of the tabulated expressions. Thus we have

$$I_{xx} = \frac{1}{36} (400) (2) (3.6^2) = 288, \quad I_{yy} = \frac{1}{36} (400) (2) (2.4^2) = 128,$$

$$I_{zz} = I_{xx} + I_{yy} = 416 \text{ kg-m}^2,$$

$$I_{xy} = +\frac{1}{36} (400) (3.6) (2.4) = 96, \quad I_{yz} = I_{xz} = 0.$$

It is worth noting  $I_{zz}$  was evaluated as the sum of the other moments of inertia. This is identically true for any thin flat slab when the origin of  $xyz$  lies in the plane of the slab and the  $z$  axis is normal to that plane.

The rotation transformation from  $xyz$  to  $x'y'z'$  is

$$[R] = \begin{bmatrix} \cos \theta & \sin \theta & 0 \\ -\sin \theta & \cos \theta & 0 \\ 0 & 0 & 1 \end{bmatrix}.$$

We wish to determine all inertia properties with respect to  $x'y'z'$ , so we implement the full rotation transformation:

$$\begin{aligned} [I'] &= [R] \begin{bmatrix} 288 & -96 & 0 \\ -96 & 128 & 0 \\ 0 & 0 & 416 \end{bmatrix} [R]^T \\ &= \begin{bmatrix} 288(c\theta)^2 + 128(s\theta)^2 - 192s\theta c\theta & 96 - 192(c\theta)^2 - 160s\theta c\theta & 0 \\ 96 - 192(c\theta)^2 - 160s\theta c\theta & 288(s\theta)^2 + 128(c\theta)^2 + 192s\theta c\theta & 0 \\ 0 & 0 & 416 \end{bmatrix}, \end{aligned}$$



where  $s\theta$  and  $c\theta$  are abbreviations for  $\sin\theta$  and  $\cos\theta$ . We find the value of  $\theta$  that makes  $I_{x'y'}$  vanish by applying the identities for the sine and cosine of  $2\theta$  to the (1,2) element of  $[I']$ , which leads to

$$-96 \cos(2\theta) - 80 \sin(2\theta) = 0 \implies \theta = 64.903^\circ, -25.097^\circ. \quad \triangleleft$$

These two possible angles differ by  $90^\circ$ , so they merely correspond to alternate labeling of the  $x'$  and  $y'$  axes. The principal moments of inertia for  $\theta = 64.903^\circ$  are

$$I_{x'x'} = I_1 = 83.04, \quad I_{y'y'} = I_2 = 332.96, \quad I_{z'z'} = I_3 = 416 \text{ kg}\cdot\text{m}^2. \quad \triangleleft$$

Solution of this problem by use of the ellipsoid of inertia barely resembles the preceding operations. Because we know that  $z$  is a principal axis, we focus on the  $xy$  plane by writing the defining equation, Eq. (5.2.30), for the case in which  $z = 0$ , which gives

$$288x^2 + 128y^2 - 192xy = 1.$$


This is an ellipse. The multivalued nature of the value of  $y$  as a function of  $x$  makes it convenient to use polar coordinates. By definition, the distance from the origin to a point on the ellipsoid of inertia is  $\rho$ , so we define

$$x = \rho \cos \phi, \quad y = \rho \sin \phi.$$

The equation for the  $xy$  ellipse then becomes

$$\rho^2 [288 (\cos \phi)^2 + 128 (\sin \phi)^2 - 192 (\sin \phi) (\cos \phi)] = 1.$$

We obtain the graph of this ellipse by solving the preceding equation for the value of  $\rho$  corresponding to numerous values of  $\phi$  covering a  $2\pi$  range.



The major and minor diameters depicted in this graph could be located by several methods, each of which is based on the same property. In general,  $\rho$  has an extreme value at the principal axes. Hence the major and minor diameters correspond to points at which  $\rho$  has a maximum or minimum value. We could locate both lines by visually searching for the points on the ellipse that are farthest and closest to the origin. Another procedure is to search through a table of values of  $\phi$  and  $\rho$  for the points where  $\rho$  is largest and smallest. Both procedures have limited precision. A mathematical approach is to use calculus to locate values of  $\phi$  for which

## 5.2 Inertia Properties

267

$d\rho/d\phi = 0$ . To expedite such an evaluation we introduce the identities for  $\cos(2\phi)$  and  $\sin(2\phi)$  into the equation for the  $xy$  ellipse, which gives

$$\rho^2 (208 + 80 \cos 2\phi - 96 \sin 2\phi) = 1.$$

Implicit differentiation of this equation with respect to  $\phi$  yields

$$2\rho \frac{d\rho}{d\phi} (208 + 80 \cos 2\phi - 96 \sin 2\phi) + \rho^2 (-160 \sin 2\phi - 192 \cos 2\phi) = 0.$$

Setting  $d\rho/d\phi = 0$  shows that the principal axes correspond to  $160 \sin 2\phi + 192 \cos 2\phi = 0$ , which is the same as the condition identified from the rotation transformation. Thus the values of  $\phi$ , and the corresponding  $\rho$ , are

$$\phi = 64.903^\circ \implies \rho_1 = 0.109740,$$

$$\phi = -25.097^\circ \implies \rho_2 = 0.054803.$$

The principal moments of inertia are the reciprocals of the squares of the extreme values of  $\rho$ , so

$$I_1 = \frac{1}{\rho_1^2} = 83.04, \quad I_2 = \frac{1}{\rho_2^2} = 332.96 \text{ kg-m}^2.$$

These are the same principal values as those found earlier.

The key aspect to bear in mind is that both procedures, explicitly setting the off-diagonal elements of  $[I']$  to zero and geometrically analyzing the inertia ellipsoid, were expedited by the fact that  $z$  was known to be a principal axis. Consequently, only a single angle needed to be evaluated. Either approach would be substantially more difficult to implement if multiple direction angles needed to be found. Also worth noting is the fact that the orientation of the principal axes has no simple geometrical explanation, unlike the case for symmetrical bodies.

### 5.2.4 Principal Axes

Identification of principal axes from the properties of the inertia ellipsoid is unwieldy in a general situation where none of the axes of the original coordinate system are principal. Here we establish a mathematical procedure that achieves the same goal in a straightforward manner. We seek to determine a rotation transformation  $[R]$  that converts the inertia matrix  $[I]$  associated with nonprincipal axes  $xyz$  to a diagonal matrix  $[I']$ . Let  $I_1 \leq I_2 \leq I_3$  denote the principal moments of inertia corresponding to axes whose unit vectors are respectively  $\bar{e}_1$ ,  $\bar{e}_2$ , and  $\bar{e}_3$ . Equation (5.2.22) describes a rotation transformation as a column of partitions that consist of the components of unit vectors. In terms of the principal directions, that description is

$$[R] = \begin{bmatrix} \{e_1\}^T \\ \{e_2\}^T \\ \{e_3\}^T \end{bmatrix}. \quad (5.2.33)$$

When we replace  $[I']$  and the arbitrary unit vectors in the first line of Eq. (5.2.25) with the quantities for principal axes, we find that

$$\begin{bmatrix} I_1 & 0 & 0 \\ 0 & I_2 & 0 \\ 0 & 0 & I_3 \end{bmatrix} = \begin{bmatrix} \{e_1\}^T \\ \{e_2\}^T \\ \{e_3\}^T \end{bmatrix} [I] \begin{bmatrix} \{e_1\} & \{e_2\} & \{e_3\} \end{bmatrix}. \quad (5.2.34)$$

Our task now is to determine the unit vector components and principal moments of inertia that satisfy the preceding relation when  $[I]$  is given. The first step is to premultiply by  $[R]^T$  and apply the orthonormal property. This gives

$$\begin{bmatrix} \{e_1\} & \{e_2\} & \{e_3\} \end{bmatrix} \begin{bmatrix} I_1 & 0 & 0 \\ 0 & I_2 & 0 \\ 0 & 0 & I_3 \end{bmatrix} = [I] \begin{bmatrix} \{e_1\} & \{e_2\} & \{e_3\} \end{bmatrix}. \quad (5.2.35)$$

The multiplication property for partitioned matrices simplifies this to

$$\begin{bmatrix} I_1 \{e_1\} & I_2 \{e_2\} & I_3 \{e_3\} \end{bmatrix} = \begin{bmatrix} [I] \{e_1\} & [I] \{e_2\} & [I] \{e_3\} \end{bmatrix}. \quad (5.2.36)$$

Like columns on either side of this equation must match, from which it follows that each principal direction and its associated moment of inertia are solutions of

$$I_j \{e_j\} = [I] \{e_j\}, \quad j = 1, 2, 3. \quad (5.2.37)$$

In other words,  $I_j$  are the eigenvalues  $\lambda$  and  $\{e_j\}$  are the eigenvectors  $\{e\}$  satisfying

$$([I] - \lambda [U]) \{e\} = \{0\}, \quad (5.2.38)$$

where  $[U]$  is the identity matrix.

This is called a standard eigenvalue problem. Routines for solving such problems are contained in most mathematical software. Only the concepts are highlighted here. Equation (5.2.38) represents three simultaneous equations for the components of  $\{e\}$ , which are the direction cosines between a principal axis and the axes associated with inertia matrix  $[I]$ . These equations are homogeneous. Consequently, the only solution is the trivial one,  $\{e\} = \{0\}$ , unless the coefficient matrix  $[I] - \lambda [U]$  cannot be inverted. Hence nontrivial solutions for  $\{e\}$  require that  $\lambda$  satisfy the characteristic equation corresponding to vanishing of the determinant of the coefficients:

$$|[I] - \lambda [U]| = 0. \quad (5.2.39)$$

Evaluation of this determinant with  $\lambda$  as an algebraic parameter leads to a cubic equation. The eigenvalues, which are the three roots of the characteristic equation, are the principal moments of inertia,  $\lambda = I_1, I_2, I_3$ .

Once the eigenvalues are known, we may proceed to determine the eigenvectors, which will be the principal directions. The fact that the determinant of  $[I] - \lambda [U]$  vanishes means that its rank has been reduced, so that the elements of an eigenvector  $\{e_j\}$  cannot be determined uniquely from Eq. (5.2.38). In the standard situation the principal moments of inertia are distinct values. In that case the rank of  $[I] - \lambda [U]$  is two, so that one of the three simultaneous equations represented by Eq. (5.2.38) is a linear

## 5.2 Inertia Properties

269

combination of the others. Because of this loss of an independent equation, any nonzero component of  $\{e_j\}$  may be chosen arbitrarily. The other components may then be found in terms of the arbitrary one by solving the independent equations.

The eigenvectors satisfying Eq. (5.2.38) have an arbitrary element, but that is so because consideration has not been given to the definition of  $\{e_j\}$  as the components of a unit vector oriented parallel to the  $j$ th principal axis. The condition that such a vector has a unit magnitude is written in matrix form as

$$\{e_j\}^T \{e_j\} = 1. \quad (5.2.40)$$

Enforcement of this condition yields the additional equation required to evaluate uniquely  $\{e_j\}$ . Note that the solution of the preceding leads to an ambiguity in sign. Even though any eigenvector multiplied by  $-1$  is still an eigenvector, assembling the three eigenvectors to form  $[R]$  might lead to a left-handed system, identifiable by the fact that  $|[R]| = -1$ . Such a condition is readily corrected by multiplying one of the eigenvectors by  $-1$ .

The eigenvectors  $\{e_j\}$  form an orthogonal set. To prove this property, consider Eq. (5.2.37) for two different principal values,  $j = m$  and  $j = n$ . Premultiplying each equation by the transpose of the other eigenvector leads to

$$\begin{aligned} \{e_n\}^T [I] \{e_m\} &= I_m \{e_n\}^T \{e_m\}, \\ \{e_m\}^T [I] \{e_n\} &= I_n \{e_m\}^T \{e_n\}. \end{aligned} \quad (5.2.41)$$

The quantities that are equated are scalars, so we may transpose the products without altering the result. Because  $[I]$  is symmetric, performing this operation on the second of the preceding equations gives

$$\{e_n\}^T [I] \{e_m\} = I_n \{e_n\}^T \{e_m\}. \quad (5.2.42)$$

If the moments of inertia are distinct values,  $I_n \neq I_m$ , subtracting this equation from the first of Eqs. (5.2.41) leads to the conclusion that

$$\{e_n\}^T \{e_m\} = 0 \quad \text{if} \quad I_m \neq I_n. \quad (5.2.43)$$

This is the matrix form of the dot product  $\bar{e}_n \cdot \bar{e}_m = 0$ , which proves the orthogonality of the unit vectors. It then follows from Eq. (5.2.42) that

$$\{e_n\}^T [I] \{e_m\} = 0 \quad \text{if} \quad I_m \neq I_n. \quad (5.2.44)$$

According to the second of Eqs. (5.2.26), the left-hand side of this relation is the negative of the product of inertia associated with axes  $\bar{e}_m$  and  $\bar{e}_n$ . Hence the preceding merely proves that the directions derived by solving the eigenvalue problem will be principal axes.

Both Eqs. (5.2.43) and (5.2.44) exclude the case in which the moments of inertia about axes  $\bar{e}_m$  and  $\bar{e}_n$  are equal. In general, the rank of  $[I] - I_m [U]$  is reduced by the number of times the eigenvalue  $\lambda = I_m$  occurs as a root of the characteristic equation. Thus, if  $I_m = I_n$  and the third eigenvalue is different from  $I_m$ , then  $[I] - I_m [U]$  has a rank of one. This means that  $[[I] - I_m [U]] \{e\} = \{0\}$  consists of one independent equation for  $\{e\}$ , so that  $\{e\}$  has two arbitrary elements. It follows that, in addition

to requiring that  $\{e\}$  represent a unit vector, Eq. (5.2.40), another condition must be identified.

The method in which to proceed when this ambiguity arises becomes apparent when we consider a body of revolution. Any coordinate system having an axis that coincides with the axis of symmetry will be principal, and the moments of inertia about the axes perpendicular to the axis of symmetry will be the same. This suggests that, when two principal moments of inertia are equal, the ratio of two arbitrary elements in the first eigenvector can be set to any convenient value. (For example, we might wish that the first eigenvector have no component parallel to the  $z$  axis, in which case we would equate the third element of  $\{e_m\}$  to zero.) The principal direction described by  $\{e_n\}$  should be orthogonal to the direction described by  $\{e_m\}$ , so we require that

$$\{e_n\}^T \{e_m\} = 0 \quad \text{if } m \neq n. \quad (5.2.45)$$

This, in combination with Eq. (5.2.40), gives two conditions required to determine uniquely the second eigenvector.

The greater degree of arbitrariness associated with identical principal moments of inertia arises because the corresponding principal directions are not unique. The case in which all three principal values are identical merely means that any set of axes are principal. There is then no need to solve an eigenvalue problem. This feature is exemplified by a homogeneous sphere or cube when the origin is placed at the centroid.

The ellipsoid of inertia provides an interesting geometrical interpretation of the eigenvalue problem, which was derived from the mathematical properties of the rotation transformation of inertia properties. We saw in the previous section that principal axes correspond to locations on the inertia ellipsoid at which the distance to the center is a local extremum. At such locations the normal to the ellipsoid's surface will be parallel to the line to the origin. The vector from the origin to a point on the surface is  $\bar{\rho} = x\bar{i} + y\bar{j} + z\bar{k}$ . If a surface is described in functional form as  $f(x, y, z) = C$ , a constant, then the gradient of  $f$  is normal to the surface.

Thus the condition that  $\bar{\rho}$  is parallel to the surface normal when it is aligned with a principal axis is described by

$$\bar{\rho} = x\bar{i} + y\bar{j} + z\bar{k} = \sigma \nabla f, \quad (5.2.46)$$

where  $\sigma$  is a factor of proportionality. Equation (5.2.30) is the function for the ellipsoid. The gradient of this function is

$$\begin{aligned} \nabla f = & 2(I_{xx}x - I_{xy}y - I_{xz}z)\bar{i} + 2(I_{yy}y - I_{xy}x - I_{yz}z)\bar{j} \\ & + 2(I_{zz}z - I_{xz}x - I_{yz}y)\bar{k}. \end{aligned} \quad (5.2.47)$$

We substitute this expression into Eq. (5.2.46), and match like components, which leads to

$$\begin{aligned} x &= 2\sigma (I_{xx}x - I_{xy}y - I_{xz}z), \\ y &= 2\sigma (I_{yy}y - I_{xy}x - I_{yz}z), \\ z &= 2\sigma (I_{zz}z - I_{xz}x - I_{yz}y). \end{aligned} \quad (5.2.48)$$

## 5.2 Inertia Properties

271

The matrix form of this set of simultaneous equations is

$$[I][x \ y \ z]^T = \frac{1}{2\sigma} [x \ y \ z]^T. \quad (5.2.49)$$

This is equivalent to the eigenvalue problem described by Eq. (5.2.37) when  $\sigma = 1/2\lambda_j$ .

**EXAMPLE 5.8** Determine the principal moments of inertia and associated rotation transformation for the triangular plate in Example 5.7 by solving an eigenvalue problem.

**SOLUTION** This example demonstrates the formal mathematical eigensolution. In Example 5.7 the inertia matrix of the triangular plate relative to centroidal axes matching those in the Appendix was found to be

$$[I] = \begin{bmatrix} 288 & -96 & 0 \\ -96 & 128 & 0 \\ 0 & 0 & 416 \end{bmatrix} \text{ kg-m}^2.$$

The corresponding eigenvalue problem for principal axes is

$$\begin{bmatrix} (288 - \lambda) & -96 & 0 \\ -96 & (128 - \lambda) & 0 \\ 0 & 0 & 416 - \lambda \end{bmatrix} \{e\} = \{0\}.$$

The characteristic equation is

$$\begin{aligned} |[I] - \lambda [U]| &= (416 - \lambda) [(288 - \lambda)(128 - \lambda) - 96^2] \\ &= (416 - \lambda) (\lambda^2 - 416\lambda + 27648) = 0. \end{aligned}$$

One eigenvalue makes the first factor vanish, whereas the other two roots are solutions of the quadratic equation we obtain by setting the second factor to zero. These values are

$$\lambda_1 = I_1 = 83.036, \quad \lambda_2 = I_2 = 332.964, \quad \lambda_3 = I_3 = 416 \text{ kg-m}^2. \quad \triangleleft$$

Note that the eigenvalues have been sequenced from smallest to largest.

We denote the elements of eigenvector  $\{e\}$  corresponding to  $I_j$  as  $e_{nj}$ . Thus the first eigenvector must satisfy

$$[[I] - \lambda_1 [U]] \begin{Bmatrix} e_{11} \\ e_{21} \\ e_{31} \end{Bmatrix} = \begin{bmatrix} 204.964 & -96 & 0 \\ -96 & 44.964 & 0 \\ 0 & 0 & 332.964 \end{bmatrix} \begin{Bmatrix} e_{11} \\ e_{21} \\ e_{31} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \\ 0 \end{Bmatrix}.$$

This eigenvalue is a single root of the characteristic equation, so one row of the coefficient matrix is a linear combination of the others. The third row clearly is different

from the other two, so we discard the second row. Thus we need to find the solution of

$$204.964e_{11} - 96e_{21} = 0,$$

$$332.964e_{31} = 0.$$

The last of the preceding equations requires that  $e_{31} = 0$ , which means that it cannot be considered arbitrary. The first equation defines the ratio of  $e_{21}$  to  $e_{11}$ , so we have

$$e_{21} = 2.1350e_{11}, \quad e_{31} = 0.$$

The condition that  $\{e\}$  represent a unit vector requires that

$$e_{11}^2 + e_{21}^2 = (1 + 2.1350^2) e_{11}^2 = 1.$$

We select the positive root, so that the first principal axis will have a component in the positive  $x$  direction. This leads to

$$e_{11} = 0.4242, \quad e_{21} = 0.9056, \quad e_{31} = 0.$$

The evaluation of the second principal direction follows similar steps. We have

$$[[I] - \lambda_2 [U]] \begin{Bmatrix} e_{12} \\ e_{22} \\ e_{32} \end{Bmatrix} = \begin{bmatrix} -44.964 & -96 & 0 \\ -96 & -204.964 & 0 \\ 0 & 0 & 83.036 \end{bmatrix} \begin{Bmatrix} e_{12} \\ e_{22} \\ e_{32} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \\ 0 \end{Bmatrix}.$$

Once again, we discard the second equation as the one that is not independent, which leads to

$$\begin{aligned} -44.964e_{12} - 96e_{22} &= 0 \\ 83.036e_{32} &= 0 \end{aligned} \implies e_{22} = -0.4684e_{12}, \quad e_{32} = 0.$$

Making this eigenvector represent a unit vector gives

$$e_{12} = 0.9056, \quad e_{22} = -0.4242, \quad e_{32} = 0.$$

The situation for the third eigenvector is slightly different. In this case, we have

$$[[I] - \lambda_3 [U]] \begin{Bmatrix} e_{13} \\ e_{23} \\ e_{33} \end{Bmatrix} = \begin{bmatrix} -128 & -96 & 0 \\ -96 & -128 & 0 \\ 0 & 0 & 0 \end{bmatrix} \begin{Bmatrix} e_{13} \\ e_{23} \\ e_{33} \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \\ 0 \end{Bmatrix}.$$

The first two rows of the coefficient matrix are independent of each other, and the third coefficient in each is zero, so the associated equations require that  $e_{13} = e_{23} = 0$ , but place no conditions on  $e_{33}$ . The last row of the coefficient matrix represents

## 5.2 Inertia Properties


273

a trivial equation, so any value of  $e_{33}$  will constitute an eigenvector. For it to represent a unit vector it must be that  $|e_{33}| = 1$ . If  $e_{33} = +1$  and the first two rows of  $[R]$  are the values we have determined, then  $|[R]| = -1$ . Multiplying an eigenvector by  $-1$ , which corresponds to reversing the associated unit vector, does not alter the fact that it is an eigensolution. Thus we set  $e_{33} = -1$ . According to Eq. (5.2.33), the eigenvectors are the rows of the transformation matrix, so we have found that

$$[R] = \begin{bmatrix} 0.4242 & 0.9056 & 0 \\ 0.9056 & -0.4242 & 0 \\ 0 & 0 & -1 \end{bmatrix}. \quad \triangleleft$$

A comparison of this result with the one found in Example 5.7 shows that the second and third principle directions are reversed.

**EXAMPLE 5.9** In the sketch,  $xyz$  are centroidal axes of the 60-kg homogeneous orthogonal tetrahedron. Determine the principal moments of inertia and the rotation transformation for the principal axes whose origin also is the centroid.



Example 5.9

**SOLUTION** This example addresses how mathematical software can be used to evaluate the principal inertia properties.<sup>†</sup> For the dimensions of the given body with  $m = 60$  kg, we find from the Appendix that

$$[I] = \begin{bmatrix} 1.170 & 0.060 & 0.090 \\ 0.060 & 0.900 & 0.180 \\ 0.090 & 0.180 & 0.450 \end{bmatrix} \text{ kg-m}^2.$$

Most mathematical software packages have functions or subroutines that can solve the standard eigenvalue problem  $[[I] - \lambda [U]]\{e\} = \{0\}$ . In Matlab, one obtains the desired result by writing `[e_vecs, I_princ] = eigs(I)`; where  $I$  is the preceding  $3 \times 3$  array,  $I_{\text{princ}}$  is a  $3 \times 3$  diagonal array whose elements are the principal

<sup>†</sup> One should check the behavior of their software version. In particular, the manner in which eigenvectors are normalized is somewhat arbitrary. The results presented here were obtained from Matlab 7.1 and Mathcad 13.1.



moments of inertia, and  $e\_vecs$  is a  $3 \times 3$  array whose  $j$ th column is the eigenvector corresponding to  $I\_princ(j, j)$ . The Matlab result is

$$I\_princ(1, 1) = 1.2059 \quad I\_princ(2, 2) = 0.9327 \quad I\_princ(3, 3) = 0.3814,$$

$$e\_vecs = \begin{bmatrix} -0.9395 & -0.3322 & -0.0836 \\ -0.2908 & 0.9023 & -0.3181 \\ -0.1811 & 0.2746 & 0.9444 \end{bmatrix}.$$

The algorithm employed by Matlab returns  $e\_vecs$  as an orthonormal transformation, that is,  $[e\_vecs][e\_vecs]^T = [U]$ , but the principal values are not sequenced from smallest to largest, as we prefer. We therefore swap the first and third principal moments of inertia, and correspondingly swap the first and third columns of  $[e\_vecs]$ . However, swapping a pair of columns of a  $3 \times 3$  matrix reverses the sign of its determinant, which brings to the fore the question of whether the transformation initially computed by Matlab was right-handed. The raw output previously listed has a determinant of  $-1$ , so the result of swapping columns one and three yields the correct result. After these steps, the transformation matrix  $[R]$  is readily obtained by recalling that the individual eigenvectors constituting the columns of  $[e\_vecs]$  are the rows of  $[R]$ , so that  $[R] = [e\_vecs]^T$ . After these adjustments, the results obtained from Matlab are

$$I_1 = 0.3814, I_2 = 0.9327, I_3 = 1.2059 \text{ kg-m}^2, \quad \triangleleft$$

$$[R] = \begin{bmatrix} -0.0836 & -0.3181 & 0.9444 \\ -0.3322 & 0.9023 & 0.2746 \\ -0.9395 & -0.2908 & -0.1811 \end{bmatrix}. \quad \triangleleft$$

An excellent check for any solution, whether it is obtained by solving the characteristic equation or from computer software, is to verify that  $[R][I][R]^T$  yields a diagonal array whose nonzero elements are the principal moments of inertia in the correct sequence.

Mathcad uses two functions to solve the eigenvalue problem corresponding to a specified  $3 \times 3$  array  $I$ . The principal moments of inertia are computed by  $I\_princ := \text{eigenvals}(I)$ ; and the eigenvectors are obtained from  $e\_princ := \text{eigenvecs}(I)$ ; where  $I\_princ$  is a three-element column vector of principal moments of inertia, and  $e\_princ$  is a  $3 \times 3$  array whose columns are the eigenvectors sequenced to match  $I\_princ$ . The result is

$$\{I\_princ\} = \begin{Bmatrix} 1.2059 \\ 0.9327 \\ 0.3814 \end{Bmatrix}, \quad [e\_princ] = \begin{bmatrix} 0.9395 & 0.3322 & -0.0836 \\ 0.2908 & -0.9023 & -0.3181 \\ 0.1811 & -0.2746 & 0.9444 \end{bmatrix}.$$

The eigenvectors returned by Mathcad's algorithm, like Matlab's, have the orthonormal property. Mathcad, like Matlab, does not address the handedness of the

### 5.3 Rate of Change of Angular Momentum

275

transformation, and it does not necessarily sequence the principal moments of inertia from smallest to largest. The preceding values are like the raw output from Matlab, except that the first two columns of  $[e_{\text{princ}}]$  are multiplied by  $-1$  relative to their Matlab correspondences, so  $||[e_{\text{princ}}]|| = -1$ . Because the principal moments of inertia are reversed from the desired order, as they were in Matlab, we swap the first and third values of  $\{I_{\text{princ}}\}$  and swap the first and third columns of  $[e_{\text{princ}}]$ . This leads to  $||[e_{\text{princ}}]|| = +1$ , as required. The result is that the principal moments of inertia are the same as those obtained from Matlab, whereas the last two rows of  $[R]$  obtained from Mathcad are the negative of the Matlab values.

### 5.3 RATE OF CHANGE OF ANGULAR MOMENTUM

The angular momentum of a rigid body is used in several contexts. Our focus here is its usage to form Eq. (5.1.22), which describes the effect of the resultant moment. The angular momentum was shown in Eq. (5.2.3) to be describable in terms of the body's angular velocity and inertia properties. Evaluation of the inertia matrix was discussed in detail in the preceding section, and the techniques for evaluating angular velocity should be familiar by now. We now turn to the task of taking the time derivative of the angular momentum.

A careful reading of the development thus far will reveal that we have not fully defined how the  $xyz$  reference frame rotates. To use the simplified moment equation, we stipulated that point  $A$  for the moment sum shall be an allowable point. We then placed the origin of the  $xyz$  coordinate system, which was used to describe the position of each mass element, at point  $A$ . These conditions do not address how  $xyz$  rotates. We remove this ambiguity by imposing a restriction that expedites differentiating  $\bar{H}_A$ .

In the context of kinematics,  $xyz$  has played the role of a global coordinate system. We use it to describe the body's distribution of mass, as well as its angular velocity components. If  $xyz$  has an arbitrary angular velocity  $\bar{\Omega}$ , then the derivatives of its unit vectors are  $d\bar{i}/dt = \bar{\Omega} \times \bar{i}$ , etc. Further, because the body's angular velocity differs from  $\bar{\Omega}$ , the orientation of the body relative to  $xyz$  is not constant, so that the inertia properties are not constant. Consequently, every term in Eq. (5.2.3) might change with time. The time derivative of that equation therefore is

$$\begin{aligned} \frac{d\bar{H}_A}{dt} = & \left[ \frac{d}{dt} (I_{xx}\omega_x - I_{xy}\omega_y - I_{xz}\omega_z) \right] \bar{i} + \left[ \frac{d}{dt} (I_{yy}\omega_y - I_{yx}\omega_x - I_{yz}\omega_z) \right] \bar{j} \\ & + \left[ \frac{d}{dt} (I_{zz}\omega_z - I_{zx}\omega_x - I_{zy}\omega_y) \right] \bar{k} + \bar{\Omega} \times \bar{H}_A. \end{aligned} \quad (5.3.1)$$

Clearly, it would be preferable if the inertia properties were constant. This condition is achieved if the body's orientation relative to  $xyz$  is invariant. For this reason we introduce the requirement that

$xyz$  should be a body-fixed coordinate system.

In addition to simplifying evaluation of the derivatives in Eq. (5.3.1), such a requirement sets  $\bar{\Omega} = \bar{\omega}$ , so the only angular velocity we need to evaluate is that of the body. A third simplification that results is more subtle. Differentiating the components of  $\bar{H}_A$  in accord with Eq. (5.3.1) results in the occurrence of terms containing  $\dot{\omega}_x$ ,  $\dot{\omega}_y$ , and  $\dot{\omega}_z$ , which suggests that we need to describe the components of  $\bar{\omega}$  as functions of time. In contrast, the procedures we established for evaluating angular acceleration did not require such a description. When  $\bar{\omega}$  is described in terms of components relative to coordinate system  $xyz$  that rotates at  $\bar{\Omega}$ , its time derivative is given by

$$\bar{\alpha} = \frac{d\bar{\omega}}{dt} = \frac{\partial \bar{\omega}}{\partial t} + \bar{\Omega} \times \bar{\omega} \equiv (\dot{\omega}_x \bar{i} + \dot{\omega}_y \bar{j} + \dot{\omega}_z \bar{k}) + \bar{\Omega} \times \bar{\omega}. \quad (5.3.2)$$

By deciding to attach  $xyz$  to the body, we always have  $\bar{\Omega} = \bar{\omega}$ , in which case the partial and total derivatives of  $\bar{\omega}$  are identical, so that

$$\bar{\alpha} = \frac{\partial \bar{\omega}}{\partial t} \implies \alpha_p = \dot{\omega}_p, \quad p = x, y, z \text{ if } xyz \text{ is body fixed.} \quad (5.3.3)$$

In other words, the angular acceleration components are the rates of change of the angular velocity components when those components are relative to body-fixed axes.

The overall consequence of requiring that  $xyz$  be body fixed is that differentiation of  $\bar{H}_A$  becomes reasonably straightforward. We apply the partial derivative technique in Eq. (3.3.15) to the angular momentum. In that equation  $\bar{\omega}$  was the angular velocity of the reference frame. It now also is the angular velocity of the body, so we have

$$\dot{\bar{H}}_A = \frac{\partial \bar{H}_A}{\partial t} + \bar{\omega} \times \bar{H}_A. \quad (5.3.4)$$

The components of  $\partial \bar{H}_A / \partial t$  are the derivatives of the respective components of  $\bar{H}_A$ , which are indicated by Eq. (5.2.3) to consist of products of inertia coefficients and  $\bar{\omega}$  components. The former are constant, and derivatives of the latter are described by Eq. (5.3.3). Thus,

$$\begin{aligned} \frac{\partial \bar{H}_A}{\partial t} = & (I_{xx}\alpha_x - I_{xy}\alpha_y - I_{xz}\alpha_z)\bar{i} + (I_{yy}\alpha_y - I_{yx}\alpha_x - I_{yz}\alpha_z)\bar{j} \\ & + (I_{zz}\alpha_z - I_{zx}\alpha_x - I_{zy}\alpha_y)\bar{k}. \end{aligned} \quad (5.3.5)$$

It is evident that evaluation of  $d\bar{H}_A/dt$  requires prior determination of  $[I]$  for the body and analysis of  $\bar{\omega}$  and  $\bar{\alpha}$  for the body's motion. These quantities are substituted into Eq. (5.2.3) for  $\bar{H}_A$  and the preceding equation for  $\partial \bar{H}_A / \partial t$ , which are then assembled to form Eq. (5.3.4). The matrix representation of  $\bar{H}_A$  in Eq. (5.2.5) leads to a compact representation of the full expression:

$$\{\dot{H}_A\} = [I]\{\alpha\} + \{\omega\} \otimes ([I]\{\omega\}), \quad (5.3.6)$$

where  $\otimes$  denotes the matrix implementation of a cross product.

### 5.3 Rate of Change of Angular Momentum

277

If  $xyz$  are principal axes, there are fewer terms to compute in  $\bar{H}_A$  and  $\partial \bar{H}_A / \partial t$ . This simplifies the vector form of the various quantities, with the result that

$$\begin{aligned} \dot{\bar{H}}_A = & [I_{xx}\alpha_x - (I_{yy} - I_{zz})\omega_y\omega_z]\bar{i} + [I_{yy}\alpha_y - (I_{zz} - I_{xx})\omega_x\omega_z]\bar{j} \\ & + [I_{zz}\alpha_z - (I_{xx} - I_{yy})\omega_x\omega_y]\bar{k}. \end{aligned} \quad (5.3.7)$$

This standard form is known as *Euler's equations*. Their simpler appearance makes it quite attractive to select  $xyz$  as principal axes. However, it is important to realize that the orientation of these axes affects the ease with which  $\bar{\omega}$  and  $\bar{\alpha}$  are determined. Also, as we have seen, principal axes have no special orientation relative to a nonsymmetrical body, in which case their identification requires additional mathematical operations. This leads to the recognition that

It is best to select the  $xyz$  reference frame based on its suitability for describing  $[I]$ ,  $\bar{\omega}$ , and  $\bar{\alpha}$ .


If our choice for  $xyz$  happens to correspond to principal axes, then we may use Eq. (5.3.7).

Many mechanical systems feature axisymmetric bodies that spin about their axis of symmetry. Any coordinate system having an axis that coincides with the axis of symmetry represents a principal set of axes. In Fig. 5.8  $xyz$  is attached to axisymmetric body 1 such that its  $z$  axis coincides with the axis of symmetry. The spinning rotation  $\dot{\phi}$  occurs about the  $z$  axis relative to body 2, whose angular velocity is an arbitrary quantity  $\bar{\Omega}$ . Thus the angular velocity of body 1, and of  $xyz$ , is

$$\bar{\omega} = \bar{\Omega} + \dot{\phi}\bar{k}. \quad (5.3.8)$$

In the figure  $x'y'z'$  is introduced as a reference frame that is attached to body 2 such that its  $z'$  axis also coincides with the axis of symmetry of body 1. This leaves  $x'$  and  $y'$  axes unspecified, so we may orient those axes to facilitate description of  $\bar{\Omega}$ . For example, we might choose to let the  $y'$  axis coincide with the line of nodes for nutation in an Eulerian angle formulation.

There are two ways in which we may use  $x'y'z'$  to formulate the problem. In the first we observe that, at any instant, there is a body-fixed coordinate system that is parallel to  $x'y'z'$ . This is evident from the fact that the reference line used to measure  $\phi$  may be defined arbitrarily. Thus, in this special circumstance, using  $x'y'z'$  as a global coordinate



**Figure 5.8.** Reference frames for describing the rotation of axisymmetric body 1 relative to arbitrarily rotating body 2.

system leads to a description of vectors that is valid at any instant. In other words we may consider  $x'y'z'$  to be the body-fixed  $xyz$  coordinate system that is situated at  $\phi = 0$  at the instant of interest. This leads to a general procedure for axisymmetric bodies:

To evaluate  $d\bar{H}_A/dt$  for a body spinning about its axis of the symmetry, we may define the body-fixed  $xyz$  reference frame such that one axis coincides with the axis of symmetry. Then an expression for  $d\bar{H}_A/dt$  that is valid at any instant will be derived, regardless of how the other axes of  $xyz$  are aligned. Thus the other axes should be aligned instantaneously to expedite the component description of  $\bar{\omega}$  and  $\bar{\alpha}$ .

The invariance of the inertia properties with respect to angle  $\phi$  has led some to employ an alternative formulation of  $d\bar{H}_A/dt$  based on truly using  $x'y'z'$  as a global coordinate system. Evaluating  $d\bar{H}_A/dt$  in this approach requires that we return to Eq. (5.2.3). We form  $\bar{\omega}$  according to Eq. (5.3.8). Because the  $z'$  axis always coincides with the axis of symmetry of body 2, it must be that  $x'y'z'$  constitute principal axes regardless of  $\phi$ . Thus the angular momentum of body 1 is

$$\bar{H}_A = I_{xx}\Omega_{x'}\bar{i}' + I_{yy}\Omega_{y'}\bar{j}' + I_{zz}(\Omega_{z'} + \dot{\phi})\bar{k}'. \quad (5.3.9)$$

Because the components in this expression are relative to  $x'y'z'$ , the unit vector derivatives are described by  $\bar{\Omega} \times \bar{e}'$ . Thus the total and partial derivatives are related by

$$\dot{\bar{H}}_A = \frac{\partial \bar{H}_A}{\partial t} + \bar{\Omega} \times \bar{H}_A. \quad (5.3.10)$$

Differentiation of the component representation of  $\bar{H}_A$  given by Eq. (5.3.9) leads to

$$\frac{\partial \bar{H}_A}{\partial t} = I_{xx}\dot{\Omega}_{x'}\bar{i}' + I_{yy}\dot{\Omega}_{y'}\bar{j}' + I_{zz}(\dot{\Omega}_{z'} + \ddot{\phi})\bar{k}'. \quad (5.3.11)$$

As we did previously, we observe that, because  $\Omega_{x'}$ ,  $\Omega_{y'}$ , and  $\Omega_{z'}$  are the angular velocities of a reference frame relative to its own axes, their derivatives are the components of the angular acceleration of  $x'y'z'$ , that is,

$$\bar{\alpha}' = \dot{\Omega}_{x'}\bar{i}' + \dot{\Omega}_{y'}\bar{j}' + \dot{\Omega}_{z'}\bar{k}'.$$

The result of assembling these expressions is

$$\begin{aligned} \dot{\bar{H}}_A = & [I_{xx}\alpha'_{x'} - (I_{yy} - I_{zz})\Omega_{y'}(\Omega_{z'} + \dot{\phi})]\bar{i}' + [I_{yy}\alpha'_{y'} - (I_{zz} - I_{xx})\Omega_{x'}(\Omega_{z'} + \dot{\phi})]\bar{j}' \\ & + [I_{zz}(\alpha'_{z'} + \ddot{\phi}) - (I_{xx} - I_{yy})\omega_{x'}\omega_{y'}]\bar{k}'. \end{aligned} \quad (5.3.12)$$

These are sometimes referred to as the *modified Euler equations*. The primary advantage of this approach lies in the fact that it makes the role of the spinning motion apparent. Countering it is the fact that the procedure is not generally applicable and therefore prone to misapplication. In contrast, the fundamental methodology is valid regardless of the inertia properties.

### 5.3 Rate of Change of Angular Momentum

279


In relatively simple circumstances featuring axisymmetric bodies, yet another method may be available to evaluate  $d\bar{H}_A/dt$ . It is mostly employed to explain phenomena qualitatively, but sometimes it is suitable for quantitative analysis. Suppose we evaluate the angular momentum according to Eq. (5.2.3) by using a body-fixed  $xyz$  reference frame. That description should be representative of an arbitrary position of the body. Depending on the motion it might be that an alternative global coordinate system  $\hat{x}\hat{y}\hat{z}$  executing fewer rotations than  $xyz$  is equally suitable for describing the components of  $\bar{H}_A$ . Then, either by graphical projections or through a rotation transformation, we can write

$$\bar{H}_A = (H_A)_{\hat{x}} \bar{e}_{\hat{x}} + (H_A)_{\hat{y}} \bar{e}_{\hat{y}} + (H_A)_{\hat{z}} \bar{e}_{\hat{z}}. \quad (5.3.13)$$

We consider each component individually. If we are following a pictorial approach, we evaluate the derivative of each component as the sum of a term parallel to the unit vector that is due to the change of its magnitude plus the change perpendicular to the unit vector resulting from its rotation at the angular velocity  $\hat{\omega}$  of  $\hat{x}\hat{y}\hat{z}$ . Mathematically, this is equivalent to writing

$$\dot{\bar{H}}_A = \sum_{\hat{p}=\hat{x},\hat{y},\hat{z}} \left[ (\dot{H}_A)_{\hat{p}} \bar{e}_{\hat{p}} + (H_A)_{\hat{p}} \hat{\omega} \times \bar{e}_{\hat{p}} \right]. \quad (5.3.14)$$

This representation might not seem to be easier than any of the other approaches developed thus far, but that depends on the characteristics of the system and the choice for a global coordinate system. To explore this, consider the situation in Fig. 5.9, in which a disk sander spinning at  $\omega_1$  must be rotated at angular speed  $\omega_2$  about the handle, which is transverse to the disk's centerline.



**Figure 5.9.** Disk sander illustrating the evaluation of the rate of change of angular momentum of a spinning axisymmetric body.

Our focus is on the angular momentum of the rotating disk about its center of mass  $G$ . Let  $z$  denote the body-fixed axis for  $\omega_1$  and  $z'$  be a parallel axis for a reference frame attached to the motor housing. The  $x'$  axis is aligned with the handle, so it is the axis about which  $\omega_2$  occurs. We make use of the simplification afforded by axisymmetry by defining the body-fixed centroidal  $x$  axis at the instant of interest to be parallel to  $x'$ . Because  $xyz$  are principal axes, the angular momentum at any instant is correspondingly indicated by Eq. (5.2.3) to be

$$\bar{H}_G = I_2 \omega_2 \bar{i} + I_1 \omega_1 \bar{k}, \quad (5.3.15)$$

where  $I_1$  and  $I_2$  are respectively the centroidal moments of inertia of the disk about its centerline and any transverse axis. This expression is generally valid. It follows that we


may replace the unit vectors in Eq. (5.3.15) with those of  $x'y'z'$ , so at any instant the two components of angular momentum are as depicted in Fig. 5.9

We know that  $\bar{i}'$  is stationary, whereas  $\bar{k}'$  rotates at  $\omega_2 \bar{i}'$ . Furthermore, the values of the moments of inertia and rotation rates are constant. Thus, in the figure the  $\bar{i}'$  component of  $\bar{H}_G$  is constant, and the sole variability of the  $\bar{k}'$  component of  $\bar{H}_G$  is the changing direction of  $\bar{k}'$ . We can visualize that the tip of  $I_1 \omega_1 \bar{k}'$  moves in the  $-\bar{j}'$  direction, so we can anticipate that  $d\bar{H}_G/dt$  will be oriented in that direction. This is confirmed by the fact that the only variable in Eq. (5.3.15) is  $\bar{k}'$ , whose derivative is  $\omega_2 \bar{i}' \times \bar{k}'$ . Thus we have

$$\dot{\bar{H}}_A = -I_2 \omega_1 \omega_2 \bar{j}'.$$


The moment equation of motion requires that a couple equal to  $d\bar{H}_G/dt$  be applied to the rotor. This must ultimately be applied by the operator to the sander's handle. Thus a moment perpendicular to both rotation axes is required to sustain the motion, which is not what an inexperienced operator would anticipate.

**EXAMPLE 5.10** The right triangular plate is welded along its hypotenuse to a shaft that rotates at the variable rate  $\Omega$ . Determine  $d\bar{H}_G/dt$  for the plate. For the special case in which  $\Omega$  is constant, predict which way the dynamic reactions generated at the bearings will be oriented.



Example 5.10

**SOLUTION** One purpose of this example is to emphasize that bodies rotating about a fixed axis sometimes cannot be fully described by a planar formulation. Also, the simplicity of this system will enable us to assess fully the analytical results from a qualitative viewpoint. The axes of the body-fixed  $xyz$  coordinate system depicted in the sketch match those described in the Appendix for a right triangular prism whose width is zero.



Angular momentum components of the spinning plate relative to the body-fixed coordinate system defined in the Appendix.

### 5.3 Rate of Change of Angular Momentum

281

The tabulation gives

$$I_{xx} = \frac{1}{18}mb^2, \quad I_{yy} = \frac{1}{18}mb^2(\sin\theta)^2, \quad I_{zz} = \frac{1}{18}mb^2(\cos\theta)^2,$$

$$I_{xy} = I_{yx} = I_{xz} = I_{zx} = 0, \quad I_{yz} = I_{zy} = -\frac{1}{36}mb^2\sin\theta\cos\theta.$$

It is given that  $\Omega$  is not constant, so the angular velocity and angular acceleration are parallel to the shaft. We resolve both quantities into components with respect to  $xyz$ , so

$$\bar{\omega} = \Omega\bar{e}_{A/B} = \Omega(\cos\theta\bar{j} - \sin\theta\bar{k}),$$

$$\bar{\alpha} = \dot{\Omega}\bar{e}_{A/B} = \dot{\Omega}(\cos\theta\bar{j} - \sin\theta\bar{k}).$$

Substitution of the inertia values and the components of  $\bar{\omega}$  and  $\bar{\alpha}$  into Eqs. (5.2.3) and (5.3.5) leads to

$$\bar{H}_G = \frac{1}{36}mb^2\Omega\sin\theta\cos\theta(\sin\theta\bar{j} - \cos\theta\bar{k}),$$

$$\frac{\partial\bar{H}_G}{\partial t} = \frac{1}{36}mb^2\dot{\Omega}\sin\theta\cos\theta(\sin\theta\bar{j} - \cos\theta\bar{k}).$$

Correspondingly, Eq. (5.3.4) yields

$$\dot{\bar{H}}_G = \frac{1}{36}mb^2\Omega^2\sin\theta\cos\theta\left[-(\cos\theta)^2 + (\sin\theta)^2\right]\bar{i}$$

$$+ \frac{1}{36}mb^2\dot{\Omega}\sin\theta\cos\theta(\sin\theta\bar{j} - \cos\theta\bar{k}),$$

which is identically

$$\dot{\bar{H}}_G = \frac{1}{72}mb^2\sin 2\theta\left[-\Omega^2\cos 2\theta\bar{i} + \dot{\Omega}(\sin\theta\bar{j} - \cos\theta\bar{k})\right]. \quad \triangleleft$$

It is evident from this result that the forces acting on the plate must exert a moment about point  $G$  to sustain the rotation, even if  $\Omega$  is constant. The only exception is  $\theta = \pi/4$ , in which case  $d\bar{H}_G/dt = \bar{0}$  if  $\dot{\Omega} = 0$ .


To understand this result, the  $\bar{H}_G$  vector appears in the sketch defining  $xyz$ . The preceding expression for  $\bar{H}_G$  indicates that its direction cosines are  $\sin\theta$  and  $-\cos\theta$  with respect to the  $y$  and  $z$  axes, respectively. This leads to the observation that at any instant the angle between  $\bar{H}_G$  and the shaft is  $\pi/2 - 2\theta$ , as shown in the sketch. Rotation of the system changes the direction of  $\bar{H}_G$ , but the angle between  $\bar{H}_G$  and the shaft remains constant. Thus the rotation of  $\bar{H}_G$  changes only the component of  $\bar{H}_G$  perpendicular to the shaft,  $(H_G)_\perp = |\bar{H}_G|\sin(\pi/2 - 2\theta) = (1/36)mb^2\Omega\sin\theta\cos\theta\cos(2\theta)$ . The rotation causes the tip of this vector component to move into the plane of the sketch, which is the  $-\bar{i}$  direction, and the magnitude of the rate of change is  $\Omega(H_G)_\perp$ , which matches the  $\bar{i}$  component in the derived expression. The  $\bar{j}$  and  $\bar{k}$  components in that expression are proportional to  $\dot{\Omega}$ . An increase in the value of  $\Omega$  increases the length of  $\bar{H}_G$  in the sketch, which is manifested as terms in  $d\bar{H}_G/dt$  that are parallel to  $\bar{H}_G$ , which are the  $\bar{j}$  and  $\bar{k}$  components of the result.



The fact that the portion of  $d\bar{H}_G/dt$  that is independent of  $\dot{\Omega}$  vanishes when  $\theta = \pi/4$  is readily explained. In that case a centroidal coordinate system having one axis, say  $y'$ , parallel to the shaft symmetrically bisects the plate, so it represents principal axes. Using these principal axes to form the angular momentum shows that  $\bar{H}_G$  reduces to  $I_{y'y'}\Omega\bar{j}'$ . Thus in this case,  $\bar{H}_G$  is always oriented parallel to the axis of rotation, whose orientation is constant.

When  $\Omega$  is constant our analysis indicates that  $d\bar{H}_G/dt$  is in the negative  $\bar{i}$  direction, which is inward in the perspective of the sketch depicting  $\bar{H}_G$ . Thus the external forces acting on the system must exert a net moment that is clockwise relative to the sketch. Such a moment is provided by the bearings, which exert forces situated in the plane of the diagram. Their total moment about point  $G$  must equal  $d\bar{H}_G/dt$ . In addition, when  $\Omega$  is constant, the center-of-mass acceleration is directed toward the shaft. The sum of the bearing forces must equal  $m\bar{a}_G$ , which also is situated in the plane of the sketch. From these observations we conclude that the bearing forces required to sustain a constant  $\Omega$  act perpendicularly to the shaft in the plane of the plate. Both  $|d\bar{H}_G/dt|$  and  $|m\bar{a}_G|$  are proportional to  $\Omega^2$ , which means that these bearing forces will increase as the square of the rotation rate. We say that these are the *dynamic reactions* because they are generated to support the rotation. In contrast the static reactions counter the gravity force. They act in the fixed vertical direction. The direction of the dynamic reactions rotates at  $\Omega$ , so the components of the dynamic reactions in the fixed horizontal and vertical directions vary sinusoidally as  $\cos(\Omega t)$  and  $\sin(\Omega t)$ . Thus we see that the system supporting the bearings will experience fluctuating forces having an amplitude that increases as  $\Omega^2$ . Such forces could induce strong vibration in the supporting system.

**EXAMPLE 5.11** The square plate is pinned at corner  $A$  to the vertical shaft, which rotates at the constant angular speed  $\Omega$ . The angle  $\theta$  is an arbitrary function of time. Determine  $d\bar{H}_A/dt$  for the plate as a function of  $\theta$ .



Example 5.11

### 5.3 Rate of Change of Angular Momentum

283

**SOLUTION** The rotation in this example occurs about two axes, so this solution will give a more complete picture of the general procedures. Nevertheless, the motion is sufficiently simple that we will be able to understand the physical meaning of the result. To form  $\bar{H}_A$ , the origin of  $xyz$  must coincide with point  $A$ . We align the  $x$  axis with edge  $AD$  and the  $y$  axis with edge  $AB$ , which are parallel to the centroidal axes described in the Appendix. The inertia properties obtained from the parallel axis theorems are

$$I_{xx} = I_{yy} = \frac{1}{3}mL^2, \quad I_{zz} = \frac{2}{3}mL^2, \\ I_{xy} = \frac{1}{4}mL^2, \quad I_{xz} = I_{yz} = 0.$$

The  $\Omega$  rotation occurs about the fixed vertical axis, which we designate as  $\bar{K}$ . The  $\theta$  rotation occurs about the pin, whose axis is perpendicular to the plate; this is the body-fixed  $z$  axis. The general expressions for the angular velocity of  $xyz$  and of the reference frames for the rotation directions are

$$\bar{\omega} = \Omega \bar{e}_1 + \dot{\theta} \bar{e}_2, \quad \bar{e}_1 = \bar{K}, \quad \bar{\Omega}_1 = \bar{0}, \quad \bar{e}_2 = \bar{k}, \quad \bar{\Omega}_2 = \bar{\omega}.$$

The angular acceleration corresponding to constant  $\Omega$  and variable  $\dot{\theta}$  are

$$\bar{\alpha} = \ddot{\theta} \bar{e}_2 + \dot{\theta} (\bar{\omega} \times \bar{e}_2).$$

It is convenient to let  $\gamma = \pi/4 + \theta$ , so that

$$\bar{\omega} = \Omega (\sin \gamma \bar{i} + \cos \gamma \bar{j}) + \dot{\theta} \bar{k}, \\ \bar{\alpha} = \Omega \dot{\theta} (\cos \gamma \bar{i} - \sin \gamma \bar{j}) + \ddot{\theta} \bar{k}.$$

Equation (5.2.3) for the present rotation gives

$$\bar{H}_A = (I_{xx}\omega_x - I_{xy}\omega_y) \bar{i} + (I_{yy}\omega_y - I_{yx}\omega_x) \bar{j} + I_{zz}\omega_z \bar{k} \\ = mL^2 \left[ \Omega \left( \frac{1}{3} \sin \gamma - \frac{1}{4} \cos \gamma \right) \bar{i} + \Omega \left( \frac{1}{3} \cos \gamma - \frac{1}{4} \sin \gamma \right) \bar{j} + \frac{2}{3} \dot{\theta} \bar{k} \right],$$

and the corresponding expression for the body-fixed derivative of  $\bar{H}_A$  is

$$\frac{\partial \bar{H}_A}{\partial t} = (I_{xx}\alpha_x - I_{xy}\alpha_y) \bar{i} + (I_{yy}\alpha_y - I_{yx}\alpha_x) \bar{j} + I_{zz}\alpha_z \bar{k} \\ = mL^2 \left[ \Omega \dot{\theta} \left( \frac{1}{3} \cos \gamma + \frac{1}{4} \sin \gamma \right) \bar{i} + \Omega \dot{\theta} \left( -\frac{1}{3} \sin \gamma - \frac{1}{4} \cos \gamma \right) \bar{j} + \frac{2}{3} \ddot{\theta} \bar{k} \right].$$

The rate at which angular momentum changes is correspondingly found to be

$$\dot{\bar{H}}_A = \frac{\partial \bar{H}_A}{\partial t} + \bar{\omega} \times \bar{H}_A \\ = mL^2 \Omega \dot{\theta} \left( \frac{2}{3} \cos \gamma + \frac{1}{2} \sin \gamma \right) \bar{i} + mL^2 \Omega \dot{\theta} \left( -\frac{2}{3} \sin \gamma - \frac{1}{2} \cos \gamma \right) \bar{j} \\ + mL^2 \left[ \frac{2}{3} \ddot{\theta} + \frac{1}{4} \Omega^2 ((\cos \gamma)^2 - (\sin \gamma)^2) \right] \bar{k}.$$

The result was requested as a function of  $\theta$ , which we can recover by setting  $\gamma = \pi/4 + \theta$  in the trigonometric terms. The identities for the sine and cosine of a sum lead to

$$\begin{aligned}\dot{\bar{H}}_A = & \frac{\sqrt{2}}{12}mL^2\Omega\dot{\theta}(7\cos\theta - \sin\theta)\bar{i} + \frac{\sqrt{2}}{12}mL^2\Omega\dot{\theta}(-7\cos\theta - \sin\theta)\bar{j} \\ & + mL^2\left[\frac{2}{3}\ddot{\theta} - \frac{1}{4}\Omega^2\sin 2\theta\right]\bar{k}.\end{aligned}\quad \triangleleft$$


To understand this result it is useful to eliminate  $\gamma$  in the preceding expression for  $\bar{H}_A$ . Doing so yields

$$\bar{H}_A = \frac{\sqrt{2}}{24}mL^2\Omega(\cos\theta + 7\sin\theta)\bar{i} + \frac{\sqrt{2}}{24}mL^2\Omega(\cos\theta - 7\sin\theta)\bar{j} + \frac{2}{3}mL^2\dot{\theta}\bar{k}.$$

We may separately examine the manner in which  $\Omega$  and  $\dot{\theta}$  cause  $\bar{H}_A$  to change. Let us designate the portion of  $\bar{H}_A$  that lies in the plane of the plate as  $\bar{H}_{\parallel} = (H_A)_x\bar{i} + (H_A)_y\bar{j}$ . When  $\theta = 0$  the components of  $\bar{H}_{\parallel}$  have equal magnitude. In that case  $\bar{H}_{\parallel}$  is along the diagonal to corner  $C$ , which is aligned with vertical rotation axis. When  $\theta > 0$ , we see that  $(H_A)_x > (H_A)_y$ , which means that the angle from the  $y$  axis to  $\bar{H}_{\parallel}$  exceeds  $\pi/4$ . In fact, this angle, which is given by

$$\beta = \tan^{-1}\left[\frac{(H_A)_x}{(H_A)_y}\right] = \tan^{-1}\left(\frac{\cos\theta + 7\sin\theta}{\cos\theta - 7\sin\theta}\right),$$

can be shown to be greater than  $\gamma = \pi/4 + \theta$ , so the angle from the  $y$  axis to  $\bar{H}_{\parallel}$  exceeds the angle to the  $\Omega$  rotation vector. Thus  $\bar{H}_{\parallel}$  is situated as shown in the second sketch.



Rotation about the vertical axis causes the tip of  $\bar{H}_{\parallel}$  to move in the negative  $\bar{k}$  direction. This portion combines with the term  $I_{zz}\ddot{\theta}$  corresponding to the changing magnitude of  $\bar{H}_A \cdot \bar{k}$  to produce the  $\bar{k}$  component of  $d\bar{H}_A/dt$ .

This is not the sole effect of the  $\Omega$  rotation on  $\bar{H}_A$ . The sketch shows  $\bar{H}_A \cdot \bar{k} = I_{zz}\dot{\theta}$ . Rotation about the vertical axis at  $\Omega$  causes the tip of this vector to move in the horizontal direction, parallel to the plane of the plate. This is one of the effects

producing the  $\bar{i}$  and  $\bar{j}$  components of  $d\bar{H}_A/dt$ . The other source of these components is the fact that changing  $\theta$  changes  $(H_A)_x$  and  $(H_A)_y$ .

The fact that two rotations are present in this system makes it more difficult than in the previous example to visualize the reasons why the angular momentum changes. As system complexity increases, we will come to rely on the analytical result, and only occasionally seek a physical explanation for some particularly interesting aspect.

## SELECTED REFERENCES


- 
- Arnold, R. N., and Maunder, M., *Gyrodynamics and Its Engineering Applications*, Academic, New York (1961).
- Beer, F. P., Johnston, E. R., Jr., Clausen, W. E., and Staab, G. H., *Vector Mechanics for Engineers*, 7th ed., McGraw-Hill, New York (2004).
- Boas, M. L., *Mathematical Methods in the Physical Sciences*, 3rd ed., Wiley, New York (2006).
- D'Souza, A. F., and Garg, V. K., *Advanced Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1985).
- Ginsberg, J. H., and Genin, J., *Dynamics*, 2nd ed., Wiley, New York (1984).
- Goldstein, H., *Classical Mechanics*, 2nd ed., Addison-Wesley, Reading, Massachusetts (1980).
- Goodman, L. E., and Warner, W. H., *Dynamics*, Dover, New York (2001).
- Greenwood, D. T., *Principles of Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1965).
- Greiner, W., *Classical Mechanics: Systems of Particles and Hamiltonian Dynamics*, Springer-Verlag, New York (2003).
- Haug, E. J., *Intermediate Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1992).
- Hibbeler, R. C., *Engineering Mechanics—Combined*, 10th ed., Prentice-Hall, Englewood Cliffs, New Jersey (2003).
- Josephs, H., and Huston, R. L., *Dynamics of Mechanical Systems*, CRC Press, Boca Raton, Florida (2002).
- Marion, J. B., *Classical Dynamics of Particles and Systems*, Academic, New York (1960).
- Meirovitch, L., *Methods of Analytical Dynamics*, McGraw-Hill, New York (1970).
- Muvdi, B. B., Al-Khafaji, A. W., and McNabb, J. W., *Statics for Engineers*, Springer-Verlag, New York (1997).
- Protter, M. H., and Morrey, C. B., Jr., *Intermediate Calculus*, Springer-Verlag, New York (1985).
- Schaub, H., and Junkins, J. L., *Analytical Mechanics of Space Systems*, American Institute of Aeronautics and Astronautics, Reston, Virginia (2003).
- Shames, I. H., *Engineering Mechanics. Dynamics*, 4th ed., Prentice-Hall, Upper Saddle River, New Jersey (1997).
- Sverdrup, K. A., Duxbury, A. B., and Duxbury, A. C., *An Introduction to the World's Oceans*, 8th ed., McGraw-Hill, New York (2005).

Syngé, J. L., and Griffith, B. A., *Principles of Mechanics*, 3rd ed., McGraw-Hill, New York (1959).

Thomson, W. T., *Introduction to Space Dynamics*, Dover, New York (1986).


## HOMEWORK PROBLEMS

**EXERCISE 5.1** Spheres  $A$  and  $B$  are welded to a connecting bar of negligible mass that is mounted obliquely on a shaft that rotates at the constant rate  $\Omega$ . The mass of the shaft also is negligible, so the center of mass  $O$  of this system is situated on the shaft. Thus the system is statically balanced. Evaluate the angular momentum of the two spheres about the center of mass when the connecting bar is horizontal and when the shaft has rotated by  $1^\circ$  from that position. The difference between the value of the angular momentum at these two positions is approximately  $d\bar{H}_O$ . Evaluate that difference, and from that result deduce the sense of the moment the bearing forces must exert to sustain a constant rotation rate.



Exercise 5.1

**EXERCISE 5.2** The bar is pinned to the vertical shaft, whose rate of rotation is  $\Omega$ . The mass distribution of the bar is represented by three small spheres having mass  $m/3$  shown in the sketch. Consider the situation in which the bar is falling at  $\dot{\theta} = 2\Omega$  at the instant when  $\theta = 53.13^\circ$ . Determine and sketch the angular velocity and angular momentum of the bar relative to pin  $A$ . Then use these quantities to evaluate the kinetic energy of the bar and verify that this result is the same as that obtained by adding the kinetic energy of each sphere.




Exercise 5.2

**EXERCISE 5.3** Use integration to determine the inertia properties of the truncated parallelepiped in Example 5.5 relative to the  $XYZ$  system defined there.

**EXERCISE 5.4** Derive the centroidal location and centroidal inertia properties of a homogeneous prism, as tabulated in the Appendix.

**EXERCISE 5.5** Use integration to determine the inertia properties of the semicone appearing in the Appendix.

**EXERCISE 5.6** The body in the sketch is a truncated cone. Use integration to determine its inertia properties relative to the  $xyz$  coordinate system in the sketch.




Exercise 5.6

## Homework Problems

287


**EXERCISE 5.7** A constant thickness shell is a body whose dimension measured perpendicular to its curved surface is an invariant value that is a small fraction of the other dimensions. Consider a semiconical shell whose thickness is  $h$ . The origin of  $xyz$  is placed at the apex and the  $z$  axis is aligned with the cone's axis. (a) Use cylindrical coordinates to evaluate the inertia properties. (b) Use spherical coordinates to evaluate the inertia properties.



Exercise 5.7


**EXERCISE 5.8** Use integration to determine the inertia properties of a spheroid tabulated in the Appendix.

**EXERCISE 5.9** The thin wire is bent to a parabolic shape such that its centerline is defined by the generic equation  $y = kx^2$ . The wire is steel,  $\rho = 7800 \text{ kg/m}^3$ , and its circular cross section has a 20-mm diameter. Use numerical integration to determine its mass, the location of its center of mass, and its moments and products of inertia relative to the  $xyz$  coordinate system in the sketch.




Exercise 5.9

**EXERCISE 5.10** A cylinder is sliced in half along its diagonal. Determine the location of the center of mass and the inertia properties relative to a coordinate system whose  $z$  axis coincides with the axis of the cylinder and whose origin is situated at the circular end.




Exercise 5.10

**EXERCISE 5.11** The semicircular cutout in the steel cylinder is filled with lead. Determine the centroidal location and the inertia properties of this body with respect to the centroidal coordinate system whose axes are parallel to the  $xyz$  system shown.




Exercise 5.11

**EXERCISE 5.12** Use the inertia properties of an orthogonal tetrahedron given in the Appendix to determine the location of the center of mass and inertia properties of the tetrahedron relative to the  $xyz$  coordinate specified in the sketch.




**Exercise 5.12**

**EXERCISE 5.13** The  $x$  axis forms a diagonal intersecting the centroid of the homogeneous cylinder. Determine the inertia properties of the cylinder with respect to  $xyz$ .




**Exercise 5.13**

**EXERCISE 5.14** A rotor in the shape of a disk is welded obliquely to a shaft, such that its centerline does not coincide with the axis of the shaft. The mass of the shaft is 5 kg, and the rotor's mass is 20 kg. Determine the location of the center of mass of this assembly, then evaluate the centroidal moments and products of inertia for a coordinate system whose  $x$  axis coincides with the axis of the shaft.



**Exercise 5.14**

**EXERCISE 5.15** The mass per unit length of the wire frame is the constant value  $\sigma$ . Determine its inertia properties relative to the  $xyz$  coordinate system in the sketch.




**Exercise 5.15**

## Homework Problems


289

**EXERCISE 5.16** The origin of the  $xyz$  coordinate system coincides with the centroid of the upper face of the box. The mass of the box is 10 kg. Graph  $I_{xx}$ ,  $I_{yy}$ , and  $I_{xy}$  as functions of  $\theta$ . Also determine the values of  $\theta$  for which  $|I_{xy}|$  has its maximum and minimum values.




Exercise 5.16

**EXERCISE 5.17** Two metal plates are welded to the aluminum cylinder as shown in the sketch. Each plate has a mass of 20 kg, and the mass of the cylinder is 200 kg. Determine the location of the center of mass and the moments and products of inertia of this body relative to the  $xyz$  coordinate system shown in the sketch.



Exercise 5.17


**EXERCISE 5.18** The  $x$  axis lies in the plane of the 500-g plate, and the  $y$  axis is elevated at  $25^\circ$  above the diagonal. Determine the inertia matrix of the plate relative to the  $xyz$  coordinate system in the sketch.



Exercises 5.18 and 5.19

**EXERCISE 5.19** The mass of the plate is 500 g. Determine the principal moments of inertia relative to a coordinate system whose origin coincides with the origin of  $xyz$  depicted in the sketch.

**EXERCISE 5.20** A rigid body consists of five small spheres of mass  $m$  mounted at the corners of a lightweight wire frame in the shape of an orthogonal pyramid. Determine the principal moments of inertia and the direction angle between each principal axis and the  $xyz$  coordinate axes.




Exercise 5.20

**EXERCISE 5.21** The  $y$  axis is normal to the inclined face of the 400-kg homogeneous prism. Consider the situation in which the  $x$  axis coincides with diagonal  $AC$ . Determine the inertia matrix of the prism relative to this coordinate system.



**EXERCISE 5.22** The  $y$  axis is normal to the inclined face of the 400-kg homogeneous prism. Is there any value of the angle  $\theta$  for which the product of inertia  $I_{xz} = 0$ ? If so, what is the angle and what is the corresponding inertia matrix?




Exercises 5.21, 5.22, and 5.23

**EXERCISE 5.23** The prism's mass is 400 kg. Determine the principal moments of inertia with respect to a coordinate system whose origin is coincident with the origin of  $xyz$  in the sketch. Also determine the rotation transformation for the principal axes relative to coordinate axes aligned with the orthogonal edges.

**EXERCISE 5.24** Consider the tetrahedron in Exercise 5.12. Determine the principal moment of inertia for the origin specified there. Also determine the direction angle of the principal axes relative the given  $xyz$  coordinate system.

**EXERCISE 5.25** In the case of a flat plate having an arbitrary shape, any coordinate system whose  $xy$  plane coincides with the midplane is a plane of symmetry, so that  $I_{xz}$  and  $I_{yz}$  are identically zero. In such situations the principal axes are obtained by a rotation transformation by angle  $\theta$  about the  $z$  axis, which one can evaluate by considering only the inertia properties with respect to the  $xy$  plane. A Mohr's circle construction, typically encountered in stress analysis, may be used to perform such an evaluation. Derive expressions for  $I_{x'x'}$ ,  $I_{y'y'}$ , and  $I_{x'y'}$  corresponding to arbitrary values of  $I_{xx}$ ,  $I_{yy}$ , and  $I_{xy}$ . Show that if the points  $(I_{x'x'}, I_{x'y'})$  and  $(I_{y'y'}, -I_{x'y'})$  are plotted relative to orthogonal axes, the distance between these points is constant, regardless of  $\theta$ . From this, prove that the points lie on a circle. Then explain the significance of the angle from the abscissa to the line connecting the plotted points. Also explain how the principal moments of inertia may be evaluated from the properties of the circle.

**EXERCISE 5.26** Thin bar  $ACB$  is welded to a shaft that rotates at the constant angular speed  $\Omega$ , so the angle  $\theta$  between the bar and the shaft is constant. (a) Derive expressions for the angular momentum  $\bar{H}_C$  and the kinetic energy of the bar. Draw a sketch of  $\bar{H}_C$ . (b) Based on an analysis of the manner in which  $\bar{H}_C$  in Part (a) rotates, derive an expression for  $d\bar{H}_C/dt$ . (c) Use Eq. (5.3.4) to evaluate  $d\bar{H}_C/dt$ , and compare it with the result of Part (b).




Exercise 5.26

## Homework Problems


291

**EXERCISE 5.27** Two identical disks having radius  $R$  and mass  $m$  are welded together by a rigid bar. The ends of the connecting bar are welded at diametrically opposite points on the perimeter of each wheel. The mass of the rod also is  $m$ . The disks roll without slipping at constant speed  $v$ . Derive an expression for the angular momentum of this assembly about its center of mass as a function of the angle  $\theta$  for the rolling. Depict this quantity in a sketch for  $\theta = 0$  and  $\theta = 90^\circ$ , and describe the corresponding friction and normal forces that are required to maintain the steady rolling. *Hint:* Use a body-fixed coordinate system whose  $y$  axis aligns with the disks' center line, and whose  $z$  axis is perpendicular to the bar.




Exercise 5.27

**EXERCISE 5.28** The 24-kg block is welded to a shaft that rotates about bearings  $A$  and  $B$  at a constant rate  $\omega$ . The shaft is collinear with the diagonal to a face of the block. Determine the inertia properties of the block relative to the  $xyz$  coordinate system in the sketch, whose  $x$  axis coincides with the shaft and whose  $z$  axis is normal to the face of the block. Also determine the inertia properties for a set of principal axes sharing the same origin as  $xyz$ . Then evaluate the angular momentum about the origin of  $xyz$  and the kinetic energy of the block by using each set of inertia properties.




Exercise 5.28

**EXERCISE 5.29** A 200-g rectangular plate is mounted diagonally on a shaft whose mass is negligible. The system has an unsteady rotation rate  $\Omega$ . Determine the force-couple system acting at bearing  $B$  that is equivalent to the external forces that must be applied to attain such a motion. What portion of that couple represents the torque required to change  $\Omega$ ?




Exercise 5.29

**EXERCISE 5.30** The sketch shows a steel plate whose thickness perpendicular to the plane of the diagram is very small. The mass per unit surface area of this plate is  $\sigma$ . The plate rotates about axis  $AB$  at constant angular speed  $\omega$ . (a) Determine the mass and the location of the center of mass of this plate. (b) Determine  $I_{xx}$ ,  $I_{yy}$ , and  $I_{xy}$  for the  $xyz$  coordinate system shown in the sketch. (c) Determine  $\bar{H}_O$  and  $d\bar{H}_O/dt$  for the plate about origin  $O$  on the axis of rotation. Draw a sketch  $\bar{H}_O$  and explain the sense of  $d\bar{H}_O/dt$  by considering how  $\bar{H}_O$  rotates. (d) Predict the direction of the dynamic reactions exerted by bearings at ends  $A$  and  $B$ .




Exercise 5.30

**EXERCISE 5.31** The right triangular plate is welded to the shaft, which rotates at constant speed  $\omega$ . Determine the force-couple acting at bearing  $A$  that is equivalent to the force system the bearings must exert to sustain this motion.



Exercise 5.31

**EXERCISE 5.32** The gyroscopic turn indicator consists of a 1-kg flywheel whose principal radii of gyration are  $\kappa_x = 50$  mm,  $\kappa_y = \kappa_z = 35$  mm, where the  $x$  axis is the flywheel's axis of symmetry. The center of mass of the flywheel coincides with the intersection of axes  $AB$  and  $CD$ . The flywheel spins relative to the gimbal at the constant rate  $\Omega_1 = 50\,000$  rev/min, while the whole system rotates about the vertical axis at  $\Omega_2 = 1.2$  rad/s. The pivot angle  $\beta$  is constant. Determine the force-couple system acting on the flywheel at its center that is equivalent to the actual forces acting on it, assuming that only the mass of the flywheel is significant. What portion of this couple represents the torque  $M$  that must be applied to shaft  $CD$ ?




Exercise 5.32

## Homework Problems


293

**EXERCISE 5.33** The radar antenna tracks airplane  $P$  by rotating about the vertical axis at  $\dot{\psi}$  while the elevation angle  $\theta$  is adjusted. Assuming that the body-fixed  $xyz$  axes are principal, what is the force–couple system acting at the stationary pivot  $O$  that must be applied to overcome the inertial resistance when  $\psi$  and  $\theta$  are arbitrary time functions?



Exercise 5.33


**EXERCISE 5.34** The rotation rates of the ship with respect to the body-fixed centroidal  $xyz$  coordinate system in the sketch are the pitch  $\omega_x$ , roll  $\omega_y$ , and yaw  $\omega_z$ . Consider the case in which these rates simultaneously attain their maximum magnitudes, with  $\omega_x = 0.5$  rad/s,  $\omega_y = -1.1$  rad/s,  $\omega_z = 0.2$  rad/s. The accelerations of the center of mass at this instant are  $a_x = 5$  m/s<sup>2</sup>,  $a_y = -12$  m/s<sup>2</sup>,  $a_z = 15$  m/s<sup>2</sup>. The mass of the ship is  $40(10^6)$  kg, and the radii of gyration are  $\kappa_x = 90$  m,  $\kappa_y = 10$  m,  $\kappa_z = 15$  m; it may be assumed that  $xyz$  are principal axes. Determine the force–couple system acting at the origin of  $xyz$  that is equivalent to the forces exerted on the ship by the ocean.



Exercise 5.34

**EXERCISE 5.35** A very thin circular disk rolls without slipping relative to the ground such that its plane is oriented vertically throughout the motion. Consider the situation in which the center  $C$  of the disk follows a circular path of radius  $\rho$ . Determine  $\bar{H}_C$  and  $d\bar{H}_C/dt$ . From those results explain why the condition that the plane of the disk be vertical can be satisfied only if the center follows a straight path, unless forces other than gravity and the contact force are exerted on the disk.


**EXERCISE 5.36** The device shown is a wobble plate, in which the precession rate  $\omega_1$  of shaft  $AB$  and the spin rate  $\omega_2$  of the disk relative to the shaft are constant. The mass of the shaft is negligible. Let  $\lambda$  denote the ratio of the angular speeds, such that  $\omega_2 = \lambda\omega_1$ . (a) In terms of  $\omega_1$  and  $\lambda$ , derive expressions for the angular velocity, angular momentum  $H_C$  relative to the center of the disk, and  $d\bar{H}_C/dt$ . (b) Evaluate the results in Part (a) for the case in which  $\lambda = 3$ , and draw a sketch depicting these quantities. Determine the magnitude of each and the angle between each quantity and the bearing axis  $AB$ . (c) Determine whether there is any value of  $\lambda$  for which no



Exercise 5.36


dynamic reactions are generated at bearings  $A$  and  $B$ . Explain your answer in terms of the properties of  $H_C$ .

**EXERCISE 5.37** Arm  $ABC$  rotates about the vertical axis at constant rate  $\omega_1$ , and the disk rotates relative to the arm at constant rate  $\omega_2$ . The mass of the disk is  $m$ , and its centroidal moments of inertia are  $I_1 = 0.5mR^2$  about its centerline and  $I_2 = 0.25mR^2$  about a diameter. (a) Draw one or more sketches depicting the angular momentum  $\bar{H}_C$  of the disk about its center. (b) Based on the sketch(es) in Part (a) and the manner in which the system rotates, evaluate  $d\bar{H}_C/dt$ . (c) Compare the result in Part (b) with what is obtained by evaluating  $\partial\bar{H}_C/\partial t + \bar{\omega} \times \bar{H}_C$ .



Exercise 5.37

**EXERCISE 5.38** The topic of rotation of a body in free motion is treated extensively in Chapter 10. Some key aspects of that study are described in the sketch, which shows a body that is axisymmetric about the body-fixed  $z$  axis. The moment of inertia of the body about this axis is  $I_1$ , and the moment of inertia about any axis intersecting the center of mass and perpendicular to  $z$  is  $I_2$ . The body is in free flight and air resistance is negligible, so the only force acting on the body is its weight. Because this force acts at the center of mass  $G$ ,  $\Sigma \bar{M}_G = d\bar{H}_G/dt \equiv \bar{0}$ , so the angular momentum  $\bar{H}_G$  is constant. Let the fixed  $Z$  axis denote the constant direction of  $\bar{H}_G$ . Eulerian angles are used to describe the rotation of the body, with precession angle  $\psi$  being defined as the rotation about the fixed  $Z$  axis and the spin angle  $\phi$  being the rotation about the  $z$  axis of symmetry. The nutation angle  $\theta$  is the angle between these two axes, as shown in the sketch. (a) Describe the angular velocity of the body in terms of  $\psi$ ,  $\theta$ , and  $\phi$ . Use this description of  $\bar{\omega}$  to derive an expression for  $\bar{H}_G$ . (b) Derive a component description for  $\bar{H}_G$  based on the fact that  $\bar{H}_G$  is parallel to the  $Z$  axis. Match this description to the expression for  $\bar{H}_G$  in Part (a). Show that the two descriptions are consistent only if the nutation angle is constant, that is,  $\dot{\theta} = 0$ . (c) From the fact that  $\dot{\theta} = 0$ , it follows that at any instant the angular velocity  $\bar{\omega}$  must lie in the  $xz$  plane, so that  $\bar{\omega} = \omega \sin \beta \bar{i} + \omega \cos \beta \bar{k}$ , where  $\beta$  is the angle between  $\bar{\omega}$  and the  $z$  axis, and the  $x$  axis lies in the plane formed by  $Z$  and  $z$ . Compare the descriptions of  $\bar{\omega}$  and  $\bar{H}_G$  in terms of  $\omega$  and  $\beta$  with the corresponding expressions in terms of  $\psi$ ,  $\theta$ , and  $\phi$ . From that comparison, derive the expression



Exercise 5.38


$$\tan \beta = \frac{I_1}{I_2} \tan \theta.$$

(d) Derive an expression for  $\dot{\psi}$  in terms of  $\dot{\phi}$  and  $\theta$ .

### Homework Problems

295

**EXERCISE 5.39** The disk is mounted obliquely on its hub, which spins at angular speed  $\Omega$  about the horizontal arm  $AB$  of the T-bar. Consequently, the disk's center line forms a constant angle  $\theta$  relative to arm  $AB$ . This rotation rate is  $\dot{\phi}$ , with  $\phi = 0$  corresponding to the instant depicted in the sketch, where the disk's axis is situated in the vertical plane. Both this rotation rate and the precession rate  $\Omega$  are constant. The disk's mass is  $m$ , whereas the hub and both shafts have negligible mass. Derive an expression for the force–couple system exerted on the disk by hub  $B$  when  $\phi = 0$ .



Exercise 5.39

**EXERCISE 5.40** Determine the force–couple systems in Exercise 5.39 as a function of the rotation angle  $\phi$ .

## CHAPTER 6

# Newton–Euler Equations of Motion

The previous chapter focused on describing and understanding the variability of angular momentum. We now apply those concepts to relate the motion of a system to the forces driving that motion. The formulation is based on the linear and angular momentum principles of Newton and Euler. These principles govern the motion of a single rigid body, but practical applications feature many bodies. In such situations, individual equations of motion may be written for each body. If one pursues such an analysis, careful attention must be given to accounting for the forces exerted between bodies, so the construction of free-body diagrams will play a prominent role in this chapter's development. As a supplement to this approach, a following section develops a momentum-based concept for systems of rigid bodies that sometimes can lead to the desired solution without considering all of the interaction forces. Ultimately, the energy-based concepts associated with Lagrange, whose development is taken up in the next chapter, provide a more robust alternative approach. However, they are mathematical in nature and afford little physical insight. For this reason, particular attention is given here to providing physical explanations for the results derived from the Newton–Euler formulation of equations of motion.

## 6.1 FUNDAMENTAL EQUATIONS

### 6.1.1 Basic Considerations

The basic laws governing each rigid body in a system are Eq. (5.1.13) for the resultant force and Eq. (5.1.22) for the resultant moment, which are repeated here as a single reference:

$$\begin{aligned}\Sigma \bar{F} &= m\bar{a}_G, \\ \Sigma \bar{M}_A &= \frac{\partial \bar{H}_A}{\partial t} + \bar{\omega} \times \bar{H}_A.\end{aligned}\tag{6.1.1}$$


It cannot be emphasized too much that this moment equation should be applied only when point  $A$  is either

1. the center of mass of the body, or
2. a fixed point in a body that is in a state of pure rotation.

## 6.1 Fundamental Equations

297

From a philosophical viewpoint, each expresses a dynamic equilibrium, in which either the forcing or the inertial effect can be considered to be the causative agent. For example, in some situations we might consider the resultant moment to change the angular momentum of the body, whereas in others it might be better to consider that changing the linear momentum requires application of the required moment. The same is true for angular momentum. The key to understanding is recognizing that one must accompany the other. A conceptual picture reinforcing this perspective is provided in Fig. 6.1, where the inertial effects are depicted as a force–couple system acting at the center of mass  $G$ . The equations of motion state that this combination is equivalent to the actual force system acting on the body. One side of the figure cannot exist without the other.



**Figure 6.1.** The force system acting on a body and its equivalent inertial effect.

Some individuals use a diagram such as Fig. 6.1 as the basis for a slightly modified set of equations of motion based on summing moments about an arbitrary point. Because the forces and inertial effects in Fig. 6.1 have equivalent effect, the moment of each about the selected point must be equal, which leads to

$$\Sigma \bar{M}_B = \frac{d\bar{H}_G}{dt} + \bar{r}_{G/B} \times m\bar{a}_G. \quad (6.1.2)$$

This equation of motion is reminiscent of the general principle in Eq. (5.1.18), except that the kinematical reference point is the center of mass, rather than the point for the moment sum. The formulation is like the treatment of a static system, for which one can select the point for a moment sum to avoid the occurrence of some unknown reactions in the moment equation. From a practical standpoint, the simplification of possibly eliminating an unknown variable is balanced by the need to include a linear acceleration in the moment equation. This increases the chance for error, especially in regard to signs. An analysis following this approach is seldom necessary for a single rigid body. However, we will see later in this chapter that it can be quite useful for some systems containing several interconnected bodies.

Both the force and moment equations of motion are vector relations, whose formulation requires definition of an  $xyz$  coordinate system for components. For the moment equation this coordinate system will always be attached to the body. The basic relations for  $\bar{H}_A$  and its relative derivative were found to be



$$\begin{aligned}
 \bar{H}_A &= (I_{xx}\omega_x - I_{xy}\omega_y - I_{xz}\omega_z)\bar{i} + (I_{yy}\omega_y - I_{yx}\omega_x - I_{yz}\omega_z)\bar{j} \\
 &\quad + (I_{zz}\omega_z - I_{zx}\omega_x - I_{zy}\omega_y)\bar{k}, \\
 \frac{\partial \bar{H}_A}{\partial t} &= (I_{xx}\alpha_x - I_{xy}\alpha_y - I_{xz}\alpha_z)\bar{i} + (I_{yy}\alpha_y - I_{yx}\alpha_x - I_{yz}\alpha_z)\bar{j} \\
 &\quad + (I_{zz}\alpha_z - I_{zx}\alpha_x - I_{zy}\alpha_y)\bar{k}.
 \end{aligned} \tag{6.1.3}$$

In some situations it might be easier to analyze the acceleration of the center of mass or the resultant force components with respect to a global coordinate system  $\hat{x}\hat{y}\hat{z}$  that is not attached to the body. Such a coordinate system can be used for formulate the force equations. To emphasize this aspect, the components of force and moment are indicated explicitly as dot products in the following equations:

$$\begin{aligned}
 \Sigma \bar{F} \cdot \hat{i} &= m(\bar{a}_G \cdot \hat{i}), \quad \Sigma \bar{F} \cdot \hat{j} = m(\bar{a}_G \cdot \hat{j}), \\
 \Sigma \bar{F} \cdot \hat{k} &= m(\bar{a}_G \cdot \hat{k}), \\
 \Sigma \bar{M}_A \cdot \bar{i} &= \left( \frac{\partial \bar{H}_A}{\partial t} + \bar{\omega} \times \bar{H}_A \right) \cdot \bar{i}, \quad \Sigma \bar{M}_A \cdot \bar{j} = \left( \frac{\partial \bar{H}_A}{\partial t} + \bar{\omega} \times \bar{H}_A \right) \cdot \bar{j}, \\
 \Sigma \bar{M}_A \cdot \bar{k} &= \left( \frac{\partial \bar{H}_A}{\partial t} + \bar{\omega} \times \bar{H}_A \right) \cdot \bar{k}.
 \end{aligned} \tag{6.1.4}$$

Matrix notation offers a compact scheme for performing calculations, and several symbolic mathematics software packages are well attuned to such notation. The angular momentum was written in this form in Eq. (5.2.5). The corresponding forms of the equations of motion are

$$\begin{aligned}
 \begin{Bmatrix} \Sigma \bar{F} \cdot \hat{i} \\ \Sigma \bar{F} \cdot \hat{j} \\ \Sigma \bar{F} \cdot \hat{k} \end{Bmatrix} &= m \begin{Bmatrix} (\bar{a}_G \cdot \hat{i}) \\ (\bar{a}_G \cdot \hat{j}) \\ (\bar{a}_G \cdot \hat{k}) \end{Bmatrix}, \\
 \begin{Bmatrix} \Sigma \bar{M}_A \cdot \bar{i} \\ \Sigma \bar{M}_A \cdot \bar{j} \\ \Sigma \bar{M}_A \cdot \bar{k} \end{Bmatrix} &= [I] \begin{Bmatrix} \alpha_x \\ \alpha_y \\ \alpha_z \end{Bmatrix} + \begin{Bmatrix} \omega_x \\ \omega_y \\ \omega_z \end{Bmatrix} \otimes \begin{Bmatrix} [I] \omega_x \\ [I] \omega_y \\ [I] \omega_z \end{Bmatrix},
 \end{aligned} \tag{6.1.5}$$

where  $\otimes$  denotes the cross-product operator. The moment equations simplify considerably when  $xyz$  are principal axes. The result is *Euler's equations of motion*, which explicitly display the role of the angular velocity and angular acceleration components:

$$\begin{aligned}
 \Sigma \bar{M}_A \cdot \bar{i} &= I_{xx}\alpha_x - (I_{yy} - I_{zz})\omega_y\omega_z, \\
 \Sigma \bar{M}_A \cdot \bar{j} &= I_{yy}\alpha_y - (I_{zz} - I_{xx})\omega_x\omega_z, \\
 \Sigma \bar{M}_A \cdot \bar{k} &= I_{zz}\alpha_z - (I_{xx} - I_{yy})\omega_x\omega_y.
 \end{aligned} \tag{6.1.6}$$

## 6.1 Fundamental Equations

299

One can use the repetitive pattern of Euler's equations to remember the individual components by a mnemonic algorithm based on permutations of the alphabetical order. Euler's equations are particularly useful when it is only necessary to address the moment exerted about one axis.

A basic aspect of the force and moment components is their dual interpretation. One way of evaluating them is to form the resultant as the vector sum of the contribution of each force acting on the body. Alternatively, we may sum the contribution of each force to a specific force or moment component. The latter is very useful for the moment components, which are the moments each force exerts about each of the  $xyz$  coordinate axes.

The previous section made it evident that a spatial rotation will require that  $\bar{H}_A$  change, even if the all rates of rotation are constant, as a consequence of changing the orientation of  $\bar{H}_A$ . The moment equation merely requires that the force system apply a moment that balances the rate at which the angular momentum changes. The moment required to balance the portion of  $d\bar{H}_A/dt$  that features products of rotation rates, and therefore is present even if the rotation rates are constant, is often referred to as the *gyroscopic moment*.

Various questions may be investigated with the equations of motion. In the simplest case, the motion of a rigid body is fully specified. This permits complete evaluation of the right side of the translational and rotational equations. The forcing effects, which appear on the left side of the equations, originate from known excitations, as well as reactions. The latter are particularly important to characterize. A free-body diagram, in which the body is isolated from its surroundings, is essential to the correct description of the reactions. As an aid in drawing a free-body diagram, recall that reactions are the physical manifestations of kinematical constraints. Thus, if a support prevents a point in the body from moving in a certain direction, then at that point there must be a reaction force exerted on the body in that direction. Similarly, a kinematical constraint on rotation about an axis is imposed by a reaction couple exerted about that axis. The reactions are not known in advance—they are unknown values that will appear in some or all of the equations of motion.

In real applications the system usually contains multiple interconnected bodies. Because the translational and rotational equations of motion describe a single isolated body, it is necessary in such cases to isolate each body whose mass is significant. Care must be taken in the respective free-body diagrams to account for Newton's Third Law in the depiction of the connective forces exerted between bodies. There are only six scalar equations of motion for each body contained in a system (three force and three moment components). The unknowns appearing in these equations might be kinematical parameters or parameters describing the forces. Some equations might be trivial as a consequence of the basic nature of the system. For example, planar motion, which is treated in the next section, reduces to two force equations and one moment equation per body. In any event, a system composed of  $N$  bodies can have no more than  $6N$  component equations of motion. It is possible for the number of unknown reactions to exceed the number of available equations, yet for the equations to have a consistent solution for the motion variables. Assuming that this condition does not result from erroneous

omission of some characteristic of the supports, it represents a condition of *redundant constraint*. That is the dynamic analog of the condition of static indeterminacy, whose resolution requires consideration of deformation effects.

In some situations, analysis of a system's motion entails determination of a few unknown constant parameters, such as an angle of orientation or a rotation rate. This is the case, for example, if it is necessary to determine the conditions for a steady precession. The equations of motion in this case are algebraic. The more difficult situation arises when the nature of the motion is not fully known in advance. The orientation of each body may then be described in terms of Eulerian angles (precession, nutation, and spin), and the position of the center of mass of each body may be described by any of the formulations used to describe point motion. In addition to these kinematical variables, parameters describing any reactions will appear in the equations of motion. The reaction parameters enter into the equations of motion algebraically through the force and moment sums. Hence their elimination involves a process of simultaneous solution of algebraic equations. (This, of course assumes that a condition of redundant constraint does not exist.) Algebraic elimination of the force parameters will lead to a set of differential equations of motion for the kinematical variables. We saw that  $d\bar{H}_A/dt$  generally features products of rotation rates, and the description of the motion of a point in terms of curvilinear coordinates or moving reference frames also contains products of rate variables. As a result, the equations of rotational motion will be coupled second-order differential equations. Analytical solutions of such equations are available in limited situations, such as when the equations are linear in the dependent variables. Numerical techniques are always available as an alternative. Procedures for numerically solving differential equations of motion are discussed in Chapters 7 and 8.

### 6.1.2 Procedural Steps

Although a specific system may have distinctive features, many aspects of the formulation of its equations of motion are generic. The following list assembles the operations into a standard procedure that we shall follow in the examples that follow.

1. Draw a free-body diagram describing each body whose mass is significant. To be sure that all constraint forces are properly described, remember that, if the motion of a point is restricted in a certain direction, then an unknown force acts in that direction to impose the condition. Similarly, if the rotation of a body about a certain axis is restricted, then there must be an unknown reaction couple about that axis.
2. Choose a point, designated here as  $A$ , for summing moments for the isolated body. This point should be the center of mass when the body is translating or in general motion. For the case of pure rotation, use the fixed point in order that the reaction forces holding that point stationary not occur in the moment equation of motion.
3. Attach  $xyz$  to the body with origin at point  $A$ . The first consideration in selecting the orientation of  $xyz$  is minimizing computations of inertia properties. Thus, if possible, orient  $xyz$  parallel to the axes used in the Appendix to describe the inertia properties. If this does not lead to a full specification of the coordinate axes, as would be the case for an axisymmetric body, then finalize the definition by considering the


## 6.1 Fundamental Equations

301

axes of rotation and the manner in which the geometry of the system is described. Show the coordinate axes of  $xyz$  in the free-body diagram.

4. Write down, in equation form, all given information that does not appear in the free-body diagram. List all quantities to be determined in the solution.
5. Follow the standard kinematical procedure to describe  $\bar{\omega}$  and  $\bar{\alpha}$  of the body in terms of components relative to  $xyz$ . Be sure to satisfy any auxiliary kinematical conditions that are known, such as that certain points have known motions, or that there is no slipping at some location.
6. Evaluate the inertia properties of the body with respect to  $xyz$ .
7. Compute the moment about point  $A$  exerted by all forces appearing in the free-body diagram. Equate this moment to  $d\bar{H}_A/dt$ . This may be done as a vector equation with Eqs. (6.1.1) and (6.1.3), but the matrix form in Eqs. (6.1.5) might be preferred for numerical problems. Also, if it can be recognized that only the moment about a specific axis  $x$ ,  $y$ , or  $z$  is needed, and  $xyz$  are principal axes, then the corresponding component of Euler's equations, Eqs. (6.1.6), offers a shortcut.
8. Examine whether the moment equation(s) obtained from the preceding step are sufficient to solve the problem. If additional equations are required, form the force equation of motion. In that event describe the center-of-mass acceleration  $\bar{a}_G$  in terms of the basic kinematical parameters. The components of  $\bar{a}_G$  may be described in terms of components with respect to any convenient coordinate system  $x'y'z'$ , although  $xyz$  often will be sufficient for this purpose. Equate like components of  $\Sigma \bar{F}$  and  $m\bar{a}_G$ .
9. Count the number of scalar equations  $J$  and number of unknowns  $N$ . If  $J > N$ , something such as a kinematical relation has been assumed incorrectly, or else a reaction might have been omitted from the free-body diagram. If  $J < N$ , some information that was given might not have been used, or else some kinematical condition imposed on the body, such as rolling without slipping, might not have been satisfied.


**EXAMPLE 6.1** The cylinder, whose mass is  $m$ , is welded to the shaft such that its center is situated on the axis of rotation. Application of a constant torque  $\Gamma$  at  $t = 0$  causes the rotation rate  $\Omega$  to increase from zero. Derive expressions for  $\Omega$  and the reactions at bearings  $A$  and  $B$  as functions of the elapsed time.



Example 6.1

**SOLUTION** This example reinforces our recognition that a planar analysis might not suffice, even though the motion is a simple rotation. Examination of the solution

will lead us to a general discussion of the topic of dynamic imbalance. The forces of interest are the reactions the bearings apply to the shaft. These are represented in the free-body diagram as components transverse to the shaft at both bearings and a thrust component parallel to the shaft at bearing  $A$ . We may consider the shaft and the cylinder to constitute a single body because they are welded together. Doing so makes the forces exerted between them internal to the system. We ignore the weight because it is a static force. It is balanced by a static force acting in the (stationary) vertical direction at each bearing that superposes on the dynamic reactions we shall evaluate.



Free-body diagram of the rigid body consisting of the cylinder and the shaft.

The cylinder executes a simple rotation, so any point along shaft  $AB$  would be an allowable point for summing moments. We use the center of mass  $G$ . We align the  $xyz$  axes with the centerline of the cylinder in accord with the Appendix, and exploit the axisymmetry to define the  $y$  axis to be perpendicular to the plane formed by the shaft and the centerline. We also define an  $x'y'z'$  coordinate system aligned with the shaft and with its  $y'$  axis coincident with the  $y$  axis to facilitate describing the bearing forces and the rotation.

The angular velocity is parallel to the shaft, and the direction of this rotation is constant, so

$$\bar{\omega} = \Omega \bar{k}', \quad \bar{\alpha} = \dot{\Omega} \bar{k}', \quad (6.1.7)$$

which when resolved into  $xyz$  components become

$$\bar{\omega} = \Omega (\sin \theta \bar{i} + \cos \theta \bar{k}), \quad \bar{\alpha} = \dot{\Omega} (\sin \theta \bar{i} + \cos \theta \bar{k}). \quad (6.1.8)$$

We know from symmetry that  $xyz$  are principal axes, and the tabulated inertia properties are

$$I_{xx} = I_{yy} = m \left( \frac{1}{4} R^2 + \frac{1}{12} h^2 \right), \quad I_{zz} = \frac{1}{2} m R^2. \quad (6.1.9)$$

We may employ Euler's equations because  $xyz$  are principal axes. To form the moment resultants the applied couple  $\Gamma$  must be resolved into components. The moment of the bearing forces may be computed vectorially. For example, for bearing  $A$  the moment is  $\bar{r}_{A/G} \times (A_{x'} \bar{i}' + A_{z'} \bar{k}')$ . Alternatively the moment sums can be computed as moments about the coordinate axes. Thus the bearing forces  $A_{x'}$  and  $B_{x'}$  exert moments about only the  $y$  axis, for which the lever arms are  $L/2$ , whereas  $A_{y'}$  and  $B_{y'}$  have lever arms of  $(L/2) \sin \theta$  about the  $z$  axis and  $(L/2) \cos \theta$  about the

## 6.1 Fundamental Equations

303

$x$  axis. Applying the right-hand rule to ascertain the sign of each moment yields

$$\begin{aligned}\Sigma \bar{M}_A \cdot \bar{i} &= \Gamma \sin \theta + (-A_{y'} + B_{y'}) \frac{L}{2} \cos \theta = I_{xx} \alpha_x \\ &= m \left( \frac{1}{4} R^2 + \frac{1}{12} h^2 \right) \dot{\Omega} \sin \theta, \\ \Sigma \bar{M}_A \cdot \bar{j} &= (A_{x'} - B_{x'}) \frac{L}{2} = -(I_{zz} - I_{xx}) \omega_x \omega_z \\ &= m \left( -\frac{1}{4} R^2 + \frac{1}{12} h^2 \right) \Omega^2 \sin \theta \cos \theta, \\ \Sigma \bar{M}_A \cdot \bar{k} &= \Gamma \cos \theta + (A_{y'} - B_{y'}) \frac{L}{2} \sin \theta = I_{zz} \alpha_x \\ &= m \left( \frac{1}{2} R^2 \right) \dot{\Omega} \cos \theta.\end{aligned}$$

The unknowns in these three equations are the four transverse bearing forces and  $\Omega$ . The force equation of motion provides the additional equations required for determining these parameters and the thrust bearing force. The center of mass is on the axis of rotation, so  $\bar{a}_G = \bar{0}$ . In terms of components relative to  $x'y'z'$ , the force resultants are

$$\begin{aligned}\Sigma \bar{F} \cdot \bar{i}' &= A_{x'} + B_{x'} = 0, \\ \Sigma \bar{F} \cdot \bar{j}' &= A_{y'} + B_{y'} = 0, \\ \Sigma \bar{F} \cdot \bar{k}' &= A_{z'} = 0.\end{aligned}$$

The solution of these equations is

$$\begin{aligned}\dot{\Omega} &= \frac{12\Gamma}{m \left[ 6R^2 + (h^2 - 3R^2) (\sin \theta)^2 \right]}, \\ A_{x'} &= -B_{x'} = \frac{m\Omega^2}{24L} (h^2 - 3R^2) \sin 2\theta, \\ A_{y'} &= -B_{y'} = -\frac{m\dot{\Omega}}{24L} (h^2 - 3R^2) \sin 2\theta, \\ A_{z'} &= 0.\end{aligned}$$

The torque is constant, so it follows that  $\dot{\Omega}$  is constant. Because  $\Omega = 0$  initially, integrating  $\dot{\Omega}$  leads to a rotation rate that increases proportionally to elapsed time:

$$\Omega = \frac{12\Gamma t}{m \left[ 6R^2 + (h^2 - 3R^2) (\sin \theta)^2 \right]}.$$

Substitution of these results into the expressions for the bearing forces shows that  $A_{x'}$  and  $B_{x'}$  increase as  $t^2$ , whereas  $A_{y'}$  and  $B_{y'}$  are independent of the elapsed time.

Each of these results may be readily explained by following the manner in which the angular momentum  $\bar{H}_G$  changes. Such an examination would show that the rotation moves the head of  $\bar{H}_G$  in the  $-y'$  direction, which requires a couple about the negative  $y'$  axis. Such a moment is generated by the bearing forces  $A_{x'}$  and  $B_{x'}$ , which depend solely on the current rotation rate. The bearing forces rotate at  $\Omega$ , which means that the forces the shaft exerts in the bearing are experienced by the foundation as rotating forces. Such forces cause vibration in the foundation because their components relative to a fixed reference frame oscillate in magnitude. This is a condition of *dynamic imbalance*. The other transverse bearing forces,  $A_{y'}$  and  $B_{y'}$ , are proportional to  $\dot{\Omega}$ . They are associated with the changing magnitude of  $\bar{H}_G$  and remain constant as long as  $\dot{\Omega}$  does not change. They too rotate at  $\Omega$  relative to a fixed reference frame, and therefore also produce oscillations in the foundation, although their value usually is small compared with that of the dynamic imbalance forces.

The nature of the forces would be more apparent if we had formulated the equations of motion by using  $x'y'z'$  as the body-fixed reference frame. This would have required the rotation transformation to evaluate  $[I']$ . We may generalize such an analysis. Consider an arbitrary body that executes a pure rotation at angular speed  $\Omega$  about a shaft as the result of a torque  $\Gamma$ . The center of mass is situated at an arbitrary distance from this rotation axis. Let  $x'y'z'$  be a body-fixed coordinate system whose  $z'$  axis coincides with the shaft, and let  $[I']$  be the corresponding inertia matrix. In this case the angular motion is  $\bar{\omega} = \Omega \bar{k}'$ ,  $\bar{\alpha} = \dot{\Omega} \bar{k}'$ . Because  $x'y'z'$  is not necessarily principal, we use Eqs. (6.1.3) to form  $\bar{H}_G$  and its relative derivative, which gives

$$\begin{aligned}\bar{H}_G &= -I_{x'z'}\Omega\bar{i}' - I_{y'z'}\Omega\bar{j}' + I_{z'z'}\Omega\bar{k}', \\ \partial\bar{H}_G/\partial t &= -I_{x'z'}\dot{\Omega}\bar{i}' - I_{y'z'}\dot{\Omega}\bar{j}' + I_{z'z'}\dot{\Omega}\bar{k}'.\end{aligned}$$

We refer to the free-body diagram to sum forces and moments relative to  $x'y'z'$ . The equations of motion, Eqs. (6.1.1), then require that

$$\begin{aligned}(A_{x'} + B_{x'})\bar{i}' + (A_{y'} + B_{y'})\bar{j}' + A_{z'}\bar{k}' &= m\bar{a}_G, \\ (-A_{y'} + B_{y'})\frac{L}{2}\bar{i}' + (A_{x'} - B_{x'})\frac{L}{2}\bar{j}' + \Gamma\bar{k}' \\ &= (-I_{x'z'}\dot{\Omega} + I_{y'z'}\Omega^2)\bar{i}' + (-I_{y'z'}\dot{\Omega} - I_{x'z'}\Omega^2)\bar{j}' + I_{z'z'}\dot{\Omega}\bar{k}'.\end{aligned}$$

A dynamically balanced system is one in which any rotation can occur without generating dynamic reactions at either bearing,  $A_{x'} = A_{y'} = A_{z'} = B_{x'} = B_{y'} = 0$ . The preceding equations of motion indicate that such a condition requires that  $\bar{a}_G = 0$  and  $I_{x'z'} = I_{y'z'} = 0$ . In other words, dynamic balancing requires that the center of mass be situated on the rotation axis and that the rotation axis be a principal axis of inertia. In contrast, the condition of *static balance* merely requires the former.


This general observation is manifested by the specific results for the skewly mounted cylinder of the present system. When  $\theta = 0$  the  $z$  axis coincides with the

## 6.1 Fundamental Equations

305

rotation axis, whereas  $\theta = 90^\circ$  corresponds to alignment of  $x$  and the rotation axis. Both  $x$  and  $z$  are principal axes, and the results confirm that the bearing forces are zero in both cases. We also see that the forces are zero for any  $\theta$  if  $h = \sqrt{3}R$ . In that case  $I_{xx} = I_{yy} = I_{zz}$ , so that the cylinder is inertially equivalent to a sphere, for which all centroidal axes are principal. In any other case, bearing forces are required to sustain the motion, even though the center of mass coincides with the shaft.

**EXAMPLE 6.2** A servomotor maintains a constant value of the spin rate  $\dot{\phi}$  at which the disk rotates relative to the pivoted shaft  $AB$ . The precession rate  $\Omega$  is held constant by a torque  $M(t)$  applied to the vertical shaft. Derive the differential equation governing the unsteady nutation angle  $\theta$ , and also derive an expression for  $M$  as a function of  $\theta$ . Then determine all possible states of steady precession, in which  $\theta$  is constant, and evaluate the stability of each state.




Example 6.2

**SOLUTION** This system is truly in spatial motion, so the analysis will bring to the fore some of the issues that one might typically encounter. In addition, it will address the characterization of connections in terms of the kinematical restrictions they impose and the constraint forces they exert. The only body having significant inertia is the disk, but the fork-and-clevis joint at point  $A$  must be considered because we know how it constrains motion. We assume that the shaft's mass is negligible, which enables us to consider it and the disk to be a single rigid body. (Without this assumption we would need to consider each body individually, and account for the forces exerted between them at bearing  $B$ .)

Point  $A$  is at a constant distance from the disk along the disk's centerline, which means that the disk is in pure rotation about this point. Consequently we choose point  $A$  as the origin of the body-fixed  $xyz$  coordinate system. We align the  $x$  axis with the centerline to employ directly the tabulated inertia properties of a disk. The axisymmetry of the disk gives us some freedom to define the body-fixed  $xyz$  system in a manner that suits the kinematical features. Thus we align the  $y$  axis at the instant of interest horizontally to facilitate describing the  $\theta$  rotation. To describe



$\bar{\omega}$  and the reactions at point  $A$  we also define  $x'y'z'$  to precess at  $\Omega$  with  $z'$  vertical and  $x'$  situated in the vertical plane formed by the  $x$  and  $z'$  axes.



Free-body diagram of the spinning disk and its shaft.

Joint  $A$  prevents movement of the shaft, so we show the corresponding force reactions as components parallel to  $x'y'z'$ . Also, this connection allows shaft  $AB$  to rotate only about the  $y'$  axis relative to the vertical shaft. Thus the free-body diagram depicts couple reactions about the  $x'$  and  $z'$  axes, but not about the  $y'$  axis. The vertical component is the torque  $M$  applied to the vertical shaft to sustain  $\Omega$ . The free-body diagram also includes the weight of the disk, whose role is not static because its moment is not constant in magnitude and direction. The angular velocity and the angular acceleration of the disk are described by

$$\begin{aligned}\bar{\omega} &= -\dot{\phi}\bar{i} + \Omega\bar{k}' - \dot{\theta}\bar{j}', & \bar{\omega}' &= \Omega\bar{k}', \\ \bar{\alpha} &= -\dot{\phi}(\bar{\omega} \times \bar{i}) - \ddot{\theta}\bar{j}' - \dot{\theta}(\bar{\omega}' \times \bar{j}').\end{aligned}$$

At the instant in the free-body diagram  $\bar{j}' = \bar{j}$  and  $\bar{k}' = -\cos\theta\bar{i} + \sin\theta\bar{k}$ , so the angular motion is

$$\begin{aligned}\bar{\omega} &= (-\dot{\phi} - \Omega\cos\theta)\bar{i} - \dot{\theta}\bar{j} + \Omega\sin\theta\bar{k}, & \bar{\omega}' &= -\Omega\cos\theta\bar{i} + \Omega\sin\theta\bar{k}, \\ \bar{\alpha} &= \dot{\theta}\Omega\sin\theta\bar{i} + (-\ddot{\theta} - \dot{\phi}\Omega\sin\theta)\bar{j} + (-\dot{\phi}\dot{\theta} + \dot{\theta}\Omega\cos\theta)\bar{k}.\end{aligned}\tag{1}$$

We use the Appendix and the parallel axis theorems to find the inertia properties of the disk relative to  $xyz$ , which are principal:

$$I_{xx} = \frac{1}{2}mR^2, \quad I_{yy} = I_{zz} = m\left(\frac{1}{4}R^2 + L^2\right).$$

Inspection of the free-body diagram reveals that the force equations of motion will contain the reaction forces at the pin, which are of no interest here. Thus we focus on the moment equation. Euler's equations are applicable because  $xyz$  are

## 6.1 Fundamental Equations

307

principal axes. We refer to the free-body diagram to determine the moment sums, which leads to

$$\begin{aligned}\Sigma \bar{M}_A \cdot \bar{i} &= -M \cos \theta + M_{x'} \sin \theta = I_{xx} \alpha_x - (I_{yy} - I_{zz}) \omega_y \omega_z, \\ &= \left( \frac{1}{2} m R^2 \right) \dot{\theta} \Omega \sin \theta, \\ \Sigma \bar{M}_A \cdot \bar{j} &= mg (L \sin \theta) = I_{yy} \alpha_y - (I_{zz} - I_{xx}) \omega_x \omega_z \\ &= \left( \frac{1}{4} R^2 + L^2 \right) (-\ddot{\theta} - \dot{\phi} \Omega \sin \theta), \\ &\quad -m \left( \frac{1}{4} R^2 - L^2 \right) (-\dot{\phi} - \Omega \cos \theta) (\Omega \sin \theta), \\ \Sigma \bar{M}_A \cdot \bar{k} &= M \sin \theta + M_{x'} \cos \theta = I_{zz} \alpha_z - (I_{xx} - I_{yy}) \omega_x \omega_y \\ &= m \left( \frac{1}{4} R^2 + L^2 \right) (-\dot{\phi} \dot{\theta} + \dot{\theta} \Omega \cos \theta) \\ &\quad - \left( \frac{1}{4} R^2 - L^2 \right) (-\dot{\phi} - \Omega \cos \theta) (-\dot{\theta}).\end{aligned}$$

The sole unknown in the second equation is  $\theta$ , so it yields the desired differential equation, and the first and third equations combine to give an expression for  $M$ :

$$\begin{aligned}\left( \frac{1}{4} R^2 + L^2 \right) \ddot{\theta} - \left( L^2 - \frac{1}{4} R^2 \right) \Omega^2 \sin \theta \cos \theta + \left( \frac{1}{2} R^2 \dot{\phi} \Omega + g L \right) \sin \theta &= 0, \\ M = -\frac{1}{2} m R^2 \dot{\phi} \dot{\theta} \sin \theta + 2 \left( L^2 - \frac{1}{4} R^2 \right) \dot{\theta} \Omega \sin \theta \cos \theta.\end{aligned}\tag{2}$$

It is interesting to note that couples acting about both the  $x'$  and  $z'$  axes are required for sustaining the precession and spin rates.

To find the possible steady precession states we take  $\theta$  to be constant in the differential equation, which leads to two possibilities:

$$\sin \theta = 0 \quad \text{or} \quad \left( L^2 - \frac{1}{4} R^2 \right) \Omega^2 \cos \theta = \frac{1}{2} R^2 \dot{\phi} \Omega + g L.\tag{3}$$

The diagram describing the system indicates that the construction of the fork-and-clevis joint makes  $\theta = \pi$  impossible, but we allow for it in order to get a full picture of the behavior. Thus there are three possible constant nutation angles:

$$\theta_1 = 0, \quad \theta_2 = \pi, \quad \theta_3 = \cos^{-1} \left[ \frac{2 R^2 \dot{\phi} \Omega + 4 g L}{\Omega^2 (4 L^2 - R^2)} \right].\tag{4}$$

The nutated state represented by  $\theta_3$  arises for only a range of parameters. The analysis is most easily carried out if  $\Omega$  is considered to be fixed, whereas  $\dot{\phi}$  is adjustable.

Let us consider  $L > R/2$ . Then the condition that  $|\cos(\theta_3)| \leq 1$  is satisfied when

$$\begin{aligned} \dot{\phi}_{\min} \leq \dot{\phi} \leq \dot{\phi}_{\max}, \\ \dot{\phi}_{\min} = -2 \frac{gL}{R^2 \Omega} - \Omega \frac{4L^2 - R^2}{2R^2}, \quad \dot{\phi}_{\max} = -2 \frac{gL}{R^2 \Omega} + \Omega \frac{4L^2 - R^2}{2R^2}. \end{aligned} \quad (5)$$

Note that  $L > R/2$  leads to  $\dot{\phi}_{\min}$  being negative, whereas  $\dot{\phi}_{\max}$  can be either positive or negative.

Nutation angles  $\theta_1$  and  $\theta_2$  correspond to the precession and spin rates both being about vertical axes, so the angular momentum  $\bar{H}_A$  also is vertical, and therefore constant. The gravity force acting on the disk intersects joint  $A$  in this case, so there is no moment about the  $y$  axis to be balanced by  $d\bar{H}_A/dt$ . In the third state,  $\bar{H}_A$  lies in the  $xz$  plane, which means that it precesses at  $\Omega$  about the vertical axis. The moment of gravity about the pin of joint  $A$  balances the rate at which  $\bar{H}_A$  is changed by this rotation. The value of  $\theta_3$  ranges from zero at  $\dot{\phi}_{\max}$  to  $\pi$  at  $\dot{\phi}_{\min}$ .

Although the three roots for constant  $\theta$  are mathematically possible, determining whether they will actually occur requires consideration of the stability of the steady precession. This involves investigating whether the steady motion will change drastically if it is disturbed. For our purpose we limit consideration to a small disturbance that changes one of the constant  $\theta_n$  solutions by a small amount  $\Delta$ . The smallness restriction enables us to simplify  $\sin \theta$  and  $\cos \theta$  with a Taylor series:

$$\theta = \theta_n + \Delta \implies \sin \theta \approx \sin \theta_n + \Delta \cos \theta_n, \quad \cos \theta \approx \cos \theta_n - \Delta \sin \theta_n.$$

We set  $\ddot{\theta} = \ddot{\Delta}$  in the differential equation (2) and substitute the preceding expressions, which leads to

$$\begin{aligned} \left( \frac{1}{4} R^2 + L^2 \right) \ddot{\Delta} - \left( L^2 - \frac{1}{4} R^2 \right) \Omega^2 (\sin \theta_n + \Delta \cos \theta_n) (\cos \theta_n - \Delta \sin \theta_n) \\ + \left( \frac{1}{2} R^2 \dot{\phi} \Omega + gL \right) (\sin \theta_n + \Delta \cos \theta_n) = 0. \end{aligned}$$

This equation is further simplified by the fact that  $\Delta$  is very small, so quadratic terms in  $\Delta$  may be dropped. Furthermore, the terms that do not contain  $\Delta$  correspond to the steady precession solution, so they cancel. Thus we are led to

$$\left( \frac{1}{4} R^2 + L^2 \right) \ddot{\Delta} + \left[ - \left( L^2 - \frac{1}{4} R^2 \right) \Omega^2 \cos(2\theta_n) + \left( \frac{1}{2} R^2 \dot{\phi} \Omega + gL \right) \cos \theta_n \right] \Delta = 0. \quad (6)$$

The preceding is the equation for a one-degree-of-freedom undamped linear oscillator, so the stability condition is governed by the sign of the coefficient of  $\Delta$ , which is

$$K(\theta_n, \Omega, \dot{\phi}) = - \left( L^2 - \frac{1}{4} R^2 \right) \Omega^2 \cos(2\theta_n) + \left( \frac{1}{2} R^2 \dot{\phi} \Omega + gL \right) \cos \theta_n. \quad (7)$$

## 6.1 Fundamental Equations

309

Positive  $K$  corresponds to an oscillatory  $\Delta$ , which means that  $\theta$  always remains close to the steady value, whereas negative  $K$  corresponds to an exponentially increasing  $\Delta$ , which indicates that the precession will diverge from the steady value. For  $\theta = \theta_1 = 0$ , we have

$$K(0, \Omega, \dot{\phi}) = -\left(L^2 - \frac{1}{4}R^2\right)\Omega^2 + \frac{1}{2}R^2\dot{\phi}\Omega + gL.$$

When we consider  $K(0, \Omega, \dot{\phi})$  to be a function of  $\dot{\phi}$  for fixed  $\Omega$ , we see that the condition  $K(0, \Omega, \dot{\phi}) > 0$  is satisfied when  $\dot{\phi} > \dot{\phi}_{\max}$ . The steady-state precession at  $\theta = \theta_2 = \pi$  leads to

$$K(\pi, \Omega, \dot{\phi}) = -\left(L^2 - \frac{1}{4}R^2\right)\Omega^2 - \frac{1}{2}R^2\dot{\phi}\Omega - gL.$$

Stability of this steady nutation, corresponding to  $K(\pi, \Omega, \dot{\phi}) > 0$ , occurs when  $\dot{\phi} < \dot{\phi}_{\min}$ . Analysis of the case in which  $\theta = \theta_3$  is slightly more complicated. The identity  $\cos(2\theta_3) \equiv 2(\cos\theta_3)^2 - 1$  gives

$$K(\theta_3, \Omega, \dot{\phi}) = \left(L^2 - \frac{1}{4}R^2\right)\Omega^2 \left[1 - 2(\cos\theta_3)^2\right] + \left(\frac{1}{2}R^2\dot{\phi}\Omega + gL\right)\cos\theta_3.$$

Rather than using the last of Eqs. (3) to replace  $\theta_3$  in this expression, let us use it to eliminate  $\dot{\phi}$ . The result is

$$K(\theta_3, \Omega, \dot{\phi}) = \left(L^2 - \frac{1}{4}R^2\right)\Omega^2 (\sin\theta_3)^2.$$


The value of  $K(\theta_3, \Omega, \dot{\phi})$  is positive whenever  $\theta_3$  is real, which means that this state is stable if it exists.

An overview of the results gives a clearer picture. We find that, if  $\dot{\phi} > \dot{\phi}_{\max}$ , then the vertically suspended state,  $\theta = 0$ , is the only stable steady precession. If the spin rate falls below  $\dot{\phi}_{\max}$ , but exceeds  $\dot{\phi}_{\min}$ , then the only stable steady precession is one in which the shaft is tilted at  $\theta_3$ . Further decrease of  $\dot{\phi}$  below  $\dot{\phi}_{\min}$  makes the inverted position  $\theta_2 = \pi$  the only stable steady precession. Proper interpretation of this result requires that one recall that  $\dot{\phi}_{\min}$  is negative, so the condition that  $\dot{\phi} < \dot{\phi}_{\min}$  corresponds to a large spin rate in the sense of the positive  $x$  axis.  $\triangleleft$

The system in this example is referred to as a *spinning top*, because it effectively is identical to the toy that spins with its apex in contact with the ground. This system has been widely studied as a way of explaining many of the physical principles of spatial kinetics. Further exploration of the behavior of a spinning top may be found in Chapter 10.


**EXAMPLE 6.3** The vertical force  $F$  causes the vertical bar to translate upward at a speed  $v$  that is a specified function of time, and the whole system precesses about the vertical axis at the constant speed  $\Omega$  as a result of the action of the torque  $M$ . Derive the equation of motion for the nutation angle  $\theta$ , as well as an expression for

the value of  $F$  required to attain this motion. It may be assumed that the mass of the vertical shaft is negligible.



Example 6.3

**SOLUTION** This exercise, which requires the simultaneous application of the linear and angular equations of motion, highlights the need to pick the moment reference point appropriately. We begin with a free-body diagram. Because the vertical shaft is massless, it effectively is in static equilibrium. The bearing can resist neither the vertical force  $F$  nor the torque  $M$ , so these are transmitted to the bar, as shown in the diagram. The couple  $M_1$  acts horizontally perpendicular to the pin, and  $F_1$  and  $F_2$  are horizontal forces that the pin can exert on the bar.



Free-body diagram of the swinging bar.

It is tempting to the novice to place the origin of the body-fixed  $xyz$  coordinate system at pin  $A$ , because doing so eliminates the pin forces from the moment equation. However, this point is not allowable for using the moment equation of motion in Eqs. (6.1.1) because it is accelerating upward at  $\dot{v}$ . We therefore must place the origin at the center of mass  $G$ . The orientation of  $xyz$  shown in the free-body diagram allows us to find the inertia properties of the bar directly from the Appendix, with  $I_{xx} = 0$ ,  $I_{yy} = I_{zz} = (1/12)mL^2$  based on considering the bar to be slender.

The angular velocity is the sum of the precession and the rotation  $\theta$ , which actually is a nutation. The precession direction  $\bar{e}_1$  is constant, whereas the nutation direction  $\bar{e}_2$  precesses at  $\Omega$ , so that

$$\bar{\omega} = \Omega \bar{e}_1 + \dot{\theta} \bar{e}_2, \quad \bar{\alpha} = \ddot{\theta} \bar{e}_2 + \dot{\theta} (\Omega \bar{e}_1 \times \bar{e}_2).$$

The rotation directions are

$$\bar{e}_1 = -\cos \theta \bar{i} + \sin \theta \bar{k}, \quad \bar{e}_2 = -\bar{j},$$

which leads to

$$\bar{\omega} = -\Omega \cos \theta \bar{i} - \dot{\theta} \bar{j} + \Omega \sin \theta \bar{k}, \quad \bar{\alpha} = \Omega \dot{\theta} \sin \theta \bar{i} - \ddot{\theta} \bar{j} + \Omega \dot{\theta} \cos \theta \bar{k}.$$

## 6.1 Fundamental Equations

311

Because we cannot eliminate the pin forces from the moment equation, we need the additional relations provided by the force equation of motion, which requires that we describe the acceleration of the center of mass. Pin  $A$  is in rectilinear motion, so we have

$$\begin{aligned}\bar{a}_G &= \dot{v}\bar{e}_1 + \bar{\alpha} \times \bar{r}_{G/A} + \bar{\omega} \times (\bar{\omega} \times \bar{r}_{G/A}) \\ &= -\left[\dot{v} \cos \theta + \frac{L}{2}\Omega^2 (\sin \theta)^2 + \frac{L}{2}\dot{\theta}^2\right]\bar{i} + L\Omega\dot{\theta} \cos \theta \bar{j} \\ &\quad + \left[\dot{v} \sin \theta + \frac{L}{2}\ddot{\theta} - \Omega^2 \frac{L}{2} \sin \theta \cos \theta\right]\bar{k}.\end{aligned}$$

The Euler equations of motion are applicable because  $xyz$  are principal axes. This is an aid because the  $y$  axis is the only axis about which neither  $M$  nor  $M_1$  exerts a moments. Consequently, only the Euler equation for moment about the  $y$  axis is relevant. We add the moment of each pin force about the respective axes, and substitute that sum, along with the inertia properties and components of  $\bar{\omega}$  and  $\bar{\alpha}$ , into Eqs. (6.1.6). Because we have approximated  $I_{xx}$  as being zero, we have

$$\begin{aligned}\Sigma \bar{M} \cdot \bar{j} &= F \frac{L}{2} \sin \theta + F_1 \frac{L}{2} \cos \theta \\ &= I_{yy}\alpha_y - I_{zz}\omega_x\omega_z = \frac{1}{12}mL^2(-\ddot{\theta} + \Omega^2 \sin \theta \cos \theta).\end{aligned}$$

We are not interested in the value of  $F_2$ , which means that we can omit the force equation of motion in the  $\bar{j}$  direction. The useful force equations are

$$\begin{aligned}\Sigma \bar{F} \cdot \bar{i} &= -F \cos \theta + F_1 \sin \theta + mg \cos \theta = -m\left[\dot{v} \cos \theta + \frac{L}{2}\Omega^2 (\sin \theta)^2 + \frac{L}{2}\dot{\theta}^2\right], \\ \Sigma \bar{F} \cdot \bar{k} &= F \sin \theta + F_1 \cos \theta - mg \sin \theta = m\left[\dot{v} \sin \theta + \frac{L}{2}\ddot{\theta} - \Omega^2 \frac{L}{2} \sin \theta \cos \theta\right].\end{aligned}$$

These equations give the force values corresponding to a specified motion:

$$\begin{aligned}F &= m\left[\dot{v} + g + \frac{L}{2}\ddot{\theta} \sin \theta + \frac{L}{2}\dot{\theta}^2 \cos \theta\right], \\ F_1 &= m\left[\frac{L}{2}\ddot{\theta} \cos \theta - \frac{L}{2}\dot{\theta}^2 \sin \theta - \Omega^2 \frac{L}{2} \sin \theta\right].\end{aligned}\quad \triangleleft$$

Substitution of these expressions into the moment equation gives a differential equation governing the rotation:


$$\frac{1}{3}\ddot{\theta} - \frac{2}{3}\Omega^2 \sin \theta \cos \theta + \frac{\dot{v} + g}{L} \sin \theta = 0. \quad \triangleleft$$

This equation resembles the one for a pendulum, with the effective gravitational acceleration being  $g + \dot{v}$ . The term containing  $\Omega^2$  represents the influence of the centripetal acceleration associated with precession. Similarly, the result for  $F$  shows that it must overcome the effective gravitational acceleration and the vertical

components of the transverse and centripetal accelerations of the center of mass that are due to the unsteady value of  $\theta$ .

It is evident that solving this problem would have been much easier if we were able to form the moment relative to the pin. In Section 6.3 we will see how to do so.


**EXAMPLE 6.4** A thin homogeneous disk of mass  $m$  rolls without slipping on a horizontal plane such that its center has a constant speed  $v$  as it follows a circular path of radius  $\rho$ . The angle of elevation of the disk's axis is a constant value  $\theta$ . Derive an expression relating  $v$  to the value of  $\theta$ .



Example 6.4

**SOLUTION** The problem of a rolling disk has classical interest. Here we explore the special case of steady precession as an illustration of the full set of Newton–Euler equations of motion. The kinematics of this type of motion was discussed in Section 4.4. That development is an important aspect of the present analysis.

In addition to the gravitational force, there are reactions at the contact between the disk and the ground. They are depicted in the free-body diagram as the normal force  $N$  and two frictional force components lying in the horizontal plane:  $F_n$  toward the vertical axis about which the disk rotates and  $F_t$  opposite the velocity of point  $G$ . The former represents the force required to make the center of mass follow a circular path, whereas the latter force anticipates that friction opposes the sliding tendency of the contact point. The normal force  $N$  prevents the contact point from penetrating the ground.



Free-body diagram of the rolling disk.

## 6.1 Fundamental Equations

313

We place the origin of the body-fixed coordinate system  $xyz$  at the center  $G$ , which is valid regardless of how the disk moves. (The intersection of the center-line of the disk with the vertical axis for the precession also is an allowable point for the moment equation, because it is a stationary point whose position relative to the disk is fixed. However, there is no advantage to using this point.) We exploit the axisymmetry of the disk by defining the body-fixed  $x$  and  $y$  axes to lie in the plane of the disk, with the  $y$  axis at the instant of interest aligned horizontal, in the sense of the velocity of point  $G$ . The precession  $\dot{\psi}$  is the only rotation of the  $x'y'z'$  coordinate system depicted in the free-body diagram. This coordinate system expedites description of  $\bar{\omega}$ , as well as the acceleration of the center of mass.

The rotation of the disk consists of a precession  $\dot{\psi}$  about the vertical axis and a spin  $\dot{\phi}$  about the  $z$  axis. The angular velocity of the disk is a superposition of the rotations about the two axes,

$$\bar{\omega} = \dot{\psi} \bar{i}' + \dot{\phi} \bar{k}, \quad \bar{\omega}' = \dot{\psi} \bar{i}'.$$

All rotation rates are constant in steady precession, so the corresponding angular acceleration is

$$\bar{\alpha} = \dot{\psi} (\bar{\omega}' \times \bar{i}') + \dot{\phi} (\bar{\omega} \times \bar{k}) = \dot{\psi} \dot{\phi} (\bar{i}' \times \bar{k}).$$

At the instant depicted in the free-body diagram,

$$\bar{i}' = \cos \theta \bar{i} - \sin \theta \bar{k},$$

which leads to instantaneous expressions for the angular motion of the disk,

$$\bar{\omega} = \dot{\psi} \cos \theta \bar{i} + (\dot{\phi} - \dot{\psi} \sin \theta) \bar{k}, \quad \bar{\alpha} = -\dot{\psi} \dot{\phi} \cos \theta \bar{j}.$$

The velocity of the center is  $v \bar{j}$ , and the rotation rates are related to the speed  $v$  by the no-slip condition at the contact point  $C$ , which requires that  $\bar{v}_C = 0$ . Points  $C$  and  $G$  belong to the disk, so we have

$$\bar{v}_G = v \bar{j} = \rho \dot{\psi} \bar{j} = \bar{\omega} \times \bar{r}_{G/C} = R(\dot{\phi} - \dot{\psi} \sin \theta) \bar{j},$$

from which we find that

$$\dot{\psi} = \frac{v}{\rho}, \quad \dot{\phi} = \frac{v}{R} + \frac{v}{\rho} \sin \theta.$$

Correspondingly, the angular motion expressions become

$$\bar{\omega} = \frac{v}{\rho} \cos \theta \bar{i} + \frac{v}{R} \bar{k}, \quad \bar{\alpha} = -\frac{v^2}{\rho} \left( \frac{1}{R} + \frac{1}{\rho} \sin \theta \right) \cos \theta \bar{j}.$$

The  $xyz$  axes are principal, with

$$I_{xx} = I_{yy} = \frac{1}{4} m R^2, \quad I_{zz} = \frac{1}{2} m R^2.$$



For the sake of variety, we shall formulate  $d\bar{H}_A/dt$  from the basic relations, rather than invoke Euler's equations. Combining the inertia properties with the angular rotation variables leads to

$$\begin{aligned}\bar{H}_G &= mR^2 \left( \frac{1}{4} \frac{v}{\rho} \cos \theta \bar{i} + \frac{1}{2} \frac{v}{R} \bar{k} \right), \\ \frac{\partial \bar{H}_G}{\partial t} &= -\frac{1}{4} mR^2 \frac{v^2}{\rho} \left( \frac{1}{R} + \frac{1}{\rho} \sin \theta \right) \cos \theta \bar{j}.\end{aligned}$$

The reaction forces applied by the ground are unknown, so there the moment equations of motion will not be sufficient to determine all the unknown quantities. We also need the force equation of motion. We know that point  $G$  follows a circular path at constant speed  $v$ , and the  $z'$  axis points toward the center of curvature. Thus the acceleration of the center of mass is

$$\bar{a}_G = \frac{v^2}{\rho} \bar{k}'.$$

The corresponding Eqs. (6.1.1) are

$$\begin{aligned}\Sigma \bar{F} &= m \frac{v^2}{\rho} \bar{k}', \\ \Sigma \bar{M}_G &= -\frac{1}{4} m v^2 \frac{R}{\rho} \left( 2 + \frac{R}{\rho} \sin \theta \right) \cos \theta \bar{j}.\end{aligned}$$

We form the components of the force sums relative to the  $x'y'z'$  axes, and the moments of the forces at the ground about the axes of  $xyz$ . Equating each to the corresponding inertial term yields

$$\begin{aligned}\Sigma \bar{F} \cdot \bar{i}' &= N - mg = 0, \quad \Sigma \bar{F} \cdot \bar{j}' = F_t = 0, \quad \Sigma \bar{F} \cdot \bar{k}' = F_n = m \frac{v^2}{\rho}, \\ \Sigma \bar{M}_G \cdot \bar{i} &\equiv 0, \\ \Sigma \bar{M}_G \cdot \bar{j} &= F_n (R \cos \theta) - N (R \sin \theta) = -\frac{1}{4} m v^2 \frac{R}{\rho} \left( 2 + \frac{R}{\rho} \sin \theta \right) \cos \theta, \\ \Sigma \bar{M}_G \cdot \bar{k} &= F_t R = 0.\end{aligned}$$

We solve the force equations for  $N$  and  $F_n$ , and substitute those expressions into  $\Sigma \bar{M}_G \cdot \bar{j}$ . The result is

$$m \frac{v^2}{\rho} (R \cos \theta) - mg (R \sin \theta) = -\frac{1}{4} m v^2 \frac{R}{\rho} \left( 2 + \frac{R}{\rho} \sin \theta \right) \cos \theta,$$

which reduces to

$$v^2 = \frac{4g\rho^2 \tan \theta}{6\rho + R \sin \theta}. \quad \triangleleft$$

There is a simple explanation for this steady motion. The gravitational force and normal reaction form a couple about the horizontal diameter of the disk because the


## 6.1 Fundamental Equations

315

disk is tilted. The frictional reaction required to impart the centripetal acceleration to the center of mass also exerts a moment about this line. The net moment must be matched by a change in the angular momentum. This effect is achieved by the precession, which alters the true direction of the angular momentum, even though its components relative to the  $xyz$  axes are constant.

It will be noted that  $f_i$  was found to be zero. This is comparable to planar rolling of a disk on level ground. The moment equation of motion in that case indicates that the friction force is zero unless another force exerts a moment about the center of mass, which leads to the anomaly that a disk rolling freely should never slow. This is the fault of the rigid-body model for contacting surfaces. The rolling friction model [see, for example, Ginsberg and Genin (1984)] addresses this anomaly. It would lead to the correct conclusion that a steady precessional motion of the rolling disk is not possible.

**EXAMPLE 6.5** An experiment in aerodynamics features a square plate that is free to spin at rate  $\dot{\phi}$  about axis  $AB$  of the bent shaft, while the precession rate  $\dot{\psi}$  about the horizontal shaft is held constant by application of a torque  $\Gamma$  about the shaft. The angles are defined such that  $\psi = \phi = 0$  when the plate coincides with the vertical plane. This system is situated in a wind tunnel whose flow is horizontal. The resultant of the aerodynamic pressure is a known force  $F(t)$  acting at the center of pressure  $P$  and always normal to the plane of the plate. Derive the differential equation of motion for  $\phi$ . Include the effect of gravity in the derivation.




Example 6.5

**SOLUTION** This example addresses situations in which a nonaxisymmetric body executes a spatial rotation. Aligning the body-fixed coordinate system to match the tabulated inertia properties fully specifies each axis, so we are not free to align the axes to simplify the kinematical analysis. Rather, we need to use rotation transformations.

To construct the free-body diagram we recognize that the bent shaft applies a distributed force to the plate along edge  $AB$ . The resultant of this is arbitrary, except that it cannot exert a torque about that edge because the plate rotates freely. Thus we represent the reaction exerted by the shaft on the plate as a force-couple system at corner  $A$ , in which the couple has no component parallel to edge  $AB$ . In

addition to the aerodynamic force, the free-body diagram shows the gravity force acting vertically downward.



Free-body diagram of the plate showing the supporting forces as a force-couple system at point A.

In the free-body diagram the origin of body-fixed  $xyz$  coordinate system is placed at bearing A. This point has a fixed position relative to the plate, and it is stationary, which means that the plate executes a pure rotation about point A. The axes of  $xyz$  are aligned with the edges of the plate in order to use the tabulated inertia properties. The  $x'y'z'$  coordinate systems depicted in the free-body diagram is introduced to aid in the description of the gravity force and the angular motion. The sole rotation it undergoes is the precession about the horizontal  $x'$  axis. We define  $\psi = 0$  to correspond to the  $z'$  axis being vertical.

The transformation from  $x'y'z'$  to  $xyz$  may be pictured as a pair of body-fixed rotations:  $\theta$  about the  $y'$  axis, followed by  $-\phi$  about the  $x$  axis. The associated simple rotation transformations are

$$[R_\theta] = \begin{bmatrix} \cos \theta & 0 & -\sin \theta \\ 0 & 1 & 0 \\ \sin \theta & 0 & \cos \theta \end{bmatrix},$$

$$[R_\phi] = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \phi & -\sin \phi \\ 0 & \sin \phi & \cos \phi \end{bmatrix},$$

so the transformation of the unit vectors is

$$[\bar{i} \quad \bar{j} \quad \bar{k}]^T = [R][\bar{i}' \quad \bar{j}' \quad \bar{k}']^T,$$

$$[R] = [R_\phi][R_\theta] = \begin{bmatrix} \cos \theta & 0 & -\sin \theta \\ -\sin \phi \sin \theta & \cos \phi & -\sin \phi \cos \theta \\ \cos \phi \sin \theta & \sin \phi & \cos \phi \cos \theta \end{bmatrix}.$$

## 6.1 Fundamental Equations

317

We may now form the angular velocity and angular acceleration. Adding the precessional motion about the horizontal  $x'$  axis and the spin about the  $x$  axis leads to

$$\bar{\omega} = -\dot{\psi}\bar{i}' - \dot{\phi}\bar{i}.$$

The precession rate is specified to be constant and it is about a fixed axis, so the angular acceleration of the plate is

$$\bar{\alpha} = -\ddot{\phi}\bar{i} - \dot{\phi}(\bar{\omega} \times \bar{i}).$$

We need the components of  $\bar{\omega}$  and  $\bar{\alpha}$  relative to  $xyz$ , and we need to express  $\bar{i}$  in terms of its  $xyz$  components. The transformation from  $x'y'z'$  to  $xyz$  is described by  $[R]$ , so we extract the components of  $\bar{i}'$  from the first row of  $[R]^T$ , with the result that

$$\bar{i}' = \cos\theta\bar{i} - \sin\phi\sin\theta\bar{j} + \cos\phi\sin\theta\bar{k},$$

which leads to

$$\bar{\omega} = (-\dot{\psi}\cos\theta - \dot{\phi})\bar{i} + \dot{\psi}\sin\phi\sin\theta\bar{j} - \dot{\psi}\cos\phi\sin\theta\bar{k},$$

$$\bar{\omega}' = -\dot{\psi}\cos\theta\bar{i} + \dot{\psi}\sin\phi\sin\theta\bar{j} - \dot{\psi}\cos\phi\sin\theta\bar{k},$$

$$\bar{\alpha} = -\ddot{\phi}\bar{i} + \dot{\phi}\dot{\psi}\cos\phi\sin\theta\bar{j} + \dot{\phi}\dot{\psi}\sin\phi\sin\theta\bar{k}.$$

We find the inertia properties for the square plate by setting to zero the dimension along the  $y$  edge of the rectangular parallelepiped in the Appendix, and then invoking the parallel axis transformation. The result is

$$I_{xx} = \frac{1}{3}m\ell^2, \quad I_{yy} = m\left(\frac{2}{3}\ell^2 + \ell b + b^2\right), \quad I_{zz} = m\left(\frac{1}{3}\ell^2 + \ell b + b^2\right),$$

$$I_{xy} = I_{yz} = 0, \quad I_{xz} = m\left(\frac{1}{4}\ell^2 + \frac{1}{2}\ell b\right).$$

We combine these properties and the components of  $\bar{\omega}$  and  $\bar{\alpha}$  to form  $d\bar{H}_A/dt$ . For this we must use the full equations (6.1.3) because some products of inertia are nonzero. Thus the angular momentum is

$$\begin{aligned} \bar{H}_A &= (I_{xx}\omega_x - I_{xz}\omega_z)\bar{i} + I_{yy}\omega_y\bar{j} + (I_{zz}\omega_z - I_{zx}\omega_x)\bar{k} \\ &= [I_{xx}(-\dot{\psi}\cos\theta - \dot{\phi}) - I_{xz}(-\dot{\psi}\cos\phi\sin\theta)]\bar{i} + I_{yy}\dot{\psi}\sin\phi\sin\theta\bar{j} \\ &\quad + [I_{zz}(-\dot{\psi}\cos\phi\sin\theta) - I_{xz}(-\dot{\psi}\cos\theta - \dot{\phi})]\bar{k}, \end{aligned}$$

$$\begin{aligned} \frac{\partial \bar{H}_A}{\partial t} &= (I_{xx}\alpha_x - I_{xz}\alpha_z)\bar{i} + I_{yy}\alpha_y\bar{j} + (I_{zz}\alpha_z - I_{zx}\alpha_x)\bar{k} \\ &= [I_{xx}(-\ddot{\phi}) - I_{xz}(\dot{\phi}\dot{\psi}\sin\phi\sin\theta)]\bar{i} + I_{yy}\dot{\phi}\dot{\psi}\cos\phi\sin\theta\bar{j} \\ &\quad + [I_{zz}(\dot{\phi}\dot{\psi}\sin\phi\sin\theta) - I_{xz}(-\ddot{\phi})]\bar{k}. \end{aligned}$$

The algebraic operations required to form  $d\bar{H}_A/dt$  according to the second of Eqs. (6.1.1) are somewhat tedious, but symbolic mathematical software lessens the difficulty. The result is

$$\begin{aligned}\dot{\bar{H}}_A = & \left\{ -I_{xx}\ddot{\phi} + \left[ (I_{yy} - I_{zz}) \sin \phi \cos \phi (\sin \phi)^2 + I_{xz} \sin \phi \sin \theta \cos \theta \right] \dot{\psi}^2 \right\} \bar{i} \\ & + \left\{ \left[ (I_{xx} - I_{yy}) \cos \phi \sin \theta \cos \theta + I_{xz} \left( (\cos \theta)^2 - (\cos \phi)^2 (\sin \theta)^2 \right) \right] \dot{\psi}^2 \right. \\ & + \left. \left[ (I_{xx} + I_{yy} - I_{zz}) \cos \phi \sin \theta + 2I_{xz} \cos \theta \right] \psi \dot{\phi} - I_{xz} \dot{\phi}^2 \right\} \bar{j} \\ & + \left\{ I_{xz}\ddot{\phi} + \left[ (I_{xx} - I_{yy}) \sin \phi \sin \theta \cos \theta - I_{xz} \sin \phi \cos \phi (\sin \theta)^2 \right] \dot{\psi}^2 \right. \\ & + \left. \left[ (I_{xx} - I_{yy} + I_{zz}) \sin \phi \sin \theta \right] \psi \dot{\phi} \right\} \bar{k}.\end{aligned}$$

We now are ready to form the equations of motion. We seek an equation of motion for  $\phi$  that does not contain unknown reactions. The force equations of motion will contain  $A_x$ ,  $A_y$ , and  $A_z$ , so we will gain nothing by actually forming those equations. We also can see that the unknown couple reactions  $M_y$  and  $M_z$  would appear in the equations governing the moment sums about the  $y$  and  $z$  axes. In contrast, none of the reactions exert a moment about the  $x$  axis, so we focus solely on that term. Two forces exert a moment about that axis: the aerodynamic force  $F$ , whose lever arm about the  $x$  axis is  $d$ , and gravity, which acts in the (fixed) vertical direction. Rather than trying to visualize the moment of gravity about the  $x$  axis, we proceed formally by using a cross product. The angle between the vertical and the  $z'$  axis is  $\psi$ , so

$$m\bar{g} = mg \left( \sin \psi \bar{j}' - \cos \psi \bar{k}' \right).$$

The position of the center of mass is readily described in terms of components relative to  $xyz$ :

$$\bar{r}_{G/A} = \left( \frac{\ell}{2} + b \right) \bar{i} - \frac{\ell}{2} \bar{k}.$$

To evaluate the cross product of these vectors, both need to be described in terms of components relative to the same coordinate system. We select  $xyz$  for this purpose, because those are the axes for the moment sums. The transformation from  $x'y'z'$  to  $xyz$  is described by  $[R]$ , so we have

$$\{mg\} = mg [R] \begin{Bmatrix} 0 \\ -\sin \psi \\ \cos \psi \end{Bmatrix} = mg \begin{Bmatrix} \sin \theta \cos \psi \\ \cos \phi \sin \psi + \sin \phi \cos \theta \cos \psi \\ \sin \phi \sin \psi - \cos \phi \cos \theta \cos \psi \end{Bmatrix}.$$

## 6.2 Planar Motion

319

The gravitational moment is  $\bar{r}_{G/A} \times m\bar{g}$ . We require only the  $x$  component of this moment. We add that result to the moment of  $\bar{F}$  about the  $x$  axis and equate that result to the  $x$  component of  $d\bar{H}_A/dt$  obtained previously. This gives

$$\begin{aligned}\Sigma \bar{M}_A \cdot \bar{i} &= -Fd + mg\frac{\ell}{2}(\cos\phi \sin\psi + \sin\phi \cos\theta \cos\psi) = \dot{\bar{H}}_A \cdot \bar{i} \\ &= -I_{xx}\ddot{\phi} + \left[(I_{yy} - I_{zz})\sin\phi \cos\phi(\sin\theta)^2 + I_{xz}\sin\phi \sin\theta \cos\theta\right]\dot{\psi}^2.\end{aligned}$$

Substituting the values of the inertia properties yields

$$\begin{aligned}\frac{1}{3}\ddot{\phi} - \left[\frac{1}{3}\cos\phi \sin\theta + \left(\frac{1}{4} + \frac{1}{2}\frac{b}{\ell}\right)\cos\theta\right](\sin\phi \sin\theta)\dot{\psi}^2 \\ + \frac{g}{2\ell}(\cos\phi \sin\psi + \sin\phi \cos\theta \cos\psi) = \frac{Fd}{m\ell}.\end{aligned}\quad \triangleleft$$

It was stated that  $\dot{\psi}$  is constant, so we may set  $\psi = \dot{\psi}t$ . The value of  $\theta$  presumably is known, so the preceding is the differential equation of motion governing  $\phi$ . It is nonlinear, and its coefficients depend on time as a consequence of the known variation of  $\psi$ . The solution of this differential equation satisfying specified initial conditions could be obtained numerically if all parameter values were provided. The case in which the shaft is straight,  $\theta = 0$ , provides a check for this expression. The equation of motion then reduces to  $\ddot{\phi}/3 + (g/2\ell)\sin\phi = Fd/m\ell$ . This is the equation of a pendulum subjected to an external moment, which is what the system reduces to when  $\theta = 0$ , because precession of the shaft becomes irrelevant.

## 6.2 PLANAR MOTION

In planar motion there is a single axis of rotation, whose direction is the normal to the plane. To the extent that it is a special case of arbitrary spatial motion, there is no reason to consider planar motion separately. However, many systems are limited to planar motion, and the simple nature of this type of motion affords a good opportunity to delve into some interesting effects, such as friction.

To derive the equations of planar motion from the general set, we define  $xyz$  to be a body-fixed coordinate system whose origin is an allowable point for summing moments, with the further specification that the  $z$  axis be perpendicular to the plane of motion. To describe the motion of the center of mass we define a convenient coordinate system  $x'y'z'$  whose  $z'$  axis also is perpendicular to the plane of motion. The angular motion and the acceleration of the center of mass correspondingly are

$$\bar{\omega} = \omega\bar{k}, \quad \bar{\alpha} = \dot{\omega}\bar{k}, \quad \bar{a}_G = a_{Gx'}\bar{i}' + a'_{Gy'}\bar{j}'. \quad (6.2.1)$$

For a body having arbitrary inertia properties the angular momentum is

$$\bar{H}_G = -I_{xz}\omega\bar{i} - I_{yz}\omega\bar{j} + I_{zz}\omega\bar{k}. \quad (6.2.2)$$

The corresponding equations of motion are

$$\begin{aligned}\Sigma \bar{\mathbf{F}} \cdot \bar{\mathbf{i}}' &= ma_{Gx'}, & \Sigma \bar{\mathbf{F}} \cdot \bar{\mathbf{j}}' &= ma_{Gy'}, & \Sigma \bar{\mathbf{F}} \cdot \bar{\mathbf{k}}' &= 0, \\ \Sigma \bar{\mathbf{M}}_A \cdot \bar{\mathbf{i}} &= -I_{xz}\dot{\omega} + I_{yz}\omega^2, & \Sigma \bar{\mathbf{M}}_A \cdot \bar{\mathbf{j}} &= -I_{yz}\dot{\omega} + I_{xz}\omega^2, \\ \Sigma \bar{\mathbf{M}}_A \cdot \bar{\mathbf{k}} &= I_{zz}\dot{\omega}.\end{aligned}\tag{6.2.3}$$

The three force equations and the equation governing the moment about the  $z$  axis are the same as those developed in elementary dynamics courses. If the  $z$  axis is not principal, that is, if  $I_{xz} \neq 0$  or  $I_{yz} \neq 0$ , then the remaining moment equations describe the resultant moments about axes lying in the plane required to constrain the body from rotating about those axes. We could have anticipated the need for these moment resultants by considering Eq. (6.2.2), which shows that the angular momentum is not parallel to  $\bar{\omega}$ , and therefore not constant, if the  $z$  axis is not principal. The portion of the moments about the  $x$  and  $y$  axes that are proportional to  $\omega^2$  are gyroscopic moments that are the consequence of unsymmetrical distributions of mass relative to the  $xy$  plane.

For situations concerning dynamic imbalance of rotating machinery, such as the system treated in Example 6.1, consideration of these restraining moments is vital to the analysis. However, the force equations and the moment equation about the  $z$  axis are independent of the values of  $I_{xz}$  and  $I_{yz}$ . Thus the same motion in the  $xy$  plane will occur regardless of how the body's mass is distributed in the  $z$  direction. For this reason most planar motion analyses implicitly assume that the distribution is such that the body is symmetric relative to the  $xy$  plane. Then the orientations of the  $x$  and  $y$  axes are irrelevant to the moment equation. This leaves us free to let these axes be parallel to the  $x'$  and  $y'$  axes, whose orientations are selected to expedite the description of  $\bar{a}_G$  and the force components. Thus the equations of planar motion reduce to


$$\begin{aligned}\Sigma \bar{\mathbf{F}} \cdot \bar{\mathbf{i}}' &= ma_{Gx}, & \Sigma \bar{\mathbf{F}} \cdot \bar{\mathbf{j}}' &= ma_{Gy}, \\ \Sigma \bar{\mathbf{M}}_A \cdot \bar{\mathbf{k}} &= I_{zz}\dot{\omega}.\end{aligned}\tag{6.2.4}$$

It follows that a system in planar motion is governed by three scalar equations of motion for each body in the system.

**EXAMPLE 6.6** The rectangular plate, whose mass is  $m$ , serves as a fire door. In case of an emergency, the cable holding the plate is severed and the door swings down under the restraint of the rigid links that suspend the plate from the ceiling. Derive a differential equation of motion governing the angle of inclination  $\theta$  of the links. Also derive expressions for the forces exerted by the links on the plate. The mass of each link is negligible.


## 6.2 Planar Motion

321



Example 6.6

**SOLUTION** This plate undergoes a translational motion because the links remain parallel for any  $\theta$ . Thus it might seem that the system is unremarkable, but the solution will serve to emphasize the fundamental changes relative to statics concepts that are required to analyze any system in motion. In the free-body diagram of the plate, the links are considered to exert tensile forces. This is a consequence of neglecting the mass of the links, which makes them two-force members. Note that the forces on the left and right are taken to be different because the arrangement is not symmetrical when  $\theta$  is nonzero.



Free-body diagram of the translating fire door.

In general, all points in a translating rigid body have the same acceleration. Hence the acceleration of the center of mass matches that of either point where a link is attached. The latter follow circular paths centered at the respective upper pivot, so we have

$$\bar{a}_G = \bar{a}_A = \bar{a}_B = -L\dot{\theta}^2 \bar{e}_R + L\ddot{\theta} \bar{e}_\theta.$$

Because the box translates, we must sum moments about the center of mass. As shown in the free-body diagram, we align the  $x$  and  $y$  axes with the polar directions for  $\bar{a}_G$ , so that

$$\bar{a}_G = \bar{a}_A = \bar{a}_B = L\dot{\theta}^2 \bar{j} + L\ddot{\theta} \bar{i}.$$

The angular momentum in translation is identically zero, so moments of inertia need not be computed. The corresponding equations of motion are

$$\Sigma \bar{F} \cdot \bar{i} = -mg \sin \theta = mL\ddot{\theta},$$

$$\Sigma \bar{F} \cdot \bar{j} = F_A + F_B - mg \cos \theta = mL\dot{\theta}^2,$$

$$\Sigma \bar{M}_G \cdot \bar{k} = F_B \cos \theta \left( \frac{b}{2} \right) + F_B \sin \theta \left( \frac{h}{2} \right) - F_A \cos \theta \left( \frac{b}{2} \right) + F_A \sin \theta \left( \frac{h}{2} \right) = 0.$$




The solution of these equations is

$$\begin{aligned}\ddot{\theta} + \frac{g}{L} \sin \theta &= 0, \\ F_A &= \frac{1}{2} \left( 1 + \frac{h}{b} \tan \theta \right) (mg \cos \theta + mL\dot{\theta}^2), \\ F_B &= \frac{1}{2} \left( 1 - \frac{h}{b} \tan \theta \right) (mg \cos \theta + mL\dot{\theta}^2).\end{aligned}$$

Note that the differential equation for  $\theta$  is identical to that for a simple pendulum formed by attaching a particle to the end of a cable of length  $L$ .

**EXAMPLE 6.7** A cable drum, which is shown in cross section, consists of a cylinder having radius  $R_2$  that is capped at both ends by circular plates whose radius is  $R_1$ . A cable is wrapped around the cylinder and then pulled out horizontally by a force  $\bar{F}$ , as shown. The system was at rest when the force was applied. The mass of the wrapped wire and the drum is  $m$ , the mass of the unwrapped segment of cable is negligible, and the centroidal radius of gyration is  $\kappa$ . The static and kinetic coefficients of friction between the end plates and the ground are  $\mu_s$  and  $\mu_k$ , respectively. (a) Determine the acceleration of the center of the drum assuming that the end plates roll without slipping. (b) Determine the maximum magnitude of  $\bar{F}$  for which slipping will not occur. (c) Determine the angular acceleration and the acceleration of the center of the drum when the magnitude of  $\bar{F}$  exceeds the value obtained in Part (b).




Example 6.7

**SOLUTION** Along the way to the solution of this problem, which highlights the various aspects of the Coulomb friction model, we arrive at a result that demonstrates once again that intuition based on experience with static systems cannot be trusted. A free-body diagram shows  $\bar{F}$  and the weight, as well as normal forces  $2\bar{N}$  and friction forces  $2\bar{f}$  exerted between the two end plates and the ground. The relationship between  $\bar{N}$  and  $\bar{f}$  is governed by Coulomb's laws, which we will address separately. Here the friction force  $\bar{f}$  is depicted as acting to the left, based on the assumption that it opposes the action of  $\bar{F}$ , but we will be able to verify that assumption. We select the center of mass as the reference point for summing moments because the drum is in general motion. The axes of the body-fixed  $xyz$  coordinate

## 6.2 Planar Motion

323

system are defined to be horizontal and vertical, which matches the direction of the motion.



We know that the drum is in planar motion and that the center follows a horizontal path. Thus, regardless of the slipping condition, we know that

$$\bar{\alpha} = \dot{\omega} \bar{k}, \quad \bar{a}_G = \dot{v} \bar{i}. \quad (1)$$

Note that we have selected the sense of positive  $v$  and  $\omega$  to match the direction of the respective axis, but any other selection is acceptable if it is implemented consistently. In the special case where the drum rolls without slipping, the rotation will occur about the negative  $z$  axis, with

$$v = -\omega R_1 \text{ for no slippage.} \quad (2)$$

The centroidal moment of inertia corresponding to the given radius of gyration is  $I_{zz} = m\kappa^2$ . The equations of motion are

$$\begin{aligned} \Sigma \bar{F} \cdot \bar{i} &= F - 2f = m\dot{v}, \\ \Sigma \bar{F} \cdot \bar{j} &= 2N - mg = 0, \\ \Sigma \bar{M}_A \cdot \bar{k} &= FR_2 - 2fR_1 = m\kappa^2\dot{\omega}. \end{aligned} \quad (3)$$

There are four unknowns,  $f$ ,  $N$ ,  $\dot{v}$ , and  $\dot{\omega}$ , in these three equations. In general, the only available relations between force and kinematical variables in a kinetics problem are the equations of motion, so the additional equation required for solving Eqs. (3) must relate  $f$  and  $N$  or  $\dot{v}$  and  $\dot{\omega}$ . This is where the question of slippage enters. It is given that the drum starts from rest, so initially the drum rolls without slipping. This means that Eq. (2) applies. The contacting surfaces then are described by Coulomb's law for static friction, because the surfaces do not move relative to each other. Thus we know *a priori* only that the magnitude of  $\bar{f}$  is less than  $\mu_s N$  times. The actual magnitude and sense of  $\bar{f}$  are dictated by the laws of motion. In effect, the friction force is a constraint force—it prevents the relative movement of the contacting surfaces.

When Eq. (2) is substituted into Eqs. (3), the result is

$$\dot{v} = \frac{FR_1(R_1 - R_2)}{m(R_1^2 + \kappa^2)}, \quad f = \frac{1}{2} \left( \frac{R_1 R_2 + \kappa^2}{R_1^2 + \kappa^2} \right) F. \quad (4)$$

The signs of  $\dot{v}$  and  $f$  are both positive, so the sense initially assumed for both quantities is correct. This means that the drum rolls to the right and rotates clockwise. Kinematically, this implies that the cable gets wound around the drum, even though  $\bar{F}$  seems to act to pull it off the drum. The explanation of this behavior lies in the result for  $\dot{v}$ . We know that  $F(R_1 - R_2)$  is the moment of  $\bar{F}$  about the contact point, and  $m(R_1^2 + \kappa^2)$  is the moment of inertia about an axis parallel to  $z$  intersecting the contact point. Replacing  $\dot{v}$  with  $-\dot{\omega}R_1$  shows that the motion is a consequence of angular acceleration caused by  $\bar{F}$  exerting a moment about the contact point. (Recall that the contact point is an allowable point when there is no slipping, provided that the wheel is balanced.) The maximum magnitude of  $\bar{F}$  that can be sustained corresponds to impending slippage, at which  $|\bar{f}| = \mu_s N$ . From the force equation of motion in the  $y$  direction we have  $N = \frac{1}{2}mg$ , so the second of Eqs. (4) correspondingly gives


$$F_{\max} = \frac{R_1^2 + \kappa^2}{R_1 R_2 + \kappa^2} \mu_s mg. \quad \triangleleft$$

When slipping occurs because  $|\bar{F}| > F_{\max}$ , the friction force is governed by the kinetic portion of Coulomb's friction law, which states that  $|\bar{f}| = \mu_k N$  in opposition to the relative sliding motion. We know this sense from the solution of the no-slip case, which indicated that  $\bar{f}$  acts to the left. Thus we substitute  $f = \mu_k N = \mu_k mg$  into Eqs. (3). Note that, when slippage occurs, the friction force no longer acts to constrain the sliding, so there is no kinematical relation between  $\omega$  and  $v$ . The solution of Eqs. (3) now is

$$\dot{v} = \frac{F}{m} - \mu_k g, \quad \dot{\omega} = \frac{F R_2}{m \kappa^2} - \frac{\mu_k g R_1}{\kappa^2}. \quad \triangleleft$$

The positive sign for  $\dot{\omega}$  indicates that the rotation is counterclockwise. Thus the drum will accelerate to the right and the cable will unwrap when  $F$  is sufficiently large to cause slippage.

**EXAMPLE 6.8** The homogeneous box, whose mass is  $m$ , is placed horizontally on the semicylindrical surface, such that contact is below the centroid  $G$ . Assuming that the box does not slip, derive the differential equation of motion governing the angle  $\phi$  by which the box rotates away from horizontal.




Example 6.8

## 6.2 Planar Motion

325

**SOLUTION** The center of the wheel in the previous problem followed a straight path, whereas the motion of the center of the box had no obvious feature. Thus this example will give a more complete description of the analysis of bodies that roll. The free-body diagram of the bar must show the bar at an arbitrary angle of elevation  $\phi$ . The friction and normal forces act at the contact point  $C$ . In the absence of slippage, the distance along the bottom from point  $C$  to the centerline of the box must equal the arc length  $R\phi$  along the circle from the contact point to the top from the center. Note that neither the magnitude nor sense of the friction force is known, because it acts as a constraint force that prevents relative motion of the contacting surfaces. The only allowable point for summing moments is the center of mass, and it makes sense from a kinematical viewpoint to orient the  $x$  and  $y$  axes consistently with the local plane of contact with the cylindrical surface.



Free-body diagram of the box showing the contact forces that prevent slippage.

The position of the box clearly is specified by the value of  $\phi$ . (In the terminology of the analytical dynamics concepts of the following chapters,  $\phi$  is a generalized coordinate.) We must express the acceleration of point  $G$  in terms of  $\phi$  consistent with the no-slip condition. The rate of rotation is  $\dot{\phi}$ , and we know that point  $C$  has zero velocity, so the velocity of point  $G$  is given by

$$\bar{v}_G = \bar{\omega} \times \bar{r}_{G/C}, \quad \bar{\omega} = \dot{\phi} \bar{k}.$$

For the arbitrary position described by the free-body diagram, we have

$$\bar{r}_{G/C} = R\phi \bar{i} + \frac{1}{2}h \bar{j},$$

which gives

$$\bar{v}_G = -\frac{1}{2}h\dot{\phi} \bar{i} + R\phi \dot{\phi} \bar{j}. \quad (1)$$

Because this expression describes an arbitrary position, it may be differentiated. The unit vectors are not constant, so we use the partial differential technique for relative motion. This gives

$$\begin{aligned} \bar{a}_G &= \frac{\partial \bar{v}_G}{\partial t} + \bar{\omega} \times \bar{v}_G \\ &= -\frac{1}{2}h\ddot{\phi} \bar{i} + R(\dot{\phi}^2 + \phi\ddot{\phi}) \bar{j} + \dot{\phi} \bar{k} \times \left( -\frac{1}{2}h\dot{\phi} \bar{i} + R\phi \dot{\phi} \bar{j} \right) \\ &= -\left( \frac{1}{2}h\ddot{\phi} + R\phi \dot{\phi}^2 \right) \bar{i} + \left( R\dot{\phi}^2 + R\phi \ddot{\phi} - \frac{1}{2}h\dot{\phi}^2 \right) \bar{j}. \end{aligned} \quad (2)$$

The Appendix gives the centroidal moment of inertia. The corresponding equations of motion are

$$\begin{aligned}\Sigma \bar{F} \cdot \bar{i} &= f - mg \sin \phi = ma_{Gx} = -m \left( \frac{1}{2} h \ddot{\phi} + R \dot{\phi}^2 \right), \\ \Sigma \bar{F} \cdot \bar{j} &= N - mg \cos \phi = ma_{Gy} = m \left( R \dot{\phi}^2 + R \ddot{\phi} - \frac{1}{2} h \dot{\phi}^2 \right), \\ \Sigma \bar{M}_G \cdot \bar{k} &= f \left( \frac{h}{2} \right) - N(R\phi) = I_{zz} \dot{\omega} = \frac{1}{12} m (b^2 + h^2) \ddot{\phi}.\end{aligned}\quad (3)$$

There are three unknowns,  $\phi$ ,  $N$ , and  $f$ , in these three equations, so we may proceed to their solution. To obtain the desired differential equation we eliminate the reactions. The force equations give

$$f = m \left( g \sin \phi - \frac{1}{2} h \ddot{\phi} + R \dot{\phi}^2 \right), \quad N = m \left( g \cos \phi + R \dot{\phi}^2 + R \ddot{\phi} - \frac{1}{2} h \dot{\phi}^2 \right), \quad (4)$$

which, when substituted into the moment equations, yield

$$\left[ \frac{h^2}{3} + \frac{b^2}{12} + R^2 \phi^2 \right] \ddot{\phi} + R^2 \phi \dot{\phi}^2 = \frac{gh}{2} \sin \phi - g R \phi \cos \phi. \quad (5) \triangleleft$$

If the initial values of  $\phi$  and  $\dot{\phi}$  are specified, this differential equation could be solved for  $\phi$  as a function of  $t$ . We would use numerical techniques to obtain the solution, because an analytical solution would be difficult. When one performs a numerical analysis it is useful to have test solutions to verify the analysis. We may derive one such solution by considering  $\phi$  to be small, which enables us to linearize Eq. (5). We introduce the approximations  $\cos \phi \approx 1$ ,  $\sin \phi \approx \phi$ , and drop any terms that have quadratic or higher powers of  $\phi$ . The resulting equation for small rotations is

$$\left( \frac{h^2}{3} + \frac{b^2}{12} \right) \ddot{\phi} + g \left( R - \frac{h}{2} \right) \phi = 0. \quad (6)$$

When  $h < 2R$ , the response obtained from this equation is sinusoidal, corresponding to oscillations about a stable static equilibrium position. The results obtained from solving Eq. (6) should then be a good approximation of those for Eq. (5). In contrast, when  $h > 2R$ , the solution of the linearized equation of motion is exponential, corresponding to continuous movement away from an unstable static equilibrium position. The solutions of Eqs. (5) and (6) then will be consistent only in the early phase of the response, when  $\phi$  is small.

The transition from stability to instability has a simple explanation. In the case where the bar is slender,  $h < 2R$ , the center of mass rises as  $\phi$  increases. Thus  $\phi = 0$  is a position of minimum potential energy. In contrast, when  $h > 2R$ , the center of mass descends with movement away from the equilibrium position, which means that  $\phi = 0$  corresponds to maximum potential energy. Note that the stability transition is independent of the value of the length  $b$ , whose only effect is its influence on the effective moment of inertia of the bar, which is the coefficient of the angular


## 6.2 Planar Motion

327

acceleration term in the equation of motion. Thus, when the equilibrium position is stable, the value of  $b$  solely affects the frequency of the stable oscillation.

The derivation of Eq. (5) assumed that the box does not slip over the cylinder, but that might not be true. At every instant at which the differential equation has been solved, the no-slip condition should be verified. This requires that, in addition to knowing the instantaneous value of  $\phi$ , we would need to determine  $\dot{\phi}$ , either analytically or by finite differences. The corresponding  $\ddot{\phi}$  may be found from Eq. (5), which then allows us to evaluate  $f$  and  $N$  according to Eqs. (4). Coulomb's friction laws state that the maximum friction force that can be developed between surfaces that rub against each other is  $\mu_s N$ . It follows that, if the computed value of  $|f|$  is less than  $\mu_s N$ , then the solution is acceptable. Conversely, if  $|f|$  exceeds  $\mu_s N$ , slippage will occur. In addition, one should monitor the value of  $|N|$ . Negative  $N$  indicates that the surface must pull on the box, which is not possible. When the criteria for no-slip or positive contact fail to be met, the problem must be reformulated. In the case of slippage, kinematical equations (1) and (2) are no longer valid, but the friction force is known. Occurrence of a negative  $N$  would indicate that the box has left the surface, in which case it would be in free motion.


**EXAMPLE 6.9** The slender bar moves in the horizontal plane under the constraint of collars  $A$  and  $B$ . The horizontal force  $F$  acting on collar  $A$  is such that the velocity of this collar is observed to be a constant value  $v$  to the right. The mass of bar  $AB$  is  $m$ , and the collars have negligible mass. The coefficient of sliding friction between each collar and its guide bar is  $\mu$ . Derive an expression for the value of  $F$  as a function of the angle of elevation  $\theta$  and the other parameters of the system.



Example 6.9

**SOLUTION** This example highlights some of the issues entailed in applying the Newton–Euler equations of motion to analyze linkages, without introducing the complications associated with multibody systems. Properly accounting for the friction forces is another aspect to be covered. The condition that the collars follow the guide bars is enforced by the normal constraint forces  $\bar{N}_A$  and  $\bar{N}_B$ . The friction forces  $\bar{f}_A$  and  $\bar{f}_B$  oppose the movement of the collars relative to the respective guide bars, as shown in the free-body diagram. The sense in which the free-body diagram depicts the friction forces is set by the condition that these forces act in opposition to the movement of each collar. However, either normal force might

act in the opposite sense from the one that appears in the diagram, depending on which direction either end would move if there were no normal force. We will deal with this complication when we solve the equations of motion. The applied force  $\bar{F}$  also acts as a constraint force because it imposes the kinematical condition that end  $A$  has a constant velocity. Gravity has been omitted from the free-body diagram, which implies that the system lays in the horizontal plane or that the applied force  $\bar{F}$  is large compared to  $mg$ .



Free-body diagram of the sliding bar.

Bar  $AB$  is in general motion, so we place the origin of  $xyz$  at the center of mass. It will be necessary to relate the motions of ends  $A$  and  $B$ . Doing so is assisted by aligning the axes such that at the instant described by the equations of motion the axes are horizontal and vertical.

It is apparent that knowledge of the value of the elevation angle  $\theta$  fully specifies the position of the bar. Furthermore,  $\dot{\theta}$  is the rotation rate of the bar, which means that we need to establish the kinematical relationship between  $\dot{\theta}$  and the given speed  $v$ . As we saw in Chapter 4, we could obtain this relationship by differentiating algebraic expressions derived from trigonometry. Instead, to convey a picture of how multibody linkages could be treated, we pursue a kinematical analysis relating the velocity and acceleration of constrained points. The velocity of end  $A$  is stated to be constant  $v$  to the right, so end  $B$  must move downward parallel to its guide bar. Because  $\dot{\theta}$  is the rotation rate about the  $z$  axis, we have

$$\begin{aligned}\bar{v}_A &= v\bar{i}, & \bar{v}_B &= v_B(\cos\beta\bar{i} - \sin\beta\bar{j}), & \bar{\omega} &= -\dot{\theta}\bar{k}, \\ \bar{a}_A &= \bar{0}, & \bar{a}_B &= \dot{v}_B(\cos\beta\bar{i} - \sin\beta\bar{j}), & \bar{\alpha} &= -\ddot{\theta}\bar{k}.\end{aligned}$$

We relate the velocities of both ends, using  $\theta$  to describe the relative position. This gives

$$\begin{aligned}\bar{v}_B &= \bar{v}_A + \bar{\omega} \times \bar{r}_{B/A}, \\ v_B(\cos\beta\bar{i} - \sin\beta\bar{j}) &= v\bar{i} + (-\dot{\theta}\bar{k}) \times (-L\cos\theta\bar{i} + L\sin\theta\bar{j}).\end{aligned}$$

The scalar equations we obtain by matching like components are

$$\bar{v}_B \cdot \bar{i} = v_B \cos\beta = v + \dot{\theta}L\sin\theta, \quad \bar{v}_B \cdot \bar{j} = -v_B \sin\beta = \dot{\theta}L\cos\theta.$$

Elimination of  $v_B$  from these equations and use of a trigonometric identity lead to

$$\dot{\theta} = -\frac{v \sin\beta}{L \cos(\beta - \theta)}. \quad (1)$$

## 6.2 Planar Motion

329

We now apply the analogous analysis to acceleration,

$$\bar{a}_B = \bar{a}_A + \bar{\alpha} \times \bar{r}_{B/A} - \omega^2 \bar{r}_{B/A},$$

$$\dot{v}_B (\cos \beta \bar{i} - \sin \beta \bar{j}) = (-\ddot{\theta} \bar{k}) \times (-L \cos \theta \bar{i} + L \sin \theta \bar{j}) - \dot{\theta}^2 (-L \cos \theta \bar{i} + L \sin \theta \bar{j}).$$

Matching like components gives

$$\bar{a}_B \cdot \bar{i} = \dot{v}_B \cos \beta = \ddot{\theta} L \sin \theta + \dot{\theta}^2 L \cos \theta,$$

$$\bar{a}_B \cdot \bar{j} = -\dot{v}_B \sin \beta = \ddot{\theta} L \cos \theta - \dot{\theta}^2 L \sin \theta.$$

Elimination of  $\dot{v}_B$  leads to

$$\ddot{\theta} = -\dot{\theta}^2 \frac{\sin(\beta - \theta)}{\cos(\beta - \theta)} = -\left(\frac{v}{L}\right)^2 \frac{(\sin \beta)^2 \sin(\beta - \theta)}{\cos(\beta - \theta)^3}. \quad (2)$$

Note that we could have obtained the same expression directly by differentiating Eq. (1) with respect to time.

Equations (1) and (2) allow us to describe the acceleration of the center of mass in terms of  $v$  and  $\theta$ . Relating this point to the constrained point  $A$  gives

$$\begin{aligned} \bar{a}_G &= \bar{a}_A + \bar{\alpha} \times \bar{r}_{G/A} - \omega^2 \bar{r}_{G/A} \\ &= \frac{L}{2} (\ddot{\theta} \sin \theta + \dot{\theta}^2 \cos \theta) \bar{i} + \frac{L}{2} (\ddot{\theta} \cos \theta - \dot{\theta}^2 \sin \theta) \bar{j}. \end{aligned}$$

Substitution of Eqs. (1) and (2) and a trigonometric identity eventually lead to

$$\bar{a}_G = \frac{v^2}{2L \cos(\beta - \theta)^3} (\cos \beta \bar{i} - \sin \beta \bar{j}). \quad (3)$$

[The preceding expression indicates that  $\bar{a}_G$  is parallel to the left guide bar. This is a consequence of a general property of rigid-body motion. If  $G$  is the midpoint between points  $A$  and  $B$ , describing  $\bar{a}_G$  in terms of  $\bar{a}_A$  and  $\bar{a}_B$  leads to  $\bar{a}_G = \frac{1}{2} (\bar{a}_A + \bar{a}_B)$ .]

We now are ready to form the equations of motion. The centroidal moment of inertia of the bar is  $(1/12) mL^2$ , so we have

$$\begin{aligned} \Sigma \bar{F} \cdot \bar{i} &= F - f_A + N_B \sin \beta - f_B \cos \beta = m (\bar{a}_G \cdot \bar{i}) = \frac{mv^2}{2L} \frac{(\sin \beta)^2 \cos \beta}{\cos(\beta - \theta)^3}, \\ \Sigma \bar{F} \cdot \bar{j} &= N_A + N_B \cos \beta + f_B \sin \beta = m (\bar{a}_G \cdot \bar{j}) = -\frac{mv^2}{2L} \frac{(\sin \beta)^2 \sin \beta}{\cos(\beta - \theta)^3}, \\ \Sigma \bar{M}_A \cdot \bar{k} &= N_A \left( \frac{L}{2} \cos \theta \right) - f_A \left( \frac{L}{2} \sin \theta \right) - [N_B \cos(\beta - \theta)] \frac{L}{2} \\ &\quad - [f_B \sin(\beta - \theta)] \frac{L}{2} = I_{zz} (-\ddot{\theta}) = -\frac{1}{12} mL^2 \left( \frac{v}{L} \right)^2 \frac{(\sin \beta)^2 \sin(\beta - \theta)}{\cos(\beta - \theta)^3}. \end{aligned} \quad (4)$$



These three equations of motion contain five unknown variables:  $F$ ,  $N_A$ ,  $N_B$ ,  $f_A$ , and  $f_B$ . The required additional equations relate the sliding friction and normal forces at each collar. Coulomb's law asserts that, when two surfaces slide over each other, then  $|\bar{f}| = \mu_k |\bar{N}|$ . The free-body diagram properly showed the sense of each friction force, but it was noted that either normal force might actually be in the opposite sense from the one that was used to construct the diagram. Equations (4) may be employed if either normal force is reversed, provided that  $N_A$  or  $N_B$  is replaced with its negative value. In other words, we may obtain a set of equations that are valid in all cases by defining  $N_A$  and  $N_B$  to be positive values, and replacing  $N_A$  with  $\sigma_A N_A$  and  $N_B$  with  $\sigma_B N_B$  in Eqs. (4), with  $\sigma_A = \pm 1$  and  $\sigma_B = \pm 1$ . Correspondingly, Eqs. (4) may be written as


$$[H(\sigma_A, \sigma_B)] \begin{Bmatrix} F \\ N_A \\ N_B \end{Bmatrix} = \frac{mv^2}{L} \{K\},$$

$$[H(\sigma_A, \sigma_B)] = \begin{bmatrix} 1 & -\mu & (\sigma_B \sin \beta - \mu \cos \beta) \\ 0 & \sigma_A & (\sigma_B \cos \beta + \mu \sin \beta) \\ \sin(\theta) & \sigma_A \cos(\theta) - \mu \sin(\theta) & -\sigma_B \cos(\beta - \theta) - \mu \sin(\beta - \theta) \end{bmatrix},$$

$$\{K\} = \frac{(\sin \beta)^2}{\cos(\beta - \theta)^3} [0.5 \cos \beta \quad -0.5 \sin \beta \quad -\sin(\beta - \theta)/6]^T.$$

(5)

A corollary of this modification is that solutions of Eqs. (5) are meaningful only if  $N_A$  and  $N_B$  are both positive. Thus we select an angle of inclination in the range  $0 < \theta < \beta$  and solve Eqs. (5) for each permutation of  $\sigma_A = 1$  or  $-1$  and  $\sigma_B = 1$  or  $-1$ . We discard the solution for a set of signs if either  $N_A$  or  $N_B$  is found to be negative. This leads to the possibility of multiple solutions, which is a common occurrence in nonlinear systems. However, the normal forces found for  $\beta = 75^\circ$  and  $\mu = 0.25$ , which are depicted nondimensionally in the first set of graphs, indicate that  $\sigma_A = \sigma_B = -1$  is the only valid case over the entire range of  $\theta$ .



Values of the normal forces  $N_A$  and  $N_B$  as functions of  $\theta$  when  $\beta = 75^\circ$ ,  $\mu_k = 0.25$ , for each permutation of their sign factors


### 6.3 Newton–Euler Equations for a System

331

The concluding graph shows  $F$  and the reaction forces as functions of the nondimensional time  $vt/L$ . This parameter is related to  $\theta$  by the law of sines. If we take  $t = 0$  to correspond to  $\theta = \beta$ , then we have

$$\frac{vt}{\sin(\beta - \theta)} = \frac{L}{\sin \beta}.$$

One reason for the rising value of  $F$  as  $t$  increases (decreasing  $\theta$ ) is the presence of  $\cos(\beta - \theta)^3$  in the denominators of both  $\bar{a}_G$  and  $\ddot{\theta}$ .




Forces as functions of nondimensional elapsed time corresponding to  $\sigma_A = \sigma_B = -1$ ;  $\beta = 75^\circ$ ,  $\mu_k = 0.25$


### 6.3 NEWTON–EULER EQUATIONS FOR A SYSTEM

The reduction from an arbitrary collection of particles to a rigid body had important benefits, in that doing so reduced enormously the number of kinematical variables, simultaneously with enabling us to ignore the interaction forces exerted between the particles. Both gains result from the recognition that the particles forming a rigid body are mutually constrained. In the same manner, it sometimes is useful to consider interacting rigid bodies as a unified system. The concepts we develop here consider several bodies to act in unison. Doing so lessens the need to consider the forces associated with the interaction of these bodies. However, in doing so, fewer equations of motion will be available. Thus the concepts that follow should be considered to supplement, rather than replace, the basic Newton–Euler equations for each body in a system.

To assemble a system from its constituent rigid bodies, consider the pair of bodies in Fig. 6.2, which are loaded by a set of external forces that are not labeled. In addition, Body 2 exerts force  $\bar{f}_{1,2}$  and couple  $\bar{M}_{1,2}$  on Body 1 as a result of their interaction, which can be the result of their being connected or as a consequence of field effects such as gravity. The influence of Body 1 on Body 2 consists of force  $\bar{f}_{2,1}$  and couple  $\bar{M}_{2,1}$ . These



**Figure 6.2.** Forces acting on a pair of interconnected rigid bodies.



**Figure 6.3.** Inertial force–couple systems equivalent to the forces acting on a pair of interacting rigid bodies.

interaction effects are governed by Newton's Third Law, which means that  $\vec{f}_{2,1} = -\vec{f}_{1,2}$ ,  $\vec{M}_{2,1} = -\vec{M}_{1,2}$ , and  $\vec{f}_{2,1}$  and  $\vec{f}_{1,2}$  share the same line of action.

The method by which we combine these two bodies into a system appeared in Fig. 6.1, which depicted the force system acting on a rigid body as being equivalent in its effect to a dynamic  $m\vec{a}_G$  applied at the center of mass and a dynamic couple  $d\vec{H}_G/dt$ . Figure 6.3 applies the same representation to each body considered in the previous figure. The forces and couples acting on each body in Figs. 6.2 and 6.3 are equivalent, so their combined effect must also be equivalent. It follows that their sum, which represents the resultant force acting on the system, is the same, and their moment about any point  $B$  also is the same. The same conclusion would be reached if the system were composed of  $N$  bodies, so the *Newton–Euler equations for the system* are

$$\begin{aligned}\Sigma \vec{F} &= \sum_{j=1}^N m_j \vec{a}_{Gj}, \\ \Sigma \vec{M}_B &= \sum_{j=1}^N \frac{d\vec{H}_{Gj}}{dt} + \sum_{j=1}^N \vec{r}_{Gj/B} \times m_j \vec{a}_{Gj}.\end{aligned}\tag{6.3.1}$$

These equations of motion share with Eq. (6.1.2) the cumbersome feature of having the center-of-mass accelerations appear in the moment equations. For a single body, which was the scope of Eq. (6.1.2), there was no advantage to such an approach. The same is not true here because of an aspect of the resultant force and moment of the actual force system. As was noted, the forces and couples exerted between any pair of rigid bodies satisfies Newton's Third Law. The contributions of each pair to the force and moment sums cancel, so we may ignore any forces or couples that are internal to the system when we formulate the resultants in Eqs. (6.3.1). Another useful aspect of these equations lies in the arbitrariness of point  $B$ . The main consideration in selecting the point for a moment sum in the static case is the ability to avoid the appearance of unknown forces (usually reactions) in the moment equilibrium equations. We have developed here a comparable ability for dynamic systems.

To see the possible advantage in the system viewpoint consider two interacting rigid bodies in spatial motion. Describing the motion of each rigid body in isolation from the other yields a total of 12 scalar Newton–Euler equations: three force component equations and three moment component equations for each body. These equations contain the forces and/or couples exerted between each body as unknown reactions, so the solution of the equations must determine, or at least eliminate, those reactions. Considering the two bodies as a single system, so that the interaction forces exerted

### 6.3 Newton–Euler Equations for a System

333

between them become internal to the system, leads to three scalar force equations and three scalar moment equations that do not contain these forces.

The systems viewpoint does not necessarily lead to a solvable set of equations, because that question depends on the number of external reaction forces and kinematical variables that arise. In the event that Eqs. (6.3.1) are not sufficient to find the desired variables, the equations may be supplemented by Newton–Euler equations of motion for any of the rigid bodies. However, it is important to recognize that Eqs. (6.3.1) are essentially the same as the result of summing the equations of motion for each isolated body, so they do not contain any new information. If there are  $N$  bodies in a system, then there are no more than  $6N$  independent scalar Newton–Euler equations of motion. Up to six of these may be obtained from Eqs. (6.3.1).

The ability to consider a set of moving parts as a system enables us to qualitatively explain how a bicyclist can maintain balance and maneuver without falling. To avoid going into details that would obscure the discussion, we employ a simplified model of the steering configuration. Our model, which is shown in top view in Fig. 6.4, considers the axis of the steering fork to be perpendicular to the longitudinal axis and to intersect vertically the axis of the front wheel. Under perfect conditions, to follow a straight path the bicycle would be oriented vertically, with the rider's center of mass situated directly over the line connecting the centers of the wheels. The angular momenta of the forward and rear wheels,  $\bar{H}_f$  and  $\bar{H}_r$ , are horizontal in this case, as shown. If it were not for rolling resistance, this motion could be sustained without any effort on the rider's part.




Figure 6.4. Balancing of a bicycle as seen in a top view.

Such ideal conditions cannot be maintained. For example, the rider might lean over or a gust of wind might arise. Such a disturbance, in combination with the reaction of the wheels, creates an overturning moment  $\bar{M}$  that acts about the longitudinal axis. (The situation in the figure corresponds to the rider leaning to the left.) This moment must be matched by a corresponding change in the angular momentum. If the rider makes no adjustments and remains stationary relative to the bike, the result will be an angular acceleration in the direction of  $\bar{M}$ . In other words, the bike would fall over. Instead, the rider turns the handlebars, which causes the steering fork to rotate at some angular speed  $\Omega$ . This rotation causes the tip of  $\bar{H}_f$  to move in the sense of  $\bar{\Omega} \times \bar{H}_f$ . The consequence of  $d\bar{H}_f/dt$  equaling  $\bar{M}$  is that the sense of  $\bar{\Omega}$  induces a turn to the side in which the bike is tending to lean (left in the case of the figure).

If the rider wishes to return to the direction initially set, then this correctional maneuver must be reversed. The rider turns the steering wheel in the opposite sense, thereby reversing the sense of  $d\bar{H}_f/dt$ . Thus, in the scenario of Fig. 6.4, after compensating for  $\bar{M}$ , the rider would turn the handlebars clockwise as viewed from above, thereby generating a  $d\bar{H}_f/dt$  effect that is oriented forward. To generate a force system whose

resultant moment about the longitudinal axis matches this rate of change of the angular momentum, the rider simultaneously leans to the right, thereby shifting the center mass to the other side. Thus riding in a straight line is actually a sequence of corrective steering maneuvers and shifts of the center of mass. In essence, the bicyclist is both the actuator and controller of a feedback control system. This feature is most evident in children who have just begun to ride a bicycle. For a very experienced bicyclist, the corrective maneuvers are barely perceptible. Also, if the rider's hands are not placed on the handlebars, then the steering wheel turns of its own accord in the manner required to change the angular momentum at a rate that matches the unbalanced moment. In any event the ability to steer is essential to maintaining one's balance.

When a rider wishes to execute a steady turn the handlebars are not returned after their initial rotation, so the bicycle is leaning to the side in which the turn is being executed. This situation is essentially as described by Example 6.4, except that it is now convenient to use a reference frame whose origin is the center of mass of the whole bicycle, with the  $y$  axis intersecting the center of both wheels. There is a normal force and a friction force acting on each wheel, the resultant of the latter being what is required to make the center of mass of the bicycle follow a circular path at speed  $v$ . The angular momenta of both wheels no longer are oriented in fixed directions, because the bicycle is rotating about the vertical axis at  $v/\rho$ , where  $\rho$  is the radius of the circular path. For a left turn in Fig. 6.4, both  $d\bar{H}_f/dt$  and  $d\bar{H}_r/dt$  will be rearward. Regardless of the direction of the turn, we know that  $d\bar{H}_f/dt + d\bar{H}_r/dt$  must equal the overturning moment of the friction, gravity, and normal forces about the longitudinal axis.

A performer riding a unicycle exploits these same phenomena to maintain left–right balance. Thus falling to the left is controlled by twisting the wheel left, and vice versa. Forward–rear balance requires a different control strategy. This relies on the fact that a falling stick can be kept at a constant angle of tilt if it is given the correct translational acceleration in the horizontal direction. Thus the unicyclist compensates for a tendency to fall forward or back by accelerating in the direction of that tendency. Obviously riding a unicycle is substantially more difficult than riding a bicycle.


This discussion of a bicycle simplifies much, and it also ignores some important effects. For example, if the bicycle begins to tip over, the angular momentum of each wheel will change in the vertical direction. The matching moment is generated at the front and rear wheels in the form of transverse friction forces that form a vertical couple. These forces influence the handling and stability of the bicycle. Nevertheless, the discussion does give a reasonable picture.

**EXAMPLE 6.10** An automobile moving at a constant speed  $v$  follows a circular path of radius  $\rho$ . The track (distance between a pair of wheels) is  $w$  and the wheel-base (distance from front to rear axle) is  $\ell$ . The mass of the automobile is  $m$ , and the center of mass is on the midplane, at distance  $b$  behind the front axle and height  $h$  above the ground. Each wheel has radius  $R$ , mass  $m_w$ , moment of inertia  $J$  about its axle, and coefficient of static friction  $\mu$ . Determine the maximum speed  $v$  that may be sustained by the vehicle without skidding or tipping over.

### 6.3 Newton–Euler Equations for a System

335

**SOLUTION** This example explores an interesting effect of the inertia of a wheel as a way of illustrating the analysis of an assembly of bodies. The system consists of the vehicle chassis and the four wheels. The  $xyz$  coordinate system is defined in the free-body diagram to have its origin at the center of mass of the chassis, with the  $x$  axis forward. Acting at each wheel is the normal force  $\bar{N}_j$ , which is assumed to be collinear with the weight of the wheel acting at its center of mass of the wheel. Each wheel also has a friction force  $\bar{f}_j$ , which is depicted in the free-body diagram as acting to the left relative to the forward direction, as they would for a left turn.



Free-body diagram of an automobile executing a turn to the left.

It is reasonable to neglect rolling resistance, so each friction force should be shown as acting perpendicular to the plane of the wheel. However, this introduces a complication regarding the front wheels, because they must be rotated to execute the turn, so the friction forces at the front and rear wheels are not parallel. One consequence is that there is a net component of the friction force in the longitudinal  $x$  direction, which means that a friction force representing traction must be applied to maintain a constant speed. To simplify the analysis all friction forces are shown in the diagram as though the front wheels were not steering, so that they act in the transverse  $y$  direction.

Another simplification we employ is to consider all centers of mass to be following circles whose normal direction are  $\bar{i}$ . For the wheels on the left side, which are closer to the center of curvature, the radius of the circle is  $\rho - w/2$ , whereas the radius for wheels on the right side is  $\rho + w/2$ . Thus the center-of-mass accelerations are approximated as

$$\bar{a}_{G0} = \rho \Omega^2 \bar{j}, \quad \bar{a}_{G1} = \bar{a}_{G3} = \left( \rho - \frac{w}{2} \right) \Omega^2 \bar{j}, \quad \bar{a}_{G2} = \bar{a}_{G4} = \left( \rho + \frac{w}{2} \right) \Omega^2 \bar{j}, \quad (1)$$

where  $\Omega = v/\rho$  is the rotation rate about the vertical axis. The angular momentum of the chassis is due to  $\Omega$ , and it is constant. The rotation rate of a wheel about its axle is  $v/R$ , so the angular momentum of a wheel has two components:  $J(v/R)$  about its axle, which is parallel to the  $y$  axis, and a constant component in the vertical direction that is due to  $\Omega$ . The horizontal component rotates at  $\bar{\Omega}$ , so the rates of change of the angular momenta are

$$\dot{\bar{H}}_{G0} = \bar{0}, \quad \dot{\bar{H}}_{Gj} = \bar{\Omega} \times \left( J \frac{v}{R} \bar{j} \right) = -J \Omega^2 \frac{\rho}{R} \bar{i}. \quad (2)$$

We sum moments about the chassis' center of mass. In view of Eqs. (1) and (2) and the fact that each  $m\bar{a}$  vector is in the  $y$  direction, Eqs. (6.3.1) become

$$\begin{aligned}\Sigma \bar{F} &= \sum_{j=1}^N m_j \bar{a}_{Gj} = (m + 4m_w) \rho \Omega^2 \bar{j}, \\ \Sigma \bar{M}_B &= \sum_{j=0}^4 \frac{d\bar{H}_{Gj}}{dt} + \sum_{j=0}^4 \bar{r}_{Gj/B} \times m_j \bar{a}_{Gj} = -4J\Omega^2 \frac{\rho}{R} \bar{i} + [b\bar{i} - (h - R)\bar{k}] \\ &\quad \times m_w (\bar{a}_{G1} + \bar{a}_{G2}) + [-(\ell - b)\bar{i} - (h - R)\bar{k}] \times m_w (\bar{a}_{G1} + \bar{a}_{G2}) \\ &= \left[ -4J\Omega^2 \frac{\rho}{R} + 4(h - R) \rho m_w \Omega^2 \right] \bar{i} + (2b - \ell) \rho m_w \Omega^2 \bar{k}.\end{aligned}\quad (3)$$

The simplified construction of the friction force enables us to evaluate the moments by inspection, so matching like components in Eqs. (1) and (2) leads to

$$\Sigma \bar{F} \cdot \bar{i} \equiv 0,$$

$$\Sigma \bar{F} \cdot \bar{j} = (f_1 + f_2 + f_3 + f_4) = (m + 4m_w) \rho \Omega^2, \quad (4)$$

$$\Sigma \bar{F} \cdot \bar{k} = N_1 + N_2 + N_3 + N_4 - mg - 4m_w g = 0, \quad (5)$$

$$\begin{aligned}\Sigma \bar{M}_G \cdot \bar{i} &= (N_1 - N_2 + N_3 - N_4) \frac{w}{2} + (f_1 + f_2 + f_3 + f_4) h \\ &= \Omega^2 \left[ -J \frac{\rho}{R} + 4(h - R) \rho m_w \right],\end{aligned}\quad (6)$$

$$\Sigma \bar{M}_G \cdot \bar{j} = (-N_1 - N_2 + 2m_w g) b + (N_3 + N_4 - 2m_w g) (\ell - b) = 0, \quad (7)$$

$$\Sigma \bar{M}_G \cdot \bar{k} = (f_1 + f_2) b - (f_3 + f_4) (\ell - b) = (2b - \ell) \rho m_w \Omega^2 \bar{k}. \quad (8)$$

There are more unknown forces than the number of available equations of motion. It is possible to solve Eqs. (4) and (8) for the combinations  $f_1 + f_2$  and  $f_3 + f_4$ , and simultaneous solution of Eqs. (5) and (7) leads to a solution for  $N_1 + N_2$  and  $N_3 + N_4$ . Doing so shows that

$$\begin{aligned}N_1 + N_2 &= \left( \frac{\ell - b}{\ell} m + 2m_w \right) g, \\ N_3 + N_4 &= \left( \frac{b}{\ell} m + 2m_w \right) g, \\ f_1 + f_2 &= \left[ \frac{\ell - b}{\ell} (m + 4m_w) + \frac{2(2b - \ell)}{\ell} m_w \right] \frac{v^2}{\rho}, \\ f_3 + f_4 &= \left[ \frac{b}{\ell} (m + 4m_w) - \frac{2(2b - \ell)}{\ell} m_w \right] \frac{v^2}{\rho}, \\ (N_1 - N_2 + N_3 - N_4) \frac{w}{2} &= \left[ -\frac{J}{R} - hm - 4Rm_w \right] \frac{v^2}{\rho}.\end{aligned}\quad (9)$$

### 6.3 Newton–Euler Equations for a System

337

We recover the static normal forces from these equations by setting  $v = 0$ . It is reasonable to assume that the dynamic effect is such that  $N_1$  and  $N_3$  on the left side of the automobile decrease by the same amount  $\Delta$  relative to their values, whereas  $N_2$  and  $N_4$  increase by that same amount. Hence we set

$$\begin{aligned} N_1 &= \left( \frac{\ell - b}{2\ell} m + m_w \right) g - \Delta, & N_2 &= \left( \frac{\ell - b}{2\ell} m + m_w \right) g + \Delta, \\ N_3 &= \left( \frac{b}{2\ell} m + m_w \right) g - \Delta, & N_4 &= \left( \frac{b}{2\ell} m + m_w \right) g + \Delta. \end{aligned} \quad (10)$$

The last of Eqs. (9) then yields

$$\Delta = \frac{J + h R m + 4 R^2 m_w}{2 w R \rho} v^2. \quad (11)$$

Even though we cannot determine the individual friction forces, we have sufficient information to identify the critical conditions. In the skidding limit, each wheel has attained its maximum possible friction force, so we analyze it by setting  $f_j = \mu N_j$ . From the first and third of Eqs. (9) we find that

$$v_{\text{skid}} = \left[ \frac{(\ell - b) m + 2 m_w \ell}{(\ell - b)(m + 4 m_w) + 2(2b - \ell) m_w} \right]^{1/2} (\mu \rho g)^{1/2}. \quad \triangleleft$$

The same calculation made with the second and fourth of Eqs. (9) yields

$$v_{\text{skid}} = \left[ \frac{b m + 2 m_w \ell}{b(m + 4 m_w) - 2(2b - \ell) m_w} \right]^{1/2} (\mu \rho g)^{1/2}. \quad \triangleleft$$

Note that  $f_1 + f_2$  and  $f_3 + f_4$  both increase monotonically with increasing  $v$ , whereas the corresponding normal force sums are independent of speed. Thus the first value of  $v_{\text{skid}}$  is the maximum speed for which the front wheels will not skid, and the second value is the maximum speed for which the rear wheels do not skid. Safe operation requires that we remain below the lower speed. In the special case in which the center of mass is midway,  $b = \ell/2$ , both speeds reduce to  $(\mu \rho g)^{1/2}$ . The same result is obtained in the limiting case in which each wheel's mass vanishes. Thus we deduce that the primary factors influencing whether the wheels will skid are the coefficient of static friction and the radius of curvature of the turn.

The condition in which the vehicle is about to tip over occurs if the normal force at both inner wheels is zero,  $N_1 = N_3 = 0$ , but the vehicle is still horizontal. In a strict sense, Eqs. (9) do not apply in this case because Eqs. (10) indicate that if  $b > \ell/2$  then the value of  $\Delta$  for which  $N_3 = 0$  gives  $N_1 < 0$ , which is not possible. Similarly, if  $b < \ell/2$ , zero  $N_1$  corresponds to negative  $N_3$ . Rather than reanalyze the basic equations, we argue that any condition where a wheel loses contact with the ground is dangerous. In that case we take  $\Delta$  to be the smaller of the values for



which  $N_1$  or  $N_3$  vanishes, then substitute that value into Eq. (11) to determine the corresponding value of the speed. The result is

$$v_{\text{tip}} = \left[ \frac{\min(b, \ell - b)m + 2\ell m_w}{J + hRm + 4R^2m_w} \right]^{1/2} \left( \frac{wR\rho g}{\ell} \right)^{1/2}. \quad \triangleleft$$

In the limiting case in which the mass of the wheels is negligible, setting  $m_w = J = 0$  in the preceding equation gives

$$v_{\text{tip}} = \left[ \frac{\min(b, \ell - b)}{\ell} \right]^{1/2} \left( \frac{w\rho g}{h} \right)^{1/2}.$$

Our analysis indicated that the speed at which the automobile will begin to skid is not strongly dependent on the vehicle's inertial properties, but that is not the case for tipping over. One is more likely to recover control of a vehicle that has begun to skid than one that is about to tip over, so we wish that  $v_{\text{tip}} > v_{\text{skid}}$ . Because any value of  $J$  decreases  $v_{\text{tip}}$ , it is desirable to minimize the mass of the wheels. In the limit as  $m$  and  $J$  vanish, we find that this design criterion on the speed is satisfied if

$$\frac{w}{h} > \frac{\ell}{\min(b, \ell - b)}\mu.$$

This is consistent with our intuition that an automobile will be less likely to tip over than a truck or SUV having the same track  $w$ .

## 6.4 MOMENTUM AND ENERGY PRINCIPLES

The force and moment equations discussed thus far govern the linear and angular acceleration of a body. Momentum and energy principles, which represent standard integrals of these equations, may be used to relate the linear and angular velocity of the body at successive instants or locations. Because these principles are derived directly from the Newton–Euler equations of motion, these integral relations should be considered to supplement, rather than replace, the basic acceleration equations. Furthermore, evaluation of the associated impulse and work quantities often requires knowledge of some aspects of a body's motion, in which case these principles cannot be used to predict the motion. One place where momentum principles are particularly useful is understanding the manner in which any projectile rotates, which is the focus of Section 10.1.

### 6.4.1 Impulse–Momentum Principles

Equations (5.1.22) and (5.1.24) are the time derivative forms of impulse–momentum relations. Definite integration of each between any two instants  $t_1$  and  $t_2$  leads to

$$\begin{aligned} \bar{P}_2 &= \bar{P}_1 + \int_{t_1}^{t_2} \Sigma \bar{F} dt, \\ (\bar{H}_A)_2 &= (\bar{H}_A)_1 + \int_{t_1}^{t_2} \Sigma \bar{M}_A dt. \end{aligned} \quad (6.4.1)$$

## 6.4 Momentum and Energy Principles

339

These relations state that the final value of a body's linear or angular momentum exceeds the initial value by the corresponding type of impulse, which is defined to be the time integral of the resultant force or moment. The linear momentum of a rigid body is  $m\bar{v}_G$  and the angular momentum is described by Eqs. (6.1.3).

Both momentum principles are vector equations, so they each yield three scalar equations obtained from equating like components. If the impulses can be evaluated, then the scalar equations fully define the corresponding change in the linear or angular velocities. The difficulty lies in that evaluation. The resultant force and moment acting on a body are seldom known in advance because the reactions are unknown. Furthermore, it is not sufficient to know the force or moment in terms of components relative to the body because the corresponding unit vectors are not constant. Evaluating the impulse integrals in that case would require knowledge of the orientation of the unit vectors, and of the components, as functions of time. Such information usually is not available, because it depends on the bodily motion being studied.

Momentum-impulse relations are particularly useful when *impulsive forces* act on a body. Examples of such forces are the those generated by an impact, such as between a golf club and a ball, and explosions. Impulsive forces are defined to impart very large accelerations to a body over a very short time interval. The notion of an impulsive force is that it is sufficiently large that the influence of nonimpulsive forces, such as those associated with gravity and springs, may be ignored during the brief interval of the impulse. (Note in this regard that reactions can act impulsively, because they must be as large as necessary to impose the associated motion constraint.) A corollary of the brevity of the time interval is that the system's position cannot change much because the velocity is finite. These observations lead to a simplified model of the action of impulsive forces, which is quite useful if we are interested in the macroscopic aspects of a system's motion. We represent the linear and angular impulses by the average values of the resultant force and moment, and take the velocity to change instantly from time  $t_0^-$  to time  $t_0^+$ , while the position is unaltered. Let  $t_i < t < t_i + \Delta t$  denote the interval in which the impulsive forces act, and let a subscript "imp" denote average values of the resultant force and moment of the impulsive forces. The simplified model of impulsive action then states that

$$\begin{aligned}\bar{P}(t = t_i^+) &= \bar{P}(t = t_i^-) + (\Sigma \bar{F})_{\text{imp}} \Delta t, \\ \bar{H}_A(t = t_i^+) &= \bar{H}_A(t = t_i^-) + (\Sigma \bar{M}_A)_{\text{imp}} \Delta t, \\ \bar{r}_{P/O}(t = t_i^+) &= \bar{r}_{P/O}(t = t_i^-),\end{aligned}\tag{6.4.2}$$

where point  $P$  referred to in the last relation is any point in the body. It is obvious that these relations should be used judiciously. For example, the corollary of taking the velocity to change instantaneously is that the corresponding acceleration is infinite. Thus the simplified model is of no use if one wishes to study the details of the impulsive process, such as what stresses are generated by the collision of bodies. The role of impulse forces in accounting for collisions between bodies is treated in Subsection 6.4.3.

The extension of impulse–momentum principles to systems of bodies is readily obtained from Eqs. (6.3.1). We seek time integrals of those relations in which the final result requires knowledge of motion parameters at only the initial and final instants. Toward that end we operate on the last term in the angular momentum equation by referring the acceleration of each body's center of mass to the motion of point  $B$ . Because the summation of  $m_j \bar{r}_{Gj/B}$  for each body is the first moment of mass, which defines the system's center of mass  $G$ , this operation leads to

$$\begin{aligned} \sum_{j=1}^N \bar{r}_{Gj/B} \times m_j \bar{a}_{Gj} &= \sum_{j=1}^N m_j \bar{r}_{Gj/B} \times \bar{a}_B + \sum_{j=1}^N \bar{r}_{Gj/B} \times m_j \bar{a}_{Gj/B} \\ &= m_{\text{system}} \bar{r}_{G/B} \times \bar{a}_B + \sum_{j=1}^N \bar{r}_{Gj/B} \times m_j \bar{a}_{Gj/B}. \end{aligned} \quad (6.4.3)$$

The next step mirrors the derivation of the angular momentum principle for a particle, in which the acceleration term in the summation is converted to a velocity-dependent term by taking the time derivative of the cross product. Because  $d/dt (\bar{r}_{Gj/B}) \equiv \bar{v}_{Gj/B}$ , the result is

$$\sum_{j=1}^N \bar{r}_{Gj/B} \times m_j \bar{a}_{Gj} = m_{\text{system}} \bar{r}_{G/B} \times \bar{a}_B + \sum_{j=1}^N \frac{d}{dt} (\bar{r}_{Gj/B} \times m_j \bar{v}_{Gj/B}). \quad (6.4.4)$$

Thus an alternative form of the second equation of Eqs. (6.3.1) governing the moment acting on a system is

$$\Sigma \bar{M}_B = \sum_{j=1}^N \frac{d\bar{H}_{Gj}}{dt} + m_{\text{system}} \bar{r}_{G/B} \times \bar{a}_B + \sum_{j=1}^N \frac{d}{dt} (\bar{r}_{Gj/B} \times m_j \bar{v}_{Gj/B}). \quad (6.4.5)$$

We seek a form of this relation in which the momentum terms are time derivatives. We therefore require that *the point  $B$  about which we sum moments be an inertial point*, for which  $\bar{a}_B = \bar{0}$ , or else the system's center of mass, in which case  $\bar{r}_{G/B} \equiv \bar{0}$ . In either case the right side is an exact derivative, whose integration yields the principle of angular impulse and momentum for a system. Integration of the first of Eqs. (6.3.1) yields the corresponding linear impulse–momentum principle, so we have found that

$$\begin{aligned} \sum_{j=1}^N m (\bar{v}_{Gj})_2 &= \sum_{j=1}^N m (\bar{v}_{Gj})_1 + \int_{t_1}^{t_2} \Sigma \bar{F} dt, \\ \sum_{j=1}^N (\bar{H}_{Gj})_2 + \sum_{j=1}^N (\bar{r}_{Gj/B} \times m_j \bar{v}_{Gj/B})_2 &= \sum_{j=1}^N (\bar{H}_{Gj})_1 + \sum_{j=1}^N (\bar{r}_{Gj/B} \times m_j \bar{v}_{Gj/B})_1 + \int_{t_1}^{t_2} \Sigma \bar{M}_B dt. \end{aligned} \quad (6.4.6)$$

Proper application of this principle requires that one be cognizant that the moment equation is valid only if the reference point  $B$  is either stationary, in which case the

## 6.4 Momentum and Energy Principles

341


term  $\bar{v}_{Gj/B}$  is the absolute velocity, that is,  $\bar{v}_{Gj/B} = \bar{v}_{Gj}$ , or else it must be the center of mass for the entire system, which corresponds to  $\bar{v}_{Gj/B} = \bar{v}_{Gj} - \bar{v}_B$ . One simplification arises if it should happen that the center of mass is stationary relative to a body. In that case  $\bar{v}_{Gj/B} = \bar{\omega}_j \times \bar{r}_{Gj/B}$ , but  $\bar{r}_{Gj/B} \equiv -\bar{r}_{B/Gj}$ , so that

$$\begin{aligned} \bar{H}_{Gj} + \bar{r}_{Gj/B} \times m_j \bar{v}_{Gj/B} &= \bar{H}_{Gj} + m_j \bar{r}_{B/Gj} \times (\bar{\omega}_j \times \bar{r}_{B/Gj}) \\ &= \bar{H}_{Bj} \text{ if point } B \text{ is stationary relative to body } j, \end{aligned} \quad (6.4.7)$$

where the final form follows from Eq. (5.1.36).

A primary aspect of the system momentum principles is associated with their vectorial nature. Although we might not have a complete idea of the time dependence of all forces acting on a body, it might be that the component of the resultant force in a specific fixed direction  $\bar{e}_F$  is known as a function of time. Similarly, we might know the resultant moment about a fixed axis in direction  $\bar{e}_M$  intersecting an allowable point for the moment equation. The component of the corresponding type of impulse may be evaluated and equated to the momentum change in each direction. The most common situation fitting this specification is that in which an impulse component vanishes. In that case, the associated component of Eqs. (6.4.6) becomes a conservation principle, stating that a system's linear momentum in a certain direction, or angular momentum about a certain axis, is constant.


**EXAMPLE 6.11** A 10-kg square plate suspended by ball-and-socket joint  $A$  is at rest when it is struck by a hammer. The impulsive force  $\bar{F}$  generated by the hammer is normal to the surface of the plate, and its average value during the 4-ms interval that it acts is 5000 N. Determine the angular velocity of the plate at the instant following the impact and the average reaction at the support.



Example 6.11

**SOLUTION** This straightforward example once again highlights the fact that the behavior of bodies in spatial motion is often counterintuitive. We ignore the weight of the plate, which is much smaller than the average applied force. In contrast, the reaction exerted by the ball-and-socket joint, which consists of forces acting in each of the coordinate directions, is impulsive, because it must be as large as necessary to prevent movement of point  $A$ . The plate pivots about the stationary point  $A$

where the ball-and-socket joint is located, so we place the origin of the body-fixed  $xyz$  coordinate system there and align the axes with the edges of the plate.



We know that  $\bar{\omega}_1 = \bar{0}$ , but have no idea what angular velocity results from the action of  $\bar{F}$ . If we knew  $\bar{\omega}_2$  we could find  $\bar{v}_G$  kinematically according to

$$\bar{\omega}_2 = \omega_x \bar{i} + \omega_y \bar{j} + \omega_z \bar{k}, \quad (\bar{v}_G)_2 = \bar{\omega}_2 \times \bar{r}_{G/A}.$$

We set  $\bar{r}_{G/A} = 0.18\bar{i} - 0.06\bar{j}$  m, which leads to

$$(\bar{v}_G)_2 = 0.06\omega_z \bar{i} + 0.18\omega_z \bar{j} + (-0.06\omega_x - 0.18\omega_y) \bar{k}.$$

The inertia properties relative to  $xyz$  are obtained from the Appendix and the parallel axis theorems. The coordinates of point  $A$  relative to centroidal axes parallel to  $xyz$  are  $(-0.18, 0.06, 0)$  m, which leads to

$$I_{xx} = 0.144 \text{ kg}\cdot\text{m}^2, \quad I_{yy} = 0.432 \text{ kg}\cdot\text{m}^2, \quad I_{zz} = 0.576 \text{ kg}\cdot\text{m}^2, \\ I_{xy} = -0.108 \text{ kg}\cdot\text{m}^2, \quad I_{xz} = I_{yz} = 0.$$

The final angular momentum about pivot  $A$  corresponding to these properties is

$$(\bar{H}_A)_2 = (0.144\omega_x + 0.108\omega_y) \bar{i} + (0.432\omega_y + 0.108\omega_x) \bar{j} + 0.576\omega_z \bar{k}.$$

The initial angular momentum is zero, so the final angular momentum must equal the moment impulse. The sole impulsive force exerting a moment about point  $A$  is  $\bar{F}$ . The moment impulse is the average moment of this force multiplied by the 4-ms interval or, equivalently, the moment of the linear impulse of  $\bar{F}$  during this interval. Thus,

$$(\bar{H}_A)_2 = \bar{r}_{F/A} \times \bar{F}_{av}(\Delta t) = (0.36\bar{i} + 0.12\bar{j}) \times (5000\bar{k})(0.004).$$

Matching like components in the two descriptions of  $(\bar{H}_A)_2$  gives

$$(\bar{H}_A)_2 \cdot \bar{i} = (0.144\omega_x + 0.108\omega_y) = 2.4, \\ (\bar{H}_A)_2 \cdot \bar{j} = (0.432\omega_y + 0.108\omega_x) = -7.2, \\ (\bar{H}_A)_2 \cdot \bar{k} = 0.576\omega_z = 0.$$

## 6.4 Momentum and Energy Principles

343

We solve these equations for the rotation rates, from which we obtain

$$\bar{\omega}_2 = 35.90\bar{i} - 25.64\bar{j} \text{ rad/s.} \quad \triangleleft$$

The next step is to form the linear impulse–momentum principle in order to determine the reaction. The velocity of the center of mass corresponding to  $\bar{\omega}_2$  is

$$(\bar{v}_G)_2 = \bar{\omega}_2 \times \bar{r}_{G/A} = 2.462\bar{k} \text{ m/s.}$$

The initial linear momentum was zero, so the final momentum must equal the impulse of all forces:

$$m(\bar{v}_G)_2 = [A_x\bar{i} + A_y\bar{j} + (A_z + F)\bar{k}] \Delta t.$$

The solution of these equations is

$$A_x = A_y = 0, \quad A_z = 1153 \text{ N.} \quad \triangleleft$$

These are average values over the 4-ms interval. The maximum values exceed these.

It might surprise you that the reaction is in the same sense as the impulsive force  $\bar{F}$ . This result indicates that, if the ball-and-socket joint were not present, the plate would rotate about its mass center because of the moment of the force, such that point  $A$  moves in the negative  $z$  direction. It is possible to locate a curve on the plate representing the locus of points at which the force can be applied without generating a dynamic reaction at the joint. Any such point is sometimes referred to as a *center of percussion*.

### 6.4.2 Work–Energy Principles

We begin the derivation of work–energy principles for rigid bodies by considering an isolated rigid body as a collection of particles. Equation (1.2.14) states the principle for a single particle. We use it to describe particle number  $j$  in a system of  $N$  particles. As we did previously, we denote each force acting on this particle as  $\bar{f}_{j,k}$  if it is exerted by any other particle  $k$  within the body, while  $\bar{F}_j$  represents the resultant of all forces exerted on particle  $j$  by bodies not included in the system. The resultant force acting on the particle is the sum of  $\bar{F}_j$  and all of the  $\bar{f}_{j,k}$ . The work done by this resultant is the integral of the resultant's component in the direction of the displacement, multiplied by the differential displacement. The work–energy principle for this particle states that this work increases the kinetic energy:

$$\frac{1}{2}m_j(v_j^2)_2 = \frac{1}{2}m_j(v_j^2)_1 + \oint_1^2 \left( \sum_{\substack{k=1 \\ k \neq j}}^N \bar{f}_{j,k} + \bar{F}_j \right) \cdot d\bar{r}_j. \quad (6.4.8)$$

This relation describes an arbitrary particle within a system, but we are interested in the specific case in which the particles constitute a rigid body. We recall Chasle's theorem, and select any convenient point  $B$  as the reference point for the motion. The

differential displacement  $d\bar{r}_j$  is the result of the displacement of point  $B$  and the infinitesimal rotation  $d\bar{\theta}$  about point  $B$ , see Eq. (3.3.6), so that

$$d\bar{r}_j = d\bar{r}_B + d\bar{\theta} \times \bar{r}_{j/B}. \quad (6.4.9)$$

We know from the Newton–Euler equations of motion that the forces internal to a rigid body do not directly affect its motion, so the same must be true of any energy principle. Thus let us focus on the term in Eq. (6.4.8) that contains these force. The identity for the scalar triple product,  $\bar{a} \cdot (\bar{b} \times \bar{c}) \equiv (\bar{c} \times \bar{a}) \cdot \bar{b}$ , in conjunction with the preceding representation of  $d\bar{r}_j$ , leads to

$$\sum_{\substack{k=1 \\ k \neq j}}^N \bar{f}_{jk} \cdot d\bar{r}_j = \sum_{\substack{k=1 \\ k \neq j}}^N \bar{f}_{j,k} \cdot d\bar{r}_B + \sum_{\substack{k=1 \\ k \neq j}}^N \bar{r}_{j/B} \times \bar{f}_{j,k} \cdot d\bar{\theta}. \quad (6.4.10)$$

Note that  $\bar{r}_{j/B} \times \bar{f}_{j,k}$  is the moment of  $\bar{f}_{j,k}$  about point  $B$ . Thus the right side of this expression replaces the work done by internal forces acting on particle  $j$  with the work done by an equivalent force–couple system acting at point  $B$ .

Now consider the combination of all particles obtained by adding Eq. (6.4.10) for  $j = 1, 2, \dots, N$ . The first term on the right side will add all of the internal forces at point  $B$ , and the second term will add all moments. Specifically,

$$\sum_{j=1}^N \sum_{\substack{k=1 \\ k \neq j}}^N \bar{f}_{jk} \cdot d\bar{r}_j = \left( \sum_{j=1}^N \sum_{\substack{k=1 \\ k \neq j}}^N \bar{f}_{j,k} \right) \cdot d\bar{r}_B + \left( \sum_{j=1}^N \sum_{\substack{k=1 \\ k \neq j}}^N \bar{r}_{j/B} \times \bar{f}_{j,k} \right) \cdot d\bar{\theta}. \quad (6.4.11)$$

For every occurrence of a specific  $j$  in the first sum and a specific  $k$  in the second, there is a matching occurrence in the opposite sequence. According to Newton’s Third Law,  $\bar{f}_{j,k}$  and  $\bar{f}_{k,j}$  are equal in magnitude, opposite in sense, and collinear. The consequence of these properties was seen in Eqs. (5.1.7) to be that the internal forces have a zero resultant, and they exert no net moment about any point. Thus the preceding sum reduces to zero.

It follows that adding work–energy equation (6.4.8) for each particle of the rigid body will result in cancellation of the contribution of all internal forces. Because  $\frac{1}{2}m_j v_j^2$  is the kinetic energy of one particle of the rigid body, and kinetic energy is a scalar, adding the work–energy equation for each particle in a rigid body leads to the *work–energy equation* for a rigid body,

$$T_2 = T_1 + W_{1 \rightarrow 2}, \quad (6.4.12)$$

where  $T_1$  and  $T_2$  are the kinetic energy of the rigid body at any two instants and  $W_{1 \rightarrow 2}$  is the work done by all forces acting on the body as it moves from its position at  $t_1$  to its position at  $t_2$ :

$$W_{1 \rightarrow 2} = \sum_{j=1}^N \oint_1^2 \bar{F}_j \cdot d\bar{r}_j. \quad (6.4.13)$$

## 6.4 Momentum and Energy Principles

345

Recall that the kinetic energy of a rigid body corresponding to specified  $\bar{v}_G$  and  $\bar{\omega}$  is

$$T = \begin{cases} \frac{1}{2}mv_G^2 + \frac{1}{2}\bar{\omega} \cdot \bar{H}_G : \text{any motion} \\ \frac{1}{2}\bar{\omega} \cdot \bar{H}_O : \text{pure rotation about point } O \end{cases}. \quad (6.4.14)$$

Evaluation of the work according to Eq. (6.4.13) requires that we describe functionally how each external force depends on the position of the point at which it is applied. This can be quite cumbersome for two reasons: There might be many points to consider, and some or all of the points might follow intricate paths. An alternative is to shift the forces from the point at which they are applied to any convenient point  $B$  in the body. When Eq. (6.4.9) is used to relate the displacement of a force's point of application to the displacement of the reference point, the work done by force  $\bar{F}_j$  in a differential displacement  $d\bar{r}_j$  becomes

$$\bar{F}_j \cdot d\bar{r}_j = \bar{F}_j \cdot d\bar{r}_B + \bar{F}_j \cdot (\bar{d}\theta \times \bar{r}_{j/B}) \equiv \bar{F}_j \cdot d\bar{r}_B + (\bar{r}_{j/B} \times \bar{F}_j) \cdot \bar{d}\theta, \quad (6.4.15)$$

where the final form stems from the identity for the scalar triple product. Because  $\bar{r}_{j/B} \times \bar{F}_j$  is the moment of  $\bar{F}_j$  about point  $B$  and both  $d\bar{r}_B$  and  $\bar{d}\theta$  are independent of which force is under consideration, adding the work done by each force, as required by Eq. (6.4.13), will lead to two terms containing the resultant force and resultant moment about point  $B$ , specifically,

$$W_{1 \rightarrow 2} = \oint_1^2 \Sigma \bar{F} \cdot d\bar{r}_B + \oint_1^2 \Sigma \bar{M}_B \cdot \bar{d}\theta. \quad (6.4.16)$$

This expression could have been anticipated from Chasle's theorem. It shows that the total work is the sum of the work done by the resultant of the external forces in moving an arbitrary point  $B$  and the work done by the moment of the external forces in the rotation about that point.

Another alternative to direct evaluation of the work done by a force arises when a force is *conservative*. The term “conservative” is a corollary of the property that such a force does no net work when the point at which it is applied follows an arbitrary closed path. Consequently, whatever work it does in going from position 1 to position 2 on a closed path is the negative of the work it will do to return to position 1, so that work is not lost. This property is expressed by

$$W_{1 \rightarrow 2} = -W_{2 \rightarrow 1}. \quad (6.4.17)$$

This must be true for any closed path containing the specified positions  $\bar{r}_1$  and  $\bar{r}_2$  of the point of application. Furthermore, it must be true for any pair of points  $\bar{r}_1$  and  $\bar{r}_2$  on a specific path. These conditions can only be satisfied if the work is determined by the



change in the value of a function of position. This function, termed the *potential energy*, is defined such that

$$W_{1 \rightarrow 2} = V(\vec{r}_1) - V(\vec{r}_2) \equiv V_1 - V_2. \quad (6.4.18)$$

Strictly speaking, all requirements would be met if the opposite sign was used to define  $V(\vec{r})$ . The definition we use enables us to interpret the work done by a conservative force as the amount by which its potential energy is depleted or, equivalently, as the ability of a force to do work.

One method by which we may determine whether a specific force is conservative, and if so, determine the corresponding form of the potential energy, is to evaluate the work the force does when the point at which it is applied follows an arbitrary path. If it is found that the work depends solely on the initial and final position coordinates of its point of application, then  $V(\vec{r}_1)$  and  $V(\vec{r}_2)$  are merely  $V(\vec{r})$  at either location. Clearly, forces imparted with a specified time history are not conservative because the work they do will depend explicitly on the time interval. In the same vein, velocity-dependent forces such as friction are not conservative.

This approach is readily implemented in the case of gravity close to the Earth's surface. Because the force acts in a constant direction, we use Cartesian coordinates to represent the force and the position, which leads to

$$\vec{F} = -mg\vec{K}, \quad d\vec{r} = dX\vec{I} + dY\vec{J} + dZ\vec{K}. \quad (6.4.19)$$

The work done by this force is

$$W_{1 \rightarrow 2} = \oint_1^2 (-mg\vec{K}) \cdot (dX\vec{I} + dY\vec{J} + dZ\vec{K}) = - \int_{Z_1}^{Z_2} mg dZ = mgZ_1 - mgZ_2. \quad (6.4.20)$$

Matching this to Eq. (6.4.18) leads to

$$\boxed{V_{\text{grav}} = mgZ}, \quad (6.4.21)$$

which usually is applied by taking  $Z$  to be the height of the center of mass above some arbitrarily selected reference elevation known as the *datum*.

When we are concerned with a gravity force exerted by a body other than the Earth, or the motion is known to result in large changes in the distance to the center of the Earth, we need to apply the universal law of gravitation, which states that

$$\vec{F} = -\frac{GMm}{r^2}\vec{e}_r, \quad (6.4.22)$$

where  $r$  is the distance to the center of mass of the interacting body and  $\vec{e}_r$  is the unit vector oriented from the attracting body to the body to which  $\vec{F}$  is applied. For the Earth, one can use  $GM = 5.990(10^4) \text{ m}^3/\text{s}^2$ . For the determination of  $V(\vec{r})$  we may consider the attracting body to be stationary, so that  $\vec{e}_r$  is the radial unit vector for spherical

## 6.4 Momentum and Energy Principles

347

coordinates. Correspondingly, the differential displacement is  $d\vec{r} = \bar{v}dt = dr\bar{e}_r + r d\phi\bar{e}_\phi + (r \sin \phi) d\theta\bar{e}_\theta$ , so the work is given by

$$\begin{aligned} W_{1 \rightarrow 2} &= \oint_1^2 \left( -\frac{GmM}{r^2} \bar{e}_r \right) \cdot (dr\bar{e}_r + r d\phi\bar{e}_\phi + r d\theta \sin \phi \bar{e}_\theta) \\ &= - \int_{r_1}^{r_2} \frac{GmM}{r^2} dr = -\frac{GmM}{r_1} + \frac{GmM}{r_2}. \end{aligned} \quad (6.4.23)$$

The terms on the right side are the same function of  $r$  evaluated at each position, so the potential energy is given by

$$V_{\text{grav}} = -\frac{GmM}{r}. \quad (6.4.24)$$

Springs are important as actual devices, as well as models for elastic bodies. If we take one end of the spring to be stationary, the force  $\vec{F}$  applied to the moving point is oriented along the radial line toward the fixed end. In the model of a spring that behaves linearly, the magnitude of the force is  $k\Delta$ , where  $k$  is the spring stiffness and  $\Delta$  is the elongation. The latter is defined as the difference between the current length  $\ell$  of the spring and the undeformed length  $\ell_0$ :

$$\Delta = \ell - \ell_0 \quad (6.4.25)$$

Spherical coordinates centered at the fixed end are suitable for describing the orientation of  $\vec{F}$ . Then  $r = \ell$  and  $dr = d\ell = d\Delta$ , so that

$$\begin{aligned} \vec{F} &= -k\Delta\bar{e}_r, \quad d\vec{r} = d\Delta\bar{e}_r + \ell d\phi\bar{e}_\phi + (\ell \sin \phi) d\theta\bar{e}_\theta, \\ W_{1 \rightarrow 2} &= \oint_1^2 (-k\Delta\bar{e}_r) \cdot (d\Delta\bar{e}_r + \ell d\phi\bar{e}_\phi + \ell d\theta \sin \phi \bar{e}_\theta) \\ &= - \int_{\Delta_1}^{\Delta_2} k\Delta d\Delta = \frac{1}{2}k\Delta_1^2 - \frac{1}{2}k\Delta_2^2. \end{aligned} \quad (6.4.26)$$

Comparison of the latter expression with Eq. (6.4.18) shows that the potential energy of a spring is

$$V_{\text{spr}} = \frac{1}{2}k\Delta^2. \quad (6.4.27)$$

At any position,  $\Delta$  is the elongation of the spring referenced to the unstretched length of the spring, as described, by Eq. (6.4.25). Failure to properly describe  $\Delta$  is a common error in the evaluation of a spring's potential energy.

An alternative approach for examining the conservative nature of a force employs vector calculus. Consider two positions that differ by an infinitesimal amount, so that  $\vec{r}_2 = \vec{r}_1 + d\vec{r}$ . The infinitesimal work  $dW$  done by a conservative force in such a displacement is given by

$$dW = V(\vec{r}_1) - V(\vec{r}_1 + d\vec{r}) = -dV. \quad (6.4.28)$$

Let us use Cartesian coordinates to define the position, so that  $V$  is considered to be a known function of the  $XYZ$  coordinates of the point where the force is applied. The chain rule for differentiation yields

$$dW = -\frac{\partial V}{\partial X}dX - \frac{\partial V}{\partial Y}dY - \frac{\partial V}{\partial Z}dZ. \quad (6.4.29)$$

In Cartesian coordinates an infinitesimal displacement is  $d\vec{r} = dX\vec{i} + dY\vec{j} + dZ\vec{k}$ , so the preceding equation is the scalar form of  $dW = -\nabla V \cdot d\vec{r}$ . However, the work done by any force in an infinitesimal displacement is  $dW = \vec{F} \cdot d\vec{r}$ . Either form is equally correct if  $\vec{F}$  is conservative, so it must be that a conservative force is the negative of the gradient of its potential-energy function:

$$\boxed{\vec{F}_{\text{cons}} = -\nabla V.} \quad (6.4.30)$$

This leads to a simple way of checking that a force is conservative. The curl of the gradient is identically zero, so it must be that

$$\text{if } \nabla \times \vec{F} \equiv \vec{0}, \text{ then } \vec{F} \text{ is conservative.} \quad (6.4.31)$$

If some forces are not conservative, we may use Eq. (6.4.18) to account for the conservative effects, whereas the work done by the nonconservative forces, which we denote as  $W_{1 \rightarrow 2}^{\text{nc}}$ , is found according to either Eq. (6.4.13) or Eq. (6.4.16). Thus,

$$W_{1 \rightarrow 2} = V_1 - V_2 + W_{1 \rightarrow 2}^{\text{nc}}. \quad (6.4.32)$$

Substitution of this expression into the basic work–energy equation yields

$$\boxed{T_2 + V_2 = T_1 + V_1 + W_{1 \rightarrow 2}^{\text{nc}}.} \quad (6.4.33)$$

The quantity  $T + V$  is called the *mechanical energy*. In any motion in which the non-conservative forces do no work, there is *conservation of energy*, meaning that  $T + V$  is constant throughout the motion.

The development thus far is sufficient for the purpose of analyzing specific systems. However, we may garner a different perspective for the role of energy by deriving another energy principle. The motion of the center of mass is governed by Newton’s Second Law. The derivation in Chapter 1 of the work–energy principle for a particle is equally valid when applied to the center of mass, so it must be that

$$\frac{1}{2}m(v_G^2)_2 = \frac{1}{2}m(v_G^2)_1 + \oint_1^2 \Sigma \vec{F} \cdot d\vec{r}_G. \quad (6.4.34)$$

This equation has a simple explanation when we recall Chasle’s theorem to consider the body’s motion to be a superposition of a translation following the center of mass and a rotation about the center of mass. As indicated by Eq. (6.4.14),  $\frac{1}{2}mv_G^2$  is the translational kinetic energy. Thus Eq. (6.4.34) states that the work done by the resultant force to move the center of mass of a rigid body increases the translational kinetic energy.

An interesting aspect of Eq. (6.4.34) is that the work term on the right side also appears in the alternative description of work given by Eq. (6.4.16). In view of Eqs. (6.4.14)

## 6.4 Momentum and Energy Principles

349

and (6.4.16), taking the difference between the work–energy principle of Eq. (6.4.12) and Eq. (6.4.34) leaves

$$\frac{1}{2}\bar{\omega}_2 \cdot (\bar{H}_G)_2 = \frac{1}{2}\bar{\omega}_1 \cdot (\bar{H}_G)_1 + \oint_1^2 \Sigma \bar{M}_G \cdot d\bar{\theta}. \quad (6.4.35)$$

This relation shows that the work done by the resultant moment about the center of mass has the effect of increasing the rotational kinetic energy. Thus replacing the actual forces by an equivalent force–couple system acting at the center of mass leads to an uncoupling of effects, with the resultant force increasing the translational kinetic energy and the resultant moment increasing the rotational kinetic energy.

It might seem that Eqs. (6.4.34) and (6.4.35) provide an alternative to the work–energy principle stated by Eq. (6.4.33). However, this seldom is true, because of a subtle aspect of constraint forces. We will see in the next chapter that such forces often do no work. However, if we transfer a constraint force from its actual point of application to the center of mass, this force will contribute to the work terms in both Eqs. (6.4.34) and (6.4.35). Constraint forces are not known in advance, so neither the translational nor rotational work–energy equation would be useful by themselves for evaluating the motion.

Constraint forces of particular concern are those associated with connections between moving bodies. It sometimes is possible to avoid the occurrence of such forces by considering the assembly of bodies to form a system. The mechanical energies  $T$  and  $V$ , and the work done by forces, are scalars, so the addition of Eq. (6.4.33) for each body in a system yields the same form for the assembly:

$$(T_2)_{\text{total}} + (V_2)_{\text{total}} = (T_1)_{\text{total}} + (V_1)_{\text{total}} + (W_{1 \rightarrow 2}^{\text{nc}})_{\text{total}}. \quad (6.4.36)$$

The value of this principle is that some forces exerted between the bodies will do no work when bodies are considered as a system, even though they do work when each body is considered individually. To see how this might be, consider the planar situation in Fig. 6.5, where two bodies are connected by pins to massless link  $AB$ . Because the link has no mass, it effectively is in static equilibrium, which means that it can sustain only axial force  $F$ . The forces exerted to each body are equal and opposite. The differential amount of work done by these forces when both bodies move is

$$dW = (F\bar{e}_{B/A}) \cdot d\bar{r}_B + (-F\bar{e}_{B/A}) \cdot d\bar{r}_A. \quad (6.4.37)$$

If the connecting link is considered to be a rigid bar, then the length  $L$  is taken to be constant. In that case the displacements are related by  $d\bar{r}_B = d\bar{r}_A + d\bar{\theta}_{AB} \times \bar{r}_{B/A}$ . The work is zero because the rotational part of the displacement is perpendicular to  $\bar{e}_{B/A}$ .




Figure 6.5. Forces exerted by a massless rigid connecting link.

If the link is regarded as an elastic spring, the length  $L$  is treated as a variable. The displacements in this case are related by  $d\bar{r}_B = d\bar{r}_A + dL\bar{e}_{B/A} + d\bar{\theta}_{AB} \times \bar{r}_{B/A}$ , and the work is  $dW = FdL$ . The axial force  $F$  in a spring is known to be  $k\Delta$ , where  $\Delta$  is the change in the value of  $L$ . Thus we may compute the work done by an elastic connecting force. (It would be simpler to merely account for the work of the spring in terms of its potential energy.) The problematic case occurs when the length  $L$  is a variable that is controlled, as in the case of a servo-actuated hydraulic cylinder. The force  $F$  in this case is not known. Rather, it is a constraint force whose role is to change  $L$  in the prescribed manner. Considering both bodies to form a system will not enable us to avoid considering the unknown connective force in this situation.

The work–energy principle relates velocity parameters at two different positions. If we differentiate this expression with respect to time we obtain the *power balance law*,

$$\dot{T} + \dot{V} = \mathcal{P}^{\text{nc}}, \quad (6.4.38)$$

where  $\mathcal{P}^{\text{nc}}$  represents the power input to the body by the nonconservative forces. This is equivalent to the first law of thermodynamics for a rigid body, for it states that the rate of increase of the body’s mechanical energy equals the rate at which power is provided to the body. By definition, power is the rate at which work is done, so the work done by a force in an infinitesimal displacement  $d\bar{r}$  during an interval  $dt$  can be computed as either  $\bar{F} \cdot d\bar{r}$  or  $\mathcal{P}dt$ . It follows from Eq. (6.4.16) that

$$\mathcal{P}^{\text{nc}} = \sum_{j=1}^N \bar{F}_j^{\text{nc}} \cdot \bar{v}_j = \Sigma \bar{F}^{\text{nc}} \cdot \bar{v}_B + \oint_1^2 \Sigma \bar{M}_B^{\text{nc}} \cdot \bar{\omega}. \quad (6.4.39)$$

Some individuals use the power balance law to obtain a differential equation of motion corresponding to known energy expressions for a system, but we will see in the next chapter that there is a better way of achieving that end.

As is true for momentum principles, the work–energy principles have inherent limitations. Most profound of these is the necessity to evaluate the work done by non-conservative forces. Equation (6.4.16), which replaces any external force by an equivalent force–couple system acting at an arbitrary point, is an aid. Obviously, the motion of such a point must be known in order to evaluate the path integrals. It is equally important to know how the resultant force varies as the position of the selected point changes and how the moment depends on the angle of orientation. Also, as noted previously, the work–energy principle is not likely to be useful if any force acting on the body is a specified function of time or is velocity dependent. Even if it might seem that the work could be evaluated, doing so might be quite complicated.

Another reason why we cannot rely on momentum and energy principles comes from the fact that there usually are many position variables to evaluate. For example, we can locate the position of a rigid body with three position coordinates for its center of mass and three Eulerian angles. In general, the number of momentum and energy equations not containing unknown reactions will be fewer than the number of unknown


## 6.4 Momentum and Energy Principles

351

position and rate variables. The important thing to remember is that momentum and energy principles are derived as standard integrals of the Newton–Euler equations of motion. Thus any information we obtain from these first integrals could be obtained by solving the differential equations of motion. Although it might be more difficult to solve such equations, formulation and solution of the equations of motion is often the only useful approach.

**EXAMPLE 6.12** A disk is rolling without slipping in an unsteady manner, such that the angle  $\theta$  at which the plane of the coin is inclined is not constant. Prove that the work done by the friction and normal forces is zero.

**SOLUTION** The main objective here is to demonstrate how one can evaluate work when a force acts at a point whose motion is uncertain. Also, the result that the friction force does no work if the body rolls without slipping has important implications for our later studies. We draw a free-body diagram of the disk in which  $xyz$  is a centroidal body-fixed reference frame whose  $y$  axis at the instant in the diagram is the horizontal diameter of the disk. The contact force exerted by the ground is decomposed into three components:  $\bar{N}$  is the normal force,  $\bar{f}_t$  is the tangential friction force, which is parallel to the  $y$  axis, and  $\bar{f}_n$  is the friction force transverse to the  $y$  axis.



Free-body diagram of the disk rolling in an unsteady precession.

At first glance, the fact that the velocity of the contact point  $C$  is zero might seem to make it obvious that the contact forces do no work. Such thinking is based on the belief that, because  $\bar{v}_C = \bar{0}$ , the contact force acts at a stationary point, so it cannot do work. The difficulty with such reasoning is that the contact point is at rest for only an instant. After even an infinitesimal rotation, a different point is in contact with the ground, so one cannot assert with certainty that the forces act at a single point that does not move. We therefore transfer the forces at the contact point to the center  $G$ , whose motion is easier to understand. The normal and friction forces at point  $C$  are equivalent to a force  $\bar{F}$  and couple  $\bar{M}_G$  at point  $G$ , where  $\bar{F}$  is the resultant force and  $\bar{M}_G$  is the resultant moment about point  $G$ :

$$\bar{F} = \bar{N} + \bar{f}_t + \bar{f}_n, \quad \bar{M}_G = \bar{r}_{C/G} \times (\bar{N} + \bar{f}_t + \bar{f}_n) = \bar{r}_{C/G} \times \bar{F}.$$

In an infinitesimal time interval  $dt$ , point  $G$  displaces by  $\bar{v}_G dt$  and the disk rotates by  $\bar{\omega} dt$ . The work done by the equivalent force–couple system in this infinitesimal movement is

$$dW = \bar{F} \cdot (\bar{v}_G dt) + \bar{M}_G \cdot (\bar{\omega} dt) = [\bar{F} \cdot \bar{v}_G + (\bar{r}_{C/G} \times \bar{F}) \cdot \bar{\omega}] dt.$$

If there is slippage at the contact point, then  $\bar{v}_G$  and  $\bar{\omega}$  are kinematically unrelated, which leads to a nonzero value for  $dW$ . The absence of slippage requires that  $\bar{v}_G = \bar{\omega} \times \bar{r}_{G/C}$ . Correspondingly, we have


$$dW = [\bar{F} \cdot (\bar{\omega} \times \bar{r}_{G/C}) + (\bar{r}_{C/G} \times \bar{F}) \cdot \bar{\omega}] dt.$$

We apply the identity  $\bar{a} \cdot (\bar{b} \times \bar{c}) \equiv (\bar{c} \times \bar{a}) \cdot \bar{b}$  to the first term inside the brackets, which gives

$$dW = [(\bar{r}_{G/C} \times \bar{F}) \cdot \bar{\omega} + (\bar{r}_{C/G} \times \bar{F}) \cdot \bar{\omega}] dt \equiv 0,$$

where the result is a consequence of the fact that  $\bar{r}_{G/C} \equiv -\bar{r}_{C/G}$ . The present analysis is completely general, other than considering the ground to be stationary. Intuitively, it makes sense that no work is done when there is no relative slippage between contacting surfaces, because we associate rubbing with heat generation, which depletes the mechanical energy.

**EXAMPLE 6.13** The sphere, whose mass is  $m$ , spins relative to shaft  $AB$  at the constant rate  $\eta = 10$  rad/s. This shaft is attached to the vertical shaft  $AC$  by fork-and-clevis joint  $A$ . The vertical shaft rotates freely, with no torque applied to its rotation axis. The mass of bar  $AB$  is  $m/2$ , and the other parameters are  $R = 150$  mm and  $L = 400$  mm. Initially,  $\theta$  is held constant at  $90^\circ$  by a cable, and the precession rate is  $\Omega = 5$  rad/s. Determine the maximum and minimum values of  $\theta$  in the motion following breakage of the cable and the corresponding precession rates. Then determine the values of  $\dot{\theta}$  and  $\Omega$  at the instant when  $\theta$  is the average of these extreme angles.




Example 6.13

## 6.4 Momentum and Energy Principles

353

**SOLUTION** We see here that momentum and energy principles can be used simultaneously, thereby enabling us to analyze an intricate motion. We consider the sphere and shaft  $AB$  to form a system, because the forces exerted between them do no net work. We include the massless vertical shaft in this system to utilize our knowledge of how bearing  $C$  acts.



Free-body diagram of the sphere and its supporting shafts.

The free-body diagram of this system shows that bearing  $C$  exerts an arbitrary force and couple, except that the couple has no component about the vertical axis. This force–couple system does no work, and gravity is conservative. Therefore mechanical energy is conserved throughout the motion. We also observe that none of the forces or couples depicted in the free-body diagram exert no moment about the  $z'$  axis, which means that the system's angular momentum about the  $z'$  axis is conserved.

Both the sphere and shaft  $AB$  are in pure rotation about stationary point  $A$ , so the  $xyz$  coordinate system shown in the free-body diagram, whose  $z$  axis coincides with  $AB$ , will be convenient for describing the angular momentum of both bodies. We also define another reference frame  $x'y'z'$  that solely precesses about its  $z'$  axis.

Point  $A$  is on the  $z'$  axis, and it is the pivot point for the pure rotation of both the shaft and the sphere. We develop an expression for  $\bar{H}_A$  of each body under arbitrary conditions in order to address all aspects of the problem. The inertia properties in the Appendix and the parallel axis theorems indicate that

$$(I_{zz})_s = \frac{2}{5}mR^2 = 0.009m \equiv I_1, \quad (I_{xx})_s = (I_{yy})_s = \frac{2}{5}mR^2 + mL^2 = 0.169m \equiv I_2,$$

$$(I_{xx})_{AB} = (I_{yy})_{AB} = \frac{1}{3}\left(\frac{m}{2}\right)L^2 = 0.02667m \equiv I_3. \quad (1)$$

The angular velocity of these bodies is sum of the precession rate  $\Omega$  and the nutation rate  $\dot{\theta}$ :

$$\bar{\omega}_s = \Omega\bar{k}' + \dot{\theta}\bar{j}' - \eta\bar{k} = -\Omega\sin\theta\bar{i} + \dot{\theta}\bar{j} + (\Omega\cos\theta - \eta)\bar{k},$$

$$\bar{\omega}_{AB} = \Omega\bar{k}' + \dot{\theta}\bar{j}' = -\Omega\sin\theta\bar{i} + \dot{\theta}\bar{j} + \Omega\cos\theta\bar{k}.$$



The corresponding angular momenta and kinetic energies corresponding to pure rotation are

$$\begin{aligned} (\bar{H}_A)_s &= -I_2\Omega \sin \theta \bar{i} + I_2\dot{\theta} \bar{j} + I_1(\Omega \cos \theta - \eta) \bar{k}, \\ (\bar{H}_A)_{AB} &= -I_3\Omega \sin \theta \bar{i} + I_3\dot{\theta} \bar{j}, \\ (T)_s &= \frac{1}{2}\bar{\omega}_s \cdot (\bar{H}_A)_s = \frac{1}{2} \left[ I_2\Omega^2 (\sin \theta)^2 + I_2\dot{\theta}^2 + I_1(\Omega \cos \theta - \eta)^2 \right], \\ (T)_{AB} &= \frac{1}{2}\bar{\omega}_{AB} \cdot (\bar{H}_A)_{AB} = \frac{1}{2} \left[ I_3\Omega^2 (\sin \theta)^2 + I_3\dot{\theta}^2 \right]. \end{aligned} \quad (2)$$

Because no resultant moment about the  $z'$  axis acts on the system, the angular momentum about this axis is conserved. Point  $A$  lies on this axis, so we assert that

$$[(\bar{H}_A)_s + (\bar{H}_A)_{AB}]_2 \cdot \bar{k}' = [(\bar{H}_A)_s + (\bar{H}_A)_{AB}]_1 \cdot \bar{k}'.$$

In terms of  $xyz$  components we have  $\bar{k}' = -\sin \theta \bar{i} + \cos \theta \bar{k}$ , which in combination with Eqs. (2) gives

$$[(\bar{H}_A)_s + (\bar{H}_A)_{AB}] \cdot \bar{k}' = (I_2 + I_3) \Omega (\sin \theta)^2 + I_1 (\Omega \cos \theta - \eta) \cos \theta.$$

We take instant  $t_1$  to be the initial condition, at which it is given that  $\Omega_1 = 5$  rad/s,  $\theta_1 = 90^\circ$ , and  $\dot{\theta}_1 = 0$ . The value of  $\eta$  is specified and the inertia properties are listed in Eqs. (1). Thus, conservation of angular momentum about the vertical shaft requires that

$$(I_2 + I_3) \Omega_2 (\sin \theta_2)^2 + I_1 (\Omega_2 \cos \theta_2 - \eta) \cos \theta_2 = 0.9783m. \quad (3)$$

This is one relation between  $\Omega_2$  and  $\theta_2$  that must be satisfied. Another is obtained from conservation of energy. The only force acting on the system of rigid bodies that does work is gravity. We take the elevation of point  $A$  to be the datum, so that

$$V = mg(-L \cos \theta) + \frac{mg}{2} \left( -\frac{L}{2} \cos \theta \right).$$

Correspondingly, conservation of energy requires that

$$\begin{aligned} T_2 + V_2 &= T_1 + V_1, \\ \frac{1}{2} \left[ (I_2 + I_3) \Omega_2^2 (\sin \theta_2)^2 + (I_2 + I_3) \dot{\theta}_2^2 + I_1 (\Omega_2 \cos \theta_2 - \eta)^2 \right] \\ &- 1.25mgL \cos \theta_2 = 2.896m. \end{aligned} \quad (4)$$

Thus we have two conservation principles relating  $\Omega$  and  $\theta$  at any instant  $t_2$ .

The value of  $\theta_2$  is a maximum or minimum when  $\dot{\theta}_2 = 0$ . To determine the corresponding values of  $\theta_2$  and  $\Omega_2$ , we observe that Eq. (3) may be solved for  $\Omega_2$  as a function of  $\theta_2$ :

$$\Omega_2(\theta) = \frac{0.9783m + I_1 \eta \cos \theta_2}{(I_2 + I_3) (\sin \theta_2)^2 + I_1 \cos(\theta_2)^2}. \quad (5)$$

## 6.4 Momentum and Energy Principles

355

When this expression is substituted into Eq. (4), the result is an equation that contains only  $\theta_2$ . To determine the roots of this equation, let  $E(\theta_2, \dot{\theta}_2, \Omega_2)$  denote the left side of Eq. (4). Thus we seek the roots of a function  $F(\theta_2)$  defined symbolically by

$$F(\theta_2) \equiv \frac{1}{m} E(\theta_2, 0, \Omega_2(\theta_2)) - 2.896.$$

A plot of this function would show that it is positive at  $\theta_2 = 0$  and  $\theta_2 = \pi$  and is negative slightly below  $\theta_2 = \pi/2$ . Thus there are two roots. Numerical software readily yields these values if we use  $\theta_2 = \pi/4$  and  $\theta_2 = \pi/2$  as the initial guesses. The results, and the corresponding values of  $\Omega$  at each position, are

$$\begin{aligned} (\theta_2)_{\min} &= 36.288^\circ, & \Omega_2((\theta_2)_{\min}) &= 14.128 \text{ rad/s}, \\ (\theta_2)_{\max} &= 90^\circ, & \Omega_2((\theta_2)_{\max}) &= 5 \text{ rad/s}. \end{aligned}$$

The fact that the system does not rise higher than the angle at which it was released is not surprising. When the cable is severed, the system falls. As it does so, the value of  $\Omega$  must increase to conserve angular momentum, because the mass is situated closer to the vertical axis. The inertia of this descent carries the bar past the value of  $\theta$  at which a steady precession is possible. At the minimum  $\theta_2$  the gyroscopic rotational effects cause the system to swing upward, slowing  $\Omega$ . When the system reaches its initial elevation, it has the value of  $\Omega$  with which it was released. Because the mechanical energy is conserved, and both  $\theta$  and  $\Omega$  match the conditions when the system was released, it must be that  $\dot{\theta}$  also matches the initial value.

The second part seeks the values of  $\Omega_2$  and  $\dot{\theta}_2$  corresponding when  $\theta_2 = 0.5[(\theta_2)_{\min} + (\theta_2)_{\max}] = 63.14^\circ$ . To find  $\Omega_2$  we substitute this value of  $\theta_2$  into Eq. (3) to find

$$\Omega_2 = 6.467 \text{ rad/s} \quad \text{at} \quad \theta_2 = 63.14^\circ. \quad \triangleleft$$

Substitution of this value into Eq. (4) converts it to a single equation for  $\dot{\theta}_2$ , whose solution is

$$\dot{\theta}_2 = \pm 4.0807 \text{ rad/s} \quad \text{at} \quad \theta_2 = 63.14^\circ. \quad \triangleleft$$

The alternative sign, which results from the fact that  $\dot{\theta}_2$  is obtained by taking a square root, indicates that the magnitude of the nutation rate does not depend on whether the sphere is rising or falling. This is another consequence of the conservative nature of this system.

**EXAMPLE 6.14** The orbiting satellite is spinning about its  $z$  axis at 3 rad/s, and its velocity is 8 km/s parallel to that axis. The mass of the satellite is 5000 kg, and its inertia properties relative to its center of mass  $C$  are  $I_{xx} = 32\,000$ ,  $I_{yy} = 40\,000$ ,  $I_{zz} = 3\,600$ ,  $I_{xy} = I_{xz} = I_{yz} = 0$  kg-m<sup>2</sup>. A 2-kg meteorite, whose velocity is

## 6.4 Momentum and Energy Principles

357

These relations are general, so they may be differentiated to describe the relative velocity terms in Eq. (2). The result is

$$\bar{v}_{C/G} = -\frac{m_m}{(m_s + m_m)} \bar{v}_{m/C}, \quad \bar{v}_{m/G} = \frac{m_s}{(m_s + m_m)} \bar{v}_{m/C}.$$

Substitution of these relations into Eq. (2) simplifies that equation to

$$(\bar{H}_C)_2 + \frac{m_s m_m}{m_s + m_m} (\bar{r}_{m/C})_2 \times (\bar{v}_{m/C})_2 = (\bar{H}_C)_1 + \frac{m_s m_m}{m_s + m_m} (\bar{r}_{m/C})_1 \times (\bar{v}_{m/C})_1. \quad (3)$$

By definition,  $\bar{v}_{m/C} = \bar{v}_m - \bar{v}_C$ . The initial values of both velocities are given. To determine the final relative velocity we observe that embedding of the meteorite means that its velocity will match that of point *A* on the satellite. Therefore its final velocity is related to the velocity of point *C* by the fact that points *A* and *C* belong to the same rigid body. Also, as a consequence of taking the embedding process to be impulsive, positions are the same at the beginning and end of the impact, so we take  $(\bar{r}_{m/C})_2 = (\bar{r}_{m/C})_1 = \bar{r}_{A/C}$ . Another aspect of ignoring position changes is that the given body-fixed *xyz* coordinate system may be used to describe vectors throughout the duration of the impact. Thus we have

$$\begin{aligned} (\bar{v}_m)_1 &= -9000\bar{i} + 12000\bar{j}, \quad (\bar{v}_C)_1 = 8000\bar{k} \text{ m/s}, \quad \bar{\omega}_1 = 3\bar{k} \text{ rad/s}, \\ (\bar{v}_{m/C})_1 &= (\bar{v}_m)_1 - (\bar{v}_C)_1 = -9000\bar{i} + 12000\bar{j} - 8000\bar{k} \text{ m/s}, \\ (\bar{v}_m)_2 &= (\bar{v}_C)_2 + \bar{\omega}_2 \times \bar{r}_{A/C}, \quad (\bar{v}_{m/C})_2 = \bar{\omega}_2 \times \bar{r}_{A/C}. \end{aligned} \quad (4)$$

The initial values enables us to compute the right side of Eqs. (1) and (3), which represent the constant values of the respective momenta. For this evaluation we know  $\bar{H}_C$  from the standard relation for angular momentum in conjunction with the given centroidal inertia properties. The result is

$$\begin{aligned} (m_s + m_m) (\bar{v}_C)_2 + m_m \bar{\omega}_2 \times \bar{r}_{A/C} &= 5000 (\bar{v}_C)_1 + 2 (\bar{v}_m)_1 \\ &= (-0.018\bar{i} + 0.024\bar{j} + 40.000\bar{k}) (10^6) \text{ kg-m/s}, \end{aligned} \quad (5)$$

$$\begin{aligned} (\bar{H}_C)_2 + \frac{m_s m_m}{m_s + m_m} \bar{r}_{A/C} \times (\bar{\omega}_2 \times \bar{r}_{A/C}) &= (\bar{H}_C)_1 + \frac{10\,000}{5002} \bar{r}_{A/C} \times (\bar{v}_{m/C})_1 \\ &= 235106\bar{i} + 161935\bar{j} - 10791\bar{k} \text{ kg-m}^2/\text{s}. \end{aligned} \quad (6)$$

In view of the vectorial nature of Eqs. (5) and (6), their components give six scalar equations. The unknowns are the components of  $(\bar{v}_C)_2$  and  $\omega_2$ , but Eq. (6) does not depend on  $(\bar{v}_C)_2$ . Thus we first solve Eq. (6) for  $\bar{\omega}_2$ . To assist that solution, we evaluate the cross product term by representing  $\bar{\omega}_2$  in terms of its components,  $\omega_x$ ,  $\omega_y$ , and  $\omega_z$ :

$$\begin{aligned} \frac{m_s m_m}{m_s + m_m} \bar{r}_{A/C} \times (\bar{\omega}_2 \times \bar{r}_{A/C}) &= 164.8140\omega_x\bar{i} + (161.9352\omega_y - 21.5914\omega_z)\bar{j} \\ &\quad + (-21.5914\omega_y + 2.8788\omega_z)\bar{k} \end{aligned} \quad (7)$$

## 6.4 Momentum and Energy Principles

359

Substitution of the velocity parameters at the initial and final instants yields

$$T_1 = 1.602250 (10^{11}), \quad T_2 = 1.599373 (10^{11}) \text{ J},$$

$$W_{1 \rightarrow 2} = -2.877 (10^8) \text{ J}.$$

It will be noted that  $T_1$  and  $T_2$  are quite close, so an accurate determination of the energy change necessitated extra precision in the calculations. The fact that  $W_{1 \rightarrow 2}$  is negative means that mechanical energy is lost. It is converted to other types of energy, such as heat and plastic material deformation. Although the value of  $W_{1 \rightarrow 2}$  is small relative to the total kinetic energy, it is an enormous amount of energy transfer. These observations, in combination with the large value of  $\bar{F}_{av}$ , make it evident that this impact would be devastating for the satellite.

The momentum conservation equations, Eqs. (5) and (6), have an interesting interpretation. At the conclusion of the impulse process, the meteorite is embedded in the satellite, so they are essentially one body. The left side of the linear momentum equation, Eq. (5), is actually the product of the total mass and the velocity of the center of mass of this body. Similarly, the left side of the angular momentum equation, Eq. (6), is the product of the inertia matrix of this new body and its angular velocity. In both cases, the motion variables change because the inertial properties of the combined body are different from those of the satellite before the impact.

In closure, it is useful to observe that formulating the angular momentum with respect to the system's center of mass considerably complicated the analysis. The smallness of the meteorite's mass causes that center of mass to be nearly coincident with that of the satellite. If we had ignored the difference between these two points, it would not have been necessary to consider first moments of mass, and the general angular impulse-momentum equation would have reduced to

$$(\bar{H}_C)_2 + \bar{r}_{A/C} \times m_m (\bar{\omega}_2 \times \bar{r}_{A/C}) \approx (\bar{H}_C)_1 + \bar{r}_{A/C} \times m_m [(\bar{v}_m)_1 - (\bar{v}_C)_1],$$

which yields

$$\bar{\omega}_2 \approx 7.31232\bar{i} + 4.03206\bar{j} - 2.97343\bar{k} \text{ m/s}.$$


This value is extremely close to the value obtained from the full analysis. The average force and mechanical-energy loss would be essentially unchanged. However, the distinction between the center of mass of the system and of the satellite would have been important if  $m_s$  and  $m_m$  were of similar orders of magnitude.

### 6.4.3 Collisions of Rigid Bodies

To the naked eye a collision seems to cause the velocity of a body to change instantaneously, which is a characteristic of an impulsive force. This is a fundamental feature of the model for the action of impulsive forces. In many situations, such as the study of crash dynamics for vehicles, deformation effects are of primary importance, which obviates analysis by use of rigid-body concepts. In other situations, such as the collision of

billiard balls, the presence of deformation is not apparent. Although deformation is always important, we consider here a concept based on empirical observations that makes it possible to adapt the concepts of rigid-body dynamics. The scope of the treatment is limited to collisions that leave the bodies essentially unchanged, which is possible if the relative speed of the colliding bodies is sufficiently low.

We restrict our attention to cases in which there is an identifiable plane of contact for each body that is tangent to each body at a single point. (For planar motion, this would correspond to contact along a line perpendicular to the plane.) In the strictest sense a corner is marked by a slope discontinuity, so no unique tangent point exists at such a location. However, this ambiguity is removed if we consider the corner to be slightly rounded. We define a coordinate system  $xyz$  whose origin is the point at which the bodies are in contact and whose  $yz$  plane coincides with the contact point. The configuration is depicted in Fig. 6.6, where points  $A$  and  $B$  are the centers of mass of bodies 1 and 2, and points  $C1$  and  $C2$  mark the contact point on the respective body.



**Figure 6.6.** Collision of rigid bodies. Points  $A$  and  $B$  are the centers of mass, and points  $C1$  and  $C2$  are the respective contact points.

The bodies in Fig. 6.6(a) are free of external restrictions on their movement, so the only force to consider during the impact is the one exerted between the bodies at the contact point, as shown in the free-body diagrams of Fig. 6.6(b). We begin with the idealization that the contacting surfaces are very smooth, so the impact force  $\bar{F}$  on body  $A$  acts in the positive  $\bar{i}$  direction, whereas it acts on body  $B$  in the negative  $\bar{i}$  direction. In addition to requiring determination of the final velocities, we need to account for the angular motion of each body. Thus the initial condition consists of the initial velocities  $(\bar{v}_A)_0$  and  $(\bar{v}_B)_0$  of the centers of mass, as well as the angular velocities  $(\bar{\omega}_1)_0$  and  $(\bar{\omega}_2)_0$ . The quantities to be determined are these variables at the termination of the impact, whose values are denoted with the subscript  $f$ , and the impulse of the contact force.

The impulsive force model is appropriate, so we represent the unknown impulse as the product  $F\Delta t$  of the average force magnitude and the duration of the impact. An important aspect of the impulsive force model is that the brevity of the contact interval makes it permissible to consider all points to have a constant position during the impact. Hence we can consider  $xyz$  to maintain its orientation, and the contact points on each body are indistinguishable with regard to their position. Thus we may write the position vector from each center of mass to the respective contact point simply as  $\bar{r}_{C/A}$  and  $\bar{r}_{C/B}$ .

Equations that are available to determine the unknown linear and angular velocity parameters come from both the linear and angular impulse–momentum principles. We formulate these relative to each body’s center of mass because doing so decouples the

## 6.4 Momentum and Energy Principles

361

linear and angular velocities in the momentum principles. Thus we have four vector equations representing the kinetics of the system:

$$\begin{aligned} m_1 (\bar{v}_A)_f &= m_1 (\bar{v}_A)_0 + F \Delta t \bar{i}, \\ m_2 (\bar{v}_B)_f &= m_2 (\bar{v}_B)_0 - F \Delta t \bar{i}, \\ (\bar{H}_A)_f &= (\bar{H}_A)_0 + \bar{r}_{C/A} \times (F \Delta t \bar{i}), \\ (\bar{H}_B)_f &= (\bar{H}_B)_0 + \bar{r}_{C/B} \times (-F \Delta t \bar{i}). \end{aligned} \quad (6.4.40)$$

The final angular momenta contain the components of the respective angular velocities. Thus, if the value of  $F \Delta t$  were known, it would be a simple matter to determine the unknown velocity parameters. It follows that we need one more scalar equation.

A proper analysis would examine the manner in which each body deforms, but doing so is quite challenging. Instead, we introduce a concept that allows for deformation in the vicinity of the point of contact while retaining the elements of rigid-body dynamics. The deformation of the surfaces that is produced by the large collision force may be considered to cause each body's surface to move relative to its nominal position. Thus, in the time interval following the initial contact  $t_0$  until the instant  $t_f$  immediately before the bodies separate, the velocity of the contact points  $C1$  and  $C2$  are generally not describable by rigid-body kinematics. However, there is one exceptional instant when this is not true. At an instant that we denote as  $t_{\max}$  the local deformation has reached a maximum. This means that the inward displacement of each contact point relative to the undeformed state has reached its largest value. It follows that the velocity of the contact points at this instant relative to the nominal rigid-body configuration is zero. Hence, at this instant, each contact point's velocity is describable by rigid-body kinematics in terms of the center-of-mass velocities  $(\bar{v}_A)_{\max}$  and  $(\bar{v}_B)_{\max}$  and angular velocities  $(\bar{\omega}_A)_{\max}$  and  $(\bar{\omega}_B)_{\max}$ . It follows that, at  $t = t_0$ ,  $t_{\max}$ , or  $t_f$ , the contact point velocities are given by

$$\bar{v}_{C1} = \bar{v}_A + \bar{\omega}_1 \times \bar{r}_{C/A}, \quad \bar{v}_{C2} = \bar{v}_B + \bar{\omega}_2 \times \bar{r}_{C/B}. \quad (6.4.41)$$

The values of  $(\bar{v}_{C1})_0$  and  $(\bar{v}_{C2})_0$  are set by the initial conditions, whereas  $(\bar{v}_{C1})_f$  and  $(\bar{v}_{C2})_f$  are a consequence of the system's kinetics. However, at  $t_{\max}$  the contact point velocities are also related by

$$(\bar{v}_{C1})_{\max} \cdot \bar{i} = (\bar{v}_{C2})_{\max} \cdot \bar{i}. \quad (6.4.42)$$

The importance of the instant of maximum deformation is that it is featured in the definition of the *coefficient of restitution*,  $\varepsilon$ . This empirical parameter may be considered to be the result of observation of many collisions in which the bodies do not display significant permanent deformation. It is the ratio of the impulse of the contact force during the restitution interval  $t_{\max} < t < t_f$  to the impulse in the deformation interval  $t_0 < t < t_{\max}$ . In other words,

$$\varepsilon = \frac{\int_{t_{\max}}^{t_f} F dt}{\int_{t_0}^{t_{\max}} F dt}. \quad (6.4.43)$$

If the collision is not energetic, then the value of  $\varepsilon$  is a number between zero and unity that depends on the materials, shape, and size of the body. (An energetic collision releases an internal energy source, such as a spring with a trigger release.)

Our task now is to convert this definition of  $\varepsilon$  to one that features the same kinematical variables as those appearing in Eqs. (6.4.40). Such a derivation for the case of an arbitrary spatial motion is complicated by the fact that each angular momentum component contains all angular velocity components if each body has an arbitrary shape. We therefore consider the case of bodies in planar motion. The result will be a form that is applicable for spatial motion.

For planar motion, we set  $\bar{H}_A = I_A \omega_1 \bar{k}$  and  $\bar{H}_B = I_B \omega_2 \bar{k}$  in Eqs. (6.4.40). Also, because the centers of mass and the contact point lie in the  $xy$  plane for planar motion, the  $\bar{k}$  components of the cross products in the moments of  $\bar{F}$  about points  $A$  and  $B$  can be written as

$$\bar{k} \cdot (\bar{r} \times F\bar{i}) \equiv F\bar{r} \cdot (\bar{i} \times \bar{k}) = -F\bar{r} \cdot \bar{j} \quad \text{if} \quad \bar{r} \cdot \bar{k} = 0. \quad (6.4.44)$$

We use this relation to break each of Eqs. (6.4.40) into portions covering the deformation interval  $t_0 < t < t_{\max}$  and the restitution period  $t_{\max} < t < t_f$ . Doing so for body  $A$  yields

$$\begin{aligned} m_1 (\bar{v}_A)_{\max} &= m_1 (\bar{v}_A)_0 + \int_{t_0}^{t_{\max}} (F\bar{i}) dt, \\ m_1 (\bar{v}_A)_f &= m_1 (\bar{v}_A)_{\max} + \int_{t_{\max}}^{t_f} (F\bar{i}) dt, \\ I_A (\omega_1)_{\max} \bar{k} &= I_A (\omega_1)_0 \bar{k} + \bar{r}_{C/A} \times \int_{t_0}^{t_{\max}} (F\bar{i}) dt, \\ I_A (\omega_1)_f \bar{k} &= I_A (\omega_1)_{\max} \bar{k} + \bar{r}_{C/A} \times \int_{t_{\max}}^{t_f} (F\bar{i}) dt. \end{aligned} \quad (6.4.45)$$

Notice that the position vector was brought outside the integral in both angular impulses because positions are taken to not change during the short interval of the impulsive action. We take the  $\bar{i}$  component of the linear momentum equations and the  $\bar{k}$  component of the angular momentum equations and apply Eq. (6.4.44) to the latter, with the result that

$$\begin{aligned} \int_{t_0}^{t_{\max}} F dt &= m_1 [(\bar{v}_A)_{\max} \cdot \bar{i} - (\bar{v}_A)_0 \cdot \bar{i}], \\ \int_{t_{\max}}^{t_f} F dt &= m_1 [(\bar{v}_A)_f \cdot \bar{i} - (\bar{v}_A)_{\max} \cdot \bar{i}], \\ (\bar{r}_{C/A} \cdot \bar{j}) \int_{t_0}^{t_{\max}} F dt &= -I_A [(\omega_1)_{\max} - (\omega_1)_0], \\ (\bar{r}_{C/A} \cdot \bar{j}) \int_{t_0}^{t_{\max}} (F\bar{i}) dt &= -I_A [(\omega_1)_f - (\omega_1)_{\max}]. \end{aligned} \quad (6.4.46)$$

We ratio the second equation to the first and the fourth to the third. In view of Eq. (6.4.43), each ratio is  $\varepsilon$ . The result of clearing denominators is

$$\begin{aligned} [(\bar{v}_A)_f \cdot \bar{i} - (\bar{v}_A)_{\max} \cdot \bar{i}] &= \varepsilon [(\bar{v}_A)_{\max} \cdot \bar{i} - (\bar{v}_A)_0 \cdot \bar{i}], \\ [(\omega_1)_f - (\omega_1)_{\max}] &= \varepsilon [(\omega_1)_{\max} - (\omega_1)_0]. \end{aligned} \quad (6.4.47)$$

## 6.4 Momentum and Energy Principles

363

Comparable equations result from following the same procedures for the momenta of body  $B$ :

$$\begin{aligned} [(\bar{v}_B)_f \cdot \bar{i} - (\bar{v}_B)_{\max} \cdot \bar{i}] &= \varepsilon [(\bar{v}_B)_{\max} \cdot \bar{i} - (\bar{v}_B)_0 \cdot \bar{i}], \\ [(\omega_2)_f - (\omega_2)_{\max}] &= \varepsilon [(\omega_2)_{\max} - (\omega_2)_0]. \end{aligned} \quad (6.4.48)$$

Neither set of equations is quite in the form we would like because they contain the linear and angular velocities at the instant  $t_{\max}$ , which are not parameters we need to know. We remedy this by recalling that the normal velocity components match at  $t_{\max}$ , as described in Eq. (6.4.42). We find an expression for these velocity components by taking the dot product of the velocities in Eqs. (6.4.41), which gives

$$\begin{aligned} \bar{v}_{C1} \cdot \bar{i} &= \bar{v}_A \cdot \bar{i} + (\omega_1 \bar{k} \times \bar{r}_{C/A}) \cdot \bar{i} \equiv \bar{v}_A \cdot \bar{i} - \omega_1 (\bar{r}_{C/A} \cdot \bar{j}), \\ \bar{v}_{C2} \cdot \bar{i} &= \bar{v}_B \cdot \bar{i} + (\omega_2 \bar{k} \times \bar{r}_{C/B}) \cdot \bar{i} \equiv \bar{v}_B \cdot \bar{i} - \omega_2 (\bar{r}_{C/B} \cdot \bar{j}). \end{aligned} \quad (6.4.49)$$

In light of the form of this relation, we multiply the second of Eqs. (6.4.47) by  $\bar{r}_{C/A} \cdot \bar{j}$  and subtract it from the first of those equations. We also apply similar operations to Eqs. (6.4.48) for body  $B$ . The result is

$$\begin{aligned} [(\bar{v}_{C1})_f \cdot \bar{i} - (\bar{v}_{C1})_{\max} \cdot \bar{i}] &= \varepsilon [(\bar{v}_{C1})_{\max} \cdot \bar{i} - (\bar{v}_{C1})_0 \cdot \bar{i}], \\ [(\bar{v}_{C2})_f \cdot \bar{i} - (\bar{v}_{C2})_{\max} \cdot \bar{i}] &= \varepsilon [(\bar{v}_{C2})_{\max} \cdot \bar{i} - (\bar{v}_{C2})_0 \cdot \bar{i}]. \end{aligned} \quad (6.4.50)$$

In view of Eqs. (6.4.48), the velocity components at  $t_{\max}$  are identical, so subtraction of the first of the preceding equations from the second leads to

$$[(\bar{v}_{C2})_f \cdot \bar{i} - (\bar{v}_{C1})_f \cdot \bar{i}] = \varepsilon [(\bar{v}_{C1})_0 \cdot \bar{i} - (\bar{v}_{C2})_0 \cdot \bar{i}]. \quad (6.4.51)$$

This is the additional equation to be used in conjunction with Eqs. (6.4.40) to evaluate the velocities with which the bodies rebound. Although it was derived by considering planar motion, it is equally applicable to spatial motion. Equation (6.4.51) is useful for an experiment in which the velocities are measured and the value of  $\varepsilon$  is computed. When we need to determine how bodies move after they collide, it will be necessary to eliminate the contact velocities in favor of the center-of-mass velocities and the angular velocities. Equations (6.4.41) are available for that purpose. Evaluation of the  $\bar{i}$  component of the cross-product term is somewhat simplified by the identity that  $(\bar{\omega} \times \bar{r}) \cdot \bar{i} = \bar{\omega} \cdot (\bar{r} \times \bar{i})$ . This leads to

$$\begin{aligned} [(\bar{v}_B)_f \cdot \bar{i} - (\bar{v}_A)_f \cdot \bar{i}] &+ (\bar{\omega}_2)_f \cdot (\bar{r}_{C/B} \times \bar{i}) - (\bar{\omega}_1)_f \cdot (\bar{r}_{C/A} \times \bar{i}) \\ &= \varepsilon \left\{ [(\bar{v}_A)_0 \cdot \bar{i} - (\bar{v}_B)_0 \cdot \bar{i}] + (\bar{\omega}_1)_f \cdot (\bar{r}_{C/A} \times \bar{i}) - (\bar{\omega}_2)_f \cdot (\bar{r}_{C/B} \times \bar{i}) \right\}. \end{aligned} \quad (6.4.52)$$


Note that this form is convenient for spatial motion, but planar motion problems are readily formulated by use of Eq. (6.4.51).

This is a scalar equation. For an arbitrary spatial motion, decomposing Eqs. (6.4.40) into their components leads to 12 additional scalar equations. The 13 unknowns are the three components of each center-of-mass velocity, the three components of each angular



## 6.4 Momentum and Energy Principles

365



**Figure 6.7.** An example of a collision in which a body is constrained. The constraint force  $N$  and the collision force  $F$  are impulsive.

the number of force impulses that are unknown. Suppose  $(\bar{v}_A)_0$  were given. Then the unknowns to be determined in this planar situation are the two components of  $(\bar{v}_A)_f$ , the value of  $(v_B)_f$ ,  $F$ , and  $N$ . The angular velocity of the sphere is irrelevant because this is a central impact for that body. The five available equations are the linear impulse–momentum equations for the sphere and the wedge, and the relation between velocity components in the  $x$  direction associated with the coefficient of restitution. (A minor shortcut is to formulate only the horizontal component of the impulse–momentum equation for the wedge, which would avoid the occurrence of  $N$  in the equations to solve.)

A bar that executes a pure rotation is a common configuration featuring constrained motion. The reactions at the pivot must act impulsively to prevent that point from moving. These unknown reactions can be avoided in the formulation if the angular impulse–momentum equation is formulated about the fixed pivot. If the impulse associated with each component of the pivot reaction is required, such information can be extracted from the linear impulse–momentum after the rebound velocity of the center of mass has been determined.

Examination of the collision of unconstrained bodies reveals a general weakness of this model of collisions. The contact force is taken to act solely in the normal direction. Consequently the linear impulse–momentum equations indicate that the velocity of each body’s center of mass tangent to the contact plane is unaltered by the impact. This does not fit our observation of certain situations in which the contact surfaces are rough, for example, when a tennis ball touches the ground. This shortcoming can be remedied by use of a standard friction model. At the initial contact the contact points have different tangential velocities, which means that a sliding friction model should be appropriate. The magnitude of the friction force in that model is proportional to the normal force magnitude  $F$ , and the latter acts impulsively.

Consequently, we can insert a tangential force  $f = \mu_k F$  in each free-body diagram. The direction of this force would be opposite the initial tangential velocity of one surface relative to the other at the initial instant  $t_0$ . Thus we can say that the force on body  $A$  would be


$$\bar{f} = -\mu_k F \frac{(\bar{v}_{CA})_0 \cdot \bar{i} - (\bar{v}_{CB})_0 \cdot \bar{i}}{|(\bar{v}_{CA})_0 \cdot \bar{i} - (\bar{v}_{CB})_0 \cdot \bar{i}|}. \quad (6.4.53)$$

The friction force applied to body  $B$  would be oppositely directed. The validity of the coefficient of restitution is unaltered by the friction force, so Eq. (6.4.52) still applies.

The impulse–momentum equations would be modified by replacing the contact force  $F\bar{i}$  acting on body  $A$  with  $F\bar{i} + \bar{f}$ , whereas the force acting on body  $B$  would be changed from  $-F\bar{i}$  to  $-F\bar{i} - \bar{f}$ . No new variables are introduced by these modifications, so the solvability of the equations is not altered.


This preceding model of friction effects has limitations. For example, it is hypothetically possible that the analysis will lead to a rebound in which the tangential relative velocity at the contact points is reversed from its initial sense, which would indicate that the sense of  $\bar{f}$  reverses at some intermediate instant between  $t_0$  and  $t_f$ . As explained in Example 6.17, using this simple friction model would require determination of the instant at which slipping ceases, which is not part of the analysis.

**EXAMPLE 6.15** The bar, whose mass is  $m_1$  and whose moment of inertia about its pivot is  $I_A$ , is at rest in the vertical position when it is obliquely struck by the ball, whose mass is  $m_2$ . The coefficient of restitution is an unspecified value. Determine the angular velocity of the bar and the velocity of the ball immediately after the collision. Also determine the impulse of the pivot force during the collision. Is there a distance  $h$  for the impact that minimizes this impulse?



Example 6.15

**SOLUTION** This example addresses the role of constraint forces during a collision. In addition to the impact force, which is horizontal, the free-body diagram shows the forces exerted by the pin to prevent movement of point  $A$ . The  $x$  axis is defined to be normal to the contact plane, and the origin has been placed at the pivot point  $A$ , which is an allowable point for summing moments, because doing so will eliminate the reaction impulses from the angular momentum equation.



Individual free-body diagrams of the bar and the ball.

## 6.4 Momentum and Energy Principles

367

We carry out the analysis by considering the ball to be a particle, which means that we need not consider its rotation. Because the bar executes a pure rotation about point  $A$ , the rebound velocities of the center of mass  $G$  and of the impact point  $C$  are kinematically related to the angular velocity of the bar at the conclusion of the impact. The duration of the impact is brief, so we may use the initial position of points to characterize this relationship. It is convenient to consider a clockwise rotation in rebound to be positive, so we have

$$\begin{aligned}(\bar{v}_G)_f &= (-\omega_f \bar{k}) \times \bar{r}_{G/A} = -\omega_f \frac{L}{2} \bar{i}, \\ (\bar{v}_C)_f &= (-\omega_f \bar{k}) \times \bar{r}_{C/A} = -\omega_f h \bar{i}.\end{aligned}\tag{1}$$

We now turn to the momentum equations. It is evident that the linear momentum equations for the bar will feature  $A_x$  and  $A_y$ . As noted at the outset, these forces will not appear in the equation describing the angular momentum of the bar about the pivot point. We therefore delay consideration of the bar's linear momentum. As we did for the kinematical equations, we consider the bar's position to not change during the impact, so equating the bar's angular momentum change about point  $A$  to the corresponding angular impulse gives

$$I_A (-\omega_f) = - (F \Delta t) h. \tag{2}$$

The linear impulse-momentum equations for the ball relate the ball's rebound velocity to the impact force. It is helpful to write these equations in component form:

$$m_2 (\bar{v}_2)_f \cdot \bar{i} = m_2 (-v \cos \theta) + (F \Delta t), \tag{3a}$$

$$m_2 (\bar{v}_2)_f \cdot \bar{j} = m_2 v \cos \theta. \tag{3b}$$

The second of the preceding equations shows that the velocity of the ball parallel to the plane of contact is unaltered by the collision. Three unknowns,  $\omega_f$ ,  $(\bar{v}_2)_f \cdot \bar{i}$ , and  $F \Delta t$ , appear in Eqs. (2) and (3a). The third equation is obtained from the coefficient of restitution. Application of Eq. (6.4.51) in the present case gives

$$(\bar{v}_C)_f \cdot \bar{i} - (\bar{v}_2)_f \cdot \bar{i} = \varepsilon [(-v \cos \theta) - 0].$$

Substitution of the second of Eqs. (1) into this relation converts it to

$$-\omega_f h - (\bar{v}_2)_f \cdot \bar{i} = \varepsilon [(-v \cos \theta) - 0]. \tag{4}$$

The simultaneous solution of Eqs. (2), (3a), and (4) yields

$$\begin{aligned}\omega_f &= (\varepsilon + 1) \frac{m_2 h^2}{I_A + m_2 h^2} \left( \frac{v}{h} \cos \theta \right), \quad F \Delta t = \frac{I_A}{h} \omega_f, \\ (\bar{v}_2)_f \cdot \bar{i} &= \frac{\varepsilon I_A - m_2 h^2}{I_A + m_2 h^2} (v \cos \theta).\end{aligned}\tag{5}$$

Now that the rebound velocity of the bar is known, we may evaluate the impulse of the reaction forces. We use Eqs. (1) to describe the velocity of the center

of mass when we form the linear impulse–momentum equation for the bar, whose component form is

$$\begin{aligned} m_1 (\bar{v}_G)_f \cdot \bar{i} &= m_1 \left( -\frac{L}{2} \omega_f \right) = A_x \Delta t - F \Delta t, \\ m_1 (\bar{v}_G)_f \cdot \bar{j} &= 0 = 0 + A_y \Delta t. \end{aligned}$$

The result is

$$A_x \Delta t = \left( \frac{I_A}{h} - \frac{m_1 L}{2} \right) \omega_f, \quad A_y \Delta t = 0. \quad \triangleleft$$

Several aspects of these results are interesting. The vertical reaction impulse is negligible because the impact force acts horizontally. The horizontal reaction impulse also is negligible if  $h = 2I_A/m_1 L = 2\kappa^2/L$ , where  $\kappa$  is the radius of gyration. For the case of a bar whose cross section is uniform,  $h = 2L/3$ . This distance is called the *center of percussion*, which previously was mentioned in Example 6.11. When a bar is struck at this distance from an end, it will execute a pure rotation about that end, even if it is unsupported.  $\triangleleft$

Another interesting aspect of the results is the change in mechanical energy. The initial kinetic energy is solely stored in the ball,  $T_0 = m_2 v^2/2$ . The kinetic energy after the collision is found to be

$$T_f = \frac{1}{2} m_2 (\bar{v}_2)_f \cdot (\bar{v}_2)_f + \frac{1}{2} I_A \omega_f^2 = \frac{1}{2} m_2 v^2 \left[ \frac{I_A \varepsilon^2 + m_2 h^2}{I_A + m_2 h^2} (\cos \theta)^2 + (\sin \theta)^2 \right].$$

Thus the energy lost is

$$\Delta T = T_0 - T_f = T_0 (1 - \varepsilon^2) (\cos \theta)^2 \left( \frac{I_A}{I_A + m_2 h^2} \right).$$

Therefore, except for this idealized condition of a perfectly elastic impact,  $\varepsilon = 1$ , mechanical energy is dissipated as a result of the collision. This behavior is generally true. Because the amount of energy that is dissipated can be determined only after the collision dynamics has been evaluated, one should not use the work–energy principle to analyze collisions. Another interesting feature of the expression for  $\Delta T$  is the  $(\cos \theta)^2$  factor, which shows that the energy loss decreases significantly if the ball arrives obliquely. We refer to such an impact as a “grazing blow.”

**EXAMPLE 6.16** Suppose the square plate in Example 6.11 is struck at corner  $A$  by a 500-g ball, rather than a hammer. The impact velocity of the ball is  $v$  normal to the plate’s surface, and the plate is initially at rest. The coefficient of restitution is  $\varepsilon = 0.6$ . In Example 6.11 the impulsive force had an average value of 5000 N over a 4-ms duration. Determine the initial speed  $v$  of the ball bearing that will generate an impact equal to the hammer blow. For this initial speed, determine the angular

In view of  $(\bar{v}_G)_f$  in Eqs. (1), the linear impulse–momentum principle for the plate gives

$$\begin{aligned} 10 [0.06\omega_z\bar{i} + 0.18\omega_z\bar{j} + (-0.06\omega_x - 0.18\omega_y)\bar{k}] \\ = [A_x\bar{i} + A_y\bar{j} + (A_z + 5000)\bar{k}] (0.004). \end{aligned} \quad (4)$$

The linear impulse–momentum equation for the ball is

$$0.5 (\bar{v}_2)_f = 0.5 (v\bar{k}) - (5000\bar{k}) 0.004. \quad (5)$$

The last of the basic equations is the one featuring the coefficient of restitution. Here  $\bar{k}$  is the normal to the contact plane, so we have

$$(\bar{v}_2)_f \cdot \bar{k} - (\bar{v}_C)_f \cdot \bar{k} = \varepsilon [0 - v].$$

Substitution of Eq. (2) gives

$$(\bar{v}_2)_f \cdot \bar{k} - (0.12\omega_x - 0.36\omega_y) = -0.6v. \quad (6)$$

We find the final angular velocity components and normal velocity of the ball by simultaneously solving Eqs. (3), which yield

$$\omega_x = 35.90, \quad \omega_y = -25.64 \text{ rad/s.}$$

These values are substituted into Eq. (6), which is solved simultaneously with the  $\bar{k}$  component of Eq. (5) to find

$$(\bar{v}_2)_f \cdot \bar{k} = -16.54, \quad v = 23.46 \text{ m/s.} \quad \triangleleft$$

According to Eq. (5), there is no change in the velocity components parallel to the plate because the contact force does not act in those directions, so the rebound velocity of the ball is

$$(\bar{v}_2)_f = -16.54\bar{k} \text{ m/s.} \quad \triangleleft$$

Because  $F$  here is stated to match the impulsive force in Example 6.11, the average reaction forces, which are obtained from Eq. (4), are the same as those of the previous results:


$$A_x = A_y = 0, \quad A_z = 1153 \text{ N.} \quad \triangleleft$$

When one considers that the impact was generated by a 0.5-kg ball moving at an initial speed of almost 24 m/s, these average reaction forces are not exceptionally large. However, these are average values that vary inversely to the time duration, corresponding to a fixed impulse.

## 6.4 Momentum and Energy Principles


371

**EXAMPLE 6.17** A ball obliquely hits the ground with speed  $v$  at angle of elevation  $\theta$ . The coefficient of restitution is an unspecified value  $\varepsilon$ . The rotation rate at the instant of impact is  $\omega_0$  about the horizontal diameter that is perpendicular to the initial velocity. The ground is rough, with the effect of friction described by an impulsive friction force corresponding to coefficient of sliding friction  $\mu$ . Derive an expression for the velocity with which the ball bounces off the ground in terms of  $v$ ,  $\omega$ ,  $\varepsilon$ ,  $\mu$ ,  $\theta$ , and the ball's radius  $R$ . Compare the result with the rebound velocity that would result if the surface were smooth, so that  $\mu = 0$ .



Example 6.17

**SOLUTION** This example explores how one can account for friction along the surface where bodies collide. We consider the ground to be stationary, so only a free-body diagram of the ball is required. In that diagram the friction force is merely labeled as  $f$ , in the sense it would act if the contact point on the ball were moving to the left. The only impulsive forces are generated at the contact plane because the ball's motion is unconstrained.



Free-body diagram of the spinning ball showing the impulsive contact forces.

The impulse-momentum equations are

$$\begin{aligned} m(\bar{v}_G)_f \cdot \bar{i} &= mv \cos \theta - f \Delta t, \\ m(\bar{v}_G)_f \cdot \bar{j} &= m(-v \sin \theta) + F \Delta t, \\ I_G(-\omega_f) &= I_G(-\omega_0) - f R \Delta t. \end{aligned} \quad (1)$$

The velocity of the contact point is

$$\bar{v}_C = \bar{v}_G + \omega(-\bar{k}) \times (-R\bar{j}) = \bar{v}_G - \omega R\bar{i}, \quad (2)$$


so the normal velocity at the point of contact is  $\bar{v}_G \cdot \bar{j}$ . Thus the proportionality of normal velocity components imposed by the coefficient of restitution gives

$$(\bar{v}_G)_f \cdot \bar{j} = \varepsilon [0 - (-v \sin \theta)]. \quad (3)$$

The unknown variables in Eqs. (1) and (2) are the components of  $(\bar{v}_G)_f$ , the normal impulse  $F \Delta t$ , the friction impulse  $f \Delta t$ , and the final rotation rate  $\omega_f$ .


### HOMEWORK PROBLEMS

**EXERCISE 6.1** The cable holds the angle  $\theta$  for the bar constant as the vertical shaft rotates at the constant speed  $\Omega$ . Determine the value of  $\Omega$  for which the tension in the cable is twice as large as it would be if  $\Omega$  were zero.




Exercise 6.1

**EXERCISE 6.2** Torque  $\Gamma$  causes the horizontal shaft to rotate. The triangular plate's thickness is negligible, as is the mass of the shaft. A torque  $\Gamma$  is applied to the shaft, thereby inducing a time-dependent rotation rate  $\Omega$ . The system was at rest at  $t = 0$ . Derive expressions for  $\Omega$  and the bearing reactions as functions of time. The influence of gravity may be ignored.




Exercise 6.2

**EXERCISE 6.3** The vertical shaft rotates at the constant speed  $\Omega$ . Determine the forces, including those required to balance the effect of gravity, exerted by the bearings on this shaft. The shaft and the bar have equal mass  $m$ .



Exercise 6.3

**EXERCISE 6.4** Bar  $AB$  is pinned to the T-bar and rubs along the ground. The coefficient of friction is  $\mu$ . A torque acting about the vertical axis imposes a constant rotation rate  $\Omega$ . Determine the contact forces exerted on bar  $AB$  by the ground and the force–couple system exerted on the bar at pin  $A$ . (It may be assumed that the friction force acts perpendicular to the vertical plane depicted in the sketch.)




Exercise 6.4

# Homework Problems


375

**EXERCISE 6.5** The rectangular plate is welded to the vertical shaft, whose mass is negligible. An unsteady precession rate  $\Omega$  is generated by the application of torque  $M$  to the shaft. Derive expressions for  $M$  and the total reactions exerted by bearings  $A$  and  $B$ , including the influence of gravity, as functions of the instantaneous values of  $\Omega$  and  $\dot{\Omega}$ .




Exercise 6.5

**EXERCISE 6.6** Two identical disks having radius  $R$  and mass  $m$  are joined by a rigid bar whose ends are welded at diametrically opposite points on the perimeter of each wheel. The mass of the rod also is  $m$ . The disks roll without slipping at constant speed  $v$ . Prove that such a motion is consistent with the equations of motion, and also determine the corresponding friction and normal forces as a function of the angle  $\theta$  through which the assembly has rotated. *Hint:* Define a body-fixed coordinate system such that the  $y$  axis aligns with the disks' center line and the  $z$  axis is perpendicular to the bar.




Exercise 6.6

**EXERCISE 6.7** The cylinder is mounted on a gimbal that rotates about the horizontal axis at constant rate  $\Omega$  induced by a torque  $\Gamma$  that acts about shaft  $AB$ . Derive the differential equation governing the angle  $\beta$  between the bar and the horizontal axis, and also derive an expression for  $\Gamma$ .



Exercise 6.7


**EXERCISE 6.8** The torque  $M$  acting on the gimbal of the gyroscopic turn indicator is exerted by a torsional spring, so  $M = -k\beta$ . The precession rate  $\Omega_2$  is a specified function of time, and the spin rate  $\Omega_1$  is held constant by a servomotor. Let  $I_1$  denote the moment of inertia of the flywheel about axis  $AB$ , and let  $I_2$  be the centroidal moment of inertia perpendicular to axis  $AB$ . Derive the differential equation of motion for  $\beta$ .



Exercise 6.8




**EXERCISE 6.9** Precession angle  $\psi$  of the electric fan is unsteady, and the spin rate  $\Omega$  is constant at 1800 rev/min. The fan blade assembly has a mass of 10 kg, and its radii of gyration are 200 mm about the spin axis and 150 mm about a centroidal axis perpendicular to the spin axis. This assembly may be considered to be axisymmetric. Determine the dynamic force–couple system that must be exerted on the motor housing at pin  $A$  to sustain this motion.




Exercise 6.9

**EXERCISE 6.10** Pin  $A$  supporting the 50-kg thin bar has ideal properties. The angle  $\theta$  is adjusted by pulling the cable inward at the constant rate  $w = 20$  m/s. The precession rate is constant at  $\Omega = 5$  rad/s. Determine the tensile force in the cable when  $\theta = 35^\circ$ . The bar's length is  $L = 600$  mm.




Exercise 6.10

**EXERCISE 6.11** The thin disk is mounted on shaft  $AB$ , which coincides with a diametral line. Servomotors sustain the rotation rates  $\Omega_1$  about this axis and  $\Omega_2$  about the vertical are maintained at constant values by servomotors that exert torques about the respective shafts. Derive expressions for the dynamic reactions at bearings  $A$  and  $B$  and the required moment about shaft  $AB$  as functions of  $\theta$ . It may be assumed that the bearings exert forces, but not couples, and that only the mass of the disk is significant.



Exercise 6.11

**EXERCISE 6.12** The uniform bar is pinned to the vertical shaft  $AB$ . A servomotor applies torque  $\Gamma$  about the axis of pin  $C$ , with the result that the angle  $\theta$  oscillates periodically,  $\theta = \pi/2 \sin(\mu t)$  rad. Torque  $M$  applied to the vertical shaft maintains the rotation rate about the vertical shaft at the constant value  $\Omega$ . The mass of the bar is  $m$  and the mass of the shaft is negligible. For the instants when  $\theta = \pi/2$  and  $\theta = \pi/3$ , derive expressions for  $M$  and  $\Gamma$ .




Exercise 6.12

### Homework Problems


377

**EXERCISE 6.13** The disk of mass  $m$  is obliquely mounted on shaft  $AB$ , such that the angle between the center line of the disk and the shaft always is  $\theta$ . The disk spins freely relative to this shaft at the unknown angular rate  $\dot{\phi}$ . The illustrated position, in which the diametral line perpendicular to the shaft is horizontal, corresponds to  $\phi = 0$ . A torque  $\Gamma$  acting about the vertical shaft maintains the precession rate at the constant value  $\Omega$ . Derive the differential equation of motion governing  $\phi$  and an expression for  $\Gamma$  in terms of  $\phi$ . Only the mass of the disk is significant.




Exercise 6.13

**EXERCISE 6.14** Bar  $BC$  is pivoted from the end of the T-bar. A torque  $\Gamma$  applied to the vertical shaft is such that the system rotates about the vertical axis at the constant speed  $\Omega$ . Derive the differential equation of motion for the angle of elevation  $\theta$ .




Exercise 6.14

**EXERCISE 6.15** Collar  $C$  is attached to the vertical shaft by a fork-and-clevis, so the angle of inclination  $\theta$  of bar  $AB$  is arbitrary. Because this bar slides through the collar, the distance  $x$  from the pivot point to the center of mass is variable, but it may be assumed that the bar does not spin about its own axis. The vertical shaft rotates at the constant rate  $\dot{\psi}$ . Determine the differential equations of motion for  $x$  and  $\theta$ , as well as expressions for the force–couple system exerted by the collar on the bar in terms of these responses.




Exercise 6.15

**EXERCISE 6.16** Collar  $A$  is welded to the vertical shaft, so the angle of inclination  $\theta$  is constant. The rectangular plate, whose mass is  $m$ , is welded to bar  $BC$ . This bar may slide through the collar, as well as spin about its own axis at angular speed  $\dot{\phi}$ , with  $\phi = 0$  defined to be the position where the plate is upright in the vertical plane. The mass of the plate is  $m$  and the mass of the bar may be neglected. Consider the situation in which the system precesses at the constant rate  $\dot{\psi}$ . Derive the corresponding differential equations of motion for  $\phi$  and the distance  $\xi$  to the end  $C$  of the bar.




Exercise 6.16

**EXERCISE 6.17** The vertical shaft rotates at constant speed  $\Omega$ . Bar  $AB$  has mass  $m$ . Both collars have negligible mass, and friction between the collars and their respective guides is negligible. Derive the differential equation of motion governing  $\theta$ .




Exercise 6.17

**EXERCISE 6.18** The cross-sectional view shows a disk of radius  $R$  that rolls without slipping over the interior surface of a cone whose apex angle is  $2\beta$ . The axis of the cone is vertical. The motion depicted in the sketch is such that the disk remains upright as it precesses at constant speed  $\Omega$ , with its center following a circular path of radius  $\rho$ . Prove that there is no combination of  $\Omega$  and  $\beta$  for which this motion is possible.




Exercise 6.18

**EXERCISE 6.19** The sphere, whose mass is  $m$ , spins freely relative to shaft  $AB$ , whose mass is negligible. The system precesses about the vertical axis at constant rate  $\Omega$ , and joint  $A$  is an ideal pin. Consider the possibility that the sphere rolls over the ceiling without slipping. Determine whether there is a range of values of  $\Omega$  for which such a motion can occur. It is permissible to assume that the radial component of the friction force at the ceiling is zero.



Exercise 6.19

**EXERCISE 6.20** A hemisphere is observed to roll without slipping on a horizontal surface. The motion is such that the center of the hemisphere follows a horizontal circle of radius  $\rho$  at constant speed  $v$ , and the angle of inclination  $\theta$  of the centerline of the hemisphere is constant. Derive an algebraic equation for the speed  $v$  corresponding to specified values of  $\theta$  and  $\rho$ . Also determine friction force  $f$ .




Exercise 6.20

# Homework Problems


379

**EXERCISE 6.21** A thin disk of mass  $m$  rolls over the ground without slipping as it rotates freely relative to bent shaft  $ABC$ . The connection at end  $A$  is an ideal pin. The precession rate of the bent shaft about the vertical axis is the constant value  $\Omega$ . Determine the magnitude of the normal force  $N$  exerted between the disk and the ground.




Exercise 6.21

**EXERCISE 6.22** The sphere spins freely about its shaft, which is connected by pin  $A$  to the vertical shaft whose rotation rate is  $\Omega_1$ . The cylindrical housing, which is shown in cross section, rotates at  $\Omega_2$ . Derive an expression for the normal force exerted on the sphere by the cylinder wall based on the assumption that the sphere rolls over the wall without slippage.




Exercise 6.22

**EXERCISE 6.23** The cone, whose mass is  $m$  and apex angle is  $2\beta$ , rolls without slipping over the horizontal surface. The rolling motion of the cone is such that it is observed to rotate about a fixed vertical axis intersecting its apex at constant angular rate  $\omega_1$ . Determine the maximum value of  $\omega_1$  for which the cone will not tip over its rim in this motion. Also, determine the minimum coefficient of static friction corresponding to that value of  $\omega_1$ . *Hint:* The line force along the edge where the cone contacts the ground may be replaced with a normal force and radial friction force. The magnitude of these forces and the location along the edge where the normal force acts may be determined from the equations of motion.



Exercise 6.23


**EXERCISE 6.24** The sphere, whose radius is  $r$ , rolls without slipping relative to the wall of the cylindrical tank and the conical floor. The tank and the floor rotate about the vertical axis at the constant rates of  $\Omega_1$  and  $\Omega_2$ , respectively. It is observed that the radial line to the center of the sphere also rotates at  $\Omega_2$ . This behavior arises when  $\Omega_2$  is very large, which also has the consequence that the friction force exerted by the floor is negligible. (a) Determine the forces exerted on the sphere by each surface it contacts in the special



Exercise 6.24

case in which  $\beta = 90^\circ$ . (b) Determine the forces exerted on the sphere by each surface it contacts if  $\beta$  is an arbitrary acute angle.


**EXERCISE 6.25** The sketch shows the cross section of a stationary cylindrical tank of radius  $b$ . A torque, which is not depicted, acting on the vertical shaft maintains the precession rate at a constant angular speed  $\Omega_1$  that is very large. The connection between this shaft and shaft  $AB$  is an ideal pin, so the angle  $\theta$  can have any value in the range  $0 \leq \theta \leq \theta_{\max}$ , where  $L \sin \theta_{\max} + R = b$ . The sphere spins freely at angular speed  $\Omega_2$  relative to shaft  $AB$ . For  $t < 0$ , a torque applied to shaft  $AB$  keeps the sphere in close proximity to the tank's wall, that is,  $\theta$  is slightly less than  $\theta_{\max}$ . The spin rate in this condition is  $\Omega_2 = 0$ . At  $t = 0$ , the shaft is released, causing the sphere to immediately contact the cylinder. The coefficient of sliding friction between the sphere and the cylinder wall is  $\mu$ , and all other frictional effects are negligible. Derive the differential equation governing  $\Omega_2$  for  $t > 0$ . The mass of the sphere is  $m$ , which is much larger than the mass of shaft  $AB$ . *Hint:* The moment exerted on the sphere by shaft  $AB$  has a zero component in the direction of the shaft.



Exercise 6.25


**EXERCISE 6.26** Consider an automobile that is following a straight path at speed  $v$ . Its wheelbase is  $L$  and its center of mass is located at distance  $b$  behind the front wheels and distance  $h$  above the ground. The coefficient of friction between the tires and the ground is  $\mu$ . Determine the maximum possible acceleration rate  $\dot{v}$  for cases of front-wheel, rear-wheel, and all-wheel drive.

**EXERCISE 6.27** Bar  $AB$  is attached at both ends to rollers that follow a horizontal circular groove of radius  $R$ . Frictional resistance is negligible. At what angle  $\theta$  relative to the bar should force  $\bar{F}$  be applied to maximize the angular acceleration of the bar? What is the corresponding angular acceleration?



Exercise 6.27

**EXERCISE 6.28** The bar of mass  $m$  is falling toward the horizontal surface as it slides over the ground. The coefficient of sliding friction is  $\mu$ . Derive differential equations of motion for the position coordinate  $x_A$  of the lower end and the angle of inclination  $\theta$ .




Exercise 6.28

## Homework Problems


381

**EXERCISE 6.29** Bar  $AB$  is pinned at its lower end to collar  $A$ , and its groove slides over the stationary pin  $C$ . Friction effects are negligible, as is the mass of the collar. The bar's center of mass is situated at its midpoint, and its centroidal radius of gyration is  $0.4L$ . At  $\theta = 30^\circ$  it is observed that  $\dot{\theta} = -2(g/L)^{1/2}$ . What is  $\ddot{\theta}$  this position?



Exercise 6.29


**EXERCISE 6.30** The system lies in the vertical plane. The bar is released from rest at  $\phi = 70^\circ$ . Determine the angular acceleration of the bar at the instant of release. Friction between the collars and their guides is negligible, as is the mass of the collars.



Exercises 6.30 and 6.31

**EXERCISE 6.31** When the bar is at  $\phi = 20^\circ$ , it is falling with an instantaneous angular velocity of  $\dot{\phi} = -8$  rad/s. The coefficients of sliding friction at the ground and the incline are both  $\mu = 0.10$ , and the collars have negligible mass. Determine the angular acceleration  $\ddot{\phi}$  of the bar in this position.

**EXERCISE 6.32** Corner  $A$  of the homogeneous square box remains in contact with the wall as the box falls. Frictional resistance at both the wall and the floor is negligible. Derive the differential equation of motion for the angle  $\theta$  at which the box is tilted. Also derive algebraic equations for the contact forces exerted by the wall in terms of instantaneous values of  $\theta$  and its derivatives.




Exercise 6.32

**EXERCISE 6.33** At  $t = 0$  a bowling ball is thrown onto the ground with a velocity  $v$  that is essentially horizontal. It is not spinning at the instant it first comes into contact with the ground. Observation of the ball's motion reveals that it begins to roll without slipping at a certain time  $t = \tau$ . Derive an expression for the coefficient of friction in terms of  $\tau$  and the system's parameters.


**EXERCISE 6.34** A cable is wrapped around the drum of the stepped cylinder and held at angle of elevation  $\theta$  by the tensile force  $\bar{F}$ . The system was at rest before the application of  $\bar{F}$ . The mass of the cylinder is  $m$ , its centroidal radius of gyration is  $\kappa$ , and the coefficients of static and kinetic friction with the ground are both  $\mu$ . The elevation

angle can be any value in the range  $0 \leq \theta \leq 90^\circ$ . (a) Derive an expression for the maximum value of  $F$  for which the cylinder will roll without slipping at a specified  $\theta$ . Also determine the corresponding acceleration of the center of the cylinder. (b) Graph the results in Part (a) for the case in which  $m = 500$  kg,  $r_1 = 400$  mm,  $r_2 = \kappa = 300$  mm, and  $\mu = 0.2$ . (c) Derive expressions for the acceleration of the center of cylinder and the angular acceleration when  $F$  at a specified  $\theta$  is 10% greater than the value found in Part (a).




Exercise 6.34

**EXERCISE 6.35** The homogeneous semicylinder has an angular speed  $\omega = 5$  rad/s when  $\theta = 30^\circ$ . The cylinder's mass is 20 kg, and  $R = 150$  mm. Determine the minimum coefficient of static friction between the ground and the semicylinder for which slipping between the semicylinder and the ground will not occur in this position. What is the corresponding angular acceleration  $\dot{\omega}$  of the semicylinder?




Exercise 6.35

**EXERCISE 6.36** Bar  $AB$ , which is pinned to collar  $A$  and to the perimeter of the cylindrical pipe, is pushed to the right by application of force  $F$  to the collar. The mass of the cylinder is  $m$ ; the influence of the mass of the bar and of the collar may be neglected. Consider the situation in which  $F = 0.5mg$ . From the assumption that the cylinder rolls without slipping, determine the acceleration of the center of the cylinder when the system is at the instantaneous position depicted in the sketch. Also determine the minimum value of the coefficient of static friction required to prevent slippage at this position.




Exercise 6.36

**EXERCISE 6.37** Horizontal force  $F$  is applied to the piston, whose mass is small compared with that of the circular cylinder of mass  $m$ . The coefficients of friction are  $\mu$  and  $\eta$  for static and kinetic friction, respectively. (a) For the case in which there is no slipping relative to the ground, determine the acceleration of the cylinder's center. (b) Determine the largest value of  $F$  for which the motion in Part (a) is possible. (c) Determine the translational and angular acceleration of the disk when the magnitude of  $F$  exceeds the value in Part (b).




Exercise 6.37

**EXERCISE 6.42** A single-engine turbojet airplane has its minimum speed  $v$  at the top of a vertical circle of radius  $\rho$ . At that instant, the airplane is executing a roll, clockwise as viewed by the pilot, at angular speed  $\omega_1$ . The engine turns at angular speed  $\Omega$  about the longitudinal axis, which is labeled  $x$  in the diagram. This rotation is clockwise from the pilot's viewpoint. The rotating parts of the engine have mass  $m_2$ , and centroidal moments of inertia  $J$  about the rotation axis and  $J'$  transverse to the rotation axis. The mass of the airplane, excluding the rotating parts of the engine, is  $m_1$ , and the corresponding moments of inertia about centroidal  $xyz$  axes are  $I_x$ ,  $I_y$ , and  $I_z$ . The spin axis of the engine is collinear with the longitudinal  $x$  axis of the airplane, and the centers of mass  $G_1$  and  $G_2$ , associated respectively with  $m_1$  and  $m_2$ , both lie on this axis. Derive expressions for the aerodynamic force and moment about the center of mass of the airplane required to execute this maneuver.




Exercise 6.42

**EXERCISE 6.43** While Abby pushes a lawn mower at constant speed  $v$  along level ground, she pushes down on the handle, causing it to rotate about its rear axle at constant speed  $\Omega_2 = \dot{\psi}$ . The motor's rotation rate  $\Omega_1 = \dot{\theta}$  is constant. Derive an expression for the dynamic force at each wheel associated with these rotations when the motor's axis is inclined at angle  $\psi$  from the vertical. Do these forces depend on the angular position of the blade? The mass of the cutting blade is  $m$ , the length of the blade is  $L$ , and the blade may be considered to be a slender bar.



Exercise 6.43

**EXERCISE 6.44** The barrel of a truck transporting wet-mix concrete rotates at 1 rev/min. The axis of rotation is elevated  $14^\circ$  from horizontal. The barrel and its contents have a mass of 30 000 kg, and the concrete may be considered to be a solid that fills the rotating barrel. The centroidal radii of gyration of the rotating parts are 1.5 m about the rotation axis and 2.5 m transversely to that axis. Determine the dynamic force at each wheel associated with rotation of the barrel when the truck executes a 40-m radius turn at 50 km/h. The track (distance between a pair of wheels on opposite sides) is 3 m.




Exercise 6.44



### Homework Problems

385

**EXERCISE 6.45** The gimbal supporting the flywheel is suspended from pivot  $A$  by two cables of equal length. The flywheel, which may be modeled as a thin disk of mass  $m_1$ , spins at the constant rate  $\chi$ . The mass of the gimbal is  $m_2$ . It is observed that under certain conditions the system will undergo a steady precession  $\Omega$  about the vertical axis through pivot  $A$  with the angle of inclination  $\theta$  constant and the spin axis  $BC$  of the flywheel horizontal. Derive expressions for  $\chi$  and  $\Omega$  under these circumstances as functions of the angle  $\theta$  and the other system parameters.




Exercise 6.45

**EXERCISE 6.46** The force  $\bar{F}$  in Exercise 6.38 is constant and frictional resistance between pin  $B$  and the groove is negligible. Initially,  $\theta = -60^\circ$  and  $\dot{\theta} = 0$ . The distance  $h = 0.6R$ . Derive an expression for the angular speed of the wheel when  $\theta = 30^\circ$ , based on the assumption that there is no slippage when the wheel rolls.

**EXERCISE 6.47** The bar in Exercise 6.29 is released from rest at  $\theta = 60^\circ$ . Determine its angular velocity when  $\theta = 10^\circ$ . The mass of the collar is half the mass of the bar.


**EXERCISE 6.48** The semicylinder in Exercise 6.35 is released with angular speed  $\omega_0$  at  $\theta = 0$ . Derive expressions for the normal and friction forces exerted by the ground as functions of  $\omega_0$  and  $\theta$  if the semicylinder rolls without slipping.

**EXERCISE 6.49** Bar  $AB$  has a mass of 40 kg, and the stiffness of the spring is 9 kN/m. The bar is released from rest at  $\phi = 0$ , at which position the spring is elongated by 300 mm. The linkage lies in the vertical plane. (a) Determine the largest value of  $\phi$  attained in the subsequent motion. (b) Determine  $\dot{\phi}$  when  $\phi$  is  $5^\circ$  less than the value found in Part (a).




Exercise 6.49

**EXERCISE 6.50** The small ball is released from rest with the cable horizontal. At its lowest point the cable encounters the fixed peg. Describe the speed of the sphere as a function of the angle  $\theta$ .



Exercise 6.50


**EXERCISE 6.51** Gear  $A$  has mass  $m$  and centroidal radius of gyration  $\kappa$ . It rolls over the horizontal rack because of the constant horizontal force  $F$  acting on collar  $C$ . The connecting bar and collar  $C$  have negligible mass. The system was at rest at  $\theta = 0$ . Derive an expression for the speed  $v$  of the center of gear  $A$  as a function of  $\theta$ .



Exercise 6.51


**EXERCISE 6.52** Solve Exercise 6.51 for the case in which the mass of rod  $BC$  is  $m/2$ .

**EXERCISE 6.53** The semicircular plate is falling at speed  $v$  with its plane oriented horizontally. It strikes the ledge at corner  $A$ , and the impact is perfectly elastic (that is, the recoil velocity of corner  $A$  is  $v$  upward). The interval of the collision is  $\Delta t$ . Derive expressions for the velocity of the center of mass and the angular velocity at the instant following the collision. Also, derive an expression for the collision force exerted between the plate and the ledge.




Exercise 6.53

**EXERCISE 6.54** Bar  $AB$  is pinned to the vertical shaft, which rotates freely. When the bar is inclined at  $\theta = 10^\circ$ , the rotation rate about the vertical axis is  $\Omega = 10$  rad/s, and  $\dot{\theta} = 4$  rad/s at that instant. Determine the maximum value of  $\theta$  in the subsequent motion. The mass of the vertical shaft may be neglected.



Exercise 6.54

**EXERCISE 6.55** The pin allows the angle of inclination  $\theta$  of the 50-kg bar to change when a constant tensile force of  $F = 2$  kN is applied. No torque is applied to the vertical shaft, so the precession rate  $\Omega$  varies as  $\theta$  is altered. At the initial position  $\theta = 20^\circ$ ,  $\dot{\theta} = 0$ , and  $\Omega = 5$  rad/s. Determine the values of  $\dot{\theta}$  and  $\Omega$  when  $\theta = 90^\circ$ .




Exercise 6.55

**EXERCISE 6.56** The system in Exercise 6.14 spins freely about the vertical axis because the torque  $\Gamma$  is not present. Initially  $\Omega = 4(g/L)^{1/2}$  with  $\theta = 150^\circ$  and  $\dot{\theta} = 0$ . The moment of inertia of the T-bar about its rotation axis is  $0.5mL^2$ , where  $m$  is the masses of bar  $BC$ . (a) Determine the value of  $\dot{\theta}$  when  $\theta = 90^\circ$ . (b) Determine the minimum value of  $\theta$  in the ensuing motion.

# Homework Problems

387


**EXERCISE 6.57** The system rotates freely about the vertical axis. Collars  $A$  and  $B$  are pinned to the bar that is welded to sphere  $C$ . The mass of the sphere is 12 kg, and the masses of the collars and the bar are negligible. Initially, the system is precessing at  $\Omega = 100$  rad/s with  $\theta$  held constant at  $20^\circ$ . It then is released, causing  $\theta$  to increase and  $\Omega$  to change. Determine whether  $\theta = 90^\circ$  is attained in the subsequent motion. If so, what is the angular velocity of the sphere at that position?



Exercise 6.57


**EXERCISE 6.58** The system in Exercise 6.57 was rotating at rate 50 rad/s with  $\theta$  constant at  $30^\circ$  when it was released. Determine whether in the ensuing motion there is another value of  $\theta$  at which  $\dot{\theta}$  is zero. If so, what is the value of  $\Omega$  at that position?

**EXERCISE 6.59** A slender bar of mass  $m$ , which is suspended by a cable from pivot  $A$ , executes a steady precession about the vertical axis at angular speed  $\Omega$  as it maintains the orientation shown. (a) Determine  $\Omega$  and the angle of inclination  $\beta$ . (b) An impulsive force  $\bar{F}$  at end  $B$ , parallel to the initial velocity of that end, acts over a short time interval  $\Delta t$ . Determine the magnitude of  $\bar{F}$  for which  $\Omega = 0$  at the conclusion of the impulsive action. What are the corresponding velocity of the center of mass  $G$  and angular velocity of the bar? *Hint:* If  $\Omega = 0$ , the angular velocity of the bar must be horizontal.




Exercise 6.59

**EXERCISE 6.60** The flyball speed governor consists of two 500-g spheres connected to the vertical shaft by a parallelogram linkage. This shaft, which passes through the collar supporting the linkage, rotates freely. The mass of the links is negligible. The system is initially rotating steadily at 900 rev/min about the vertical axis, with  $\theta = 75^\circ$ . A constant upward force  $\bar{F}$  is applied to the vertical shaft at end  $B$ , causing point  $A$  to move upward and  $\theta$  to decrease. Derive algebraic equations for  $\Omega$  and  $\dot{\theta}$  as functions of the magnitude of  $\bar{F}$  and  $\theta$ .




Exercise 6.60

**EXERCISE 6.61** The package was translating to the left at speed  $v$  when it hit cleat  $A$ . The collision is perfectly plastic. Determine the angular velocity of the package immediately after the collision.




Exercise 6.61

**EXERCISE 6.62** The 100-kg bar was released from rest in the horizontal position. The coefficient of restitution between the bar and bumper  $B$  is 0.4, and the duration of the impact is 5 ms. Determine the maximum angle of inclination of the bar subsequent to the impact and the average force exerted by the bumper during the impact.




Exercise 6.62

**EXERCISE 6.63** The square plate, whose mass is  $m$ , strikes corner  $C$  of ledge at angular speed  $\omega$ . The impact point is slightly above the corner of the plate. The coefficient of restitution is  $\varepsilon$  and the impact's duration is 8 ms. Determine the angular velocity at which the plate rebounds and the average forces that are exerted on the plate by the ledge and pin  $A$  during the impact.




Exercise 6.63

**EXERCISE 6.64** The 20-kg bar was at rest when it was hit by the 1-kg ball whose initial velocity was  $v = 30$  m/s in the direction shown in the sketch. The coefficient of restitution is 0.75. Determine the angular velocity of the bar and the velocity of the ball immediately after the collision.



Exercise 6.64

**EXERCISE 6.65** The sketch shows the velocity of a small disk at the instant before its collision with a rigid body consisting of the same disks connected by a rigid massless bar. Determine the rebound velocity of each disk in terms of the coefficient of restitution  $\varepsilon$ .



Exercise 6.65

## CHAPTER 7

# Introduction to Analytical Mechanics

Any formulation of equations of motion requires characterization of the role of the physical restrictions that are imposed on a system's movement. These restrictions lead to kinematical relations between motion variables, and they also are manifested as reaction forces. When a system consists of interconnected bodies, the standard Newton–Euler formulation isolates individual bodies. The need to account for the kinematical constraints and corresponding reaction forces associated with each connection substantially enhances the level of effort entailed in deriving equations of motion.

The Lagrangian formulation implicitly recognizes the dual role of motion constraints. Indeed, it is recognition of this duality that has made it preferable to use the term *constraint force* rather than reaction. A primary benefit of the Lagrangian formulation is the ability to automatically account for constraint forces in the equations of motion. The formulation will allow us to treat connected bodies as a single system, rather than individual entities. The primary kinetic quantity for Lagrange's equations of motion is mechanical energy (kinetic and potential), whereas the Newtonian equations of motion are time derivatives of momentum principles.

The term *analytical mechanics*, which encompasses the developments of Lagrange, Hamilton, and many others who followed Euler, refers to the fact that the procedures that we shall develop are more mathematical than those of Newton and Euler. They also are more abstract. In fact, we often will find that features of the equations of motion, as well as of the physical responses predicted by those equations, are most readily explained in terms of Newton–Euler concepts.

## 7.1 BACKGROUND

As a preview to where we are headed, it is useful to consider a historical development that preceded Lagrange and provided an important impetus to his work. Some popular undergraduate textbooks, for example, Hibbeler (2003), state that d'Alembert reformulated Newton's Second Law as a static principle by defining an inertial force to be the negative of the product of mass and acceleration, that is,

$$\Sigma \vec{F} + \vec{F}_{\text{inertial}} = \vec{0} \text{ where } \vec{F}_{\text{inertial}} = -m\vec{a}. \quad (7.1.1)$$

Such a viewpoint would be problematic, in that the so-called inertial force is not exerted by another body, as postulated by Newton's Third Law. A different perspective, which one may find in more advanced works such as Goldstein (1980) and Rosenberg (1977),

asserts that d'Alembert introduced the inertial force concept as a vehicle for applying the principle of virtual work, which had often been used for static systems, to the analysis of dynamic systems. In fact, it is not clear how d'Alembert came to be associated with the inertial force concept. Dugas' (1988) extensive treatment of d'Alembert's work does not mention either an inertial force or virtual work. Truesdell (1960) attributes the inertial force concept to Euler and credits Lagrange with using the concept to apply the principle of virtual work. We avoid this question of attribution by referring to the concept as the *principle of dynamic virtual work*, without mention of d'Alembert. Development of this principle is how we will begin, but doing so requires that we first consider the principle of virtual work for static systems.

### 7.1.1 Principle of Virtual Work

Were it not for the requirement that one consider movement of a static system, the principle of virtual work would be quite straightforward. The statics laws state that the actual forces acting on a body are self-equilibrating. Because any set of forces may be replaced with an equivalent force–couple system acting at an arbitrary point  $P$ , static equilibrium requires that there be a force balance and a moment balance about point  $P$ :

$$\Sigma \bar{F} = \bar{0}, \quad \Sigma \bar{M}_P = \bar{0}. \quad (7.1.2)$$

Physically moving a body that is in static equilibrium requires that the forces acting on it be altered, such that their resultant does not vanish. Thus let us introduce an abstraction called a *virtual movement*; the word virtual is used here in the same sense as virtual reality, to denote something that does not really occur. When we introduce the virtual movement, we consider all forces, including those that constrain motion, to be unchanged, even though we ignore kinematical restrictions.

The virtual movement results in altering the position of the point  $P$  chosen for moment equilibrium, and it also leads to rotation of the body. The virtual movement we impart could have any magnitude we wish. However, if it leads to finite changes in the position of points and the orientation of the body, it will be necessary to evaluate the work as a path integral that accounts for the dependence of the force components as the position changes. For this reason, a virtual movement is limited to be such that the virtual displacements of points and the virtual rotations of bodies are infinitesimal. Correspondingly, we denote the virtual displacement of point  $P$  as  $\delta \bar{r}_P$  and the virtual rotation of the body as  $\delta \bar{\theta}$ , where we use the symbol  $\delta$ , rather than the differential symbol  $d$ , to emphasize that we are not dealing with an increment that actually occurs.

The work done by the resultant force in Eq. (7.1.2) is  $\Sigma \bar{F} \cdot \delta \bar{r}_P$ , and the work done by the resultant moment is  $\Sigma \bar{M}_P \cdot \delta \bar{\theta}$ . Because both the resultant force and resultant moment vanish, each work term is zero. Furthermore, work is additive as a scalar quantity, so the *virtual work*  $\delta W$  also is zero for a system of rigid bodies. A further consequence of work being a scalar is that we may form it from the individual contributions of each force  $\bar{F}_j$  and couple  $\bar{M}_n$  that acts on the system. Thus, we are led to the *principle of*

## 7.1 Background

393

*virtual work*, which states that the work done by the set of forces and couples acting on a static system vanishes in a virtual displacement,

$$\delta W = \sum_j \bar{\mathbf{F}}_j \cdot \delta \bar{\mathbf{r}}_j + \sum_n \bar{M}_n \cdot \delta \bar{\theta}_n = 0, \quad (7.1.3)$$

where  $\delta \bar{\mathbf{r}}_j$  is the virtual displacement of the point where force  $\bar{\mathbf{F}}_j$  is applied and  $\delta \bar{\theta}_n$  is the virtual rotation of the body on which couple  $\bar{M}_n$  acts.

At this juncture, it might seem strange that the principle of virtual work can be useful, because it is a single scalar equation, yet there are likely to be many unknown forces to determine. Such thoughts ignore a key feature, specifically that we may impose any virtual movement we wish. The virtual work is different for different movements, thereby leading to different equilibrium equations. Furthermore, we may select the virtual movement such that the only unknown forces doing work are the forces we wish to determine. This enables us to form one or more equilibrium equations that contain only the forces we wish to determine.

These concepts can be understood by considering the frame structure in Fig. 7.1, where it is desired to determine the horizontal constraint force  $C_x$ . To avoid the occurrence of the reactions  $A_x$ ,  $A_y$ , and  $C_y$  in the virtual work, the virtual movement of the system should be such that end  $A$  remains stationary and end  $C$  moves horizontally. Such a movement will alter the angle  $\theta$ . Let us denote the virtual increment of this angle as  $\delta\theta$ .




Figure 7.1. Free-body diagram of a frame structure in static equilibrium.

The work done by the couple  $M$  will be  $M\delta\theta$ , but we also must determine the work done by  $\bar{\mathbf{F}}$  and  $\bar{\mathbf{C}}_y$ , which means that we need to determine the virtual displacement of their points of application. This actually is a familiar task, because ignoring the constraint against horizontal motion of point  $C$  effectively converts the system to a linkage. To determine infinitesimal displacements associated with  $\delta\theta$ , we first describe both positions in terms of  $\theta$ :

$$\bar{\mathbf{r}}_{C/A} = 2L \cos \theta \bar{\mathbf{i}}, \quad \bar{\mathbf{r}}_{G/A} = \frac{3}{2}L \cos \theta \bar{\mathbf{i}} + \frac{1}{2}L \sin \theta \bar{\mathbf{j}}. \quad (7.1.4)$$

The virtual displacements, being infinitesimal, may be obtained from the chain rule, so that

$$\begin{aligned} \delta \bar{\mathbf{r}}_{C/A} &= \frac{\partial \bar{\mathbf{r}}_{C/A}}{\partial \theta} \delta \theta = (-2L \sin \theta \bar{\mathbf{i}}) \delta \theta, \\ \delta \bar{\mathbf{r}}_{G/A} &= \frac{\partial \bar{\mathbf{r}}_{G/A}}{\partial \theta} \delta \theta = \left( -\frac{3}{2}L \sin \theta \bar{\mathbf{i}} + \frac{1}{2}L \cos \theta \bar{\mathbf{j}} \right) \delta \theta. \end{aligned} \quad (7.1.5)$$

We add the virtual work done by both forces and  $\bar{M}$ , and equate it to zero. This gives

$$\begin{aligned}\delta W &= C_x \bar{i} \cdot \delta \bar{r}_{C/A} + (-F \bar{j}) \cdot \delta \bar{r}_{G/A} + M \delta \theta \\ &= C_x (-2L \sin \theta) \delta \theta + (-F) \left( \frac{1}{2} L \cos \theta \right) \delta \theta + M \delta \theta = 0.\end{aligned}\quad (7.1.6)$$

According to the principle of virtual work,  $\delta W$  must vanish, even though  $\delta \theta$  is not zero, so we find that

$$C_x = \frac{M}{2L \sin \theta} - \frac{F \cot \theta}{4}.\quad (7.1.7)$$

The same result could be obtained by equilibrating bars  $AB$  and  $BC$  individually. However, doing so would lead to several simultaneous equations in which the internal forces exerted between the bars at pin  $B$  appear. The ability to focus on the variables of interest is what makes the principle of virtual work attractive for both static and dynamic systems.

### 7.1.2 Principle of Dynamic Virtual Work


The first step in extending the principle of virtual work to dynamic systems entails a slight alteration of the concept of dynamic equivalence, which we used in Section 6.3 to obtain equations of motion for a system of rigid bodies. This alteration involves drawing a single free-body diagram of the system. In addition to the actual forces, an inertial force–couple system,  $-m\bar{a}_G$  and  $-d\bar{H}_A/dt$ , respectively, is shown for each body. (The former is the d'Alembert inertial force discussed at the beginning of this chapter, and the second term is the analogous moment effect.) The point  $A$  at which this force–couple system is applied is the same as the reference point for the Newton–Euler equations of motion. Thus we limit the specific point  $A$  to be each body's center of mass, unless a body is in pure rotation, in which case it may be the stationary pivot point. These inertial forces and couples must equilibrate the actual forces and couples that act on the bodies. Consequently, the total virtual work done by the inertial and actual forces and couples must be zero, as though the system were in static equilibrium. Also, as in the static case, the virtual movement may be defined in any manner. Selecting a virtual movement in which constraint forces do no virtual work will lead to an equation of motion whose only unknowns are position variables.

A slight modification of the system in Fig. 7.1 serves well to illustrate this concept. In Fig. 7.2 the pin connection at end  $C$  has been replaced with a collar riding in a horizontal guide, so the system is not rigid. Bar  $BC$  executes a general motion, so its center of mass  $G$  is the reference point for the Euler moment equation. Correspondingly, the inertial force  $-m\bar{a}_G$  is applied at the center of mass, and the inertial couple applied to this bar is  $I_G \ddot{\theta} \bar{k}$ , where the sense is opposite the angular acceleration associated with positive  $\ddot{\theta}$ . In contrast, bar  $AB$  executes a pure rotation about pin  $A$ , so it is advantageous to use this point. Thus the inertial force  $-m\bar{a}_D$  is applied at end  $A$ , and the inertial couple is  $-I_G \ddot{\theta} \bar{k}$ . These forces and couples are depicted in the free-body diagram.



## 7.1 Background

395



**Figure 7.2.** Free-body diagram showing the actual forces acting on a linkage, as well as d'Alembert's inertial forces.

We select the same virtual movement that we used to solve the static version of this system. Doing so avoids the occurrence of the constraint forces  $\bar{A}_x$ ,  $\bar{A}_y$ , and  $\bar{C}_y$  in the virtual work. We must add the virtual work of the inertial forces and couples to that of the actual force system. Because  $-m\bar{a}_D$  acts at the stationary pin  $A$ , it does no work. We described the virtual displacement of point  $G$  in Eqs. (7.1.5). For the virtual rotations, we observe that increasing  $\theta$  by  $\delta\theta$  causes bar  $AB$  to rotate by  $\delta\theta\bar{k}$  and bar  $BC$  to rotate by  $-\delta\theta\bar{k}$ . Thus the total virtual work done by the actual and inertial effects is

$$\delta W = (M\bar{k} - I_A\bar{\alpha}_{AB}) \cdot \delta\theta\bar{k} + (-m\bar{a}_G - F\bar{j}) \cdot \delta\bar{r}_{G/A} + (-I_G\bar{\alpha}_{BC}) \cdot (-\delta\theta\bar{k}) = 0. \quad (7.1.8)$$

Although we have equated the virtual work to zero, we cannot yet obtain an equation of motion because we must account for the dependence of  $\bar{a}_G$  on  $\theta$ . Differentiating  $\bar{r}_{G/A}$  in Eqs. (7.1.4) gives

$$\bar{a}_G = \ddot{\bar{r}}_{G/A} = -\frac{3}{2}L(\ddot{\theta}\sin\theta + \dot{\theta}^2\cos\theta)\bar{i} + \frac{1}{2}L(\ddot{\theta}\cos\theta - \dot{\theta}^2\sin\theta)\bar{j}. \quad (7.1.9)$$

Substitution of this expression and the angular accelerations into the preceding equation for  $\delta W$  results in

$$\begin{aligned} \delta W = & (M - I_A\ddot{\theta})\delta\theta + \frac{3}{2}mL(\ddot{\theta}\sin\theta + \dot{\theta}^2\cos\theta)\left(-\frac{3L}{2}\delta\theta\sin\theta\right) \\ & - \left[\frac{1}{2}mL^2(\ddot{\theta}\cos\theta - \dot{\theta}^2\sin\theta) + F\right]\left(\frac{L}{2}\delta\theta\cos\theta\right) + I_G\ddot{\theta}(-\delta\theta) = 0. \end{aligned} \quad (7.1.10)$$

Because  $\delta\theta$  is not zero, it may be factored out. What remains is the differential equation of motion:

$$\left[I_A + I_G + \frac{9}{4}mL^2(\sin\theta)^2 + \frac{1}{4}mL^2(\cos\theta)^2\right]\ddot{\theta} + 2mL^2\dot{\theta}^2\sin\theta\cos\theta = M - \frac{FL}{2}\cos\theta. \quad (7.1.11)$$

The analysis leading to this equation of motion exemplifies the direct application of the principle of dynamic virtual work. Each body is treated as though it were in static equilibrium under a force-couple system composed of the actual and inertial forces, where the latter are as given by the Newton-Euler equations of motion. Regardless of the type of motion, the center of mass is always an appropriate reference point for the moment equations, so we begin with

$$\Sigma \bar{F}_i + (-m_i\bar{a}_{Gi}) = \bar{0}, \quad \Sigma \bar{M}_{Gi} + \left(-\frac{d\bar{H}_{Gi}}{dt}\right) = \bar{0}, \quad i = 1, \dots, K. \quad (7.1.12)$$

The virtual work of each force resultant is obtained from a dot product with the virtual displacement of the corresponding body's center of mass, and the the virtual work of

## 7.2 Generalized Coordinates and Kinematical Constraints

397

we could have used the horizontal distance  $\ell$  from the fixed pin  $A$  to the collar  $C$ . In fact, because  $\ell = 2L \cos \theta$ , we could switch between the two variables. The variables that we select to locate the current position of a system are called *generalized coordinates*.

### 7.2.1 Selection of Generalized Coordinates

Suppose the reference location of a system is given. (Such a location might be the starting position or the static equilibrium position.) The generalized coordinate values must uniquely define any possible position of the system relative to the initial position. For example, it should be possible to draw a diagram of the system in its current position by knowing only values of the generalized coordinates and the fixed dimensions. The minimum number of generalized coordinates required to specify the position of the system is the *number of degrees of freedom* of that system. The linkage in Fig. 7.2 has one degree of freedom because we are able to locate the current configuration of the linkage solely from knowledge of  $\theta$ . As mentioned earlier, the choice of generalized coordinates is not unique. Thus, different individuals analyzing the same system might select different generalized coordinates, and therefore derive different equations of motion.

When a body moves in space without any restrictions, its current location is defined by the position of any point, such as the center of mass, and a set of three independent direction angles locating lines in the body. Thus, in the absence of kinematical constraints, any rigid body moving in space has six degrees of freedom, and a possible set of generalized coordinates are three position coordinates of the center of mass relative to a convenient fixed reference frame and three Eulerian angles defined relative to that reference frame. Now suppose a body is constrained to execute a planar motion. This restriction reduces the number of degrees of freedom to three, because only two position coordinates are required to locate a point in the plane of motion, and the only angle of rotation is about the axis perpendicular to that plane.

Consider the rigid bar in Fig. 7.3(a), where position coordinates  $x_A$  and  $y_A$  locate one end of the bar, and angle  $\theta$  measured from the horizontal locates the current orientation. Only geometrical parameters that change as the system moves are candidates for generalized coordinates, whereas fixed parameters, such as  $L$ , are considered to be known system properties. Thus the generalized coordinates defined in Fig. 7.3(a) are  $(x_A, y_A, \theta)$ .

Figure 7.3(b) defines an alternative set of three generalized coordinates. The bar's location is there described in terms of  $(x_B, y_B, \phi)$ , which define the position of end  $B$  and the rotation relative to the vertical direction. In general, it must be possible to express




Figure 7.3. Alternative generalized coordinates for a bar moving in a plane.

constraint force. In this case the linkage is reduced to two degrees of freedom, and  $(\theta, \phi)$  serve as convenient unconstrained generalized coordinates. Alternatively, we could use  $(\theta, \phi, x_C)$  as a set of constrained generalized coordinates.

It might be troubling that generalized coordinates can be either constrained or unconstrained. We will see that in some situations it is not possible to identify an unconstrained set. Furthermore, our studies will show that, when the alternative is available, there are specific advantages to selecting either type. It also might be troubling that there is no unique set of generalized coordinates. However, this is the essence of the modeling process. When we select the variables with which to characterize the motion of a system, we are concurrently making decisions about the features of the system that will need to be considered. Different individuals can use different variables to represent these features and therefore obtain different equations of motion. However, if their models are equivalent, they will have the same number of degrees of freedom, and the physical motion predicted by solution of those equations will be identical.

### 7.2.2 Constraint Equations

To progress in our study of analytical mechanics we need to fit the notions of generalized coordinates and constraint equations into a mathematical framework. Suppose we select a set of  $N$  constrained generalized coordinates to represent a system. We reserve the symbol  $q_j$  to denote the  $j$ th generalized coordinate. There might be several constraint equations that these generalized coordinates must satisfy. If these equations are like those arising in the previous subsection, each may be written in the functional form

$$f_i(q_n, t) = 0, \quad (7.2.2)$$

where the subscript  $i$  denotes which of the several constraints is being considered and the appearance in the argument list of  $q_n$  with  $n$  unspecified serves to indicate dependence on all of the generalized coordinates. A relation such as Eq. (7.2.2) is referred to as a *configuration constraint* equation. This term stems from the fact that, by limiting the values the generalized coordinates may have, it restricts the overall arrangement of the system at any instant. Examples of configuration constraint equations are Eqs. (7.2.1), which constitute three equations that must be satisfied by the six generalized coordinates  $(x_A, y_A, x_B, y_B, \theta, \phi)$ . Given the value of three of these variables, the values of the other three may be determined by simultaneously solving these equations.

Constraint equations like Eqs. (7.2.1) represent relations that are time invariant. Solving such equations for a subset of generalized coordinates would yield values that depend on only the current values of the other coordinates. In contrast, the general configuration constraint described by Eq. (7.2.2) contains  $t$  in its argument list. This is done to accommodate situations in which physical features of a system change in a known manner. For example, instead of being fixed, suppose the bar in Fig. 7.3 is replaced with a hydraulic cylinder whose length  $L$  is controlled. In that case Eqs. (7.2.1) would still apply, except that  $L$  would be the length at a specified value of  $t$ .

## 7.2 Generalized Coordinates and Kinematical Constraints

401


Rather than directly constraining the position of a system, we can impose conditions on the velocity of its points or the angular velocity of its bodies. Such restrictions are described by *velocity constraint* equations. Any configuration constraint may be converted into an equivalent velocity constraint by differentiating it with respect to time. The chain rule for differentiation must be employed to differentiate Eq. (7.2.2) because the generalized coordinates are (unknown) functions of time. Thus the velocity constraint equation corresponding to Eq. (7.2.2) is

$$\dot{f}_i = \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} f_i(q_n, t) \right] \dot{q}_j + \frac{\partial}{\partial t} f_i(q_n, t) = 0. \quad (7.2.3)$$

One way of viewing the preceding velocity constraint equation is that it is a differential equation that the generalized coordinates must satisfy. In view of its derivation, multiplying Eq. (7.2.3) by  $dt$  converts it to a perfect differential that may be integrated. The constant of integration that arises in this process may be evaluated by substitution of initial values of the generalized coordinates. If these initial values satisfy the configuration constraint equation, the restriction on velocity represented by Eq. (7.2.3) is fully equivalent in its effect to the configuration constraint.

A different perspective results if we ignore the fact that a *generalized velocity*  $\dot{q}_j$  is known if the corresponding  $q_j$  is a known function of time. Instead, suppose we were to begin to observe a system at an arbitrary time  $t$ . We could deduce the corresponding values of the  $q_j$  variables at that instant from measurements of the physical position. In this view, Eq. (7.2.3) constrains the possible values of the generalized velocities when the system is at a specific position. Such a view is comparable with using  $\bar{v}_B = \bar{v}_A + \bar{\omega} \times \bar{r}_{B/A}$  to relate the velocities of points in a rigid body, rather than differentiating a general expression for  $\bar{r}_{B/O}$ . Another example of this dual viewpoint is to consider using as constrained generalized coordinates the  $x$  and  $y$  coordinates of the centroid of a collar that slides along a circular of radius  $R$ . If we place the center of the guide bar at the origin, then the configuration constraint equation for the motion is  $x^2 + y^2 - R^2 = 0$ . Differentiation of this relation with respect to time yields the velocity constraint equation  $2x\dot{x} + 2y\dot{y} = 0$ . The position and velocity in Cartesian coordinates are  $\bar{r} = x\bar{i} + y\bar{j}$  and  $\bar{v} = \dot{x}\bar{i} + \dot{y}\bar{j}$ . Thus the velocity constraint equation requires that  $\bar{v} \cdot \bar{r} = 0$ , that is, the velocity of the collar must always be perpendicular to the position vector from the origin to the collar. As shown in Fig. 7.5, we could arrive at the same velocity constraint directly through a kinematical analysis, in which we adjust the velocity components to make  $\bar{v}$  tangent to the circle, and then observe that the angle  $\theta$  locating  $\bar{v}$  also defines the radial line. Note that the radius  $R$  does not appear in the velocity constraint equation. However, integrating the velocity constraint equation would require that the initial values of  $x$  and  $y$  correspond to a point on a circle of radius  $R$ .

Figure 7.5 exemplifies a primary reason to consider velocity constraints. In many cases, especially those involving complicated systems, it is easier to identify constraint conditions by analyzing the velocity of a system at a specific system. Furthermore, there are important situations in which the velocity of a system is constrained, but there is no corresponding configuration constraint. Such cases may be represented by modifying



**Figure 7.5.** Kinematical relationship of generalized velocities for motion along a circular path.

Eq. (7.2.3) such that the coefficients of the generalized velocities are arbitrary functions, rather than being restricted to be partial derivatives of a configuration function  $f_n$ . Specifically, this more general form is

$$\sum_{j=1}^N a_{ij}(q_n, t) \dot{q}_j + b_i(q_n, t) = 0. \quad (7.2.4)$$

Constraint conditions that have this form are said to be *linear velocity constraints*, because they represent linear algebraic equations for the generalized velocities when the values of the generalized coordinates and time are given.<sup>†</sup>

From a philosophical standpoint, considering a generalized coordinate and the corresponding generalized velocity to be independent variables is an important development. A configuration constraint represents an algebraic/transcendental equation that governs how a system arrived at its current state. In contrast, a velocity constraint represents a restriction on the manner in which the system can move given its current state. Movements that are consistent with the constraint conditions are said to be *kinematically admissible*.

A kinematical analysis of a system will often lead to one or more velocity constraint equation. It is useful in such cases to determine whether these equations are equivalent to configuration constraints. To carry out such an analysis, we convert the velocity form to a differential by multiplying it by  $dt$ , which leads to

$$\sum_{j=1}^N a_{ij}(q_n, t) dq_j + b_i(q_n, t) dt = 0. \quad (7.2.5)$$

This is the *Pfaffian form* of a constraint equation. Instead of restricting the generalized velocities, it represents a restriction on the amount by which the generalized coordinates may change in a time interval  $dt$ . The Pfaffian form of the configuration constraint may be obtained similarly by multiplying Eq. (7.2.3) by  $dt$ :

$$df_i = \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} f_i(q_n, t) \right] dq_j + \frac{\partial}{\partial t} f_i(q_n, t) dt = 0. \quad (7.2.6)$$

<sup>†</sup> Equation (7.2.4) does not represent the most general type of kinematical constraint that can be imposed on the motion of a system. Some types of motion restrictions cannot be treated in any general manner. One such situation arises in treating inequality relationships, such as the limitation that the wheels of a car reaching the top of a hill remain in contact with the ground only if the normal contact force is positive. Also, it is conceivable that generalized velocities might occur nonlinearly in a constraint equation.

## 7.2 Generalized Coordinates and Kinematical Constraints

403

Equations (7.2.5) and (7.2.6) are equivalent if they differ by only a multiplicative factor. This *integrating factor* may be a function of the generalized coordinates and time, so we denote it as  $g_i(q_1, q_2, \dots, q_N, t)$ . Thus we deduce that a given velocity constraint equation is derivable from a configuration constraint if there exists an integrating factor and constraint function such that

$$g_i(q_n, t) a_{ij}(q_n, t) = \frac{\partial}{\partial q_j} f_i(q_n, t), \quad j = 1, 2, \dots, N, \quad (7.2.7a)$$

$$g_i(q_n, t) b_i(q_n, t) = \frac{\partial}{\partial t} f_i(q_n, t). \quad (7.2.7b)$$

If a velocity constraint equation can be shown to satisfy Eqs. (7.2.7) for every  $j$ , it is said to be *holonomic*, which is a Greek word for “integrable.” Constraint equations that do not satisfy these conditions are *nonholonomic*. This terminology arises from the fact that differentiating a configuration constraint yields a velocity constraint, and integration is the inverse process. The terms  $\partial f_i / \partial q_j$  constitute the Jacobian of a set of holonomic constraints. The coefficients  $a_{ij}$  are referred to as the *Jacobian constraint matrix*, even when the constraint conditions are not holonomic. We will encounter this matrix in several contexts.

Ascertaining whether a velocity constraint is holonomic requires that we determine whether, for a given a set coefficient functions  $a_{ij}$ ,  $j = 1, 2, \dots, N$  and  $b_i$ , there is a single integrating factor  $g_i$  and single constraint function  $f_i$  that satisfy Eqs. (7.2.7). Such a determination might not be trivial. If we are lucky, we might be able to do it by inspection. For example, consider the velocity constraint equation  $y\dot{x} - x\dot{y} = 0$ , whose Pfaffian form is  $ydx - xdy = 0$ . The left side is recognizable as the numerator of the perfect differential  $d(x/y)$ . Thus we multiply the Pfaffian form by the integrating factor  $g = 1/y^2$ . The altered form may be integrated, which leads to  $x/y = C$ , where  $C$  is the integration constant. This is the equation of a straight line that intersects the origin, which was not obvious from the original velocity constraint equation.

If we do not succeed in identifying a suitable integrating factor, there is another process we can pursue. Let us multiply Eq. (7.2.7a) for each  $j$  by the corresponding  $dq_j$ , and multiply Eq. (7.2.7b) by  $dt$ , then take the indefinite integral of each. Note that all other variables other than the one for the integral are held constant in the integration. Also, the constant of integration is replaced with a function that can depend on all of the variables, other than the integration variable. Let us denote these functions as  $h_{ij}(q_n, t)$ , where the first subscript,  $i$ , indicates the constraint equation to which it pertains, and the second subscript,  $j$ , indicates the generalized coordinate on which it does *not depend*, with  $h_{it}(q_n)$  being independent of  $t$ . Thus the result of integrating each of Eqs. (7.2.7) may be written as

$$\begin{aligned} f_i(q_n, t) &= \int g_i(q_n, t) a_{ij}(q_n, t) dq_j + h_{ij}(q_n, t), \quad j = 1, 2, \dots, N, \\ f_i(q_n, t) &= \int g_i(q_n, t) b_i(q_n, t) dt + h_{it}(q_n). \end{aligned} \quad (7.2.8)$$

If a single configuration function  $f_i$  and integrating factor  $g_i(q_n, t)$  consistently satisfying each of these  $N + 1$  constraint can be identified, then the velocity constraint is indeed

derivable from a configuration constraint. Conversely, if attempting to satisfy conditions associated with each  $j$  leads to an inconsistency, it must be that the constraint is non-holonomic.

The occurrence of nonholonomic constraint conditions serves to limit our options when we select generalized coordinates. Suppose there are  $J_c$  configuration constraints and  $J_v$  nonholonomic velocity constraints to be satisfied by our choice of  $N$  generalized coordinates. Let  $D$  denote the number of degrees of freedom, so the number of generalized coordinates must be

$$N = D + J_c + J_v. \quad (7.2.9)$$

In principle, we can solve the configuration constraints for  $J_c$  generalized coordinates in terms of the other. Such a solution may be used to eliminate the solved generalized coordinates from the formulation. In contrast, nonholonomic velocity equations cannot be integrated, unless we know the time history of the generalized coordinates, which requires solution of the equations of motion. Thus the presence of nonholonomic constraints means that generalized coordinates must be a constrained set, with the minimum number of generalized coordinates being  $D + J_v$ . Because it might be difficult to determine whether some velocity constraints are holonomic, we treat any system represented by velocity constraint equations as though it were nonholonomic.

The action of the edge of an ice skate blade serves to illustrate these matters. In Fig. 7.6 point  $P$  is the idealized single point of contact between the ice and the curved blade. The blade's position is set by the coordinates  $x_P$  and  $y_P$  of this point and the angle  $\theta$  from the  $x$  axis along which the blade is aligned. Thus we have  $N = 3$ . As shown in the figure, the velocity of the point of contact must be aligned with the blade. Thus it must be that  $\vec{v}_P = \dot{x}_P \vec{i} + \dot{y}_P \vec{j} = v_P (\cos \theta \vec{i} + \sin \theta \vec{j})$ . Eliminating the speed  $v_P$  leads to  $\dot{x}_P \sin \theta - \dot{y}_P \cos \theta = 0$ , which matches the standard velocity constraint form, with  $a_{11} = \cos \theta$ ,  $a_{12} = -\sin \theta$ ,  $a_{13} = 0$ , and  $b_1 = 0$ . This constraint is nonholonomic. To prove this we observe that, if it were holonomic, then  $a_{13}g_1 = 0 = \partial f_1 / \partial \theta$ . This requires that the constraint be independent of  $\theta$ , which contradicts the dependence of  $a_{11}$  and  $a_{12}$ .




Figure 7.6. Velocity constraint for an ice skate blade.

The skate blade exemplifies a fundamental characteristic of systems with nonholonomic constraints. The blade may be set down in any location, which means that any set of values for  $x_P$ ,  $y_P$ , and  $\theta$  is possible. However, when the blade is brought into contact with the ice, the equivalent Pfaffian form of the constraint equations requires that  $dy_P = dx_P \tan \theta$ , which restricts what new position point  $P$  can attain.


Further consideration of this ice skate blade points out a problematic aspect of the term “degrees of freedom” when it is applied to a system having nonholonomic constraints. In Subsection 7.2.1  $N$  was defined as the minimum number of generalized coordinates required to locate a system. Here, setting down the skate corresponds to

## 7.2 Generalized Coordinates and Kinematical Constraints

405

defining the initial conditions of the three generalized coordinates, so it might seem that  $N = 3$ . However, on specification of the three generalized coordinates, their values at the next instant are restricted to be consistent with the Pfaffian form of the differential constraint equations. Because there is one such equation for the skate blade, only two of the three generalized coordinates are independent. Provided one recognizes this aspect, it is consistent to say that the number of degrees of freedom is  $D = N - J_c - J_v$  in any situation.

**EXAMPLE 7.1** The disk rolls without slipping as it is pulled to the right by the yoke. Generalized coordinates are the horizontal distance  $x$  to pin  $B$  and the angle  $\theta$  by which the radial line to pin  $B$  rotates. Derive the velocity constraint equation relating these two variables and show that it is holonomic. What is the corresponding configuration constraint?



Example 7.1

**SOLUTION** This example demonstrates that the kinematical tools developed previously are readily adapted for analytical mechanics formulation. We sequence the generalized coordinates as  $q_1 = x$ ,  $q_2 = \theta$ . There is no doubt that these variables fully locate all parts of the system, but picking both values arbitrarily will lead to a motion in which there is slippage at the point where the disk is in contact with the ground. Let the  $XY$  axes be horizontal and vertical, respectively. The angular velocity of the disk is  $\bar{\omega} = -\dot{\theta}\bar{K}$ , and the condition that there is no slip requires that  $\bar{v}_A = R\dot{\theta}\bar{I}$ . The velocity of pin  $B$  perpendicular to the wall of the groove must match the velocity of the yoke in that direction, so that  $\bar{v}_B \cdot \bar{I} = \dot{x}$ . Because points  $A$  and  $B$  are part of the disk, we therefore have

$$\dot{x} = \bar{v}_B \cdot \bar{I} = (\bar{v}_A + \bar{\omega} \times \bar{r}_{B/A}) \cdot \bar{I}.$$

Substitution of  $\bar{r}_{B/A} = \epsilon \sin \theta \bar{I} + \epsilon \cos \theta \bar{J}$  into the preceding equation shows that the constraint equation relating  $\dot{x}$  and  $\dot{\theta}$  is

$$\dot{x} - (R + \epsilon \cos \theta) \dot{\theta} = 0. \quad \triangleleft$$

All terms have been brought to the left side in this equation in order to match it to the standard linear velocity constraint, Eq. (7.2.4). From this we identify the Jacobian constraint coefficients to be

$$a_{11} = 1, \quad a_{12} = -(R + \epsilon \cos \theta), \quad b_1 = 0.$$



To determine whether the constraint equation is holonomic we multiply it by  $dt$  to convert it to Pfaffian form,


$$dx - (R + \varepsilon \cos \theta) d\theta = 0.$$

There is no need to introduce an integrating factor because  $\cos \theta d\theta = d(\sin \theta)$ . Thus the Pfaffian form is a perfect differential, whose integration yields

$$x - R\theta - \varepsilon \sin \theta = C. \quad \triangleleft$$

The constant  $C$  may be determined by substituting the values of  $x$  and  $\theta$  at some reference location. For example, if  $x = 0$  corresponds to  $\theta = 0$ , then  $C = 0$ . We could have derived this configuration constraint directly by observing that, if there is no slip, then the horizontal distance displaced by the center is  $R\theta$ . Adding the horizontal distance  $\varepsilon \sin \theta$  from the center to the yoke gives  $x$ .

**EXAMPLE 7.2** Two bars, pinned at joint  $B$ , move in the horizontal plane subject only to the restriction that the velocity of end  $C$  must be directed toward end  $A$ . Determine the corresponding velocity constraint. Is this constraint holonomic?



Example 7.2

**SOLUTION** The objective here is to demonstrate the procedure for analyzing constraint conditions that are more complicated than the one in the previous example. Determining whether the velocity constraint is holonomic will require more ingenuity on our part. The position of each bar is uniquely specified by the coordinates of pin  $B$  and the angle of rotation of each bar. Hence we define  $q_1 = x_B$ ,  $q_2 = y_B$ ,  $q_3 = \theta$ ,  $q_4 = \phi$ . The given condition on the velocity of point  $C$  may be written in vector form as

$$\bar{v}_C = v_C \bar{e}_{A/C}.$$

We must express this condition in terms of the generalized coordinates, which means that the speed  $v_C$  should be eliminated. Thus we restate the constraint condition as

$$\bar{v}_C \times \bar{r}_{A/C} = \bar{0}. \quad (1)$$

Points  $B$  and  $C$  are common to the same body, so their velocities are related by

$$\bar{v}_C = \bar{v}_B + \bar{\omega}_{BC} \times \bar{r}_{C/B}.$$

## 7.2 Generalized Coordinates and Kinematical Constraints

409




Figure 7.7. System paths in the configuration space.

configuration paths. Path  $C_1$  corresponds to the actual set of forces for the case in which we are interested, whereas path  $C_2$  represents the motion that is due to a slightly different set of forces. Let  $\hat{r}_1(t)$  be a point on  $C_1$  at a specific instant  $t$ , and let  $\hat{r}_2(t)$  be the corresponding point on  $C_2$  at that instant. Clearly,  $\hat{r}_2(t) - \hat{r}_1(t)$  depends somehow on the difference between the actual and alternative forces. Let us denote this position difference as  $\delta\hat{r}$ . We restrict the difference between the actual and alternative force systems to be infinitesimal solely because doing so will enable us to employ the tools of differential calculus. Consequently  $C_2$  is infinitesimally close to  $C_1$ , so that  $\delta\hat{r}$  also is infinitesimal. It follows from the definition of  $\hat{r}$  that

$$\delta\hat{r} = \delta q_1 \hat{e}_1 + \cdots + \delta q_N \hat{e}_N. \quad (7.2.13)$$

An alternative configuration path that is infinitesimally close to the actual path is called the *variational path*. Figure 7.7 depicts the situation for a three-degree-of-freedom system described by three unconstrained generalized coordinates. We see there that the vector  $d\hat{r}$  represents the actual movement of the system over an elapsed time  $dt$ , whereas  $\delta\hat{r}$  represents the shift in the position at instant  $t$  that would arise if the system followed the variational path rather than the actual path. Because this position shift does not represent an actual movement, we say that  $\delta\hat{r}$  represents a *virtual displacement*. Despite the similar appearance of  $d\hat{r}$  and  $\delta\hat{r}$  in Eqs. (7.2.11) and (7.2.13), respectively, one should recall the very different nature of their definitions. In particular,  $d\hat{r}$  is tangent to the actual configuration path, whereas  $\delta\hat{r}$  is not. The symbol  $\delta$  is used to convey the fact that the associated change in any quantity does not represent the actual manner in which the system evolves.

If the generalized coordinates are unconstrained, then any point in the configuration space is attainable, assuming one has the ability to generate the forces required to cause the configuration path to pass through that point. In contrast, a constraint equation represents a restriction on the values that the generalized coordinates may have. Thus, if a system is described by a set of constrained generalized coordinates, then there are restrictions on the possible paths the system may follow through the configuration space.


The restrictions imposed by a configuration constraint that is independent of time are the easiest to visualize. Such a constraint has the mathematical form  $f_i(q_1, \dots, q_N) = 0$ . Imposing a single mathematical relation on the generalized coordinates restricts the position to lie on a surface in the  $N$ -dimensional configuration space. Because the constraint does not depend on time, this *constraint surface* has a shape that is time invariant.

## 7.2 Generalized Coordinates and Kinematical Constraints

411

The first relation is the Pfaffian form of a configuration constraint, Eq. (7.2.6), in the case of a scleronomic constraint for which  $\partial f_i / \partial t$  is identically zero. It follows from the definition of the generalized velocity vector in Eq. (7.2.12) that a scleronomic velocity constraint requires that  $\hat{v}$ , like  $d\hat{r}$  and  $\delta\hat{r}$ , always be perpendicular to the constraint surface's normal direction.

The situation changes if we consider a *rheonomic constraint*, which is the term used to describe a configuration constraint that is time dependent,  $f_i(q_n, t) = 0$ . Figure 7.9 depicts a rheonomic constraint imposed on three generalized coordinates. At a specific instant  $t$ , the rheonomic constraint requires that any point be situated on a plane in the configuration space. Unlike a scleronomic constraint surface, a rheonomic constraint surface changes with time. That is, each instant  $t$  corresponds to a different surface. The prefix “rheo” is Greek for flowing, which is appropriate because the surface seems to flow through the configuration space in a pictorial representation like Fig. 7.9.



**Figure 7.9.** Virtual and real displacements in the configuration space satisfying a rheonomic constraint condition.

One consequence of the evolving nature of a rheonomic constraint surface is that the actual configuration path cannot lie in the surface corresponding to a specific instant. Rather, each instant  $\hat{r}(t)$  must locate a point on the constraint surface associated with that instant  $t$ . Thus neither the actual displacement  $d\hat{r}$  nor the generalized velocity  $\hat{v}$  is tangent to the normal to the constraint surface at the instant associated with  $\hat{r}(t)$ .

The character of the virtual movement  $\delta\hat{r}$  is quite different. By definition, if the alternative motion described by the variational path is consistent with the rheonomic constraint, then the point  $\hat{r}(t)$  on a variational path will be situated somewhere on the configuration surface associated with that  $t$ , as does the vector  $\hat{r}(t)$  for the actual path. By definition,  $\delta\hat{r}$  extends from the point on the configuration path to the point on a variational path associated with the same instant. It follows that a kinematically admissible virtual displacement  $\delta\hat{r}$  will be situated in the local tangent plane. The condition of tangency is described by stating that  $\delta\hat{r}$  is perpendicular to the normal to the surface. Because  $t$  is constant for the constraint surface at a specific instant, the normal to the

## 7.2 Generalized Coordinates and Kinematical Constraints

413

coordinates. Describe in terms of each set of variables the constraint imposed on the motion of the insect by the condition that it remain on the surface. Describe the constraint condition in each case as a velocity equation and as a configuration constraint. Identify the constraint surface in the configuration space, and the corresponding normal  $\hat{a}_1$  to a point on that surface.

**SOLUTION** The intent of this example is to provide a visualization of the mathematical relations that we have developed. In practice, one seldom would actually examine a constraint surface. We begin with generalized coordinates that are Cartesian coordinates,  $q_1 = x$ ,  $q_2 = y$ ,  $q_3 = z$ . The origin is not specified, so we can select the center of the sphere. The distance from the origin to a point on the surface is the current value of  $r$ , so the configuration constraint corresponding to a set of Cartesian coordinates may be expressed as

$$f_1(x, y, z, t) = x^2 + y^2 + z^2 - c^2 t^2 = 0. \quad \triangleleft$$

We obtain the corresponding velocity constraint by differentiating this equation with respect to  $t$ , which gives

$$x\dot{x} + y\dot{y} + z\dot{z} - c^2 t = 0. \quad \triangleleft$$

This is a linear velocity constraint whose Jacobian constraint coefficients are

$$a_{11} = x, \quad a_{12} = y, \quad a_{13} = z.$$

The generalized coordinates in this case are the physical coordinates, so the configuration space is the physical space. Thus the constraint surface is the expanding sphere. The Jacobian coefficients are the components of  $\hat{a}_1$ , so the normal to this constraint surface is

$$\hat{a}_1 = x\hat{e}_1 + y\hat{e}_2 + z\hat{e}_3. \quad \triangleleft$$

This is identical to the radial vector  $\hat{r}$  from the origin to the point on the sphere represented by the current values of the generalized coordinates, which verifies that  $\hat{a}_1$  is normal to the constraint surface.

Let  $z$  be the axial direction for cylindrical coordinates, so the second case uses  $q_1 = R$ ,  $q_2 = \theta$ ,  $q_3 = z$ . The transverse distance  $R$  is related to the Cartesian coordinates by  $R = (x^2 + y^2)^{1/2}$ , so the configuration constraint equation now is

$$f_1(R, \theta, z, t) = R^2 + z^2 - c^2 t^2 = 0. \quad \triangleleft$$

Differentiating this with respect to  $t$  yields the linear velocity constraint,

$$R\dot{R} + z\dot{z} - c^2 t = 0, \quad \triangleleft$$

for which the Jacobian constraint coefficients are

$$a_{11} = R, \quad a_{12} = 0, \quad a_{13} = z.$$

The corresponding normal to the constraint surface at any instant is

$$\hat{a}_1 = R\hat{e}_1 + z\hat{e}_3. \quad \triangleleft$$

To identify the nature of the configuration constraint surface we replace the physical variables with their equivalent generalized coordinate label, so we have  $q_1^2 + q_3^2 = c^2t^2$ . The axes of the configuration space are Cartesian, so the surface at any  $t$  now is a cylinder whose radius is  $ct$  and whose axial direction is  $\hat{e}_2$ . In this view, the normal direction is  $\hat{a}_1 = q_1\hat{e}_1 + q_3\hat{e}_3$ , which is the line from the origin to the projection of the current position onto the  $q_1q_3$  plane. The fact that  $\hat{a}_1 \cdot \hat{e}_2 = 0$  verifies that  $\hat{a}_1$  actually is normal to the cylindrical constraint surface.

Let  $x = y = z = 0$  be the origin of the spherical coordinates, so the third case is  $q_1 = r$ ,  $q_2 = \phi$ ,  $q_3 = \theta$ . The configuration constraint now is

$$f_1(r, \phi, \theta, t) = r^2 - c^2t^2 = 0, \quad \triangleleft$$

which corresponds to the velocity constraint

$$r\dot{r} - c^2t = 0. \quad \triangleleft$$

The Jacobian constraint coefficients in this case are

$$a_{11} = r, \quad a_{12} = a_{13} = 0,$$

so the normal to the constraint surface at any instant is

$$\hat{a}_1 = r\hat{e}_1.$$

In the  $q_1q_2q_3$  Cartesian space of this set of variables, the configuration surface at any instant is the plane,  $r = q_1 = ct$ ; the other two generalized coordinates are unconstrained. The normal to the constraint surface is  $\hat{e}_1$ , which is parallel to  $\hat{a}_1$ .

### 7.3 EVALUATION OF VIRTUAL DISPLACEMENTS

When we applied the principle of dynamic virtual work earlier in this chapter, the linkage we considered was a holonomic, one-degree-of-freedom system. The notion of a virtual movement was introduced there as the differential position shift that would occur if the single generalized coordinate was given an infinitesimal increment. The analysis of the corresponding point displacements was expedited by the geometrical simplicity of the system. The introduction of the configuration space significantly extends the variety of situations that can be considered. An important aspect of this generalization is the definition of a virtual displacement as the difference between a system's actual position at some instant and the position that would be obtained at that same instant if the forces acting on the system were altered. In the configuration space the virtual displacement  $\delta\hat{r}$  appears as a vector from a point on the configuration path to a point on the variational path, with both points corresponding to the same  $t$ . The symbol  $\delta$  serves to distinguish this displacement from the one that actually occurs. The vector  $\delta\hat{r}$  is taken to be infinitesimal in order to use differential calculus to describe the difference of various quantities

It will be necessary in many cases to express the amount by which angles that define the orientation of bodies, but are not generalized coordinates, change in a virtual movement. The analytical method for virtual displacement requires that we first establish the functional dependence of those angles on the generalized coordinates, for which trigonometric relations such as the laws of sines and cosines often are useful. The result is that, if  $\beta$  represents an angle of orientation, then we have determined the functional dependence  $\beta = f(q_n, t)$ . The virtual rotation is then found by the chain rule to be

$$\delta\beta = \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} f(q_n, t) \right] \delta q_j. \quad (7.3.3)$$

Before we implement the analytical method it is instructive to develop Eq. (7.3.2) in a manner that relates to the earlier discussion of alternative paths in the configuration space. Consider a system at time  $t - dt$ . In the actual movement of the system from this time to time  $t$  the generalized coordinates are incremented by the infinitesimal amounts  $dq_j$ . Time is not constant in the true displacement, so the chain rule for the differential displacement gives

$$d\bar{r}_P = \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} \bar{r}_{P/O}(q_n, t) \right] dq_j + \frac{\partial}{\partial t} \bar{r}_{P/O}(q_n, t) dt. \quad (7.3.4)$$

The values of  $dq_j$  appearing here are those for the true motion.

Suppose we were to alter at time  $t - dt$  and onward the forces applied to the system. This would cause the system to execute a different motion subsequent to time  $t - dt$ . (This different motion corresponds to a variational path in the configuration space that branches off from the true path at time  $t - dt$ .) The set of values of  $dq_j$  in this alternative motion would be different from those of the true motion. Let superscript  $a$  denote a quantity associated with this alternative force system. Thus the displacement corresponding to altering the force system at  $t - dt$  and onward is given by

$$d\bar{r}_P^{(a)} = \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} \bar{r}_{P/O}(q_n, t) \right] dq_j^{(a)} + \frac{\partial}{\partial t} \bar{r}_{P/O}(q_n, t) dt. \quad (7.3.5)$$

The true position of point  $P$  at time  $t$  is given by  $\bar{r}_{P/O}(q_n, t - dt) + d\bar{r}_P$ , whereas the position at the same instant of this point in the alternative motion would be  $\bar{r}_{P/O}(q_n, t - dt) + d\bar{r}_P^{(a)}$ . By definition, the virtual displacement of point  $P$  is the difference between its position in the actual motion and the position it would have at the same instant with a slightly different set of forces. Thus the virtual displacement of the point at time  $t$  is given by  $\delta\bar{r}_P = d\bar{r}_P^{(a)} - d\bar{r}_P$ . Using Eqs. (7.3.4) and (7.3.5) to describe the differential displacements leads to

$$\delta\bar{r}_P = \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} \bar{r}_{P/O}(q_n, t) \right] (dq_j^{(a)} - dq_j). \quad (7.3.6)$$


By definition, the difference between a generalized coordinate value on the actual and variational paths is  $\delta q_j$ , so the preceding equation is identical to Eq. (7.3.2). This

### 7.3 Evaluation of Virtual Displacements

417

strengthens the earlier observation that the study of virtual movement and its associated effects highlights the differences between alternative responses that could possibly occur under the action of different sets of forces.

**EXAMPLE 7.4** Collar  $P$  slides over guide bar  $CD$  that is bent in the shape of a parabola given by  $y = x^2/300$ , where  $x$  and  $y$  are measured in millimeters. This system has one degree of freedom. Determine the virtual displacement of the collar and the virtual rotation of bar  $AB$  corresponding to the following alternatives: (a)  $x$  is a single unconstrained generalized coordinate; (b)  $\theta$  is a single unconstrained generalized coordinate; (c)  $x$  and  $\theta$  are two constrained generalized coordinates.



Example 7.4

**SOLUTION** In addition to demonstrating the procedure for implementing the analytical method, this example illustrates how the choice of generalized coordinates can significantly alter the analysis. That this system has one degree of freedom is demonstrated by the fact that, if  $x$  is given, then  $y$  is known from the equation of bar  $CD$ . Also, the horizontal distance from pivot  $A$  to the collar is  $0.8 - x$  m, which then sets the value of  $\theta$ . Thus we have

$$y = \frac{x^2}{0.3}, \text{ where } x \text{ and } y \text{ are in meters,}$$

$$\tan \theta = \frac{y}{0.8 - x} = \frac{x^2}{0.24 - 0.3x}.$$

In the first approach,  $q_1 = x$ . Point  $O$  is the origin at which  $x = y = 0$ . We express the position of point  $P$  and angle  $\theta$  as functions of  $x$ :

$$\bar{r}_{P/O} = x\bar{i} + \frac{x^2}{0.3}\bar{j}, \quad \theta = \tan^{-1} \left( \frac{x^2}{0.24 - 0.3x} \right).$$

Differentiating each with respect to  $x$  yields

$$\delta \bar{r}_P = \left( \bar{i} + \frac{x}{0.15}\bar{j} \right) \delta x,$$

$$\delta \theta_{AB} = -\delta \theta \bar{k} = -\frac{d}{dx} \left[ \tan^{-1} \left( \frac{x^2}{0.24 - 0.3x} \right) \right] \delta x$$

$$\times \delta x \bar{k} = - \left[ \frac{2x(0.24 - 0.3x) + 0.3x^2}{(0.24 - 0.3x)^2 + x^4} \right] \bar{k} \delta x.$$

The second formulation requires that we express  $\bar{r}_{P/O}$  in terms of  $\theta$ . The inverse of the preceding expression for  $\theta$  is a quadratic equation for  $x$  at a given  $\theta$ ,

$$x^2 + (0.3 \tan \theta) x - 0.24 \tan \theta = 0,$$

from which we find

$$x = -0.15 \tan \theta + \left[ (0.15 \tan \theta)^2 + 0.24 \tan \theta \right]^{1/2},$$

where the positive sign is associated with the square root because  $x > 0$ . We differentiate this with respect to  $\theta$  to find

$$\delta x = \left\{ -0.15 + \frac{0.0225 \tan \theta + 0.12}{\left[ (0.15 \tan \theta)^2 + 0.24 \tan \theta \right]^{1/2}} \right\} \frac{1}{(\cos \theta)^2} \delta \theta.$$

The virtual displacement in the  $y$  direction is given by

$$\delta y = \left( \frac{dy}{dx} \right) \delta x = \frac{x}{0.15} \delta x.$$

We replace  $x$  and  $\delta x$  with their representations in terms of the generalized coordinate  $\theta$ , which yields

$$\begin{aligned} \delta \bar{r}_P &= \delta x \bar{i} + \delta y \bar{j} = \left( \bar{i} + \frac{x}{0.15} \bar{j} \right) \delta x \\ &= \left( \bar{i} + \frac{\left\{ -0.15 \tan \theta + \left[ (0.15 \tan \theta)^2 + 0.24 \tan \theta \right]^{1/2} \right\}}{0.15} \bar{j} \right) \\ &\quad \times \left\{ -0.15 + \frac{0.045 \tan \theta + 0.24}{\left[ (0.15 \tan \theta)^2 + 0.24 \tan \theta \right]^{1/2}} \right\} \frac{1}{(\cos \theta)^2} \delta \theta. \end{aligned} \quad \triangleleft$$

The virtual rotation of bar  $AB$  is  $\delta \bar{\theta}_{AB} = -\delta \theta \bar{k}$ , so that evaluation is simpler than the first case. Nevertheless, there is no doubt that using  $\theta$  as the generalized coordinate leads to much more complicated mathematical relations than those obtained when  $x$  is used.

Using  $q_1 = x$ ,  $q_2 = \theta$  as constrained generalized coordinates actually is the simplest approach. These variables are related by the configuration constraint equation obtained at the outset of this analysis. What makes the use of constrained generalized coordinates easier is that, after their constraint equation is identified, the coordinates are considered to be independent until all elements of the equations of motion are synthesized. Thus the position of the collar is described as it was in the



### 7.3 Evaluation of Virtual Displacements

419

first case,  $\bar{r}_{P/O} = x\bar{i} + (x^2/0.3)\bar{j}$ , and  $\theta$  gives the orientation of bar  $AB$ . Then the virtual displacement and rotation are given by

$$\begin{aligned}\delta\bar{r}_P &= \left(\bar{i} + \frac{x}{0.15}\bar{j}\right)\delta x, \\ \delta\theta_{AB} &= -\delta\theta\bar{k}.\end{aligned}\quad \triangleleft$$

A conclusion to be carried away from this example is that some choices for generalized coordinates are better than others, but that any set can lead to a successful analysis if one perseveres. Also, in certain circumstances it might be advantageous to use constrained generalized coordinates.

#### 7.3.2 Kinematical Method

The analytical method for evaluating virtual displacements requires that we explicitly differentiate the representation of position as a function of the generalized coordinates. Simple systems, such as those whose parts form isosceles triangles or right angles, are relatively easy to describe geometrically, and the resulting expressions are likely to be quite easy to differentiate. However, increasing the complexity of the geometry can lead to substantial complication. One of the primary reasons for developing kinematical formulas is to address such difficulties. Those formulas represent standard derivatives.

The essence of the kinematical approach for virtual displacement is to exploit similarities between the mathematical forms of velocity and virtual displacement. Equation (7.3.4) expresses the true differential displacement of a point in terms of the generalized coordinates and their increments  $dq_j$  over an infinitesimal time interval. Dividing that expression by  $dt$  gives an expression for the velocity of a point, which is accompanied in the following by Eq. (7.3.2) to highlight the similarity between velocity and virtual displacement:

$$\begin{aligned}\bar{v}_P &= \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} \bar{r}_{P/O}(q_n, t) \right] \dot{q}_j + \frac{\partial}{\partial t} \bar{r}_{P/O}(q_n, t), \\ \delta\bar{r}_P &= \sum_{j=1}^N \left[ \frac{\partial}{\partial q_j} \bar{r}_{P/O}(q_n, t) \right] \delta q_j.\end{aligned}\quad (7.3.7)$$

These equations indicate that  $\bar{v}_P$  depends linearly on the generalized velocities  $\dot{q}_j$ , whereas the virtual displacement depends linearly on the virtual increments  $\delta q_j$ . The significant aspect of this similarity is that the coefficient associated with a specific  $\dot{q}_j$  is the same as the coefficient of the corresponding  $\delta q_j$  and that this coefficient is a vector function of generalized coordinates and time. The fact that the coefficients are derivatives of the position is unimportant, so we denote them as  $\bar{v}_{Pj}(q_n, t)$  and let  $\bar{v}_{pt}(q_n, t)$

### 7.3 Evaluation of Virtual Displacements

423

position of this point is given by

$$\bar{r}_{P/C} = r_1 (-\sin \theta \bar{i} - \cos \theta \bar{j}) = r_1 \left[ -\sin \left( \frac{r_2}{r_1} \phi \right) \bar{i} - \cos \left( \frac{r_2}{r_1} \phi \right) \bar{j} \right],$$


so that

$$\begin{aligned} \bar{v}_P &= \bar{v}_C + \omega \bar{k} \times \bar{r}_{P/C} \\ &= (r_1 + r_2) \dot{\phi} \bar{i} + \left[ -\frac{(r_1 + r_2)}{r_1} \dot{\phi} \right] \left[ r_1 \cos \left( \frac{r_2}{r_1} \phi \right) \bar{i} - r_1 \sin \left( \frac{r_2}{r_1} \phi \right) \bar{j} \right]. \end{aligned}$$

The kinematical method indicates that  $\bar{v}_P$  should be replaced with  $\delta \bar{r}_P$  and  $\dot{\phi}$  with  $\delta \phi$ . Furthermore, we observe that  $\bar{v}_P = 0$  if  $\dot{\phi} = 0$ , which means that there are no terms to drop. Thus we find that the virtual displacement of point  $P$  is

$$\delta \bar{r}_P = (r_1 + r_2) \left\{ \left[ 1 - \cos \left( \frac{r_2}{r_1} \phi \right) \right] \bar{i} + \sin \left( \frac{r_2}{r_1} \phi \right) \bar{j} \right\} \delta \phi. \quad \triangleleft$$

**EXAMPLE 7.6** The angles  $\theta_1$ ,  $\theta_2$ , and  $\theta_3$  locate the links of the mechanism, but there is a geometrical relation that these angles must satisfy. Determine the virtual displacement of collar  $C$ , which slides along bar  $DE$  under each of the following conditions: (a)  $\theta_1$  and  $\theta_2$  are unconstrained generalized coordinates; (b)  $\theta_1$  and  $\theta_3$  are unconstrained generalized coordinates; and (c)  $\theta_1$  is driven by a motor such that it is a known function of time, and  $\theta_2$  is an unconstrained generalized coordinate; and (d)  $\theta_3$  is driven by a motor such that it is a known function of time, and  $\theta_1$  is an unconstrained generalized coordinate.



Example 7.6

**SOLUTION** The purpose here is to illustrate the variety of conditions that can arise in a system and the significant effect that these conditions can have on the formulation of virtual displacement. In Part (a) we have  $q_1 = \theta_1$  and  $q_2 = \theta_2$ . These variables uniquely locate the collar, so the fact that  $\theta_3$  depends on the generalized coordinates is irrelevant to the evaluation of the virtual displacement of the collar. We follow the kinematical method by describing the velocity of the collar in terms of the generalized coordinates:

$$\begin{aligned} \bar{v}_C &= \bar{v}_B + \bar{\omega}_{BC} \times \bar{r}_{C/B} = \dot{\theta}_1 \bar{k} \times \bar{r}_{B/A} + \dot{\theta}_2 \bar{k} \times \bar{r}_{C/B} \\ &= -(L_1 \dot{\theta}_1 \sin \theta_1 + L_2 \dot{\theta}_2 \sin \theta_2) \bar{i} + (L_1 \dot{\theta}_1 \cos \theta_1 + L_2 \dot{\theta}_2 \cos \theta_2) \bar{j}. \end{aligned} \quad (1)$$

We obtain the virtual displacement by replacing the rate variables with the corresponding virtual increments. It is useful to group the coefficients of  $\delta\theta_1$  and  $\delta\theta_2$ , so we find

$$\begin{aligned}\delta\bar{r}_C = & (-L_1\dot{\theta}_1 \sin\theta_1\bar{i} + L_1\dot{\theta}_1 \cos\theta_1\bar{j})\delta\theta_1 \\ & + (-L_2\dot{\theta}_2 \sin\theta_2\bar{i} + L_2\dot{\theta}_2 \cos\theta_2\bar{j})\delta\theta_2.\end{aligned}\quad (2)$$

In Part (b) we have  $q_1 = \theta_1$  and  $q_2 = \theta_3$ . We cannot describe the position of the collar  $C$  in terms of only the generalized coordinates without considering how  $\theta_2$  depends on  $\theta_1$  and  $\theta_3$ . To that end we form the tangent of  $\theta_3$  in terms of horizontal and vertical distances constructed along bars  $AB$  and  $BC$ . This gives

$$\tan\theta_3 = \frac{L_1 \sin\theta_1 + L_2 \sin\theta_2}{L_1 \cos\theta_1 + L_2 \cos\theta_2 - H},$$

which may be written as

$$\sin\theta_2 = \tan\theta_3 \cos\theta_2 + \tan\theta_3 \left( \frac{L_1}{L_2} \cos\theta_1 - \frac{H}{L_2} \right) - \frac{L_1}{L_2} \sin\theta_1. \quad (3)$$

We need to solve this relation for  $\theta_2$  in terms of  $\theta_1$  and  $\theta_3$ , which we can do by using symbolic software or by using  $\sin\theta_2 \equiv [1 - (\cos\theta_2)^2]^{1/2}$  to obtain a quadratic equation for  $\cos\theta_2$ . The specific solution is unimportant for the present purpose, so we merely denote it in functional form as

$$\theta_2 = f(\theta_1, \theta_3). \quad (4)$$

We proceed to the analysis of  $\bar{v}_C$ , for which we recognize that we need to determine  $\dot{\theta}_2$  in terms of the generalized coordinates and velocities. We could obtain this result by differentiating Eq. (4), but the function is quite complicated. Instead we carry out a velocity analysis of the collar, based on its being constrained to move radially outward at an unknown rate  $u$  relative to bar  $DE$ . This means that  $\bar{v}_C = u\bar{e}_{E/D} + \bar{\omega}_{DE} \times \bar{r}_{C/D}$ . We describe  $\bar{r}_{C/D}$  in terms of  $\theta_1$  and  $\theta_2$  to avoid introducing the distance from pin  $D$  to the collar as another geometrical variable to eliminate. Comparing this viewpoint for  $\bar{v}_C$  with Eq. (1) gives

$$\begin{aligned}\bar{v}_C = & u(\cos\theta_3\bar{i} + \sin\theta_3\bar{j}) + \dot{\theta}_3\bar{k} \times [(L_1 \cos\theta_1 + L_2 \cos\theta_2)\bar{i} \\ & + (L_1 \sin\theta_1 + L_2 \sin\theta_2)\bar{j}] \\ = & -(L_1\dot{\theta}_1 \sin\theta_1 + L_2\dot{\theta}_2 \sin\theta_2)\bar{i} + (L_1\dot{\theta}_1 \cos\theta_1 + L_2\dot{\theta}_2 \cos\theta_2)\bar{j}.\end{aligned}$$

Matching like components in the preceding equation gives two simultaneous equations that may be solved for  $u$  and  $\dot{\theta}_2$  in terms of  $\theta_1$ ,  $\theta_2$ ,  $\theta_3$ ,  $\dot{\theta}_1$ , and  $\dot{\theta}_3$ . Equation (4) describes  $\theta_2$ . Thus the result of this kinematical analysis has the form

$$\dot{\theta}_2 = g_1(\theta_1, \theta_3)\dot{\theta}_1 + g_3(\theta_1, \theta_3)\dot{\theta}_3. \quad (5)$$

The detailed expressions are intricate, so we merely monitor how the analysis builds on them. Substitution of Eq. (5) into Eq. (1) gives  $\bar{v}_C$  in terms of the generalized

### 7.3 Evaluation of Virtual Displacements

425

velocities for this case:

$$\begin{aligned}\bar{v}_C = & \left\{ -[L_1 \sin \theta_1 + L_2 g_1(\theta_1, \theta_3) \sin(f(\theta_1, \theta_3))] \bar{i} \right. \\ & + [L_1 \cos \theta_1 + L_2 g_1(\theta_1, \theta_3) \cos(f(\theta_1, \theta_3))] \bar{j} \left. \right\} \dot{\theta}_1 \\ & + \left\{ -L_2 g_3(\theta_1, \theta_3) \sin(f(\theta_1, \theta_3)) \bar{i} + L_2 g_3(\theta_1, \theta_3) \cos(f(\theta_1, \theta_3)) \bar{j} \right\} \dot{\theta}_3.\end{aligned}$$

To obtain the virtual displacement of the collar we replace the generalized velocities with the corresponding virtual increments, which gives

$$\begin{aligned}\delta \bar{r}_C = & \left\{ -[L_1 \sin \theta_1 + L_2 g_1(\theta_1, \theta_3) \sin(f(\theta_1, \theta_3))] \bar{i} \right. \\ & + [L_1 \cos \theta_1 + L_2 g_1(\theta_1, \theta_3) \cos(f(\theta_1, \theta_3))] \bar{j} \left. \right\} \delta \theta_1 \\ & + \left\{ -L_2 g_3(\theta_1, \theta_3) \sin(f(\theta_1, \theta_3)) \bar{i} + L_2 g_3(\theta_1, \theta_3) \cos(f(\theta_1, \theta_3)) \bar{j} \right\} \delta \theta_3.\end{aligned}\quad (6)$$

It is obvious that analyzing  $\delta \bar{r}_C$  with  $\theta_1$  and  $\theta_3$  as generalized coordinates is much more difficult than it is if  $\theta_1$  and  $\theta_2$  are the generalized coordinates. The same would be true for most other steps ultimately leading to the equations of motion. Thus it is wise to assess at the outset of a solution the difficulty of eliminating variables that are not generalized coordinates.

The situation in Part (c) is like that of Part (a), except that  $\theta_1$  is specified, rather than a generalized coordinate. Thus the terms in Eq. (1) that contain  $\dot{\theta}_1$  correspond to the  $\bar{v}_{P_1}$  term in Eq. (7.3.8). In accord with the kinematical method, in Eq. (1) we replace  $\bar{v}_C$  with  $\delta \bar{r}_C$  and  $\dot{\theta}_2$  with  $\delta \theta_2$ , and ignore the  $\dot{\theta}_1$  term. The resulting virtual displacement is


$$\delta \bar{r}_C = (-L_2 \dot{\theta}_2 \sin \theta_2 \bar{i} + L_2 \dot{\theta}_2 \cos \theta_2 \bar{j}) \delta \theta_2. \quad \triangleleft$$

This is the same as Eq. (2) when  $\delta \theta_1 = 0$ , which is consistent with the definition of a virtual displacement as corresponding to fixed  $t$ , so that  $\theta_1$  does not change.

Similar to the preceding case, the analysis for Part (d) may be performed by referring back to Part (b). Because  $\theta_3$  is not a generalized coordinate in this case, we set  $\delta \theta_3 = 0$  in Eq. (6), which reduces the virtual displacement to

$$\begin{aligned}\delta \bar{r}_C = & \left\{ -[L_1 \sin \theta_1 + L_2 g_1(\theta_1, \theta_3) \sin(f(\theta_1, \theta_3))] \bar{i} \right. \\ & + [L_1 \cos \theta_1 + L_2 g_1(\theta_1, \theta_3) \cos(f(\theta_1, \theta_3))] \bar{j} \left. \right\} \delta \theta_1.\end{aligned}\quad \triangleleft$$

An overview of the cases considered here shows that eliminating constrained variables can lead to significant complications. An alternative not listed in the problem statement is to use all three angles as constrained generalized coordinates, rather than trying to eliminate one variable. In each case a constraint equation relating the angles, specifically Eq. (3) or its equivalent, would need to be enforced as a separate condition. Specification of the rotation of  $\theta_1$  or  $\theta_3$  as a function of time would lead to an additional constraint equation.



Example 7.8

**SOLUTION** This example of spatial motion uses the kinematical method for virtual displacements. There is no need to evaluate acceleration, so we may use any convenient coordinate system. We attach  $xyz$  to the gimbal with its origin at center  $C$ , such that the  $y$  axis is aligned with shaft  $AB$ , upward, and the  $z$  axis is aligned with the axis of the disk, leftward in the sketch. The angular velocities of the gimbal and of the disk are

$$\bar{\omega}_{\text{gimbal}} = \dot{\psi} \bar{e}_{\psi} + \dot{\beta} \bar{e}_{A/B}, \quad \bar{\omega}_{\text{disk}} = \bar{\omega}_{\text{gimbal}} + \dot{\phi} \bar{k}.$$

We describe the unit vectors in terms of the generalized coordinates,

$$\bar{e}_{\psi} = -\sin \beta \bar{i} + \cos \beta \bar{k}, \quad \bar{e}_{A/B} = \bar{j},$$

from which we find that

$$\bar{\omega}_{\text{gimbal}} = -\dot{\psi} \sin \beta \bar{i} + \dot{\beta} \bar{j} + \dot{\psi} \cos \beta \bar{k}, \quad \bar{\omega}_{\text{disk}} = -\dot{\psi} \sin \beta \bar{i} + \dot{\beta} \bar{j} + (\dot{\psi} \cos \beta + \dot{\phi}) \bar{k}.$$

To describe the velocity of point  $D$  where  $\bar{F}$  is applied, we proceed along the gimbal from collar  $A$ , whose center is stationary, to center  $C$ , and then onward to  $D$  along the disk, which leads to

$$\bar{v}_C = \bar{\omega}_{\text{gimbal}} \times \bar{r}_{C/A}, \quad \bar{v}_D = \bar{v}_C + \bar{\omega}_{\text{disk}} \times \bar{r}_{D/C}.$$

The positions are  $\bar{r}_{C/A} = -(3h/2) \bar{j}$ ,  $\bar{r}_{D/C} = R \sin \phi \bar{i} - R \cos \phi \bar{j}$ , so that

$$\begin{aligned} \bar{v}_D = & \left[ \dot{\psi} \cos \beta \left( \frac{3h}{2} + R \cos \phi \right) + \dot{\phi} R \cos \phi \right] \bar{i} + [(\dot{\psi} \cos \beta + \dot{\phi}) R \sin \phi] \bar{j} \\ & + \left[ \dot{\psi} \left( \frac{3h}{2} + R \cos \phi \right) \sin \beta - \dot{\beta} R \sin \phi \right] \bar{k}. \end{aligned}$$

We obtain the virtual displacement by replacing rate variables with virtual increments:

$$\begin{aligned} \delta \bar{r}_D = & \left[ \delta \psi \cos \beta \left( \frac{3h}{2} + R \cos \phi \right) + \delta \phi R \cos \phi \right] \bar{i} + [(\delta \psi \cos \beta + \delta \phi) R \sin \phi] \bar{j} \\ & + \left[ \delta \psi \left( \frac{3h}{2} + R \cos \phi \right) \sin \beta - \delta \beta R \sin \phi \right] \bar{k}. \end{aligned}$$

## 7.4 Generalized Forces

431

The force is perpendicular to  $\bar{r}_{D/C}$  in the  $xy$  plane, so its component representation is

$$\bar{F} = -F \cos \phi \bar{i} - F \sin \phi \bar{j},$$

which leads to the virtual work being

$$\begin{aligned} \delta W = \bar{F} \cdot \delta \bar{r}_D &= (-F \cos \phi) \left[ \delta \psi \cos \beta \left( \frac{3h}{2} + R \cos \phi \right) + \delta \phi R \cos \phi \right] \\ &\quad + (-F \sin \phi) (\delta \psi \cos \beta + \delta \phi) R \sin \phi \\ &= \left[ -F \cos \beta \left( \frac{3h}{2} \cos \phi + R \right) \right] \delta \psi - F R \delta \phi. \end{aligned}$$

The standard form of virtual work in this case is  $\delta W = Q_1 \delta \psi + Q_2 \delta \beta + Q_3 \delta \phi$ . Matching this to the actual  $\delta W$  yields

$$Q_1 = -F \cos \beta \left( \frac{3h}{2} \cos \phi + R \right), \quad Q_2 = 0, \quad Q_3 = -FR. \quad \triangleleft$$

Observe that  $Q_3$  is the moment of  $\bar{F}$  about the axis of the disk, which is sensible because that moment is what causes  $\phi$  to change. The value of  $Q_2$  is zero because  $\bar{F}$  intersects the line of shaft  $AB$ , so it does not have a tendency to change  $\beta$ . The first generalized force represents the tendency of  $\bar{F}$  to change  $\psi$ , which we would expect to be the moment of  $\bar{F}$  about the horizontal shaft. It is not difficult to verify that  $Q_1 = (\bar{r}_{D/A} \times \bar{F}) \cdot \bar{e}_\psi$ .

### 7.4.2 Relation Between Constraint Forces and Conditions

The terms “reactions” and “constraint forces” are synonyms describing the forces and couples that enforce constraint equations, either by preventing motion or by imposing a motion that is a specified function of time. Whereas the Newton–Euler formulation requires separate consideration of the forcing effect and the kinematical restriction of a constraint, we will find here that knowledge of the velocity constraint equation will suffice to describe the effect of the associated constraint force. We begin by considering the case in which a particle is constrained to move along a specified curve. A kinematical description using tangent-normal components indicates that the position of this particle is given by the arc length  $s(t)$  measured along the path, which we select to be the generalized coordinate. The resultant force may be resolved into components  $\Sigma F_t$ ,  $\Sigma F_n$ , and  $\Sigma F_b$  in the tangent, normal, and binormal directions, respectively. The latter two include constraint forces because they prevent the particle from moving perpendicularly to the path. In a virtual movement that increases  $s$  by  $\delta s$ , the particle moves in the tangential direction by that amount, so  $\delta \bar{r} = \delta s \bar{e}_t$ . The corresponding virtual work is  $\delta W = \Sigma F_t \delta s$ . In this simple situation a virtual displacement that is kinematically admissible, meaning that it obeys the motion constraints imposed on the system, leads to the constraint forces doing no work.

We encountered a similar result when we applied the principle of dynamic virtual work in Subsection 7.1.2. The free-body diagram in Fig. 7.2 showed constraint forces  $\bar{A}_x$  and  $\bar{A}_y$  that prevent movement of pin  $A$ , and vertical constraint force  $\bar{C}_y$  exerted by the horizontal guidebar on collar  $C$  to prevent movement in the vertical direction. The virtual movement used there kept the pin stationary and moved the collar horizontally. Such a movement is kinematically admissible, and the virtual work done by the constraint forces again was found to be zero.

This observation that the virtual work done by a reaction is zero is not a chance occurrence. In fact, it provides a consistent definition of a constraint force. (Once again, constraint force is the preferred term, rather than reaction.) Specifically,

*A force or couple is a constraint force associated with a kinematical constraint condition if, and only if, it does no work in a virtual movement that is consistent with the constraint.*

An important corollary applies when the generalized coordinates are unconstrained, which can be the case only for a holonomic system. In such a situation, any set of generalized coordinate values is kinematically possible, so any virtual displacement will be kinematically admissible. Consequently,

*The virtual work done by constraint forces always is zero when unconstrained generalized coordinates are used to describe a holonomic system.*

Let us now consider what happens when we use constrained generalized coordinates. A virtual displacement entails incrementing each generalized coordinate by an arbitrary amount  $\delta q_j$ , whereas Eq. (7.2.18) indicates that the  $\delta q_j$  values cannot all be selected arbitrarily if the virtual displacement is to be consistent with the  $i$ th constraint equation. It follows that


*When constrained generalized coordinates are used to describe the position of a system, constraint forces will do virtual work.*

It is necessary in that case to account for the contribution of constraint forces to each of the generalized forces. One way of doing so is to treat constraint forces as forces that are known when the virtual work is formed. However, a simpler alternative is available.

In the physical world each constraint equation has an associated constraint force or couple. Let us denote as  $R_j^{(i)}$ ,  $i = 1, 2, \dots, J$ , the contribution of the  $i$ th constraint force to the  $j$ th generalized force. In the configuration space the generalized forces are the components of the vector  $\hat{Q}$  representing the forcing effect on the system. Let  $\hat{R}^{(i)}$  denote the portion that is attributable to the constraint, so that

$$\hat{R}^{(i)} = R_1^{(i)}\hat{e}_1 + \dots + R_N^{(i)}\hat{e}_N. \quad (7.4.9)$$

As noted earlier, if the  $\delta q_j$  values are selected arbitrarily, the virtual displacement will not be kinematically admissible. In the configuration space, this would be represented by a displacement vector  $\delta\hat{r}$  that may point in any direction. Let us consider the special situation in which the  $\delta q_j$  values are selected such that the virtual displacement is consistent with the  $i$ th constraint equation. Equation (7.2.20) indicates that  $\delta\hat{r}$  then must



**Figure 7.10.** Generalized coordinates for a system consisting of two spheres connected by a rigid bar.

Establishing the proportionality factor  $\sigma_i$  in a specific case requires determination of the  $c_{ij}$  coefficients.

Let us examine a few situations that illustrate when constraint forces may be avoided in the formulation. First, consider Fig. 7.10(a), where two tiny spheres, modeled as particles, are constrained to move in the  $xy$  plane. The spheres are connected by a massless rigid bar. As a result, the distance  $L$  is constant, so  $(x_A, y_A, \phi)$  constitute a set of unconstrained generalized coordinates.

Because the bar is massless, it can exert only an axial force on each particle, as shown in the free-body diagram for each particle, Fig. 7.10(b). To evaluate the virtual work done by this force, we employ the kinematical method to relate the virtual displacements of the spheres. The velocities are related by

$$\bar{v}_B = \bar{v}_A + (\dot{\phi} \bar{k}) \times \bar{r}_{B/A} = \bar{v}_A + L\dot{\phi} \bar{e}_\phi, \quad (7.4.17)$$

so the virtual displacements are related by

$$\delta \bar{r}_B = \delta \bar{r}_A + L\delta\phi \bar{e}_\phi. \quad (7.4.18)$$

The virtual work done by the axial force is therefore

$$\delta W = (-F\bar{e}_R) \cdot \delta \bar{r}_A + F\bar{e}_R \cdot \delta \bar{r}_B = F\bar{e}_R \cdot L\delta\phi \bar{e}_\phi = 0. \quad (7.4.19)$$

The axial force does no work in this situation because it is the constraint force required to keep  $L$  constant. If we employ a set of constrained generalized coordinates, this constraint will be violated. For example, suppose that  $(x_A, y_A, x_B, y_B)$  are used as generalized coordinates. The constraint condition that the bar distance between the spheres must be  $L$  gives a configuration constraint equation,  $(x_B - x_A)^2 + (y_B - y_A)^2 = L^2$ . The velocity form of this equation is

$$\begin{aligned} a_{11}\dot{x}_A + a_{12}\dot{y}_A + a_{13}\dot{x}_B + a_{14}\dot{y}_B &= 0, \\ a_{11} &= -a_{13} = x_A - x_B, \quad a_{12} = -a_{14} = y_A - y_B, \end{aligned} \quad (7.4.20)$$

where the leading subscript 1 denotes the first constraint equation. The virtual displacements of the spheres now are unrelated, being given by

$$\delta \bar{r}_A = \delta x_A \bar{i} + \delta y_A \bar{j}, \quad \delta \bar{r}_B = \delta x_B \bar{i} + \delta y_B \bar{j}. \quad (7.4.21)$$

The virtual work done by the axial force in this case is

$$\delta W = (-F\bar{e}_R) \cdot \delta \bar{r}_A + F\bar{e}_R \cdot \delta \bar{r}_B = F \cos \phi (\delta x_B - \delta x_A) + F \sin \phi (\delta y_B - \delta y_A). \quad (7.4.22)$$



## 7.4 Generalized Forces

435

We must eliminate  $\phi$  from this expression because it is not a generalized coordinate. Forming a right triangle whose hypotenuse is  $L$  shows that  $\cos \phi = (x_B - x_A)/L$  and  $\sin \phi = (y_B - y_A)/L$ . We substitute these expressions into  $\delta W$  and match the result to the standard form,  $\delta W = R_1^{(1)}\delta x_A + R_2^{(1)}\delta y_A + \dots$ , from which we find that the contributions of the axial force to the generalized forces are

$$\begin{aligned} R_1^{(1)} &= -R_3^{(1)} = -\frac{x_B - x_A}{L}F, \\ R_2^{(1)} &= -R_4^{(1)} = -\frac{y_B - y_A}{L}F. \end{aligned} \quad (7.4.23)$$

The virtual work is not zero, as expected. Furthermore, we observe that these expressions fit Eq. (7.4.14), with the constraint force  $F = C_1$  and

$$c_{11} = -c_{13} = -\frac{x_B - x_A}{L}, \quad c_{12} = -c_{14} = -\frac{y_B - y_A}{L}. \quad (7.4.24)$$

This is consistent with Eqs. (7.4.16), for we see that

$$\frac{a_{j1}}{c_{j1}} = \sigma_1 = L, \quad j = 1, 4. \quad (7.4.25)$$

It follows from Eqs. (7.4.16) that  $\lambda_1 = F/L$ .

The case in which the spheres in Fig. 7.10 are connected by a spring offers an instructive contrast. Instead of being an unknown reaction that restricts motion, the axial force within a spring is known in terms of the deformation,  $\Delta = L - L_0$ , where  $L_0$  is the undeformed length. There would be no constraints on the planar motion of the spheres in this case, so the system would have four degrees of freedom, and  $(x_A, y_A, x_B, y_B)$  would be unconstrained generalized coordinates. The contributions of the axial spring force to each generalized coordinate in this case are still given by Eqs. (7.4.23), except that  $F = k\Delta$ , which means that the force is now known in terms of the generalized coordinates. This exemplifies the general fact that

*Forces and couples are either unknown constraint effects that impose a kinematical condition, or else they are known as function of time and/or the generalized coordinates, in which case they do not kinematically restrict the motion.*

The two-particle system provides an important analogy for the general task of modeling. Let the spheres represent two adjacent particles in a body. Correspondingly, the force  $\bar{F}$  represents the stress resultant exerted between them. When a body is considered to be rigid, then the internal stress resultants are equivalent to reactions that maintain the particles at fixed relative distances. These forces do no virtual work. In contrast, when deformation of a body must be considered, the internal stress resultants are equivalent to spring forces. Thus derivation of the equations of motion for deformable bodies requires consideration of the effects of internal stresses.

Connections between bodies are an important element in most dynamic systems. They impose kinematical conditions on the relative movement of the parts they connect. According to the definition of a constraint force, the force or couple associated with a connection will do no virtual work if the virtual movement does not violate the condition imposed by that connection. An important example of this aspect is described




Figure 7.11. Constraint forces associated with a pin connection.

by Fig. 7.11, where two bars are connected by a pin. Let  $B1$  and  $B2$  denote the connection point on the respective bars. The pin exerts opposing horizontal and vertical forces on each bar, which enforce the condition that points  $B1$  and  $B2$  move in unison. The corresponding virtual work is

$$\delta W = (B_x \bar{i} + B_y \bar{j}) \cdot \delta \bar{r}_{B1} + (-B_x \bar{i} - B_y \bar{j}) \cdot \delta \bar{r}_{B2}. \quad (7.4.26)$$

If the constraint imposed by the pin is not violated in a virtual displacement, then the virtual displacements of the connection points will be identical,  $\delta \bar{r}_{B2} = \delta \bar{r}_{B1}$ , and  $\delta W = 0$ . Thus, if the virtual movement of a system maintains the integrity of a pin connection, the forces exerted by the pin will not contribute to the generalized forces.

Another connection that is commonly encountered is a sliding collar, such as the one in Fig. 7.12. The collar can move only inward or outward relative to bar  $CD$ , corresponding to changing distance  $R$  measured along bar  $CD$ . In a virtual movement that is consistent with this constraint, the virtual displacements of points  $B1$  on bar  $CD$  and  $B2$  on the collar are related by

$$\delta \bar{r}_{B2} = \delta \bar{r}_{B1} + \delta R \bar{e}_R. \quad (7.4.27)$$

If friction is negligible,  $\bar{f} \equiv \bar{0}$ , then the only force that is developed between the collar and bar  $CD$  is the normal reaction  $\bar{N}$ . The virtual work done by this force is

$$\delta W = (N \bar{e}_\phi) \cdot \delta \bar{r}_{B1} + (-N \bar{e}_\phi) \cdot \delta \bar{r}_{B2}. \quad (7.4.28)$$

If the virtual displacement is consistent with the constraint imposed by the collar, so that Eq. (7.4.27) holds, then we find that  $\delta W = (-N \bar{e}_\phi) \cdot \delta R \bar{e}_R = 0$ . Thus the force associated with a collar connection will not appear in the generalized forces if the virtual movement satisfies the kinematical restriction imposed by the collar.

Not all forces associated with a connection are associated with a constraint condition. For example, the friction force  $\bar{f}$  in Fig. 7.12 acts in opposition to the direction in which each contacting surface moves relative to the other. (The situation appearing in




Figure 7.12. Forces associated with a collar connection.

## 7.4 Generalized Forces

437

this figure corresponds to the collar sliding outward,  $\dot{R} > 0$ .) The virtual work in this case would be

$$\delta W = (N\bar{e}_\phi + f\bar{e}_R) \cdot \delta\bar{r}_{B1} + (-N\bar{e}_\phi - f\bar{e}_R) \cdot \delta\bar{r}_{B2}. \quad (7.4.29)$$

Even if the the virtual displacement satisfies Eq. (7.4.27), so that the virtual displacement is consistent with the constraint imposed by the collar, the virtual work is not zero. Rather, it is

$$\delta W = (-N\bar{e}_\phi - f\bar{e}_R) \cdot \delta R\bar{e}_R = -f\delta R. \quad (7.4.30)$$

Note that kinetic friction is not a constraint force, because it does not prevent sliding motion. Rather it is known by Coulomb's kinetic friction model to be  $\mu_k |\bar{N}|$ . (A static friction force does prevent relative motion. Such a force in the present case would have the effect of making the collar act as a pin connection, because the collar would not move relative to the bar.)

Many other types of constraint forces could be considered at this juncture, for example, the constraint forces associated with rolling motion. The normal force prevents interpenetration of the contacting surfaces. In the case of no slipping, the tangential force, developed by friction or gear teeth, makes the points of contact on the two bodies move by the same amount. Hence it also is a constraint force. It follows that the forces exerted between two rolling bodies will do no virtual work if there is no slippage in the rolling motion, provided that the virtual movement does not lead to relative displacement of the contacting points. (This was proven for a true displacement in Example 6.12.) Conversely, the tangential force will do virtual work when there is slippage, because it then does not constrain motion.

One should realize that, when a system is represented by a set of constrained generalized coordinates that must satisfy a certain number of constraint equations, it is only the forces associated with these conditions that contribute to the virtual work. There may be numerous other kinematical restrictions that are always satisfied, regardless of the values of the generalized forces. The forces associated with the latter conditions will not appear in the virtual work. For example, if one uses constrained generalized coordinates to model a linkage, but a pin connection remains intact when the  $\delta q_j$  values are arbitrary, then the virtual work of the forces associated with the pin will be zero.

**EXAMPLE 7.9** Tensile force  $\bar{F}$  is applied to the free end of the cable, such that the cable remains horizontal regardless of the position of the pin to which it is attached. First consider the case in which the disk slips as it rolls over the ground. The coefficient of kinetic friction is  $\mu_k$ . Select generalized coordinates, evaluate the virtual work done by all forces acting on the disk, and identify the corresponding generalized forces. Then repeat the analysis for the case in which there is no slippage in the rolling motion.

## 7.4 Generalized Forces

439

The coefficient of  $\delta x_O$  in this expression is  $Q_1$ , and  $Q_2$  is the coefficient of  $\delta\theta$ , so we have

$$Q_1 = F - f, \quad Q_2 = FR\cos\theta + fR. \quad \triangleleft$$

When slipping occurs, the velocity of the contact point is  $\vec{v}_C = (\dot{x}_O - R\dot{\theta})\vec{i}$  and  $N = mg$ , so the friction force is  $f = \mu_k mg \operatorname{sgn}(\dot{x}_O - R\dot{\theta})$ .

We see that  $Q_1$  is the resultant horizontal force, which is the force tending to increase  $x_O$ , whereas  $Q_2$  is the clockwise resultant moment about the center of the disk, which is the forcing effect causing  $\theta$  to increase. As expected, the normal force does not appear in any generalized force, and the absence of gravity is a consequence of the center moving horizontally.

When there is no slippage, the angle of rotation is  $\theta = x_O/R$ , which is a configuration constraint. We use it to eliminate  $\theta$ , so  $x_O$  is now the single unconstrained generalized coordinate. Differentiating the configuration constraint gives  $\delta\theta = \delta x_O/R$ . Equation (2) for the virtual work is generally valid. When the rotation is consistent with the no-slip condition, this equation becomes


$$\delta W = F\delta x_O \left[ 1 + \cos\left(\frac{x_O}{R}\right) \right].$$

Matching this to  $\delta W = Q_1\delta x_O$  shows that the generalized force is

$$Q_1 = F \left[ 1 + \cos\left(\frac{x_O}{R}\right) \right]. \quad \triangleleft$$

This is the moment of  $\vec{F}$  about the contact point divided by the radius  $R$ . The friction force does not appear in the generalized force when there is no slippage because it then is a constraint force that prevents relative movement of the contacting surfaces.

**EXAMPLE 7.10** Force  $F_1$  causes the collar to translate such that its horizontal position  $x$  is known as a function of  $t$ . Force  $F_2$  is known as a function of  $t$ . Generalized coordinates are the absolute angle of rotation  $\theta_1$  for the upper bar and the relative angle  $\theta_2$  for the lower bar. Determine the corresponding generalized forces. The weight of each bar is negligible in comparison with the magnitude of  $\vec{F}_2$ .



Example 7.10

**SOLUTION** The intent here is to clarify the role of constraint forces in comparison with applied forces for a system with prescribed motion. The fact that  $x$  is a specified time function means that it is not a generalized coordinate. It also means that force  $\bar{F}_1$  imposing the motion is a constraint force. The normal force acting on the collar also is a constraint force. We know that neither will contribute to the virtual work because  $\theta_1$  and  $\theta_2$  are unconstrained generalized coordinates. However, let us verify that property by explicitly evaluating the virtual work done by all forces.

We employ the analytical method to determine the virtual displacement. In terms of horizontal and vertical components, the positions of the points where forces act are

$$\bar{r}_1 = x\bar{i}, \quad \bar{r}_2 = [x + L_1 \sin \theta_1 + L_2 \sin (\theta_1 + \theta_2)]\bar{i} - [L_1 \cos \theta_1 + L_2 \cos (\theta_1 + \theta_2)]\bar{j}.$$

Because  $t$  is constant in a virtual displacement,  $x$  remains constant in the evaluation of  $\delta\bar{r}_1$  and  $\delta\bar{r}_2$ , which are found to be

$$\begin{aligned} \delta\bar{r}_1 &= \frac{\partial\bar{r}_1}{\partial\theta_1}\delta\theta_1 + \frac{\partial\bar{r}_1}{\partial\theta_2}\delta\theta_2 = \bar{0}, \\ \delta\bar{r}_2 &= \frac{\partial\bar{r}_2}{\partial\theta_1}\delta\theta_1 + \frac{\partial\bar{r}_2}{\partial\theta_2}\delta\theta_2 \\ &= \{[L_1 \cos \theta_1 + L_2 \cos (\theta_1 + \theta_2)]\bar{i} + [L_1 \sin \theta_1 + L_2 \sin (\theta_1 + \theta_2)]\bar{j}\}\delta\theta_1 \\ &\quad + \{[L_2 \cos (\theta_1 + \theta_2)]\bar{i} + [L_2 \sin (\theta_1 + \theta_2)]\bar{j}\}\delta\theta_2. \end{aligned}$$

The virtual work is

$$\begin{aligned} \delta W &= (F_1\bar{i} + N\bar{j}) \cdot \delta\bar{r}_1 + [F_2 \cos (\theta_1 + \theta_2)\bar{i} + F_2 \sin (\theta_1 + \theta_2)\bar{j}] \cdot \delta\bar{r}_2 \\ &= F_2 \{[L_1 \cos \theta_1 + L_2 \cos (\theta_1 + \theta_2)]\cos (\theta_1 + \theta_2) \\ &\quad + [L_1 \sin \theta_1 + L_2 \sin (\theta_1 + \theta_2)]\sin (\theta_1 + \theta_2)\}\delta\theta_1 \\ &\quad + F_2 \{[L_2 \cos (\theta_1 + \theta_2)]\cos (\theta_1 + \theta_2) + [L_2 \sin (\theta_1 + \theta_2)]\sin (\theta_1 + \theta_2)\}\delta\theta_2 \\ &= F_2 (L_1 \cos \theta_2 + L_2)\delta\theta_1 + F_2 L_2 \delta\theta_2. \end{aligned}$$

As expected, neither  $F_1$  nor  $N$  appears in  $\delta W$ . The standard form is  $\delta W = Q_1\delta\theta_1 + Q_2\delta\theta_2$ , which matches the actual  $\delta W$  with


$$Q_1 = F_2 (L_1 \cos \theta_2 + L_2), \quad Q_2 = F_2 L_2. \quad \triangleleft$$

It is apparent that the second generalized force is the moment of  $F_2$  about the pin connecting the bars, and it is not difficult to show that  $Q_1$  is the moment of  $F_2$  about the pivot in the collar. Both forces exemplify the notion that a generalized force captures the tendency of the force system to alter the associated generalized coordinate.

## 7.4 Generalized Forces

441

**EXAMPLE 7.11** The bar is constrained by collars  $A$  and  $B$  that slide over smooth guide bars. Force  $\bar{F}$  acts perpendicularly to the bar at its midpoint. (a) Determine the generalized force when the angle of elevation  $\phi$  is selected as the single unconstrained generalized coordinate. (b) Determine the generalized forces when the angle of elevation  $\phi$  and the horizontal distance  $x_A$  are selected as constrained generalized coordinates. Perform the analysis by evaluating the virtual work done by the constraint forces. (c) Use Lagrange multipliers to carry out the determination in Part (b). From this analysis, identify the meaning of the Lagrange multiplier. (d) Prove that the constraint forces do no virtual work if one selects  $\delta\phi$  and  $\delta x_A$  in Part (b) to be kinematically admissible.



Example 7.11

**SOLUTION** This example addresses most of the situations we encounter in the evaluation of generalized forces. This system clearly has one degree of freedom, so using a single generalized coordinate  $\phi$  in the first analysis automatically leads to a virtual movement of the system that is consistent with all constraints. Consequently, no reactions do work, so we need to evaluate  $\delta W$  only for the applied force  $\bar{F}$ . We must describe  $\delta \bar{r}_D$  for the point where  $\bar{F}$  is applied solely in terms of  $\phi$ , without reference to  $x_A$ . To eliminate the latter variable we apply the law of sines to triangle  $OAB$ , where point  $O$  is the intersection of the guide bars. This gives

$$\frac{x_A}{\sin(\beta - \phi)} = \frac{L}{\sin \beta}.$$

We solve this for  $x_A$ , then differentiate the result to determine  $\dot{x}_A$ :

$$x_A = L \frac{\sin(\beta - \phi)}{\sin \beta}, \quad \dot{x}_A = -L\dot{\phi} \frac{\cos(\beta - \phi)}{\sin \beta}. \quad (1)$$

The velocity of collar  $A$  is now known in terms of  $\phi$  and  $\dot{\phi}$ , and the angular velocity of bar  $AB$  is  $-\dot{\phi}\bar{k}$ , so we proceed to describe the velocity of the midpoint  $D$  according to

$$\begin{aligned} \bar{v}_D &= \bar{v}_A + (-\dot{\phi}\bar{k}) \times \bar{r}_{D/A} = \dot{x}_A\bar{i} + (-\dot{\phi}\bar{k}) \times \frac{L}{2}(-\cos\phi\bar{i} + \sin\phi\bar{j}) \\ &= L\dot{\phi} \left[ \left( \frac{1}{2}\sin\phi - \frac{\cos(\beta - \phi)}{\sin\beta} \right) \bar{i} + \frac{1}{2}\cos\phi\bar{j} \right]. \end{aligned}$$

We obtain  $\delta \bar{r}_D$  by replacing  $\dot{\phi}$  with  $\delta\phi$ , so

$$\delta \bar{r}_D = L\delta\phi \left[ \left( \frac{1}{2} \sin \phi - \frac{\cos(\beta - \phi)}{\sin \beta} \right) \bar{i} + \frac{1}{2} \cos \phi \bar{j} \right]. \quad (2)$$


The applied force is  $\bar{F} = F \sin \phi \bar{i} + F \cos \phi \bar{j}$ , so the virtual work done by this force is

$$\delta W = \bar{F} \cdot \delta \bar{r}_D = FL\delta\phi \left[ \left( \frac{1}{2} \sin \phi - \frac{\cos(\beta - \phi)}{\sin \beta} \right) \sin \phi + \frac{1}{2} (\cos \phi)^2 \right].$$

The standard form is  $\delta W = Q_1 \delta\phi$ , so the preceding equation leads to

$$Q_1 = FL \left( \frac{1}{2} - \frac{\cos(\beta - \phi) \sin \phi}{\sin \beta} \right). \quad \triangleleft$$

In the second analysis  $q_1 = \phi$  and  $q_2 = x_A$  are constrained generalized coordinates. The first of Eqs. (1) is the configuration constraint, and the second is the corresponding velocity constraint. Reaction forces contribute to the virtual work in such cases, and we are requested to evaluate these contributions explicitly. As an aid to this analysis, we draw a free-body diagram of the system.



Free-body diagram showing the bar in a position corresponding to arbitrary values of the two constrained generalized coordinates.

The important aspect of using constrained generalized coordinates is that, after the constraint equations have been characterized, the subsequent analytical steps consider these variables to be independent. Thus, in the free-body diagram, collar  $A$  is situated at an arbitrary distance  $x_A$ , whereas bar  $AB$  is attached to collar  $A$  and elevated to an arbitrary  $\phi$ . This places end  $B$  at a location that is not situated on the inclined guidebar. We may directly describe in terms of  $\phi$  and  $x_A$  the velocities of the points where forces are applied:

$$\bar{v}_A = \dot{x}_A \bar{i}, \quad \bar{v}_B = \dot{x}_A \bar{i} + (-\dot{\phi} \bar{k}) \times \bar{r}_{B/A} = (\dot{x}_A + L\dot{\phi} \sin \phi) \bar{i} + L\dot{\phi} \cos \phi \bar{j},$$

$$\bar{v}_D = \dot{x}_A \bar{i} + (-\dot{\phi} \bar{k}) \times \bar{r}_{D/A} = \left( \dot{x}_A + \frac{L}{2} \dot{\phi} \sin \phi \right) \bar{i} + \frac{L}{2} \dot{\phi} \cos \phi \bar{j}.$$

Changing the rate variables to virtual increments gives

$$\begin{aligned} \delta \bar{r}_A &= \delta x_A \bar{i}, \quad \delta \bar{r}_B = (\delta x_A + L\delta\phi \sin \phi) \bar{i} + L\delta\phi \cos \phi \bar{j}, \\ \delta \bar{r}_D &= \left( \delta x_A + \frac{L}{2} \delta\phi \sin \phi \right) \bar{i} + \frac{L}{2} \delta\phi \cos \phi \bar{j}. \end{aligned} \quad (3)$$

#### 7.4 Generalized Forces

443

Correspondingly, the virtual work done by  $\bar{F}$  and the normal force applied to each collar is

$$\begin{aligned}\delta W &= (F \sin \phi \bar{i} + F \cos \phi \bar{j}) \cdot \delta \bar{r}_D + N_A \bar{j} \cdot \delta \bar{r}_A + (N_B \sin \beta \bar{i} + N_B \cos \beta \bar{j}) \cdot \delta \bar{r}_B \\ &= (F \sin \phi) \delta x_A + \frac{FL}{2} \delta \phi + (N_B \sin \beta) \delta x_A + N_B L \delta \phi (\sin \beta \sin \phi + \cos \beta \cos \phi).\end{aligned}\quad (4)$$

We match this expression to  $\delta W = Q_1 \delta \phi + Q_2 \delta x_A$  to find that

$$\begin{aligned}Q_1 &= \frac{FL}{2} + N_B L \cos(\beta - \phi), \\ Q_2 &= F \sin \phi + N_B \sin \beta.\end{aligned}\quad (5) \triangleleft$$

The third analysis also uses  $q_1 = \phi$  and  $q_2 = x_A$ , but the contributions of  $N_A$  and  $N_B$  to the generalized forces will be described by Lagrange multipliers. The velocity constraint equation, the second of Eqs. (1), has the standard form of a linear velocity constraint,  $a_{11}\dot{\phi} + a_{12}\dot{x}_A + b_1 = 0$ , with the Jacobian constraint coefficients being

$$a_{11} = L \frac{\cos(\beta - \phi)}{\sin \beta}, \quad a_{12} = 1. \quad (6)$$

Equation (7.4.12) indicates that the contributions of the associated constraint force to the generalized forces are

$$R_1^{(1)} = \lambda_1 a_{11} = \lambda_1 L \frac{\cos(\beta - \phi)}{\sin \beta}, \quad R_2^{(1)} = \lambda_1 a_{12} = \lambda_1. \quad (7)$$

A comparison of these expressions with the terms in Eqs. (5) that contain the  $N_B$  shows that

$$\lambda_1 = N_B \sin \beta. \quad (8) \triangleleft$$

In other words, the Lagrange multiplier associated with the single constraint equation is the horizontal component of the associated constraint force. The same relation could have been derived by matching the  $N_B$  terms in Eq. (4) to Eq. (7.4.13), which would lead to the recognition that

$$c_{11} = L \cos(\beta - \phi), \quad c_{12} = \sin \beta.$$

Substitution of the preceding equation and Eqs. (6) into Eqs. (7.4.16) reveals that

$$\sigma_1 = \frac{a_{11}}{c_{11}} = \frac{a_{12}}{c_{12}} = \frac{1}{\sin \beta}.$$

Thus Eq. (8) is consistent with  $N_B = \sigma_1 \lambda_1$ , as indicated by Eqs. (7.4.16).

The contribution to  $\delta W$  of standard applied like  $\bar{F}$  proceeds in the same way regardless of whether one employs unconstrained or constrained generalized coordinates. Thus the portion of the generalized forces associated with  $\bar{F}$  is described in Eq. (4). Adding those terms to the respective  $R_j^{(1)}$  in Eqs. (6) gives

$$Q_1 = \frac{FL}{2} + \lambda_1 L \frac{\cos(\beta - \phi)}{\sin \beta}, \quad Q_2 = F \sin \phi + \lambda_1. \quad \triangleleft$$



The last task is to consider a situation in which  $\delta\phi$  and  $\delta x_A$  are consistent with the constraint equation. This requires that  $a_{11}\delta\phi + a_{12}\delta x_A = 0$ . For the Jacobian coefficients in Eqs. (6) this leads to

$$\delta x_A = -\frac{a_{11}}{a_{12}}\delta\phi = -L\frac{\cos(\beta - \phi)}{\sin\beta}\delta\phi.$$

When  $\delta x_A$  is related to  $\delta\phi$  in this way the virtual work in Eq. (4) becomes

$$\begin{aligned}\delta W &= Q_1\delta\phi + Q_2\delta x_A \\ &= \left[ \frac{FL}{2} + N_B L \cos(\beta - \phi) \right] \delta\phi + (F \sin\phi + N_B \sin\beta) \left( -L \frac{\cos(\beta - \phi)}{\sin\beta} \delta\phi \right) \\ &= FL\delta\phi \left( \frac{1}{2} - \frac{\cos(\beta - \phi) \sin\phi}{\sin\beta} \right).\end{aligned}$$

◁

We see that neither reaction appears in  $\delta W$  for this special choice of virtual increments. We also see that the resulting  $\delta W$  is identical to the virtual work in Part (a).

### 7.4.3 Conservative Forces

The work done by a conservative force equals the amount by which the associated potential energy is depleted, that is,  $W_{1 \rightarrow 2} = V_1 - V_2$ . This property enables us to characterize a conservative force's contribution to the generalized forces solely in terms of the properties of the potential energy. The potential energy depends on only the position of the system, so it is an explicit function of the generalized coordinates. It is also possible that  $V$  will explicitly depend on time, which would be the case if generalized coordinates are measured from reference locations that move in a prescribed manner. Thus the potential energy is described functionally as  $V(q_j, t)$ .

We obtain a virtual movement by adding a virtual increment  $\delta q_j$  to each generalized coordinate and holding time constant. The corresponding virtual work is the amount by which  $V$  decreases in the shift from the original to the displaced position:

$$\delta W = V(q_j, t) - V(q_j + \delta q_j, t). \quad (7.4.31)$$

Because the  $\delta q_j$  values are infinitesimal, the chain rule for partial differentiation indicates that

$$\delta W = \sum_{j=1}^N \left[ -\frac{\partial}{\partial q_j} V(q_j, t) \right] \delta q_j. \quad (7.4.32)$$

The definition of a generalized force is that it is the coefficient of the corresponding  $\delta q_j$  in an expression for  $\delta W$ . Hence the bracketed term in the preceding expression must be

## 7.4 Generalized Forces

445

the contribution of conservative forces to the generalized forces:

$$(Q_j)_{\text{conservative}} = -\frac{\partial}{\partial q_j} V(q_j, t). \quad (7.4.33)$$

Of course, not all forces are conservative. The virtual work in a general situation may be apportioned between conservative and nonconservative effects, such that


$$\delta W = (\delta W)_{\text{nonconservative}} - \delta V. \quad (7.4.34)$$

The corresponding expression for the generalized forces may be written as

$$(Q_j)_{\text{total}} = Q_j - \frac{\partial}{\partial q_j} V(q_j, t). \quad (7.4.35)$$

Here, and in all future developments, the symbol  $Q_j$  denotes generalized forces associated with forces and couples that are not described by the potential energy. This provides a degree of flexibility. It is not necessary to formulate the potential energy of a conservative force. If the nature of a force is uncertain, or if it is straightforward to evaluate the virtual work of a force that is known to be conservative, then that force may be considered to be nonconservative. Thus the generalized forces  $Q_j$  should be understood to describe all forces, conservative and nonconservative, whose effect is derived from an analysis of the virtual work. Obviously, it would not be correct to account for a conservative force by including it in the potential energy and also evaluating its virtual work.

**EXAMPLE 7.12** The stiffness of the spring is  $k$ , and the unstretched length is  $R$ . Friction between the collar and the vertical guide bar, and between the bar and the cylinder is negligible. The mass of the bar is  $m$  and the mass of the collar is  $m/2$ . Determine the generalized force corresponding to  $\theta$ 's being the generalized coordinate.



Example 7.12

**SOLUTION** We see here that recognizing that a force is conservative simplifies the evaluation of generalized forces. The fact that the bar is tangent to the cylinder means that its position is uniquely specified by  $\theta$ , so this system has one degree of freedom and there is no need to define other generalized coordinates. The contact point, the center of the cylinder, and the collar form a right triangle whose

hypotenuse is  $R + \ell$ , where  $\ell$  is the current length of the spring. We find from this triangle that

$$\ell = \frac{R}{\sin \theta} - R.$$

A free-body diagram of the bar and collar would show the spring and gravity forces, which are conservative. The diagram also would show a horizontal force exerted by the guide bar and a normal force exerted by the cylinder. The latter two are constraint forces because they prevent movement in the direction in which they act. The generalized coordinate for this system is unconstrained. These forces may be ignored in the evaluation of  $\delta W$  because the associated constraint conditions will not be violated in a virtual movement.

The potential energy of the spring is  $\frac{1}{2}k\Delta^2$ , where  $\Delta$  is the elongation. We express this quantity in terms of  $\theta$  by subtracting the unstretched length  $R$  from  $\ell$ :

$$V_{\text{spring}} = \frac{1}{2}k(\ell - R)^2 = \frac{1}{2}k\left(\frac{R}{\sin \theta} - 2R\right)^2.$$

The potential energy of a gravity force near the Earth's surface is defined in terms of the elevation above a reference location, which should be a physical stationary point in the system in order to avoid confusion. A convenient location here is the center of the cylinder. The distance of the collar above this datum is  $R + \ell$ . The bar's center of mass is  $(L/2)\cos \theta$  below the collar, so the potential energy of gravity is given by

$$V_{\text{gravity}} = \frac{mg}{2}(R + \ell) + mg\left(R + \ell - \frac{L}{2}\cos \theta\right).$$

We add the potential energy of each conservative force:

$$V = \frac{1}{2}k\left(\frac{R}{\sin \theta} - 2R\right)^2 + \frac{3}{2}mg\left(\frac{R}{\sin \theta}\right) - \frac{mgL}{2}\cos \theta.$$

These are the only forces that do virtual work, so the generalized force is found from Eq. (7.4.35) to be

$$Q_1 = -\frac{\partial V}{\partial \theta} = \left[kR^2\left(\frac{1}{\sin \theta} - 2\right) + \frac{3}{2}mgR\right]\frac{\cos \theta}{(\sin \theta)^2} - \frac{mgL}{2}\sin \theta. \quad \triangleleft$$

This evaluation certainly is easier than one based on determining the virtual work done by the gravity and spring forces. Perhaps the only negative aspect of the procedure is that it sheds little light on the way the forces act.

## 7.5 LAGRANGE'S EQUATIONS

The generalized forces describe the actual force system's effects. We now turn our attention to characterizing the inertial features of a system. The outcome will be a standard set of equations of motion, which were first derived by Lagrange and therefore bear his

## 7.5 Lagrange's Equations

447

name. We begin the derivation by considering a single particle, numbered  $n$ , in this system. Newton's Second Law describes the relationship between the resultant force  $\Sigma \bar{F}_n$  acting on this particle and the particle's motion variable, acceleration  $\bar{a}_n$ . The principle of dynamic virtual work to this particle states that

$$(m_n \bar{a}_n - \Sigma \bar{F}_n) \cdot \delta \bar{r}_n = m_n \bar{a}_n \cdot \delta \bar{r}_n - \delta W_n = 0, \quad (7.5.1)$$

where  $\delta W_n$  denotes the contribution of the resultant force to the virtual work for the whole system.

Lagrange's primary contribution is to account for the dependence of kinematical variables on the generalized coordinates. Two key relations are Eqs. (7.3.7) for velocity and virtual displacement. Let  $\bar{r}_n$  denote the position of the particle. The aforementioned equations then give

$$\bar{v}_n = \sum_{j=1}^N \left( \frac{\partial \bar{r}_n}{\partial q_j} \right) \dot{q}_j + \frac{\partial \bar{r}_n}{\partial t}, \quad (7.5.2)$$

$$\delta \bar{r}_n = \sum_{j=1}^N \left( \frac{\partial \bar{r}_n}{\partial q_j} \right) \delta q_j. \quad (7.5.3)$$

A crucial identity may be derived from Eq. (7.5.2). Because position depends solely on the values of the generalized coordinates and time, the partial derivatives  $\partial \bar{r}_n / \partial \dot{q}_j$  depend on only those variables. Hence only the  $k$ th term the summation for  $\bar{v}_n$  contains a specific  $\dot{q}_k$ . It follows that evaluating  $\partial \bar{v}_n / \partial \dot{q}_k$  will filter out all terms other than the  $k$ th term, so it must be that

$$\frac{\partial \bar{v}_n}{\partial \dot{q}_k} \equiv \frac{\partial \bar{r}_n}{\partial q_k}, \quad k = 1, 2, \dots, N. \quad (7.5.4)$$

Each of the preceding relations will be needed at an appropriate juncture as we manipulate the principle of dynamic virtual work. First we substitute Eq. (7.5.3) into Eq. (7.5.1), and bring the inertial term inside the sum, which gives

$$\sum_{j=1}^N m_n \bar{a}_n \cdot \left( \frac{\partial \bar{r}_n}{\partial q_j} \right) \delta q_j - \delta W_n = 0. \quad (7.5.5)$$

The next step is suggested by the fact that  $\bar{a}_n \equiv d\bar{v}_n/dt$ . Rather than differentiating only the velocity, let us introduce the rule for the time derivative of a product. Doing so results in

$$\begin{aligned} & \sum_{j=1}^N m_n \frac{d\bar{v}_n}{dt} \cdot \left( \frac{\partial \bar{r}_n}{\partial q_j} \right) \delta q_j - \delta W_n \\ & \equiv \sum_{j=1}^N \left\{ \frac{d}{dt} \left[ m_n \bar{v}_n \cdot \left( \frac{\partial \bar{r}_n}{\partial q_j} \right) \right] - m_n \bar{v}_n \cdot \frac{d}{dt} \left( \frac{\partial \bar{r}_n}{\partial q_j} \right) \right\} \delta q_j - \delta W_n = 0. \end{aligned} \quad (7.5.6)$$

Consistent with the occurrence of  $\bar{v}_n$ , we use Eq. (7.5.4) to remove  $\partial \bar{r}_n / \partial q_j$  from the first term in the summation. Furthermore, various derivatives of a quantity may be

performed in any sequence, which means that

$$\frac{d}{dt} \left( \frac{\partial \bar{r}_n}{\partial q_j} \right) \equiv \frac{\partial}{\partial q_j} \left( \frac{d}{dt} \bar{r}_n \right) \equiv \frac{\partial \bar{v}_n}{\partial q_j}. \quad (7.5.7)$$

These operations convert the expression for virtual work to

$$\sum_{j=1}^N \left\{ \frac{d}{dt} \left[ m_n \bar{v}_n \cdot \left( \frac{\partial \bar{v}_n}{\partial \dot{q}_j} \right) \right] - m_n \bar{v}_n \cdot \frac{\partial \bar{v}_n}{\partial q_j} \right\} \delta q_j - \delta W_n = 0. \quad (7.5.8)$$

Each term in the summation may be represented as a derivative of  $\bar{v}_n \cdot \bar{v}_n$  because a dot product is commutative. Thus we have

$$\sum_{j=1}^N \left\{ \frac{d}{dt} \left[ m_n \frac{\partial}{\partial \dot{q}_j} \left( \frac{1}{2} \bar{v}_n \cdot \bar{v}_n \right) \right] - m_n \frac{\partial}{\partial q_j} \left( \frac{1}{2} \bar{v}_n \cdot \bar{v}_n \right) \right\} \delta q_j - \delta W_n = 0. \quad (7.5.9)$$

When we bring  $m_n$  inside each pair of parentheses, we recognize that the term being differentiated is the kinetic energy  $T_n$  of the particle, so that

$$\sum_{j=1}^N \left\{ \frac{d}{dt} \left( \frac{\partial T_n}{\partial \dot{q}_j} \right) - \frac{\partial T_n}{\partial q_j} \right\} \delta q_j - \delta W_n = 0, \quad T_n = \frac{1}{2} m_n \bar{v}_n \cdot \bar{v}_n. \quad (7.5.10)$$

A relation such as this applies to each particle in the system. When all such equations are added, the virtual work terms describe the effect of all forces, which is described by Eq. (7.4.35). Also, the summation over all particles may be taken inside the sum over the generalized coordinate index, but the sum of  $T_n$  for all particles is merely the kinetic energy  $T$  of the system. Thus we find that

$$\sum_{j=1}^N \left\{ \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \right) - \frac{\partial T}{\partial q_j} + \frac{\partial V}{\partial q_j} - Q_j \right\} \delta q_j = 0. \quad (7.5.11)$$

Although this is a single equation, it leads to multiple equations governing each of the  $N$  generalized coordinates. In a virtual displacement the generalized coordinates are given arbitrary increments. This means that the values of the  $\delta q_j$  are an arbitrary set of infinitesimal values. Suppose we select the first increment,  $\delta q_1$ , to be nonzero and all other  $\delta q_j$  values to be zero. Then the summation consists of only the  $j = 1$  term. Because  $\delta q_1$  is not zero, the coefficient contained within the brace for  $j = 1$  must be zero. Now repeat the process, except make  $\delta q_2$  the only nonzero virtual increment. Then the term inside the brace for  $n = 2$  must be zero. Continuing this procedure to  $j = N$  leads to the conclusion that the coefficient of each  $\delta q_j$  must vanish.

A different way to arrive at the same conclusion is to observe that  $\delta q_j$  are the components of the configuration space vector  $\delta \hat{r}$ . Correspondingly, Eq. (7.5.11) may be considered to be a dot product in the configuration space of  $\delta \hat{r}$  and a vector whose components are contained inside the braces. Let  $\hat{A}$  denote the latter vector. Equation (7.5.11) requires  $\hat{A} \cdot \delta \hat{r} = 0$ , which could simply mean that the vectors are orthogonal. However, the direction of  $\delta \hat{r}$  is completely arbitrary. It is not possible for a vector to be orthogonal

## 7.5 Lagrange's Equations

449

simultaneously to vectors in all directions, so it must be that  $\hat{A}$  is a null vector. The result of either line of reasoning is that

$$\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \right) - \frac{\partial T}{\partial q_j} + \frac{\partial}{\partial q_j} V(q_j, t) = Q_j, \quad j = 1, 2, \dots, N, \quad (7.5.12)$$

which are *Lagrange's equations*.

In this version of Lagrange's equations any contributions of constraint forces is contained in the generalized forces  $Q_j$ . The remainder of this chapter is limited to derivation of the equations of motion for holonomic systems. Constraint forces do not appear in the generalized forces in that case, so the  $q_j$  in the case of a holonomic system are the only dependent variables contained in these equations. Because Eq. (7.5.12) must apply for each index  $j$ , we will obtain  $N$  ordinary differential equations for the  $N$  generalized coordinates, in which the  $Q_j$  contain the nonconservative forces causing the system to move.

When the generalized coordinates are constrained, the generalized forces contain contributions from the constraint force associated with each kinematical constraint that must be enforced explicitly. Section 8.1 develops the techniques by which Lagrange's equations are employed in such situations. In any event, derivation of the equations of motion is only the first part of a dynamic analysis. Determining the system's response requires that the differential equations be solved. If these equations are not amenable to analytical solution, numerical techniques can be employed. This phase of an analysis is taken up in Sections 7.6 and 8.2.

An alternative form of Lagrange's equations features the *Lagrangian* function, which is defined to be

$$\mathcal{L} = T - V. \quad (7.5.13)$$

The potential energy cannot depend on the generalized velocities, so it must be that

$$\frac{\partial \mathcal{L}}{\partial \dot{q}_j} \equiv \frac{\partial T}{\partial \dot{q}_j}, \quad (7.5.14)$$

which allows us to rewrite Lagrange's equations as

$$\frac{d}{dt} \left( \frac{\partial \mathcal{L}}{\partial \dot{q}_j} \right) - \frac{\partial \mathcal{L}}{\partial q_j} = Q_j, \quad j = 1, 2, \dots, N. \quad (7.5.15)$$

Although this form has one fewer term than Eq. (7.5.12), both equations require equivalent mathematical evaluations. The primary reason for introducing the Lagrangian function is its utility for the development of other kinetics principles, some of which are treated in Chapter 9.

The actual evaluation of Lagrange's equations for a specific system is straightforward, provided that one is cognizant of the difference between partial and total derivatives. For the partial derivatives the generalized coordinates  $q_j$  and generalized velocities  $\dot{q}_j$  are treated as independent variables. In the total derivative with respect to time, both  $q_j$  and  $\dot{q}_j$  are time-dependent quantities that must be differentiated.

The fact that  $\ell$  is not a generalized coordinate is irrelevant to the description of the kinetic energy. The sphere's velocity in terms of spherical coordinates is

$$\bar{v} = \dot{\ell}\bar{e}_r + \ell\dot{\phi}\bar{e}_\phi + \ell\dot{\theta}\sin\phi\bar{e}_\theta.$$

The corresponding kinetic energy is

$$T = \frac{1}{2}m\left[\dot{\ell}^2 + \ell^2\dot{\phi}^2 + \ell^2\dot{\theta}^2(\sin\phi)^2\right].$$

The top of the post is a convenient datum for gravitational potential energy, so

$$V = mg(-\ell\cos\phi).$$

Other than gravity, the only force acting on the suspended sphere is the cable force. This force does not contribute to the generalized forces. One way of recognizing this is to evaluate the virtual work. To convert the preceding expression for  $\bar{v}$  to the virtual displacement, we replace  $\dot{\phi}$  with  $\delta\phi$  and  $\dot{\theta}$  with  $\delta\theta$ , and drop the  $\dot{\ell}$  term because it is not a generalized velocity. Thus,

$$\delta\bar{r} = \ell\delta\phi\bar{e}_\phi + \ell\delta\theta\sin\phi\bar{e}_\theta.$$

The tensile force acts radially, so  $\delta W = (-F\bar{e}_r) \cdot \delta\bar{r} = 0$ , giving  $Q_1 = Q_2 = 0$ . Of course, rather than evaluating the virtual work, we could have observed that  $\bar{F}$  is the force that makes  $\ell$  change in the specified manner. This means that it is a constraint force, and constraint forces do not appear in the generalized forces when the generalized coordinates are unconstrained.

We now proceed to evaluate the derivatives for Lagrange's equations. Observe that, in these derivatives,  $\ell$  is held constant in the partial differentiations, whereas the variability of  $\ell$  must be recognized when total derivatives with respect to  $t$  are evaluated. Thus,

$$\begin{aligned}\frac{d}{dt}\left(\frac{\partial T}{\partial \dot{\phi}}\right) &= \frac{d}{dt}(m\ell^2\dot{\phi}) = m(\ell^2\ddot{\phi} + 2\ell\dot{\ell}\dot{\phi}), \\ \frac{d}{dt}\left(\frac{\partial T}{\partial \dot{\theta}}\right) &= \frac{d}{dt}[m\ell^2\dot{\theta}(\sin\phi)^2] = m[\ell^2\ddot{\theta}(\sin\phi)^2 + 2\ell\dot{\ell}\dot{\theta}(\sin\phi)^2 + 2\ell^2\dot{\theta}\dot{\phi}\sin\phi\cos\phi], \\ \frac{\partial T}{\partial \phi} &= m\ell^2\dot{\theta}^2\sin\phi\cos\phi, \quad \frac{\partial T}{\partial \theta} = 0, \quad \frac{\partial V}{\partial \phi} = mg\ell\sin\phi, \quad \frac{\partial V}{\partial \theta} = 0.\end{aligned}$$

The corresponding Lagrange's equations are

$$\begin{aligned}\ell^2\ddot{\phi} + 2\ell\dot{\ell}\dot{\phi} - \ell^2\dot{\theta}^2\sin\phi\cos\phi + g\ell\sin\phi &= 0, \\ \ell^2\ddot{\theta}(\sin\phi)^2 + 2\ell\dot{\ell}\dot{\theta}(\sin\phi)^2 + 2\ell^2\dot{\phi}\dot{\theta}\sin\phi\cos\phi &= 0.\end{aligned}\quad \triangleleft$$

We may verify that these equations are correct by recalling the relations for acceleration in terms of spherical coordinates. The preceding equations are merely  $\Sigma F_\phi = ma_\phi$ , multiplied by  $\ell/m$ , and  $\Sigma F_\theta = ma_\theta$ , multiplied by  $(\ell/m)\sin\phi$ .

## 7.5 Lagrange's Equations

455

It is possible to remove one equation of motion by a procedure that anticipates the treatment of ignorable generalized coordinates in Subsection 9.2.3. Because  $T$  and  $V$  do not explicitly depend on  $\theta$ , and  $Q_2 = 0$ , the second Lagrange equation states that

$$\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{\theta}} \right) = 0,$$

from which it follows that  $\partial T / \partial \dot{\theta}$  is a constant value we denote as  $m\beta$ . For the  $T$  function of this system, we therefore have

$$\ell^2 \dot{\theta} (\sin \phi)^2 = \beta,$$

which is what we would find if we actually integrated the preceding second Lagrange equation. The value of  $\beta$  may be determined by substituting the values of the generalized coordinates and generalized velocities at the initial instant, which must be specified if the response is to be uniquely defined. Once that value is known, we may solve the preceding relation for  $\dot{\theta}$ , and then use that result to eliminate  $\dot{\theta}$  from the Lagrange equation for  $\phi$ . This yields

$$\begin{aligned} \dot{\theta} &= \frac{\beta}{\ell^2 (\sin \phi)^2}, \\ \ell \ddot{\phi} + 2\dot{\ell}\dot{\phi} - \frac{\beta^2 \cos \phi}{\ell^3 (\sin \phi)^3} + g \sin \phi &= 0. \end{aligned}$$

The fact that  $\ell$  is not constant would necessitate solution by numerical methods. However, it is slightly less difficult to solve the second equation than the two Lagrange equations originally obtained. Also, having a single differential equation makes it somewhat easier to apply formal mathematical analysis tools to identify fundamental properties.

It is useful at this juncture to compare the situations in the preceding two examples. In the second,  $\ell$  was a length that depended on time in a specified manner as a result of the unknown tensile force  $F$ . This force did not enter into the analysis because it is a constraint force whose kinematical condition is not violated when the generalized coordinates  $\phi$  and  $\theta$  are given virtual increments. In contrast, in the first example the torque causing the rotation was a specified function of time and the corresponding angle of rotation was unknown. That analysis led to an equation of motion for the rotation angle. Similarly, specifying  $F$  in the second example would lead to  $\ell$  being unknown, and therefore a suitable generalized coordinate. The result would be three equations of motion.

These observations lead to an important alternative for systems in which a force (or couple) causes a length (or angle) parameter  $\xi$  to change in a specified manner. We can consider the force to be an unknown constraint force and treat  $\xi$  as we would any other parameter. In that approach the unknown force will not appear in any of the equations of motion. On the other hand, we can defer accounting for the fact that the



## 7.5 Lagrange's Equations

457

Using these expressions to form the kinetic-energy function of the bars and collar  $C$  gives

$$\begin{aligned} T &= \frac{1}{2} I_A \dot{\theta}^2 + \frac{1}{2} m_1 v_G^2 + \frac{1}{2} I_G \dot{\theta}^2 + \frac{1}{2} m_2 v_C^2 \\ &= \frac{1}{2} (I_A + I_G) \dot{\theta}^2 + \frac{1}{2} m_1 \left( \frac{L}{2} \dot{\theta} \right)^2 \left[ (3 \sin \theta)^2 + (\cos \theta)^2 \right] + \frac{1}{2} m_2 (2L\dot{\theta})^2 (\sin \theta)^2 \\ &= \frac{1}{2} \left[ I_A + I_G + \frac{1}{4} m_1 L^2 + (2m_1 + 4m_2) L^2 (\sin \theta)^2 \right] \dot{\theta}^2. \end{aligned}$$

Subtracting the unstretched length of the spring from its length at an arbitrary  $\theta$  shows that the elongation is  $L \cos \theta - L/2$ . We place the datum for gravitational potential energy at pin  $A$ , so the potential-energy function is

$$V = \frac{1}{2} k (L \cos \theta - L/2)^2 + mg \left( \frac{L}{2} \sin \theta \right) (2).$$

The effects of the applied force  $\bar{F}$  and torque  $\Gamma$  are contained in the virtual work. We find the virtual displacement of point  $G$  where  $\bar{F}$  acts by applying the kinematical method to the expression for  $\bar{v}_G$ . Thus,

$$\delta \bar{r}_G = \frac{L}{2} \delta \theta (-3 \sin \theta \bar{i} + \cos \theta \bar{j}).$$

The virtual work is

$$\delta W = (-F \bar{j}) \cdot \delta \bar{r}_G + M \delta \theta = Q_1 \delta \theta,$$

so the generalized force is

$$Q_1 = -\frac{L}{2} F \cos \theta + M.$$

The derivatives in Lagrange's equations for this system are

$$\begin{aligned} \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{\theta}} \right) &= \frac{d}{dt} \left\{ \left[ I_A + I_G + \frac{1}{4} m_1 L^2 + (2m_1 + 4m_2) L^2 (\sin \theta)^2 \right] \dot{\theta} \right\} \\ &= \left[ I_A + I_G + \frac{1}{4} m_1 L^2 + (2m_1 + 4m_2) L^2 (\sin \theta)^2 \right] \ddot{\theta} \\ &\quad + (4m_1 + 8m_2) L^2 (\sin \theta \cos \theta) \dot{\theta}^2, \\ \frac{\partial T}{\partial \theta} &= (2m_1 + 4m_2) L^2 (\sin \theta \cos \theta) \dot{\theta}^2, \\ \frac{\partial V}{\partial \theta} &= k (L \cos \theta - L/2) (-L \sin \theta) + mg L \cos \theta. \end{aligned}$$

The corresponding Lagrange equation is

$$\begin{aligned} &\left[ I_A + I_G + \frac{1}{4} m_1 L^2 + (2m_1 + 4m_2) L^2 (\sin \theta)^2 \right] \ddot{\theta} \\ &\quad + (m_1 + 2m_2) L^2 (\sin 2\theta) \dot{\theta}^2 + \frac{1}{2} k L^2 [\sin \theta - \sin (2\theta)] \\ &\quad + mg L \cos \theta = \frac{FL}{2} \cos \theta + M. \end{aligned}$$

## 7.5 Lagrange's Equations

459

This system has two degrees of freedom, which is indicated by the observation that  $x$  locates the slider and  $\theta$  locates the gear relative to the slider. There is no slippage between the gear and the rack, so point  $D$  on the perimeter of the gear diametrically opposite pin  $B$  was the point of contact with the gear when  $\theta = 0$ . The arc length from point  $D$  to the current contact point  $C$  is  $R\theta$ , which must equal the distance along the rack from point  $C$  to point  $D'$  on the rack, which contacted point  $D$ . This enables us to locate any point on the rack. Another line of reasoning leading to the same conclusion evaluates velocities, which we will need to do to form the kinetic energy. Let  $x_r$  denote the distance the rack moves rightward from its starting position. We relate the velocities of points  $C$ ,  $A$ , and  $B$  by using the facts that they are common to the gear, that point  $A$  moves horizontally, and that the horizontal movement of pin  $B$  must match the slider's motion. Thus,

$$\begin{aligned}\bar{v}_C &= \dot{x}_r \bar{I}, \quad \bar{v}_A = v_A \bar{I} = \bar{v}_C + (-\dot{\theta} \bar{K}) \times R \bar{J}, \\ \bar{v}_B &= \bar{v}_A + (-\dot{\theta} \bar{K}) \times (\varepsilon \sin \theta \bar{I} + \varepsilon \cos \theta \bar{J}), \quad \bar{v}_s = \dot{x} \bar{I}, \quad \dot{x} = \bar{v}_B \cdot \bar{I}.\end{aligned}$$

Matching like components in the preceding conditions leads to

$$v_A = \dot{x}_r + R\dot{\theta}, \quad \dot{x} = v_A + \varepsilon \dot{\theta} \cos \theta, \quad (1)$$

from which we find that

$$\dot{x}_r = \dot{x} - (R + \varepsilon \cos \theta) \dot{\theta}. \quad (2)$$

This is a linear velocity constraint relating  $x$ ,  $\theta$ , and  $x_r$ , which proves that the system has two degrees of freedom. Furthermore, it is holonomic. Multiplying it by  $dt$  and integrating leads to

$$x_r = x - R\theta - \varepsilon \sin \theta + S, \quad (3)$$

where  $S$  is a constant of integration that may be evaluated if the values of  $x_r$ ,  $x$ , and  $\theta$  at some reference location, such as the initial position, are given. Thus we may take  $q_1 = x$  and  $q_2 = \theta$ , and use Eqs. (2) and (3) to eliminate any dependence on  $x_r$ .

We form the kinetic energy of the system by adding the energies of the three bodies, with Eqs. (1) and (2) used to describe  $v_A$  and  $\dot{x}_r$ . Thus,

$$\begin{aligned}T &= \frac{1}{2} m_s \dot{x}^2 + \frac{1}{2} m_A v_A^2 + \frac{1}{2} (m_A \kappa^2) \dot{\theta}^2 + \frac{1}{2} m_r \dot{x}_r^2 \\ &= \frac{1}{2} m_s \dot{x}^2 + \frac{1}{2} m_A (\dot{x} - \varepsilon \dot{\theta} \cos \theta)^2 + \frac{1}{2} (m_A \kappa^2) \dot{\theta}^2 + \frac{1}{2} m_r [\dot{x} - (R + \varepsilon \cos \theta) \dot{\theta}]^2 \\ &= \frac{1}{2} (m_s + m_A + m_r) \dot{x}^2 + \frac{1}{2} [m_A \kappa^2 + m_A \varepsilon^2 (\cos \theta)^2 + m_r (R + \varepsilon \cos \theta)^2] \dot{\theta}^2 \\ &\quad - [m_r R + (m_A + m_r) \varepsilon \cos \theta] \dot{x} \dot{\theta}.\end{aligned} \quad (4)$$

Note that the terms in the kinetic-energy function are grouped according to their dependence on the generalized velocities in order to expedite evaluation of the derivatives in Lagrange's equations.

The spring is the only conservative force requiring consideration. It is given that the spring is unstretched when  $x = 2R$ , so the spring is shortened at a general position by  $x - 2R$ , and the potential energy is

$$V = \frac{1}{2}k(x - 2R)^2.$$

To account for the nonconservative force  $\bar{F}$ , we evaluate its virtual work. We may describe  $\delta\bar{r}_r$  by applying the kinematical method to Eq. (2), which gives

$$\begin{aligned}\delta\bar{r}_r &= [\delta x - (R + \varepsilon \cos \theta) \delta \theta] \bar{I}, \\ \delta W &= (-F\bar{I}) \cdot \delta\bar{r}_r = -F\delta x + F(R + \varepsilon \cos \theta) \delta \theta.\end{aligned}$$

Matching the corresponding virtual work to the standard form,  $\delta W = Q_1\delta x + Q_2\delta\theta$ , gives

$$Q_1 = -F, \quad Q_2 = F(R + \varepsilon \cos \theta). \quad (5)$$

For the kinetic energy described by Eq. (4), the derivatives appearing in Lagrange's equations are

$$\begin{aligned}\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{x}} \right) &= \frac{d}{dt} \{ (m_s + m_A + m_r) \dot{x} - [m_r R + (m_A + m_r) \varepsilon \cos \theta] \dot{\theta} \} \\ &= (m_s + m_A + m_r) \ddot{x} - [m_r R + (m_A + m_r) \varepsilon \cos \theta] \ddot{\theta} \\ &\quad + (m_A + m_r) \varepsilon (\sin \theta) \dot{\theta}^2, \\ \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{\theta}} \right) &= \frac{d}{dt} \left\{ [m_A \kappa^2 + m_A \varepsilon^2 (\cos \theta)^2 + m_r (R + \varepsilon \cos \theta)^2] \dot{\theta} \right. \\ &\quad \left. - [m_r R + (m_A + m_r) \varepsilon \cos \theta] \dot{x} \right\} \\ &= [m_A \kappa^2 + m_A \varepsilon^2 (\cos \theta)^2 + m_r (R + \varepsilon \cos \theta)^2] \ddot{\theta} \\ &\quad - [m_r R + (m_A + m_r) \varepsilon \cos \theta] \ddot{x} - 2[(m_A + m_r) \varepsilon^2 \cos \theta \sin \theta \\ &\quad + m_r R \varepsilon \sin \theta] \dot{\theta}^2 + (m_A + m_r) \varepsilon (\sin \theta) \dot{x} \dot{\theta}, \\ \frac{\partial T}{\partial x} &= 0, \\ \frac{\partial T}{\partial \theta} &= [-(m_A + m_r) \varepsilon^2 (\cos \theta \sin \theta) + m_r R \varepsilon \sin \theta] \dot{\theta}^2 + (m_A + m_r) \varepsilon (\sin \theta) \dot{x} \dot{\theta}, \\ \frac{\partial V}{\partial x} &= k(x - 2R), \quad \frac{\partial V}{\partial \theta} = 0.\end{aligned}$$


## 7.5 Lagrange's Equations

461

The corresponding set of Lagrange's equations is

$$\begin{aligned} (m_s + m_A + m_r) \ddot{x} - [m_r R + (m_A + m_r) \varepsilon \cos \theta] \ddot{\theta} \\ + (m_A + m_r) \varepsilon (\sin \theta) \dot{\theta}^2 + k (x - 2R) = -F, \\ \left[ m_A \kappa^2 + m_A \varepsilon^2 (\cos \theta)^2 + m_r (R + \varepsilon \cos \theta)^2 \right] \ddot{\theta} - [m_r R + (m_A + m_r) \varepsilon \cos \theta] \ddot{x} \\ - [(m_A + m_r) \varepsilon^2 \cos \theta \sin \theta + m_r R \varepsilon \sin \theta] \dot{\theta}^2 = F (R + \varepsilon \cos \theta). \end{aligned} \quad (6)$$

**EXAMPLE 7.17** The device depicted in the sketch is a simple model of a gyroscope. Servomotors make the flywheel spin at a constant rate  $\dot{\phi}$  and maintain the precession rate  $\dot{\psi}$  at a constant value. The  $Z$  axis is vertical, and the center of mass of the flywheel is situated on the spin axis at distance  $L$  from point  $O$ , which is the intersection of the precession axis and the line of nodes. The flywheel's centroidal moments of inertia are  $I_1$  about the spin axis and  $I_2$  transverse to that axis, and the inertia of the gimbals may be neglected. Derive the differential equations of motion for the system.



Example 7.17

**SOLUTION** We see here that Lagrange's equations are readily employed to analyze systems in spatial motion. This system is quite similar to the one in Example 6.2, so a comparison of the present and previous solutions affords one an opportunity to judge the merits of the Newton–Euler and Lagrange formulations. Because point  $O$  is stationary, the orientation of the disk, which is the only inertial body in the model, is completely specified by its three Eulerian angles. However, it is specified that only the nutation angle is uncontrolled, so this system has one degree of freedom, which is well represented by selecting  $q_1 = \theta$ . The system that is best considered includes the flywheel and gimbals, because doing so enables us to avoid consideration of all bearing effects other than the one at the base. There, we see that the base does not move and the torques that are exerted prevent rotation perpendicular to the

precession axis. Thus the virtual work is zero, so  $Q_1 = 0$ . Note that the role of the servomotors is to maintain a constant rotation rate, so the associated couple moments do not contribute to the virtual work.

To describe the kinetic energy we need a general description of the angular velocity of the disk. The axisymmetry of the disk makes it suitable to use a coordinate system attached to the inner gimbal with origin  $O$ ; the  $z$  axis is defined such that  $\bar{k} = \bar{e}_{G/O}$  and the  $x$  axis is upward in the vertical plane. Then the angular velocity of the disk at any instant is given by

$$\begin{aligned}\bar{\omega} &= \dot{\psi} \bar{K} - \dot{\theta} \bar{j} - \dot{\phi} \bar{k} \\ &= \dot{\psi} \sin \theta \bar{i} - \dot{\theta} \bar{j} + (\dot{\psi} \cos \theta - \dot{\phi}) \bar{k}.\end{aligned}$$

The inertia properties with respect to  $xyz$  are

$$I_{xx} = I_{yy} = I_2 + mL^2, \quad I_{zz} = I_1.$$

Because  $\bar{v}_O = \bar{0}$ , the disk is in pure rotation about that point, so we have

$$\begin{aligned}T &= \frac{1}{2} \left[ (I_2 + mL^2) ((\dot{\psi} \sin \theta)^2 + \dot{\theta}^2) + I_1 (\dot{\psi} \cos \theta - \dot{\phi})^2 \right] \\ &= \frac{1}{2} \left[ (I_2 + mL^2) (\sin \theta)^2 + I_1 (\cos \theta)^2 \right] \dot{\psi}^2 \\ &\quad + \frac{1}{2} (I_2 + mL^2) \dot{\theta}^2 - I_1 \dot{\psi} \dot{\phi} \cos \theta + \frac{1}{2} I_1 \dot{\phi}^2.\end{aligned}$$

The gravity force acts parallel to the  $Z$  axis through point  $G$ , so the potential energy is

$$V = mgL \sin \theta.$$

In the derivatives for Lagrange's equations the values of  $\dot{\psi}$  and  $\dot{\phi}$  are treated as constants, so that

$$\begin{aligned}\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{\theta}} \right) &= (I_2 + mL^2) \ddot{\theta}, \\ \frac{\partial T}{\partial \theta} &= (I_2 + mL^2 - I_1) \sin \theta \cos \theta + I_1 \dot{\psi} \dot{\phi} \sin \theta, \\ \frac{\partial V}{\partial \theta} &= mgL \sin \theta.\end{aligned}$$

The corresponding equation of motion is


$$(I_2 + mL^2) \ddot{\theta} - (I_2 + mL^2 - I_1) \sin \theta \cos \theta + (mgL - I_1 \dot{\psi} \dot{\phi}) \sin \theta = 0.$$

An interesting aspect of the analysis is that it is readily generalized to handle the case in which the precession or spin rates are specified time functions. Doing so would merely require that the derivatives occurring in Lagrange's equations recognize the dependence of those rates.

## 7.5 Lagrange's Equations

463

**EXAMPLE 7.18** A servomotor makes the bar spin about shaft  $AB$  at angular speed  $\Omega_1$  that is a specified function of time, whereas the known torque  $\Gamma$  induces the unknown precession rate  $\Omega_2$ . Pin  $A$  allows the angle  $\theta$  to change. The bar, which may be considered to be thin, has mass  $m_1$ , whereas the mass of shaft  $AB$  is  $m_2$ , and the moment of inertia of the vertical shaft about its axis of rotation is  $I_3$ . Derive the equations of motion and an expression for the required torque.



Example 7.18


**SOLUTION** This example generalizes the techniques for treating spatial motion by introducing rotation transformations to describe the motion of a nonaxisymmetric body. In terms of Eulerian angles  $\Omega_1 = \dot{\phi}$  is the spin rate,  $\Omega_2 = \dot{\psi}$  is the precession rate, and  $\theta$  is the nutation angle. Integrating the spin rate subject to the initial condition that  $\phi = 0$  at  $t = 0$  gives

$$\phi = \int_0^t \Omega_1(\tau) d\tau. \quad (1)$$

Hence, the position of all parts is specified by knowing  $t$ , which gives  $\phi$ , and the corresponding values of the other Eulerian angles. Thus we select as the generalized coordinates,  $q_1 = \psi$  and  $q_2 = \theta$ . To ensure that we recognize the functional dependence of all terms, we denote the respective rotation rates as  $\dot{\psi}$  and  $\dot{\theta}$ , rather than  $\Omega_1$  and  $\Omega_2$ .

The vertical shaft's bearing permits rotation only about its axis. Thus a free-body diagram of the system would show, at that bearing, a force-couple reaction that is arbitrary, except that the couple would have no vertical component. The free-body diagram also would show the conservative gravity forces acting on the flywheel and shaft  $AB$ , and the nonconservative torque  $\Gamma$ .

Unlike the previous example, the present system is not axisymmetric, so describing the kinetic energy will require somewhat more effort. The sketch defines two moving coordinate systems:  $xyz$  is attached to the bar, whereas  $x'y'z'$  only precesses and nutates. Both the  $z'$  and  $z$  axes coincide with the spin axis, and  $x'$  is defined to align with the line of nodes, whereas the  $x$  axis is parallel to the bar's longitudinal axis. The angle between  $x'$  and  $x$  is  $\phi$ .



Moving coordinate systems and generalized coordinates for the spinning bar and the shafts that support it.

The  $xyz$  coordinate system executes a simple rotation about the  $z'$  axis relative to  $x'y'z'$ , so the associated rotation transformation is

$$\begin{Bmatrix} x \\ y \\ z \end{Bmatrix} = \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{Bmatrix} x' \\ y' \\ z' \end{Bmatrix}. \quad (4)$$

The angular velocity of the bar is readily found in terms of  $x'y'z'$  components to be  $\bar{\omega}_{\text{bar}} = \dot{\theta}\bar{i}' + \dot{\psi}(\sin \theta\bar{j}' + \cos \theta\bar{k}') + \dot{\phi}\bar{k}'$ . The introduction of rotation transformations makes it convenient to switch to matrix notation. Then the  $xyz$  components are given by

$$\{\omega_{\text{bar}}\} = \begin{bmatrix} \cos \phi & \sin \phi & 0 \\ -\sin \phi & \cos \phi & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{Bmatrix} \dot{\theta} \\ \dot{\psi} \sin \theta \\ \dot{\psi} \cos \theta + \dot{\phi} \end{Bmatrix} = \begin{Bmatrix} \dot{\theta} \cos \phi + \dot{\psi} \sin \theta \sin \phi \\ -\dot{\theta} \sin \phi + \dot{\psi} \sin \theta \cos \phi \\ \dot{\psi} \cos \theta + \dot{\phi} \end{Bmatrix}. \quad (5)$$

The inertia matrix for the bar relative to  $xyz$  is obtained from the tabulated properties and the parallel axis theorems, which give

$$[I_{\text{bar}}] = \begin{bmatrix} m_1 L^2 & 0 & 0 \\ 0 & \frac{1}{12} m_1 (2R)^2 + m_1 L^2 & 0 \\ 0 & 0 & \frac{1}{12} m_1 (2R)^2 \end{bmatrix}.$$

The kinetic energy of the bar is  $T_{\text{bar}} = \frac{1}{2} \{\omega_{\text{bar}}\}^T [I_{\text{bar}}] \{\omega_{\text{bar}}\}$ . The  $x'y'z'$  axes are principal axes for shaft  $AB$ , with  $I_{x'x'} = I_{y'y'} = (1/3)m_2 L^2$ ,  $I_{z'z'} = 0$ , and the angular velocity of this shaft is  $\bar{\omega}_{AB} = \dot{\theta}\bar{i}' + \dot{\psi}(\sin \theta\bar{j}' + \cos \theta\bar{k}')$ . The vertical shaft is in pure rotation at rate  $\dot{\psi}$ , and its moment of inertia about its rotation axis is  $I_3$ . The sum of

## 7.5 Lagrange's Equations

465

the kinetic energy of each body is

$$\begin{aligned} T_{\text{bar}} = & \frac{1}{2} \left[ (m_1 L^2) (\dot{\theta} \cos \phi + \dot{\psi} \sin \theta \sin \phi)^2 \right. \\ & + \left( \frac{1}{3} m_1 R^2 + m_1 L^2 \right) (-\dot{\theta} \sin \phi + \dot{\psi} \sin \theta \cos \phi)^2 \\ & + \left( \frac{1}{3} m_1 R^2 \right) (\dot{\psi} \cos \theta + \dot{\phi})^2 \left. + \frac{1}{2} \left( \frac{1}{3} m_2 L^2 \right) [(\dot{\psi} \sin \theta)^2 + \dot{\theta}^2] + \frac{1}{2} I_3 \dot{\psi}^2 \right]. \end{aligned} \quad (6)$$

Collecting like coefficients of the generalized velocities in  $T$  expedites evaluation of the derivatives in Lagrange's equations, so we write the expression as

$$\begin{aligned} T = & \frac{1}{2} \left\{ (I'_2 + I'_3) (\sin \theta)^2 + I'_1 [1 - (\sin \theta)^2 (\sin \phi)^2] + I_3 \right\} \dot{\psi}^2 \\ & + \frac{1}{2} [I'_2 + I'_3 + I'_2 (\sin \phi)^2] \dot{\theta}^2 + \frac{1}{2} I'_1 \dot{\phi}^2 - \frac{1}{2} I'_1 \dot{\psi} \dot{\theta} (\sin \theta) (\sin 2\phi) \\ & + I'_1 \dot{\psi} \dot{\phi} (\cos \theta), \end{aligned} \quad (7)$$

where

$$I'_1 = \frac{1}{3} m_1 R^2, \quad I'_2 = m_1 L^2, \quad I'_3 = \frac{1}{3} m_2 L^2.$$

The elevations of the centers of mass depend only on  $\theta$ . The corresponding potential energy is

$$V = - \left( m_1 + \frac{1}{2} m_2 \right) g L \cos \theta \quad (8)$$

We may now form Lagrange's equations for each generalized coordinate. The derivatives of  $T$  are more intricate than they were in the previous problem because the precession angle now is a generalized coordinate and the spin rate is variable. The derivatives are

$$\begin{aligned} \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{\psi}} \right) &= \frac{d}{dt} \left\{ [(I'_2 + I'_3) (\sin \theta)^2 + I'_1 [1 - (\sin \theta)^2 (\sin \phi)^2] + I_3] \dot{\psi} \right. \\ &\quad \left. - \frac{1}{2} I'_1 \dot{\theta} (\sin \theta) (\sin 2\phi) + I'_1 \dot{\phi} (\cos \theta) \right\} \\ &= \left\{ (I'_2 + I'_3) (\sin \theta)^2 + I'_1 [1 - (\sin \theta)^2 (\sin \phi)^2] + I_3 \right\} \ddot{\psi} \\ &\quad - \left[ \frac{1}{2} I'_1 (\sin \theta) (\sin 2\phi) \right] \ddot{\theta} + I'_1 \ddot{\phi} (\cos \theta) \\ &\quad + \left[ (I'_2 + I'_3 - I'_1 (\sin \phi)^2) (\sin 2\theta) \right] \dot{\psi} \dot{\theta} - \left[ I'_1 (\sin \theta)^2 (\sin 2\phi) \right] \dot{\psi} \dot{\phi} \\ &\quad - \left[ \frac{1}{2} I'_1 (\cos \theta) (\sin 2\phi) \right] \dot{\theta}^2 - \left[ 2 I'_1 (\sin \theta) (\cos \phi)^2 \right] \dot{\theta} \dot{\phi}, \end{aligned}$$



$$\begin{aligned}
 \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{\theta}} \right) &= \frac{d}{dt} \left\{ \left[ I_2' + I_3' + I_2' (\sin \phi)^2 \right] \dot{\theta} - \frac{1}{2} I_1' \dot{\psi} (\sin \theta) (\sin 2\phi) \right\} \\
 &= \left[ I_2' + I_3' + I_2' (\sin \phi)^2 \right] \ddot{\theta} - \left[ \frac{1}{2} I_1' (\sin \theta) (\sin 2\phi) \right] \ddot{\psi} \\
 &\quad + \left[ I_2' (\sin 2\phi) \right] \dot{\theta} \dot{\phi} - \frac{1}{2} \left[ I_1' (\cos \theta) (\sin 2\phi) \right] \dot{\psi} \dot{\theta} \\
 &\quad - \left[ I_1' (\sin \theta) (\cos 2\phi) \right] \dot{\psi} \dot{\phi}, \\
 \frac{\partial T}{\partial \psi} &= 0, \quad \frac{\partial T}{\partial \theta} = \frac{1}{2} \left[ I_2' + I_3' - I_1'^2 (\sin \phi)^2 \right] (\sin 2\theta) \dot{\psi}^2 \\
 &\quad - \frac{1}{2} I_1' \dot{\psi} \dot{\theta} (\cos \theta) (\sin 2\phi) - I_1' \dot{\psi} \dot{\phi} (\sin \theta),
 \end{aligned}$$

We could proceed to substitute the preceding terms into Lagrange's equations, but there is little to be gained from doing so because we will not solve the resulting equations of motion. It is obvious that the loss of axisymmetry complicated the analysis. At the same time, it also is obvious that these complications entail mathematical operations, rather than the basic formulation. As was mentioned earlier, symbolic mathematical software can significantly alleviate these complications.

## 7.6 SOLUTION OF EQUATIONS FOR HOLONOMIC SYSTEMS

When the motion of a system is known, the equations of motion may be solved algebraically for the forces, such as applied loads, required for sustaining that motion. The more interesting situation arises when some aspect of the motion is unknown. In that case the generalized coordinates are governed by differential equations of motion. In some situations, notably those involving vibration relative to a static equilibrium position, the generalized coordinates remain sufficiently small to permit linearizing problematic terms in the equations of motion. For example, when a pendulum is released from a small initial angle, the rotation angle  $\theta$  will be small. The gravity moment for a pendulum is  $mg\ell \sin \theta$ , which may be simplified under the small-angle restriction to  $mg\ell \theta$ . Linearization of equations of motion and the solution of the resulting linearized equations of motion are discussed extensively by Ginsberg (2001).

Our concern here is situations for which it is inappropriate to simplify the equations of motion. When these equations are derived by direct application of Lagrange's equations, they have a standard form that follows as a consequence of the fact that the kinetic energy has a standard functional dependence on the generalized velocities. To demonstrate this, consider the general form of the kinetic energy of a particle. The position  $\bar{r}_k$  of particle  $k$  in a system may be an explicit function of the generalized coordinates and time, that is,  $\bar{r}_k = \bar{r}_k(q_i, t)$ . The corresponding velocity expression is

$$\bar{v}_k \equiv \frac{d}{dt} \bar{r}_k(q_i, t) = \sum_j \left( \frac{\partial}{\partial q_j} \bar{r}_k(q_i, t) \right) \dot{q}_j + \frac{\partial}{\partial t} \bar{r}_k(q_i, t). \quad (7.6.1)$$

## 7.6 Solution of Equations for Holonomic Systems

467

The kinetic energy of this particle therefore is

$$\begin{aligned} T_k &= \frac{1}{2} m_k \bar{v}_k \cdot \bar{v}_k \\ &= \frac{1}{2} \sum_j \sum_n m_k \left( \frac{\partial}{\partial q_j} \bar{r}_k(q_i, t) \right) \left( \frac{\partial}{\partial q_n} \bar{r}_k(q_i, t) \right) \dot{q}_j \dot{q}_n \\ &\quad + \sum_j m_k \left( \frac{\partial}{\partial q_j} \bar{r}_k(q_i, t) \right) \left( \frac{\partial}{\partial t} \bar{r}_k(q_i, t) \right) \dot{q}_j + \frac{1}{2} m_k \left( \frac{\partial}{\partial t} \bar{r}_k(q_i, t) \right)^2. \end{aligned} \quad (7.6.2)$$

The preceding expression indicates that the terms forming the kinetic energy of a particle fall into one of three categories: They either contain the generalized velocities as quadratic products or as linear terms, or they are independent of the generalized velocities; no term in the kinetic energy contains the  $\dot{q}_i$  in any other manner. We also see that the terms multiplying each occurrence of a generalized velocity may depend on the generalized coordinates and time. This basic form is not altered if we add the kinetic energy of the various particles forming a system. Furthermore, the kinetic energy of a rigid body contains quadratic products of the velocity of the center of mass and the angular velocity, and both types of velocities depend on the generalized coordinates in a manner similar to that of Eq. (7.6.1). It follows that the kinetic energy of a system of particles and rigid bodies is a *quadratic sum* in the generalized velocities, which means that it consists of three groups of terms:  $T_2$  is quadratic in  $\dot{q}_i$ ,  $T_1$  is linear in  $\dot{q}_i$ , and  $T_0$  is independent of the  $\dot{q}_i$ . The general form is

$$T = T_2 + T_1 + T_0(q_i, t), \quad (7.6.3)$$

where

$$T_2 = \frac{1}{2} \sum_j \sum_n M_{jn}(q_i, t) \dot{q}_j \dot{q}_n, \quad T_1 = \sum_j N_j(q_i, t) \dot{q}_j. \quad (7.6.4)$$

A useful property obeyed by the coefficients of the quadratic terms,  $M_{jn}$ , is symmetry:

$$M_{nj} = M_{jn}, \quad j, n = 1, 2, \dots, N, \quad (7.6.5)$$

which follows from the fact that the order in which the product  $\dot{q}_j \dot{q}_n$  is formed is unimportant.

It will be crucial for some later developments to recognize situations in which all terms in the kinetic energy are quadratic in the generalized velocities, so that  $T = T_2$ . To identify when such a condition arises, we note that the terms contributing to  $T_1$  and  $T_0$  originated from  $\partial \bar{r}_k / \partial t$  in Eq. (7.6.1). This term vanishes if all generalized coordinates are measured from a stationary position, in which case the system is at rest if all generalized coordinates are maintained at zero.

Let us consider the result of using Eqs. (7.6.4) to form the Lagrange's equations associated with a specific generalized coordinate  $q_s$ . We begin with  $\partial T_2 / \partial \dot{q}_s$ . We know that  $\partial M_{jn} / \partial \dot{q}_s \equiv 0$ . Partial differentiation of the product  $\dot{q}_j \dot{q}_n$  with respect to  $\dot{q}_s$  will give zero unless either or both of the indices  $j$  and  $n$  matches  $s$ . We use the Kronecker delta

$\delta_{js}$ , which is zero if  $j \neq s$  and one if  $j = s$ , to describe this property. This symbol allows us to write

$$\begin{aligned} \frac{\partial T_2}{\partial \dot{q}_s} &= \frac{1}{2} \sum_j \sum_n M_{jn} \frac{\partial}{\partial \dot{q}_s} (\dot{q}_j \dot{q}_n) = \frac{1}{2} \sum_j \sum_n M_{jn} (\delta_{sj} \dot{q}_n + \dot{q}_j \delta_{sn}) \\ &= \frac{1}{2} \sum_n M_{sn} \dot{q}_n + \frac{1}{2} \sum_j M_{js} \dot{q}_j = \sum_n (M_{sn} + M_{ns}) \dot{q}_n = \sum_n M_{sn} \dot{q}_n, \end{aligned} \quad (7.6.6)$$

where the last step is a consequence of the symmetry of the  $M_{jn}$  coefficients. Similar operations applied to  $T_1$  and  $T_0$  lead to

$$\frac{\partial T_1}{\partial \dot{q}_s} = N_s, \quad \frac{\partial T_0}{\partial \dot{q}_s} = 0, \quad (7.6.7)$$

from which it follows that

$$\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_s} \right) = \sum_n \left[ M_{sn} \ddot{q}_n + \left( \frac{dM_{sn}}{dt} \right) \dot{q}_n \right] + \frac{dN_s}{dt}. \quad (7.6.8)$$

Proper evaluation of the total time derivative requires that we recognize that the coefficients may depend explicitly on the generalized coordinates, which are time dependent. Accounting for this dependence leads to

$$\begin{aligned} \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_s} \right) &= \sum_n M_{sn} \ddot{q}_n + \sum_n \sum_j \frac{\partial M_{sn}}{\partial q_j} \dot{q}_j \dot{q}_n + \sum_n \dot{M}_{sn} \dot{q}_n \\ &\quad + \sum_j \frac{\partial N_s}{\partial q_j} \dot{q}_j + \dot{N}_s, \end{aligned} \quad (7.6.9)$$

where the overdot indicates partial differentiation with respect to time. We proceed similarly to evaluate  $\partial T / \partial q_s$ . Because the generalized coordinates and velocities constitute independent variables for the partial differentiation, we find that

$$\frac{\partial T}{\partial q_s} = \frac{1}{2} \sum_n \sum_j \frac{\partial M_{jn}}{\partial q_s} \dot{q}_j \dot{q}_n + \sum_j \frac{\partial N_j}{\partial q_s} \dot{q}_j + \frac{\partial T_0}{\partial q_s}. \quad (7.6.10)$$

Substitution of the preceding derivatives into Lagrange's equations leads to

$$\begin{aligned} \sum_n M_{sn} \ddot{q}_n + \sum_n \sum_j \left( \frac{\partial M_{sn}}{\partial q_j} - \frac{1}{2} \frac{\partial M_{jn}}{\partial q_s} \right) \dot{q}_j \dot{q}_n + \sum_n \left( \dot{M}_{sn} + \frac{\partial N_s}{\partial q_n} - \frac{\partial N_n}{\partial q_s} \right) \dot{q}_n \\ + \dot{N}_s + \frac{\partial T_0}{\partial q_s} + \frac{\partial V}{\partial q_s} = Q_s, \quad s = 1, 2, \dots, N. \end{aligned} \quad (7.6.11)$$

This expression is an analytical confirmation that a wide variety of terms might be generated when one forms the Lagrange equations for a system. For our present purpose the main feature is that the highest derivative of a generalized coordinate that can occur is second order and that these derivatives occur linearly. The other terms may be grouped on the right side of the equality sign as a single function  $F_s(q_i, \dot{q}_i, t)$ . The term containing the second derivative is the summation form of the product of a matrix  $[M]$  and a vector of generalized coordinates  $\{q\}$ . Thus the standard form of Lagrange's

## 7.6 Solution of Equations for Holonomic Systems

469

equations for a holonomic system described by unconstrained generalized coordinates is

$$[M(q_i, t)]\{\ddot{q}\} = \{F(q_i, \dot{q}_i, t)\}. \quad (7.6.12)$$

This set of second-order differential equations is likely to be highly nonlinear and  $[M]$  seldom is constant. An analytical solution of these equations is not likely to be found, so evaluation of the response will require a numerical procedure. Numerous numerical methods and associated standard computerized routines have been developed to assist us to solve sets of coupled differential equations, but most require that we express the differential equations of motion in first-order form. The standard form of such equations is

$$\frac{d}{dt}\{z\} = \{G(z_i, t)\}. \quad (7.6.13)$$

A discussion of numerical algorithms by which a set of equations in this form may be solved is beyond the scope of this book. A good starting point to learn about possible techniques is the text by Press *et al.* (1992). Most computational software packages, such as Matlab and Mathcad, as well as libraries of compiled languages such as C and FORTRAN, provide functions or subroutines that can solve these equations. The procedures step forward in time, that is, they obtain the value of  $\{z\}$  at time  $t + \Delta t$ , in some cases proceeding in an automatic manner for as many time steps as required. Implementing this capability requires that one specify how to compute  $\{G\}$  from the current values of the elements of  $\{z\}$  and  $t$ . From this juncture onward, we assume that a reliable technique capable of solving a system of differential equations in the form of Eq. (7.6.13) is available. The task we address here is how we convert Eq. (7.6.12) to a form that is compatible with Eq. (7.6.13).

At any instant  $t$ , the state of a system consists of the values of its generalized coordinates  $\{q\}$  and velocities  $\{\dot{q}\}$ . From such data the generalized accelerations may be computed from Eq. (7.6.12), and higher derivatives may be computed by differentiating that equation. For this reason the values of  $\{q\}$  and  $\{\dot{q}\}$  are said to constitute the *state space*. Conversion of the governing equations to state-space form will lead to the requisite form of the equations of motion.

The key step is to treat the generalized velocities as variables that are independent of the generalized coordinates by defining a set of  $2N$  variables  $x_i$ . The first group of  $N$  variables comprises the generalized coordinates, whereas the second group comprises the generalized velocities:

$$x_i = q_i, \quad x_{i+N} = \dot{q}_i, \quad i = 1, \dots, N. \quad (7.6.14)$$

This may be described in matrix form with  $\{q\}$  and  $\{\dot{q}\}$  used as upper and lower partitions of a vector, according to

$$\{x\} = \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \end{Bmatrix}. \quad (7.6.15)$$

The derivative of  $\{q\}$  obviously is  $\{\dot{q}\}$ . We may write this identity for the derivative in partitioned form by recognizing that  $\{q\}$  is the upper partition of  $\{x\}$  and  $\{\dot{q}\}$  is the lower partition. Recall that, when matrices are partitioned conformably, then a product may be formed by treating the partitions as though they were individual elements. Thus we have

$$\begin{bmatrix} [U]_{N \times N} & [0]_{N \times N} \end{bmatrix} \{x\} = \{q\}, \quad \begin{bmatrix} [0]_{N \times N} & [U]_{N \times N} \end{bmatrix} \{x\} = \{\dot{q}\}, \quad (7.6.16)$$

where  $[U]$  is an identity matrix. The following set of  $N$  differential equations results from using these relations to enforce the identity that the time derivative of  $\{q\}$  is  $\{\dot{q}\}$ :

$$\begin{bmatrix} [U]_{N \times N} & [0]_{N \times N} \end{bmatrix} \{\dot{x}\} = \begin{bmatrix} [0]_{N \times N} & [U]_{N \times N} \end{bmatrix} \{x\}. \quad (7.6.17)$$

We obtain another set of  $N$  equations by solving the equations of motion, Eq. (7.6.12), for the generalized accelerations, which yields

$$\{\ddot{q}^*\} = [M(q_i, t)]^{-1} \{F(q_i, \dot{q}_i, t)\}. \quad (7.6.18)$$

The asterisk is used to indicate that the generalized accelerations are obtained by solving a set of equations that is evaluated at the current instant. Note that the inverse is used here solely to indicate solution of the matrix equation. Unless  $[M]$  is constant, it is far more efficient in practice to merely solve Eq. (7.6.12) numerically by any convenient algorithm, such as LU decomposition or Gauss elimination. To fully transform to the state-space variables we use Eqs. (7.6.14) to replace any occurrence of a  $q_i$  or  $\dot{q}_i$  variable appearing in the preceding equation with the corresponding variable  $x_i$  or  $\dot{x}_{i+N}$ , respectively. The last step is to assemble the full set of equations by stacking the derivative identity above the equations of motion. The result is a form of the equations of motion for a holonomic system suitable for solution by most numerical algorithms, specifically

$$\frac{d}{dt} \{x\} = \begin{Bmatrix} \begin{bmatrix} [0]_{N \times N} & [U]_{N \times N} \end{bmatrix} \{x\} \\ [M(x_i, t)]^{-1} \{F(x_i, \dot{x}_{i+N}, t)\} \end{Bmatrix}. \quad (7.6.19)$$

The foregoing, whose form is the same as that of Eq. (7.6.13), represents a set of  $2N$  first-order differential equations for the  $2N$  elements of  $\{x\}$ . To solve them numerically one needs to identify to the software how to compute the vector on the right side. In addition, initial values are required to start the numerical solver. Thus we need to specify the initial values of the generalized coordinates and velocities at an initial time  $t_0$ , from which we may form the initial state-space vector according to

$$\{x_0\} = \begin{Bmatrix} \{q(t=t_0)\} \\ \{\dot{q}(t=t_0)\} \end{Bmatrix}. \quad (7.6.20)$$

## 7.6 Solution of Equations for Holonomic Systems

471

The preceding equation describes the analytical steps required to solve numerically the equations of motion for a holonomic system. Software packages typically offer several functions/subroutines based on different algorithms. Each has its benefits for certain classes of problems. A good starting point for dynamical systems is the fourth-order-Runge–Kutta algorithm, but one should be prepared to switch if irregularities, such as numerical instability, severely decreased time step in an automated algorithm, or error build-up, are observed as the program marches forward. Methods for stiff systems, such as the Gear method, often are useful if such difficulties are encountered.

**EXAMPLE 7.19** Parameters for the rack and gear in Example 7.16 are  $m_r = 20$  kg,  $m_A = 10$  kg,  $m_s = 2$  kg,  $R = 200$  mm,  $\varepsilon = 0.175$  mm,  $\kappa = 150$  mm, and  $k = 40$  kN/m. The system starts from rest at  $x = 2R$ ,  $\theta = 0$ , at which location  $x_r$  is defined to be zero. A constant actuating force  $F = 200$  N is applied at  $t = 0$ . Determine and graph  $x$ ,  $x_r$ , and  $\theta$  as functions of time.

**SOLUTION** The emphasis for this example is the setup of the differential equations and the application of a software package. The discussion is framed in terms of Matlab, but it is readily modified to treat the reader's choice of software. The generalized coordinates are  $q_1 = x$  and  $q_2 = \theta$ , so the state-space vector is<sup>‡</sup>

$$\{x\} = [x \ \theta \ \dot{x} \ \dot{\theta}]^T.$$

It is easier to program the solution if the equations of motion are written in terms of the elements of  $\{x\}$ . Thus the coefficient matrix multiplying generalized accelerations in Eqs. (6) of Example 7.16 is written as

$$[M] = \begin{bmatrix} (m_s + m_A + m_r) & -[m_r R + (m_A + m_r) \varepsilon \cos(x_2)] \\ -[m_r R + (m_A + m_r) \varepsilon \cos(x_2)] & [m_A \kappa^2 + m_A \varepsilon^2 (\cos(x_2))^2 + m_r (R + \varepsilon \cos(x_2))^2] \end{bmatrix}. \quad (1)$$

All terms not containing generalized accelerations are placed on the right side of the first-order equations, so that

$$\{F\} = \begin{Bmatrix} -(m_A + m_r) \varepsilon (\sin(x_2)) (x_4)^2 - k(x_1 - 2R) - F \\ [(m_A + m_r) \varepsilon^2 \cos(x_2) \sin(x_2) + m_r R \varepsilon \sin(x_2)] (x_4)^2 + F(R + \varepsilon \cos(x_2)) \end{Bmatrix}. \quad (2)$$

<sup>‡</sup> The parameters in the problem statement are given as dimensional quantities, so the equations are programmed in that form. However, nondimensionalizing a system of equations can sometimes beneficially affect both the accuracy and stability of a solution. One can obtain such a form in the present problem by using  $R$  as a length scale,  $m_s + m_A + m_r$  as a mass scale, and  $[(m_s + m_A + m_r)/K]^{1/2}$  as a time scale.

The state-space equations to be solved are

$$\frac{d}{dt} \{x\} = \begin{Bmatrix} x_3 \\ x_4 \\ [M]^{-1} \{F\} \end{Bmatrix}. \quad (3)$$

It is specified that the system starts from rest with  $x = 2R$ ,  $\theta = 0$ , so the initial state-space vector is  $\{x(0)\} = [2R \ 0 \ 0 \ 0]^T$ .

The ODE suite of functions in Matlab (ODE45, ODE23, etc.) differ in their internal algorithmic steps, but they all require that one define in an M-file a function that evaluates the right side of Eq. (3). The first two input arguments for this function are required to be the current values of  $t$  and  $\{x\}$ , after which one can place other system parameters. The function that was used to obtain the following solution is

```
function dx_dt = dx_dt_rack(t, x, m_r, m_A, m_s, R, eps, ...
    kappa, K, Force)
M(1,1) = m_r + m_A + m_s;
M(1,2) = -(m_r * R + (m_A + m_r) * eps * cos(x(2)));
M(2,1) = M(1,2);
M(2,2) = m_A * (kappa^2 + (eps * cos(x(2)))^2) ...
    + m_r * (R + eps * cos(x(2)))^2;
F(1,1) = - (m_A + m_r) * eps * sin(x(2)) * x(4)^2 ...
    - K * (x(1) - 2 * R) - Force ;
F(2,1) = ((m_A + m_r) * eps^2 * sin(x(2)) * cos(x(2)) ...
    + m_r * R * eps * sin(x(2))) * x(4)^2 ...
    + Force * (R + eps * cos(x(2)));
dx_dt = [x(3:4); M\F];
```

Note that the “\”, or left divide, operation in the last line implements an algebraic solution, which is more efficient than actually evaluating  $[M]^{-1} \{F\}$ .

The ODE suite implement adaptive algorithms with built-in error controls, which means that they have the capability of automatically evaluating the output at a succession of instants in a single invocation of the ODE function. However, the author’s experience is that using this automatic capability is unreliable, and requires tuning of the error tolerances. Such was found to be the case here for some combinations of parameters other than those specified in the problem statement. When the code appearing after this discussion was modified to call ODE45 once for the same error parameters (stored in `options`) with an initial  $t_0 = 0$  and a final  $t_f = 1$ , significant deviations from the results displayed here were found as  $t$  increased. In contrast, the displayed results were unaltered when the error parameters were reduced by a factor of 100 or alternative algorithms were used. In general, if one is analyzing a system with relatively few degrees of freedom and does not need to perform multiple computations with a variety of system parameters, it is preferable

## 7.6 Solution of Equations for Holonomic Systems

473

to limit the time steps to be sufficiently small that error build-up is not an issue. This is achieved here with a program loop in which the new start time is set to the final time for the previous step. Although 100 integration steps are used here, far fewer would suffice. Another item to note in the following program fragment is the manner in which the argument list of ODE45 specifies which function should evaluate  $d\{x\}/dt$ . An anonymous function, which is a feature of Matlab 7, provides the capability of passing system parameters other than  $t$  and  $\{x\}$  to the function `dx_dt_rack`. Here `dx_dt_anon` is the anonymous function that is passed as a “function handle” to ODE45. The definition of this function, which must appear before it is used, tells the differential equation solver to look for the variables it needs in the function `dx_dt_rack`. Note that all parameters other than those contained in the argument list, which are  $t$  and  $x$  in the present case, have been defined. The main steps stored in a Matlab script file are

```
options = odeset('RelTol',1e-6,'AbsTol',[1e-6 1e-6 1e-6 1e-6]);
x_state(1, 1:4) = [2*R 0 0 0]'; t_state(1,1) = 0;
dx_dt_anon = @(t, x) dx_dt_rack(t, x, m_r, m_A, m_s, R, eps, ...
    kappa, K, Force);
t_max = 1; N_step = 100; t = [0:N_step]/N_step;
for j = 2:N_step + 1
    x_0 = x_state(j - 1,:);
    [t_ode, x] = ode45(dx_dt_anon, [t(j - 1) t(j)], x_0,
options);
% Determine how many steps ODE45 took.
% Save the values at the last step.
% Row j of x_state is the state vector at t(j)
    n_steps = size(x, 1);
    x_state(j,:) = x(n_steps,1:4);
    t_state(j,1) = t(j);
end
```

The state-space vectors provide all of the response information required to evaluate any feature of the response. The first two columns of `x_state` contain the values of  $x$  and  $\theta$  at the instants in `t_state`, whereas the third and fourth columns are the corresponding generalized velocity values. The problem statement requested the response  $x_r$ , for which we recall Eq. (3) in Example 7.16. It is stated here that  $x_r = 0$  when  $x = 2R$  and  $\theta = 0$ . Substituting these values into Eq. (3) gives  $S = -2R$ . It also is useful to consider where the center of the gear is situated. This quantity is given by  $x_A = x - \varepsilon \sin \theta$ . We compute these displacements by writing `x_rack = x_state(:,1) - 2 * R - R * x_state(:,2) - eps * sin(x_state(:,2))`; `x_A = x_state(:,1) - eps * sin(x_state(:,2))`; If it is desired to evaluate




forces, such as the one exerted between pin  $B$  and the groove, one can employ the Newton–Euler equations of motion for isolated bodies. Such an evaluation would require the accelerations at each instant, which can be obtained from the equations of motion, which indicate that


$$[\ddot{x} \ \ddot{\theta}]^T = [M(\{x\})]^{-1} \{F(\{x\})\},$$

where the state vector  $\{x\}$  would be the state vector at any instant. (An alternative method for finding internal forces by use of constrained generalized coordinates is discussed in the next chapter.)

The first graph shows that  $\theta$  increases almost monotonically to a peak value and then falls off. The slider moves little in the early stages of the motion, after which it begins to oscillate, with an amplitude that increases after the gear has attained its maximum rotation. The mean value for  $x$  is approximately  $2R$ , which is its starting value. The second graph compares the positions of the rack, the slider, and the center of the gear. The rack moves to the left (negative  $x_r$ ) in a nearly monotonic manner until the gear attains its maximum rotation, after which it begins to move rightward. In contrast, the slider and the gear execute similar oscillations. The physical interpretation of this behavior is that force  $\bar{F}$  pushes the rack to the left, and the inertia of the gear resists this movement, thereby causing it to rotate clockwise (positive  $\theta$ ) about its center. The result is that pin  $B$  and the follower move to the right. When  $\theta$  is small in the early stage, this movement is small, but  $x$  becomes eventually becomes large. This increases the compression of the spring, until a position is reached at which the follower's velocity reverses. Then the follower moves to the left, which eventually induces a tensile force in the spring that is sufficient to pull the follower back to the right, and so on.



Time dependence of the generalized coordinates.



Positions of the slider, rack, and gear center as functions of time.

## SELECTED REFERENCES

- Ardema, M. D., *Analytical Dynamics: Theory and Applications*, Kluwer Academic/Plenum, New York (2005).
- Baruh, H., *Analytical Dynamics*, McGraw-Hill, New York (1999).
- Chapra, S.C., and Canale, R.P., *Numerical Methods for Engineers*, 5th ed., McGraw-Hill, New York (2005).
- Desloge, E. A., *Classical Mechanics*, Vols. 1 and 2, Wiley, New York (1982).
- D'Souza, A. F., and Garg, V. K., *Advanced Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1984).
- Dugas, R., *A History of Mechanics*, Dover, New York (1988).
- Ginsberg, J. H., *Mechanical and Structural Vibrations*, Wiley, New York (2001).
- Goldstein, H., *Classical Mechanics*, 2nd ed., Addison-Wesley, Reading, Massachusetts (1980).
- Greenwood, D. T., *Principles of Dynamics*, Prentice-Hall, Upper Saddle River, New Jersey (1965).
- Greenwood, D. T., *Advanced Dynamics*, Cambridge University Press, New York (2003).
- Hibbeler, R. C., *Engineering Mechanics-Combined*, 10th ed. Prentice-Hall, Englewood Cliffs, New Jersey (2003).
- Jose, J. V., and Saletan, E. J., *Classical Dynamics: A Contemporary Approach*, Cambridge University Press, New York (1998).
- Josephs, H., and Huston, R. L., *Dynamics of Mechanical Systems*, CRC Press, Boca Raton, Florida (2002).
- Lanczos, C., *The Variational Principles of Mechanics*, 4th ed., University of Toronto Press, Toronto (1970).
- Marion, J. B., *Classical Dynamics of Particles and Systems*, Academic, New York (1960).

MATLAB Reference Guide, Version 7.1, The MathWorks, Cambridge, Massachusetts, 2005.

Meirovitch, L., *Methods of Analytical Dynamics*, McGraw-Hill, New York (1970).

Pars, L. A., *A Treatise on Analytical Dynamics*, Heinemann, London (1965).

Press, W. H., Flannery, B. P., Teukolsky, S. A., and Vetterling, W. T., *Numerical Recipes*, 2nd ed., Cambridge University Press, New York (1992).

Rosenberg, R. M., *Analytical Dynamics of Discrete Systems*, Plenum, New York (1977).


Shabana, A. A., *Computational Dynamics*, Wiley, New York (2001).

Symon, K. R., *Mechanics*, 3rd ed., Addison-Wesley, Reading, Massachusetts (1971).

Truesdell, C., *Essays in the History of Mechanics*, Springer-Verlag, New York (1960).


## HOMEWORK PROBLEMS

**EXERCISE 7.1** The slider descends along a curved guide as the guide translates to the right at the constant speed  $u$ . The shape of the guide bar in terms of a body-fixed set of coordinates is  $y = \beta x^2$ . Generalized coordinates selected for this system are the fixed  $X$  and  $Y$  coordinates of the collar. Independently derive the velocity and configuration constraint equations relating  $X$  and  $Y$ . Then show that integration of the velocity constraint yields the configuration constraint.




Exercise 7.1

**EXERCISE 7.2** The length of rod  $AB$  connecting the collars is a controlled function  $L(t)$ . Generalized coordinates selected for this system are the distances  $s_A$  and  $s_B$  and the inclination angle  $\theta$ . Derive the velocity constraint equations governing these variables, then integrate those constraint equations to obtain the corresponding configuration constraints. Show that the configuration constraint equations could have alternatively been obtained from a geometrical analysis.



Exercise 7.2

**EXERCISE 7.3** The gear rolls without slipping over the rack, which pivots about pin  $A$ . Generalized coordinates for this system are selected to be the angle of rotation  $\theta$  of the rack, the distance  $s$  from the pivot to the center of the gear, and the  $(X, Y)$  coordinates of the center of the gear. Determine the velocity constraints relating these generalized coordinates. Are these constraints holonomic? How many degrees of freedom does this system have?




Exercise 7.3

## Homework Problems


477

**EXERCISE 7.4** The generalized coordinates selected for the compound pendulum are the  $x, y$  coordinates of the lower end and the rotation angle of the upper bar. Perform a kinematical analysis to derive the velocity constraint equation relating these variables. Then perform a geometrical analysis of position to derive the configuration constraint. Prove that differentiating the configuration constraint leads to the velocity constraint.




Exercise 7.4

**EXERCISE 7.5** Collar  $A$  slides along the vertical guide bar, and collar  $B$  follows the horizontal guide. Bar  $AB$  is connected to collar  $A$  by a fork-and-clevis, and the connection to collar  $B$  is a ball-and-socket joint. It has been decided to use  $y, \theta$ , and  $\psi$  as constrained generalized coordinates for this system. (a) Derive all applicable configuration constraints relating these variables based on a geometrical analysis. (b) Derive all applicable velocity constraints relating these variables based on a velocity analysis that uses these generalized coordinates to represent the position. (c) Show that differentiating the results of Part (a) yields velocity constraints that are equivalent to the results of Part (b).



Exercise 7.5

**EXERCISE 7.6** The yoke permits collar  $C$  to precess through angle  $\psi$  and to nutate through angle  $\theta$ . Bar  $AB$  slides freely relative to the collar, so the distance  $x$  to end  $B$  is an unknown function of time. What velocity constraint(s) must apply in order that the velocity of end  $B$  always be horizontal. Are they holonomic? If so, determine the corresponding configuration constraints.




Exercise 7.6

**EXERCISE 7.7** The Cartesian coordinates  $(x, y, z)$  of a particle relative to a fixed reference frame are related by

$$\left[ ay^2 \cos\left(\frac{ax}{y^2}\right) - cxy^2 \right] \dot{x} + \left[ -2axy \cos\left(\frac{ax}{y^2}\right) + 2byz \sin\left(\frac{bz}{y^2}\right) + 2cxyz \right] \dot{y} - \left[ by^2 \sin\left(\frac{bz}{y^2}\right) + cxy^2 \right] \dot{z} = 0,$$


where  $a, b$ , and  $c$  are constants. Prove that this constraint is holonomic, and derive the corresponding configuration constraint.

**EXERCISE 7.8** The angles  $\theta_1$ ,  $\theta_2$ , and  $\theta_3$  have been selected as generalized coordinates for the linkage. Perform a velocity analysis of the linkage to derive the velocity constraint equations that must be satisfied by these angles. Then prove that these equations are holonomic.




Exercise 7.8

**EXERCISE 7.9** The bar is made to slide along the horizontal plane such that the velocity of end  $A$  is always directed at a constant angle  $\gamma$  relative to the bar. Generalized coordinates are the  $x$  and  $y$  coordinates of end  $B$  and the angle  $\theta$ . Describe the corresponding velocity constraint. Then determine whether the constraint is holonomic.




Exercise 7.9

**EXERCISE 7.10** The sketch shows the top view of a sled that is towed over the ice by fastening a cable to loop  $D$ . The ice constrains the velocity of points  $A$  and  $B$  to be parallel to the rails, but the speeds of each point may be different. Generalized coordinates have been selected as the east and north coordinates of point  $C$  in the horizontal plane and the heading angle  $\theta$ . What are the associated constraint equations?




Exercise 7.10

**EXERCISE 7.11** The illustrated linkage lies in the horizontal plane. End  $A$  of the bar follows the horizontal guide, and a wheel at end  $B$  is aimed at an angle  $\beta$  that is a specified function of time. The wheel rolls without slipping over the ground, so the velocity  $\bar{v}_B$  must be in the direction indicated in the diagram. Generalized coordinates are selected to be the horizontal position  $x_A$  and the rotation angle  $\theta$ . Determine the velocity constraint relating these variables. Prove that this constraint equation is nonholonomic unless  $\beta$  is constant.



Exercise 7.11

**EXERCISE 7.12** The figure shows a disk that is constrained to roll without slipping on a horizontal  $XY$  plane, such that its plane remains vertical. Let the position coordinates  $X$  and  $Y$  of the geometric center, the heading angle  $\psi$ , and the spin angle  $\phi$  be generalized coordinates. Describe the velocity constraints between these generalized coordinates. From those results, determine the number of degrees of freedom, and whether the system is holonomic.




Exercise 7.12

# Homework Problems


479

**EXERCISE 7.13** An interesting example of a non-holonomic constraint, which does not usually arise in a course in mechanics, is a pursuit problem. The sketch depicts airplane  $A$  that flies eastward at a constant velocity  $v_A$ . Airplane  $B$  has a laser that is mounted parallel to its axis, and therefore parallel to  $\bar{v}_B$ . It is necessary to maneuver this airplane such that the laser is always aimed at airplane  $A$ . Derive the constraint equations that must be satisfied by the coordinates  $X_B$  and  $Y_B$  and the heading angle  $\beta$ .




Exercise 7.13

**EXERCISE 7.14** The horizontal platform translates upward at constant speed  $u$  as the T-bar assembly rotates about the vertical axis at angular speed  $\dot{\psi}$ . Disk  $C$ , which spins freely about its shaft, rolls over the platform without slipping in the direction perpendicular to the diagram, although slippage in the direction transverse to the vertical shaft does occur. Derive the velocity constraint equation(s) relating the precession angle  $\psi$ , the elevation angle  $\beta$ , and the angle  $\phi$  by which the disk spins about shaft  $BC$ .




Exercise 7.14

**EXERCISE 7.15** The figure shows a child's tricycle as viewed from above. When the wheels do not slip over the ground, the velocity of each wheel's center must be perpendicular to the wheel's shaft in the horizontal plane, as shown. Consider a set of generalized coordinates consisting of the position coordinates  $X_A$  and  $Y_A$  of the steering joint, the angle of orientation  $\theta$  of the frame, the steering angle  $\beta$ , and the spin angles  $\phi_A$ ,  $\phi_B$ , and  $\phi_C$  of the wheels. Derive the velocity constraints among these seven generalized coordinates. From that result, determine the number of degrees of freedom.



Exercise 7.15

**EXERCISE 7.16** The parallelogram linkage, which lies in the vertical plane, is loaded by force  $F$  that acts perpendicular to the link to which it is applied, and torque  $M$ . The mass per unit length of each bar is  $\sigma$ . The spring can support compressive or tensile axial force, and is unstretched when  $y = 1.5L$ . Determine the conservative and nonconservative portions of the generalized force associated with the selection of the vertical distance  $y$  as the generalized coordinate. Then repeat the analysis using the angle  $\theta$  as the generalized coordinate.



Exercise 7.16

**EXERCISE 7.17** The distances  $s_A$  and  $s_B$  have been selected as generalized coordinates for the system in Exercise 7.2. Determine the virtual work done by all forces acting on the collars in an arbitrary virtual displacement. Then show that the virtual work done by the forces exerted by the hydraulic cylinder vanishes if the virtual displacement is kinematically admissible.

**EXERCISE 7.18** Suppose the angle  $\theta$  and vertical distance  $y$  are selected as generalized coordinates for the system in Example 7.12. Determine the virtual work done by all forces acting on the collar and bar when  $\delta y$  and  $\delta\theta$  are arbitrary values. Then show that the result is equivalent to the expression obtained in Example 7.12 when the virtual displacement is kinematically admissible.


**EXERCISE 7.19** Consider the force that constrains the velocity of the wheel in Exercise 7.11. Evaluate the virtual work done by this force when the generalized coordinates  $x_A$  and  $\theta$  are given arbitrary virtual increments. Then show that this work vanishes if the increments  $\delta x_A$  and  $\delta\theta$  are kinematically admissible.

**EXERCISE 7.20** Generalized coordinates for the linkage in Exercise 7.5 are the vertical distance  $y$  and the angles  $\theta$  and  $\psi$ . Determine the virtual work done by gravity and the constraint force exerted by the horizontal guide on collar  $B$ . Then show that the virtual work of the constraint force vanishes when  $\delta y$ ,  $\delta\theta$ , and  $\delta\psi$  are kinematically admissible.

**EXERCISE 7.21** A force is observed to depend on the  $x$  and  $y$  coordinates of the point at which it is applied according to  $\vec{F} = (x\vec{i} - y\vec{j}) / (x^2 + y^2)^{1/2}$ . Show that this force is conservative, and determine its potential-energy function. Is there a limitation on the range of values of  $x$  and  $y$  for which this function applies?

**EXERCISE 7.22** The slider in Exercise 7.1 has mass  $m$ , and the curved guide bar is situated in the vertical plane. Determine the differential equations of motion. Friction has negligible effect.

**EXERCISE 7.23** The collar of mass  $m$  slides over the smooth guide, which is elevated by  $\beta$  from the horizontal. The spring's stiffness is  $k$ , and its unstretched length  $0.8L$ . The force  $F$  acting tangentially to the guide varies in a known manner. Determine the equations of motion for the system.




Exercise 7.23

## Homework Problems


481

**EXERCISE 7.24** Rod  $AB$  slides through collar  $C$ , which is pinned to collar  $D$  that slides over the vertical guide. The bar's mass is  $m$ , and the mass of each collar is  $m/2$ . The motion is actuated by torque  $\Gamma(t)$ . The system lies in the vertical plane, and the spring is unstretched in the position where  $\theta = 20^\circ$ . Determine the equations of motion for the system. Then determine  $\theta$  for static equilibrium when  $(g/H)^{1/2} = 4 \text{ rad/s}$ ,  $(k/m)^{1/2} = 5 \text{ rad/s}$ ,  $L = 2H$ , and  $\Gamma = 0$ .




Exercise 7.24

**EXERCISE 7.25** The bar is supported by two springs whose stiffness is  $k$ . The springs are unstretched when the bar is horizontal. Determine the equations of motion. The force  $F$ , which acts perpendicularly to the bar, is a known excitation.




Exercise 7.25

**EXERCISE 7.26** The stiffness of the horizontal spring is  $2k$ , whereas the spring holding the small block has stiffness  $k$ . The masses are  $4m$  and  $m$  for the cart and the block, respectively. Frictional resistance at all contacting surfaces is negligible. Determine the equations of motion for the system.



Exercise 7.26

**EXERCISE 7.27** A downward force  $F(t)$  is applied to block 2. The masses are  $m_1 = 2m$ ,  $m_2 = 3m$ . (a) Derive the equation of motion corresponding to using  $y$  as the generalized coordinate for the system. (b) Derive the equation of motion corresponding to using  $\theta$  as the generalized coordinate for the system.




Exercise 7.27

**EXERCISE 7.28** A horizontal force  $H(t)$  is applied at the low end of the compound pendulum in Exercise 7.4. Both bars have mass  $m$ . Determine the corresponding differential equations of motion.




**EXERCISE 7.29** Identical small collars of mass  $m$  slide with negligible frictional resistance over the bar that is made to rotate in the vertical plane by torque  $\Gamma$  that acts about its pivot. The result is that the angle  $\theta$  is made to vary as a specified function of time. The unstretched length of the identical springs is  $L$ . Derive differential equations of motion governing the radial distances  $R_1$  and  $R_2$ .




Exercise 7.29

**EXERCISE 7.30** The linkage is braced by a spring of stiffness  $k$  in order to support the force  $P$  that acts perpendicularly to the long link. The system lies in the vertical plane, and  $\sigma$  is the mass per unit length of both bars. The spring is unstretched when  $\theta = 45^\circ$ . Derive the equation of motion governing  $\theta$ .



Exercise 7.30

**EXERCISE 7.31** Determine the equations of motion for the linkage shown in the diagram when the horizontal distance from pin  $A$  to piston  $B$  is used as the generalized coordinate. The mass of each bar is  $m$ , the mass of collar  $B$  is negligible, and the unstretched length of the spring is  $3L/4$ .




Exercise 7.31

**EXERCISE 7.32** Derive the differential equation governing the motion of the parallelogram linkage in Exercise 7.16. The mass per unit length of each bar is  $\sigma$ , and the unstretched length of the spring is  $2L$ .

**EXERCISE 7.33** Use Lagrange's equations to derive the differential equation of motion for the angle  $\theta$  at which the box in Exercise 6.32 is tilted.

**EXERCISE 7.34** The collar to which the bar is pinned is given a specified displacement  $u(t)$ . The collar and the bar have equal mass  $m$ . Use Lagrange's equations to derive the equations of motion for this system.




Exercise 7.34

# Homework Problems


483

**EXERCISE 7.35** The collar, whose mass is  $m_1$ , supports a bar whose mass is  $m_2$ . The springs restraining the collar have identical properties. Determine the equations of motion for this system.



Exercise 7.35

**EXERCISE 7.36** A simplified model of one blade of a helicopter is shown in the sketch. The short segment  $AB$  is driven at a constant rotational speed  $\Omega$ . The blade  $BC$  is connected to  $AB$  by a pin, about which is wrapped a torsional spring having stiffness  $k_T$ . The spring is unstressed when the lag angle  $\phi$  is zero. Derive the equation of motion governing  $\phi$ . Blade  $BC$  may be considered to be a homogeneous bar whose cross section is uniform.




Exercise 7.36

**EXERCISE 7.37** Consider the system treated in Example 7.12. Derive the differential equation of motion when  $\theta$  is used as the unconstrained generalized coordinate.


**EXERCISE 7.38** Use Lagrange's equations to solve Exercise 6.29.

**EXERCISE 7.39** The circular hoop rotates in the vertical plane about its pivot at the constant angular speed  $\omega$ , so  $\omega t$  is the angle from the diametral line to the vertical. The collar, whose mass is  $m$ , slides over the guide bar under the influence of the cable, which carries a known tensile force  $F$  at its free end. Frictional resistance between the collar and the guide is negligible. Derive the equation of motion for this system.




Exercise 7.39

**EXERCISE 7.40** A known torque  $\Gamma$  acts about the horizontal shaft, resulting in rotation  $\Omega$ . The collar slides without friction over the hoop. The collar is essentially a hollow circular cylinder whose axis of symmetry is the tangential  $x$  axis. The mass of the collar is  $m$ , and its centroidal moments of inertia are  $I_1$  and  $I_2$  about the  $x$  and  $z$  axes, respectively. The moment of inertia of the hoop-shaft assembly about its rotation axis is  $I_3$ . Derive the equations of motion based on the assumption that the collar does not spin about the  $x$  axis relative to the hoop.




Exercise 7.40

**EXERCISE 7.41** Application of the force  $F$  to the vertical control rod in the flyball speed governor causes the angle  $\theta$  to change. Simultaneously, a servomotor applies torque  $M$  to maintain a constant precession rate  $\Omega$ . Determine the differential equations of motion for this system. The mass of each sphere is  $m$ , and the links have negligible mass.




Exercise 7.41

**EXERCISE 7.42** Each collar has mass  $m$  and is sufficiently small to consider it to be a particle. The bar assembly on which the collars ride rotates about the vertical axis due to a known torsional load  $\Gamma(t)$ . The moment of inertia of the bar assembly about its axis of rotation is  $I$ . Derive the differential equations of motion for the system.




Exercise 7.42

**EXERCISE 7.43** The homogeneous semicylinder rolls without slipping. Derive the equation of motion governing the angle of rotation  $\psi$ .



Exercise 7.43

**EXERCISE 7.44** The known excitation force  $F$  pushes the cart to the right, which causes the homogeneous cylinder to roll without slipping relative to the cylindrical cavity in the cart. The mass of the cart is  $m_1$  and the mass of the cylinder is  $m_2$ . The spring's unstretched length is  $L$ , so  $x$  is the displacement from the static equilibrium position in the absence of  $F$ . It may be assumed that the cart's wheels are massless and friction at the wheel bearings is negligible. Derive differential equations of motion governing  $x$  and the angle  $\theta$  locating the center of the cylinder.




Exercise 7.44

**EXERCISE 7.45** The pulleys roll over the rack without slipping. The masses and centroidal radii of gyration are  $m_i$  and  $\kappa_i$  ( $i = 1$  for the left pulley and  $i = 2$  for the right). The spring, whose stiffness is  $k$ , is capable of sustaining both compressive and tensile forces. Determine the equations of motion.

# Homework Problems


485



Exercise 7.45


**EXERCISE 7.46** Use Lagrange's equations to derive the differential equation of motion governing the elevation angle for the box in Example 6.8.

**EXERCISE 7.47** The cylinders roll in the vertical plane such that there is no slipping between them, nor between cylinder  $A$  and the ground. The vertical surface is sufficiently smooth to assume that there is negligible frictional resistance there. The masses of the cylinders are  $m_A$  and  $m_B$ . Derive the equation of motion governing the unconstrained generalized coordinate  $\theta$ .




Exercise 7.47

**EXERCISE 7.48** Because of the cutout section, the center of mass of the gear is situated at a distance  $\varepsilon$  from the geometrical center. The gear has mass  $m_1$ , its centroidal radius of gyration is  $\kappa$ , and the mass of the rack is  $m_2$ . Friction between the rack and the incline is negligible. Derive differential equations of motion governing the angle  $\theta$  locating the center of mass and the distance  $s$  that the rack has translated.




Exercise 7.48

**EXERCISE 7.49** The couple  $M$  acting causing the crankshaft to rotate is resisted by the drag force  $f$  acting on the piston. The masses are  $m_1$ ,  $m_2$ , and  $m_3$  for the piston. Gravity is unimportant. Derive the differential equation governing the angle of rotation of the crankshaft.




Exercise 7.49

**EXERCISE 7.50** Two cylinders, each having mass  $m$ , are linked by a connecting rod whose mass is negligible. A known horizontal force  $F(t)$  is applied to the right cylinder, and neither cylinder slips in its rolling motion. In the initial position, the angle  $\theta$  locating the connecting pin is zero. Derive the equation of motion for this angle.




Exercise 7.50

**EXERCISE 7.51** The horizontal force  $F$  pushes cylinder  $A$  to the right, thereby pushing cylinder  $B$  up the hill. Both cylinders have identical mass  $m$  and radius of gyration  $\kappa$  about their axis of symmetry. The mass of the connecting rod also is  $m$ . Determine the equation of motion corresponding to using the elevation angle  $\theta$  of the connecting rod as the generalized coordinate. It may be assumed that there is no slippage when the cylinders roll.




Exercise 7.51

**EXERCISE 7.52** Force  $P$  acts normal to rack  $CD$ , which pivots about pin  $D$ . Because gear  $A$  must roll without slipping, the result is that rack  $B$  is forced to move to the left. The mass of the racks is  $m$ , and they may be approximated as homogeneous bars. The mass of the gear is  $2m$  and its radius of gyration about its center is  $0.8R$ . Derive the equations of motion for the system assuming that frictional resistance is unimportant.




Exercise 7.52

**EXERCISE 7.53** A circular disk of mass  $m$  is suspended in the horizontal plane by three cables of equal length  $L$ . The cables are vertical when the system is at its equilibrium position. Derive the equation of motion for the angle  $\theta$  by which the disk rotates about its vertical axis of symmetry. Assume that all cables remain taut.




Exercise 7.53

**EXERCISE 7.54** The slider, whose mass is  $m_1$ , oscillates within the groove in the turntable, so the distance  $s$  from the center of the block to the axis of the shaft is an undefined function of time. In turn, the turntable rotates freely relative to the shaft, so the nutation angle  $\theta$  also is variable, and the torque  $\Gamma(t)$  induces the precessional rotation  $\psi$ . The shaft is horizontal, and  $\psi = 0$  corresponds to the diagram depicting the vertical plane. The centroidal moments of inertia of the turntable are  $I_1$  and  $I_2$  about axes that are respectively perpendicular to, and parallel to, the shaft, and the inertia of the shaft may be ignored. The spring restraining the slider has stiffness  $k$  and it is unstretched when  $s = 0$ . Derive the Lagrange equations




Exercise 7.54

**EXERCISE 7.60** A shipping container is suspended from a crane by an inextensible cable. The crane rotates in the vertical plane at angular speed  $\Omega$  whose time dependence is known. It may be assumed that the cable remains taut, so its orientation is describable in terms of the angle  $\theta$  locating the vertical plane in which it is situated relative to the plane of the crane, and the angle of elevation  $\phi$  from a vertical line. Based on a model of the container as a small particle, derive differential equations of motion in which the only unknowns are  $\theta$  and  $\phi$ .




Exercise 7.60

**EXERCISE 7.61** Collar  $C$  is attached to the vertical shaft by a fork-and-clevis, so the angle of inclination  $\theta$  of bar  $AB$  is arbitrary. Because this bar slides through the collar, the distance  $\xi$  from the pivot point to the end of the bar is variable, but it may be assumed that the bar does not spin about its own axis. The vertical shaft rotates at the constant rate  $\Omega$ . Derive the differential equations governing  $\xi$  and  $\theta$ .



Exercise 7.61

**EXERCISE 7.62** The force–couple system  $\bar{F}$  and  $\bar{M}$  causes the vertical shaft to move upward and precess. The couple is such that the precession rate  $\dot{\psi}$  is constant, but the vertical displacement  $z$  of the shaft is not known *a priori*. The spring's extensional stiffness (in opposition to displacement  $z$ ) is  $k_E$ , and  $z = 0$  corresponds to the spring being undeformed. The mass of the shaft is  $m_1$ , and the mass of bar  $AB$  is  $m_2$ , and both bodies may be approximated as being very thin. Pin  $A$  is ideal, so the angle of inclination  $\theta$  is an unknown function of time. Derive the differential equations of motion for  $z$  and  $\theta$ .




Exercises 7.62 and 7.63

**EXERCISE 7.63** A specified force–couple system  $\bar{F}$  and  $\bar{M}$  causes the vertical shaft to move upward and precess. The spring's extensional stiffness  $k_E$  acts in opposition to displacement  $z$ , and the torsional stiffness  $k_T$  opposes precession  $\psi$ . The spring is undeformed in the position where  $z = \psi = 0$ . The mass of the shaft is  $m_1$ , the mass of bar  $AB$  is  $m_2$ , and both bodies may be approximated as being very thin. Pin  $A$  is ideal. Derive the differential equations of motion for  $z$ ,  $\psi$  and  $\theta$ .

# Homework Problems


489

**EXERCISE 7.64** A known torque  $\Gamma$  acting about the vertical shaft causes the T-bar to precess at angular speed  $\dot{\psi} = \Omega$ . Pin  $B$  is ideal, so the angle of elevation of bar  $BD$  also is unknown. The mass of bar  $BC$  is  $m$ , and the moment of inertia of the T-bar about its rotation axis is  $I_T$ . Derive the differential equations of motion governing  $\theta$  and  $\psi$ .




Exercise 7.64

**EXERCISE 7.65** A known couple  $\Gamma(t)$  induces rotation of the system about the vertical axis. Collars  $A$  and  $B$ , each of whose mass is  $m$ , are interconnected by a rigid bar whose mass is  $4m$ . The moment of inertia of the T-bar about the vertical axis is  $I_T$ . Derive the equations of motion for this system.




Exercise 7.65

**EXERCISE 7.66** A known torque  $\Gamma$  is applied to the vertical post, which causes the system to rotate about the vertical axis at angular speed  $\dot{\psi}$ . Pin  $B$  allows the angle  $\beta$  to change freely, but the spin rate of the flywheel is the constant value  $\dot{\phi}$ . The moment of inertia of the vertical post about its axis of rotation is  $I_P$ , the mass of the forked arm may be neglected, and the flywheel may be considered to be a thin disk with mass  $m$  and moment of inertia  $I_\phi$  about its spin axis. Derive the equations of motion for  $\dot{\psi}$  and  $\beta$ . Under what conditions will  $\beta$  be constant?




Exercise 7.66

**EXERCISE 7.67** Bent arm  $ABC$  is welded to the vertical shaft, which rotates at the constant rate  $\Omega$ . The square plate rotates freely about axis  $BC$  at angular speed  $\dot{\phi}$ , with  $\phi = 0$  corresponding to the plate being situated in the vertical plane, as shown in the sketch. Determine the differential equation governing  $\phi$ .



Exercise 7.67

**EXERCISE 7.68** Collar  $A$  is welded to the vertical shaft, so the angle  $\theta$  is constant. The rectangular plate is welded to bar  $BC$ , which may slide through the collar and rotate by angle  $\phi$  about its own axis relative to the collar. When  $\phi = 0$ , the plate is in the upright position shown. The whole system freely precesses about the vertical axis, and frictional resistance is negligible. Only the mass of the plate is significant. Derive the differential equations of motion for this system.



Exercise 7.68

**EXERCISE 7.69** The semicylinder in Exercise 7.43 is released from rest with its flat side in the vertical plane,  $\psi = \pi/2$ . Determine and graph the ensuing response  $\psi(t)$ . From that result deduce the period of oscillation. Compare that result with the period when the semicylinder is released from rest at  $\psi = \pi/20$ . *Hint:* Use the nondimensional time  $\tau = (g/R)^{1/2}t$  to remove algebraic parameters from the differential equations.

**EXERCISE 7.70** Consider the system in Example 7.15 when there is no applied couple,  $M = 0$ . The system is initially at rest at  $\theta = 80^\circ$  when a constant force  $F = 2mg$  is applied. The spring stiffness is  $k = 0.5mg/L$ . Determine whether the linkage attains the horizontal position,  $\theta = 0$ . If so, what is the elapsed time and angular speed  $\dot{\theta}$  for that condition?

**EXERCISE 7.71** The parameters of the system in Exercise 7.64 are  $R = L$ ,  $I_T = 0.5mL^2$ ,  $M = 4mgL$ , and  $(L/g)^{1/2} = 0.1$  s. The system is released from rest at  $t = 0$  with  $\theta = 90^\circ$ . Determine  $\theta$  as function of time in the ensuing motion, as well as the torque  $\Gamma$ . What is the minimum value of  $\theta$  during the course of the motion? Does  $\theta$  approach a steady-state value?

**EXERCISE 7.72** Prior to  $t = 0$  the spherical pendulum in Example 7.14 was undergoing a steady precession at angle of inclination  $\theta = 15^\circ$ , with the cable length  $\ell$  constant at a specified value  $L$ . The angular speed  $\Omega$  in this condition was the value associated with steady precession at a constant cable length. At  $t = 0$  the tensile force is suddenly changed from the value required for steady precession to  $F = 4mg$ . Determine and graph as functions of time the length  $\ell$ , angle  $\theta$ , and precession rate  $\Omega$ . Compare the instants when each of these variables have their maximum and minimum values. *Hint:* Use the nondimensional time  $\tau = (g/L)^{1/2}t$  to convert the equations of motion to a form suitable for numerical integration.

**EXERCISE 7.73** The compound pendulum in Exercise 7.4 is released from rest with both bars inclined at  $75^\circ$  from the vertical position. The bars are identical with  $(g/L)^{1/2} = 2$  rad/s. Examine the equations of motion to determine whether it is possible for the system to oscillate with both bars remaining aligned. Then solve the equations of motion to determine each angle of inclination as a function of time. Is the response periodic?

**EXERCISE 7.74** The system in Exercise 7.54 is initially at rest in the vertical plane,  $\psi = 0$ , with the groove tilted at  $\theta = \pi/4$  and the block coincident with the axis of the shaft,  $s = 0$ . At that instant a constant torque of  $M = 40$  N-m is applied. Determine and graph the displacement  $s$  and rotation  $\theta$  as functions of time. Also graph the precession



# Homework Problems

491

rate  $\dot{\psi}$ . Properties of the system are  $m_1 = 500$  g,  $k = 128$  N/m, and  $I_1 = 2.5$  kg-m<sup>2</sup>,  $I_2 = 1.5$  kg-m<sup>2</sup>.

**EXERCISE 7.75** The system of interest is the flyball governor in Exercise 7.41 in the case where the torque  $M$  acting about the vertical axis is zero. Suitable generalized coordinates are  $q_1 = \psi$  and  $q_2 = \theta$ , where  $\psi$  is the precession angle. The initial conditions for the system are

$$\psi = 0, \quad \dot{\psi} = 1500 \text{ rev/min}, \quad \theta = 85^\circ, \quad \dot{\theta} = 0 \text{ @ } t = 0,$$

and the system parameters are  $m = 250$  g, and  $L = 400$  mm. (a) If properly derived, the Lagrange equation associated with  $\psi$  is a perfect differential. The result of integrating that equation is the constant angular momentum about the  $z$  axis, which relates the values of  $\dot{\psi}$  and  $\theta$  corresponding to the specified initial conditions. Solve this equation for  $\dot{\psi}$  at  $\theta = 30^\circ$ . (b) Let  $F$  have the constant value obtained from the Lagrange equation when  $\theta = 30^\circ$ ,  $\dot{\theta} \equiv 0$ , and  $\dot{\psi}$  has the value found in Part (a). Use numerical methods to solve the equations of motion corresponding to this value of  $F$  and the specified initial conditions. Plot  $\psi$  and  $\theta$  as functions of  $t$  for an interval sufficiently long to ascertain whether  $\theta = 30^\circ$  is a dynamic equilibrium state. Check the correctness of the integration by monitoring whether the angular momentum about the vertical axis is constant. (c) An alternative value of  $F$  is found by simultaneously solving the angular momentum equation in Part (a) and the work-energy principle  $\Delta T + \Delta V = F\Delta y_B$ , where  $\Delta y_B$  is the upward displacement of the vertical bar to which  $F$  is applied. The initial conditions for this evaluation of  $F$  are those specified and  $\theta = 30^\circ$  and  $\dot{\theta} = 0$  at the second position. The value of  $F$  obtained in this manner does the minimum amount of work required to attain the second state, but it is possible that this value of  $F$  would not be adequate to move the system beyond some intermediate position. Solve the equations of motion with the initial conditions set at the specified values and  $F$  equated to this minimum-work value. Does the system actually arrive at  $\theta = 30^\circ$  with  $\dot{\theta} = 0$ ?

## CHAPTER 8

# Constrained Generalized Coordinates

The basic development of Lagrange's equations in the preceding chapter is suitable for many important engineering applications. However, up to now these equations have only been employed when the generalized coordinates constitute an unconstrained set. The first part of this chapter removes this limitation. For nonholonomic systems the use of constrained generalized coordinates is mandatory. However, it might be desirable to use constrained coordinates to analyze holonomic systems, as will be seen. This is the situation when the effect of sliding friction is an important feature, which will be treated in depth.

Regardless of whether one follows the Lagrangian or Newton–Euler approach, derivation of the differential equations of motion is only the first phase of a dynamic analysis. Solution of those equations to simulate a system's response is usually the ultimate objective. As several examples have already demonstrated, the equations of motion can be quite complicated, and therefore not amenable to analytical solution. The basic state-space approach to solving the differential equations of motion associated with holonomic systems was developed in Section 7.6. The occurrence of constraint equations and Lagrange multipliers requires modification of that formulation. The second part of this chapter develops and implements several numerical algorithms that may be used to solve the equations of motion governing constrained generalized coordinates.

## 8.1 LAGRANGE'S EQUATIONS—CONSTRAINED CASE

Lagrange's equations for unconstrained coordinates constitute a set of differential equations of motion whose number equals the number of generalized coordinates. Thus the only other information required to solve these equations is an appropriate set of initial conditions. When generalized coordinates are constrained, the equations of motion are supplemented by kinematical constraint equations. Another difference is that an arbitrary virtual movement will not be consistent with the stated constraint conditions, which has the consequence of causing constraint forces to be manifested in the generalized forces. Our first task is to see how to synthesize a solvable set of equations in this situation. We then consider some general situations in which constrained generalized coordinates are either necessary or useful, and specific procedures for analyzing each situation.

### 8.1 Lagrange's Equations—Constrained Case

493

As we saw in the previous chapter, scleronomic (time-invariant) and rheonomic (time-dependent) configuration constraints can be written as linear velocity constraint equations, which is the only form of nonholonomic constraint we consider here. Writing all constraint equations in velocity form is more than a matter of convenience. The equations that result turn out to be much more amenable to standard numerical analysis than they would be if configuration constraints equations were used. Thus we consider a set of  $N$  generalized coordinates that are required to satisfy  $J$  velocity constraint equations described by

$$\sum_{j=1}^N a_{ij} \dot{q}_j + b_i = 0, \quad i = 1, 2, \dots, J. \quad (8.1.1)$$

The Jacobian constraint coefficients  $a_{ij}$ , which multiply the generalized velocities, as well as the  $b_i$  coefficients, may depend on the values of the  $q_j$  variables and time  $t$ .

By definition, the symbol  $Q_j$  represents the role of all nonconservative forces, as well as any conservative forces that have not been represented by the potential energy. Let us apportion  $Q_j$  into two parts:  $Q_j^{(a)}$  is associated with the applied loads and  $R_j$  is associated with the unknown reactions,

$$Q_j = Q_j^{(a)} + R_j. \quad (8.1.2)$$

A constraint force enforces each constraint equation that is described by Eq. (8.1.1). The influence of each such force will appear in the  $R_j$  terms. Virtual work is additive as a scalar, which means that  $R_j$  is a scalar sum of the contribution  $R_j^{(i)}$  associated with each constraint:

$$R_j = \sum_{i=1}^J R_j^{(i)}, \quad j = 1, 2, \dots, N. \quad (8.1.3)$$

We saw in Subsection 7.4.2 that knowledge of the Jacobian constraint coefficients is sufficient to characterize each  $R_j^{(i)}$  term. According to Eq. (7.4.12), a Lagrange multiplier  $\lambda_i$  is proportional to  $R_j^{(i)}$ . When we use that equation to represent each  $R_j^{(i)}$  term in Eq. (8.1.3), and combine that result with  $Q_j^{(a)}$ , the resulting Lagrange's equations are

$$\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \right) - \frac{\partial T}{\partial q_j} + \frac{\partial V}{\partial q_j} = Q_j^{(a)} + \sum_{i=1}^J a_{ij} \lambda_i, \quad j = 1, 2, \dots, N. \quad (8.1.4)$$

In some situations it is necessary to determine the actual constraint forces  $C_i$ , as well as the generalized coordinates. We may obtain these quantities from the associated Lagrange multipliers  $\lambda_i$  by invoking Eqs. (7.4.16), which stated that  $C_i = \sigma_i \lambda_i$ . We may identify the proportionality factors  $\sigma_i$  by explicitly evaluating the virtual work of the constraint forces. Alternatively, we can express the virtual work explicitly in terms of the constraint forces. This approach will be demonstrated in Example 8.7.

The requirement that one eliminate all variables other than the  $q_j$  and  $t$  from the potential and kinetic energies applies equally for constrained and unconstrained generalized coordinates. Such an analysis leads to the functions  $T(q_n, \dot{q}_n, t)$  and  $V(q_n, t)$ . It follows that the terms on the left side of Lagrange's equations will contain generalized coordinates, velocities, and accelerations. Thus these equations constitute a set of  $N$  differential equations governing the  $N$  generalized coordinates. They are not a sufficient set of equations because they also contain  $J$  unknown  $\lambda_i$  parameters. The necessary  $J$  additional equations are provided by the kinematical constraint equations. Thus evaluation of system response when a system is described by constrained generalized coordinates entails simultaneously satisfying  $N$  differential equations of motion, given by Eqs. (8.1.4) and  $J$  differential equations of constraint, Eq. (8.1.1). The result of such a solution would be the value of each  $q_j$  and each  $\lambda_i$  as a function of  $t$ .

When a system has nonholonomic constraints, we have no choice but to use constrained coordinates. However, we might decide to use constrained generalized coordinates to describe holonomic systems. One reason for doing so is to simplify the synthesis of the equations of motion. This aspect may be explained by considering a one-degree-of-freedom system. Suppose the positions of various parts of such a system are conveniently described by two generalized coordinates that are related by a scleronomic constraint,  $f(q_1, q_2) = 0$ . If we wish to use  $q_1$  as a single unconstrained generalized coordinate, we must algebraically solve this constraint equation for  $q_2$  in terms of  $q_1$ . It might be that this solution,  $q_2 = g(q_1)$ , is extremely difficult to obtain, but if we succeed in doing so, we must differentiate it to describe the generalized velocity,  $\dot{q}_2 = \dot{q}_1 (dg/dq_1)$ . Substitution of this relationship and  $q_2 = g(q_1)$  into the energy expressions yields  $T$  and  $V$  as functions of only  $q_1$  and  $\dot{q}_1$ . These functions are likely to be quite complicated unless the  $g$  function has a simple form. Now consider the alternative of using both  $q_2$  and  $q_1$  to describe the system. The velocity constraint equation obtained by differentiating the configuration constraint will be enforced explicitly as part of the solution, so  $q_1$  and  $q_2$  are treated as completely independent variables in the formulation. Thus we leave the energy expressions in basic forms containing both  $q_1$  and  $q_2$ . Because the expressions for  $T$  and  $V$  will be functionally simpler, the complexity of the operations required to form Lagrange's equations will be lessened. At the same time, there is a penalty, because there are two Lagrange equations and a velocity constraint in this case, as opposed to the single Lagrange equation when  $q_1$  solely is used. In essence, the philosophy underlying the use of constrained generalized coordinates for complicated holonomic systems is to shift the burden from formulating the equations of motion to solving them. Computer methods are quite adept at the latter, as we will see.

Another reason to use constrained generalized coordinates to describe a holonomic system is to evaluate constraint forces. If we were to use unconstrained generalized coordinates, reaction forces could be determined by a multiphase process that begins with the solution of the equations of motion, and saving the values of  $q_j$ ,  $\dot{q}_j$ , and  $\ddot{q}_j$  at each instant. These results would be used to compute the linear and angular positions, velocities, and accelerations of all parts of the system. Substituting those values into the Newton–Euler equations of motion for individual bodies would yield the constraint force of interest. Such a procedure is suitable to situations in which most or

## 8.1 Lagrange's Equations—Constrained Case

495

all of the reaction forces need to be evaluated, but it is inefficient if only a few reactions are of interest. In contrast, it is possible to solve for the instantaneous reactions simultaneously with the generalized coordinates when we use constrained generalized coordinates.

We previously encountered in Example 7.14 a simple situation suggesting how constrained generalized coordinates can be used for this purpose. We found there that we could obtain an expression for the cable force in the spherical pendulum by considering the cable length to be a generalized coordinate subject to a rheonomic constraint, rather than a specified length variable. The general concept underlying the treatment of such situations uses a set of generalized coordinates that do not automatically satisfy the kinematical condition imposed by the desired constraint force. This force, in the form of the associated Lagrange multiplier, will appear in the equations of motion. Solution of the differential equations of motion formulated in this manner would yield the time history of the Lagrange multiplier. The actual constraint force can then be determined from  $C_i = \sigma_i \lambda_i$ , as described by Eqs. (7.4.16).

The need to evaluate a constraint force is often a discretionary matter. However, in situations involving Coulomb sliding friction, the evaluation of the normal force is an intrinsic part of the solution process, because the magnitude of the tangential friction force depends on the normal force. The sliding friction force does not prevent motion. Therefore it acts like an applied force that does virtual work. Hence, even if we use unconstrained generalized coordinates, the magnitude of the normal force will always occur in some of the generalized forces. The procedure we follow is to use constrained generalized coordinates that are selected such that the constraint against movement perpendicular to the contact surface must be enforced explicitly. The associated normal force will appear in the virtual work in addition to the friction force. The constraint equations and the additional Lagrange equations arising from using more generalized coordinates than necessary will provide the requisite number of equations.

A system illustrating this aspect is the linkage in Fig. 8.1, which was the subject of Example 7.15. In the previous analysis there was no friction between collar  $C$  and the guide bar, so the angle  $\theta$  could be used as an unconstrained coordinate, with the angle  $\phi$  for bar  $BC$  equated to  $\theta$ . If there is sliding friction at the collar, that analysis will not suffice, because the friction force will do virtual work when  $\theta$  is incremented. The friction force  $f$  is proportional to the magnitude of the normal force, so the single equation of motion would contain two unknowns,  $\theta$  and  $N_C$ . A constrained formulation of this problem could use  $\theta$  and  $\phi$  as generalized coordinates that must satisfy the scleronomous constraint,  $\theta - \phi = 0$ . Because it is necessary to violate the kinematical constraint of the collar without having other constraint forces contribute to the virtual work, the




Figure 8.1. A linkage in which there is friction at collar  $C$ .

Considering the thickness of both bars to be negligible gives

$$\begin{aligned} T &= \frac{1}{2} I_3 \dot{\psi}^2 + \frac{1}{2} \left( \frac{1}{3} m_1 H^2 \right) \dot{\psi}^2 + \frac{1}{2} m_2 v_G^2 + \frac{1}{2} \bar{\omega}_{BC} \cdot \bar{H}_G \\ &= \frac{1}{2} \left( I_3 + \frac{1}{3} m_1 H^2 \right) \dot{\psi}^2 + \frac{1}{2} m_2 \left[ \dot{\psi}^2 \left( H + \frac{L}{2} \cos \theta \right)^2 + \frac{L^2}{4} \dot{\theta}^2 \right] \\ &\quad + \frac{1}{2} \left( \frac{1}{12} m_2 L^2 \right) \left[ \dot{\theta}^2 + \dot{\psi}^2 (\cos \theta)^2 \right] \\ &= \frac{1}{2} \left( \frac{1}{3} m_2 L^2 \right) \dot{\theta}^2 + \frac{1}{2} \left[ I_3 + \left( \frac{1}{3} m_1 + m_2 \right) H^2 \right. \\ &\quad \left. + \left( \frac{1}{3} m_2 L^2 \right) (\cos \theta)^2 + m_2 H L \cos \theta \right] \dot{\psi}^2. \end{aligned}$$

We define the datum for gravitational potential energy to coincide with the shaft. We may find the elevation of point  $G$  by geometrically projecting this point's position onto the vertical direction, or else by coordinate transformations. Either way, the result is

$$V = m_1 g \frac{H}{2} \cos \psi + m_2 g \left( H + \frac{L}{2} \cos \theta \right) \cos \psi.$$

Note that the positive sign for the elevation applies because  $\psi = 0$  was defined to correspond to bar  $AB$  being upright.

To evaluate the virtual work we observe that  $\Gamma$  imposes the constraint on  $\dot{\psi}$ . We can represent its effect with a Lagrange multiplier. (If we wished to derive an equation for  $\Gamma$  we would evaluate how it contributes to the virtual work, rather than using a Lagrange multiplier.) The bearing forces constrain the shaft from moving, and those constraints are not violated by a virtual movement, regardless of the values of  $\delta\psi$  and  $\delta\theta$ . Thus we have  $\delta W = 0$ , so that  $Q_1 = Q_2 = 0$ . (Depending on how the bearings are designed, it is possible that they also exert couples orthogonally to the shaft. Those couples too would not appear in  $\delta W$  because they would impose rotational constraints that are not violated in the virtual movement.) We form the derivatives of  $T$  and  $V$  appearing in Lagrange's equations and substitute the result into the Lagrange multiplier form of the equations of motion, Eq. (8.1.4). This yields

$$\begin{aligned} \frac{1}{3} m_2 L^2 \ddot{\theta} + \left[ \frac{1}{3} m_2 L^2 (\cos \theta) + \frac{1}{2} m_2 H L \right] (\sin \theta) \dot{\psi}^2 - \frac{1}{2} m_2 g L \sin \theta \cos \psi &= a_{11} \lambda_1 = 0 \\ \left[ I_3 + \left( \frac{1}{3} m_1 + m_2 \right) H^2 + \left( \frac{1}{3} m_2 L^2 \right) (\cos \theta)^2 + m_2 H L \cos \theta \right] \ddot{\psi} \\ - \left[ \frac{2}{3} m_2 L^2 (\cos \theta) + m_2 H L \right] (\sin \theta) \dot{\theta} \dot{\psi} - \left( \frac{1}{2} m_1 + m_2 \right) g \sin \psi \\ - \frac{1}{2} m_2 g L \cos \theta \sin \psi &= a_{12} \lambda_1 = \lambda_1. \end{aligned} \quad \triangleleft$$


## 8.1 Lagrange's Equations—Constrained Case

499

There are three unknowns in these two equations; the third equation is the constraint,  $\dot{\psi} = b\dot{\theta}^2$ .

The simple nature of some constraint equations, such as  $\dot{\psi} = c\dot{\theta}$  in the present case, sometimes leads inexperienced individuals to a fundamental error. It might seem that we could simplify the energy expressions if we were to use the constraint equations to eliminate one or more generalized coordinates. For example, here we could completely eliminate  $\theta$  by substituting  $\theta = (\dot{\psi}/b)^{1/2}$ . However, this is a forbidden operation. The reason for this prohibition goes back to the derivation of Lagrange's equations, which requires an arbitrary virtual displacement, whereas using a constraint equation in the aforementioned manner limits the adjacent variational paths.

**EXAMPLE 8.2** A known torque  $M(t)$  actuates the linkage. The masses are  $m_1$ ,  $m_2$ , and  $m_3$  for bars  $AB$ ,  $BC$ , and  $DE$ , respectively, and collar  $C$  has mass  $m_4$ . The system lies in the vertical plane, and friction is negligible. Derive the equations of motion.



Example 8.2

**SOLUTION** The benefits of using constrained generalized coordinates to lessen the complications of geometrical complexity are demonstrated in this example. We encountered this system previously in Example 7.6. It has two degrees of freedom, because the position of all bars is specified by their respective angles, and one angle is algebraically related to the other two. If we were to use  $\theta_1$  and  $\theta_2$  as unconstrained generalized coordinates, we would find that the expression for  $\theta_3$  is fairly complicated, so that the kinetic-energy expression is intricate. We therefore use all three angles as a set of constrained generalized coordinates.

The first task is to establish the constraint equation these variables must satisfy. We could obtain the velocity equation directly by following a linkage analysis, according to

$$\bar{v}_C = v_{\text{rel}}\bar{e}_{E/D} + \dot{\theta}_3\bar{k} \times \bar{r}_{C/D} = \dot{\theta}_1\bar{k} \times \bar{r}_{B/A} + \dot{\theta}_2\bar{k} \times \bar{r}_{C/B}.$$

However, Example 7.6 derived the configuration constraint based on the horizontal and vertical distances proceeding from pin  $A$  to pin  $B$  and then pin  $C$ . Doing so gave

$$\tan \theta_3 = \frac{L_1 \sin \theta_1 + L_2 \sin \theta_2}{L_1 \cos \theta_1 + L_2 \cos \theta_2 - H},$$

which may be rewritten as

$$\left( \cos \theta_1 + \frac{L_2}{L_1} \cos \theta_2 - \frac{H}{L_1} \right) \tan \theta_3 - \sin \theta_1 - \frac{L_2}{L_1} \sin \theta_2 = 0.$$

Differentiation of this expression yields the velocity constraint equations:

$$\begin{aligned} a_{11}\dot{\theta}_1 + a_{12}\dot{\theta}_2 + a_{13}\dot{\theta}_3 &= 0, \\ a_{11} &= -\sin \theta_1 \tan \theta_3 - \cos \theta_1, \quad a_{12} = -\frac{L_2}{L_1} (\sin \theta_2 \tan \theta_3 + \cos \theta_2), \quad \triangleleft \\ a_{13} &= \frac{L_1 \cos \theta_1 + L_2 \cos \theta_2 - H}{L_1 (\cos \theta_3)^2}. \end{aligned}$$

The kinetic energy of the system is the sum of contributions of the three bars and the sliding collar. Each term may be described in terms of whichever generalized coordinates are appropriate, without concern for the fact that they are constrained. Thus the angular velocities of the bars are  $\dot{\theta}_1 \bar{k}$ ,  $\dot{\theta}_2 \bar{k}$ , and  $\dot{\theta}_3 \bar{k}$ . Bars  $AB$  and  $DE$  are in pure rotation. We may obtain expressions for the velocity of the center of mass of bar  $BC$  and of the collar by differentiating the respective position vectors described in terms of  $\theta_1$  and  $\theta_2$ , which are

$$\begin{aligned} \bar{r}_{G2/A} &= \left( L_1 \cos \theta_1 + \frac{L_2}{2} \cos \theta_2 \right) \bar{i} + \left( L_1 \sin \theta_1 + \frac{L_2}{2} \sin \theta_2 \right) \bar{j}, \\ \bar{r}_{C/A} &= (L_1 \cos \theta_1 + L_2 \cos \theta_2) \bar{i} + (L_1 \sin \theta_1 + L_2 \sin \theta_2) \bar{j}, \end{aligned}$$

which leads to

$$\begin{aligned} \bar{v}_{G2} &= \left( -L_1 \dot{\theta}_1 \sin \theta_1 - \frac{L_2}{2} \dot{\theta}_2 \sin \theta_2 \right) \bar{i} + \left( L_1 \dot{\theta}_1 \cos \theta_1 + \frac{L_2}{2} \dot{\theta}_2 \cos \theta_2 \right) \bar{j}, \\ \bar{v}_C &= (-L_1 \dot{\theta}_1 \sin \theta_1 - L_2 \dot{\theta}_2 \sin \theta_2) \bar{i} + (L_1 \dot{\theta}_1 \cos \theta_1 + L_2 \dot{\theta}_2 \cos \theta_2) \bar{j}. \end{aligned}$$

Let  $L_3$  be the length of bar  $DE$ . Then the kinetic energy derived from these expressions is

$$\begin{aligned} T &= \frac{1}{2} \left( \frac{1}{3} m_1 L_1^2 \right) \dot{\theta}_1^2 + \frac{1}{2} m_2 \left[ \left( -L_1 \dot{\theta}_1 \sin \theta_1 - \frac{L_2}{2} \dot{\theta}_2 \sin \theta_2 \right)^2 \right. \\ &\quad \left. + \left( L_1 \dot{\theta}_1 \cos \theta_1 + \frac{L_2}{2} \dot{\theta}_2 \cos \theta_2 \right)^2 \right] + \frac{1}{2} \left( \frac{1}{12} m_2 L_2^2 \right) \dot{\theta}_2^2 \\ &\quad + \frac{1}{2} \left( \frac{1}{3} m_3 L_3^2 \right) \dot{\theta}_3^2 + \frac{1}{2} m_4 \left[ \left( -L_1 \dot{\theta}_1 \sin \theta_1 - L_2 \dot{\theta}_2 \sin \theta_2 \right)^2 \right. \\ &\quad \left. + \left( L_1 \dot{\theta}_1 \cos \theta_1 + L_2 \dot{\theta}_2 \cos \theta_2 \right)^2 \right]. \end{aligned}$$

Collecting like coefficients of the generalized velocities converts this to

$$\begin{aligned} T &= \frac{1}{2} \left( \frac{1}{3} m_1 + m_2 + m_4 \right) L_1^2 \dot{\theta}_1^2 + \frac{1}{2} \left( \frac{1}{3} m_2 + m_4 \right) L_2^2 \dot{\theta}_2^2 + \frac{1}{2} \left( \frac{1}{3} m_3 L_3^2 \right) \dot{\theta}_3^2 \\ &\quad + \frac{1}{2} (m_2 + 2m_4) L_1 L_2 \cos (\theta_1 - \theta_2) \dot{\theta}_1 \dot{\theta}_2. \end{aligned}$$



### 8.1 Lagrange's Equations—Constrained Case

501

The system is stated to lie in the vertical plane, which implies that the analysis should account for gravity. The elevation of the center of mass of each body above the datum for gravity, which we take to coincide with pins  $A$  and  $D$ , may be represented in terms of whichever of the generalized coordinates is most suitable. Hence the potential energy of gravity is


$$\begin{aligned} V &= m_1 g \frac{L_1}{2} \sin \theta_1 + m_2 g \left( L_1 \sin \theta_1 + \frac{L_2}{2} \sin \theta_2 \right) \\ &\quad + m_4 g (L_1 \sin \theta_1 + L_2 \sin \theta_2) + m_3 g \frac{L_3}{2} \sin \theta_3 \\ &= \left( \frac{m_1}{2} + m_2 + m_4 \right) g L_1 \sin \theta_1 + \left( \frac{m_2}{2} + m_4 \right) g L_2 \sin \theta_2 + \frac{m_3}{2} g L_3 \sin \theta_3. \end{aligned}$$

The constraints imposed by pin  $A$  and  $D$  are not violated when the angle of each bar is incremented. Therefore the only nonconservative load contributing to the virtual work is the torque  $M$ , which gives  $\delta W = M \delta \theta_1 \implies Q_1 = M$ ,  $Q_2 = Q_3 = 0$ . The Jacobian coefficients were listed earlier. The three Lagrange equations that result are

$$\begin{aligned} \left( \frac{1}{3} m_1 + m_2 + m_4 \right) L_1^2 \ddot{\theta}_1 + \frac{1}{2} (m_2 + 2m_4) L_1 L_2 [\ddot{\theta}_2 \cos(\theta_1 - \theta_2) + \dot{\theta}_2^2 \sin(\theta_1 - \theta_2)] \\ + \left( \frac{m_1}{2} + m_2 + m_4 \right) g L_1 \cos \theta_1 &= Q_1 + a_{11} \lambda_1 = M - (\sin \theta_1 \tan \theta_3 + \cos \theta_1) \lambda_1, \\ \left( \frac{1}{3} m_2 + m_4 \right) L_2^2 \ddot{\theta}_2 + \frac{1}{2} (m_2 + 2m_4) L_1 L_2 [\ddot{\theta}_1 \cos(\theta_1 - \theta_2) - \dot{\theta}_1^2 \sin(\theta_1 - \theta_2)] \\ + \left( \frac{m_2}{2} + m_4 \right) g L_2 \cos \theta_2 &= Q_2 + a_{12} \lambda_1 = -\frac{L_2}{L_1} (\sin \theta_2 \tan \theta_3 + \cos \theta_2) \lambda_1, \\ \frac{1}{3} m_3 L_3^2 \ddot{\theta}_3 &= Q_3 + a_{13} \lambda_1 = \frac{L_1 \cos \theta_1 + L_2 \cos \theta_2 - H}{L_1 (\cos \theta_3)^2} \lambda_1. \end{aligned} \quad \triangleleft$$

Evaluation of the response would entail simultaneously solving these three equations of motion and the constraint equation for the three generalized coordinates and the Lagrange multiplier  $\lambda_1$ . We could eliminate the Lagrange multiplier by solving one equation of motion for  $\lambda_1$ , and substituting that expression into the other two equations of motion. This would reduce the problem to three simultaneous differential equations (two equations of motion and the velocity constraint), whose form would be significantly more complicated than the original set of four equations.

**EXAMPLE 8.3** A known force  $\bar{F}$  is applied to the yoke, causing the system to move rightward. The disk rolls without slipping, and the coefficient of kinetic friction between pin  $B$  and the yoke is  $\mu$ . Masses are  $m_1$  for the yoke and  $m_2$  for the homogeneous disk. Derive the equations of motion.




Example 8.3

**SOLUTION** We see here how constrained generalized coordinates are used to analyze systems with Coulomb friction. As was shown in Example 7.1, this system has a single degree of freedom. That example derived the velocity constraint and corresponding configuration constraint that must be satisfied by  $x$  and  $\theta$  in order that the pin remain situated in the groove of the yoke. The result was

$$\dot{x} - \dot{\theta}(R + \varepsilon \cos \theta) = 0 \iff x - R\theta - \varepsilon \sin \theta = C, \quad (1)$$

where  $C$  depends on where the disk is situated when  $x = \theta = 0$ . We need to obtain equations of motion in which the normal force exerted between pin  $B$  and the yoke appears. That force imposes Eq. (1). We select  $q_1 = \theta$  and  $q_2 = x$  as generalized coordinates because arbitrary increments of each will result in the normal force appearing in  $\delta W$ . The disk is always situated on the ground, and the yoke is on the guide bar, so that the only constraint not automatically satisfied is the one associated with pin  $B$ .

To capture the effect of the forces exerted at pin  $B$ , we draw a free-body diagram of each body. The forces at the ground are constraint forces associated with the no-slip condition, and  $\bar{N}_3$  prevents vertical movement of the yoke; these conditions are not violated when  $x$  and  $\theta$  are incremented. Also, the center of mass of each body displaces horizontally in this virtual movement. Thus the only forces that do virtual work are the normal force  $\bar{N}_2$ , the friction force  $\bar{f}_2$  associated with contact between pin  $B$  and the yoke, and the applied force  $\bar{F}$ .



Free-body diagrams of the rolling disk and the yoke showing the pin force exerted between them.

These constitute three differential equations for  $\theta$ ,  $x$ , and  $N_2$ . Their relatively simple form allows us to contemplate reducing the number of equations. Two different approaches are possible. We can eliminate  $N_2$  by solving the second of Eqs. (6) to obtain

$$N_2 = F - m_2 \ddot{x}. \quad (7)$$

If we substitute Eq. (7) into the first of Eqs. (6), we can ignore the second of Eqs. (6) when we solve the equations of motion. Alternatively, we can eliminate  $x$  by differentiating the constraint equation with respect to  $t$ , which yields

$$\ddot{x} = \ddot{\theta} (R + \varepsilon \cos \theta) - \varepsilon \dot{\theta}^2 \sin \theta. \quad (8)$$

Substitution of Eq. (8) into the second of Eqs. (6) allows us to ignore the third equation in the solution process. Furthermore, substitution of both Eqs. (7) and (8) into the first of Eqs. (6) reduces the problem to a single, rather complicated, differential equation for  $\theta$ . In the ideal case, in which  $\mu = 0$ , that equation would be found to be identical to the one we would have obtained by using  $\theta$  as a single unconstrained generalized coordinate.


**EXAMPLE 8.4** A thin disk wobbles as it rolls without slipping along the ground. Consequently, the plane of the disk is inclined at an unsteady angle. Derive the equations of motion for the system. Then specialize the result to the steady precession case, in which the disk is tilted at a constant angle and the disk's center follows a circular path. The radius of gyration of the disk about its axis of symmetry is  $\kappa$ .

**SOLUTION** This problem is a comprehensive illustration of the use of Lagrange multipliers. We will solve the resulting equations of motion in the next section. The position of any rigid body may always be described in terms of three position coordinates for any point, such as the center of mass, and three Eulerian angles. The circular shape of the disk and the absence of slipping constrain some of these variables, so we recall from Section 4.4 the kinematical analysis of a disk that wobbles as it rolls without slipping.

The first step is to draw a free-body diagram of the disk, in which several reference frames are depicted. The axes of  $XYZ$  are fixed, and  $x'y'z'$  is defined to have its origin at the center of the disk with the  $z'$  axis always vertical and the  $y'$  axis always coincident with the horizontal diametral line for the disk. The angle between  $y'$  and  $\bar{J}$  for the fixed reference frame is defined to be the precession angle  $\psi$ , and  $y'$  is the line of nodes for nutation angle  $\theta$  measured from vertical to the axis of symmetry. The  $xyz$  reference frame is defined to execute the nutation relative to  $x'y'z'$ , with the  $z$  and  $z'$  axes always coincident. The  $x'y'$  plane is horizontal, so the friction force has been represented in the free-body diagram in terms of components parallel to the  $x'$  and  $y'$  axes. The only other forces are the normal reaction and gravity.

## 8.1 Lagrange's Equations—Constrained Case

505



Free-body diagram and Eulerian angles for a disk that rolls unsteadily.

To ascertain the kinematical restrictions imposed on the Eulerian angles and position coordinates, we relate the velocities of the constrained points on the disk: the contact point and the center. Because of the rotational symmetry of the disk, a kinematical description using  $xyz$  components will yield a general representation. The angular velocity of the disk is the vector sum of precession  $\dot{\psi}$ , nutation  $\dot{\theta}$ , and spin  $\dot{\phi}$ :

$$\bar{\omega} = \dot{\psi} \bar{k}' + \dot{\theta} \bar{j}' + \dot{\phi} \bar{k} = -\dot{\psi} \sin \theta \bar{i} + \dot{\theta} \bar{j} + (\dot{\psi} \cos \theta + \dot{\phi}) \bar{k}. \quad (1)$$

It is stated that there is no slippage at the ground, so the velocity of the center of the disk is

$$\bar{v}_C = \bar{\omega} \times (-R \bar{i}) = -R(\dot{\psi} \cos \theta + \dot{\phi}) \bar{j} + R\dot{\theta} \bar{k}. \quad (2)$$

The velocity of the center may also be described in terms of the coordinates relative to the fixed reference frame:

$$\bar{v}_C = \dot{X} \bar{i} + \dot{Y} \bar{j} + \dot{Z} \bar{k}. \quad (3)$$

Matching Eqs. (2) and (3) will yield relations between the position coordinates and the Eulerian angles. This operation requires that both descriptions be converted to a common set of components, which we can do by using rotation transformations or by projecting the unit vectors as follows:

$$\bar{i} = \cos \theta (\cos \psi \bar{i} + \sin \psi \bar{j}) - \sin \theta \bar{k},$$

$$\bar{j} = -\sin \psi \bar{i} + \cos \psi \bar{j},$$

$$\bar{k} = \sin \theta (\cos \psi \bar{i} + \sin \psi \bar{j}) + \cos \theta \bar{k}.$$

We use these expressions to match the components of Eqs. (2) and (3), which yields

$$\dot{X} = R(\dot{\psi} \cos \theta + \dot{\phi}) \sin \psi + R\dot{\theta} \cos \psi \sin \theta,$$

$$\dot{Y} = -R(\dot{\psi} \cos \theta + \dot{\phi}) \cos \psi + R\dot{\theta} \sin \psi \sin \theta, \quad (4)$$

$$\dot{Z} = R\dot{\theta} \cos \theta.$$

These relations are three velocity constraints that the six position variables must satisfy, so the disk has only three degrees of freedom. The first two equations are nonholonomic. However, the one governing  $Z$  may be integrated. Multiplying each rate variable in the last equation by  $dt$  makes both sides perfect differentials. When  $\theta = 0$ , the disk lies in the  $XY$  plane, so integrating the third velocity equation and setting  $Z = 0$  at  $\theta = 0$  leads to

$$Z = R \sin \theta. \quad (5)$$

This configuration constraint enables us to eliminate  $Z$  from the formulation. Hence we employ five generalized coordinates in the sequence:  $X, Y, \psi, \theta, \phi$ . These are constrained generalized coordinates because they must satisfy the first two of Eqs. (4), which have the standard form of linear velocity constraints:

$$a_{i1}\dot{X} + a_{i2}\dot{Y} + a_{i3}\dot{\psi} + a_{i4}\dot{\theta} + a_{i5}\dot{\phi} = 0, \quad i = 1, 2, \quad (6)$$

where

$$\begin{aligned} a_{11} &= 1, & a_{12} &= 0, & a_{13} &= -R \sin \psi \cos \theta, & a_{14} &= -R \cos \psi \sin \theta, & a_{15} &= -R \sin \psi, \\ a_{21} &= 0, & a_{22} &= 1, & a_{23} &= R \cos \psi \cos \theta, & a_{24} &= -R \sin \psi \sin \theta, & a_{25} &= R \cos \psi. \end{aligned} \quad (7)$$

We now proceed to formulate the mechanical energies. We use the fact that the disk is thin to set  $I_{xx} = I_{yy} = I_{zz}/2$ , with  $I_{zz} = m\kappa^2$ . The velocity of the center in terms of the generalized coordinates is described by Eq. (3) with  $\dot{Z} = R\dot{\theta} \cos \theta$ , and Eq. (1) gives the corresponding angular velocity, so that

$$\begin{aligned} T &= \frac{1}{2}mv_C^2 + \frac{1}{2}\bar{\omega} \cdot \bar{H}_C \\ &= \frac{1}{2}m \left[ \dot{X}^2 + \dot{Y}^2 + R^2\dot{\theta}^2 (\cos \theta)^2 \right] + \frac{1}{2}m\kappa^2 \left[ \frac{1}{2}(\dot{\psi} \sin \theta)^2 + \frac{1}{2}\dot{\theta}^2 + (\dot{\psi} \cos \theta + \dot{\phi})^2 \right]. \end{aligned} \quad (8)$$

The potential energy of gravity is

$$V = mgZ = mgR \sin \theta. \quad (9)$$

We are not specifically interested in the reactions at the ground, which enforce the constraint against slippage. Therefore we employ the Lagrange multiplier formulation. There are no other nonconservative forces to describe, so we set all  $Q_j = 0$ . The constrained Lagrange's equations, Eqs. (8.1.4), are formed from the kinetic energy in Eq. (8), the potential energy in Eq. (9), and the Jacobian constraint coefficients in Eqs. (7). There are two constraint equations, each of

### 8.1 Lagrange's Equations—Constrained Case

507

which has an associated Lagrange multiplier. The result is a set of five differential equations:

$$m\ddot{X} = \lambda_1, \quad m\ddot{Y} = \lambda_2, \quad (10, 11)$$

$$m\kappa^2 \left\{ \frac{1}{2}\ddot{\psi} \left[ 1 + (\cos \theta)^2 \right] - \dot{\psi}\dot{\theta} \sin \theta \cos \theta + \ddot{\phi} \cos \theta - \dot{\theta}\dot{\phi} \sin \theta \right\} \\ = -\lambda_1 R \sin \psi \cos \theta + \lambda_2 R \cos \psi \cos \theta, \quad (12)$$

$$m \left\{ \ddot{\theta} \left[ \frac{1}{2}\kappa^2 + R^2 (\cos \theta)^2 \right] + \left( \frac{1}{2}\kappa^2 \dot{\psi}^2 - R^2 \dot{\theta}^2 \right) \sin \theta \cos \theta \right. \\ \left. + \kappa^2 \dot{\psi}\dot{\phi} \sin \theta + g R \cos \theta \right\} = -\lambda_1 R \cos \psi \sin \theta - \lambda_2 R \sin \psi \sin \theta, \quad (13)$$

$$m\kappa^2 (\ddot{\psi} \cos \theta + \ddot{\phi} - \dot{\psi}\dot{\theta} \sin \theta) = -\lambda_1 R \sin \psi + \lambda_2 R \cos \psi. \quad (14) <$$

There are seven unknowns: the five generalized coordinates and the two Lagrange multipliers. These variables must satisfy Eq. (6) for  $i = 1$  and  $i = 2$ , and Eqs. (10)–(14).

When the disk precesses steadily, such that  $\theta$  is constant and the center follows a circular path, the precession rate will be the rotation rate of the radial line from the center of the path to the center of the disk. Also,  $\ddot{\psi} = 0$  for steady precession. Let  $\rho$  denote the radius of the path, so that  $v_c = \rho |\dot{\psi}|$ . Setting  $\dot{\theta} = 0$  in Eq. (2) shows that  $\bar{v}_c = \rho \dot{\psi} \bar{j} = -R(\dot{\psi} \cos \theta + \dot{\phi}) \bar{j}$ , from which it follows that

$$\dot{\phi} = -\left( \frac{\rho}{R} + \cos \theta \right) \dot{\psi}. \quad (15)$$

Substitution of this expression into Eqs. (4) leads to

$$\dot{X} = -\rho \dot{\psi} \sin \psi, \quad \dot{Y} = \rho \dot{\psi} \cos \psi.$$

These relations may be integrated directly to find

$$X = \rho \cos \psi + X_0, \quad Y = \rho \sin \psi + Y_0, \quad (16)$$

where  $X_0$  and  $Y_0$  are constants of integration. The fact that these coordinates satisfy  $(X - X_0)^2 + (Y - Y_0)^2 = \rho^2$  verifies that the center follows a circular path, and leads to recognition of  $X_0$  and  $Y_0$  as the coordinates of the center of the path.

With the constraint equations now satisfied, we use the Lagrange equations to relate  $\rho$  and  $\dot{\psi}$ . Substitution of Eqs. (16) into Eqs. (10) and (11) gives expressions for the Lagrange multipliers:

$$\lambda_1 = m(-\rho \dot{\psi}^2 \cos \psi), \quad \lambda_2 = m(-\rho \dot{\psi}^2 \sin \psi). \quad (10', 11')$$

We substitute these expressions, together with  $\ddot{\psi} = 0$ ,  $\dot{\theta} = 0$ , and Eq. (15) for  $\dot{\phi}$ , into Eqs. (12)–(14). The only one that is not identically satisfied is Eq. (13), which becomes

$$\left( \frac{1}{2}\kappa^2 \dot{\psi}^2 \right) \sin \theta \cos \theta - \kappa^2 \dot{\psi}^2 \left( \frac{\rho}{R} + \cos \theta \right) \sin \theta + g R \cos \theta = \rho R \dot{\psi}^2 \sin \theta.$$

Solving this for  $\dot{\psi}$  yields an expression for the steady precession rate corresponding to a constant nutation angle:

$$\dot{\psi} = \left[ \frac{2gR^2 \cot \theta}{2\rho(R^2 + \kappa^2) + \kappa^2 R \cos \theta} \right]^{1/2}. \quad \triangleleft$$

If the disk is homogeneous, then  $\kappa = R/\sqrt{2}$ , which leads to

$$\dot{\psi} = \left[ \frac{4g \cot \theta}{6\rho + R \cos \theta} \right]^{1/2}.$$

This solution is in complete agreement with the result derived in Example 6.4 with the Newton–Euler formulation. The earlier methods provide greater physical insight, but it would have been more difficult to use them to derive the equations of motion for the unsteady case treated here.

## 8.2 COMPUTATIONAL METHODS

Our focus here is on techniques for finding solutions of the differential equations of motion, which are derived from kinetics principles, that also satisfy the constraint equations, which represent kinematical restrictions intrinsic to the system. Although the discussion is centered on the application of Lagrange’s equations, the development is readily altered to treat situations in which the equations of motion are derived from a Newton–Euler formulation or from principles discussed in the next chapter. We have seen that numerical methods are often required to solve the equations of motion associated with unconstrained generalized coordinates. The need to satisfy constraint equations in addition to the equations of motion makes it even likely that we will need to invoke such methods when the generalized coordinates are kinematically constrained.

We found in Section 7.6 that it is convenient to write the equations of motion in matrix form. The presence of constraint equations does not alter the fact that the kinetic energy is a quadratic sum in the generalized velocities, so that the terms appearing in Lagrange’s equations are as described by Eqs. (7.6.9) and (7.6.10). In fact, the only alteration relative to the standard form in Eq. (7.6.12) is the addition of terms to account for the contribution of constraint forces to the  $Q_j$ . Equations (8.1.4) describe these terms as a linear sum of Lagrange multipliers. The matrix representation of that sum is  $[a]^T \{\lambda\}$ . Thus the general form of the equations of motion will be

$$[M(q_j, t)] \{\ddot{q}\} = [a(q_j, t)]^T \{\lambda\} + \{F(q_j, \dot{q}_i, t)\}, \quad (8.2.1)$$

where  $\{F(q_i, \dot{q}_i, t)\}$  consists of the generalized forces  $\{Q\}$  and any terms from the left side of Lagrange’s equations that do not contain generalized accelerations. The corresponding matrix form of the velocity constraint equations, Eq. (8.1.1), is

$$[a(q_i, t)] \{\dot{q}\} + \{b(q_i, t)\} = \{0\}. \quad (8.2.2)$$

## 8.2 Computational Methods

509

One should note that the preceding equations are the forms we shall use to discuss the implementation of numerical algorithms. However, when Coulomb friction forces are present, it is preferable to let the constraint forces appear explicitly, rather than using Lagrange multipliers to represent them. The modifications required for such systems are addressed in Subsection 8.2.4.

Usage of a computer routine to solve the differential equations of motion requires input of the current generalized acceleration values, denoted as  $\{\ddot{q}^*\}$ . When the generalized coordinates are unconstrained, these values may be obtained directly by solving Eq. (7.6.19). When the generalized coordinates form a constrained set, the occurrence of Lagrange multipliers and constraint equations means that the  $\{\ddot{q}^*\}$  values cannot be found solely from the equations of motion. Unfortunately, the manner in which  $\{\lambda\}$  occurs prevents a direct solution.

To recognize the difficulty, recall that standard numerical algorithms handle a set of first-order differential equations whose form is

$$\frac{d}{dt} \{x\} = \{G(x_i, t)\}. \quad (8.2.3)$$

The generalized velocities are treated as though they are independent coordinates, and the Lagrange multipliers also are unknown, so we form the state vector from these variables. We stack the derivative identity, the Lagrange equations, and the velocity constraint equations to form

$$\begin{bmatrix} [U]_{N \times N} & [0]_{N \times N} & [0]_{N \times J} \\ [0]_{N \times N} & [M]_{N \times N} & -([a]_{J \times N})^T \\ [a]_{J \times N} & [0]_{J \times N} & [0]_{J \times J} \end{bmatrix} \begin{Bmatrix} \{\dot{q}\} \\ \{\ddot{q}\} \\ \{\lambda\} \end{Bmatrix} = \begin{Bmatrix} \{\dot{q}\} \\ \{F\} \\ -\{b\} \end{Bmatrix}. \quad (8.2.4)$$

We need to solve these equations for the generalized accelerations, but the first and third partition rows of the coefficient matrix merely differ by the factor  $[a]$ . Consequently, this matrix is not full rank, so the equations cannot be solved for the values of  $\{\ddot{q}\}$ .

Because Eq. (8.2.4) does not contain derivatives of the  $\lambda$  variables, it is said to constitute a set of *differential-algebraic equations* (DAEs). Several solution strategies have been developed to solve them. One approach is to use a DAE solver, which is implemented programmatically in the same manner as one uses a routine such as Runge–Kutta for solving unconstrained equations of motion. Brenan *et al.* (1989) provide a comprehensive discussion of this topic. These methods do not seem to have been widely implemented by dynamics researchers, because they are more prone to numerical difficulties and often are less computationally efficient than the procedures we develop here. However, a popular dynamic simulation software package known as ADAMS relies on a DAE solver. Rather than attacking the problem with a general solution process, the procedures we consider exploit the special nature of the equations for a dynamical system.



### 8.2.1 Algorithms

The fundamental difficulty is the fact that the derivative identity and the constraint equations govern the generalized velocities rather than the accelerations. To circumvent this aspect, the latter is differentiated with respect to time, thereby converting them to acceleration constraint equations. This leads to

$$[a]\{\ddot{q}\} + \left[\frac{da}{dt}\right]\{\dot{q}\} = -\left\{\frac{db}{dt}\right\}. \quad (8.2.5)$$

The use of the total derivative notation to denote the time derivative of  $[a]$  serves as a reminder that the differentiation needs to recognize that the Jacobian constraint matrix may depend on the generalized coordinates. Consequently, the derivatives are evaluated according to

$$\frac{da_{in}}{dt} = \sum_{j=1}^N \frac{\partial a_{in}}{\partial q_j} \dot{q}_j + \frac{\partial a_{in}}{\partial t}, \quad \frac{db_i}{dt} = \sum_{j=1}^N \frac{\partial b_i}{\partial q_j} \dot{q}_j + \frac{\partial b_i}{\partial t}, \quad i = 1, \dots, J, \quad n = 1, \dots, N. \quad (8.2.6)$$

The most direct solution strategy for solving the differential equations is to define *integrated multipliers*. Let  $\mu_i$  denote the definite integral of  $\lambda_i$ :

$$\mu_i(t) = \int_0^t \lambda_i(\tau) d\tau \iff \lambda_i = \dot{\mu}_i. \quad (8.2.7)$$

When the Lagrange multipliers are replaced with the respective  $\dot{\mu}_i$  parameter, the assembly of the derivative identity, the equations of motion, and the acceleration constraint equations yields

$$\begin{bmatrix} [U] & [0] & [0] \\ [0] & [M] & -[a]^T \\ [0] & -[a] & [0] \end{bmatrix} \frac{d}{dt} \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \\ \{\mu\} \end{Bmatrix} = \begin{Bmatrix} \{\dot{q}\} \\ \{F\} \\ \left[\frac{da}{dt}\right]\{\dot{q}\} + \left\{\frac{db}{dt}\right\} \end{Bmatrix}. \quad (8.2.8)$$

(The negative of the acceleration constraint was used to form the third partition row in order that the coefficient matrix be symmetric.) This set of equations has the form described by Eq. (8.2.3) with

$$\begin{aligned} \{z\} &= [\{q\}^T \quad \{\dot{q}\}^T \quad \{\mu\}^T]^T, \\ \{G(z_i, t)\} &= \begin{bmatrix} [U] & [0] & [0] \\ [0] & [M] & -[a]^T \\ [0] & -[a] & [0] \end{bmatrix}^{-1} \begin{Bmatrix} \{\dot{q}\} \\ \{F\} \\ \left[\frac{da}{dt}\right]\{\dot{q}\} + \left\{\frac{db}{dt}\right\} \end{Bmatrix}. \end{aligned} \quad (8.2.9)$$

Note that the matrix inverse appears in the preceding equation for notational purposes. The value of  $\{G(z_i, t)\}$  at the desired instant may be obtained more efficiently by a standard technique for linear algebraic equations, such as Gauss elimination.

## 8.2 Computational Methods

511

The alternative formulation known as the *augmented method* proceeds similarly to the integrated multiplier procedure, but it is more efficient from a computational standpoint. If we omit the derivative identity when we assemble the equations, we find that

$$\begin{bmatrix} [M] & -[a]^T \\ -[a] & [0] \end{bmatrix} \begin{Bmatrix} \{\ddot{q}\} \\ \{\lambda\} \end{Bmatrix} = \begin{Bmatrix} \{F\} \\ \left[ \frac{da}{dt} \right] \{\dot{q}\} + \left\{ \frac{db}{dt} \right\} \end{Bmatrix}. \quad (8.2.10)$$

This constitutes a set of  $N + J$  simultaneous algebraic equations for the values  $\{\ddot{q}\}$  and  $\{\lambda\}$  corresponding to any instant that the values of  $\{q\}$  and  $\{\dot{q}\}$  are known. Thus the state-space vector here is defined to contain only the generalized coordinates and velocities. In combination with the current value of  $\{\dot{q}\}$ , the values of  $\{\ddot{q}\}$  obtained from the preceding equation provide the input for the differential equation solver. Thus the augmented algorithm entails implementing Eq. (8.2.3), with

$$\begin{aligned} \{z\} &= \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \end{Bmatrix}, \quad \{G(z_i, t)\} = \begin{Bmatrix} \{\dot{q}\} \\ \{\ddot{q}\} \end{Bmatrix}, \\ \begin{Bmatrix} \{\ddot{q}\} \\ \{\lambda\} \end{Bmatrix} &= \begin{bmatrix} [M] & -[a]^T \\ -[a] & [0] \end{bmatrix}^{-1} \begin{Bmatrix} \{F\} \\ \left[ \frac{da}{dt} \right] \{\dot{q}\} + \left\{ \frac{db}{dt} \right\} \end{Bmatrix}. \end{aligned} \quad (8.2.11)$$

Once again, the  $\{\ddot{q}\}$  values should be obtained by a standard technique for linear algebraic equations, rather than with a matrix inverse.

Both the integrated multiplier and augmented methods evaluate the Lagrange multipliers at each instant. A different approach to solving the coupled set of dynamical equations of motion and constraint is sometimes implemented manually in an ad hoc manner. We refer to it as the *elimination method*, because it entails eliminating the multipliers by direct substitution. We may see the essence of the approach by considering Eqs. (10) and (11) in Example 8.4. Those equations may be solved for the two Lagrange multipliers in terms of the  $q_j$ ,  $\dot{q}_j$ , and  $\ddot{q}_j$ . Substitution of those expressions into the remaining equations of motion, (12)–(14), would lead to three differential equations of motion. When these equations are combined with the acceleration form of the constraint equations, the result is a set of five differential equations governing the five generalized coordinates.

We may formalize this approach by decomposing the equations of motion into two partitions: an upper set of  $J$  equations and a lower set of  $N - J$  equations,

$$\begin{bmatrix} [M_1]_{J \times N} \\ [M_2]_{(N-J) \times N} \end{bmatrix} \{\ddot{q}\} = \begin{Bmatrix} \{F_1\}_{J \times 1} \\ \{F_2\}_{(N-J) \times 1} \end{Bmatrix} + \begin{bmatrix} [a_1]^T \\ [a_2]^T \end{bmatrix} \{\lambda\}_{J \times 1}, \quad (8.2.12)$$

where the Jacobian constraint matrix is partitioned as

$$[a]_{J \times N} = \begin{bmatrix} [a_1]_{J \times J} & [a_2]_{J \times (N-J)} \end{bmatrix}. \quad (8.2.13)$$

It is necessary that the equations used to form the first group be such that  $[a_1]$  is full rank, that is,  $[a_1] \neq 0$ . Then the upper partition of Eq. (8.2.12) may be solved for  $\{\lambda\}$ ,

$$\{\lambda\} = [a_1]^{-T} [M_1] \{\ddot{q}\} - [a_1]^{-T} \{F_1\}, \quad (8.2.14)$$

where  $[a_1]^{-T}$  is the transpose of the inverse of  $[a_1]$ . Substitution of this expression for  $\{\lambda\}$  into the second partition row of Eq. (8.2.12) leads to

$$[M_2] - [a_2]^T [a_1]^{-T} [M_1] \{\ddot{q}\} = \{F_2\} - [a_2]^T [a_1]^{-T} \{F_1\}. \quad (8.2.15)$$

All quantities appearing in this expression other than  $\{\ddot{q}\}$  are known at any instant in terms of the current values of  $\{q\}$ ,  $\{\dot{q}\}$ , and  $t$ . We then obtain a solvable set of equations by stacking these equations above the acceleration constraint equations. Thus the elimination algorithm is summarized by

$$\begin{aligned} \{z\} &= \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \end{Bmatrix}, \quad \{G(z, t)\} = \begin{Bmatrix} \{\dot{q}\} \\ \{\ddot{q}\} \end{Bmatrix}, \\ \{\ddot{q}\} &= \begin{bmatrix} [M_2] - [a_2]^T [a_1]^{-T} [M_1] \\ -[a] \end{bmatrix}^{-1} \begin{Bmatrix} \{F_2\} - [a_2]^T [a_1]^{-T} \{F_1\} \\ \left[ \frac{da}{dt} \right] \{\dot{q}\} + \left[ \frac{db}{dt} \right] \end{Bmatrix}. \end{aligned} \quad (8.2.16)$$

The preceding expression for  $\{\ddot{q}\}$  contains an important subtlety. The manner in which  $[a_1]^{-T}$  appears requires actual evaluation of an inverse. In contrast, it is solely for notational purposes that an inverse is used to indicate solution for  $\{\ddot{q}\}$  values, whereas the actual implementation should use a more efficient solution technique such as Gauss elimination.

One can perform Eq. (8.2.14), as well as subsequent operations, algebraically if the number of equations is not too large. Alternatively, one can carry out the operations numerically at each time instant using the current values of  $\{q\}$  and  $\{\dot{q}\}$ . In any event, care must be taken to avoid grouping the equations of motion in a manner that causes  $[a_1]$  to be uninvertible or ill-conditioned. If such a situation occurs subsequently to initiation of the integration process, it is necessary to interrupt the solver in order to resequence the columns of  $[a]$  and the elements of  $\{q\}$  in a consistent manner, such that the submatrix  $[a_1]$  of the rearranged  $[a]$  is well behaved.

Such resequencing can be carried out manually, but an automated procedure can be quite useful when there are many equations. The process of shifting columns of  $[a]$  may be represented by an  $N \times N$  sorting matrix  $[P]$  that satisfies

$$[\tilde{a}] = [a][P], \quad (8.2.17)$$

where a rearranged matrix is denoted with a tilde,  $\sim$ . The corresponding rearrangement of the elements of  $\{q\}$  is described by

$$\{q\} = [P] \{\tilde{q}\}. \quad (8.2.18)$$

The elements of  $[P]$  are a set of ones and zeros, and  $[P]$  would obviously be the identity matrix in the event that resequencing was not necessary. As an example, suppose  $N = 3$ ,

We see that the consequence of this operation is to remove the Lagrange multipliers from the equations to be integrated. Because  $[C]$  has  $N - J$  rows, we may compute values of the  $N$  generalized accelerations at any instant by combining Eq. (8.2.25) with the acceleration constraint equations. Thus the orthogonal complement algorithm is cap-sulized by

$$\begin{aligned} \{z\} &= \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \end{Bmatrix}, \quad \{G(z_i, t)\} = \begin{Bmatrix} \{\dot{q}\} \\ \{\ddot{q}\} \end{Bmatrix}, \\ \{\ddot{q}\} &= \begin{bmatrix} [C][M] \\ -[a] \end{bmatrix}^{-1} \begin{Bmatrix} [C]\{F\} \\ \left[ \frac{da}{dt} \right] \{\dot{q}\} + \left\{ \frac{db}{dt} \right\} \end{Bmatrix}. \end{aligned} \quad (8.2.26)$$

These values and the associated current values of the generalized velocities constitute the inputs required for implementing the differential equation solver associated with Eq. (8.2.3).

Implementation of the orthogonal complement method requires that the orthogonal complement to the current value of  $[a]$  be determined prior to each call to the differential equation solver. Several techniques for determining the orthogonal complement are discussed in the text by Amirouche (1992) under the category of coordinate reductions. One method not discussed there is suggested by the recognition that the condition for the orthogonal complement can be rewritten as

$$[a][C]^T = [0]. \quad (8.2.27)$$

Thus we may consider the columns of  $[C]^T$ , that is, the rows of  $[C]$ , to be nonzero solutions of

$$[a]\{y\} = \{0\}. \quad (8.2.28)$$

A numerical procedure for determining all possible solutions for  $\{y\}$  is the *singular value decomposition* (SVD), which is described by Press *et al.* (1992). The method is briefly summarized here.

If  $[A]$  is a known  $I \times J$  array, with  $I \geq J$ , then the SVD of  $[A]$  is

$$[A]_{I \times J} = [L]_{I \times J} [w]_{J \times J} [R]_{J \times J}^T, \quad (8.2.29)$$

where  $[w]$  is a diagonal array that holds the singular values of  $[A]$ , and  $[L]$  and  $[R]$  consist of columns that are orthonormal:

$$[L]^T[L] = [U]_{J \times J}, \quad [R]^T[R] = [U]_{J \times J}. \quad (8.2.30)$$

It is important for our development that the singular values are real and nonnegative,  $w_j \geq 0$ . Press *et al.* give a reliable subroutine for carrying out the process, and comparable routines are contained in most mathematical software packages. Only the singular values  $[w]$  are unique, so  $[L]$  and  $[R]$  obtained from different pieces of software might not be the same.

## 8.2 Computational Methods

515

Now consider the situation in which  $[A]$  is a square  $m \times m$  matrix, and we seek to solve

$$[A]\{y\} = \{0\}. \quad (8.2.31)$$

Clearly, the only solution is  $\{y\} = \{0\}$  unless  $[A] = 0$ . Any  $\{y\} \neq \{0\}$  satisfying this equation is said to be in the null space of  $[A]$ . The number  $k$  of independent solutions lying in the null space of  $[A]$  is the nullity of  $[A]$ , and the rank of  $[A]$  is  $m - k$ . It can be shown that the nullity of a matrix is the number of zero singular values obtained in its SVD. (In general, the ratio of the largest to the smallest singular value is the condition number of a matrix.) For our present purpose, the significance of zero singular values is a theorem that states that, if  $w_j = 0$ , then column  $\#j$  of  $[R]$  is an independent vector in the null space of  $[A]$ . The singular values may be arranged in any sequence without violating Eq. (8.2.29), provided that the columns of  $[L]$  and  $[R]$  are rearranged in the same manner. It is convenient to use this property to arrange the singular values such that the  $w_j$  values occur in ascending order, which leads to  $w_1 = \dots = w_k = 0$ . Let  $\{R_j\}$  denote the  $j$ th column of  $[R]$ . It follows that

$$[A]\{R_j\} = \{0\}, \quad j = 1, 2, \dots, k. \quad (8.2.32)$$

These may be assembled into a single matrix relation:

$$[A][\{R_1\} \quad \{R_2\} \quad \dots \quad \{R_k\}] = [0]. \quad (8.2.33)$$

To employ SVD to determine the orthogonal complement  $[C]$  satisfying Eq. (8.2.27), we form the square array  $[A]$  by stacking the  $J \times N$  matrix  $[a]$  above an array of  $(N - J) \times N$  zeros:

$$[A]_{N \times N} = \begin{bmatrix} [a]_{J \times N} \\ [0]_{(N-J) \times N} \end{bmatrix}. \quad (8.2.34)$$

Aside from degenerate conditions that might occur at some instant, the  $J$  constraint conditions are independent, so the rank of  $[A]$  is  $J$ . It follows that the nullity of  $[A]$  formed as previously defined is  $N - J$ . Hence, when we perform a SVD of the previously defined  $[A]$ , and resequence the singular values in the prescribed manner, then the first  $N - J$  columns of the resulting  $[R]$  are in the null space of  $[A]$ . In view of the partitioned manner in which  $[A]$  is defined, it follows that

$$[a][\{R_1\} \quad \{R_2\} \quad \dots \quad \{R_{(N-J)}\}] = [0]. \quad (8.2.35)$$

A comparison of this relation with Eq. (8.2.27) indicates that we should use these  $\{R_j\}$  to form the rows of  $[C]$ :

$$[C] = \begin{bmatrix} \{R_1\}^T \\ \{R_2\}^T \\ \vdots \\ \{R_{(N-J)}\}^T \end{bmatrix}. \quad (8.2.36)$$

The significance of this property becomes apparent when we substitute Eq. (8.2.48) into the Lagrange equation, Eq. (8.2.1), which leads to

$$[M] \left\{ [D] \{\ddot{q}_u\} + [B] \left[ \frac{da}{dt} \right] [D] \{\dot{q}_u\} + \{E\} \right\} = \{F\} + [a]^T \{\lambda\}. \quad (8.2.51)$$

We premultiply this equation by  $[D]^T$ . According to Eq. (8.2.50), we have\*

$$[D]^T [a]^T \equiv [[a][D]]^T = [0]. \quad (8.2.52)$$

Thus the equations of motion reduce to

$$[D]^T [M] [D] \{\ddot{q}_u\} = [D]^T \left\{ \{F\} - [M][B] \left[ \frac{da}{dt} \right] [D] \{\dot{q}_u\} - [M]\{E\} \right\}. \quad (8.2.53)$$

The constraint equations are embedded in these equations, rather than enforced explicitly. Thus, as indicated by Amirouche (1992), it appears that the procedure has reduced the equations of motion to a form comparable with those for a holonomic system having  $N - J$  degrees of freedom. However, this view misses the fact that  $[M]$ ,  $[a]$ , and the other coefficient matrices are likely to depend on all generalized coordinates, not just on the unconstrained variables. Furthermore,  $\{F\}$ ,  $[da/dt]$ , and  $\{db/dt\}$  are likely to depend on all of the generalized velocities. Thus, at every time step in the integration process, it will be necessary to also evaluate the current values of  $\{q_c\}$  and  $\{\dot{q}_c\}$ . Toward that end, we can consider Eq. (8.2.42) to be an auxiliary set of differential equations that are to be integrated simultaneously with the basic equations of motion. Implementation of the embedding algorithm requires that the solver implementing Eq. (8.2.3) be formulated with

$$\begin{aligned} \{z\} &= \begin{Bmatrix} \{q_u\} \\ \{\dot{q}_u\} \\ \{q_c\} \end{Bmatrix}, \quad \{G(z_i, t)\} = \begin{Bmatrix} \{\dot{q}_u\} \\ \{\ddot{q}_u\} \\ \{\dot{q}_c\} \end{Bmatrix}, \\ \{q\} &= [P] \begin{Bmatrix} \{q_u\}_{(N-J) \times 1} \\ \{q_c\}_{J \times 1} \end{Bmatrix}, \quad \begin{bmatrix} [a_u]_{J \times (N-J)} & [a_c]_{J \times J} \end{bmatrix} = [a][P], \\ \{\dot{q}_c\} &= -[a_c]^{-1} [a_u] \{\dot{q}_u\} - [a_c]^{-1} \{b\}, \\ [D]^T [M] [D] \{\ddot{q}_u\} &= [D]^T \left\{ \{F\} - [M][B] \left[ \frac{da}{dt} \right] [D] \{\dot{q}_u\} - [M]\{E\} \right\}, \end{aligned} \quad (8.2.54)$$

where  $[D]$  and  $[B]$  are defined in Eqs. (8.2.44), and Eq. (8.2.49) gives  $\{E\}$ .

At any time step the value of  $\{z\}$  will be known. To perform the next integration step one needs to extract  $\{q_u\}$  and  $\{q_c\}$  from the current  $\{z\}$ . Knowledge of the generalized coordinate values allows one to evaluate the current values of  $[a]$ ,  $[da/dt]$ , and  $\{b\}$ , which then allows for evaluation of  $[a_c]$  and  $[a_u]$ . The values of  $\{\dot{q}_c\}$  and  $\{\ddot{q}_u\}$  may then be

\* According to Eq. (8.2.50),  $[D]^T$  is the orthogonal complement of  $[a]$ . The primary difficulty with using this, rather than SVD, to implement the orthogonal complement method lies in the need to be certain that  $[a_c]$  is invertible.

## 8.2 Computational Methods

519

found by direct substitution. These values in conjunction with the  $\{\dot{q}_u\}$  values extracted from the current  $\{z\}$  are used to evaluate the current value of  $\{G\}$ , which is the input to the differential equation solver. In this process it is important to monitor  $[a_c]$  for invertibility. If this matrix were to become ill-conditioned at some integration step, or actually become rank deficient, it would be necessary to change the definition of  $\{q_c\}$ . This is readily achieved because it merely entails changing the definition of  $[P]$ .

Greenwood (2003) offers a different procedure that also embeds the constraint equations. It avoids the need to split the generalized coordinates into constrained and unconstrained sets, so that the question of invertibility of  $[a_c]$  does not arise. The modified procedure begins by solving the  $N$  Lagrange equations for the generalized accelerations, and then substituting that solution into the acceleration constraint equations, which leads to

$$\begin{aligned} \{\ddot{q}\} &= [M]^{-1} \left\{ [a]^T \{\lambda\} + \{F\} \right\}, \\ [a][M]^{-1} \left\{ [a]^T \{\lambda\} + \{F\} \right\} + \left[ \frac{da}{dt} \right] \{\dot{q}\} + \left\{ \frac{db}{dt} \right\} &= \{0\}. \end{aligned} \quad (8.2.55)$$

The expression for  $\{\lambda\}$  obtained by solving the second set of equations is used to eliminate the multipliers from the first set. This leads to an alternative embedding algorithm:

$$\begin{aligned} \{z\} &= \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \end{Bmatrix}, \quad \{G(z, t)\} = \begin{Bmatrix} \{\dot{q}\} \\ \{\ddot{q}\} \end{Bmatrix}, \\ \{\ddot{q}\} &= [M]^{-1} \{F\} - [M]^{-1} [a]^T \left[ [a][M]^{-1} [a]^T \right]^{-1} \left\{ [a][M]^{-1} \{F\} + [\dot{a}] \{\dot{q}\} + \{\dot{b}\} \right\}. \end{aligned}$$

The associated Lagrange multipliers values are not needed to invoke the differential equation solver, but their value at any instant can be obtained from

$$\{\lambda\} = - \left[ [a][M]^{-1} [a]^T \right]^{-1} \left\{ [a][M]^{-1} \{F\} + [\dot{a}] \{\dot{q}\} + \{\dot{b}\} \right\}. \quad (8.2.56)$$

An overview of the methods that have been presented shows that preparing the equations to be passed to the differential equation solver at each time instant requires several operations. Thus the issue of which is more efficient depends on more than the number of equations to be integrated in each method. Furthermore, in addition to the number of operations associated with each approach, it might happen that the equations for one of these methods are better behaved, in the sense that the method allows for a larger time step without loss of numerical stability. Which of these methods will be best in a specific situation cannot be stated *a priori*. One factor that can be used as a guideline is that some of the techniques are preferable if the values of the Lagrange multipliers/constraint forces are required. In the author's experience, the augmented method provides a reliable approach that is easy to implement, reasonably efficient, and provides all the information one might seek in a dynamics simulation.

### 8.2.2 Numerical Error Checking

Regardless of the algorithm one uses, a potential difficulty lies in the fact that the velocity constraint equations are not satisfied directly at every instant. Rather, they occur only in differentiated form as acceleration constraint equations. Numerical methods are not exact, so it is possible that a small error in satisfying the acceleration constraint equations at each time step will accumulate to a substantial error relative to the velocity constraint equations. A similar issue arises if it was decided to ignore the fact that a constraint condition is holonomic by expressing it in velocity form, rather than using unconstrained generalized coordinates. It is wise to implement an auxiliary step to monitor this error periodically as the integration process marches forward. The associated operations are simple. Let an asterisk denote a quantity that is a current value returned by the equation solver. When we substitute the instantaneous values  $\{q^*\}$  and  $\{\dot{q}^*\}$  into each velocity constraint equation, the resulting value of each equation leads to an error vector  $\{\varepsilon\}$ :

$$\{\varepsilon_v\} = [a(q_i^*, t)] \{\dot{q}^*\} + \{b(q_i^*, t)\}. \quad (8.2.57)$$

In the same manner, another error vector may be formed from the values of any configuration constraints that apply:

$$\{\varepsilon_f\} = \{f(q_i^*, t)\}. \quad (8.2.58)$$

Other error measures are available from any conservation theorems that pertain, such as mechanical energy, a linear or angular momentum component, or the Hamiltonian, which is discussed in Subsection 9.2.1. The value of a conserved quantity is known from the initial conditions, so the difference between the current and initial values of a conserved quantity is the error. The value of an error measure by itself is not significant. Rather, the magnitude of each scalar error needs to be compared with the largest term from which it is formed. If such a comparison suggests that the solution is drifting from its correct condition, one would be wise to halt the numerical solution, at least to adjust the parameters passed to the differential equation solver.

Baumgarte's (1972) *constraint stabilization method* is sometimes used to compensate for the tendency of error in the velocity constraints to accumulate. In it, the acceleration constraint is modified by the addition of the velocity constraint, multiplied by an appropriate constant. This modified constraint equation is

$$[a] \{\ddot{q}\} + [\dot{a}] \{\dot{q}\} + \{\dot{b}\} + 2\alpha \{[a] \{\dot{q}\} + \{b\}\} = \{0\}. \quad (8.2.59)$$

Clearly, the added term would have no effect if the velocity constraint equations actually have been satisfied. To understand the rationale behind this alteration, designate the constraint equation as  $\{h\} = [a] \{\dot{q}\} + \{b\} = \{0\}$ . The acceleration constraint equation requires that  $d\{h\}/dt = 0$ , but the numerical approximations and round-off errors in effect convert this to  $d\{h\}/dt = \{\varepsilon_h\}$ . Depending on the nature of  $\{\varepsilon_h\}$ , the integral of  $\{\varepsilon_h\} dt$  might grow, or even be unstable. The stabilized constraint in the presence of an error term has the form  $d\{h\}/dt + 2\alpha \{h\} = \{\varepsilon_h\}$ . This is like the equation of motion for a damped oscillator, in which  $2\alpha$  is the damping rate. The effect of the damper is to



## 8.2 Computational Methods

521

remove energy and thereby inhibit growth of the solution. In fact, the  $2\alpha\{h\}$  term acts like artificial viscosity, which is often introduced when partial differential equations are solved by finite differences. Nevertheless, the constraint stabilization method does have limitations, a discussion of which may be found in the text by Haug (1989).

The constraint stabilization method can be altered to account for any constraints that are holonomic. Also, other procedures have been developed to correct for errors in quantities that should be conserved. None of these are infallible. One reason for having several numerical algorithms for solving differential equations is the fact that, for a given set of equations with a given time increment, some might be more efficient, whereas others might be able to go farther in time with lower errors. Thus, if one encounters difficulty, it might be appropriate to change the method by which the equations are solved. This might entail restarting the simulation, or switching to a different algorithm at an intermediate instant in the integration process.

### 8.2.3 Initial Conditions

Determination of a unique solution of the differential equations of motion and constraint requires that the initial conditions be specified. As was mentioned, the left side of Lagrange's equations contains generalized accelerations. Thus we may consider these equations to give the values of the  $\ddot{q}_j$  variables when all  $q_j$  and  $\dot{q}_j$ , as well as all forces, are specified at some time  $t$ . It follows that the required initial conditions are the values of each  $q_j$  and  $\dot{q}_j$  at an initial time  $t_0$ . When the generalized coordinates are unconstrained,  $J = 0$ , the initial value of each  $q_j$  and  $\dot{q}_j$  may be selected arbitrarily. In contrast, constrained generalized coordinates must satisfy the constraint equations at every instant, including the initial one. If one fails to do so, the solution of the equations of motion will be meaningless.

Satisfaction of the velocity constraint equations is necessary to ensure that the system initially is moving in a kinematically admissible manner. A simple example of this consideration is the ice skate blade described by Fig. 7.6. The constraint that must be enforced gives a velocity that is oriented in the direction in which the blade cuts a groove in the ice. Initial generalized velocities that are inconsistent with this constraint correspond to the blade skidding sideways over the ice, which is a condition that is not described by the corresponding equations of motion.

Similarly, it is necessary that the initial conditions satisfy all configuration constraints, because failure to do so would start the system from an unattainable position. Recall that our approach is to express all constraint equations in velocity form. It is irrelevant to the algorithms described in Subsection 8.2.1 whether some of those equations actually are holonomic. However, it is crucial for setting the initial conditions that all configuration constraints be satisfied. Thus, setting the initial conditions is the only point in the solution process at which it is essential to know that a velocity constraint equation actually is holonomic. Let  $J_c \leq J$  denote the number of holonomic constraint equations, so the  $N$  initial values  $(q_j)_0$  must satisfy

$$f_k((q_j)_0, t = 0) = 0, \quad k = 1, 2, \dots, J_c. \quad (8.2.60)$$

It follows that one may assign  $N - J_c$  of the  $(q_j)_0$  to match what is known about the initial position of the system. The remaining  $(q_j)_0$  values must then be found as solutions of these (algebraic) configuration constraints.

After initial values of the generalized coordinates consistent with Eq. (8.2.60) have been determined, initial generalized velocities consistent with the velocity constraint equations may be evaluated. For this evaluation there is no need to distinguish between holonomic and nonholonomic equations. Thus the initial generalized velocities must satisfy

$$\left[ a \left( (q_0)_j, t = 0 \right) \right] \{ \dot{q}_0 \} + \left\{ b \left( (q_0)_j, t = 0 \right) \right\} = \{ 0 \}. \quad (8.2.61)$$

There are  $J$  velocity constraints. Hence only  $N - J$  elements of  $\{ \dot{q}_0 \}$  may be selected as appropriate to specific initial velocity of the system. The unassigned  $J$  elements of  $\{ \dot{q}_0 \}$  velocities must satisfy Eq. (8.2.61). These equations are linear in the generalized velocities, and one may use a sorting matrix  $[P]$  as described in the previous section to isolate the initial velocities that are computed.

**EXAMPLE 8.5** At a particular instant, the generalized coordinates and generalized velocities for the rolling disk in Example 8.4 are

$$X = 2 \text{ m}, Y = -1 \text{ m}, \psi = -0.6109 \text{ rad}, \theta = 0.4363 \text{ rad}, \phi = 3.6652 \text{ rad}, \\ \dot{\psi} = 0.4000 \text{ rad/s}, \dot{\theta} = -0.2000 \text{ rad/s}, \dot{\phi} = 80.0000 \text{ rad/s}.$$

The disk's radius is  $R = 0.25 \text{ m}$ . First determine the values of  $\dot{X}$  and  $\dot{Y}$  at this instant. Then describe programming steps and carry out the evaluation of  $\{ \dot{z} \}$  and  $\{ \ddot{z} \}$  at this instant according to the (a) integrated multiplier method, (b) augmented method, (c) the elimination method, (d) the orthogonal complement method, and (e) the embedding method.

**SOLUTION** By demonstrating the actual operations required to implement a single step of each of the algorithms, this example makes us more aware of the relative merits of each technique. In addition, converting the given initial values to a state vector  $\{ z \}$  exemplifies the operations required for initializing each algorithm. We sequence the generalized coordinates like the scheme in Example 8.4:

$$\{ q \} = [X \ Y \ \psi \ \theta \ \phi]^T. \quad (1)$$

One should note that only three of the five initial generalized velocities are given in the problem statement. The values of the other two are obtained by satisfying the velocity constraint equations.

The first step for each algorithm is to express the equations of motion and constraint in matrix form, with elements described in terms of  $q_j$  symbols. Equations

## 8.2 Computational Methods

523

(10)–(14) in the previous example can be placed into the standard matrix form, Eq. (8.2.1). Thus the inertia matrix is

$$[M(\{q\})] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0.5\kappa^2(1 + (\cos q_4)^2) & 0 & \kappa^2 \cos q_4 \\ 0 & 0 & 0 & (0.5\kappa^2 + R^2(\cos q_4)^2) & 0 \\ 0 & 0 & \kappa^2 \cos q_4 & 0 & \kappa^2 \end{bmatrix}. \quad (2)$$

The excitation matrix is

$$\{F(\{q\}, \{\dot{q}\})\} = \begin{bmatrix} 0 \\ 0 \\ \kappa^2 \left[ \frac{1}{2} \dot{q}_3 \dot{q}_4 \sin(2q_4) + \dot{q}_4 \dot{q}_5 \sin(q_4) \right] \\ \frac{1}{2} \left( R^2 \dot{q}_4^2 - \frac{1}{2} \kappa^2 \dot{q}_3^2 \right) \sin(2q_4) - \kappa^2 \dot{q}_3 \dot{q}_5 \sin(q_4) - g R \cos(q_4) \\ \kappa^2 \dot{q}_3 \dot{q}_4 \sin(q_4) \end{bmatrix}. \quad (3)$$

The Jacobian constraint matrix and its time derivative are

$$[a(\{q\}, \{\dot{q}\})] = R \begin{bmatrix} 1/R & 0 & -\cos(q_3) \cos(q_4) & \sin(q_3) \sin(q_4) & -\cos(q_3) \\ 0 & 1/R & -\sin(q_3) \cos(q_4) & -\cos(q_3) \sin(q_4) & -\sin(q_3) \end{bmatrix}, \quad (4)$$

$$\left[ \frac{da}{dt}(\{q\}, \{\dot{q}\}) \right] = R \begin{bmatrix} 0 & 0 & (\dot{q}_3 \sin(q_3) \cos(q_4) + \dot{q}_4 \cos(q_3) \sin(q_4)) \\ 0 & 0 & (-\dot{q}_3 \cos(q_3) \cos(q_4) + \dot{q}_4 \sin(q_3) \sin(q_4)) \\ (\dot{q}_3 \cos(q_3) \sin(q_4) + \dot{q}_4 \sin(q_3) \cos(q_4)) & \dot{q}_3 \sin(q_3) \\ (\dot{q}_3 \sin(q_3) \sin(q_4) - \dot{q}_4 \cos(q_3) \cos(q_4)) & -\dot{q}_3 \cos(q_3) \end{bmatrix}. \quad (5)$$

Also  $\{b\} = \{0\}$ . Note that the mass  $m$  has been factored out of all equations, so the computed Lagrange multipliers will be the true  $\lambda_n$  values divided by  $m$ . Regardless of which algorithm is implemented, functions to evaluate each of these matrices corresponding to current values of  $\{q\}$  and  $\{\dot{q}\}$  need to be provided. The discussion that follows is framed in terms of Matlab, so it is assumed that function m-files named `M.m`, `F.m`, `a.m`, and `a_dot.m` exist in the search path.

The values  $\dot{X} = \dot{q}_1$  and  $\dot{Y} = \dot{q}_2$  are not specified in the problem statement, so we know that, at the given instant,

$$\{q\} = [2 \quad -1 \quad -0.6109 \quad \theta \quad 3.6652]^T, \\ \{\dot{q}\} = [? \quad ? \quad 0.4000 \quad -0.2000 \quad 80.0000]^T.$$

To determine  $\dot{X}$  and  $\dot{Y}$  we observe that  $[a]\{\dot{q}\} = \{0\}$  constitutes two equations for the five generalized coordinates. Because  $X$  and  $Y$  are the first two variables in  $\{q\}$ , the appropriate partitioning of these equations is

$$\begin{bmatrix} [a_L]_{2 \times 2} & [a_R]_{2 \times 3} \end{bmatrix} \begin{bmatrix} [\dot{q}_1 \ \dot{q}_2] & [\dot{q}_3 \ \dot{q}_4 \ \dot{q}_5] \end{bmatrix}^T = \{0\}.$$

Thus we find that

$$\begin{Bmatrix} \dot{q}_1 \\ \dot{q}_2 \end{Bmatrix} = -[a_L]^{-1}[a_R] \begin{Bmatrix} \dot{q}_3 \\ \dot{q}_4 \\ \dot{q}_5 \end{Bmatrix}.$$

To extract  $[a_L]$  and  $[a_R]$  from  $[a]$  we use the given values of  $\psi$  and  $\theta$  to evaluate Eq. (4):

$$[a] = \begin{bmatrix} 1 & 0 & -0.1856 & -0.0606 & -0.2048 \\ 0 & 1 & 0.1300 & -0.0865 & 0.1434 \end{bmatrix},$$

Correspondingly, we find from the preceding algebraic solution that

$$\dot{X} = \dot{q}_1 = 16.4452, \quad \dot{Y} = \dot{q}_2 = -11.5408. \quad \triangleleft$$

Now that we have the initial values of  $\{q\}$  and  $\{\dot{q}\}$ , we may evaluate the other system matrices. The results corresponding to  $\kappa = R/\sqrt{2}$  for a solid disk are

$$[M] = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0.0285 & 0 & 0.0283 \\ 0 & 0 & 0 & 0.0670 & 0 \\ 0 & 0 & 0.0283 & 0 & 0.0312 \end{bmatrix},$$

$$\{F\} = \begin{bmatrix} 0 & 0 & -0.2123 & -2.6447 & -0.0011 \end{bmatrix}^T,$$

$$\left[ \frac{da}{dt} \right] = \begin{bmatrix} 0 & 0 & -0.0693 & 0.0606 & -0.0574 \\ 0 & 0 & -0.0621 & 0.0129 & -0.0819 \end{bmatrix}.$$

We are now ready to follow each algorithm. Each will be described in terms of Matlab operations, based on knowing the current value of the state-space vector  $\{z\}$  for that formulation. In the integrated multiplier method the state-space vector is

$$\{z\} = \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \\ \{\mu\} \end{Bmatrix} = \begin{Bmatrix} [X \ Y \ \psi \ \theta \ \phi]^T \\ [\dot{X} \ \dot{Y} \ \dot{\psi} \ \dot{\theta} \ \dot{\phi}]^T \\ [\mu_1 \ \mu_2]^T \end{Bmatrix}.$$

## 8.2 Computational Methods

525

The actual values of  $\mu_1$  and  $\mu_2$  do not arise in the assembled equations, so we may set them to zero. Therefore the state-space vector at the given instant is

$$\{z\} = \begin{Bmatrix} [2 \quad -1 \quad -0.6109 \quad 0.4363 \quad 3.6652]^T \\ [16.4452 \quad -11.5408 \quad 0.40 \quad -0.20 \quad 80.00]^T \\ [0 \quad 0]^T \end{Bmatrix}. \quad \triangleleft$$

The manner in which  $\{z\}$  is displayed is intended to facilitate identifying which parts are  $\{q\}$ ,  $\{\dot{q}\}$ , or  $\{\mu\}$ . Because  $\{z\}$  is the variable that would be returned by the differential equation solver, we extract the values of  $\{q\}$  and  $\{\dot{q}\}$  from  $\{z\}$  as submatrices. The following Matlab fragment defines LHS and RHS as the left coefficient matrix and right coefficient vector appearing in Eqs. (8.2.9):

```
q = z(1:5); q_dot = z(6:10);
LHS = [[eye(5) zeros(5,7)]; [zeros(5) M(q) -a(q)'];...
       [zeros(2,5) -a(q) zeros(2)]];
RHS = [q_dot; F(q,q_dot); a_dot(q,q_dot) * q_dot];
z_dot = LHS\RHS;
```

where  $M(q)$ ,  $a(q)$ ,  $a\_dot(q,q\_dot)$ , and  $F(q,q\_dot)$  are defined in function m-files. The result is

$$\{\dot{z}\} = \begin{Bmatrix} [16.4452 \quad -11.5408 \quad 0.40 \quad -0.20 \quad 80.00]^T \\ [1.9061 \quad 2.7173 \quad -75.7185 \quad -44.7319 \quad 68.5679]^T \\ [1.906 \quad 2.717]^T \end{Bmatrix}. \quad \triangleleft$$

The state-space vector in the augmented method is

$$\{z\} = \begin{Bmatrix} \{q\} \\ \{\dot{q}\} \end{Bmatrix} = \begin{Bmatrix} [X \ Y \ \psi \ \theta \ \phi]^T \\ [\dot{X} \ \dot{Y} \ \dot{\psi} \ \dot{\theta} \ \dot{\phi}]^T \end{Bmatrix},$$

whose value at the given instant is known from the analysis of initial conditions to be

$$\{z\} = \begin{Bmatrix} [2 \quad -1 \quad -0.6109 \quad 0.4363 \quad 3.6652]^T \\ [16.4452 \quad -11.5408 \quad 0.40 \quad -0.20 \quad 80.00]^T \end{Bmatrix}. \quad \triangleleft$$

The Matlab operations to compute  $\{\dot{z}\}$  are like those for the integrated multiplier method, but there are fewer partitions to define. As before, it is assumed that function m-files have been written to evaluate the basic coefficient matrices, so the following program fragments implement the operations associated with Eqs. (8.2.11):

```
q = z(1:5); q_dot = z(6:10);
LHS = [[M(q) -a(q)']; [-a(q) zeros(2)]];
RHS = [F(q,q_dot); a_dot(q,q_dot) * q_dot];
sol = LHS\RHS; q2_dot = sol(1:5);
z_dot=[q_dot; q2_dot];
```

## 8.2 Computational Methods

527

The first three singular values  $w_{\text{diag}}$  should be zero because  $[A]$  has three rows of zeros. This is confirmed by the computed results, which give

$$w = [0.0000 \ 0.0000 \ 0.0000 \ 1.0056 \ 1.0554]^T.$$

We correspondingly form the rows of  $[C]$  from the first three columns of  $[R]$ , then use that value to implement Eqs. (8.2.26),

```
C = R(:,1:3)'; LHS = [C*M(q); -a(q)];
RHS = [C * F(q,q_dot); a_dot(q,q_dot) * q_dot];
q_2dot = LHS\RHS; z_dot = [q_dot; q_2dot]
```

The value of  $\{z\}$  that results is identical to that obtained from the augmented and elimination methods. An interesting feature of Matlab is that it contains the null function, which gives the orthogonal complement without all of the intermediate programming steps. Specifically, we could have written  $C = \text{null}(A)'$ . The solution did not focus on this alternative because most mathematical software contains a SVD routine, whereas the null routine is less common. In the event that one wishes to compare these alternative functions, it is important to realize that  $[C]$  obtained from the null function is likely to differ from the result obtained from SVD.

Implementation of the embedding method version begins by selecting the generalized coordinates to place in the constrained set and defining the corresponding sorting matrix  $[P]$ . In the present context it is logical to select  $X$  and  $Y$  as the constrained variables, consistent with our analysis of initial conditions, so that

$$\{q_c\} = [X \ Y]^T, \quad \{q_u\} = [\psi \ \theta \ \phi]^T.$$

Satisfaction of Eq. (8.2.37) for these definitions of  $\{q_u\}$  and  $\{q_c\}$  requires that

$$[q_1 \ q_2 \ q_3 \ q_4 \ q_5]^T = [P][q_3 \ q_4 \ q_5 \ q_1 \ q_2]^T.$$

The nonzero element in row  $j$  of  $[P]$  occurs in column  $n$ , where  $n$  is the row where  $q_j$  occurs in the right side vector multiplying  $[P]$ . A Matlab fragment implementing this definition is

```
P = zeros(5); P(1,4) = 1; P(2,5) = 1;
P(3,1) = 1; P(4,2) = 1; P(5,3) = 1;
```

The corresponding definition of the state vector is

$$\{z\} = \begin{Bmatrix} \{q_u\} \\ \{\dot{q}_u\} \\ \{q_c\} \end{Bmatrix} = \begin{Bmatrix} [\psi \ \theta \ \phi]^T \\ [\dot{\psi} \ \dot{\theta} \ \dot{\phi}]^T \\ [X \ Y]^T \end{Bmatrix}.$$

## 8.2 Computational Methods

529

**EXAMPLE 8.6** A thin disk whose radius is 250 mm rolls without slipping after being set into motion. Two sets of initial conditions are of interest:

1. The precession and spin rates are set to the values required for a steady precession at  $\theta = 60^\circ$ , such that the center would follow a circular path having radius  $\rho = 5R$ . However, the initial nutation angle is  $\theta = 30^\circ$  and the initial nutation rate is  $\dot{\theta} = -\dot{\psi}/2$ , rather than zero. Other initial conditions are  $X = 0$ ,  $Y = 5R$ ,  $\psi = 0$ ,  $\phi = 0$ .
2. The disk is set into planar motion with its center's velocity being  $0.1155 (gR)^{1/2}$  in the  $X$  direction, and  $\dot{\psi} = \dot{\theta} = 0$ . The disk is leaning slightly, with a nutation angle of  $\pi/2 - 0.01$  rad, and the other initial conditions are  $X = Y = 0$ ,  $\psi = 0$ ,  $\phi = 0$ .

For each case use numerical methods to solve the equations of motion. Graph the response in a manner that describes the motion in each case.

**SOLUTION** This example builds on the expertise developed in the previous example, while also leading to responses that have numerous interesting features. The computation is based on the augmented algorithm because it is relatively easy to program, and reasonably efficient. For either set of initial conditions the main program performs a number of fundamental tasks. It begins with an evaluation of the full set of initial generalized velocities corresponding to the given unconstrained values. It then executes a loop that saves the current set of  $\{q\}$  and  $\{\dot{q}\}$  values, increments time, and calls the differential equation solver. As noted in Example 7.19, some subprograms for solving differential equations are adaptive. Such a routine will automatically select time steps and perform multiple corresponding substeps between the specified beginning and termination times. The present work uses such a solver with the time interval subdivided into many subintervals. The state vector computed at each step initializes the next step. Specifically, the results were obtained with the Matlab ODE45 function, which employs fourth- and fifth-order Runge–Kutta formulas. (The alternative ODE23, which implements lower-order formulas, was found to require approximately 30% more time to execute, with no difference in the output.) The programmatic steps that were executed to call ODE45 were constructed as follows. The state-space vector formed from the values of  $\{q\}$  and  $\{\dot{q}\}$  at the beginning of the integration step is contained in the variable `z_0` and the corresponding time is `t0`. The time for the desired response is `tf`. The program fragment is

```
z_dot_anon = @(t,z) z_dot_aug(t,z,radius,kappa)
for i = 1:i_max; t0 = (i - 1) * dt; tf = i * dt;
    < Data storage and error checking operations >
    [t,z] = ode45(z_dot_anon, [t0,tf], z_0, options);
    n_steps = size(z,1); z_0 = z(n_steps,1:10)';
end
```

The first argument in the call to the `ode45` function is the handle of the anonymous function `z_dot_anon`, which passes the requisite parameter values to a function m-file `z_dot_aug.m` that evaluates  $\{\dot{z}\} = [\{\dot{q}\}^T \{\ddot{q}\}^T]^T$  corresponding to the current  $\{z\} = [\{q\}^T \{\dot{q}\}^T]^T$ . (See Example 7.19 for a more detailed discussion of anonymous functions in Matlab.) These operations parallel those described in Example 8.5 for a single time step using the augmented algorithm. The options value contains various parameters for `ode45` that are set with the `odeset` function. All of these parameters were left at their defaults, except that the relative and absolute errors were set to  $10^{-8}$ , both of which are substantially smaller than the defaults. The output variable  $t$  is a vector of time steps at which `ode45` computed a response. The output  $z$  has the same number of rows, with each row containing the state vector corresponding to each row of  $t$ .

The storage and checking operations mentioned in the listing evaluate the total mechanical energy  $E = T + V$  corresponding to the current  $\{z\}$ . They also evaluate  $[a]\{\dot{q}\}$ , which would grow if the velocity constraints drift even though the acceleration constraints are satisfied. The values of  $E$  and  $\text{norm}([a]\{\dot{q}\})$  are appended to `z_0`, which is saved in additional operations before the next integration step is begun.

In general, it is a good idea to verify that any numerical simulation gives the correct results in situations in which a known solution exists. Such is the case here. The conditions for steady precession were derived in Example 8.5. If we modify the initial conditions in Case 1 such that  $\theta = 60^\circ$  and  $\dot{\theta} = 0$ , the steady precession formulas indicate that the response should be given by

$$\begin{aligned} X &= 1.25 \sin(1.7234t), \quad Y = 1.25 \cos(1.7234t) \text{ m}, \\ \psi &= 1.7234t, \quad \theta = \pi/3, \quad \phi = -9.479t \text{ rad.} \end{aligned}$$


The computed result closely matched these expressions. Throughout the integration interval the values of  $\dot{\psi}$  and  $\dot{\phi}$  matched the formula values to seven significant figures, and  $|\dot{\theta}|$  remained smaller than  $10^{-15}$  rad/s.

The responses corresponding to the Case 1 initial conditions are displayed in the first two graphs as plots of  $X$ ,  $Y$ ,  $\theta$ ,  $\psi$ , and  $\phi$  as functions of time. Throughout the time interval of the plots, the mechanical energy remained at  $E/m = 4.250498$  and the norm of the velocity constraint error remained below  $2(10^{-13})$ . The first set of plots suggests that the motion is like a steady precession, in that the time dependence of  $X$  and  $Y$  is oscillatory and nearly sinusoidal. Also,  $\theta$ , which represents the wobble, executes a relatively small oscillation about the mean value at which it was set. In contrast, the plots of  $\psi$  and  $\phi$  differ substantially from the steady precession case, in which they would be constant. These rotation rates now execute a synchronized oscillation that is a large fraction of their respective mean values.




## 8.2 Computational Methods

531



Generalized coordinates and velocities as functions of time when the disk is released with initial conditions resembling a steady precession

A clearer picture emerges from the third graph, which plots  $(X, Y)$  pairs at successive values of  $t$ ; this is the path of the center of the disk as viewed looking down the  $Z$  axis. Careful inspection would show that the center follows a nearly elliptical path relative to the  $XY$  plane, with the major and minor axes of this ellipse rotating a little in successive cycles. At any instant the distance to the disk's center from



Path of the center of the disk that is released with initial conditions resembling a steady precession

the origin is between the length of the semiminor and semimajor axes. The average distance from this center is approximately 0.32 m, which is much less than the value  $\rho = 5R$  that was intended with the initial conditions.

One might be surprised that a nearly steady precession is obtained, despite the difference between the given initial conditions and those for the intended motion. This is a manifestation of the overall stability resulting from the gyroscopic moment, which induces a rotation about an axis perpendicular to the axis of an applied moment. Stability is the motivation for considering the second set of initial conditions. A classical result states that, if one attempts to cause a disk to roll freely in the vertical plane, that motion will be unstable if the forward speed is below a certain value. Before we examine the computational result, let us see how such a stability analysis is carried out. The reference free-rolling motion corresponds to  $\dot{X} = v$ ,  $\dot{Y} = 0$ ,  $\theta = \pi/2$ ,  $\dot{\psi} = 0$ , and  $\dot{\phi} = v/R$ . A stability analysis entails considering a motion in which the generalized coordinates differ by a very small amount from this reference solution. To highlight this difference we let  $\varepsilon$  designate a small parameter, and define the deviations as  $\varepsilon\xi_j$ , where the  $\xi_j$  variables are taken to have a unit order of magnitude, specifically,

$$X = vt + \varepsilon\xi_1, \quad Y = \varepsilon\xi_2, \quad \psi = \varepsilon\xi_3, \quad \theta = \frac{\pi}{2} - \varepsilon\xi_4, \quad \phi = \frac{vt}{R} + \varepsilon\xi_5. \quad (1)$$

The idea is to substitute these expressions into the equations of motion and drop all terms that contain  $\varepsilon$  in quadratic and higher powers, on the grounds that higher-order terms will be negligible if  $\varepsilon$  is sufficiently small. The trigonometric terms are linearized with the aid of identities, such that

$$\begin{aligned} \sin \psi &= \sin(\varepsilon\xi_3) \approx \varepsilon\xi_3, \quad \cos(\psi) = \cos(\varepsilon\xi_3) \approx 1, \\ \sin(\theta) &= \sin\left(\frac{\pi}{2} - \varepsilon\xi_4\right) = \cos(\varepsilon\xi_4) \approx 1, \\ \cos(\theta) &= \cos\left(\frac{\pi}{2} - \varepsilon\xi_4\right) = \sin(\varepsilon\xi_4) \approx \varepsilon\xi_4. \end{aligned} \quad (2)$$

The equations of motion and constraint equations were derived in Example 8.4. Substitution of Eqs. (1) and (2) into the constraint equations gives

$$\begin{aligned} v + \varepsilon\dot{\xi}_1 - R\left[(\varepsilon\dot{\xi}_3)(\varepsilon\xi_4) + \left(\frac{v}{R} + \varepsilon\dot{\xi}_5\right)\right] + R(-\varepsilon\dot{\xi}_4)(\varepsilon\xi_3) &= 0, \\ \varepsilon\dot{\xi}_2 - R\left[(\varepsilon\dot{\xi}_3)(\varepsilon\xi_4) + \left(\frac{v}{R} + \varepsilon\dot{\xi}_5\right)\right](\varepsilon\xi_3) - R(-\varepsilon\dot{\xi}_4) &= 0. \end{aligned}$$

The terms in the preceding equations that are independent of  $\varepsilon$  cancel, and linearization eliminates all higher-order terms in  $\varepsilon$ . Thus the constraint equations reduce to

$$\dot{\xi}_1 = R\dot{\xi}_5, \quad \dot{\xi}_2 = -R\dot{\xi}_4 + v\xi_3. \quad (3)$$

## 8.2 Computational Methods

533

To eliminate as many generalized coordinates as possible from the equations of motion, we substitute Eqs. (1) and (3) into the Lagrange equations for  $X$  and  $Y$ , which leads to

$$m\varepsilon(R\ddot{\xi}_5) = \lambda_1, \quad m\varepsilon(-R\ddot{\xi}_4 + v\dot{\xi}_3) = \lambda_2. \quad (4)$$

Substitution of these expressions into the remaining Lagrange equations eliminates the Lagrange multipliers. We simplify the algebraic operations by observing that both  $\lambda_1$  and  $\lambda_2$  are of order  $\varepsilon$ , which makes it possible to ignore *a priori* some small terms containing  $\lambda_1$  and  $\lambda_2$ . The result is

$$\begin{aligned} m\kappa^2 \left( \frac{1}{2} \varepsilon \ddot{\xi}_3 + \varepsilon \dot{\xi}_4 \frac{v}{R} \right) &= 0, \\ m\varepsilon \left[ \frac{1}{2} \kappa^2 (-\varepsilon \ddot{\xi}_4) + \kappa^2 (\varepsilon \dot{\xi}_3) \frac{v}{R} + gR(\varepsilon \xi_4) \right] &= -\lambda_2 R, \\ m\kappa^2 (\varepsilon \ddot{\xi}_5) &= -\lambda_1 R. \end{aligned} \quad (5)$$

Satisfaction of the first of Eqs. (4) and the last of Eqs. (5) requires that  $\xi_5 = 0$ . This enables us to obtain a single differential equation for one variable. The first of Eqs. (5) indicates that  $\dot{\xi}_3 = -2(v/R)\xi_4$ , which we substitute along with  $\lambda_2$  from Eqs. (4), into the second of Eqs. (5). We thereby obtain

$$\left( \frac{1}{2} \kappa^2 + R^2 \right) \ddot{\xi}_4 + \left[ 2 \left( \frac{\kappa^2}{R^2} + 1 \right) v^2 - GR \right] \xi_4 = 0. \quad (6)$$

This is the differential equation for a linear undamped spring-mass system. The coefficient of the acceleration term is always positive, so the solution for  $\xi_4$  will be sinusoidal if the coefficient of the springlike terms is also positive. A sinusoidal term does not grow as time evolves, so it corresponds to a stable situation. In contrast, if the coefficient is negative, the solutions are exponential, with one positive characteristic exponent. Because this means that  $\xi_4$  will grow as  $t$  increases, corresponding to a divergence from the nominal value  $\theta = \pi/2$ , the response is said to be unstable. The radius of gyration for a thin disk is  $\kappa = R/\sqrt{2}$ , so we have found that


$$v > \left( \frac{gR}{3} \right)^{1/2} \implies \text{stability}.$$

This result is often misinterpreted. The analysis is valid only if  $\xi_4$  remains at unit order, so we may conclude that a disk will not roll upright along a straight line if the speed does not satisfy the stability criterion. However, the analysis does not tell us what will happen in the unstable case, just as the fact that a ball at the apex of a hill is unstable does not tell us much. Finding out what actually happens requires a numerical solution. The given forward speed in the Case 2 initial conditions is 20% of this stability limit. The full set of initial conditions, which is obtained by satisfying the constraint equations with the given initial parameters, is  $\{q\} = [0 \ 0 \ 0 \ \pi/2 - 0.1 \ 0]^T$ ,  $\{\dot{q}\} = [0.1155(gR)^{1/2} \ 0 \ 0 \ 0 \ 0.1155(gR)^{1/2}]^T$ . This

## 8.2 Computational Methods

535

precession angle has changed, thereby setting up the overall circular pattern. The computed result for the center's path is almost closed. Another run with a larger initial deviation from an upright orientation,  $\theta = \pi/2 - 0.1$ , showed a similar looping pattern, but it was visibly open. This suggests that setting the initial value of  $\theta$  extremely close to  $\pi/2$  would indeed produce a closed path corresponding to a truly periodic response.



Path of the center of the disk when it is released with a slow forward motion in a nearly upright orientation

Although this result is extremely interesting, it also points out the limits of computer modeling that do not truly capture reality. An actual disk could not sustain this motion because of rolling friction, which dissipates energy, whereas energy is conserved in the present idealized model. The only condition in our analysis that would indicate cessation of the motion would be that  $\theta < 0$  or  $\theta > \pi$ , both of which correspond to the center falling to the ground. It would also be appropriate to terminate our ideal model if the instantaneous friction force required to prevent slippage exceeds the maximum that can be developed for the current normal force. However, checking this condition would require that we redo the entire formulation, for we then would need to track the actual friction and normal forces, rather than employing Lagrange multipliers to represent those forces. We also would need to evaluate the normal force at each instant. We can implement such modifications by following techniques developed in the next section.

In closing, it is useful to consider using an algorithm other than the augmented method. Matlab's `null` function makes it particularly easy to program the orthogonal complement algorithm, as described in the previous example. Other

than altering how  $\{\ddot{q}\}$  is evaluated at each time step, all other aspects of the solution obtained with the augmented method were retained. Because the orthogonal complement eliminates the Lagrange multipliers, the instantaneous generalized accelerations are obtained by solving five simultaneous equations, whereas the augmented method entails solving seven equations. Nevertheless, the orthogonal complement method required 41% more cpu time. This apparently is due to the computational overhead required to perform the SVD.

### 8.2.4 Analysis of Coulomb Friction

When it is necessary to account for Coulomb friction forces, it is mandatory that the constraint forces be evaluated, rather than represented by Lagrange multipliers. Let us partition the virtual work into three parts:  $\delta W_a$  is the contribution of known applied forces,  $\delta W_C$  denotes the contribution of the constraint forces that act perpendicularly to contact surfaces, and  $\delta W_f$  is the contribution of the friction forces. The first part is described in the usual manner as

$$\delta W^{(a)} = \sum_{j=1}^N Q_j^{(a)} \delta q_j. \quad (8.2.62)$$

The explicit contribution of a single constraint force  $C_i$  to the virtual work is described by Eq. (7.4.13). We adapt that description to a friction analysis by using  $N_i$  to denote the normal force, and allow for the possibility that there are several such forces by adding the individual contributions. Thus we have

$$\delta W_C = \sum_{i=1}^J N_i \sum_{j=1}^N c_{ij} \delta q_j. \quad (8.2.63)$$

The form of  $\delta W_f$  is a generalization of the typical situation described by Eq. (8.1.7). Each friction force may be written as

$$\bar{f}_i = -\mu |N_i| \operatorname{sgn}((\bar{v}_{\text{rel}})_i \cdot \bar{e}_t) \bar{e}_t, \quad (8.2.64)$$

where  $(\bar{v}_{\text{rel}})_i$  is the velocity of the surface on which  $\bar{f}_i$  acts relative to the other surface and  $\bar{e}_t$  is the direction that is tangent to the plane of contact. Furthermore, velocities may be expressed as a linear sum of generalized velocities. It follows that the virtual work done by all friction forces is described in general by

$$\delta W_f = \sum_{i=1}^J \sum_{j=1}^N u_{ij}(q_i, \dot{q}_i, t) |N_i| \delta q_j, \quad (8.2.65)$$

where the  $u_{ij}(q_i, \dot{q}_i, t)$  will contain signum functions of the generalized velocities.

## 8.2 Computational Methods

537

The generalized forces obtained from these three contributions to the virtual work are

$$Q_j = Q_j^{(a)} + \sum_{i=1}^J c_{ij} N_i + \sum_{i=1}^J u_{ij} |N_i|. \quad (8.2.66)$$

The analog of Eqs. (8.1.4) when the generalized forces are described in this manner is

$$\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \right) - \frac{\partial T}{\partial q_j} + \frac{\partial V}{\partial q_j} = Q_j^{(a)} + \sum_{i=1}^J c_{ij} N_i + \sum_{i=1}^J u_{ij} |N_i|, \quad j = 1, \dots, N. \quad (8.2.67)$$

The matrix version of these equations is

$$[M] \{\ddot{q}\} = \{F\} + [c]^T \{N\} + [u] \{|N|\}, \quad (8.2.68)$$

where  $\{N\}$  is a vector of normal force values and  $\{|N|\}$  is the corresponding vector of magnitudes.

If the contacting surfaces are such that the normal force can act in only one direction, as in the case of a block on a plane, then the corresponding  $\bar{N}_i$  can act only to press the surfaces together. In that case,  $N_i$  can only be positive, because negative  $N_i$  would mean that the surfaces are about to separate. If only compressive contact forces are permitted,  $|N_i|$  can be replaced with  $N_i$ , so the equations of motion are linear in the normal forces. Any of the algorithms that entail evaluating the Lagrange multipliers are readily modified to address this situation. An important aspect of the one-sided nature of the contact force in this case is that the solution ceases to be valid whenever any  $N_i$  becomes negative.

The problematic case is that in which the sense of the normal force is not known in advance, as would be the case for a collar sliding on a guide bar. In planar motion, this means that the sign of the normal force is unknown, whereas the magnitude of the normal force in spatial motion is the resultant of the two force components perpendicular to  $\bar{e}_t$ . In either case, the normal force does not occur linearly in the equations of motion, so there is no simple modification of the solution algorithms. One approach is implemented in the next example. The idea is to use the fact that one can obtain the magnitude of a scalar by multiplying the value by its sign. Thus

$$|N_i| = N_i \text{sgn}(N_i). \quad (8.2.69)$$

The value of  $N_i$  is taken to be unknown, and  $\text{sgn}(N_i)$  is set by the value of  $N_i$  that was most recently determined.

A separate issue for Coulomb friction is whether slippage actually occurs. The static friction law states that, at any instant when there is no relative velocity between the contacting surfaces, sliding will resume only if the magnitude of the friction force exceeds  $\mu_s |N_i|$ , where  $\mu_s$  is the coefficient of static friction. Thus a simulation of the Coulomb friction force should implement a separate test for this condition, which would be called for whenever the contacting surfaces are sensed to have reversed the sense of their sliding motion.

## 8.2 Computational Methods

539

We describe the virtual work done by the normal force at point  $A$  explicitly, as called for by the general procedure for handling friction forces. Arbitrary increments in the generalized coordinates cause collar  $B$  to merely displace parallel to its guide, so the normal force acting on collar  $B$  will not contribute to the virtual work. For collar  $A$  we take the normal force  $\bar{N}_A$  to be positive upward, and the friction force  $\bar{f}_A$  is taken to be positive when it acts to the left, corresponding to  $\bar{v}_A$  being to the right. Applying the analytical method for virtual displacement to the second of Eqs. (1) gives

$$\delta \bar{r}_A = \delta s (-\cos \beta \bar{I} + \sin \beta \bar{J}) + L \delta \phi (-\sin \phi \bar{I} - \cos \phi \bar{J}).$$

The gravity and spring forces are conservative, so the virtual work is

$$\delta W = (-f_A \bar{I} + N_A \bar{J}) \cdot \delta \bar{r}_A = L(-N_A \cos \phi + f_A \sin \phi) \delta \phi + (N_A \sin \beta + f_A \cos \beta) \delta s,$$

from which it follows that the generalized forces are

$$Q_1 = -N_A L \cos \phi + f_A L \sin \phi, \quad Q_2 = N_A \sin \beta + f_A \cos \beta. \quad (4)$$

We will introduce Coulomb's law later, so we proceed to formulating the energy expressions. The bar is in general motion, with  $-\dot{\phi} \bar{k}$  being its angular velocity. The required velocities may be described by by direct differentiation of the positions in Eqs. (1):

$$\begin{aligned} \bar{v}_B &= \frac{d}{dt} \bar{r}_{B/O} = \dot{s} (-\cos \beta \bar{I} + \sin \beta \bar{J}), \\ \bar{v}_A &= \frac{d}{dt} \bar{r}_{A/O} = (-\dot{s} \cos \beta - L \dot{\phi} \sin \phi) \bar{I} + (\dot{s} \sin \beta - L \dot{\phi} \cos \phi) \bar{J}, \\ \bar{v}_G &= \frac{d}{dt} \bar{r}_{G/O} = \left(-\dot{s} \cos \beta - \frac{L}{2} \dot{\phi} \sin \phi\right) \bar{I} + \left(\dot{s} \sin \beta - \frac{L}{2} \dot{\phi} \cos \phi\right) \bar{J}. \end{aligned}$$

The kinetic energy corresponding to these quantities is

$$\begin{aligned} T &= \frac{1}{2} m v_G^2 + \frac{1}{2} \left( \frac{1}{12} m L^2 \right) \dot{\phi}^2 + \frac{1}{2} m v_A^2 + \frac{1}{2} m v_B^2 \\ &= \frac{1}{2} m \left[ \left( -\dot{s} \cos \beta - \frac{L}{2} \dot{\phi} \sin \phi \right)^2 + \left( \dot{s} \sin \beta - \frac{L}{2} \dot{\phi} \cos \phi \right)^2 + \frac{1}{12} L^2 \dot{\phi}^2 \right. \\ &\quad \left. + \left( -\dot{s} \cos \beta - L \dot{\phi} \sin \phi \right)^2 + \left( \dot{s} \sin \beta - L \dot{\phi} \cos \phi \right)^2 + \dot{s}^2 \right] \\ &= \frac{1}{2} m \left[ \frac{4}{3} L^2 \dot{\phi}^2 + 3 \dot{s}^2 - 3 L \dot{\phi} \dot{s} \sin(\beta - \phi) \right]. \end{aligned} \quad (5)$$

The potential energy is readily constructed in terms of the constrained generalized coordinates. The distance from the intersection  $O$  of the guide bars to the collar is  $\bar{r}_{A/O} \cdot \bar{I}$ . At  $\phi = 0$ , where the spring is undeformed, this distance is  $L$ . Thus the spring elongation is  $\Delta = L - \bar{r}_{A/O} \cdot \bar{I}$ . Let the  $X$  axis be the reference elevation for gravity potential energy. Then the elevation of the collars and of the center of

mass are the vertical components of the respective position vectors given in Eqs. (1). These considerations lead to

$$V = \frac{1}{2}k[L(1 - \cos \phi) + s \cos \beta]^2 + mg\left(3s \sin \beta - \frac{3}{2}L \sin \phi\right).$$

The Lagrange equations corresponding to these energy expressions and the generalized forces in Eq. (2) are

$$\begin{aligned} \frac{4}{3}mL^2\ddot{\phi} - \frac{3}{2}mL\dot{s} \sin(\beta - \phi) + kL[L(1 - \cos \phi) + s \cos \beta] \sin \phi \\ - \frac{3}{2}mgL \cos \phi = -N_A L \cos \phi + f_A L \sin \phi, \\ 3m\dot{s} - \frac{3}{2}mL\ddot{\phi} \sin(\beta - \phi) + \frac{3}{2}mL\dot{\phi}^2 \cos(\beta - \phi) + k[L(1 - \cos \phi)] \\ + s \cos \beta] \cos \beta + 3mg \sin \beta = N_A \sin \beta + f_A \cos \beta. \end{aligned} \quad (6)$$

The last step in the derivation is to characterize the friction force. The generalized forces were derived with positive  $N_A$  corresponding to the normal force acting upward. However, the constraint imposed by the guide bar is still effective if the collar is tending to move upward, which would lead to  $N_A$  being negative. We therefore describe the magnitude of the sliding friction force as  $|f_A| = \mu |N_A|$ . Furthermore,  $\bar{f}_A$  was taken to be directed to the left, which corresponds to collar  $A$  moving to the right. Such a movement means that  $\bar{v}_A \cdot \bar{I} > 0$ , so we may say that  $f_A = \mu |N_A| \text{sgn}(\bar{v}_A \cdot \bar{I})$ . Because  $\bar{v}_A \cdot \bar{I} = -\dot{s} \cos \beta - L\dot{\phi} \sin \phi$ , substituting  $f_A$  into Eqs. (6) shows that we have three unknowns,  $\phi$ ,  $s$ , and  $N_A$ , that are governed by the two Lagrange differential equations and the velocity constraint equation.

These equations are highly nonlinear, so we solve them numerically. Even if dimensional system parameters were given, it is good practice to begin by nondimensionalizing the equations. Let  $\xi = s/L$ , and let nondimensional time be  $\tau = t(g/L)^{1/2}$ , so that each time derivative is replaced with a derivative with respect to  $\tau$  according to  $d/dt = (g/L)^{1/2} d/d\tau$ . Changing the variables in this manner converts Lagrange equations (6), and velocity constraint equation (3) to

$$\begin{aligned} \frac{4}{3}\ddot{\phi} - \frac{3}{2}\ddot{\xi} \sin(\beta - \phi) + \Omega^2[(1 - \cos \phi) + \xi \cos \beta] \sin \phi - \frac{3}{2} \cos \phi \\ = -\hat{N} \cos \phi + \mu \cos \beta |\hat{N}| \text{sgn}(v_A) \sin \phi, \\ 3\ddot{\xi} - \frac{3}{2}\ddot{\phi} \sin(\beta - \phi) + \frac{3}{2}\dot{\phi}^2 \cos(\beta - \phi) + \Omega^2[(1 - \cos \phi) + \xi \cos \beta] \cos \beta + 3 \sin \beta \\ = \hat{N} \sin \beta + \mu |\hat{N}| \text{sgn}(v_A) \cos \beta, \\ \dot{\xi} \sin \beta - \dot{\phi} \cos \phi = 0, \end{aligned}$$

where an overdot now denotes differentiation with respect to  $\tau$ , and

$$v_A = -\dot{\xi} \cos \beta - \dot{\phi} \sin \phi, \quad \Omega^2 = \frac{kL}{mg}, \quad \hat{N} = \frac{N_A}{mg}.$$



## 8.2 Computational Methods

541

As suggested by Eq. (8.2.69), we handle the appearance of  $|N|$  in the friction force by replacing it with  $N \operatorname{sgn}(N)$ . The resulting differential equations to solve may be written as

$$\begin{aligned} [M] \{\ddot{q}\} &= \{F\} + \{H\} \hat{N}, \\ -[a] \{\ddot{q}\} &= [\dot{a}] \{\dot{q}\}, \end{aligned} \quad (7)$$

where  $\{q\}$  now is formed from  $\phi$  and  $\xi$ , and

$$\begin{aligned} [M] &= \begin{bmatrix} \frac{4}{3} & -\frac{3}{2} \sin(\beta - q_1) \\ -\frac{3}{2} \sin(\beta - q_1) & 3 \end{bmatrix}, \\ \{F\} &= \begin{Bmatrix} -\Omega^2 [(1 - \cos q_1) + q_2 \cos \beta] \sin q_1 + \frac{3}{2} \cos q_1 \\ -\frac{3}{2} \dot{q}_1^2 \cos(\beta - q_1) - \Omega^2 [(1 - \cos q_1) + q_2 \cos \beta] \cos \beta - 3 \sin \beta \end{Bmatrix}, \\ \{H\} &= \begin{Bmatrix} -\cos q_1 + \mu \cos \beta \operatorname{sgn}(\hat{N}) \operatorname{sgn}(-\dot{q}_2 \cos \beta - \dot{q}_1 \sin q_1) \sin q_1 \\ \sin \beta + \mu \operatorname{sgn}(\hat{N}) \operatorname{sgn}(-\dot{q}_2 \cos \beta - \dot{q}_1 \sin q_1) \cos \beta \end{Bmatrix}, \\ [a] &= [-\cos q_1 \quad \sin \beta], \quad \left[ \frac{da}{dt} \right] = [\dot{q}_1 \sin q_1 \quad 0]. \end{aligned} \quad (8)$$

We employ the augmented method to solve these equations, which requires that the values of  $\{\ddot{q}\}$  and  $\hat{N}$  be evaluated at each instant. Toward that end we write Eqs. (7) as

$$\begin{bmatrix} [M] & -\{H\} \\ -[a] & 0 \end{bmatrix} \begin{Bmatrix} \{\ddot{q}\} \\ \hat{N} \end{Bmatrix} = \begin{Bmatrix} \{F\} \\ \left[ \frac{da}{dt} \right] \{\dot{q}\} \end{Bmatrix}. \quad (9)$$

This is the standard form for the augmented algorithm, the third of Eqs. (8.2.11), except that the coefficient matrix is not symmetric. The state vector formed by stacking the current  $\{\dot{q}\}$  value above the  $\{\ddot{q}\}$  value obtained from Eq. (9) constitutes the input for the differential equation solver. Solving these equations linearly requires that  $\{H\}$ , which depends on  $\operatorname{sgn}(\hat{N})$ , be evaluated before solving the equations. The results presented in the following discussion were computed by setting the sign of  $\hat{N}$  at each time step to the sign of the result for  $\hat{N}$  computed at the previous time step.

Starting the differential equation solver requires initial values of  $\{q\}$  and  $\{\dot{q}\}$ , but this is a holonomic system, which means that only the initial values  $\phi_0$  and  $\dot{\phi}_0$  may be defined freely. The constraint conditions then give

$$s_0 = \frac{L \sin \phi_0}{\sin \beta}, \quad \dot{s}_0 = \frac{L \dot{\phi}_0 \cos \phi_0}{\sin \beta}.$$

The results presented here were obtained with the Matlab ODE45 function, which uses Runge–Kutta integration. The time step was set at  $\Delta\tau = 0.004$ . Before we examine the results, it is appropriate to consider some general issues. Error

spring, and the collars had mass, whereas friction at both collars was important for the previous case. Furthermore, the previous analysis dealt with a situation in which collar *A* had a constant velocity. Nevertheless, we can see that the kinematical aspects of the current solution were simpler by virtue of its use of unconstrained generalized coordinates. In fact, if it were necessary to account for friction at both collars, as was done previously, we would use three constrained generalized coordinates, which would need to satisfy constraint conditions associated with both collars. Another noteworthy aspect is that accounting for each collar's mass entailed little additional effort for the Lagrange equation formulation, whereas the previous approach would require that Newton's Second Law be applied to each collar to account for the internal forces exerted between each collar and the bar.

## SELECTED REFERENCES


- Amirouche, F. M. L., *Computational Methods in Multibody Dynamics*, Prentice-Hall, Englewood Cliffs, New Jersey (1992).
- Baumgarte, J., "Stabilization of constraints and integrals of motion," *Computer Methods in Applied Mechanics and Engineering* **1**, 1–16 (1972).
- Brenan, K. E., Campbell, S. L., and Petzold, L. R., *Numerical Solutions of Initial-Value Problems in Differential-Algebraic Equations*, Elsevier, New York (1989).
- Fox, B., Jennings, L. S., and Zomaya, A. Y., *Constrained Dynamics Computations: Models and Case Studies*, World Scientific, Singapore (2000).
- Goldstein, H., *Classical Mechanics*, 2nd ed., Addison-Wesley, Reading, Massachusetts (1980).
- Greenwood, D. T., *Advanced Dynamics*, Cambridge University Press, New York (2003).
- Hairer, E., and Wanner, G., *Solving Ordinary Differential Equations II: Stiff and Differential-Algebraic Problems*, Springer-Verlag, Berlin (1996).
- Haug, E. J., *Computer Aided Kinematics and Dynamics of Mechanical Systems, Vol. 1: Basic Methods*, Allyn & Bacon, Needham Heights, Massachusetts (1989).
- Kumar, A., and Daoutidis, P., *Control of Nonlinear Differential Algebraic Equation Systems*, Chapman & Hall/CRC Press, Boca Raton, Florida (1999).
- MATLAB Reference Guide, Version 7.1, The MathWorks, Cambridge, Massachusetts, 2005.
- Meirovitch, L., *Methods of Analytical Dynamics*, McGraw-Hill, New York (1970).
- Pars, L. A., *A Treatise on Analytical Dynamics*, Heinemann, London (1965).
- Press, W. H., Flannery, B. P., Teukolsky, S. A., and Vetterling, W. T., *Numerical Recipes*, 2nd ed., Cambridge University Press, New York (1992).
- Rosenberg, R. M., *Analytical Dynamics of Discrete Systems*, Plenum, New York (1977).
- Shabana, A. A., *Computational Dynamics*, Wiley, New York (2001).
- Stolarski, T.A., *Tribology in Machine Design*, Industrial Press, New York (1990).
- Wasfy, T. M., and Noor, A. K., "Computational strategies for flexible multibody systems," *Applied Mechanics Reviews*, **56**, 553–613 (2003).

## Homework Problems

545


### HOMEWORK PROBLEMS

**EXERCISE 8.1** A torque  $\Gamma$  acting about the vertical shaft is such that the precession rate is  $\Omega = \Omega_0 \sin(\beta t)$ . The sliders, whose masses are  $m_A$  and  $m_B$ , are tied together by an inextensible cable. The moment of inertia of the T-bar about the precession axis is  $I_p$ . Derive the equation of motion for the radial distance  $R$  assuming that frictional resistance is negligible, and also obtain an expression for  $\Gamma$ .




Exercise 8.1

**EXERCISE 8.2** Force  $\bar{F}(t)$  pushes collar  $A$ , whose mass is  $m$ , to the left. This causes the gear to roll over the horizontal rack. The mass of the gear is  $2m$ , and its radius of gyration about center point  $C$  is  $\kappa$ ; the mass of bar  $AB$  is  $m$ . Use the angles  $\theta$  and  $\phi$  as constrained generalized coordinates to derive the equations of motion for the system.




Exercise 8.2

**EXERCISE 8.3** The cylinder of mass  $m$  is free to rotate by angle  $\beta$  relative to the gimbal, which rotates about the horizontal axis. The precessional rate  $\Omega$  is held constant by varying an unknown torque  $\Gamma$  that acts about the horizontal axis  $AB$  of the gimbal. Use Lagrange's equations to derive the equation of motion governing  $\beta$ , as well as an expression for  $\Gamma$ .



Exercise 8.3

**EXERCISE 8.4** A torque  $\Gamma$  that is a known function of time acts about the vertical shaft, whereas  $M$  is a servotorque that controls the gimbal's precession, such that  $\dot{\beta} = c_1 \dot{\psi} + c_2 \beta + c_3$ , where the  $c_n$  are constants. The spin rate  $\Omega_1$  is maintained at a constant value by a servomotor. The mass of this motor and the gimbal are negligible. The mass of the flywheel is  $m$ , and its principal radii of gyration for centroidal axes are  $\kappa_1$  about its spin axis and  $\kappa_2$  normal to that axis. Derive Lagrange equations of motion, then assemble a set of state-space equations suitable for implementing a computer solution.




Exercise 8.4

## Homework Problems


547

**EXERCISE 8.9** The horizontal platform translates upward, and the T-bar rotates about the vertical axis. Both the force  $\bar{F}$  and torque  $\bar{M}$  are known functions of time. The rolling motion of disk  $C$ , which spins freely about shaft  $BC$ , is such that there is no slippage in the direction perpendicular to the sketch, but there is slippage in the radial direction. Derive the Lagrange equation(s) of motion governing this system in the situation where only the disk's mass is significant.




Exercise 8.9

**EXERCISE 8.10** The thrust of an outboard motor on a boat may be represented as a force  $\bar{F}$  acting at an angle  $\beta$  relative to the axis of the boat. The hydrodynamic properties of the boat are such that the velocity of the center of mass  $G$  is constrained to be parallel to the longitudinal axis of the boat. The component of the hydrodynamic force parallel to the axis of the boat is the drag  $f_d$ . Derive the equations of motion for the boat by using Lagrange multipliers. The mass of the boat is  $m$ , and its centroidal moment of inertia is  $I$ .




Exercise 8.10

**EXERCISE 8.11** The diagram depicts a linkage that is situated in the horizontal plane. Collar  $A$  slides along the stationary guide bar, and the steerable wheel  $B$  at the other end of rigid bar  $AB$  rolls over the ground. A servomotor controls the steering angle  $\beta$ . There is no slippage in the rolling motion, so the velocity of end  $B$  must be in the sense shown in the diagram. Movement is actuated by the known force  $F(t)$  applied to the collar. Generalized coordinates are the horizontal position  $x_A$  and the rotation angle  $\theta$ . Use the method of Lagrange multipliers to derive the equations of motion governing these variables.



Exercise 8.11

**EXERCISE 8.12** The sketch shows the top view of a sled that is towed over the ice by fastening a cable to hook  $C$ . Force  $F$  is the tensile force applied to the tow cable at its free end  $P$ ; its magnitude and direction angle  $\beta$  relative to the sled's center line are known functions of time. The edge contact constrains the velocity of points  $A$  and  $B$  to be parallel to the rails, but the speed of each point may be different. Generalized coordinates have been selected as the east and north coordinates of the center of mass  $G$  and the heading angle  $\theta$ . The radius of gyration about the vertical centroidal axis is  $\kappa_G$ . Use Lagrange's equations to derive the equations governing the motion for this system.



Exercise 8.12


The diagram shows a central rectangular body labeled  $G$ . Two arms,  $A$  and  $B$ , extend from the left side of  $G$ . Arm  $A$  has a force  $F_1$  applied at its end, and arm  $B$  has a force  $F_2$  applied at its end. A dashed line represents the axis of symmetry. Two dimensions are marked:  $L$  is the distance from the center of  $G$  to the point where arm  $C$  is attached, and  $R$  is the radius of the central body  $G$ . Arm  $C$  extends from the right side of  $G$  and has a force  $F_3$  applied at its end.

The diagram shows a mechanical system. A horizontal bar is supported by a roller at point A and a fixed support at point C. A force  $F$  is applied to the bar at point B, directed downwards. A vertical arm is pivoted at point C and has a mass  $m$  at its end, point D. The arm is at an angle  $\Omega t$  to the vertical. A horizontal slider is attached to the arm at point E, which is at a distance  $s$  from the pivot. The slider moves along a horizontal guide. The distance from point A to point C is  $L$ , and the height of the slider from the horizontal bar is  $H$ .

Copyrighted material


# Homework Problems

549




Exercise 8.16

**EXERCISE 8.17** Consider the motorboat in Exercise 8.10. The magnitude of the drag force depends on the speed of the center of mass. In addition, when the motor is set to full throttle, the thrust is speed dependent because of cavitation at the propeller. Thus, if  $\bar{v}_m$  and  $\bar{v}_G$  are the instantaneous velocities at the motor and the center of mass, then the respective forces are described by the functions  $f(|\bar{v}_G|)$  and  $F(u)$  described in the accompanying graphs, where  $u \equiv \bar{v}_m \cdot [\cos(\theta + \beta)\bar{I} + \sin(\theta + \beta)\bar{J}]$ . The boat's mass is 4000 kg, and its centroidal radius of gyration about the vertical axis is 4 m. Also, the distance  $H = 6$  m. Suppose the boat is at rest pointing northward when the motor is suddenly moved to full throttle and held there. The steering angle is set and held at  $1^\circ$  for 30 s, then reversed to  $-4^\circ$  for the next 30 s. Use numerical methods to determine the path of the center of mass during this 1-min interval. Also, determine the speed and heading of the boat at  $t = 60$  s.



Exercise 8.17

**EXERCISE 8.18** The collar and bar have equal mass  $m$ , and the effect of friction is negligible. The system is released from rest at  $\theta = 90^\circ$ . Determine the inclination angle  $\theta$  as a function of  $t$  for the case where  $(g/R)^{1/2} = 1.6$  rad/s by following alternative formulations: (a)  $\theta$  is a single unconstrained generalized coordinate, (b)  $\theta$  and  $y$  are constrained generalized coordinates.



Exercise 8.18


**EXERCISE 8.19** The sled in Exercise 8.12 is at rest pointed eastward ( $\theta = 0$ ), with its hook  $C$  at  $X = -L$ ,  $Y = 0$ . At  $t = 0$ , Tundra, the great Alaskan Malamute, begins to pull it by applying a constant tensile force of 300 N as she walks northward along the  $Y$  axis. Parameters for the system are  $m = 500$  kg,  $\kappa_G = 600$  mm,  $H = 1.5$  m,  $w = 1$  m, and  $L = 10$  m. Solve the equations of motion to determine how the position coordinates of point  $C$  and the heading angle  $\theta$  vary as a function of time. How long does it take for the heading angle to be  $\theta = 89^\circ$ ?

## Homework Problems

551


surfaces it is in contact with is  $\mu$ . The system is released from rest at  $\theta = 90^\circ$ , and the value of  $\mu$  is not adequate to prevent sliding. Derive Lagrange's equations of motion.

**EXERCISE 8.27** The bar is supported by a ball-and-socket joint  $A$ . The coefficient of sliding friction between end  $B$  of the bar and the wall is  $\mu$ . Use Lagrange's equations to derive the equation of motion governing the angle of inclination  $\theta$ .



Exercise 8.27

**EXERCISE 8.28** The coefficient of sliding friction between the bar and corner  $A$  is  $\mu$ , but friction between end  $B$  of the bar and the vertical wall is negligible. Derive the Lagrange equations of motion for this system.



Exercise 8.28

**EXERCISE 8.29** The bar in 8.24 is released from rest at  $\theta = 75^\circ$ . The coefficient of sliding friction is 0.1, and  $(g/L)^{1/2} = 0.5$  rad/s. Determine the time required for the bar to fall to the ground, and compare that time with the case in which friction is negligible.

**EXERCISE 8.30** In Exercise 8.18 the coefficient of sliding friction between the bar and the cylinder is  $\mu$ , but friction between the collar and the vertical post is negligible. (a) Derive the differential equations of motion. (b) Consider the case in which the coefficient of friction is  $\mu = 0.1$  and  $(g/R)^{1/2} = 1.6$  rad/s. The system is released from rest at  $\theta = 20^\circ$ . Solve the Lagrange equations of motion to determine the inclination angle  $\theta$  as a function of the elapsed time  $t$ .

**EXERCISE 8.31** In Exercise 8.28 the coefficient of sliding friction between the bar and both surfaces it is in contact with is  $\mu = 0.1$ . (a) Derive the Lagrange equations of motion. (b) Consider the situation in which the bar is released from rest at  $\phi = 85^\circ$ . The dimensions are  $L = 600$  mm and  $H = 500$  mm. Determine the angle of elevation as a function of time for the interval during which it remains in contact with both surfaces. Does the bar lose contact with the wall or with the corner?

## CHAPTER 9

# Alternative Formulations

The preceding developments suffice to treat systems that are described by a finite number of degrees of freedom. They are not directly applicable if a system is best modeled as a flexible continuum, in which bodies deform and also have mass. One cannot compartmentalize kinetic and potential energy in such systems, because a mass element also stores strain energy. Consequently, concepts like generalized coordinates become problematic. The derivation of principles that can be used to model continuous media is the first priority for this chapter.

Another focus here is exploration of alternative formulations for deriving equations of motion for discrete systems. Derivation of these formulations has received considerable attention for more than a century and a half. Those efforts were motivated by a desire to seek simpler equation forms, either from the perspective of ease of implementation or ease of solution. We consider a few formulations, but extensive discussions may be found in the works by Greenwood (2003) or Papastavridis (1998, 2002).

One of the outcomes of these alternative formulations are conservation principles that sometimes can be used when the standard momentum and energy principles cannot be implemented. Such principles enable us to determine features of a system's response without solving equations of motion and also provide checks for computation solutions. Overall, the developments that follow are intended to enhance understanding of the basic concepts of analytical mechanics and to provide increased versatility to carry an analysis to completion.

### 9.1 HAMILTON'S PRINCIPLE

Lagrange's equations are restricted to systems composed of rigid bodies that have mass, and therefore store kinetic energy, whereas potential energy is stored in massless springs and other sources of conservative forces. This is an idealization, as is evident when one considers that no material can sustain stresses without deforming, and all springs have mass. Any model of a system needs to be tested by examination of the assumptions on which the model is founded. This leads to the need to consider models in which the relative position of mass points is not kinematically constrained. Each body's displacement then is a function of location within the body. This function is the *displacement field*. It represents the spatial distribution of displacement, which causes some individuals to refer to such models as *distributed parameter systems*.



## 9.1 Hamilton's Principle

553

One approach for deriving equations of motion of continua relies on the concepts in mechanics of materials. Specifically, a differential element of the system is isolated in a free-body diagram, and the internal stress distribution is described by stress-strain and strain-displacement relations. The primary difference from the static case is the usage of Newton–Euler equations of motion, rather than the laws of statics, to describe the balance of forces acting on the isolated mass element. Such an approach works well when applied to simple systems, such as a vibrating elastic bar, but it becomes cumbersome and prone to error in more complicated situations. Fortunately, there is an alternative formulation that relies on *Hamilton's Principle*, which was presented by Sir William Rowan Hamilton in 1834. From one perspective, the relationship of continuum formulations using Hamilton's Principle and mechanics of materials approaches is analogous to the relationship of Lagrange's equations and the Newton–Euler equations for discrete systems. However, the remarkable aspect of Hamilton's Principle is that it is far more general. It provides an alternative derivation of Lagrange's equations, yet, with suitable adjustments in the definition of energy, it can be applied to relativistic systems. It also provides the basis for many approximation techniques, including finite element analysis, that are used to derive discrete models of continua.

### 9.1.1 Derivation

The steps leading to Hamilton's Principle parallel the derivation of Lagrange's equations in Chapter 7, with the important difference that generalized coordinates are not used to describe position. We begin with a single particle. The principle of dynamic virtual work states that

$$(\Sigma \bar{F} - m\bar{a}) \cdot \delta \bar{r} = 0. \quad (9.1.1)$$

The virtual work done by the actual forces is  $\delta W$ , so we have

$$\delta W - m\bar{a} \cdot \delta \bar{r} = 0. \quad (9.1.2)$$

The explicit occurrence of the acceleration may be removed by introducing the rule for differentiating a product, which leads to

$$\delta W - \frac{d}{dt} (m\bar{v} \cdot \delta \bar{r}) + m\bar{v} \cdot \frac{d}{dt} (\delta \bar{r}) = 0. \quad (9.1.3)$$

Interchanging the virtual increment and the time derivative in the last term enables us to rewrite the preceding as

$$\delta W - \frac{d}{dt} (m\bar{v} \cdot \delta \bar{r}) + m\bar{v} \cdot \delta \bar{v} = 0. \quad (9.1.4)$$

Aside from holding  $t$  constant, the rules for a virtual increment are like those for a differential, so that

$$m\bar{v} \cdot \delta \bar{v} = \delta \left( \frac{1}{2} m\bar{v} \cdot \bar{v} \right) \equiv \delta T, \quad (9.1.5)$$

where  $T$  is the kinetic energy of the particle. It follows that

$$\delta T + \delta W - \frac{d}{dt} (m\bar{v} \cdot \delta \bar{r}) = 0. \quad (9.1.6)$$

We now extend this relation to treat any system. All systems are composed of a collection of particles,\* and Eq. (9.1.6) is descriptive of any particle. Let index  $n$  denote which particle it represents. Because the preceding is a scalar equation, each term becomes a simple sum when we add the equations for all particles. This leads to redefinition of  $T$  as the kinetic energy of all particles in the system and  $\delta W$  as the virtual work done by all forces. The latter was decomposed in Eq. (7.4.34), which means that the virtual work done by the conservative forces is the negative of the virtual change in the potential energy. The symbol  $\delta W$  shall henceforth represent the virtual work done by all forces that have not been described by a potential-energy function. In that case, addition of Eq. (9.1.6) for each particle in the system yields

$$\delta T - \delta V + \delta W - \sum_n \frac{d}{dt} (m_n \bar{v}_n \cdot \delta \bar{r}_n) = 0. \quad (9.1.7)$$

The first two quantities are the increments of the kinetic and potential energies if the system were to follow the variational path, rather than the true one associated with the actual forces. The third is the virtual work done by those forces. Each quantity is evaluated for points on the true and variational points corresponding to the same time instant. The fourth term has no significance relative to the standard kinetics principles, although we recognize  $m_n \bar{v}_n$  as a particle's momentum. To handle this term, we observe that it is differentiated with respect to time. Integrating Eq. (9.1.7) over time enables us to consider this problematic term solely at the limits of the integration. These limits are the initial time  $t_0$  at which we have initial conditions and an arbitrary subsequent time  $t_1$ . Thus we have


$$\int_{t_0}^{t_1} (\delta T - \delta V + \delta W) dt - \sum_n (m_n \bar{v}_n \cdot \delta \bar{r}_n) \Big|_{t=t_0}^{t=t_1} = 0. \quad (9.1.8)$$

This relation is best understood by considering the motion of the system through the configuration space. We consider generalized coordinates for the system to be the set of position coordinates for all particles contained in that system. Then the configuration space for a system of  $N$  particles is the  $3N$ -dimensional Cartesian space whose coordinates are the set of position coordinates. (Letting the dimensionality be infinite for a continuous distribution of mass does not lessen the validity of the discussion.) Figure 9.1 shows the true path and a variational path. Recall that the concept of a variational path is that it represents a different evolution of a system's state, corresponding to a set of forces that is altered from the true one. However, regardless of what forces are applied, the system must start from the specified initial state, which we take to occur at  $t_0$ . In addition, we wish to arrive at the true state of the system at the instant corresponding

\* The rigid-body and continuum models are mathematical abstractions, which are included in the discussion by considering the particles to be differential elements of mass. A summation accounting for each particle then becomes an integration over the domain.

## 9.1 Hamilton's Principle

555



**Figure 9.1.** Actual and variational paths in the configuration space starting from a specified initial position and arriving at the same ultimate state.

to the end of the variational path. Thus the true and variational paths should intersect at both instants, as shown in Fig. 9.1, so that  $\delta \hat{r} = \hat{0}$  at  $t_0$  and  $t_1$ . Correspondingly, we set  $\delta \hat{r}_n = \hat{0}$  at these instants. Under these conditions, Eq. (9.1.8) reduces to *Hamilton's Principle*:

$$\int_{t_0}^{t_1} (\delta T - \delta V + \delta W) dt = 0. \quad (9.1.9)$$

According to this relation the true path is distinguishable from all possible variational paths by the fact that the time dependence of the generalized coordinates and forces yields a zero mean value for  $\delta T - \delta V + \delta W$ . Introducing the Lagrangian  $\mathcal{L} = T - V$  gives a more compact form of Hamilton's Principle:

$$\int_{t_0}^{t_1} (\delta \mathcal{L} + \delta W) dt = 0. \quad (9.1.10)$$

Note that  $\delta T$  and  $\delta V$  represent the difference between quantities associated with the variational and true paths at an arbitrary instant. In contrast, there is no "work" quantity  $W$  from which the virtual work of a nonconservative force may be derived. Suppose we consider the restricted class of systems for which  $\delta W = 0$ . Clearly, this can be the case only if a system is conservative, but it also is necessary that the system be holonomic. Otherwise, the constraint forces will do work when the generalized coordinates are given arbitrary virtual increments. In this special case of a conservative holonomic system, we find that, among all variational paths connecting the initial and final position, the true one is the one for which the *action integral*  $\mathcal{I}$  has a stationary value, which is stated as

$$\mathcal{I} = \int_{t_0}^{t_1} (T - V) dt, \quad \delta \mathcal{I} = 0. \quad (9.1.11)$$

In other words, the motion of a conservative holonomic system evolves in a manner that gives a stationary value of the action integral (maximum, minimum, or inflection point).

It is logical at this juncture to question the significance of these results, as Hamilton's Principle seems to represent only one relation. For example, we know that the work-energy principle  $\Delta T + \Delta V = W_{1 \rightarrow 2}$  is not adequate by itself to solve problems involving several generalized coordinates. The difference is that Eq. (9.1.9) leads to many relations, because the virtual movement is arbitrary except at the initial and final instants. An infinite number of variational curves can be constructed, and Hamilton's Principle must be satisfied for each. If the system consists of particles and rigid bodies, we can construct different variational paths by holding all generalized coordinates except one

constant, and imparting a virtual increment to the remaining generalized coordinate that is arbitrary, other than being zero at instants  $t_0$  and  $t_1$ .

Hamilton's Principle can be used in a variety of ways. One application is based on the recognition that the various kinetics principles that have been formulated in this text rely on a set of axioms, specifically Newton's Laws. We could instead take Hamilton's Principle to be the fundamental axiom on which other principles are founded. Indeed, as we will soon see, Lagrange's equations are readily derived from Hamilton's Principle. If one is merely concerned with classical mechanics, this capability might seem to be unimportant. However, generalizing the definition of kinetic energy to include relativistic effects would enable us to greatly expand the scope of our investigations.

In the present context Hamilton's Principle was introduced to derive equations of motion for continua. The mathematical tool by which those equations can be obtained is the calculus of variations. This entails treating the displacement of each particle in the system as a function of its starting position  $\bar{r}$  and time, denoted as  $\bar{u}(\bar{r}, t)$ . The concept is to evaluate the increment of the kinetic and potential energies associated with a virtual increment of the displacement field  $\delta\bar{u}$ , and then use the calculus to replace dependences on derivatives of  $\delta\bar{u}$  with explicit dependence on  $\delta\bar{u}$ . Arbitrariness of the virtual displacement field will lead to the governing equations. This application is addressed in Subsection 9.1.2.

Hamilton's Principle can also be used as the foundation for approximate solutions of the response of continuous media. The notion here is to introduce a simplified representation of the displacement field, for example, a series expansion. This leads to energy expressions corresponding to the coefficients of this series. Satisfaction of Hamilton's Principle yields the best possible equations governing these coefficients. This is the essence of the Ritz series method, which is introduced in a subsequent section.

To illustrate the use of Hamilton's Principle, let us use it to derive Lagrange's equations. Independently of the previous derivation, it is a simple matter to identify that, if position is uniquely defined by a set of generalized coordinates  $q_j$ , then the kinetic energy is a function of the  $q_j$ ,  $\dot{q}_j$ , and  $t$ , whereas the potential energy is a function of the  $q_j$  and  $t$ , that is,  $T(q_j, \dot{q}_j, t)$  and  $V(q_j, t)$ . The definitions of  $\delta T$  and  $\delta V$  are that they are the change of the respective values when the generalized coordinates and velocities are given infinitesimal increments at a specified instant, so we have

$$\begin{aligned}\delta T &= T(q_j + \delta q_j, \dot{q}_j + \delta \dot{q}_j, t) - T(q_j, \dot{q}_j, t), \\ \delta V &= V(q_j + \delta q_j, t) - V(q_j, t).\end{aligned}\tag{9.1.12}$$

Because the  $\delta q_j$  and  $\delta \dot{q}_j$  values are infinitesimal, we may use the rules of differential calculus, specifically, the chain rule for differentiation, to describe the difference. This leads to

$$\delta T = \sum_{j=1}^N \left( \frac{\partial T}{\partial \dot{q}_j} \delta \dot{q}_j + \frac{\partial T}{\partial q_j} \delta q_j \right), \quad \delta V = \sum_{j=1}^N \frac{\partial V}{\partial q_j} \delta q_j.\tag{9.1.13}$$

To apply Hamilton's Principle we consider the  $\delta q_j$  values to be a selected set of time functions, because we need to apply the variation at every instant of time along the

## 9.1 Hamilton's Principle

557

configuration path. The values of the  $\delta \dot{q}_j$  are defined by the choice for the  $\delta q_j(t)$  functions, because

$$\delta \dot{q}_j \equiv \frac{d}{dt} \delta q_j. \quad (9.1.14)$$

Accordingly, we account for this dependence by manipulating the first term in Eq. (9.1.13):

$$\frac{\partial T}{\partial \dot{q}_j} \delta \dot{q}_j = \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \delta q_j \right) - \left[ \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \right) \right] \delta q_j. \quad (9.1.15)$$

The next step is to substitute into Hamilton's Principle this expression, Eq. (9.1.13) for  $\delta V$ , and the standard description of  $\delta W$  in terms of generalized forces. The result is

$$\int_{t_0}^{t_1} \sum_{j=1}^N \left\{ \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \delta q_j \right) + \left[ -\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \right) + \frac{\partial T}{\partial q_j} - \frac{\partial V}{\partial q_j} \delta q_j + Q_j \right] \delta q_j \right\} dt = 0. \quad (9.1.16)$$

The first term in the integrand is a perfect differential; its integration yields

$$\int_{t_0}^{t_1} \sum_{j=1}^N \frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \delta q_j \right) dt = \sum_{j=1}^N \left( \frac{\partial T}{\partial \dot{q}_j} \delta q_j \right) \Big|_{t_0}^{t_1}. \quad (9.1.17)$$

In the derivation of Hamilton's principle we asserted that the variational path must originate and end at the true points in the configuration space. This means that  $\delta \hat{r} = \hat{0}$  at  $t_0$  and  $t_1$ , so it must be that all of the  $\delta q_j = 0$  at those instants. Consequently, the preceding term vanishes, which reduces Eq. (9.1.16) to

$$\int_{t_0}^{t_1} \left\{ \sum_{j=1}^N \left[ -\frac{d}{dt} \left( \frac{\partial T}{\partial \dot{q}_j} \right) + \frac{\partial T}{\partial q_j} - \frac{\partial V}{\partial q_j} \delta q_j + Q_j \right] \delta q_j \right\} dt = 0. \quad (9.1.18)$$

Hamilton's Principle must apply for any variational path, which means that the  $\delta q_j$  may be arbitrary time functions, subject only to the condition that  $\delta q_j(t_0) = \delta q_j(t_1) = 0$ . For a specific set of  $\delta q_j$  functions, the integral could vanish by merely having the negative values over portions of the time interval cancel the positive values over the remaining time portions. However, the same result must be obtained for any set of  $\delta q_j$  functions, whose value at any instant may be positive or negative. This leads to the *fundamental lemma of the calculus of variations*:

If an integral over any dependent variable  $\xi$  is such that  $\mathcal{I} = \int f(\xi) g(\xi) d\xi$ , and  $\mathcal{I}$  must be zero for arbitrary  $g(\xi)$ , then it must be that  $f(\xi) = 0$ .

Application of this reasoning to Eq. (9.1.18) leads to the conclusion that the factor of  $\delta q_j$  must be zero for each value of  $j$ , which is the same relation as the basic form of Lagrange's equations.

### 9.1.2 Calculus of Variations

The motion of continua is characterized by displacements that are functions of the initial position of the moving point, as well as  $t$ . One advantage of using the calculus of variations to derive field equations is that it will definitively identify what boundary conditions are appropriate. Furthermore, although the procedure is more intricate in its mathematical steps, it requires less physical insight. This expedites the derivation of field equations for complicated continuum models. The calculus of variations is a mathematical procedure that exists independently of Hamilton's Principle. It can be applied to a variety of other areas. For example, one can use it address a number of problems in geometry, such as the identification of a geodesic curve, which is the shortest path connecting two points on a specified curved surface. Weinstock (1974) offers a fundamental treatise on this important concept.

In the most general situation, the displacement of any continuum is defined by a vector function of position and time. For simplicity, we restrict the development to situations in which the displacement of any point may be described in terms of a scalar function  $u(x, t)$ , where  $x$  is a spatial coordinate spanning  $0 \leq x \leq L$ . Many systems of engineering significance fit this specification, including vibrating cables and beams. In a continuum model, particles are replaced with differential mass elements, so the energy expressions will consist of integrals over all mass elements. To understand how the calculus of variations is implemented, we must recognize that the kinetic energy will depend on the time derivative of the displacement, and the potential energy will depend on the material strain, which in turn depends on spatial gradients of displacement. Thus let us consider the Lagrangian  $\mathcal{L}$ , which is the primary part of the integrand in Hamilton's principle, to depend on  $\dot{u}$ ,  $u'$ ,  $u''$ , and  $\dot{u}'$ , where an overdot and prime respectively denote temporal and spatial partial differentiation. (This dependence is sufficiently general to enable us to identify the appropriate manner in which to proceed if higher derivatives of  $u$  or several displacement components appear in  $\mathcal{L}$ .) A convenient notation is to use brackets to indicate the dependent variables that appear in the integrand of  $\mathcal{L}$ , so we are considering  $\mathcal{L} [\dot{u}, u', u'', \dot{u}']$ . Mathematically, the use of square brackets is intended to convey the fact that  $\mathcal{L}$  is a functional of the bracketed variables, meaning that a variety of operations must be performed on these variables in order to obtain  $\mathcal{L}$ .

The virtual displacement we impart is a differential increment  $\delta u(x, t)$  to the actual displacement. It is important to recognize that this quantity is an arbitrary function we select, subject to some restrictions that will evolve in the course of the development. Selection of a specified  $\delta u(x, t)$  in turn sets the derivatives of  $\delta u$ . Furthermore, the outcome is the same regardless of whether one increments  $u$  and then differentiates it, or takes the virtual increment of the derivative, so that

$$\delta \dot{u} = \frac{\partial}{\partial t} \delta u, \quad \delta u' = \frac{\partial}{\partial x} \delta u. \quad (9.1.19)$$

The definition of  $\delta \mathcal{L}$  is that it is the difference in the value of the integral when its integrand is formed with  $u + \delta u$ , rather than  $u$ . Thus,

$$\delta \mathcal{L} = \mathcal{L} [\dot{u} + \delta \dot{u}, u + \delta u, u'' + \delta u'', \dot{u}' + \delta \dot{u}'] - \mathcal{L} [\dot{u}, u', u'', \dot{u}']. \quad (9.1.20)$$

## 9.1 Hamilton's Principle

559

Let  $g(\dot{u}, u', u'', \dot{u}')$  denote the integrand of  $\mathcal{L}$ , so that

$$\delta\mathcal{L} = \int_0^L [g(\dot{u} + \delta\dot{u}, u + \delta u, u'' + \delta u'', \dot{u}' + \delta\dot{u}') - g(\dot{u}, u', u'', \dot{u}')] dx. \quad (9.1.21)$$

Because  $u$  and its derivatives are infinitesimal, a Taylor series expansion of the first integrand may be truncated at first-order terms. Examination of the expression that results shows that it is the same as what one would obtain if  $\delta$  were considered to be a differential operator that is applied to the integrand. We call this the *variational derivative*, the result of which is written as

$$\delta\mathcal{L} = \int_0^L \left[ \left( \frac{\partial g}{\partial (\dot{u})} \right) \delta\dot{u} + \left( \frac{\partial g}{\partial (u')} \right) \delta u' + \left( \frac{\partial g}{\partial (u'')} \right) \delta u'' + \left( \frac{\partial g}{\partial (\dot{u}')} \right) \delta\dot{u}' \right] dx. \quad (9.1.22)$$

Note that if the integrand contains other derivatives of  $u$ , the variational derivative would account for increments of  $g$  corresponding to each derivative.

The form of  $\delta\mathcal{L}$  in Eq. (9.1.22) does not recognize that  $\delta u$  represents a function that we have selected, so that derivatives of  $\delta u$  are known in terms of  $\delta u$ . Integration by parts enables us to account for such relationships. Spatial derivatives of  $\delta u$  are handled by integrating over  $x$ , whereas time derivatives require an integration of  $\delta\mathcal{L}$  over time. Thus we form

$$\begin{aligned} \int_{t_0}^{t_1} \delta\mathcal{L} dt &= \int_{t_0}^{t_1} \int_0^L \left[ \left( \frac{\partial g}{\partial (\dot{u})} \right) \delta\dot{u} + \left( \frac{\partial g}{\partial (u')} \right) \delta u' + \left( \frac{\partial g}{\partial (u'')} \right) \delta u'' + \left( \frac{\partial g}{\partial (\dot{u}')} \right) \delta\dot{u}' \right] dx dt \\ &= \int_0^L \left( \frac{\partial g}{\partial (\dot{u})} \right) \delta u dx \Big|_{t=t_0}^{t=t_1} - \int_{t_0}^{t_1} \int_0^L \left[ \frac{\partial}{\partial t} \left( \frac{\partial g}{\partial (\dot{u})} \right) \right] \delta u dx dt \\ &\quad + \int_{t_0}^{t_1} \left( \frac{\partial g}{\partial (u')} \right) \delta u dt \Big|_{x=0}^{x=L} - \int_{t_0}^{t_1} \int_0^L \left[ \frac{\partial}{\partial x} \left( \frac{\partial g}{\partial (u')} \right) \right] \delta u dx dt \\ &\quad + \int_{t_0}^{t_1} \left( \frac{\partial g}{\partial (u'')} \right) \delta u' dt \Big|_{x=0}^{x=L} - \int_{t_0}^{t_1} \int_0^L \left[ \frac{\partial}{\partial x} \left( \frac{\partial g}{\partial (u'')} \right) \right] \delta u' dx dt \\ &\quad + \int_0^L \left( \frac{\partial g}{\partial (\dot{u}')} \right) \delta u' dx \Big|_{t=t_0}^{t=t_1} - \int_{t_0}^{t_1} \int_0^L \left[ \frac{\partial}{\partial t} \left( \frac{\partial g}{\partial (\dot{u}')} \right) \right] \delta u' dx dt. \end{aligned} \quad (9.1.23)$$

The last three integral terms still contain  $\delta u' dx$ , which gives  $\delta u$  when integrated. Thus we apply an integration by parts over  $x$  to these terms, with the result that

$$\begin{aligned} \int_{t_0}^{t_1} \delta\mathcal{L} dt &= \int_{t_0}^{t_1} \int_0^L \left[ \frac{\partial^2}{\partial x^2} \left( \frac{\partial g}{\partial (u'')} \right) + \frac{\partial^2}{\partial x \partial t} \left( \frac{\partial g}{\partial (\dot{u}')} \right) - \frac{\partial}{\partial t} \left( \frac{\partial g}{\partial (\dot{u})} \right) \right. \\ &\quad \left. - \frac{\partial}{\partial x} \left( \frac{\partial g}{\partial (u')} \right) \right] \delta u dx dt + \int_0^L \left[ \left( \frac{\partial g}{\partial (\dot{u})} \right) - \frac{\partial}{\partial x} \left( \frac{\partial g}{\partial (u')} \right) \right] \delta u dx \Big|_{t=t_0}^{t=t_1} \\ &\quad + \int_{t_0}^{t_1} \left[ \frac{\partial g}{\partial (u')} - \frac{\partial}{\partial t} \left( \frac{\partial g}{\partial (\dot{u}')} \right) - \frac{\partial}{\partial x} \left( \frac{\partial g}{\partial (u'')} \right) \right] \delta u \Big|_{x=0}^{x=L} dt \\ &\quad + \int_{t_0}^{t_1} \left( \frac{\partial g}{\partial (u'')} \right) \delta u' \Big|_{x=0}^{x=L} dt + \left( \frac{\partial g}{\partial (\dot{u}')} \right) \delta u \Big|_{x=0}^{x=L} \Big|_{t=t_0}^{t=t_1}. \end{aligned} \quad (9.1.24)$$

In addition to a description of  $\delta\mathcal{L}$ , Hamilton's Principle requires specification of the virtual work. For this we consider the external force system to consist of a distributed force  $f(x, t)$  (units of force per unit length) acting in the same sense as that of the displacement. Thus, if  $u$  is a displacement in a certain direction, then  $f$  acts in that direction. Similarly, if  $u$  is a torsional rotation, then  $f$  is distributed torsional loading. The force resultant acting on a differential segment  $dx$  is  $f dx$ , and  $\delta u$  is the virtual displacement. Hence the virtual work is

$$\delta W = \int_0^L f \delta u dx. \quad (9.1.25)$$

The result of adding Eqs. (9.1.24) and (9.1.25) to form Hamilton's Principle, as prescribed by Eq. (9.1.10), is called the *variational equation*. It is obvious that it contains a variety of terms, all of which must sum to zero. However, the function  $\delta u$  associated with the variation is selected arbitrarily, which means that the fundamental lemma of the calculus of variations applies. We begin by applying this theorem to the terms in the variational derivative that are integrated over both  $x$  and  $t$ , which must be zero. If we knew the actual response function  $u(x, t)$  associated with the distributed force  $f(x, t)$ , we certainly could find a function  $\delta u$  that would cause this double integral to vanish. However, a different  $f(x, t)$  would lead to a different  $u(x, t)$ , yet the integral must still vanish in that circumstance. In order that Hamilton's principle be satisfied for any set of applied forces, it must be that the factor of  $\delta u$  in the integrand vanishes, so we have

$$\frac{\partial^2}{\partial x^2} \left( \frac{\partial g}{\partial (u'')} \right) + \frac{\partial^2}{\partial x \partial t} \left( \frac{\partial g}{\partial (\dot{u}')} \right) - \frac{\partial}{\partial t} \left( \frac{\partial g}{\partial (\ddot{u})} \right) - \frac{\partial}{\partial x} \left( \frac{\partial g}{\partial (u')} \right) = 0. \quad (9.1.26)$$

This is the *Euler-Lagrange equation*. When we form it for the function  $g(\dot{u}, u', u'', \ddot{u})$  appropriate to the system of interest, we obtain the partial differential equation governing the displacement field.

When the Euler-Lagrange equation is satisfied, the terms remaining in the variational derivative are those that are evaluated at  $x = 0$  and  $x = L$ , and/or  $t = t_0$  and  $t = t_1$ . Recall that the latter correspond to the beginning and end points of the path through the configuration space of each particle in the system. The fact that there are an infinite number of such points, so that the configuration space has infinite dimension, does not alter the requirement that a variational path should begin and end at the true state of the system, so that  $\delta u = 0$  at  $t = t_0$  and  $t = t_1$  for every  $x$ . This condition causes all terms evaluated at the time limits to be zero, so the terms that remain in the variational derivative are

$$\begin{aligned} \int_{t_0}^{t_1} \delta \mathcal{L} dt = \int_{t_0}^{t_1} \left[ \frac{\partial g}{\partial (u')} - \frac{\partial}{\partial t} \left( \frac{\partial g}{\partial (\dot{u}')} \right) - \frac{\partial}{\partial x} \left( \frac{\partial g}{\partial (u'')} \right) \right] \delta u \Big|_{x=0}^{x=L} dt \\ + \int_{t_0}^{t_1} \left( \frac{\partial g}{\partial (u'')} \right) \delta u' \Big|_{x=0}^{x=L} dt. \end{aligned} \quad (9.1.27)$$

The arbitrariness of  $\delta u$  allows us to consider the value of  $\delta u'$  at  $x = 0$  or  $x = L$  to be a separately selectable parameter, independent of the value of  $\delta u$  at these locations. Thus



## 9.1 Hamilton's Principle

563

Potential energy is stored as a result of stretching the cable. The stipulation that the cable tension  $F$  is very high in the initial state means that there is a substantial strain within the cable, even if  $w = 0$ . Because  $w$  is assumed to be small, the additional strain associated with  $w$  will also be small relative to the initial strain. It follows that it is reasonable to assume that  $F$  remains constant when  $w$  is nonzero. Thus the work done by  $F$ , which is stored as potential energy, is the product of  $F$  and the amount  $\Delta\ell$  by which the cable length is increased from the undeformed to deflected conditions. By the Pythagorean theorem, the differential arc length is

$$d\ell = \left[ (dX)^2 + (w'dX)^2 \right]^{1/2}.$$

Integrating the preceding equation to obtain the deflected arc length  $\ell$  and then subtracting the original length  $L$  yields  $\Delta\ell$ . To  $F\Delta\ell$  we add the potential energy of gravity. Let the  $X$  axis be the datum, so that  $w$  is the elevation of segment  $d\ell$ , whose weight is  $\mu d\ell$ . Hence the potential-energy functional is

$$V = F \left[ \int_0^L \left( 1 + (w')^2 \right)^{1/2} dX - L \right] + \int_0^L w \mu g dX.$$

The virtual work  $\delta W$  is zero because all forces doing work when  $w$  is incremented have been included in the potential energy.

Rather than merely forming Eqs. (9.1.26) and (9.1.28), let us explicitly perform the basic operations on the present functionals. We begin with the kinetic-energy term in Hamilton's Principle:

$$\begin{aligned} \int_{t_0}^{t_1} \delta T dt &= \int_{t_0}^{t_1} \delta \left\{ \frac{1}{2} \mu \int_0^L \left[ \dot{w}^2 + 2vw'\dot{w} + v^2(w')^2 \right] dX + \frac{1}{2} m L v^2 \right\} dt \\ &= \int_{t_0}^{t_1} \mu \int_0^L \left[ \dot{w} \delta(\dot{w}) + v \dot{w} \delta w' + v w' \delta \dot{w} + v^2 w' \delta w' \right] dX dt. \end{aligned}$$

Note how the variational derivative is implemented as a differential operator applied to all terms containing  $w$ . We interchange the virtual increments and derivatives of  $w$  in accord with Eqs. (9.1.19). Terms containing time derivatives of  $\delta w$  are integrated by parts with respect to  $t$ , whereas terms containing spatial derivatives of  $\delta w$  are integrated by parts with respect to  $x$ . These operations replace terms containing derivatives of  $\delta w$  with equivalent representations in terms of  $\delta w$ :

$$\begin{aligned} \int_{t_0}^{t_1} \delta T dt &= \mu \int_0^L \left[ (\dot{w} + v w') \delta w \right] \Big|_{t=t_0}^{t=t_1} + \int_{t_0}^{t_1} \mu \left\{ [v \dot{w} + v^2 w'] \delta w \Big|_{x=0}^{x=L} \right\} dt \\ &\quad - \int_{t_0}^{t_1} \mu \int_0^L (\ddot{w} + 2v \dot{w}' + v^2 w'') \delta w dX dt. \end{aligned}$$

It is interesting to observe that the slope  $w'$  is essentially the rotation of the tangent line because of the smallness of the displacement. Consequently, the middle term in the integrand is the product of the angular velocity of the segment  $d\ell$  and the

translational speed  $v$ . The two factor confirms that this term represents the effects of Coriolis acceleration.

Similar operations are followed to express the contribution of the strain-energy term to Hamilton's Principle. Thus,

$$\begin{aligned}\int_{t_0}^{t_1} \delta V dt &= \int_{t_0}^{t_1} \delta \left\{ F \left[ \int_0^L (1 + (w')^2)^{1/2} dX - L \right] + \int_0^L w \mu g dX \right\} dt \\ &= \int_{t_0}^{t_1} \left\{ F \int_0^L \left( \frac{1}{2} \right) (1 + (w')^2)^{-1/2} (2w' \delta w') dX + \int_0^L \mu g \delta w dX \right\} dt \\ &= \int_{t_0}^{t_1} \left\{ F \left( \frac{w'}{(1 + (w')^2)^{1/2}} \right) \delta w \right\}_{X=0}^{X=L} dt \\ &\quad - \int_{t_0}^{t_1} \int_0^L \left[ F \frac{\partial}{\partial X} \left( \frac{w'}{(1 + (w')^2)^{1/2}} \right) - \mu g \right] \delta w dX dt.\end{aligned}$$

The variational equation is the difference of the preceding equations. The variational path is such that  $\delta w = 0$  at  $t = t_0$  and  $t = t_1$ , so

$$\begin{aligned}\int_{t_0}^{t_1} \delta T dt - \int_{t_0}^{t_1} \delta V dt &= \int_{t_0}^{t_1} \left\{ \left[ \mu [v \dot{w} + v^2 w'] - F \left( \frac{w'}{(1 + (w')^2)^{1/2}} \right) \right] \delta w \right\}_{x=0}^{x=L} dt \\ &\quad - \int_{t_0}^{t_1} \int_0^L \left\{ [\mu (\ddot{w} + 2v \dot{w}' + v^2 w'')] - F \frac{\partial}{\partial X} \left( \frac{w'}{(1 + (w')^2)^{1/2}} \right) \right. \\ &\quad \left. - \mu g \right\} \delta w dX dt = 0.\end{aligned}$$

We obtain the Euler-Lagrange equation by equating to zero the coefficient of  $\delta w$  in the integrand of the double integral over  $X$  and  $t$ :

$$F \frac{\partial}{\partial X} \left( \frac{w'}{(1 + (w')^2)^{1/2}} \right) - \mu (\ddot{w} + 2v \dot{w}' + v^2 w'') = -\mu g. \quad \triangleleft$$

When the Euler-Lagrange equation is satisfied, the remaining terms in the variational derivative are

$$\int_{t_0}^{t_1} \left\{ \left[ \mu (v \dot{w} + v^2 w') - F \left( \frac{w'}{(1 + (w')^2)^{1/2}} \right) \right] \delta w \right\}_{x=0}^{x=L} dt = 0.$$

Satisfaction of this condition requires that the integrand evaluated at each end be zero, because the value of  $\delta w$  at  $x = L$  is independent of its value at  $x = 0$ . Thus we

## 9.1 Hamilton's Principle

565

find that one boundary condition must be satisfied at each end. This boundary condition is an alternative between the geometric condition, which requires that  $\delta w = 0$  at an end, and the natural condition we obtain by equating to zero the coefficient of  $\delta w$  at that end. The latter is a condition on the vertical component of the tensile force, which does not apply to the system under condition. The rollers prevent the ends from displacing, so we set

$$w(0, t) = w(L, t) = 0. \quad \triangleleft$$

The Euler–Lagrange equation is a nonlinear partial differential equation. We may simplify it by considering  $|w'| \ll 1$ , which should be valid because  $|w|$  at all locations is small compared with  $L$ .<sup>†</sup> When we use this to simplify the denominator of the  $X$  derivative term, we obtain

$$Fw'' - \mu(\ddot{w} + 2v\dot{w}' + v^2w'') = -g.$$

An interesting aspect of this differential equation is that is not amenable to direct solution by the standard method of separation of variables. The solution of this equation and an exploration of numerous interesting phenomena may be found in the work of Wickert and Mote (1990), and many others after that.

### 9.1.3 Ritz Series Method

The Euler–Lagrange equation that is obtained from Hamilton's Principle can be quite challenging to solve. For that reason approximate analysis techniques are required. One approach begins by assuming that the displacement field can be represented as a series having a finite number of terms. Walther Ritz (1878–1909) proposed the use of a specific form of such a series, in which each term is a product of a selected function of position and a time function whose dependence is to be determined. The spatial functions are referred to as *basis functions*. The general form of a *Ritz series* for the vectorial displacement of an arbitrary continuous system therefore has the form

$$\bar{u}(\bar{r}) = \sum_{n=1}^N \bar{\psi}_n(\bar{r}) q_n(t). \quad (9.1.29)$$

The basis functions are  $\bar{\psi}_n(\bar{r})$ . They are indicated to be vectors because, in the most general situation,  $\bar{u}$  might have independently variable components. It will be noted that the symbol  $q_n$  is used to denote the time functions. This is done to emphasize that, as a consequence of selecting the basis functions as a first step in formulating the analysis, the sole variables required to evaluate the displacement  $\bar{u}$  are the  $q_n(t)$  variables, so they are effectively generalized coordinates.

<sup>†</sup> As the frequency of vibration increases, the length scale over which  $w$  changes might become significantly smaller than the span  $L$ . The consequence is that the approximation of small  $|\partial w / \partial x|$  loses validity.

A Ritz series may be considered to be a generalization of a Fourier series. [In fact, some texts have referred to Eq. (9.1.29) as “generalized Fourier series.”] To understand why, suppose a displacement field is a function of a single spatial coordinate and that it is periodic in a distance  $L$  measured along that coordinate direction. Any periodic function may be expanded in a Fourier series, so the displacement in this scenario may be expressed as

$$\bar{u}(x) = C_0 + \sum_{n=1}^N \left[ C_n \cos\left(\frac{2n\pi x}{L}\right) + S_n \sin\left(\frac{2n\pi x}{L}\right) \right]. \quad (9.1.30)$$

If we consider the coefficients  $C_n$  and  $S_n$  to be time dependent, we extend the Fourier series to situations in which the displacement field has an arbitrary time dependence, while still maintaining its spatial periodicity. Thus, in this scenario, the cosine and sine functions are the basis functions of a Ritz series, and the  $C_n$  and  $S_n$  coefficients are the generalized coordinates  $q_n$ . In a linear algebra perspective, the  $\bar{\psi}_n(\bar{x})$  define favored directions in a functional space, like the unit vectors  $\bar{e}_j$  for a vector space, which is why they are said to be basis functions. The  $q_n$  values may then be considered to be the displacement components parallel to the basis functions.

The most problematic aspect of formulating a Ritz series analysis is selection of the basis functions. There are a few inviolable requirements. The first is that the functions must be linearly independent, which is equivalent to requiring that the Ritz series yield a zero value of  $\bar{u}$  at all  $\bar{r}$  only if all  $q_n$  are zero. The second requirement is that the basis functions must satisfy all *geometric boundary conditions* that pertain to the system being analyzed. (This requirement, of course, assumes that one has identified what the geometric boundary conditions are. In extraordinary circumstances, it might be necessary to apply the calculus of variations, but we usually can identify these conditions by inspection.) It is important to realize that the natural boundary conditions need not be considered when the basis functions are selected. Because they constitute conditions on force resultants at the boundary, natural boundary conditions are accounted for in the virtual work.<sup>‡</sup>

Some individuals consider the Ritz series to be a guessing procedure, in that one has no other guidelines as to how to select the basis functions. However, in many cases it is possible to identify basis functions that satisfy the geometric boundary conditions and also constitute a parameterized family of functions. For example, the sine and cosine functions in Eq. (9.1.30) are parameterized by the harmonic number  $n$ . The terms of a power series,  $(x/L)^n$ , are another parameterized set, as are the basis functions used in finite element analysis. In fact, one can consider the finite element technique for elastic systems to be a special case of a Ritz series analysis, as discussed by Ginsberg (2001). The significance of increasing the length  $N$  of the Ritz series is that doing so will bring the solution closer to what one would obtain by solving the differential equations of

<sup>‡</sup> In some situations elastic springs might be situated at the boundaries. In that case the aspects of a natural boundary condition associated with the spring force are addressed by including in the  $V$  functional the spring's potential energy.

## 9.1 Hamilton's Principle

567

motion, if such a solution were possible. It can be proven that the limit  $N \rightarrow \infty$  would yield an infinite dimensional representation that is the true response.

Once we have selected the basis functions, generation of the equations of motion for the generalized coordinates is fairly straightforward. It is assumed that prior to initiating the analysis we have derived the appropriate functionals describing how the kinetic and potential energies of the continuous system depend on the displacement. These functionals feature integrals over the spatial domain of the system. When we substitute the Ritz series into these functionals, all spatial dependencies have been set, so the integrals may be evaluated. This process converts the functionals of displacement into functions of the generalized coordinates. As before, we limit our attention here to cases in which a displacement field consists of a single component that depends on a single spatial coordinate and time,  $u(x, t)$ . Correspondingly, we take all  $\psi_n$  to be scalar functions of  $x$  and  $t$ . The mathematical statement of the operation of substituting the Ritz series is

$$\mathcal{L}[\dot{u}, u', u'', \dot{u}', t] = \mathcal{L}\left[\sum_{n=1}^N \psi_n \dot{q}_n, \sum_{n=1}^N \psi'_n q_n, \sum_{n=1}^N \psi''_n q_n, \sum_{n=1}^N \psi'_n \dot{q}_n, t\right] = \mathcal{L}(\dot{q}_n, q_n, t). \quad (9.1.31)$$

In other words, substitution of the Ritz series enables us to reduce the Lagrangian from a functional featuring spatial integration to a discrete function of the generalized coordinates and velocities. In practice, such a reduction will entail integrating a variety of terms containing the basis functions and their derivatives. These integrations may be carried out analytically or by means of computer techniques using symbolic or numerical software.

Formulation of Hamilton's Principle also requires description of the virtual work. Let  $f(x, t)$  denote the distributed force per unit length acting in the direction of the displacement  $u$ . The external force acting on an interval  $dx$  is  $f dx$ , and the virtual displacement at this location is  $\delta u(x, t)$ , so the virtual work is

$$\delta W = \int_0^L f(x, t) \delta u dx = \int_0^L f(x, t) \delta u dx. \quad (9.1.32)$$

When we form the Ritz series, Eq. (9.1.29), the basis functions have been set. Thus a virtual displacement entails imparting virtual increments solely to the series coefficients:

$$\delta u = \sum_{n=1}^N \psi_n \delta q_n. \quad (9.1.33)$$

We substitute this representation into the preceding expression for  $\delta W$  and bring the integral inside the summation. The result is a representation of  $\delta W$  that matches the standard form containing generalized forces, specifically,

$$\delta W = \sum_{n=1}^N Q_n \delta q_n, \quad Q_n = \int_0^L f(x, t) \psi_n(x) dx. \quad (9.1.34)$$

This completes the basic operations of a Ritz series analysis. The system model has been reduced to one in which the Lagrangian is a function of the generalized coordinates and generalized velocities, and the virtual work is characterized by a set of generalized forces. As we saw earlier, Hamilton's Principle for such a system reduces to Lagrange's equations. Thus the formulation of Ritz series in essence has reduced the continuous system from one having an infinite number of degrees of freedom to an approximate one described by a finite number of degrees of freedom. An important aspect of this procedure, which is often forgotten, is that consideration should be given to whether a convergent representation of the phenomena of interest results from the analysis. If one has normalized the basis functions such that they have unit order of magnitude everywhere, then it is possible to ascertain that convergence has been attained by merely examining the convergence properties of the series coefficients  $q_n$ .

**EXAMPLE 9.2** Consider the analysis of transverse displacement of a cable that translates at a constant speed, which was described in Example 9.1. Derive the equations of motion governing a set of Ritz series coefficients.

**SOLUTION** Beyond merely illustrating how to implement a Ritz series analysis, this example is intended to interest the reader in some of the more modern issues encountered in vibration research. A suitable Ritz series is readily identified. As shown in the previous example, both ends are constrained by the rollers to not displace, so the geometric boundary condition applies at each end. We therefore seek a set of basis functions that is linearly independent and has zero value at  $X = 0$  and  $X = L$ . The simplest such function is a set of sines, specifically,

$$\psi_n = \sin\left(\frac{n\pi X}{L}\right),$$

so our Ritz series for this system is

$$w(X, t) = \sum_{n=1}^N q_n(t) \sin\left(\frac{n\pi X}{L}\right).$$

We substitute this series into the kinetic-energy functional derived previously, which leads to

$$\begin{aligned} T &= \frac{1}{2}\mu \int_0^L \left[ \dot{w}^2 + 2v w' \dot{w} + v^2 (w')^2 \right] dX + \frac{1}{2}mLv^2 \\ &= \frac{1}{2}\mu \int_0^L \left\{ \left[ \sum_{j=1}^N \dot{q}_j \sin\left(\frac{j\pi X}{L}\right) \right] \left[ \sum_{n=1}^N \dot{q}_n \sin\left(\frac{n\pi X}{L}\right) \right] \right\} dX \\ &\quad + \mu v \int_0^L \left\{ \left[ \sum_{j=1}^N \left(\frac{j\pi}{L}\right) q_j \cos\left(\frac{j\pi X}{L}\right) \right] \left[ \sum_{n=1}^N \dot{q}_n \sin\left(\frac{n\pi X}{L}\right) \right] \right\} dX \end{aligned}$$

## 9.1 Hamilton's Principle

569

$$+ \frac{1}{2} \mu v^2 \int_0^L \left\{ \left[ \sum_{j=1}^N q_j \left( \frac{j\pi}{L} \right) \cos \left( \frac{j\pi X}{L} \right) \right] \left[ \sum_{n=1}^N q_n \left( \frac{n\pi}{L} \right) \cos \left( \frac{n\pi X}{L} \right) \right] \right\} dX \\ + \frac{1}{2} \mu L v^2.$$

The most important aspect of this substitution is that a different index is used to describe the summation for each factor in products of  $w$  and its derivatives. This is done to ensure that we account for each possible combination of terms. We focus on integrating over  $x$  by bringing the integration operator inside the summations. The first and third integrals simplify as a consequence of the orthogonality of the sine function, with the result that

$$T = \frac{1}{4} \mu L \sum_{j=1}^N \left[ \dot{q}_j^2 + \left( \frac{j\pi v}{L} \right)^2 q_j^2 \right] + \mu v \sum_{j=1}^N \sum_{n=1}^N B_{jn} q_j \dot{q}_n + \frac{1}{2} m L v^2,$$

where

$$B_{jn} = \begin{cases} \frac{2jn}{n^2 - j^2} & \text{if } j+n \text{ is odd} \\ 0 & \text{if } j+n \text{ is even} \end{cases}.$$

The reduction of  $V$  from a functional of  $w$  to a function of the Ritz series coefficients follows similar steps. However, the presence of the square root substantially complicates the task of integrating over  $x$ . We address this by recalling that  $|\partial w / \partial x| \ll 1$ . When this condition is valid, the square root term may be approximated by a binomial series that is truncated. Thus we write

$$V \approx F \left[ \int_0^L \left( 1 + \frac{1}{2} (w')^2 \right) dX - L \right] + \int_0^L w \mu g dX + O(w^4) \\ = \frac{1}{2} F \int_0^L (w')^2 dX + \int_0^L w \mu g dX. \quad (9.1.35)$$

Note that the series expansion of the square root term has been truncated at the lowest order possible. This level of approximation is equivalent in every respect to linearizing the Euler-Lagrange equation in Example 9.1. Substitution of the Ritz series into this functional yields

$$V = \frac{1}{2} F \int_0^L \left( \sum_{j=1}^N \left( \frac{j\pi}{L} \right) q_j \cos \left( \frac{j\pi X}{L} \right) \right) \left( \sum_{n=1}^N \left( \frac{n\pi}{L} \right) q_n \cos \left( \frac{n\pi X}{L} \right) \right)^{1/2} dX \\ + \mu g \int_0^L \sum_{n=1}^N q_n \sin \left( \frac{n\pi X}{L} \right) dX \\ = \frac{1}{4} F L \sum_{j=1}^N \left( \frac{j\pi}{L} \right)^2 q_j^2 + \mu g \sum_{n=1}^N \left( \frac{L}{n\pi} \right) [1 - (-1)^n] q_n.$$

## 9.2 Generalized Momentum Principles

571

This set of Lagrange's equations constitutes a set of coupled linear ordinary differential equations. They have an interesting feature when written in matrix form as

$$\mu L \{\ddot{q}\} - 2\mu v [G] \{\dot{q}\} + \left( \frac{F}{L} - \mu v^2 \right) [K] \{q\} = \{F\},$$

where  $[K]$  is a diagonal array whose elements are  $K_{jj} = j^2 \pi^2$ . In the study of vibratory response of structural and mechanical systems the coefficient of  $\{\ddot{q}\}$  in equations of motion is referred to as the inertia matrix, and the coefficient of  $\{q\}$  is called the stiffness matrix. In the present context, the inertia matrix is proportional to the identity matrix, and the stiffness matrix is diagonal. Fundamental vibration studies typically do not encounter terms like  $[G]$ , which is skew symmetric. This term is the Ritz series manifestation of the Coriolis acceleration encountered in the Euler-Lagrange equation derived in Example 9.1. Similar Coriolis acceleration terms are encountered in vibrating pipes with high-speed internal flows. Terms having a similar appearance also are encountered in studies of flexible rotordynamic systems, where they are associated with gyroscopic effects. The presence of Coriolis and gyroscopic effects has a profound effect on the nature of the vibratory response. The solutions of the Ritz series equations of motion were addressed by the author (Ginsberg, 2001).

## 9.2 GENERALIZED MOMENTUM PRINCIPLES

Hamilton's enunciation of the principle bearing his name is arguably his most important contribution to the dynamics of systems, but not his only one. He used Lagrange's equations to derive a set of first-order equations of motion that are quite different from the state-space formulations encountered thus far. This formulation leads to additional conservation principles that would be more difficult to derive by other approaches.

### 9.2.1 Hamilton's Equations

Hamilton's equations of motion, which govern systems that have a finite number of degrees of freedom, are founded on a relation between momentum and kinetic energy. A suggestion that there is such a relation in general comes from considering a single particle whose motion is described by its Cartesian coordinates in a fixed reference frame,  $q_1 = x$ ,  $q_2 = y$ , and  $q_3 = z$ . The momentum components are  $m\dot{x}$ ,  $m\dot{y}$ , and  $m\dot{z}$ , and the kinetic energy is  $T = \frac{1}{2}m(\dot{x}^2 + \dot{y}^2 + \dot{z}^2)$ , so we have

$$\frac{\partial T}{\partial \dot{x}} = m\dot{x}, \quad \frac{\partial T}{\partial \dot{y}} = m\dot{y}, \quad \frac{\partial T}{\partial \dot{z}} = m\dot{z}. \quad (9.2.1)$$

These simple relations between momentum and kinetic energy actually are manifestations of a more general perspective. Consider the kinetic energy of a single particle.



Differentiation of  $T$  for this particle with respect to a selected generalized velocity  $\dot{q}_n$  gives

$$\frac{\partial T}{\partial \dot{q}_n} = \frac{\partial}{\partial \dot{q}_n} \left( \frac{1}{2} m \bar{v} \cdot \bar{v} \right) = m \bar{v} \cdot \frac{\partial \bar{v}}{\partial \dot{q}_n}. \quad (9.2.2)$$

The particle's velocity is related to the generalized coordinates by

$$\bar{v}(\dot{q}_i, q_i, t) = \sum_{j=1}^N \left( \frac{\partial}{\partial \dot{q}_j} \bar{r}(q_i, t) \right) \dot{q}_j + \frac{\partial}{\partial t} \bar{r}(q_i, t). \quad (9.2.3)$$

Because  $\dot{q}_n$  represents a specific variable, it occurs within the summation only when the index  $j$  matches  $n$ , with the result that

$$\frac{\partial}{\partial \dot{q}_n} \bar{v}(\dot{q}_i, q_i, t) \equiv \frac{\partial}{\partial \dot{q}_j} \bar{r}(q_i, t), \quad (9.2.4)$$

which is an identity we first encountered in the derivation of Lagrange's equations. With this, Eq. (9.2.2) becomes

$$\frac{\partial T}{\partial \dot{q}_n} = m \bar{v} \cdot \frac{\partial \bar{r}}{\partial \dot{q}_n}. \quad (9.2.5)$$

One way of interpreting this relation is that  $\partial \bar{r} / \partial \dot{q}_n$  is a vector in the direction of increasing  $q_n$ , like the unit vectors of a curvilinear coordinate system. In this interpretation  $\partial T / \partial \dot{q}_n$  is the component of momentum in the direction of increasing  $q_n$ , which leads to its being referred to as the *generalized momentum*. The kinetic energy of any system may be decomposed into contributions of individual particles, so it follows that  $\partial T / \partial \dot{q}_n$  is the total momentum of a system in the sense of  $q_n$ . The symbol  $p_n$  is typically reserved for a generalized momenta, so we define

$$p_n = \frac{\partial T}{\partial \dot{q}_n} = \frac{\partial \mathcal{L}}{\partial \dot{q}_n}, \quad (9.2.6)$$

where the form containing the Lagrangian is a direct consequence of the fact that  $V$  cannot depend on the generalized velocities.

The essence of Hamilton's formulation is that the generalized momenta should replace the generalized velocities as the rate variables in the equations of motion. This is accompanied by the introduction of a new energylike quantity called the *Hamiltonian* and denoted by the symbol  $\mathcal{H}$ . Motivation for the definition may be found in comparing the mechanical energy  $E = T + V$  and the Lagrangian  $\mathcal{L}$  for a particle whose position is described by its Cartesian coordinates. If we express  $T$  in terms of the momentum components in this case, we have

$$E = 2T - \mathcal{L} = (m\dot{x})\dot{x} + (m\dot{y})\dot{y} + (m\dot{z})\dot{z} - \mathcal{L}. \quad (9.2.7)$$

## 9.2 Generalized Momentum Principles

573

This suggests a generalization in which the momentum components are replaced with  $p_n$  and the velocity components are replaced with  $\dot{q}_n$ . The result is the definition of  $\mathcal{H}$ :

$$\mathcal{H} = \sum_{j=1}^N p_j \dot{q}_j - \mathcal{L}. \quad (9.2.8)$$

An alternative definition of the Hamiltonian results when we recall Eqs. (7.6.4), which decomposed the kinetic energy into a term  $T_2$  representing contributions that are quadratic in the generalized velocities, a term  $T_1$  that is linear in those variables, and a term  $T_0$  that is independent of the  $\dot{q}_j$ . The result of using Eqs. (7.6.4) to form  $p_j$  is

$$\begin{aligned} p_j &= \frac{\partial}{\partial \dot{q}_j} \left[ \frac{1}{2} \sum_{k=1}^N \sum_{n=1}^N M_{kn}(q_i, t) \dot{q}_k \dot{q}_n + \sum_{k=1}^N N_k(q_i, t) \dot{q}_k + T_0(q_i, t) \right] \\ &= \sum_{k=1}^N M_{kj}(q_i, t) \dot{q}_k + N_j(q_i, t), \quad j = 1, 2, \dots, N. \end{aligned} \quad (9.2.9)$$

This expression shows that the generalized momenta are linearly related to the generalized velocities. We will soon have another use for this relation, but currently we merely substitute it into Eq. (9.2.8), which leads to

$$\begin{aligned} \mathcal{H} &= \sum_{j=1}^N \left[ \sum_{k=1}^N M_{kj}(q_i, t) \dot{q}_k + N_j(q_i, t) \right] \dot{q}_j - (T - V) \\ &= \frac{1}{2} \sum_{j=1}^N \sum_{k=1}^N M_{jk}(q_i, t) \dot{q}_k \dot{q}_j - T_0(q_i, t) + V(q_i, t) \\ &= T_2(\dot{q}_i, q_i, t) - T_0(q_i, t) + V(q_i, t). \end{aligned} \quad (9.2.10)$$

Thus, if  $T_1$  and  $T_0$  happen to be zero for a system, so that  $T_2$  is the total kinetic energy, then  $\mathcal{H}$  is indeed the mechanical energy  $E$ .

We have not yet faced the most troublesome aspect of the Hamiltonian formulation, which is removal of the generalized velocities from the dependence. With this as our objective, we return to Eq. (9.2.9), which we now view as a set of  $N$  simultaneous equations for the generalized velocities corresponding to a specified set of  $q_i$  and  $p_i$ . Recall that  $[M]$  is always invertible because the kinetic energy is positive definite. Hence it is always possible to solve Eq. (9.2.9) for the generalized velocities. The matrix form of that solution is

$$\{\dot{q}\} = [M(q_i, t)]^{-1} \{p\} - \{N(q_i, t)\}. \quad (9.2.11)$$

These constitute one part of Hamilton's equations. It is imperative to recognize that, although matrix notation is employed here, these operations must be done algebraically. Symbolic mathematical software can be quite useful for this task.

Substitution of Eq. (9.2.11) into the alternative form of  $\mathcal{H}$ , Eq. (9.2.10), eliminates the generalized velocities. The matrix form of the result is

$$\begin{aligned}\mathcal{H} &= \frac{1}{2} \{\dot{q}\}^T [M] \{\dot{q}\} - T_0(q_i, t) + V(q_i, t) \\ &= \frac{1}{2} \left\{ \{p\}^T - \{N(q_i, t)\}^T \right\} [M(q_i, t)]^{-1} \left\{ \{p\} - \{N(q_i, t)\} \right\} - T_0 + V.\end{aligned}\quad (9.2.12)$$

When we collect like terms in this expression and recognize that  $[M]$  is symmetric, so that  $\left([M]^{-1}\right)^T = [M]^{-1}$ , we obtain a definition of the Hamiltonian that contains only the  $p_n$  and  $q_n$  variables, specifically,

$$\begin{aligned}\mathcal{H} &= \frac{1}{2} \{p\}^T [M(q_i, t)]^{-1} \{p\} - \{N(q_i, t)\}^T [M(q_i, t)]^{-1} \{p\} \\ &\quad - \frac{1}{2} \{N(q_i, t)\}^T [M(q_i, t)]^{-1} \{N(q_i, t)\} - T_0(q_i, t) + V(q_i, t).\end{aligned}\quad (9.2.13)$$

Now that we know how to construct  $\mathcal{H}$ , we turn our attention to identifying a corresponding set of equations of motion. The most direct route is to return to the original definition, Eq. (9.2.8). To ascertain some identities obeyed by derivatives of  $\mathcal{H}$ , we form the total time derivative  $d\mathcal{H}/dt$  by using two perspectives. From one view  $\mathcal{H}$  is a general function of the  $p_j$ ,  $q_j$ , and  $t$ , so that

$$\frac{d\mathcal{H}}{dt} = \sum_{j=1}^N \frac{\partial \mathcal{H}}{\partial p_j} \dot{p}_j + \sum_{j=1}^N \frac{\partial \mathcal{H}}{\partial q_j} \dot{q}_j + \frac{\partial \mathcal{H}}{\partial t}.\quad (9.2.14)$$

In the other view Eq. (9.2.8) explicitly defines  $\mathcal{H}$  in terms of these variables, so differentiating that expression yields

$$\begin{aligned}\frac{d\mathcal{H}}{dt} &= \sum_{j=1}^N (\dot{p}_j \dot{q}_j + p_j \ddot{q}_j) - \left[ \sum_{j=1}^N \left( \frac{\partial \mathcal{L}}{\partial \dot{q}_j} \ddot{q}_j + \frac{\partial \mathcal{L}}{\partial q_j} \dot{q}_j \right) + \frac{\partial \mathcal{L}}{\partial t} \right] \\ &= \sum_{j=1}^N (\dot{p}_j \dot{q}_j + p_j \ddot{q}_j) - \sum_{j=1}^N \left( p_j \ddot{q}_j + \frac{\partial \mathcal{L}}{\partial q_j} \dot{q}_j \right) - \frac{\partial \mathcal{L}}{\partial t} \\ &= \sum_{j=1}^N \left( \dot{p}_j \dot{q}_j - \frac{\partial \mathcal{L}}{\partial q_j} \dot{q}_j \right) - \frac{\partial \mathcal{L}}{\partial t}.\end{aligned}\quad (9.2.15)$$

Both descriptions of the time derivative must be the same, regardless of the details of the system's response. To enforce this assertion we observe that, although  $p_j$  and  $\dot{q}_j$  are related by Eq. (9.2.9), one set of variables does not define the other because the relation depends on the current values of the generalized coordinates. Thus we may consider the  $p_j$  variables at any instant to be independent of the  $\dot{q}_j$  variables. This means that the coefficient of each  $\dot{p}_j$  in Eq. (9.2.14) must match the corresponding coefficient in Eq. (9.2.15). When this equality holds, then the remaining terms that are coefficients of the  $\dot{q}_j$  must also match, which in turn requires that the remaining partial time derivatives

## 9.2 Generalized Momentum Principles

575

also match. The result is that

$$\dot{q}_j = \frac{\partial \mathcal{H}}{\partial p_j}, \quad \frac{\partial \mathcal{L}}{\partial q_j} = -\frac{\partial \mathcal{H}}{\partial q_j}, \quad \frac{\partial \mathcal{L}}{\partial t} = -\frac{\partial \mathcal{H}}{\partial t}. \quad (9.2.16)$$

We substitute these relations and the definition of the  $p_j$  variables as derivatives  $\mathcal{L}$  into Lagrange's equations, which yields


$$\boxed{\begin{aligned} \dot{q}_j &= \frac{\partial \mathcal{H}}{\partial p_j}, \\ \dot{p}_j + \frac{\partial \mathcal{H}}{\partial q_j} &= Q_j. \end{aligned}} \quad (9.2.17)$$

These are *Hamilton's equations of motion*.

The only occurrence of generalized velocities is in the first set of equations, because the  $\dot{q}_j$  have been removed from  $\mathcal{H}$ . These equations, which describe how the generalized coordinates are influenced by the other effects, are the scalar equivalent of Eq. (9.2.11). Some individuals prefer to use that relation to obtain the  $\dot{q}_j$  variables, rather than differentiating  $\mathcal{H}$ . In any event, Hamilton's equations constitute a set of  $2N$  coupled, first-order differential equations governing the  $N$  generalized coordinates  $q_j$  and  $N$  generalized momenta  $p_j$ . If the generalized coordinates are constrained, these equations must be supplemented by the constraint equations, in which any occurrence of generalized velocity must be replaced with its relation to the generalized momenta, as described by Eq. (9.2.11). The constraint forces would then appear in the generalized forces, or alternatively, the Lagrange multiplier terms may be added to the generalized force array.

When both sets of Hamilton's equations are assembled, the result has an attractive state-space form, in that only the state vector  $\{x\} = [\{q\}^T \{p\}^T]^T$  appears on the left side. This feature might seem to make Hamilton's equations more efficient for numerical analysis because evaluation of the right side of the assembled equations gives the value of  $\{\dot{x}\}$  to be sent to a differential equation solver. In comparison, numerical solution of the Lagrange equations for a holonomic system require evaluation of the current generalized accelerations by solving  $[M]\{\ddot{q}\} = \{F\}$ ; see Section 7.6. The fact that Hamilton's equations of motion directly give the  $\{\dot{x}\}$  vector, whereas the state-space formulation of Lagrange's equations requires intermediate calculations, might seem to make Hamilton's equations more efficient for a numerical solution. However, this is an incomplete view because it fails to recognize that  $[M]$  must be inverted algebraically to form  $\mathcal{H}$  according to Eq. (9.2.13), whereas evaluation of  $\{\ddot{q}\}$  for the state-space equations can be done by generating a formal inverse of  $[M]$  or by numerically solving  $[M]\{\ddot{q}\} = \{F\}$  at each instant.

**EXAMPLE 9.3** The angles of rotation are selected as generalized coordinates for the double pendulum, whose bars have equal mass  $m$ . Derive Hamiltonian equations of motion.



Example 9.3

**SOLUTION** This system is sufficiently simple that we could skip some steps, but we will follow the formal procedures in order to get a good picture of what operations are required for formulating Hamilton's equations for a complicated system. We begin the analysis by expressing the Lagrangian in terms of the generalized coordinates and velocities. Bar  $AB$  is in pure rotation about end  $A$ , and bar  $BC$  is in general motion. We obtain the velocity of the center of mass  $G$  of bar  $BC$  by differentiating its position, which gives

$$\vec{v}_G = \left( L\dot{\theta}_1 \cos \theta_1 + \frac{L}{2}\dot{\theta}_2 \cos \theta_2 \right) \bar{i} + \left( L\dot{\theta}_1 \sin \theta_1 + \frac{L}{2}\dot{\theta}_2 \sin \theta_2 \right) \bar{j},$$

where  $\bar{i}$  is to the right and  $\bar{j}$  is upward. The kinetic energy is

$$\begin{aligned} T &= \frac{1}{2} I_1 \dot{\theta}_1^2 + \frac{1}{2} m \vec{v}_G \cdot \vec{v}_G + \frac{1}{2} I_G \dot{\theta}_2^2 \\ &= \frac{1}{2} \left( \frac{1}{3} m L^2 \right) \dot{\theta}_1^2 + \frac{1}{2} m \left[ L^2 \dot{\theta}_1^2 + \frac{L^2}{4} \dot{\theta}_2^2 \right. \\ &\quad \left. + L^2 \dot{\theta}_1 \dot{\theta}_2 (\cos \theta_1 \cos \theta_2 + \sin \theta_1 \sin \theta_2) \right] + \frac{1}{2} \left( \frac{1}{12} m L^2 \right) \dot{\theta}_2^2 \\ &= \frac{1}{2} m L^2 \left[ \frac{4}{3} \dot{\theta}_1^2 + \frac{1}{3} \dot{\theta}_2^2 + \dot{\theta}_1 \dot{\theta}_2 \cos (\theta_2 - \theta_1) \right]. \end{aligned}$$

The elevation of pin  $A$  is a convenient datum for gravitational potential energy. The corresponding Lagrangian is

$$\begin{aligned} \mathcal{L} &= \frac{1}{2} m L^2 \left[ \frac{4}{3} \dot{\theta}_1^2 + \frac{1}{3} \dot{\theta}_2^2 + \dot{\theta}_1 \dot{\theta}_2 \cos (\theta_2 - \theta_1) \right] \\ &\quad + mg \frac{L}{2} \cos \theta_1 + mg \left( L \cos \theta_1 + \frac{L}{2} \cos \theta_2 \right). \end{aligned} \quad (1)$$

The next step is to form the generalized momenta. The kinetic energy has only quadratic terms in the generalized velocities, so  $\{N\} = \{0\}$  and  $T_0 = 0$ . The easiest way to identify  $[M]$  is to form the  $p_j$  variables by differentiating  $\mathcal{L}$  and then compare the result with Eq. (9.2.9). Differentiation yields

$$\begin{aligned} p_1 &= \frac{\partial \mathcal{L}}{\partial \dot{\theta}_1} = m L^2 \left[ \frac{4}{3} \dot{\theta}_1 + \frac{1}{2} \dot{\theta}_2 \cos (\theta_2 - \theta_1) \right], \\ p_2 &= \frac{\partial \mathcal{L}}{\partial \dot{\theta}_2} = m L^2 \left[ \frac{1}{3} \dot{\theta}_2 + \frac{1}{2} \dot{\theta}_1 \cos (\theta_2 - \theta_1) \right]. \end{aligned}$$

$$\dot{p}_2 = -\frac{\partial \mathcal{H}}{\partial \theta_2} = \frac{18 \sin(\theta_2 - \theta_1)}{mL^2 \Delta^2} [(6p_1^2 + 24p_2^2) \cos(\theta_2 - \theta_1) - p_1 p_2 (16 + 9 \cos(\theta_2 - \theta_1)^2)] - \frac{1}{2} mg L \sin \theta_2.$$

Given that this system is relatively uncomplicated, it is clear that forming Hamilton's equations in more engineering-oriented systems is likely to be a tedious process, unless one uses symbolic mathematical software.

### 9.2.2 Conservation of the Hamiltonian

One of the features of Hamilton's equations that has attracted attention is that they permit canonical transformations. The result of such transformations are new variables other than generalized coordinates and momenta that nevertheless satisfy Hamilton's equations. Goldstein (1980) and Desloges (1982) give good explanations of this application. For us, the primary value of the Hamiltonian formulation lies in an associated conservation theorem. We return to Eq. (9.2.15), into which we substitute the definition of a generalized momentum, Eq. (9.2.6), in order to eliminate  $p_j$ . The altered form is

$$\frac{d\mathcal{H}}{dt} = \sum_{j=1}^N \left[ \frac{d}{dt} \left( \frac{\partial \mathcal{L}}{\partial \dot{q}_j} \right) - \frac{\partial \mathcal{L}}{\partial q_j} \right] \dot{q}_j - \frac{\partial \mathcal{L}}{\partial t}. \quad (9.2.18)$$

The term in the brackets equals the generalized force in Lagrange's equations, so we find that

$$\frac{d\mathcal{H}}{dt} = \sum_{j=1}^N Q_j \dot{q}_j - \frac{\partial \mathcal{L}}{\partial t}. \quad (9.2.19)$$

The first case we consider is a time-invariant system, which means that the position of all points at any instant depends on the generalized coordinates in a functional relationship that does not explicitly display the elapsed time. This has a number of consequences regarding Eq. (9.2.19) because physical velocities are related homogeneously to the generalized velocities according to

$$\bar{v}(\dot{q}_i, q_i, t) = \sum_{j=1}^N \frac{\partial \bar{r}}{\partial \dot{q}_j} \dot{q}_j. \quad (9.2.20)$$

Correspondingly, the power input by a set of nonconservative forces is

$$\dot{W} = \sum_n \bar{F}_n \cdot \bar{v}_n = \sum_n \bar{F}_n \cdot \sum_{j=1}^N \left( \frac{\partial \bar{r}_n}{\partial \dot{q}_j} \right) \dot{q}_j. \quad (9.2.21)$$

According to Eq. (7.4.4) the generalized forces are describable as

$$Q_j = \sum_n \bar{F}_n \cdot \frac{\partial \bar{r}_n}{\partial \dot{q}_j}. \quad (9.2.22)$$

The only nonconservative force that does work when the system moves is the couple  $\Gamma$  that sustains a constant precession rate  $\Omega$ , so the power input is

$$\dot{W} = \Gamma \Omega.$$

The work–energy principle states that  $\dot{E} = \dot{W}$ , which leads to

$$\frac{1}{3}mL^2[\dot{\theta}\ddot{\theta} + \Omega^2\dot{\theta}(\sin\theta)(\cos\theta)] + mg\frac{L}{2}\dot{\theta}\sin\theta = \Gamma\Omega. \quad (5) \triangleleft$$

We may derive another differential equation for  $\theta$  from Jacobi's integral by observing that  $d\mathcal{H}/dt = 0$ . Differentiation of Eq. (4) shows that

$$\frac{1}{3}mL^2[\dot{\theta}\ddot{\theta} - \Omega^2\dot{\theta}(\sin\theta)(\cos\theta)] + mg\frac{L}{2}\dot{\theta}\sin\theta = 0. \quad 6 (\triangleleft)$$

This is identical to Lagrange's equation for  $\theta$  multiplied by an additional  $\dot{\theta}$  factor. Taking the difference between Eqs. (5) and (6) yields an expression for  $\Gamma$ :

$$\Gamma = \frac{2}{3}mL^2\Omega\dot{\theta}(\sin\theta)(\cos\theta). \quad (7)$$

Equations (5) and (6) can be obtained by an alternative formulation that uses as constrained generalized coordinates  $q_1 = \theta$  and  $q_2 = \psi$ , which must satisfy the constraint equation that  $\dot{\psi} = \Omega$ . The Lagrange equation for  $\theta$  would be the same as Eq. (6) divided by the common factor  $\dot{\theta}$ . Substitution of the condition that  $\dot{\psi} = \Omega$ ,  $\ddot{\psi} = 0$ , into the Lagrange equation for  $\psi$  would yield Eq. (7).

### 9.2.3 Ignorable Coordinates and Routh's Method

Consideration of generalized momenta in some circumstances can lead to additional conservation theorems, as well as simplification of the equations of motion. The first situation arises when the Lagrangian does not depend explicitly on a specific generalized coordinate  $q_n$ , even though the corresponding  $\dot{q}_n$  does appear explicitly. Because  $\partial\mathcal{L}/\partial q_n = 0$  in this case, Lagrange's equation for this generalized coordinate is

$$\frac{d}{dt}\left(\frac{\partial\mathcal{L}}{\partial\dot{q}_n}\right) \equiv \frac{dp_n}{dt} = Q_n. \quad (9.2.26)$$

The solution of this differential equation is

$$p_n|_{t_2} = p_n|_{t_1} + \int_{t_1}^{t_2} Q_n dt. \quad (9.2.27)$$

This is a *generalized impulse–momentum principle*. Both linear and angular momenta are described by it, depending on the type of geometric quantity associated with  $q_n$ . It should be noted that, if  $Q_n$  depends on any of the generalized coordinates, this momentum principle could not be used independently to relate the states at  $t_1$  and  $t_2$ , because the impulse could not be evaluated until the time dependence of the generalized coordinates has been determined. Such a situation corresponds to the Newtonian formulation

## 9.2 Generalized Momentum Principles

583

of position-dependent forces, in which momentum principles are not used because the impulse cannot be evaluated.

Now consider the more restrictive situation, in which  $\mathcal{L}$  does not depend on a specific  $q_n$  and the corresponding generalized force  $Q_n$  vanishes,  $Q_n = 0$ . We find from the foregoing that  $p_n$  is constant, which corresponds to *conservation of a generalized momentum*. When such a situation occurs, the value of  $p_n$  may be computed from the system's initial conditions. On the other hand, when we return to the definition of  $p_n$  we obtain an expression that depends on the full set of generalized coordinates and velocities. Thus, if we form

$$\frac{\partial \mathcal{L}}{\partial \dot{q}_n} = p_n = \text{constant}, \quad (9.2.28)$$

we may algebraically solve this relation for  $\dot{q}_n$  in terms of the other generalized coordinates and generalized velocities. This solution may be substituted into the remaining Lagrange's equations to obtain equations of motion in which neither  $q_n$  nor  $\dot{q}_n$  appears. For this reason  $q_n$  is said to be an *ignorable coordinate*.<sup>§</sup>

We used this procedure to simplify the equations of motion in Example 7.14 in Chapter 7. Although the resulting equations will have a more complicated form in comparison with those that feature the ignorable coordinate, there will be fewer equations to solve. Thus one should assess whether the effort to remove the ignorable coordinate is warranted in view of the potential improvement for the solution. When several generalized coordinates are ignorable, the set of momentum conservation equations, Eq. (9.2.28), comprises simultaneous algebraic equations that may be solved for each ignorable coordinate's generalized velocity in terms of the other variables.

An important aspect of the elimination process is that the coordinates are removed by operating on the Lagrange's equations that are derived by use of the full set of equations. It might seem that a shortcut would be to substitute the  $\dot{q}_n$  expressions for the ignorable coordinates derived from Eq. (9.2.28) directly into the Lagrangian and use that reduced Lagrangian to obtain the equations for the nonignorable coordinates. Doing so would be incorrect because a fundamental step leading to Lagrange's equations required that the virtual increments in the generalized coordinates be completely arbitrary.

*Routh's method for the ignoring of coordinates* is an alternative elimination procedure that enables us to remove the ignorable coordinates before the equations for the nonignorable coordinates are derived. In essence, it derives the Lagrangian for an equivalent system having a reduced number of degrees of freedom. To develop the procedure, let  $K$  denote the number of generalized coordinates, sequenced as  $q_1$  to  $q_K$ , that appear explicitly in the Lagrangian, and therefore are not ignorable. Then there are  $N - K$  ignorable coordinates, sequenced as  $q_{K+1}$  to  $q_N$ . The first step in following Routh's method is to form Eq. (9.2.28) for each ignorable coordinate and to solve those equations algebraically. These operations will yield the ignorable generalized velocities

<sup>§</sup> Rather than being said to be ignorable, such variables are often said to be *cyclic coordinates*. This name stems from the observation that most cases in which a generalized coordinate is ignorable involve rotation about an axis. Occasionally, these variables are said to be *kinosthenic coordinates*.



wheel at contact point  $C$  with the  $xz$  plane always coincident with the plane of the sketch. Because the  $x$  axis is tangent to the surface in the vertical plane, its angle of elevation  $\beta$  is related to the slope  $z' \equiv dz/dR$ , so that

$$\beta = \tan^{-1}(Z') \implies \sin \beta = \frac{Z'}{[1 + (Z')^2]^{1/2}}, \quad \cos \beta = \frac{1}{[1 + (Z')^2]^{1/2}}, \quad (1)$$

$$\bar{e}_R = \cos \beta \bar{i} - \sin \beta \bar{k}, \quad \bar{e}_Z = \sin \beta \bar{i} + \cos \beta \bar{k}.$$

The angular velocity of the ball consists of the precession  $\dot{\theta}$  at which the plane of the sketch rotates about the vertical axis, onto which is superposed unknown rotations  $\Omega_x$  about the  $x$  axis and  $\Omega_z$  about the  $z$  axis. Therefore the angular velocity of the ball is given by

$$\bar{\omega} = \dot{\theta} (\sin \beta \bar{i} + \cos \beta \bar{k}) + \Omega_x \bar{i} + \Omega_y \bar{j}. \quad (2)$$

The no-slip condition requires that  $\bar{v}_O = \bar{v}_C + \bar{\omega} \times \bar{r}_{O/C}$ , where the position of the center  $O$  relative to the contact point  $C$  is  $\bar{r}_{O/C} = \sigma \bar{k}$ . The transverse distance from the axis of rotation to the contact point is  $R_C = R + \sigma \sin \beta$ , and the velocity of this point on the roulette wheel is  $R_C \dot{\psi} \bar{j}$ . The condition that there is no slippage at point  $C$  therefore leads to

$$\begin{aligned} \bar{v}_O &= R_C \dot{\psi} \bar{j} + [(\dot{\theta} \sin \beta + \Omega_x) \bar{i} + \Omega_y \bar{j} + \dot{\theta} \cos \beta \bar{k}] \times \sigma \bar{k} \\ &= \Omega_y \sigma \bar{i} + [R_C \dot{\psi} - (\dot{\theta} \sin \beta + \Omega_x) \sigma] \bar{j}. \end{aligned} \quad (3)$$

We also can describe the velocity of the ball's center in terms of the cylindrical coordinates. Here we use the fact that  $Z$  is a known function of  $R$ , so that  $\dot{Z} = \dot{R}(dZ/dR) \equiv \dot{R}Z'$ . In view of the representation of the cylindrical coordinate unit vectors in Eqs. (1), it follows that

$$\begin{aligned} \bar{v}_O &= \dot{R} \bar{e}_R + R \dot{\theta} \bar{e}_\theta + \dot{Z} \bar{k} \\ &= (\dot{R} \cos \beta + \dot{R} Z' \sin \beta) \bar{i} + R \dot{\theta} \bar{j} + (-\dot{R} \sin \beta + \dot{R} Z' \cos \beta) \bar{k} \\ &\equiv \frac{\dot{R}}{\cos \beta} \bar{i} + R \dot{\theta} \bar{j}, \end{aligned} \quad (4)$$

where the last form is a consequence of the definition of  $\beta$  in Eqs. (1). Each component of this description of  $\bar{v}_O$  must match the corresponding component in Eq. (3), which leads to

$$\begin{aligned} \Omega_y &= \frac{\dot{R}}{\sigma} \dot{R} [1 + (Z')^2]^{1/2}, \\ \Omega_x &= -\left(\frac{R}{\sigma} + \sin \beta\right) \dot{\theta} + \frac{R_C}{\sigma} \dot{\psi} \equiv \left(\frac{R}{\sigma} + \sin \beta\right) (\dot{\psi} - \dot{\theta}). \end{aligned}$$

The angular velocity in Eq. (2) correspondingly is

$$\bar{\omega} = \left[\left(\frac{R}{\sigma} + \sin \beta\right) \dot{\psi} - \frac{R}{\sigma} \dot{\theta}\right] \bar{i} + \frac{\dot{R}}{\sigma \cos \beta} \bar{j} + \dot{\theta} \cos \beta \bar{k}. \quad (5)$$

a specified  $R$ . This solution is most conveniently described in matrix form. Let  $[M_I]$  denote the submatrix of  $[M]$  associated with the ignorable coordinates,

$$[M_I] = \begin{bmatrix} M_{2,2} & M_{2,3} \\ M_{3,2} & M_{3,3} \end{bmatrix},$$

which leads to

$$[\dot{\theta} \ \dot{\psi}]^T = [M_I]^{-1} [p_2 \ p_3]^T.$$

Forming the Routhian with this expression is assisted by the fact that  $R$  is inertially uncoupled from the ignorable coordinates, so  $\mathcal{L}$  may be rewritten as

$$\mathcal{L} = \frac{1}{2} M_{1,1} \dot{R}^2 + \frac{1}{2} [\dot{\theta} \ \dot{\psi}] [M_I] [\dot{\theta} \ \dot{\psi}]^T - mgZ.$$

The summation in Eq. (9.2.30) defining the Routhian is equivalent to  $\{p_I\}^T \{\dot{q}_I\}$ , where each vector contains the variables for the ignorable coordinates. Thus substitution of the solution for the ignorable generalized coordinates into the Routhian for the present system yields

$$\begin{aligned} \mathfrak{R} &= \mathcal{L} - \{p_I\}^T \{\dot{q}_I\} \\ &= \frac{1}{2} M_{1,1} \dot{R}^2 + \frac{1}{2} [\dot{\theta} \ \dot{\psi}] [M_I] [\dot{\theta} \ \dot{\psi}]^T - [p_2 \ p_3] [\dot{\theta} \ \dot{\psi}]^T - mgZ \\ &= \frac{1}{2} M_{1,1} \dot{R}^2 + \frac{1}{2} [p_2 \ p_3] [M_I]^{-1} [M_I] [M_I]^{-1} [p_2 \ p_3]^T \\ &\quad - [p_2 \ p_3] [M_I]^{-1} [p_2 \ p_3]^T - mgZ \\ &= \frac{1}{2} M_{1,1} \dot{R}^2 - \frac{1}{2} [p_2 \ p_3] [M_I]^{-1} [p_2 \ p_3]^T - mgZ. \end{aligned} \quad \triangleleft$$

Because  $Z$  and  $[M_I]$  are known functions of  $R$ , the Routhian  $\mathfrak{R}$  depends on only  $R$  and  $\dot{R}$ , so it represents the Lagrangian of an equivalent one-degree-of-freedom system. The first term, which contains the generalized velocity, is the equivalent kinetic energy, whereas the equivalent potential energy is the negative of the sum of the remaining terms. The single differential equation of motion is Lagrange's equation formulated in terms of  $\mathfrak{R}$  rather than the Lagrangian, with  $q_1 = R$  and  $Q_1 = 0$ . After this equation has been solved for  $R$ , the time dependence of  $\theta$  and  $\phi$  may be found by treating the definitions of  $p_2$  and  $p_3$  as first-order differential equations. One advantage of having to analyze only one acceleration equation is that fundamental properties are readily established. For example, we may identify the equilibrium positions by seeking the values of  $R$  at which  $\partial \mathfrak{R} / \partial R = 0$ .

### 9.3 FORMULATIONS WITH QUASI-COORDINATES

The dynamics principles associated with Lagrange and Hamilton share the attribute that the sole kinematical variables to be determined are the generalized coordinates. They

position, and angular velocity vectors in terms of components relative to a body-fixed reference frame. The result is

$$\bar{v}_B = \bar{v}_A + (-r_z \bar{j} + r_y \bar{k}) \omega_x + (r_z \bar{i} - r_x \bar{k}) \omega_y + (r_x \bar{j} - r_y \bar{i}) \omega_z. \quad (9.3.1)$$

The components of  $\bar{\omega}$  can be considered quasi-velocities. They occur linearly in the preceding description of velocity, with vector coefficients that may depend on generalized coordinates and time. There also is a term in the preceding equation that does not contain these quasi-velocities. This form represents a generalization of Eq. (9.2.3), with derivatives of generalized velocities  $\dot{q}_j$  replaced with quasi-velocities.

To develop this concept we begin by considering a situation in which the number of quasi-coordinates we select is  $N$ , the number of generalized coordinates. Then the mathematical form of a physical velocity will be

$$\bar{v}_P(\dot{q}_i, q_i, t) = \sum_{j=1}^N \bar{v}_{Pj}(q_i, t) \dot{q}_j + \bar{v}_{P0}(q_i, t). \quad (9.3.2)$$

In view of the fact that we have the option of describing the velocity of any point in terms of the  $\dot{q}_j$  according to Eq. (9.2.3) or in terms of the  $\dot{q}_j$  variables according to Eq. (9.3.2), it must be that the two sets of variables are kinematically related. Indeed, when we contemplate matching like components of the alternative descriptions of velocity, it becomes apparent that there is a linear relationship between the two sets of variables, with the coefficients of that relationship being dependent on the generalized coordinates. In other words,

$$\dot{q}_j = \sum_{n=1}^N C_{jn}(q_i, t) \dot{q}_n + D_j(q_i, t); \quad j = 1, \dots, N. \quad (9.3.3)$$

These are the *kinematical equations*, which will form one part of the differential equations of motion.

Suppose that there are  $J$  velocity constraint equations relating the generalized coordinates. We can formulate these equations in terms of quasi-velocities by using descriptions of linear and angular velocities having the form of Eq. (9.3.2). The result will be a set of constraint equations that are linear in the quasi-velocities. Thus, when there are  $J$  constraint equations to be satisfied, it is necessary that the quasi-velocities at any instant satisfy

$$\sum_{n=1}^N A_{jn}(q_i, t) \dot{q}_n + B_j(q_i, t) = 0; \quad j = 1, \dots, J. \quad (9.3.4)$$

[In some situations it might be that linear velocity constraint equations have already been described in terms of the generalized velocities. In that case, substitution of Eq. (9.3.3) will lead to the preceding form.]

We now come to one of the beneficial features of quasi-coordinates. Velocity constraint equations that are expressed in terms of generalized velocities also depend on the

### 9.3 Formulations with Quasi-Coordinates

591

values of the generalized coordinates. Consequently, in the nonholonomic case, they are differential equations that can be solved only in conjunction with the kinetics equations. In contrast, the  $\dot{\gamma}_i$  appear in the preceding constraint equations only linearly, with coefficients that are independent of the quasi-coordinates. Thus we may consider Eq. (9.3.4) to be a set of  $J$  algebraic equations for the instantaneous  $\dot{\gamma}_i$  values at a specified position and time. We could solve those equations for  $J$  values in terms of the remaining  $N - J$  values. The latter set constitutes *unconstrained quasi-velocities*. This name conveys the fact that any choice of the  $N - J$  remaining quasi-velocities will inherently lead to a motion that is kinematically admissible. On the other hand, there are situations in which constrained quasi-velocities are useful, such as systems in which Coulomb friction is important.

We can accommodate all possibilities by letting  $K$  denote the number of quasi-coordinates, while we retain  $N$  as the number of generalized coordinates and  $J$  as the number of constraint equations. In the initial discussion of nonholonomic constraint equations, the number of degrees of freedom was defined to be the number of generalized velocities whose value at any instant can be selected arbitrarily and still obtain a kinematically admissible velocity for all parts of the system. Thus  $K - J$  is the number of degrees of freedom. This generalization requires an adjustment of the summation range in the kinematical equations, such that

$$\dot{q}_j = \sum_{n=1}^K C_{jn}(q_i, t) \dot{\gamma}_n + D_j(q_i, t); \quad j = 1, \dots, N. \quad (9.3.5)$$

If  $J > 0$ , then the constraint equations will also be like the earlier set, except for the altered summation range. Thus the quasi-velocities must satisfy constraint equations whose form is

$$\sum_{n=1}^K A_{jn}(q_i, t) \dot{\gamma}_n + B_j(q_i, t) = 0; \quad j = 1, \dots, J. \quad (9.3.6)$$

Quasi-coordinates are also used to describe virtual movements. The true displacement of point  $P$  is  $\bar{v}_P dt$ , which Eq. (9.3.2) shows to be

$$d\bar{r}_P = \sum_{j=1}^K \bar{v}_{Pj}(q_i, t) \dot{\gamma}_j dt + \bar{v}_{P0}(q_i, t) dt. \quad (9.3.7)$$

To convert this to a virtual displacement, for which time is held constant, we drop the last term and replace each  $\dot{\gamma}_j dt$  with an infinitesimal value  $\delta\gamma_j$ . (Just as the  $\dot{\gamma}_j$  parameters need not directly describe the rates at which position coordinates change, the  $\delta\gamma_j$  values might have an abstract meaning in terms of change of position.) Thus the virtual displacement of a point is described by

$$\delta\bar{r}_P = \sum_{j=1}^K \bar{v}_{Pj}(q_i, t) \delta\gamma_j. \quad (9.3.8)$$

Similarly, the virtual increments of the generalized coordinates are found from Eq. (9.3.5) to be


$$\delta q_n = \sum_{j=1}^K C_{nj}(q_i, t) \delta \gamma_j. \quad (9.3.9)$$

We further observe that, if the quasi-coordinates are constrained, then their virtual increments must be selected to be kinematically admissible. We multiply the constraint equations, Eq. (9.3.6), by  $dt$  to obtain the Pfaffian form, then convert  $\dot{\gamma}_j dt$  to  $\delta \gamma_j$ , and drop the term containing  $dt$ , which leads to the condition that the virtual displacement will be kinematically admissible if

$$\sum_{j=1}^N A_{nj}(q_i, t) \delta \gamma_j = 0; \quad j = 1, \dots, J. \quad (9.3.10)$$

An overview of the kinematical concepts associated with quasi-coordinates shows that generalized coordinates solely describe position dependence, whereas quasi-coordinates describe velocity and virtual displacement. We begin a kinematical description by selecting the geometrical variables that constitute the set of  $q_j$  and the rate variables that constitute the  $\dot{\gamma}_j$  parameters. It is permissible that some or all of the latter are the rate of change of a generalized coordinate. The number  $K$  of quasi-velocities must be sufficient to describe every possible kinematical movement of the system.

**EXAMPLE 9.6** End  $A$  of the bar is constrained to follow the guide, whereas end  $B$  has a steerable wheel that rolls in the horizontal  $XY$  plane. The steering angle  $\beta$  is controlled by a servomotor, so it is a known function of time. Let the position coordinates of pivot  $B$  and angle  $\theta$  be generalized coordinates, and let the quasi-velocities be  $\dot{\theta}$  and the velocity components of point  $G$  relative to the body-fixed  $xyz$  coordinate system. (a) Determine the constraint equations relating the quasi-velocities. (b) Determine the kinematical equations relating the generalized coordinates to the quasi-velocities.



Example 9.6

**SOLUTION** This example demonstrates that the basic procedure for formulating velocity constraint equations by use of quasi-velocities differs little from the procedure for generalized velocities. However, to highlight this attribute, the generalized coordinates and quasi-velocities that have been selected are not the parameters an experienced practitioner would use. It is specified that the generalized

### 9.3 Formulations with Quasi-Coordinates

593

coordinates are  $q_1 = X_A$ ,  $q_2 = Y_A$ , and  $q_3 = \theta$ , and that the quasi-velocities are  $\dot{q}_1 = (v_G)_x$ ,  $\dot{q}_2 = (v_G)_y$ , and  $\dot{q}_3 = \dot{\theta}$ . Collar  $A$  requires that  $\bar{v}_A$  be parallel to the  $X$  axis, whereas wheel  $B$  requires that  $\bar{v}_B$  be at angle  $\beta$  relative to the  $x$  axis. Thus we begin by relating the velocity of each end to the velocity of the center of mass and the angular velocity, which are known in terms of the quasi-velocities:

$$\begin{aligned}\bar{v}_A &= \bar{v}_G + \bar{\omega} \times \bar{r}_{A/G} = (v_G)_x \bar{i} + (v_G)_y \bar{j} + \dot{\theta} \bar{k} \times \left( -\frac{L}{2} \bar{i} \right), \\ \bar{v}_B &= \bar{v}_G + \bar{\omega} \times \bar{r}_{B/G} = (v_G)_x \bar{i} + (v_G)_y \bar{j} + \dot{\theta} \bar{k} \times \left( \frac{L}{2} \bar{i} \right).\end{aligned}\tag{1}$$

The constraints require that  $\bar{v}_A$  be parallel to the  $X$  axis and  $\bar{v}_B$  be at angle  $\beta$  above the  $x$  axis. Both conditions can be imposed with cross products and unit vectors in the respective directions, specifically,

$$\begin{aligned}\bar{v}_A \times (\cos \theta \bar{i} - \sin \theta \bar{j}) &= \bar{0}, \\ \bar{v}_B \times (\cos \beta \bar{i} + \sin \beta \bar{j}) &= \bar{0}.\end{aligned}\tag{2}$$

We substitute Eqs. (1) to eliminate  $v_A$  and  $v_B$ , neither of which is a quasi-velocity. The cross products have only  $\bar{k}$  components, so evaluation of Eqs. (2) leads to

$$\begin{aligned}-(v_G)_x \sin \theta - \left[ (v_G)_y - \frac{L}{2} \dot{\theta} \right] \cos \theta &= 0, \\ (v_G)_x \sin \beta - \left[ (v_G)_y + \frac{L}{2} \dot{\theta} \right] \cos \beta &= 0.\end{aligned}$$

When each quasi-velocity is designated by the appropriate  $\dot{q}$  symbol, these constraint equations become

$$\begin{aligned}\dot{q}_1 \sin \theta + \dot{q}_2 \cos \theta - \frac{L}{2} \dot{q}_3 \cos \theta &= 0, \\ \dot{q}_1 \sin \beta - \dot{q}_2 \cos \beta - \frac{L}{2} \dot{q}_3 \cos \beta &= 0.\end{aligned}$$

Both of these have the standard linear velocity constraint form in Eq. (9.3.4), with

$$\begin{aligned}A_{1,1} &= \sin \theta, & A_{1,2} &= \cos \theta, & A_{1,3} &= -\frac{L}{2} \cos \theta, & B_1 &= 0, \\ A_{2,1} &= \sin \beta, & A_{2,2} &= -\cos \beta, & A_{2,3} &= -\frac{L}{2} \cos \beta, & B_2 &= 0.\end{aligned}$$

There are three quasi-velocities that must satisfy two velocity constraints, so there is one degree of freedom.

The kinematical equations express the rates at which the generalized coordinates  $X_B$ ,  $Y_B$ , and  $\theta$  change in terms of the quasi-velocities. We observe that  $\dot{\theta}$  is defined to be  $\dot{q}_3$ , so one kinematical equation is an identity. To obtain the other

kinematical equations associated with  $X_B$  and  $Y_B$  we observe that these variables describe the position of point  $B$ . Thus, instead of describing the velocity of point  $B$  according to Eqs. (1), we could have expressed  $\bar{v}_B$  in terms of the generalized velocities as

$$\bar{v}_B = \dot{X}_B \bar{I} + \dot{Y}_B \bar{J} = (v_G)_x \bar{I} + \left[ (v_G)_y \bar{J} + \dot{\theta} \frac{L}{2} \bar{J} \right].$$

Taking components of each expression and replacing the various symbols with their quasi-velocity designations yields

$$\begin{aligned} \dot{X}_B &= \dot{\gamma}_1 \cos \theta - \left( \dot{\gamma}_2 + \frac{L}{2} \dot{\gamma}_3 \right) \sin \theta, \\ \dot{Y}_B &= \dot{\gamma}_1 \sin \theta + \left( \dot{\gamma}_2 + \frac{L}{2} \dot{\gamma}_3 \right) \cos \theta, \\ \dot{\theta} &= \dot{\gamma}_3, \end{aligned} \quad \triangleleft$$

which matches Eq. (9.3.5) with

$$\begin{aligned} C_{1,1} &= \cos \theta, & C_{1,2} &= -\sin \theta, & C_{1,3} &= -\frac{L}{2} \sin \theta, & D_1 &= 0, \\ C_{2,1} &= \sin \theta, & C_{2,2} &= \cos \theta, & C_{2,3} &= \frac{L}{2} \cos \theta, & D_2 &= 0, \\ C_{3,1} &= C_{3,2} = 0, & C_{3,3} &= 1, & D_3 &= 0. \end{aligned}$$

### 9.3.2 Gibbs–Appell Equations

It is possible to modify Lagrange's equations such that the term that contains a derivative with respect to a generalized velocities is replaced with terms that depend on the quasi-velocities, see Desloge (1982). However, the transformation may be conveniently carried out only for a holonomic system. In contrast, the Gibbs–Appell equations place no restrictions on the conditions to which they apply. The derivation begins at the fundamental level of a particle  $P$ . We describe the position of this particle in terms of its coordinates with respect to a fixed  $XYZ$  reference frame, which we denote indicially as  $x_1, x_2, x_3$ . Let  $(F_P)_n$  denote the corresponding components of the resultant force acting on this particle. In view of Newton's Second Law, the virtual work done on this particle must be such that

$$\delta W_P = \sum_{n=1}^3 (F_P)_n \delta x_n = \sum_{n=1}^3 m_P \ddot{x}_n \delta x_n. \quad (9.3.11)$$

Now consider using quasi-velocities to describe the motion. The relation between the  $\dot{x}_n$  and the  $\dot{\gamma}_n$  variables has the form of Eq. (9.3.5), and the relation between

### 9.3 Formulations with Quasi-Coordinates

599

As was true for Lagrange's equations, shortcuts are available to assist the evaluation of the  $\Gamma_j$  terms. Regardless of the nature of a physical force, it is always permissible to identify its contribution to the generalized forces by explicitly evaluating its virtual work, as described by Eq. (9.3.22). For conservative forces we can alternatively use the associated potential-energy function,  $V$ , which is a function solely of the generalized coordinates and, possibly, time. The virtual work such forces do is

$$\delta W_{\text{cons}} = -\delta V = -\sum_{n=1}^N \frac{\partial V}{\partial q_n} \delta q_n. \quad (9.3.34)$$

In the Gibbs–Appell formulation, the virtual increments are the  $\delta\gamma_j$  quantities, which are kinematically related to the corresponding  $\delta q_j$  by Eq. (9.3.9). Thus,

$$\delta W_{\text{cons}} = -\sum_{n=1}^N \frac{\partial V}{\partial q_n} \sum_{j=1}^K C_{nj} \delta\gamma_j. \quad (9.3.35)$$

We obtain a useful identity for extracting the  $C_{nj}$  coefficients by differentiating the kinematical equations, Eq. (9.3.5), with respect to a specific quasi-velocity, which yields

$$C_{nj} = \frac{\partial \dot{q}_n}{\partial \dot{\gamma}_j}.$$

We substitute this relation into  $\delta W_{\text{cons}}$  and recognize that the coefficient of  $\delta\gamma_j$  is the contribution of conservative forces to the  $j$ th generalized force. It follows that

$$(\Gamma_j)_{\text{conservative}} = -\sum_{n=1}^N \frac{\partial V}{\partial q_n} \frac{\partial \dot{q}_n}{\partial \dot{\gamma}_j}. \quad (9.3.36)$$

Now consider the constraint forces. The generalized forces here are like those for Lagrange's equations, so any constraint force whose kinematical constraint condition is satisfied regardless of the  $q_j$  and  $\dot{\gamma}_j$  values will not appear in any generalized force. As a corollary, using unconstrained quasi-velocities leads to equations of motion that do not contain constraint forces. In contrast, if the quasi-velocities are a constrained set that must satisfy kinematical constraint equations like Eq. (9.3.6), then an arbitrary set of  $\delta\gamma_j$  values will correspond to a kinematically inadmissible movement, which means that the constraint forces will contribute to the virtual work. As was true for constrained generalized coordinates, the contribution of the  $i$ th constraint force to  $\Gamma_j$  may be described by a Lagrange multiplier  $\lambda_i$  defined in conjunction with the Jacobian constraint coefficients  $A_{ij}$ . We thereby find that

$$(\Gamma_j)_{\text{reactions}} = \sum_{i=1}^J A_{ij} \lambda_i. \quad (9.3.37)$$

Thus we find that a generalized force in the Gibbs–Appell formulation may consist of three types of terms,

$$\Gamma_j = \sum_P \bar{F}_P \cdot \bar{v}_{Pj}(q_i, t) - \sum_{n=1}^N \frac{\partial V}{\partial q_n} \frac{\partial \dot{q}_n}{\partial \dot{\gamma}_j} + \sum_{i=1}^J A_{ij} \lambda_i. \quad (9.3.38)$$



This leads us to the form of the Gibbs–Appell equations that we will implement:

$$\frac{\partial S}{\partial \ddot{\gamma}_j} = \sum_P \bar{F}_P \cdot \bar{v}_{Pj}(q_i, t) - \sum_{n=1}^N \frac{\partial V}{\partial q_n} \frac{\partial \dot{q}_n}{\partial \dot{\gamma}_j} + \sum_{i=1}^J A_{ij} \lambda_i, \quad j = 1, \dots, K. \quad (9.3.39)$$

Many texts use the symbol  $\tilde{\gamma}$  to denote unconstrained quasi-coordinates, corresponding to the absence of constraint equations. However, from our viewpoint there is nothing special about these variables. We merely set  $J = 0$  in the preceding equation, which removes the term with Lagrange multipliers from the preceding Gibbs–Appell equations.

A summary of the procedure required for formulating the Gibbs–Appell equations of motion is appropriate at this junction. The first step is to define a set of  $N$  generalized coordinates  $q_i$  to describe the instantaneous position and a set of  $K$  quasi-velocities  $\dot{\gamma}_i$ . A kinematical analysis is performed to derive an expression for each  $\dot{q}_i$  in terms of the instantaneous values of the  $\dot{\gamma}_i$  and  $q_i$  parameters. These relations constitute the kinematical equations, whose form is described by Eq. (9.3.5). A kinematical analysis is also required to ascertain whether assigning an arbitrary value to each  $\dot{\gamma}_i$  at an arbitrary position will lead to a kinematically admissible motion for the system. If not, then velocity constraint equations like Eq. (9.3.6) must be derived. The number of such equations is  $J$ .

A kinematics analysis also must characterize the velocity and acceleration parameters required to form the Gibbs–Appell function for each body according to Eq. (9.3.32). Thus expressions for the body-fixed angular velocity components as functions of the  $\dot{\gamma}_j$  and  $q_j$  parameters, and for the body-fixed angular acceleration components as functions of the  $\ddot{\gamma}_j$ ,  $\dot{\gamma}_j$ , and  $q_j$  parameters, need to be derived. If the reference point for the angular motion is the center of mass, then the acceleration of the center of mass of that body must also be derived as a function of  $\ddot{\gamma}_j$ ,  $\dot{\gamma}_j$ , and  $q_j$ . We obtain the Gibbs–Appell function for the system by summing the contribution of each of its bodies. The last task prior to forming the Gibbs–Appell equations is to determine the generalized force associated with each quasi-coordinate. We address the contribution of conservative forces by describing their potential energy as a function of the generalized coordinates. The contribution of forces that are not associated with constraints is described by evaluation of their virtual work. This entails further kinematical analysis in order to characterize the associated virtual displacement (or rotation) resulting from arbitrary increments  $\delta \gamma_j$  when the system is at an arbitrary location. Any constraint force that we wish to appear explicitly in the equations of motion, especially the normal force associated with Coulomb friction, may be described in this manner. The portion of the generalized forces associated with the remaining constraint forces is described by the Lagrange multipliers. In the case of unconstrained quasi-coordinates, for which all physical constraint conditions are implicitly satisfied, the Lagrange multipliers are omitted from the formulation.

After we have carried out these preliminaries, we differentiate  $S$  as called for in Eq. (9.3.39). This yields a set of  $K$  Gibbs–Appell equations of motion in which the sole

### 9.3 Formulations with Quasi-Coordinates

601

variables are  $\ddot{y}_j$ ,  $\dot{y}_j$ ,  $q_j$ , possibly  $t$ , and the Lagrange multipliers. These may be considered to be set of ordinary differential equations governing the  $\dot{y}_j$ , which will occur only linearly. In other words, the Gibbs–Appell equations may be written in matrix notation as

$$[M(q_i, t)]_{K \times K} \frac{d}{dt} \{\dot{y}_j\}_{K \times 1} = \{F(\dot{y}_i, q_i, t)\}_{K \times 1} + ([A]_{J \times K})^T \{\lambda\}_{J \times 1}. \quad (9.3.40)$$

Obviously,  $[M]$  here is not the same as the inertia matrix for Lagrange's equations. Also, if constraint forces  $R_i$  are used in lieu of Lagrange multipliers, the last term would be replaced with  $[A']\{R\}$ , where the  $[A']$  coefficients would be identified from the virtual work.

By themselves these equations cannot be sent to a differential equation solver because they feature the current values of the  $q_j$ , as well as the Lagrange multipliers if  $J \neq 0$ . A numerical solution requires the aforementioned kinematical equations, whose matrix form is

$$\frac{d}{dt} \{q_j\}_{N \times 1} = [C(q_i, t)]_{N \times K} \{\dot{y}_j\}_{K \times 1} + \{D(q_i, t)\}_{N \times 1}. \quad (9.3.41)$$

In addition, if  $J > 0$ , so that there are Lagrange multipliers to determine, then there are  $J$  velocity constraint equations. To satisfy the constraint equations simultaneously with the Gibbs–Appell and kinematical equations, we differentiate the velocity constraints to obtain acceleration constraint equations, whose matrix form is

$$[A(q_i, t)]_{J \times K} \frac{d}{dt} \{\dot{y}_j(q_i, t)\}_{K \times 1} = - \left[ \frac{d}{dt} A(q_i, t) \right]_{J \times K} \{\dot{y}_j(q_i, t)\}_{K \times 1} - \left\{ \frac{d}{dt} B \right\}. \quad (9.3.42)$$

Thus we obtain  $K + N + J$  coupled ordinary differential equations for  $\dot{y}_j$  for  $j = 1, \dots, K$ ,  $q_j$  for  $j = 1, \dots, N$ , and  $\lambda_j$  for  $j = 1, \dots, J$ . These equations have the form required to employ the numerical solution techniques in Subsection 8.2.1. As always, care must be taken to select initial conditions that are consistent with all constraints. This issue was addressed in Subsection 8.2.3.

The ability to use quasi-coordinates is the primary merit of the Gibbs–Appell approach. It affords us more flexibility than Lagrange's equations in deciding how to formulate an analysis. In many cases this freedom simplifies the equations of motion because the variables naturally fit the fundamental system features. Also, the number of quasi-coordinates can be less than the number of generalized coordinates, in which case there will be fewer differential equations of motion than there would be with Lagrange's equations. We will examine the merits of these alternative approaches after several examples applying the Gibbs–Appell equations have been presented. These examples focus on nonholonomic systems, because the primary advantage of the Gibbs–Appell equations is claimed to lie in its application to such systems.

### 9.3 Formulations with Quasi-Coordinates

603

We obtain the virtual rotation by replacing each  $\dot{\gamma} dt$  with  $\delta\gamma$ , so

$$\delta\bar{\theta} = \delta\gamma_1 \bar{i} + \delta\gamma_2 \bar{j} + \delta\gamma_3 \bar{k}.$$

The virtual work is


$$\delta W = \Sigma \bar{M}_A \cdot \delta\bar{\theta} = (\Sigma M_A)_x \delta\gamma_1 + \cdots = \Gamma_1 \delta\gamma_1 + \cdots.$$

The Gibbs–Appell equation for  $\dot{\gamma}_1$  is

$$\frac{\partial S}{\partial \dot{\gamma}_1} = I_{xx} \ddot{\gamma}_1 + (I_{zz} - I_{yy}) \dot{\gamma}_2 \dot{\gamma}_3 = \Gamma_1 = (\Sigma M_A)_x. \quad \triangleleft$$

Replacing each quasi-velocity with the corresponding component of  $\bar{\omega}$  makes it evident that this is the same as the Euler equation for moment about the  $x$  axis.

**EXAMPLE 9.8** The wheelbarrow remains upright as it is pushed in the horizontal plane by forces  $\bar{F}_A$  and  $\bar{F}_B$  acting at each handle. The body of the wheelbarrow has mass  $m_1$  with its center of mass at point  $G$ ; the corresponding centroidal moment of inertia about a vertical axis is  $I$ . The wheel, which rolls without slipping, has mass  $m_2$ , moment of inertia  $J$  about its axle, and radius  $R$ . Derive the Gibbs–Appell equations of motion.



Example 9.8

**SOLUTION** This example of a nonholonomic system illustrates how one may employ a quasi-velocity that is not a generalized velocity. Because the wheel rolls without slipping and the wheelbarrow remains upright, the angular velocity component of the wheel about its bearing axis is  $\omega_1 = v/R$ , where  $v$  is the speed of the center  $C$  of the axle. Also, because there is no slippage, the velocity of point  $C$  must be along the longitudinal centerline, which we define to be the  $x$  axis of a coordinate system that is attached to the wheelbarrow's body, that is,  $\bar{i} = \bar{e}_{C/G}$ . Convenient generalized coordinates for the wheelbarrow are the absolute position coordinates of point  $C$ ,  $q_1 = X_C$ ,  $q_2 = Y_C$ , and the angle  $\theta$  locating the  $x$  axis relative to a fixed  $XYZ$  reference frame, which we define such that  $X$  is to the right and  $Z$  is vertical.

### 9.3 Formulations with Quasi-Coordinates

605

$\bar{k}$  has been taken to be the upward vertical, so the sense of the spin axis is  $\bar{j}$ . Thus the angular velocity and angular acceleration of the wheel are

$$\begin{aligned}\bar{\omega}_2 &= \frac{\dot{\gamma}_1}{R} \bar{j} + \dot{\gamma}_2 \bar{k}, \\ \bar{\alpha}_2 &= \frac{\ddot{\gamma}_1}{R} \bar{j} + \frac{\dot{\gamma}_1}{R} (\dot{\gamma}_2 \bar{k} \times \bar{j}) + \ddot{\gamma}_2 \bar{k} = -\frac{\dot{\gamma}_1 \dot{\gamma}_2}{R} \bar{i} + \frac{\ddot{\gamma}_1}{R} \bar{j} + \ddot{\gamma}_2 \bar{k}.\end{aligned}\quad (5)$$

Based on the assumption that the wheel is thin, so that the transverse centroidal moment of inertia is  $J/2$ , the angular momentum and its body-fixed derivative are

$$\begin{aligned}\bar{H}_C &= \frac{J}{R} \dot{\gamma}_1 \bar{j} + \frac{J}{2} \dot{\gamma}_2 \bar{k}, \\ \frac{\partial \bar{H}_C}{\partial t} &= -\frac{J}{2R} \dot{\gamma}_1 \dot{\gamma}_2 \bar{i} + \frac{J}{R} \ddot{\gamma}_1 \bar{j} + \frac{J}{2} \ddot{\gamma}_2 \bar{k}.\end{aligned}\quad (6)$$

When we substitute Eqs. (3)–(6) into Eq. (2) for  $S$ , we omit any terms that do not contain either  $\ddot{\gamma}_1$  or  $\ddot{\gamma}_2$ . The specific operations are

$$\begin{aligned}S &= \frac{1}{2} m_1 \left[ (\dot{\gamma}_1 + \dot{\gamma}_2^2 L)^2 + (\dot{\gamma}_1 \dot{\gamma}_2 - \ddot{\gamma}_2 L)^2 \right] + \frac{1}{2} I \dot{\gamma}_2^2 \\ &\quad + \frac{1}{2} m_2 \left[ (\ddot{\gamma}_1)^2 + \dots \right] + \frac{1}{2} \left[ \frac{J}{R^2} \ddot{\gamma}_1^2 + \frac{J}{2} \ddot{\gamma}_2^2 \right] \\ &\quad + \left( -\frac{\dot{\gamma}_1 \dot{\gamma}_2}{R} \bar{i} + \frac{\ddot{\gamma}_1}{R} \bar{j} + \ddot{\gamma}_2 \bar{k} \right) \cdot \left[ \left( \frac{\dot{\gamma}_1}{R} \bar{j} + \dot{\gamma}_2 \bar{k} \right) \times \left( \frac{J}{R} \dot{\gamma}_1 \bar{j} + \frac{J}{2} \dot{\gamma}_2 \bar{k} \right) \right] \\ &= \frac{1}{2} m_1 \left[ (\dot{\gamma}_1 + \dot{\gamma}_2^2 L)^2 + (\dot{\gamma}_1 \dot{\gamma}_2 - \ddot{\gamma}_2 L)^2 \right] \\ &\quad + \frac{1}{2} \left( I + \frac{J}{2} \right) \ddot{\gamma}_2^2 + \frac{1}{2} \left( m_2 + \frac{J}{R^2} \right) \ddot{\gamma}_1^2 + \dots.\end{aligned}\quad (7)$$

Note that the terms associated with a gyroscopic moment for the wheel, which are the  $\bar{i}$  terms in  $\partial \bar{H}_C / \partial t$  and  $\bar{\omega}_2 \times \bar{H}_C$ , do not appear in  $S$  because the system has been constrained to move in the horizontal plane. Momentum effects tending to cause the wheelbarrow to tilt are balanced by reactions, which would be out-of-plane components of the forces  $\bar{F}_A$  and  $\bar{F}_B$ .

The next step is to evaluate the generalized forces. The friction and normal forces exerted on the wheel by the ground are constraint forces that respectively prevent slipping and prevent the wheel from penetrating the ground. Both constraint conditions are satisfied for any set of quasi-velocities, so these forces do not contribute to the virtual work. Gravity acts perpendicularly to the plane of motion, so it too does not contribute to  $\delta W$ . To characterize the effect of the applied forces  $\bar{F}_A$  and  $\bar{F}_B$ , we recall that we have already described the velocity of point  $C$ . We therefore replace these forces with a force–couple system,  $\bar{R}$  and  $\bar{M}$ , acting at point  $C$ :

$$\bar{R} = \bar{F}_A + \bar{F}_B, \quad \bar{M} = \bar{r}_{A/C} \times \bar{F}_A + \bar{r}_{B/C} \times \bar{F}_B.$$

An expression for  $\delta \bar{r}_C$  follows directly from the velocity of that point,

$$\bar{v}_C = \dot{\gamma}_1 \bar{i} \implies \delta \bar{r}_C = \delta \gamma_1 \bar{i},$$

so the virtual work associated with the forces applied to the handles is

$$\delta W = \bar{\mathbf{R}} \cdot \delta \bar{\mathbf{r}}_C + \bar{\mathbf{M}} \cdot \delta \gamma_2 \bar{\mathbf{k}} = (\bar{\mathbf{R}} \cdot \bar{\mathbf{i}}) \delta \gamma_1 + (\bar{\mathbf{M}} \cdot \bar{\mathbf{k}}) \delta \gamma_2.$$

Matching the two descriptions of  $\delta W$  yields the generalized forces:


$$\Gamma_1 = \bar{\mathbf{R}} \cdot \bar{\mathbf{i}}, \quad \Gamma_2 = \bar{\mathbf{M}} \cdot \bar{\mathbf{k}}.$$

All that remains to be done is to differentiate the Gibbs–Appell function, Eq. (7), with respect to each of the quasi-acceleration variables. This yields

$$\begin{aligned} \frac{\partial S}{\partial \ddot{\gamma}_1} &= \left( m_1 + m_2 + \frac{J}{R^2} \right) \ddot{\gamma}_1 + m_1 L \dot{\gamma}_2^2 = \bar{\mathbf{R}} \cdot \bar{\mathbf{i}}, \\ \frac{\partial S}{\partial \ddot{\gamma}_2} &= \left( m_1 L^2 + I + \frac{1}{2} J \right) \ddot{\gamma}_2 - m_1 L \dot{\gamma}_1 \dot{\gamma}_2 = \bar{\mathbf{M}} \cdot \bar{\mathbf{k}}. \end{aligned} \quad \triangleleft$$

These are two coupled first-order differential equations governing  $\dot{\gamma}_1$  and  $\dot{\gamma}_2$ . They have the interesting feature that the generalized coordinates do not appear in them. This means that the equations can be solved numerically for  $\dot{\gamma}_1 = v$  and  $\dot{\gamma}_2 = \dot{\theta}$  as functions of time. If we wish to know where the wheelbarrow goes, we would substitute these solutions into the kinematical equations, Eqs. (1)–(3), which would give  $X_C$ ,  $Y_C$ , and  $\theta$  as functions of time. This is an exceptional situation stemming from the fact that the motion is unaffected by the wheelbarrow's position. In most cases, such as the one in the next example, it is necessary to treat the Gibbs–Appell and kinematical equations as a coupled set of differential equations.

**EXAMPLE 9.9** The system in the sketch is like the one in Example 9.6. A motor mounted internally applies a known torque to the wheel's axle, thereby generating the known traction force  $F(t)$ . This force acts tangentially to the wheel. The wheel rolls without slipping, and the steering angle  $\beta$  changes in a prescribed manner. The collar is attached to a linearly elastic spring  $k$ . The mass of the bar, the collar, and the wheel are  $m_1$ ,  $m_2$ , and  $m_3$ , respectively, and the centroidal moments of inertia of the wheel are  $I_1$  and  $I_2$ , respectively parallel and perpendicular to the wheel's axle. Determine the Gibbs–Appell equations of motion governing a set of constrained quasi-coordinates.



Example 9.9

### 9.3 Formulations with Quasi-Coordinates


607

**SOLUTION** Most of the basic operations involved in formulating the Gibbs–Appell equations of motion in terms of constrained quasi-velocities are demonstrated here. Example 9.6 established that this system has one degree of freedom. The position of all parts of the system is readily described if we know the angle  $\theta$  and the length  $\ell$  of the spring, so we use these variables as generalized coordinates,  $q_1 = \theta$ ,  $q_2 = \ell$ . Similarly, all velocities and accelerations are readily described in terms of  $\dot{\theta}$  and  $\dot{\ell}$  and their time derivatives, so we select these variables as the quasi-velocities:

$$\dot{\theta} = \dot{\gamma}_1, \quad \dot{\ell} = \dot{\gamma}_2. \quad (1, 2) \triangleleft$$

These are the kinematical equations relating the generalized coordinates to the quasi-velocities.

We consider the bar, the collar, and the wheel as a system. The forces acting on this system at the wheel are the traction force and a constraint force perpendicular to  $\bar{v}_B$ . The only other force of concern is the normal force exerted on the collar. We show these forces in a free-body diagram that also defines the generalized coordinates. The  $xyz$  coordinate system in this diagram is attached to the bar. The  $x'y'z'$  system is attached to the wheel, but the fact that this body is axisymmetric enables us to take the  $x'$  axis to be horizontal without loss of generality.



Free-body diagram showing generalized coordinates

The constraint that collar  $A$  must follow the guide bar is identically satisfied by these variables, because  $\ell$  is the sole variable affecting the position of the collar, so that  $\bar{v}_A = -\dot{\ell}\bar{I} = -\dot{\gamma}_2\bar{I}$ . The constraint that  $\bar{v}_B$  be parallel to the orientation of the wheel must be enforced explicitly. Because points  $A$  and  $B$  belong to bar  $AB$ , it must be that  $\bar{v}_B = \bar{v}_A + \dot{\theta}\bar{k} \times \bar{r}_{B/A}$ . To be sure that the appropriate rate variables are recognized as quasi-velocities, we denote them as  $\dot{\gamma}$  rather than use their symbolic name. Hence the velocity of point  $B$  is described as

$$\begin{aligned} \bar{v}_B &= v_B (\cos \beta \bar{i} + \sin \beta \bar{j}) \\ &= \dot{\gamma}_2 (-\cos \theta \bar{i} + \sin \theta \bar{j}) + \dot{\gamma}_1 \bar{k} \times L \bar{i}. \end{aligned}$$

Matching like components in the preceding equation gives two simultaneous equations for  $v_B$  in terms of  $\dot{\gamma}_1$  and  $\dot{\gamma}_2$ . Eliminating  $v_B$  gives the constraint equation, and the resulting expression for  $v_B$  will soon be needed. The constraint equation is

$$\dot{\gamma}_1 L \cos \beta + \dot{\gamma}_2 \sin (\theta + \beta) = 0, \quad (3) \triangleleft$$

and the speed of end  $B$  is

$$v_B = -\dot{\gamma}_2 \frac{\cos \theta}{\cos \beta}. \quad (4)$$

Collar  $A$  translates, and bar  $AB$  is in general planar motion with angular acceleration  $\ddot{\theta}$  about the vertical axis. In contrast, the wheel executes a general three-dimensional motion. Hence the Gibbs–Appell function for this system is given by

$$S = \frac{1}{2}m_1 a_G^2 + \frac{1}{2}I_G \dot{\gamma}_1^2 + \frac{1}{2}m_2 a_A^2 + \frac{1}{2}m_3 a_B^2 + \frac{1}{2} \left( \bar{\alpha} \cdot \frac{\partial \bar{H}_B}{\partial t} \right)_{\text{wheel}} + [\bar{\alpha} \cdot (\bar{\omega} \times \bar{H}_B)]_{\text{wheel}}. \quad (5)$$

The only rate variables allowed in  $S$  are the quasi-velocities. Expressions for the point accelerations are readily obtained from the facts that all points reside on bar  $AB$  and that collar  $A$  translates to the left at  $\dot{\gamma}_2$ . Thus,

$$\begin{aligned} \bar{a}_A &= \dot{\gamma}_2 (-\cos \theta \bar{i} + \sin \theta \bar{j}), \\ \bar{a}_G &= \bar{a}_A + \dot{\gamma}_1 \bar{k} \times \frac{L}{2} \bar{i} - \frac{L}{2} \dot{\gamma}_1^2 \bar{i} = \left( -\dot{\gamma}_2 \cos \theta - \frac{L}{2} \dot{\gamma}_1^2 \right) \bar{i} + \left( \frac{L}{2} \dot{\gamma}_1 + \dot{\gamma}_2 \sin \theta \right) \bar{j}, \\ \bar{a}_B &= \bar{a}_A + \dot{\gamma}_1 \bar{k} \times L \bar{i} - L \dot{\gamma}_1^2 \bar{i} = (-\dot{\gamma}_2 \cos \theta - L \dot{\gamma}_1^2) \bar{i} + (L \dot{\gamma}_1 + \dot{\gamma}_2 \sin \theta) \bar{j}. \end{aligned} \quad (6)$$

Because the wheel rolls without slipping, its rotational motion consists of a spin about its axle at angular speed  $v_B/R$ , where  $R$  is the wheel's radius, accompanied by a precession about the vertical axis at angular speed  $\dot{\theta} + \dot{\beta}$ . Therefore

$$\bar{\omega}_{\text{wheel}} = \frac{v_B}{R} \bar{j}' + (\dot{\gamma}_1 + \dot{\beta}) \bar{k}'.$$

The parameter  $v_B$  is not a quasi-coordinate, so we use Eq. (4) to eliminate it:

$$\bar{\omega}_{\text{wheel}} = -\frac{\dot{\gamma}_2 \cos \theta}{R \cos \beta} \bar{j}' + (\dot{\gamma}_1 + \dot{\beta}) \bar{k}'. \quad (7)$$

This expression is generally valid, so it may be differentiated. In doing so, it is important to recognize that  $\beta$  is time dependent, so that

$$\begin{aligned} \bar{\alpha}_{\text{wheel}} &= \left( -\frac{\dot{\gamma}_2 \cos \theta}{R \cos \beta} + \frac{\dot{\gamma}_1 \dot{\gamma}_2 \sin \theta}{R \cos \beta} - \frac{\dot{\gamma}_2 \dot{\beta} \cos \theta \sin \beta}{R (\cos \beta)^2} \right) \bar{j}' \\ &\quad - \frac{\dot{\gamma}_2 \cos \theta}{R \cos \beta} [(\dot{\gamma}_1 + \dot{\beta}) \bar{k}' \times \bar{j}'] + (\dot{\gamma}_1 + \dot{\beta}) \bar{k}' \\ &= \left( -\frac{\dot{\gamma}_2 \cos \theta}{R \cos \beta} + \frac{\dot{\gamma}_1 \dot{\gamma}_2 \sin \theta}{R \cos \beta} - \frac{\dot{\gamma}_2 \dot{\beta} \cos \theta \sin \beta}{R (\cos \beta)^2} \right) \bar{j}' \\ &\quad + \frac{\dot{\gamma}_2 (\dot{\gamma}_1 + \dot{\beta}) \cos \theta}{R \cos \beta} \bar{i}' + (\dot{\gamma}_1 + \dot{\beta}) \bar{k}'. \end{aligned} \quad (8)$$

### 9.3 Formulations with Quasi-Coordinates

609

When the components of  $\bar{\omega}$  and  $\bar{\alpha}$  are denoted symbolically, with  $\omega_x = 0$  in the present case, the portion of  $S$  attributable to the wheel's rotation is

$$\begin{aligned} S_{\text{rot}} &= \frac{1}{2} (\alpha_x \bar{i}' + \alpha_y \bar{j}' + \alpha_z \bar{k}') \cdot (I_2 \alpha_x \bar{i}' + I_1 \alpha_y \bar{j}' + I_2 \alpha_z \bar{k}') \\ &\quad + (\alpha_x \bar{i}' + \alpha_y \bar{j}' + \alpha_z \bar{k}') \cdot [(\omega_y \bar{j}' + \omega_z \bar{k}') \times (I_1 \omega_y \bar{j}' + I_2 \omega_z \bar{k}')] \\ &= \frac{1}{2} (I_2 \alpha_x^2 + I_1 \alpha_y^2 + I_2 \alpha_z^2) + (I_2 - I_1) \alpha_x \omega_y \omega_z. \end{aligned}$$

Writing  $S_{\text{rot}}$  in this symbolic form enables us to recognize that, because neither the angular velocity components nor  $\alpha_x$  contains quasi-accelerations, the first and last terms in the preceding equation may be ignored. Furthermore, terms that do not contain either quasi-acceleration may be ignored when  $\alpha_y$  and  $\alpha_z$  are squared. We extract the  $\bar{\alpha}$  components from Eq. (8), and substitute them into  $S_{\text{rot}}$ , with the result that

$$\begin{aligned} S_{\text{rot}} &= \frac{1}{2} I_1 \left[ \left( \frac{\ddot{y}_2 \cos \theta}{R \cos \beta} \right)^2 - 2 \frac{\ddot{y}_2 \cos \theta}{R \cos \beta} \left( \frac{\dot{y}_1 \dot{y}_2 \sin \theta}{R \cos \beta} \right. \right. \\ &\quad \left. \left. - \frac{\dot{y}_2 \dot{\beta} \cos \theta \sin \beta}{R (\cos \beta)^2} \right) + \dots \right] + \frac{1}{2} I_2 (\ddot{y}_1 + \ddot{\beta})^2. \end{aligned}$$

Substitution of the acceleration terms, Eqs. (6), into Eq. (5) yields the other terms of  $S$ . Once again, terms that do not contain quasi-accelerations are ignored when the other contributions to  $S$  are formed. The evaluation proceeds as follows:

$$\begin{aligned} S &= \frac{1}{2} m_1 \left[ \left( -\ddot{y}_2 \cos \theta - \frac{L}{2} \dot{y}_1^2 \right)^2 + \left( \frac{L}{2} \ddot{y}_1 + \ddot{y}_2 \sin \theta \right)^2 \right] \\ &\quad + \frac{1}{2} \left( \frac{1}{12} m_1 L^2 \right) \ddot{y}_1^2 + \frac{1}{2} m_2 \ddot{y}_2^2 + \frac{1}{2} m_3 \left[ \left( -\ddot{y}_2 \cos \theta - L \dot{y}_1^2 \right)^2 \right. \\ &\quad \left. + (L \ddot{y}_1 + \ddot{y}_2 \sin \theta)^2 \right] + S_{\text{rot}} \\ &= \frac{1}{2} m_1 \left[ \ddot{y}_2^2 + \ddot{y}_2 \dot{y}_1^2 L \cos \theta + \frac{1}{4} L^2 \dot{y}_1^2 + \ddot{y}_1 \ddot{y}_2 L \sin \theta + \dots \right] \\ &\quad + \frac{1}{2} \left( \frac{1}{12} m_1 L^2 \right) \ddot{y}_1^2 + \frac{1}{2} m_2 \ddot{y}_2^2 + \frac{1}{2} m_3 \left[ \ddot{y}_2^2 + 2 \ddot{y}_2 \dot{y}_1^2 L \cos \theta \right. \\ &\quad \left. + L^2 \dot{y}_1^2 + 2 \ddot{y}_1 \ddot{y}_2 L \sin \theta + \dots \right] + S_{\text{rot}}. \end{aligned}$$

We collect like terms and substitute  $S_{\text{rot}}$  to find

$$\begin{aligned} S &= \frac{1}{2} \left( \frac{1}{3} m_1 + m_3 \right) L^2 \dot{y}_1^2 + \frac{1}{2} (m_2 + m_1 + m_3) \ddot{y}_2^2 \\ &\quad + \frac{1}{2} (m_1 + 2m_3) L (\ddot{y}_1 \ddot{y}_2 \sin \theta + \ddot{y}_2 \dot{y}_1^2 \cos \theta) \end{aligned}$$



$$\begin{aligned}
 & + \frac{1}{2} \frac{I_1}{R^2} \left[ \left( \dot{\gamma}_2 \frac{\cos \theta}{\cos \beta} \right)^2 - 2 \dot{\gamma}_2 \frac{\cos \theta}{\cos \beta} \left( \dot{\gamma}_1 \dot{\gamma}_2 \frac{\sin \theta}{\cos \beta} \right. \right. \\
 & \left. \left. - \dot{\gamma}_2 \dot{\beta} \frac{\cos \theta \sin \beta}{(\cos \beta)^2} \right) + \dots \right] + \frac{1}{2} I_2 (\ddot{\gamma}_1 + \ddot{\beta})^2.
 \end{aligned} \tag{9}$$

The last aspect to be considered prior to evaluating the equations of motion is the role of the forces. The spring is conservative, and its deformation is the difference between the current and original length of the spring, so that

$$V = \frac{1}{2} k (\ell - \ell_0)^2.$$

The coefficients required convert derivatives of  $V$  to generalized coordinates are found from kinematical equations (1) and (2) to be

$$\frac{\partial \dot{\ell}}{\partial \dot{\gamma}_1} = 0, \quad \frac{\partial \dot{\ell}}{\partial \dot{\gamma}_2} = 1.$$

Correspondingly the contribution of the spring force to the generalized forces is

$$(\Gamma_1)_k = -\frac{\partial V}{\partial \ell} \frac{\partial \dot{\ell}}{\partial \dot{\gamma}_1} = 0, \quad (\Gamma_2)_k = -\frac{\partial V}{\partial \ell} \frac{\partial \dot{\ell}}{\partial \dot{\gamma}_2} = -k (\ell - \ell_0).$$

The thrust  $\bar{F}$  is not conservative. The virtual displacement of point  $B$ , where it is applied, may be obtained from the initial expression for  $\bar{v}_B$ , which was

$$\bar{v}_B = -\dot{\gamma}_2 \cos \theta \bar{i} + (\dot{\gamma}_1 L + \dot{\gamma}_2 \sin \theta) \bar{j}.$$

The infinitesimal displacement of this point is  $\bar{v}_B dt$ , and changing each  $\dot{\gamma} dt$  to  $\delta \gamma_j$  gives the virtual displacement:

$$\delta \bar{r}_B = -\delta \gamma_2 \cos \theta \bar{i} + (\delta \gamma_1 L + \delta \gamma_2 \sin \theta) \bar{j}.$$

The corresponding virtual work done by  $\bar{F}$  is

$$\begin{aligned}
 \delta W_F &= F (\cos \beta \bar{i} + \sin \beta \bar{j}) \cdot \delta \bar{r}_B \\
 &= F \delta \gamma_2 (-\cos \beta \cos \theta + \sin \beta \sin \theta) + F L \sin \beta \delta \gamma_1.
 \end{aligned}$$

The generalized forces are the coefficients of each  $\delta \gamma_j$ , so

$$(\Gamma_1)_F = F L \sin \beta, \quad (\Gamma_2)_F = -F \cos (\theta + \beta).$$

The constraint of collar  $A$  is implicitly satisfied for all values of the generalized coordinates and quasi-velocities, so the normal constraint force acting on the collar does not contribute to the virtual work. The same is not true for  $\bar{N}_B$ , which makes the wheel move in the intended direction. This force is associated with constraint equation (3), so we may describe its contribution to the generalized force with a Lagrange multiplier by using the Jacobian coefficients of Eq. (3), which are

$$A_{1,1} = L \cos \beta, \quad A_{1,2} = \sin (\theta + \beta).$$

### 9.3 Formulations with Quasi-Coordinates

611

Thus the generalized forces corresponding to the quasi-coordinates are

$$\begin{aligned}\Gamma_1 &= FL \sin \beta + \lambda_1 L \cos \beta, \\ \Gamma_2 &= -F \cos (\theta + \beta) - k (\ell - \ell_0) + \lambda_1 \sin (\theta + \beta).\end{aligned}$$

The least difficult aspect of forming the Gibbs–Appell equations is evaluating the derivatives. The first equation is  $\partial S / \partial \ddot{\gamma}_1 = \Gamma_1$ , which evaluates to

$$\begin{aligned}\left(\frac{1}{3}m_1 + m_3\right)L^2\ddot{\gamma}_1 + \frac{1}{2}(m_1 + 2m_3)L\ddot{\gamma}_2 \sin \theta \\ + I_2(\ddot{\gamma}_1 + \ddot{\beta}) = FL \sin \beta + \lambda_1 L \cos \beta.\end{aligned}\quad (10)$$

The second Gibbs–Appell equation,  $\partial S / \partial \ddot{\gamma}_1 = \Gamma_1$ , is

$$\begin{aligned}(m_1 + m_2 + m_3)\ddot{\gamma}_2 + \frac{1}{2}(m_1 + 2m_3)L(\ddot{\gamma}_1 \sin \theta + \dot{\gamma}_1^2 \cos \theta) \\ + \frac{I_1}{R^2}\left[\ddot{\gamma}_2\left(\frac{\cos \theta}{\cos \beta}\right)^2 - \frac{\cos \theta}{\cos \beta}\left(\dot{\gamma}_1\dot{\gamma}_2\frac{\sin \theta}{\cos \beta} - \dot{\gamma}_2\dot{\beta}\frac{\cos \theta \sin \beta}{(\cos \beta)^2}\right)\right] \\ = -F \cos (\theta + \beta) - k (\ell - \ell_0) + \lambda_1 \sin (\theta + \beta).\end{aligned}\quad (11)$$

Thus we have obtained five equations of the differential-algebraic type, consisting of these two Gibbs–Appell equations, the two kinematical equations, Eqs. (1) and (2), and the constraint equation, Eq. (3). The variables for these equations are  $\dot{\gamma}_1$ ,  $\dot{\gamma}_2$ ,  $\theta$ ,  $\ell$ , and  $\lambda_1$ . The highest order of the derivatives of the variables is one, and those derivatives occur linearly. Hence, any of the techniques in Subsection 8.2.1 may be employed directly to obtain the response for specified initial conditions.

**EXAMPLE 9.10** Consider the system in Example 9.9. Determine the Gibbs–Appell equations of motion using unconstrained quasi-coordinates.

**SOLUTION** A comparison of this solution with the preceding one will enable us to judge the merits of eliminating the constraint equations through the use of constrained generalized coordinates. Another feature of this example is its usage of a quasi-velocity that is not a derivative of a generalized coordinate. This system has one degree of freedom. The single unconstrained quasi-velocity we use is the speed of the wheel's center:

$$\dot{\gamma}_1 = v_B.$$

As we did in the preceding example, we let the generalized coordinates be  $q_1 = \theta$ ,  $q_2 = \ell$ .

Enforcing the condition that the collar must move along its guide leads to the kinematical equations. It is necessary that  $\bar{v}_A = \bar{v}_B + \bar{\omega}_{AB} \times \bar{r}_{A/B}$ , and we know the directions in which both end points move. It actually is preferable for this system to use as the global coordinate system stationary  $XYZ$ , with  $X$  to the right and  $Y$  upward in the previous sketch, rather than the body-fixed  $xyz$  coordinate system used previously. Thus we have

$$-\dot{\ell}\bar{I} = v_B [\cos(\theta + \beta)\bar{I} + \sin(\theta + \beta)\bar{J}] + \dot{\theta}_1 \bar{K} \times L(-\cos\theta\bar{I} - \sin\theta\bar{J}).$$

Matching like components gives

$$-\dot{\ell} = v_B \cos(\theta + \beta) + L\dot{\theta} \sin\theta,$$

$$0 = v_B \sin(\theta + \beta) - L\dot{\theta} \cos\theta.$$

The solution of these equations for  $\dot{\theta}$  and  $\dot{\ell}$  in terms of  $v_B$  are the kinematical equations:

$$\begin{aligned} \dot{\theta} &= \frac{v_B \sin(\theta + \beta)}{L \cos\theta}, \\ \dot{\ell} &= -v_B \left[ \cos(\theta + \beta) + \frac{\sin(\theta + \beta)}{\cos\theta} \sin\theta \right] \equiv -v_B \frac{\cos\beta}{\cos\theta}. \end{aligned} \quad (1)$$

All parts have significant inertia, and the wheel is executing a rotation about two axes, so the Gibbs–Appell function is

$$\begin{aligned} S &= \frac{1}{2}m_1 a_G^2 + \frac{1}{2}I_G \ddot{\theta}^2 + \frac{1}{2}m_2 a_A^2 + \frac{1}{2}m_3 a_B^2 \\ &\quad + \frac{1}{2} \left( \bar{\alpha} \cdot \frac{\partial \bar{H}_B}{\partial t} \right)_w + [\bar{\alpha} \cdot (\bar{\omega} \times \bar{H}_B)]_w. \end{aligned} \quad (2)$$

The only rate variables that may appear in  $S$  are  $v_B$  and  $\dot{v}_B$ . This requires that we eliminate  $\ddot{\theta}$  and  $\ddot{\ell}$ , so we differentiate Eqs. (1) to find that

$$\begin{aligned} \ddot{\theta} &= \frac{\dot{v}_B \sin(\theta + \beta)}{L \cos\theta} + \frac{v_B (\dot{\theta} + \dot{\beta}) \cos(\theta + \beta)}{L \cos\theta} + \frac{v_B \dot{\theta} \sin(\theta + \beta) \sin\theta}{L (\cos\theta)^2} \\ &= \frac{\dot{v}_B \sin(\theta + \beta)}{L \cos\theta} + \frac{v_B^2 \sin(\theta + \beta) \cos\beta}{L^2 (\cos\theta)^3} + \frac{v_B \dot{\beta} \cos(\theta + \beta)}{L \cos\theta}, \\ \ddot{\ell} &= -\dot{v}_B \frac{\cos\beta}{\cos\theta} - v_B \dot{\theta} \frac{\sin\theta \cos\beta}{(\cos\theta)^2} + v_B \dot{\beta} \frac{\sin\beta}{\cos\theta} \\ &= -\dot{v}_B \frac{\cos\beta}{\cos\theta} - \frac{v_B^2 \sin(\theta + \beta) \sin\theta \cos\beta}{L (\cos\theta)^3} + v_B \dot{\beta} \frac{\sin\beta}{\cos\theta}. \end{aligned} \quad (3)$$

Note that these forms were obtained by use of the first of Eqs. (1) to eliminate  $\dot{\theta}$  because that variable is not a quasi-velocity.

### 9.3 Formulations with Quasi-Coordinates

613

We know that  $|\bar{a}_A| = \ddot{\ell}$ , but describing the other variables appearing in  $S$  requires a kinematical analysis. To describe  $\bar{a}_B$  we differentiate the component representation of  $\bar{v}_B$  and again use Eqs. (1) to eliminate  $\dot{\theta}$ . This gives

$$\begin{aligned}\bar{a}_B &= \frac{d}{dt} [v_B \cos(\theta + \beta) \bar{I} + v_B \sin(\theta + \beta) \bar{J}] \\ &= \dot{v}_B [\cos(\theta + \beta) \bar{I} + \sin(\theta + \beta) \bar{J}] + v_B (\dot{\theta} + \dot{\beta}) [-\sin(\theta + \beta) \bar{I} + \cos(\theta + \beta) \bar{J}] \\ &= \left[ \dot{v}_B \cos(\theta + \beta) - \frac{v_B^2 (\sin(\theta + \beta))^2}{L \cos \theta} - v_B \dot{\beta} \sin(\theta + \beta) \right] \bar{I} \\ &\quad + \left[ \dot{v}_B \sin(\theta + \beta) + \frac{v_B^2 \sin(\theta + \beta) \cos(\theta + \beta)}{L \cos \theta} + v_B \dot{\beta} \cos(\theta + \beta) \right] \bar{J}. \quad (4)\end{aligned}$$

It is not necessary to describe the motion of the center of mass explicitly, because the consequence of its being the midpoint is that

$$\bar{v}_G = \frac{1}{2} (\bar{v}_A + \bar{v}_B), \quad \bar{a}_G = \frac{1}{2} (\bar{a}_A + \bar{a}_B). \quad (5)$$

We use the  $x'y'z'$  coordinate system defined in the preceding example to describe the contribution of the wheel to  $S$ . The corresponding angular velocity and angular acceleration are found by the standard method to be

$$\begin{aligned}\bar{\omega}_w &= \frac{v_B}{R} \bar{j}' + (\dot{\theta} + \dot{\beta}) \bar{k}', \\ \bar{\alpha}_w &= \frac{\dot{v}_B}{R} \bar{j}' + \frac{v_B}{R} [(\dot{\theta} + \dot{\beta}) \bar{k}' \times \bar{j}'] + (\ddot{\theta} + \ddot{\beta}) \bar{k}'.\end{aligned}$$

Substitution of Eqs. (1) and (3) to eliminate  $\dot{\theta}$  and  $\ddot{\theta}$  yields

$$\begin{aligned}\bar{\omega}_w &= \frac{v_B}{R} \bar{j}' + \left( \frac{v_B \sin(\theta + \beta)}{L \cos \theta} + \dot{\beta} \right) \bar{k}', \\ \bar{\alpha}_w &= - \left[ \frac{v_B^2 \sin(\theta + \beta)}{LR \cos \theta} + \frac{v_B \dot{\beta}}{R} \right] \bar{i}' + \frac{\dot{v}_B}{R} \bar{j}' + \left[ \frac{v_B \sin(\theta + \beta)}{L \cos \theta} \right. \\ &\quad \left. + \frac{v_B^2 \sin(\theta + \beta) \cos \beta}{L^2 (\cos \theta)^3} + \frac{v_B \dot{\beta} \cos(\theta + \beta)}{L \cos \theta} + \dot{\beta} \right] \bar{k}'. \quad (6)\end{aligned}$$

The next step is to use Eqs. (3)–(6) to form the individual terms in  $S$ . As a start, we use Eqs. (5) to replace  $\bar{a}_G$  in  $S$ , and also account for the facts that  $\bar{a}_A = -\ddot{\ell} \bar{I}$  and  $\bar{\omega}_w$  has no component in the  $x'$  direction, from which it follows that

$$\begin{aligned}S &= \frac{1}{8} m_1 (\bar{a}_A \cdot \bar{a}_A + 2\bar{a}_A \cdot \bar{a}_B + \bar{a}_B \cdot \bar{a}_B) + \frac{1}{2} I_G \ddot{\theta}^2 + \frac{1}{2} m_2 a_A^2 + \frac{1}{2} m_3 a_B^2 \\ &\quad + \frac{1}{2} (I_{xx} a_x^2 + I_{yy} a_y^2 + I_{zz} a_z^2)_{\text{wheel}} + (\alpha_x \bar{i} + \alpha_y \bar{j} + \alpha_z \bar{k}) \cdot [(\omega_y \bar{j} + \omega_z \bar{k}) \\ &\quad \times (I_{yy} \omega_y \bar{j} + I_{zz} \omega_z \bar{k})]_{\text{wheel}}\end{aligned}$$

$$= \frac{1}{8} (m_1 + 4m_2) \ddot{\ell}^2 + \frac{1}{8} (m_1 + 4m_3) \ddot{a}_B \cdot \ddot{a}_B - \frac{1}{4} m_1 \ddot{\ell} \ddot{I} \cdot \ddot{a}_B \\ + \frac{1}{2} I_G \ddot{\theta}^2 + \frac{1}{2} (I_{yy} a_y^2 + I_{zz} a_z^2)_w + \dots$$

The terms that are omitted from the preceding equation are associated with the wheel's rotation, but do not contain  $\dot{v}_B$ . We substitute Eqs. (3), (4), and (6) into this description of  $S$  to find that

$$S = \frac{1}{8} (m_1 + 4m_2) \left[ -\dot{v}_B \frac{\cos \beta}{\cos \theta} - \frac{v_B^2}{L} \frac{\sin(\theta + \beta) \sin \theta \cos \beta}{(\cos \theta)^3} + v_B \dot{\beta} \frac{\sin \beta}{\cos \theta} \right]^2 \\ + \frac{1}{8} (m_1 + 4m_3) \left[ \dot{v}_B \cos(\theta + \beta) - \frac{v_B^2}{L} \frac{(\sin(\theta + \beta))^2}{\cos \theta} - v_B \dot{\beta} \sin(\theta + \beta) \right]^2 \\ + \frac{1}{8} (m_1 + 4m_3) \left[ \dot{v}_B \sin(\theta + \beta) + \frac{v_B^2}{L} \frac{\sin(\theta + \beta) \cos(\theta + \beta)}{\cos \theta} \right. \\ \left. + v_B \dot{\beta} \cos(\theta + \beta) \right]^2 - \frac{1}{4} m_1 \left[ -\dot{v}_B \frac{\cos \beta}{\cos \theta} - \frac{v_B^2}{L} \frac{\sin(\theta + \beta) \sin \theta \cos \beta}{(\cos \theta)^3} \right. \\ \left. + v_B \dot{\beta} \frac{\sin \beta}{\cos \theta} \right] \left[ \dot{v}_B \cos(\theta + \beta) - \frac{v_B^2}{L} \frac{(\sin(\theta + \beta))^2}{\cos \theta} - v_B \dot{\beta} \sin(\theta + \beta) \right] \\ + \frac{1}{2} I_G \left[ \frac{\dot{v}_B \sin(\theta + \beta)}{L \cos \theta} + \frac{v_B^2}{L^2} \frac{\sin(\theta + \beta) \cos \beta}{(\cos \theta)^3} + \frac{v_B \dot{\beta} \cos(\theta + \beta)}{L \cos \theta} \right]^2 \\ + \frac{1}{2} I_1 \left( \frac{\dot{v}_B}{R} \right)^2 + \frac{1}{2} \left[ \frac{\dot{v}_B \sin(\theta + \beta)}{L \cos \theta} + \frac{v_B^2}{L^2} \frac{\sin(\theta + \beta) \cos \beta}{(\cos \theta)^3} \right. \\ \left. + \frac{v_B \dot{\beta} \cos(\theta + \beta)}{L \cos \theta} + \dot{\beta} \right]^2.$$

When the products appearing in this expression are evaluated, the quasi-acceleration  $\dot{v}_B$  will appear in  $S$  in only three combinations:  $\dot{v}_B^2$ ,  $\dot{v}_B v_B^2/L$ , or  $\dot{v}_B v_B \dot{\beta}$ . All other terms are unimportant, so the final form of  $S$  may be written as

$$S = \frac{1}{2} S_1(v_B, \theta, \beta) \dot{v}_B^2 + S_2(v_B, \theta, \beta) \dot{v}_B v_B^2/L + S_3(v_B, \theta, \beta) \dot{v}_B v_B \dot{\beta}. \quad (7)$$

It still remains to describe the effect of the forces. The spring force is conservative, so its influence is described by the potential energy. The current length of the spring is  $\ell$ , and its unstretched length is  $\ell_0$ , from which it follows that

$$V = \frac{1}{2} k (\ell - \ell_0)^2.$$

### 9.3 Formulations with Quasi-Coordinates

617

The difficulty with applying the dynamic virtual work principle directly is the need to identify suitable virtual movements for various parts of a system. This issue was addressed earlier by considering virtual displacements that are produced by differential increments of the generalized coordinates, which led to Lagrange's equations. Now we consider the implication of describing virtual displacements in terms of differentials  $\delta\gamma_j$  associated with the quasi-coordinates. The virtual displacement of points in this case is given by Eq. (9.3.8), and a similar relation applies for virtual rotation. The inertial terms in Eq. (9.3.43) already require that we express the velocity of the center of mass and the angular velocity of each body in terms of the  $\dot{\gamma}_j$ . Hence this means that for each body we can derive the required virtual displacements from the corresponding velocity variables:

$$\begin{aligned}\bar{v}_{Gk} &= \sum_{j=1}^N (\bar{v}_{Gk})_j \dot{\gamma}_j + (\bar{v}_{Gk})_0 \implies \delta\bar{r}_{Gk} = \sum_{j=1}^K (\bar{v}_{Gk})_j \delta\gamma_j, \\ \bar{\omega}_k &= \sum_{j=1}^N (\bar{\omega}_k)_j \dot{\gamma}_j + (\bar{\omega}_k)_0 \implies \delta\bar{\theta}_k = \sum_{j=1}^N (\bar{\omega}_k)_j \delta\gamma_j.\end{aligned}\tag{9.3.44}$$

It is necessary that we also derive similar expressions for the point where each force is applied and the body to which each couple is applied. When we substitute these representations of virtual displacements and rotations into Eq. (9.3.43), and collect like coefficients of  $\delta\gamma_j$ , the result is

$$\begin{aligned}\sum_{j=1}^N \left\{ \sum_k \left[ -m_k \bar{a}_{Gk} \cdot (\bar{v}_{Gk})_j + \left( -\frac{d\bar{H}_{Gk}}{dt} \right) \cdot (\bar{\omega}_k)_j \right] \right. \\ \left. + \sum_n \bar{F}_n \cdot (\bar{v}_n)_j + \sum_n \bar{M}_n \cdot (\bar{\omega}_n)_j \right\} \delta\gamma_j = 0.\end{aligned}\tag{9.3.45}$$

We now invoke the usual argument that independence of the  $\delta\gamma_j$  quantities requires that the coefficient of each virtual increment vanish. Thus we obtain *Kane's equations*:

$$\begin{aligned}\sum_k \left[ m_k \bar{a}_{Gk} \cdot (\bar{v}_{Gk})_j + \left( \frac{d\bar{H}_{Gk}}{dt} \right) \cdot (\bar{\omega}_k)_j \right] \\ = \sum_n \bar{F}_n \cdot (\bar{v}_n)_j + \sum_n \bar{M}_n \cdot (\bar{\omega}_n)_j; \quad j = 1, \dots, K.\end{aligned}\tag{9.3.46}$$

There is one Kane's equation for each quasi-coordinate. In addition to the quasi-velocities, the variables in these equations will be the  $N$  generalized coordinates and the  $J$  constraint forces associated with the kinematical constraints conditions that are not automatically satisfied. As is true for the Gibbs–Appell equations,  $N$  kinematical equations in the form of Eq. (9.3.5), which give the generalized velocities  $\dot{q}_j$  in terms of the current  $\dot{\gamma}_j$  and  $q_j$  values, and  $J$  velocity constraint equations supplement Kane's equations.

One interpretation of Kane's equations comes from considering a physical velocity to consist of quasi-velocities measured parallel to corresponding directions vectors  $(\bar{v})_j$

or  $(\bar{\omega})_j$ , which are not unit vectors. It is evident from Eqs. (9.3.44) that

$$(\bar{v}_{Gk})_j \equiv \frac{\partial}{\partial \dot{\gamma}_j} \bar{v}_{Gk}, \quad (\bar{\omega}_k)_j \equiv \frac{\partial}{\partial \dot{\gamma}_j} \bar{\omega}_k. \quad (9.3.47)$$

For this reason the  $(\bar{v}_{Gk})_j$  and  $(\bar{\omega}_k)_j$  are referred to as *partial velocities*. Thus Kane's equations constitute components, in a generalized sense, of the combined dynamic force and moment equilibrium equations for a system in the directions of each partial velocity. Kane's choice to call the  $\dot{\gamma}_j$  values *generalized speeds* does not acknowledge the prior reference to them as quasi-velocities in other formulations. More profoundly, Kane's equations are typically stated in texts devoted to Kane's approach [see, for example, Kane and Levinson (1985)] directly as a new concept, without placing them in the context of prior development. From the author's perspective, it seems unlikely that one would arrive at this concept without considering the principle of dynamic virtual work.

### 9.3.4 Relationship of the Formulations

The relationship of Kane's equations to the Gibbs–Appell equations has been the topic of much discussions. Although the alternative formulations are derived quite differently, they lead to the same differential equations of motion governing a specific set of generalized coordinates and quasi-velocities. The first step in recognizing this equivalence comes from returning to the virtual work expressed in terms of quasi-coordinates, Eq. (9.3.45). The terms containing the force resultants  $\bar{F}_n$  and moment resultants  $\bar{M}_n$  represent the virtual work done by all forces. A comparison with Eq. (9.3.38) shows that the Kane equation terms containing the actual forces are merely the generalized forces  $\Gamma_j$  associated with quasi-coordinates when one ignores whether a force is conservative or imposes a constraint. Thus we can rewrite Eq. (9.3.46) as

$$\sum_k \left[ m_k \bar{a}_{Gk} \cdot (\bar{v}_{Gk})_j + \left( \frac{d\bar{H}_{Gk}}{dt} \right) \cdot (\bar{\omega}_k)_j \right] = \Gamma_j, \quad j = 1, \dots, K. \quad (9.3.48)$$

Now let us consider the left side of the Gibbs–Appell equations when  $S$  is the sum of the contributions of several bodies, with each term defined by Eq. (9.3.32). In any case we may take point  $A$  for each body to be the center of mass  $G$ . Both  $\bar{\omega}$  and  $\bar{H}_G$  depend on velocity variables, but not accelerations. Hence the derivative of  $S_k$  for body  $k$  with respect to  $\dot{\gamma}_j$  is

$$\begin{aligned} \frac{\partial S_k}{\partial \dot{\gamma}_j} &= m \left( \bar{a}_{Gk} \cdot \frac{\partial \bar{a}_{Gk}}{\partial \dot{\gamma}_j} \right) + \frac{1}{2} \frac{\partial \bar{\alpha}_k}{\partial \dot{\gamma}_j} \cdot \frac{\partial \bar{H}_{Gk}}{\partial t} + \frac{1}{2} \bar{\alpha}_k \cdot \frac{\partial}{\partial \dot{\gamma}_j} \left( \frac{\partial \bar{H}_{Gk}}{\partial t} \right) \\ &\quad + \frac{\partial \bar{\alpha}_k}{\partial \dot{\gamma}_j} \cdot (\bar{\omega}_k \times \bar{H}_{Gk}) \\ &= m \left( \bar{a}_{Gk} \cdot \frac{\partial \bar{a}_{Gk}}{\partial \dot{\gamma}_j} \right) + \frac{\partial \bar{\alpha}_k}{\partial \dot{\gamma}_j} \cdot \frac{d\bar{H}_{Gk}}{dt} - \frac{1}{2} \frac{\partial \bar{\alpha}_k}{\partial \dot{\gamma}_j} \cdot \frac{\partial \bar{H}_{Gk}}{\partial t} \\ &\quad + \frac{1}{2} \bar{\alpha}_k \cdot \frac{\partial}{\partial \dot{\gamma}_j} \left( \frac{\partial \bar{H}_{Gk}}{\partial t} \right). \end{aligned} \quad (9.3.49)$$

### 9.3 Formulations with Quasi-Coordinates

619

To progress further it is convenient to recall the matrix representation of  $\partial \bar{H}_{Gk}/\partial t$ , when  $\bar{\omega}_k$  is represented in terms of components relative to body-fixed axes:

$$\left\{ \frac{\partial H_{Gk}}{\partial t} \right\} = [I_k] \{\alpha_k\}. \quad (9.3.50)$$

In this representation  $[I_k]$  is constant, so we have

$$\bar{\alpha}_k \cdot \frac{\partial}{\partial \dot{\gamma}_j} \left( \frac{\partial \bar{H}_{Gk}}{\partial t} \right) = \{\alpha_k\}^T \frac{\partial}{\partial \dot{\gamma}_j} \left\{ \frac{\partial H_{Gk}}{\partial t} \right\} = \{\alpha_k\}^T [I_k] \left\{ \frac{\partial \alpha_k}{\partial \dot{\gamma}_j} \right\}. \quad (9.3.51)$$

Because  $[I_k]$  is symmetric, we also have

$$\begin{aligned} \frac{\partial \bar{\alpha}_k}{\partial \dot{\gamma}_j} \cdot \frac{\partial \bar{H}_{Gk}}{\partial t} &= \left\{ \frac{\partial \alpha_k}{\partial \dot{\gamma}_j} \right\}^T \left\{ \frac{\partial H_{Gk}}{\partial t} \right\} = \left\{ \frac{\partial \alpha_k}{\partial \dot{\gamma}_j} \right\}^T [I_k] \{\alpha_k\} \\ &= \{\alpha_k\}^T [I_k] \left\{ \frac{\partial \alpha_k}{\partial \dot{\gamma}_j} \right\} = \bar{\alpha}_k \cdot \frac{\partial}{\partial \dot{\gamma}_j} \left( \frac{\partial \bar{H}_{Gk}}{\partial t} \right). \end{aligned} \quad (9.3.52)$$

This reduces Eq. (9.3.49) to

$$\frac{\partial S_k}{\partial \dot{\gamma}_j} = m \bar{a}_{Gk} \cdot \frac{\partial \bar{a}_{Gk}}{\partial \dot{\gamma}_j} + \frac{\partial \bar{\alpha}_k}{\partial \dot{\gamma}_j} \cdot \frac{d \bar{H}_{Gk}}{dt}. \quad (9.3.53)$$

The final step is to recall the discussion centered around Eq. (9.3.15). As we did there, we consider the time derivative of a velocity that is expressed in terms of quasi-coordinates. The variables of interest now are the derivatives of the velocity of the center of mass and the angular velocity, which are described by Eqs. (9.3.44). The result may be written as

$$\begin{aligned} \bar{a}_{Gk} &= \sum_{j=1}^N (\bar{v}_{Gk})_j \dot{\gamma}_j + \sum_{j=1}^N \left[ \frac{d}{dt} (\bar{v}_{Gk})_j \right] \dot{\gamma}_j + \frac{d}{dt} (\bar{v}_{Gk})_0, \\ \bar{\alpha}_k &= \sum_{j=1}^N (\bar{\omega}_k)_j \dot{\gamma}_j + \sum_{j=1}^N \left[ \frac{d}{dt} (\bar{\omega}_k)_j \right] \dot{\gamma}_j + \sum_{j=1}^N \left[ \frac{d}{dt} (\bar{\omega}_k)_j \right] \dot{\gamma}_j + \frac{d}{dt} (\bar{\omega}_k)_0. \end{aligned} \quad (9.3.54)$$

Our focus here is the dependence on the  $\dot{\gamma}_j$  parameters. Such dependence cannot result from differentiating the partial velocities, which depend on only the generalized coordinates. Thus we find that

$$\frac{\partial \bar{a}_{Gk}}{\partial \dot{\gamma}_j} \equiv (\bar{v}_{Gk})_j, \quad \frac{\partial \bar{\alpha}_k}{\partial \dot{\gamma}_j} \equiv (\bar{\omega}_k)_j. \quad (9.3.55)$$

Substitution of these relations into Eq. (9.3.53) yields

$$\frac{\partial S_k}{\partial \dot{\gamma}_j} = m \bar{a}_{Gk} \cdot (\bar{v}_{Gk})_j + \frac{d \bar{H}_{Gk}}{dt} \cdot (\bar{\omega}_k)_j. \quad (9.3.56)$$


This term is the quantity within the summation in Kane's equations, Eq. (9.3.48). Because  $S$  for a system is the sum of the  $S_k$  of each body, we conclude that the Gibbs–Appell equations and Kane's equations will yield identical differential equations of motion governing a specified set of generalized coordinates and quasi-coordinates.



Gibbs–Appell or Kane’s equation formulations will be the same. Furthermore, if the quasi-velocities actually are generalized velocities, then both yield the same equations of motion as those obtained by Lagrange’s equations. Both the Gibbs–Appell and Kane’s formulations have strong advocates. There also are other formulations of the equations of motion. All are obviously related by the fact that they describe the same system subject to the same set of axioms, Newton’s Laws. The mathematical relationship between the various formulations has been extensively explored by Papastavridis (2002). In special circumstances one approach might prove to be advantageous. The author’s experience has been that Lagrange’s equations, supplemented by the Newton–Euler equations to provide physical insight, serve well as an overall tool for a broad range of engineering problems.

**EXAMPLE 9.11** Use Kane’s equations to derive the differential equations of motion of the wheelbarrow in Example 9.8.

**SOLUTION** The objective here is to compare the operations required to implement Kane’s equations and the Gibbs–Appell equations. We proceed as though we had not previously solved this problem using the Gibbs–Appell equations, except that we call on the previous results of the kinematical analysis. We begin with a free-body diagram of the system. In this diagram the  $m\bar{a}$  vector for each center of mass and the centroidal  $d\bar{H}/dt$  for each body are shown as dashed lines in order to identify them as the inertial effects. (In situations in which there are many bodies and/or many forces, it might be advantageous to draw separate diagrams for the actual forces and their inertial equivalents.) Note that, because the wheelbarrow is in planar motion,  $d\bar{H}_G/dt$  for it reduces to  $I\ddot{\theta}$  about the vertical axis.




Free-body diagram of the wheelbarrow showing the equivalent inertial effects

We use the same generalized coordinates and quasi-velocities as in the previous analysis, so  $q_1 = X_C$ ,  $q_2 = Y_C$ ,  $q_3 = \theta$ ,  $\dot{q}_1 = v$ ,  $\dot{q}_2 = \dot{\theta}$ . It is helpful to use Eqs. (9.3.47) to describe the partial velocities explicitly when we write Kane’s

into smaller steps, and one can gain some physical insights by examining the forcing effects in the directions associated with the partial velocities.

**EXAMPLE 9.12** Use Kane's equations with  $\dot{q}_1 = v_B$  and  $q_1 = \theta$ ,  $q_2 = \ell$  to derive equations of motion for the steerable linkage in Example 9.10.

**SOLUTION** As a closure to our exploration of alternative techniques for deriving equations of motion, we apply Kane's equations to a system in which the derivation of the Gibbs–Appell function encountered considerable complexity. Whether the same level of complexity is encountered here is a key question to be addressed. We begin with a free-body diagram. For the sake of clarity, we use separate diagrams to describe the actual forces and the inertial equivalents. (The diagram on the left is like the one in Example 9.9, except that it now shows the fixed  $XYZ$  coordinate system that is selected as the global system.) Bar  $AB$  is in planar motion, so the forces acting on it are equivalent to a force  $m_1 \bar{a}_G$  at the center of mass and a couple  $I_G \ddot{\theta}$  acting about the vertical axis. Collar  $A$  follows its stationary guide in any movement because the quasi-velocity is unconstrained. Hence the inertial effect for this body is merely  $m_2 \bar{a}_A$  along the guide. In contrast, the wheel executes a spatial rotation, so the equivalent system is a force  $m_3 \bar{a}_B$  and a couple  $(d\bar{H}_B/dt)_w$ .



Actual forces and their inertial equivalents

There is no need to carry out a kinematical analysis here, because the present motion variables are the same as those previously used to describe  $S$ . The only quasi-velocity is  $v_B$ , so Kane's equation for this system is

$$\begin{aligned} m_1 \bar{a}_G \cdot \frac{\partial \bar{v}_G}{\partial v_B} + I_G \ddot{\theta} \frac{\partial \dot{\theta}}{\partial v_B} + (-m_2 \ddot{\ell} \bar{I}) \cdot \frac{\partial \bar{v}_A}{\partial v_B} + m_3 \bar{a}_B \cdot \frac{\partial \bar{v}_B}{\partial v_B} + \left( \frac{d\bar{H}_B}{dt} \right)_w \cdot \frac{\partial \bar{\omega}_w}{\partial v_B} \\ = k \Delta \bar{I} \cdot \frac{\partial \bar{v}_A}{\partial v_B} + F [\cos(\theta + \beta) \bar{I} + \sin(\theta + \beta) \bar{J}] \cdot \frac{\partial \bar{v}_B}{\partial v_B}. \end{aligned}$$

It should be noted that the reaction forces  $\bar{N}_A$  and  $\bar{N}_B$  do not appear here because the respective partial velocities will be perpendicular to these constraint forces as a result of using unconstrained quasi-coordinates. Before we perform the main

$$\begin{aligned}
 & -v_B \dot{\beta} \sin(\theta + \beta)] \cos(\theta + \beta) + \left( \frac{1}{4} m_1 + m_3 \right) \left[ \dot{v}_B \sin(\theta + \beta) \right. \\
 & \left. + \frac{v_B^2}{L} \frac{\sin(\theta + \beta) \cos(\theta + \beta)}{\cos \theta} + v_B \dot{\beta} \cos(\theta + \beta) \right] \sin(\theta + \beta) \\
 & - \frac{1}{4} m_1 \left[ -\dot{v}_B \frac{\cos \beta}{\cos \theta} - \frac{v_B^2}{L} \frac{\sin(\theta + \beta) \sin \theta \cos \beta}{(\cos \theta)^3} \right. \\
 & \left. + v_B \dot{\beta} \frac{\sin \beta}{\cos \theta} \right] \cos(\theta + \beta) - \frac{1}{4} m_1 [\dot{v}_B \cos(\theta + \beta) \\
 & - \frac{v_B^2}{L} \frac{(\sin(\theta + \beta))^2}{\cos \theta} - v_B \dot{\beta} \sin(\theta + \beta)] \left( -\frac{\cos \beta}{\cos \theta} \right) \\
 & + I_G \left[ \frac{\dot{v}_B}{L} \frac{\sin(\theta + \beta)}{\cos \theta} + \frac{v_B^2}{L^2} \frac{\sin(\theta + \beta) \cos \beta}{(\cos \theta)^3} \right. \\
 & \left. + \frac{v_B \dot{\beta} \cos(\theta + \beta)}{L \cos \theta} \right] \frac{1}{L} \frac{\sin(\theta + \beta)}{\cos \theta} + I_1 \left( \frac{\dot{v}_B}{R} \right) \frac{1}{R} \\
 & + \left[ \frac{\dot{v}_B}{L} \frac{\sin(\theta + \beta)}{\cos \theta} + \frac{v_B^2}{L^2} \frac{\sin(\theta + \beta) \cos \beta}{(\cos \theta)^3} \right. \\
 & \left. + \frac{v_B \dot{\beta} \cos(\theta + \beta)}{L \cos \theta} + \ddot{\beta} \right] \frac{1}{L} \frac{\sin(\theta + \beta)}{\cos \theta} \\
 & = k(\ell - \ell_0) \frac{\cos \beta}{\cos \theta} + F.
 \end{aligned}$$

We could go on to simplify this equation of motion by collecting the coefficients of  $\dot{v}_B$ ,  $v_B^2/L$ , and  $v_B \dot{\beta}$ . There is no need to do so in the present context, because the main features are evident. We see that, for a given set of generalized coordinates and quasi-velocities, the effort to analyze the kinematical features of a system is the same for the Gibbs–Appell equations and Kane’s equations. From that common starting point, the steps leading to the final equations are considerably less intricate for Kane’s equations. The comparison of the two examples here suggests that this aspect is more important than the ability to construct the Gibbs–Appell function in a standard procedure.

## SELECTED REFERENCES

- Appell, P., “Sur les mouvements de roulement; Equations du mouvement analogues celles de lagrange,” *Comptes Rendus* **129**, 317–320 (1899).  
 Ardema, M. D., *Analytical Dynamics: Theory and Applications*, Kluwer Academic/Plenum, New York (2005).

## HOMEWORK PROBLEMS

**EXERCISE 9.1** The kinetic and potential energies of a stretched cable are

$$T = \frac{1}{2} \mu \int_0^L \dot{w}^2 dx,$$

$$V = F \left[ \int_0^L \left( 1 + (w')^2 \right)^{1/2} dx - L \right] + \int_0^L w \mu g dx,$$

where  $w(x, t)$  is the transverse displacement. Only unforced motion is of interest, so  $\delta W = 0$ . Use Hamilton's Principle to derive the nonlinear field equation and the associated boundary conditions at  $x = 0$  and  $x = L$ . The square root term in  $V$  may be approximated by a three-term truncation of its series expansion for  $|w'| \ll 1$ .

**EXERCISE 9.2** The transverse vibration of a straight beam according to linear theory is described by a function  $w(x, t)$  that is the displacement of the beam's centerline. The energy functionals and virtual work are

$$T = \frac{1}{2} \int_0^L \mu \dot{w}^2 dx,$$

$$V = \frac{1}{2} \int_0^L EI (w'')^2 dx + \int_0^L w \mu g dx,$$

$$\delta W = \int_0^L f(x, t) \delta w dx,$$

where  $\mu$  is the mass per unit length and  $EI$  is the bending rigidity, both of which can depend on  $x$ . Also,  $f(x, t)$  is the transverse load per unit length. Use Hamilton's Principle to derive the field equation governing  $w$ , as well as the possible boundary conditions. Recall that  $\delta w$  is an arbitrary, but selected, function of  $x$ . Consequently, all derivatives of  $\delta w$  are defined by  $\delta w$  in the interior region  $0 < x < L$ , whereas  $w$  and its derivatives are mutually independent at  $x = 0$  and  $x = L$ .

**EXERCISE 9.3** Torsion of a short bar whose cross section is not circular features warping of the cross section. This means that, in addition to exhibiting an overall torsional rotation  $\theta(x, t)$ , a cross section at distance  $x$  along the beam will also undergo a displacement in the axial direction that varies with position on the cross section. Approximate potential- and kinetic-energy functionals capturing this effect are

$$T = \frac{1}{2} \int_0^L \rho J \dot{\theta}^2 dx,$$

$$V = \frac{1}{2} \int_0^L \left[ GJ \left( \frac{\partial \theta}{\partial x} \right) + E\Gamma \left( \frac{\partial^2 \theta}{\partial x^2} \right) \right]^2 dx,$$

where  $GJ$  and  $E\Gamma$  are cross-section properties that may depend on  $x$ . Use Hamilton's Principle to derive the field equation governing  $w$ , as well as the possible boundary conditions corresponding to unforced motions.

The virtual displacement field in this case consists of independent fields  $\delta w_y(x, t)$  and  $\delta w_z(x, t)$ , both of which must be continuously differentiable in order to be kinematically admissible. Use Hamilton's Principle to derive the pair of differential equations governing  $w_y$  and  $w_z$ , as well as the possible boundary conditions pertaining to each displacement component.


**EXERCISE 9.7** It is desired to use the Ritz series method to derive approximate equations describing the effects of nonlinearity in the vibration of the stretched cable in Exercise 9.1. Both ends are stationary, so that  $w = 0$  at  $x = 0$  and  $x = L$ , which means that suitable basis functions are  $\psi_j = \sin(j\pi x/L)$ . Derive the differential equations governing the two-term Ritz series that uses these basis functions.

**EXERCISE 9.8** The energy functionals for flexural vibration of a beam are given in Exercise 9.2. A cantilever beam is one in which one end is not permitted to displace or rotate, corresponding to  $w = \partial w/\partial x = 0$  at  $x = 0$ , while the other end,  $x = L$ , is free to move. Suitable basis functions have the form  $\psi_j = (x/L)^{j+p}$ , where  $p$  is an integer. (a) Identify the lowest value of  $p$  that is appropriate to the cantilever beam. (b) Derive the equations for the Ritz series coefficients when the series is truncated at two terms and  $p$  has the value in Part (a). The cross-sectional properties are constant, and the transverse loading is a uniformly distributed harmonic excitation,  $f(x, t) = F_0 \sin(\Omega t)$ .

**EXERCISE 9.9** The energy functionals for an axially loaded beam are given in Exercise 9.4. A cantilever beam is one in which one end is not permitted to displace or rotate, corresponding to  $w = \partial w/\partial x = 0$  at  $x = 0$ , while the other end,  $x = L$ , is free to move. Use a three-term Ritz series for the transverse displacement to derive approximate equations for this beam's vibration in the presence of the axial force.

**EXERCISE 9.10** Both ends of a cable like the one described in Exercise 9.5 are fixed, so suitable basis functions for both displacement components are  $\sin(j\pi x/L)$ . The cable is excited by a uniformly distributed transverse load in the  $xy$  plane,  $f_y(x, t) = F_0 \sin(\Omega t)$ ,  $f_z = 0$ . Use a two-term Ritz series for each transverse displacement component to derive approximate equations describing the whirling response. All terms in the differential equations may be truncated at cubic powers of the Ritz series coefficients, which means that Taylor series expansions of the energy functionals may be truncated at quartic powers of  $w_y$  and  $w_z$ .

**EXERCISE 9.11** Torsional excitation  $\Gamma$  acting about the vertical shaft causes the T-bar to rotate at angular speed  $\Omega$ . Collars  $A$  and  $B$  are connected by an inextensible cable. Derive Hamilton's equations of motion governing  $\Omega$  and the radial distance  $R$  to a collar based on the assumption that the cable remains taut.



Exercise 9.11

to derive the equations of motion for this system corresponding to the interval during which the rod remains in contact with the wall.

**EXERCISE 9.48** Use Kane's formulation to derive the equations of motion of the steerable linkage in Example 9.9 when  $\dot{\theta}$  and  $\dot{\ell}$  are selected as the quasi-velocities.

**EXERCISE 9.49** Derive Kane's equations governing the steerable linkage in Example 9.9 when the speed  $v$  of the wheel is used as the sole quasi-velocity.

**EXERCISE 9.50** Beth, the tricycle rider in Exercise 8.14, steers by applying a known torque  $M$  to the handlebars. Derive Kane's equations corresponding to using the speed  $v_A$  of the center of the front wheel, the chassis rotation rate  $\dot{\theta}$ , and the steering rate  $\dot{\beta}$  as unconstrained quasi-velocities. The inertia of the rear wheels may be ignored.

**EXERCISE 9.51** Derive Kane's equations of motion governing a set of unconstrained quasi-velocities for the sphere on a rotating turntable in Exercise 8.23.

## CHAPTER 10

# Gyroscopic Effects

The focus thus far has been on the derivation of equations of motion for rigid-body motion. Sometimes the goal was to characterize the force system required to produce a specified motion, while other situations entailed where the response was not known, which led to differential equations of motion. Both situations will be encountered in this chapter, where the common thread is the prominent role of gyroscopic action. Such phenomena are exploited in gyroscopes, whose theory will be introduced here. However, much can be learned about the nature of dynamical responses by beginning with studies of simpler, yet more common, systems that display similar effects.

## 10.1 FREE MOTION

One of the first types of spatial motion treated in basic physics and engineering courses on mechanics is projectile motion, whose study is devoted to the determination of the motion of the center of mass. In contrast, the manner in which the body rotates about its center of mass is seldom discussed in a fundamental course. Our study of free rotation will be based on the assumption that the only external force is gravitational attraction acting at the center of mass. The corollary is that the resultant moment about the center of mass is zero, from which it follows that

$$\boxed{\vec{H}_G \text{ is constant.}} \quad (10.1.1)$$

A further corollary of taking the resultant moment to be zero is that the rotational motion occurs independently of the motion of the center of mass. In reality, aerodynamic forces acting on a body may be represented as a force–couple system acting at the mass center. Such forces depend on the orientation (angle of attack) as well as on the overall velocity. Hence, accurate models of the motion of objects through the air might require consideration of coupling between the translational and rotational motions.

### 10.1.1 Axisymmetric Bodies


An axisymmetric body, whose shape is obtained by rotating a curve about the axis of symmetry, and whose mass is independent of the azimuthal angle relative to that axis, has special inertial properties. Specifically, if the axis of symmetry is one of the coordinate axes, then the coordinate system is principal with the moments of inertia about the other two axes having equal values. Without loss of generality, we select the  $z$  axis to be

the axis of symmetry, and correspondingly let  $I_{zz} = I$  and  $I_{xx} = I_{yy} = I'$ . (Actually, any body having two equal principal moments of inertia behaves inertially as though it were axisymmetric. The analysis that follows is valid for the free motion of any such object, provided that the  $z$  axis is aligned with the axis that has the distinct moment of inertia.)

The constant value of  $\bar{H}_G$  in corollary (10.1.1) can be determined if the angular velocity is known at the instant the body is released. The direction of this constant vector defines a reference for studying the response. Let us define this direction as the  $Z$  axis for a translating reference frame  $XYZ$ , so we have

$$\bar{K} = \frac{\bar{H}_G}{|\bar{H}_G|}. \quad (10.1.2)$$

We define  $Z$  to be the precession axis for a set of Eulerian angles and let the body's axis of symmetry be the spin axis. The nutation angle is measured between the precession and spin axes, so we have the situation in Fig. 10.1. The body-fixed  $x$  axis depicted there is the centroidal transverse axis that lies in the plane containing the space-fixed  $Z$  axis and the body-fixed  $z$  axis at the instant of interest.



**Figure 10.1.** Free-body diagram and Eulerian angles for free rotation of an axisymmetric body.

The angular velocity corresponding to an arbitrary set of Eulerian angles is the precessional, spinning, and nutational rotations. The latter occurs about the line of nodes, which is perpendicular to both the precession and spin axes. This direction is opposite the sense of the  $y$  axis associated with Fig. 10.1, so

$$\bar{\omega} = \dot{\psi} \bar{K} - \dot{\theta} \bar{j} + \dot{\phi} \bar{k} = \dot{\psi} \sin \theta \bar{i} - \dot{\theta} \bar{j} + (\dot{\psi} \cos \theta + \dot{\phi}) \bar{k}. \quad (10.1.3)$$

We can use this description of  $\bar{\omega}$  to construct  $\bar{H}_G$ . A different representation comes from the observation that  $\bar{H}_G$  lies in the  $Zz$  plane at an angle  $\theta$  from the  $z$  axis, so we have

$$\begin{aligned} \bar{H}_G &= I' \dot{\psi} \sin \theta \bar{i} - I' \dot{\theta} \bar{j} + I (\dot{\psi} \cos \theta + \dot{\phi}) \bar{k} \\ &= H_G \sin \theta \bar{i} + H_G \cos \theta \bar{k}. \end{aligned} \quad (10.1.4)$$

These alternative representations must be consistent, which requires that

$$I' \dot{\psi} \sin \theta = H_G \sin \theta, \quad I' \dot{\theta} = 0, \quad I (\dot{\psi} \cos \theta + \dot{\phi}) = H_G \cos \theta. \quad (10.1.5)$$

Solving these relations for the rotation rates yields


$$\dot{\psi} = \frac{H_G}{I'}, \quad \dot{\theta} = 0, \quad \dot{\phi} = \left( \frac{1}{I} - \frac{1}{I'} \right) H_G \cos \theta. \quad (10.1.6)$$



## 10.1 Free Motion

639

This shows that the free rotation of an axisymmetric body is characterized by a steady spinning rotation about the axis of symmetry, accompanied by a steady precession about an axis that is parallel to the angular momentum, with an invariant nutation angle between these axes.



**Figure 10.2.** Evaluation of the Eulerian angle properties and angular momentum when the angular velocity of an axisymmetric body is known.

Presumably, the body's orientation and angular velocity are known when it was released. As noted earlier, this allows us to construct  $\bar{H}_G$ , from which we may determine  $\theta$ . Let us formalize this construction. Because  $\dot{\theta} = 0$ , it must be that  $\bar{\omega}$ ,  $\bar{H}_G$ , and the  $z$  axis are coplanar. Therefore the initial condition must be as depicted in Fig. 10.2, where the vector  $\bar{\omega}$  and its angle  $\beta$  from the  $z$  axis presumably are known as initial conditions. We may construct the components of  $\bar{\omega}$  from this angle. When we use these components to construct  $\bar{H}_G$ , we obtain a representation that must match either form in Eqs. (10.1.4), so it must be that


$$\begin{aligned}\bar{H}_G \cdot \bar{k} &= I(\omega \cos \beta) = I(\dot{\psi} \cos \theta + \dot{\phi}) = H_G \cos \theta, \\ \bar{H}_G \cdot \bar{i} &= I'(\omega \sin \beta) = I'\dot{\psi} \sin \theta = H_G \sin \theta.\end{aligned}\quad (10.1.7)$$

Eliminating all kinematical parameters except  $\omega$  and  $\beta$  from these relations yields

$$\begin{aligned}\tan \theta &= \frac{I'}{I} \tan \beta, \\ \dot{\psi} &= \frac{H_G}{I'} = \left[ (\sin \beta)^2 + \left( \frac{I}{I'} \cos \beta \right)^2 \right]^{1/2} \omega, \\ \dot{\phi} &= \left( 1 - \frac{I}{I'} \right) \omega \cos \beta.\end{aligned}\quad (10.1.8)$$

It is evident that there are two cases to consider, depending in whether  $I'/I$  is less than or greater than unity. If the body is slender, like a javelin, then  $I' > I$ , whereas  $I' < I$  for an oblate body, such as a disk. (In the case of a sphere, for which  $I' = I$ ,  $\bar{H}_G$  is always parallel to  $\bar{\omega}$ , so there is no need to distinguish between  $\dot{\psi}$  and  $\dot{\phi}$ .) The rotation of a slender body is such  $\theta > \beta$  and  $\dot{\phi}$  has the same sign as  $\omega$  if  $\beta < 90^\circ$ . (Cases in which  $\beta > 90^\circ$  are best treated by reversing the sense of the  $z$  axis.) The property that  $\dot{\phi}$  and  $\omega$  have the same sign indicates that the spin is in the same sense as the overall rotation; this is said to be a *regular precession*. Conversely, an oblate body executes a *retrograde precession*, in which the spin is in the opposite sense from the overall rotation ( $\dot{\phi}/\omega < 0$  when  $\beta < 90^\circ$ ). In this case  $\theta < \beta$ .

The picture provided by Fig. 10.2 is descriptive of any instant, provided we recognize that, because of the precession, the plane depicted by this figure rotates about the  $Z$  axis. Thus the angular velocity is situated on a cone whose axis coincides with  $Z$  and whose semivertex angle is  $\theta - \beta$ . The significance of this observation is that  $\bar{\omega}$  determines the velocity of points relative to the center of mass, according to  $\bar{v}_{P/G} = \bar{\omega} \times \bar{r}_{P/G}$ . Thus every point on a line parallel to  $\bar{\omega}$  and intersecting point  $G$  is not moving relative to point  $G$ . This leads us to a conceptual model formed from (right circular) space and body cones. The space cone consists of the locus of the vector  $\bar{\omega}$  from the viewpoint of an observer translating with the center of mass when the tail of  $\bar{\omega}$  is placed at that point. Thus  $\bar{H}_G$  defines the axis of the space cone, and  $|\theta - \beta|$  is the semivertex angle. The body cone represents the locus of the same  $\bar{\omega}$  vector from the perspective of an observer who moves in unison with the body. Hence the body cone's semivertex angle is  $\beta$ , and its axis is the body's axis of symmetry. The free rotation of the body may be visualized by letting the body cone, which is attached to the body, roll without slipping over the stationary space cone. The line of contact for this rolling motion is parallel to  $\bar{\omega}$  at the instant of interest.



**Figure 10.3.** Body and space cones for free motion. The body cone and the body are shaded. (a) Regular precession, (b) retrograde precession.

Because  $\theta > \beta$  for a regular precession such as the one in Fig. 10.3(a), the exterior of the body cone in this case rolls over the exterior of the space cone. The precession describes the rotation of the body cone's axis about the axis marked by  $\bar{H}_G$ , and the spin rate is such that points on the body cone that contact the space cone have zero velocity relative to the center of mass. Retrograde precession, which is depicted in Fig. 10.3(b), features  $\beta > \theta$ , so the space cone is interior to the body cone. In this case the sense of  $\omega$  indicates the sense of the precession, but the spin takes place in the opposite sense. The term "retrograde" stems from the perception that the body is spinning oppositely to the sense of its overall rotation.

**EXAMPLE 10.1** A football has an instantaneous velocity of 25 m/s parallel to its longitudinal axis,  $z$ , and it is spinning about that axis at 5 rev/s. At that instant, the ball is deflected by a transverse force  $\bar{F}$  at the forward tip. As a result of the action of  $\bar{F}$ , whose duration is very short, the ensuing motion relative to the center of mass is such that the longitudinal axis always lies on the surface of a cone whose apex

The expression for  $(\bar{H}_G)_2$  in Eqs. (1) indicates that  $\omega_x = 0$  at the instant when  $\bar{F}$  terminates and  $\omega_y > 0$  and  $\omega_z < 0$ . Hence the angular velocity at that instant must be

$$\bar{\omega} = \omega (\sin \beta \bar{j} - \cos \beta \bar{k}) = \omega (0.18526 \bar{j} - 0.9027 \bar{k}).$$

The corresponding angular momentum is

$$(\bar{H}_G)_2 = I' \omega_y \bar{j} + I \omega_z \bar{k} = m \omega (0.9078 \bar{j} - 1.5723 \bar{k})(10^{-3}).$$

Matching this to  $(\bar{H}_G)_2$  in Eqs. (1) yields

$$\begin{aligned} m \omega (0.9078)(10^{-3}) &= 0.125 F (\Delta t), \\ m \omega (-1.5723)(10^{-3}) &= -0.05027 m, \end{aligned} \quad (3)$$

from which we find that

$$\omega = 31.97 \text{ rad/s}, \quad \frac{F (\Delta t)}{m} = 0.2322 \text{ m/s}.$$

This defines the final value of  $\bar{\omega}$ , and the corresponding value of  $\bar{v}_G$  is given by the first of Eqs. (1),

$$\bar{\omega} = 5.923 \bar{j} - 31.42 \bar{k} \text{ rad/s}, \quad (\bar{v}_G)_2 = 0.2322 \bar{j} + 25 \bar{k} \text{ m/s}. \quad \triangleleft$$


The precession axis is parallel to  $(\bar{H}_G)_2$ , so we have

$$\bar{K} = \frac{(\bar{H}_G)_2}{|(\bar{H}_G)_2|} = 0.500 \bar{j} - 0.8660 \bar{k}. \quad \triangleleft$$

Note that the angle between  $\bar{K}$  and  $\bar{k}$ , that is, between the symmetry and precession axes, is  $\cos^{-1}(-0.8660) = 150^\circ$ , in agreement with the stated conditions.

From these results we may draw a sketch of the position of the body cone relative to the space cone at the initiation of the free motion. We also show  $(\bar{v}_G)_2$  in that sketch. The corresponding precession and spin rates are found from Eqs. (10.1.8):

$$\dot{\psi} = 11.85 \text{ rad/s}, \quad \dot{\theta} = 21.16 \text{ rad/s}. \quad \triangleleft$$



Movement of the football subsequent to application of the impulsive force.

## 10.1 Free Motion

643

### 10.1.2 Arbitrary Bodies

Analysis of the free motion of an arbitrary body proceeds similarly to the treatment of axisymmetric bodies. The analysis is substantially simplified by defining  $xyz$  to be the body's principal centroidal axes. The principal moments of inertia are denoted as  $I_{xx} = I_1$ ,  $I_{yy} = I_2$ , and  $I_{zz} = I_3$ . Even though the body has arbitrary inertia properties,  $\bar{H}_G$  must still be constant, so the fixed  $Z$  axis for precession  $\psi$  is again defined again to coincide with this vector. The other Eulerian angles are defined consistently with the conventions established in Section 4.2. Thus the spin  $\phi$  occurs about the principal axis denoted as  $z$ , the nutation angle  $\theta$  is measured from  $Z$  to  $z$ , and the line of nodes is perpendicular to the plane formed by the  $Z$  and  $z$  axes.

The intermediate  $x'y'z'$  coordinate system, which only precesses and nutates, facilitates the description of  $\bar{\omega}$ . The  $z'$  axis is defined to coincide with the  $z$  axis, and the  $y'$  axis is parallel to the line of nodes in the sense of the right-hand rule from  $Z$  to  $z$ . The angular velocity is then

$$\bar{\omega} = \dot{\psi} \bar{K} + \dot{\theta} \bar{j}' + \dot{\phi} \bar{k}. \quad (10.1.9)$$

We can use projections or rotation transformations to resolve  $\bar{K}$  and  $\bar{j}'$  into  $xyz$  components, with the result that

$$\begin{aligned} \bar{K} &= -\sin \theta \cos \phi \bar{i} + \sin \theta \sin \phi \bar{j} + \cos \phi \bar{k}, \\ \bar{j}' &= \sin \phi \bar{i} + \cos \phi \bar{j}. \end{aligned} \quad (10.1.10)$$

The corresponding representation of the angular velocity is

$$\begin{aligned} \bar{\omega} &= (-\dot{\psi} \sin \theta \cos \phi + \dot{\theta} \sin \phi) \bar{i} + (\dot{\psi} \sin \theta \sin \phi + \dot{\theta} \cos \phi) \bar{j} \\ &\quad + (\dot{\psi} \cos \phi + \dot{\phi}) \bar{k}. \end{aligned} \quad (10.1.11)$$

As was true for axisymmetric bodies, the angular momentum can be constructed from this description of  $\bar{\omega}$ , as well as from the fact that it coincides with the  $Z$  axis. Thus it must be that

$$\begin{aligned} \bar{H}_G &= H_G \bar{K} = H_G (-\sin \theta \cos \phi \bar{i} + \sin \theta \sin \phi \bar{j} + \cos \phi \bar{k}) \\ &= I_1 (-\dot{\psi} \sin \theta \cos \phi + \dot{\theta} \sin \phi) \bar{i} + I_2 (\dot{\psi} \sin \theta \sin \phi + \dot{\theta} \cos \phi) \bar{j} \\ &\quad + I_3 (\dot{\psi} \cos \phi + \dot{\phi}) \bar{k}. \end{aligned} \quad (10.1.12)$$

The constant value of  $\bar{H}_G$  is set by the initial conditions, in the form of a known value of  $\bar{\omega}$ . If the components of the initial angular velocity are denoted as  $(\omega_x)_0$ ,  $(\omega_y)_0$ , and  $(\omega_z)_0$ , the corresponding angular momentum is

$$\bar{H}_G = H_G \bar{K} = I_1 (\omega_x)_0 \bar{i} + I_2 (\omega_y)_0 \bar{j} + I_3 (\omega_z)_0 \bar{k}. \quad (10.1.13)$$

It follows that

$$H_G = \left[ I_1^2 (\omega_x)_0^2 + I_2^2 (\omega_y)_0^2 + I_3^2 (\omega_z)_0^2 \right]^{1/2}.$$

## 10.1 Free Motion

645

Specific results regarding stability can be obtained in the case in which a body is released with an initial rotation rate  $\Omega$  about a principal axis. Without loss of generality, we define this axis to be the  $z$  axis for the Eulerian angles. We may take the initial spin rate to be  $\Omega$ , corresponding to  $\theta = 0$ , whereas the initial precession rate and nutation angle are both zero. The case in which  $\sin \theta = 0$  was excluded from Eqs. (10.1.15), so we return to Eqs. (10.1.14). These equations are identically satisfied by constant  $\theta = 0$  or  $\pi$ ,  $\dot{\psi} = 0$ , and  $\dot{\phi} = H_G/\Omega$ . Thus a pure spinning motion about any of the principal axes is a possible type of rotation. However, we are not likely to impart an initial rotation to a body in which the axis of rotation is exactly aligned with one of the principal axes. Even if we could, any temporary disturbance, such as a mild gust of wind, would alter the initial rotation. A more realistic expectation is that, because of a small error, the initial motion will feature nutation and precession rates that are much smaller than  $\Omega$ , with the initial nutation angle being small. To study the ensuing rotation we perform a linearized perturbation analysis. If an evaluation of the response confirms that these small initial perturbations remain small for all  $t$ , then we may conclude that the rotation is stable. In contrast, a result indicating that the the disturbances grow merely means that the ensuing rotation will differ much from the initial motion.

The disturbed response is represented as

$$\dot{\phi} = \Omega + \varepsilon \dot{\xi}_3, \quad \theta = \varepsilon \xi_2, \quad \psi = \varepsilon \xi_1, \quad (10.1.16)$$

where the  $\xi_n$  parameters are time functions that are taken to be unit order and the perturbation parameter  $\varepsilon$ , which scales the magnitude of the disturbance, is a positive number much less than unity. Note that this representation considers the precession and spin nutation angles to be small values, whereas the spin angle is approximately  $\Omega t$ . We obtain the easiest derivation of solvable equations for these parameters by substituting this representation into Eqs. (10.1.14). After we do so, we apply small-angle approximations to the trigonometric terms, which leads to

$$\begin{aligned} I_1 [(\varepsilon \dot{\xi}_1) (\varepsilon \xi_2) \cos \phi - \varepsilon \dot{\xi}_2 \sin \phi] &= H_G (\varepsilon \xi_2) \cos \phi, \\ I_2 [(\varepsilon \dot{\xi}_1) (\varepsilon \xi_2) \sin \phi + \varepsilon \dot{\xi}_2 \cos \phi] &= H_G (\varepsilon \xi_2) \sin \phi, \\ I_3 [(\varepsilon \dot{\xi}_1) \cos \phi + (\Omega + \varepsilon \dot{\xi}_3)] &= H_G \cos \theta. \end{aligned} \quad (10.1.17)$$

We retain only the leading-order term in each equation, with the result that

$$\begin{aligned} -I_1 \dot{\xi}_2 \sin \phi &= H_G \xi_2 \cos \phi, \\ I_2 \dot{\xi}_2 \cos \phi &= H_G \xi_2 \sin \phi, \\ I_3 \Omega &= H_G \cos \phi. \end{aligned} \quad (10.1.18)$$

A change of variables that expedites solution of these equations is suggested by the observation that  $\sin \phi$  and  $\cos \phi$  are the direction cosines of  $\bar{j}'$ , which is the line of nodes, relative to the body-fixed  $x$  and  $y$  coordinate axes. Wherever  $\xi_2$  occurs in the perturbation equations, it is multiplied by one of these direction cosines. Because  $\xi_2$  represents the disturbance of the nutation, which is about the line of nodes, let us

define a vector  $\bar{\xi}_2$  parallel to the line of nodes, whose components are  $u$  and  $v$ , such that

$$\begin{aligned}\bar{\xi}_2 &= \xi_2 \bar{j}' = u \bar{i} + v \bar{j}, \\ u &= \xi_2 \sin \phi, \quad v = \xi_2 \cos \phi.\end{aligned}\tag{10.1.19}$$

According to Eqs. (10.1.16), the first approximation of  $\dot{\phi}$  is  $\Omega$ , so differentiation of the preceding equations shows that

$$\begin{aligned}\dot{u} &\approx \dot{\xi}_2 \sin \phi + \Omega \xi_2 \cos \phi = \dot{\xi}_2 \sin \phi + \Omega v, \\ \dot{v} &\approx \dot{\xi}_2 \cos \phi - \Omega \xi_2 \sin \phi = \dot{\xi}_2 \cos \phi - \Omega u.\end{aligned}\tag{10.1.20}$$

We use these relations to eliminate  $\xi_2$  and  $\phi$  from Eqs. (10.1.18), which yields

$$\begin{aligned}I_1 (\dot{u} - \Omega v) &= -I_3 \Omega v, \\ I_2 (\dot{v} + \Omega u) &= I_3 \Omega u.\end{aligned}\tag{10.1.21}$$

These are a pair of coupled, homogeneous, linear differential equations with constant coefficients. Their solution must be exponential in time, so we set

$$u = A \exp(\lambda t), \quad v = B \exp(\lambda t).\tag{10.1.22}$$

Substitution of these forms into Eqs. (10.1.21) gives

$$\begin{bmatrix} I_1 \lambda & (I_3 - I_1) \Omega \\ (I_2 - I_3) \Omega & I_2 \lambda \end{bmatrix} \begin{Bmatrix} A \\ B \end{Bmatrix} = \begin{Bmatrix} 0 \\ 0 \end{Bmatrix}.\tag{10.1.23}$$

This is an eigenvalue problem because the only solution is the trivial one,  $A = B = 0$ , unless the value of  $\lambda$  is such that the determinant of the coefficient matrix vanishes. The characteristic equation obtained from setting this determinant to zero is

$$I_1 I_2 \lambda^2 + (I_3 - I_1)(I_3 - I_2) = 0.\tag{10.1.24}$$

Because the moments of inertia are positive values, the roots of this quadratic equation occur either as a pair of conjugate imaginary values or as real values with opposite signs, depending on the sign of the last term. A positive value of  $\lambda$  corresponds to exponential growth of  $u$  and  $v$ , and therefore of  $\xi_2$ . This is the instability condition, which indicates that the spin axis will not remain close to the precession axis. In contrast, purely imaginary values of  $\lambda$  represent an oscillatory  $\xi_2$ . This is the stable case in which the spin axis remains close to the precession axis.

Recall that  $I_3$  is the moment of inertia about the principal axis for the nominal spin. The stability condition requires  $(I_3 - I_1)(I_3 - I_2) > 0$ , which is satisfied either if  $I_3 > I_1$  and  $I_3 > I_2$ , or else,  $I_3 < I_1$  and  $I_3 < I_2$ . In other words, a body that is released with an initial angular velocity that is essentially a spin about the principal axis having either the largest or smallest moment of inertia will continue to have that type of rotation. An initial spin about the principal axis for which the moment of inertia is the intermediate




Figure 10.4. Poincaré's construction showing the inertia ellipsoid rolling over the invariable plane.

invariable plane. At each instant, a different point on the inertia ellipsoid contacts the invariable plane. The locus of contact points on the inertia ellipsoid is a curve called the *polhode*, whereas the locus on the invariable plane is the *herpolhode*. The herpolhode is generally an open curve, which means that the rotation does not repeat, but the polhode is a closed curve. We may establish the closure of the polhode, as well as the overall nature of these curves, by noting that the inertia ellipsoid represents the constancy of the kinetic energy in the rotational motion. However, the angular momentum is also constant, which means that

$$|\bar{H}_G|^2 = I_{xx}^2 \omega_x^2 + I_{yy}^2 \omega_y^2 + I_{zz}^2 \omega_z^2. \quad (10.1.34)$$

When Eqs. (10.1.28) are used to represent the angular velocity components, the preceding equation becomes

$$I_{xx}^2 x^2 + I_{yy}^2 y^2 + I_{zz}^2 z^2 = \frac{|\bar{H}_G|^2}{2T_{\text{rot}}} = \frac{1}{\rho_H^2} \equiv D. \quad (10.1.35)$$

The usage of  $D$  rather than  $1/\rho_H^2$  is done for convenience. Clearly,  $D$  is constant, so the preceding equation represents another ellipsoid whose origin is at the center of mass and whose principal axes are  $x$ ,  $y$ , and  $z$ . In other words, constancy of the angular momentum's magnitude leads to the conclusion that the point where the inertia ellipsoid contacts the invariable plane is situated on another ellipsoid that is stationary with respect to the body-fixed  $xyz$  coordinate system. The intersection of this ellipsoid with the ellipsoid of inertia, given by Eq. (10.1.25), is the polhode. The closure of the polhode is a direct consequence of the fact that both ellipsoids, and therefore their intersection, rotate with the body.

The value of the constant  $D$  is determined by the initial motion. If this initial state is a rotation about the  $x$  axis, then  $\bar{H}_G = I_{xx} \omega \hat{i}$ , so  $|\bar{H}_G|^2 = 2T_{\text{rot}}/I_{xx}$ . Similar statements apply to initial rotations about the other principal axes. This leads to the observation that initial rotations about each of the principal axes correspond to  $D = I_1$ ,  $I_2$ , and  $I_3$ , respectively. Without loss of generality, we now specify the labeling of the  $xyz$  axes to be such that  $I_1 = I_{xx}$  is the smallest value and  $I_3 = I_{zz}$  is the largest. Then,  $I_1 \leq I_2 \leq I_3$ . We may construct the polhode for a specified value of  $D$  by picking a value of one coordinate, and then solving Eqs. (10.1.25) and (10.1.35) simultaneously for the other two. A visualization that is easier to obtain depicts polhode curves in terms of their projections onto the principal coordinate planes. We derive equations for these projections by

of  $D$  slightly larger than  $I_1$ , leads to a polhode curve projection on the  $y - z$  plane that is a small ellipse. This corresponds to an angular velocity that is always nearly parallel to the  $x$  axis. In contrast, if the initial motion is approximately about the  $y$  axis, then  $D \approx I_2$ . Then the polhode curves are close to the separatrices. Depending on whether  $D$  is greater than or less than  $I_2$ , the closed polhode curve is centered about either the  $z$  axis or the  $x$  axis, respectively. In either case, the angle between  $\omega$  and any of the coordinate axes varies greatly in the motion. This explains why the rotation of an arbitrary body is often difficult to observe.

An axisymmetric body is a special case in which two principal moments of inertia are equal. To match the earlier analysis of axisymmetric bodies, let us place the tail of  $\bar{\omega}$  at the apex of the body cone and divide  $\bar{\omega}$  by  $(2T_{\text{rot}})^{1/2}$ . The vector formed in this manner is the position vector  $\bar{\rho}$  in Poinot's construction. Because the magnitude of  $\bar{\omega}$  for free motion of an axisymmetric body is constant, it must be that the tip of the scaled vector will always be situated on a circular cross section of the body cone. This is the polhode curve. Poinot's construction leads to the same conclusion. The ellipsoid of inertia for an axisymmetric body is spheroidal. Constancy of  $|\bar{H}_G|$  corresponds to another spheroid having the same axis of symmetry. The polhode curve is the intersection of these two spheroids, which is a circular cross section they have in common. Recall that  $\bar{H}_G$  is perpendicular to the cross sections of the space cone. Thus the invariable plane for an axisymmetric body is the cross section of the space cone that contacts the cross section of the body cone that is the polhode curve. In regard to the previous stability analysis, we now see that an initial motion that is almost a pure spin about the axis of symmetry corresponds to a very small radius polhode, which means that the angular velocity does not deviate much from the initial condition. This confirms the earlier analysis. We also can now answer the degenerate case for the previous stability analysis, in which an axisymmetric body is set into motion with a rotation that is almost a pure rotation about a transverse axis. The polhode curve for such a motion is a circle close to the equator of the spheroid. This proximity leads to the conclusion that an axisymmetric body also is stable if it is launched with an angular velocity that is perpendicular to the axis of symmetry. Followers of American football will recognize this as the case of an "end-over-end" kick.

**EXAMPLE 10.2** The  $xyz$  coordinate system in the sketch is a set of body-fixed principal centroidal axes for the 10-kg rectangular plate. At the instant the plate is dropped, the  $y$  axis is horizontal and the  $z$  axis is inclined at  $30^\circ$  from vertical. The angular velocity at that instant lies in the  $xz$  plane at an unspecified angle  $\beta$  from the  $z$  axis. (a) Determine the value of  $\beta$  for which the precession axis is vertical. (b) Determine the maximum value of  $\beta$  for which the angle between the  $z$  axis and the precession axis will not exceed  $90^\circ$  in the rotation after release. (c) For the case in which  $\beta$  is one half the critical value in Part (b), determine the minimum and maximum angles between the plate's normal and the precession axis during the rotation. Evaluate the corresponding angular velocity at these limits.



corresponding to  $D > I_2$ , which surround the  $z$  axis. The tangent plane at any point on such a curve has a normal that forms an acute angle with the  $z$  axis. The limiting case is the separatrix, for which half of the curve lies on a portion of the ellipsoid where the normal is more than  $90^\circ$  from the  $z$  axis. Thus the maximum value of  $\beta$  satisfying the specification in Part (b) is that which gives  $D = I_2$ . The initial rotational kinetic energy for an arbitrary  $\beta$  is found from Eqs. (1) and (2) to be

$$2T_{\text{rot}} = \bar{\omega} \cdot \bar{H}_G = \omega^2 [I_1 (\sin \beta)^2 + I_3 (\cos \beta)^2]. \quad (3)$$

Using this expression to form the critical condition,  $D = I_2$ , leads to

$$D = \frac{|\bar{H}_G|^2}{2T_{\text{rot}}} = \frac{I_1^2 (\sin \beta)^2 + I_3^2 (\cos \beta)^2}{I_1 (\sin \beta)^2 + I_3 (\cos \beta)^2} = I_2. \quad (4)$$

In other words,

$$I_1 (I_2 - I_1) (\sin \beta)^2 = I_3 (I_3 - I_2) (\cos \beta)^2, \\ \beta = \tan^{-1} \left[ \frac{I_3 (I_3 - I_2)}{I_1 (I_2 - I_1)} \right]^{1/2} = 52.239^\circ \quad \begin{cases} \text{for rotation about} \\ \text{the } z \text{ axis} \end{cases}. \quad \triangleleft$$

For Part (c), we set  $\beta = 26.119^\circ$ . The value of  $D$  obtained from Eq. (4) for this angle is

$$D = 0.057798.$$

Because  $D > I_2$ , the polhode curve surrounds the  $z$  axis. Now examine the polhode curve for this case in Fig. 10.6. The minimum and maximum angles between the  $z$  axis and the normal to the tangent plane, which is the fixed precession axis, occur when the polhode curve intersects the  $xz$  plane and  $yz$  plane, respectively. Thus the task of identifying the minimum and maximum angle conditions reduces to establishing the conditions for which the angular velocity has either a zero  $y$  or  $x$  component, respectively. This observation leads us to conclude that the initial motion must represent the minimum angle condition, because it is specified that  $\omega_y = 0$  at that instant. Thus we obtain the minimum angle condition by setting  $\beta = 26.119^\circ$  in Eq. (2), from which we can determine the direction of  $\bar{H}_G$ , which is  $\bar{K}$ :

$$\bar{H}_G = \omega(-0.005283\bar{i} + 0.053873\bar{k}) = H_G \bar{K}.$$

The angle from  $\bar{K}$  to the  $z$  axis is  $\theta$ , so we find that

$$\theta_{\min} = \cos^{-1} \left( \frac{|\bar{H}_G \cdot \bar{k}|}{|\bar{H}_G|} \right) = 5.601^\circ. \quad \triangleleft$$

To determine the maximum angle we seek the solution of the polhode equations corresponding to the preceding value of  $D$  subject to the condition that  $x = 0$ . The polhode curves correspond to values of  $(x, y, z)$  that simultaneously satisfy

## 10.1 Free Motion

655

Eq. (10.1.25) for the inertia ellipsoid and Eq. (10.1.35) describing constancy of  $|\bar{H}_G|$ . For the present values of the parameters, these equations are

$$\begin{aligned} 0.012(x^2 + 4y^2 + 5z^2) &= 1, \\ (0.012)^2(x^2 + 16y^2 + 25z^2) &= 0.057798. \end{aligned}$$

The polhode we are interested corresponds to  $z > 0$ , because  $\omega_z$  was initially positive. We therefore seek the root of these equations for which  $x = 0$  and  $z > 0$ . The roots are

$$y = \pm 1.9553, \quad z = 3.6889.$$

The alternative sign results from the symmetry of the polhode curves. We use the positive value of  $y$ ; either sign will yield the same angle. According to Eqs. (10.1.28), the corresponding angular velocity components are

$$\omega_x = 0, \quad \omega_y = 1.9553(2T_{\text{rot}})^{1/2}, \quad \omega_z = 3.6889(2T_{\text{rot}})^{1/2}, \quad (5)$$

which leads to the angular momentum being

$$\bar{H}_G = (2T_{\text{rot}})^{1/2}(0.093854\bar{j} + 0.221334\bar{k}) = H_G\bar{K}.$$

From this we find the angle  $\beta$  between  $\bar{\omega}$  and the  $z$  axis and the angle  $\theta$  between the  $z$  axis and the precession axis to be

$$\beta = \tan^{-1}\left(\frac{\omega_y}{\omega_z}\right) = 27.926^\circ, \quad \theta_{\text{max}} = \cos^{-1}\left(\frac{\bar{H}_G \cdot \bar{k}}{|\bar{H}_G|}\right) = 22.979^\circ.$$

The rotational kinetic energy corresponding to Eq. (5) must be the same as the value when the plate was released. We obtain this value by substituting  $\beta = 26.119^\circ$  into Eq. (3), which gives


$$2T_{\text{rot}} = 0.050697\omega_0^2,$$

where  $\omega_0$  is the magnitude of the angular velocity when the plate was released. Substitution of this value into Eq. (5) results in

$$\bar{\omega} = \omega_0(0.4403\bar{j} + 0.8306\bar{k}). \quad \triangleleft$$

The orientation of the principal axes and of the angular velocity at this instant are depicted in the accompanying sketch. To construct the picture, the fixed orientation of  $\bar{H}_G$  relative to vertical is established in the release position as the difference of the  $30^\circ$  angle to the  $z$  axis and the  $5.6^\circ$  angle from the  $z$  axis to  $\bar{H}_G$ . We find the orientation of all vectors at the other extreme orientation by copying the  $\bar{H}_G$  vector to that sketch, then using the computed  $\theta_{\text{max}}$  to locate the  $z$  axis. Then the  $z$  axis provides the reference from which  $\beta$  is measured to locate  $\bar{\omega}$ . Note that the planes for each sketch are not the same; to locate the plane for the second sketch we would need to know the precession angle. Also, each configuration in the sketch is mirrored by another, not shown, in which all features are reflected to the other side

of  $\bar{H}_G$ , corresponding to a  $180^\circ$  rotation about the precession axis. At an arbitrary instant, the angles between the  $z$  axis and the precession axis, and between the angular velocity and the precession axis, will be intermediate to the illustrated conditions and its mirror image.



Orientation of the plate at extreme locations on the polhode curve: (a) release at  $\beta = 26.1^\circ$ , (b) largest  $\beta$ .

## 10.2 SPINNING TOP

The toy known as a spinning top consists of an axially symmetric body that executes a pure rotation about an apex situated on the axis of symmetry. (We shall not worry here about the drift that occurs when the apex is not anchored, primarily because such effects are complicated by minor irregularities in the surface over which the apex would move.) The study of a spinning top leads to many insights regarding the interplay among rotation, angular momentum, and the moment exerted by forces. The results for its motion may be extended to other bodies that rotate about a reference point due to the moment of the gravitational force; such systems include certain types of gyroscopes.

Point  $O$  in Fig. 10.7 is stationary because of a reaction force having three components  $F_j$  in orthogonal directions. The gravity force acts through the center of mass  $G$ . Its moment about point  $O$  is  $mgL\sin\theta$  in the sense of the horizontal axis through point  $O$  that is perpendicular to the axis of symmetry. Because such an axis is the line of nodes for a set of Eulerian angles, it is natural to use those parameters as generalized coordinates. The reactions exert no moments about the precession, spin, and nutation axes, and gravity is conservative, so the generalized force associated with each angle is identically zero. Thus the principal difference between a spinning top and an axisymmetric body in free motion is the presence of a moment about the reference point for the rotation. This moment depends on the nutation angle and must be balanced by an angular momentum that varies with time.

We employ Lagrange's equations to formulate the equations of motion. Let  $I$  be the moment of inertia about the axis of symmetry and let  $I'$  be the moment of inertia about any axis perpendicular to the axis of symmetry and intersecting point  $O$ . In terms of

An important distinction is that a constant value of  $\beta_\phi$  corresponds to constancy of the total rotation rate about the axis of symmetry,  $\omega_z = \dot{\psi} \cos \theta + \dot{\phi}$ . Thus the precession and spin rates are individually constant only when the nutation angle is constant. If  $\theta$  is known as function of time, then these equations could be integrated to determine the precession and spin angles.

Constancy of  $p_\psi$  and  $p_\phi$  are derived from the Lagrange equations associated with  $\psi$  and  $\phi$ . Proper evaluation of the Lagrange equation associated with  $\theta$  requires that the derivatives of the energy expressions be evaluated before the conserved momenta are used to eliminate the ignorable coordinates. The resulting equation of motion is

$$I'\ddot{\theta} - (\dot{\psi} \sin \theta) [I'\dot{\psi} \cos \theta - I(\dot{\psi} \cos \theta + \dot{\phi})] - mgL \sin \theta = 0. \quad (10.2.6)$$

Substitution of Eqs. (10.2.5) eliminates the precession and spin rates, with the result that

$$\ddot{\theta} + \frac{1}{(\sin \theta)^3} (\beta_\psi - \beta_\phi \cos \theta) (\beta_\phi - \beta_\psi \cos \theta) - \frac{mgL}{I'} \sin \theta = 0. \quad (10.2.7)$$

The only variable in this second-order differential equation is  $\theta$ . We shall return to it later, but for now we use conservation of energy to obtain a first integral describing the nutation rate. We require that  $T + V = E$  be constant, and we use Eqs. (10.2.5) to eliminate  $\dot{\psi}$  and  $\dot{\phi}$ , which leads to

$$\frac{1}{2} I' \dot{\theta}^2 + \frac{1}{2} I' \left( \frac{\beta_\psi - \beta_\phi \cos \theta}{\sin \theta} \right)^2 + \frac{(I')^2}{2I} \beta_\phi^2 + mgL \cos \theta = E. \quad (10.2.8)$$

As is true for the generalized momenta, the value of  $E$  is specified by the initial conditions.

Multiplication of this equation by  $(\sin \theta)^2$  leads to a form in which the derivative occurs only in the combination  $\dot{\theta} \sin \theta$ . Also, because  $(\sin \theta)^2 = 1 - (\cos \theta)^2$ , the variable terms that do not contain derivatives may be considered to depend on  $\cos \theta$ . This suggests that it would be useful to define a new variable such that

$$u = \cos \theta, \quad \dot{u} = -\dot{\theta} \sin \theta. \quad (10.2.9)$$

Also, it is convenient to define the following combination of parameters:

$$\varepsilon = \frac{2E}{I'} - \frac{I'}{I} \beta_\phi^2, \quad \gamma = \frac{2mgL}{I'}. \quad (10.2.10)$$

Substitution of these expressions into the energy conservation equation, Eq. (10.2.8), gives

$$\dot{u}^2 = (\varepsilon - \gamma u) (1 - u^2) - (\beta_\psi - \beta_\phi u)^2. \quad (10.2.11)$$

This differential equation may be solved by separating variables, which would yield an expression for  $t$  as a function of  $u$  in the form of an elliptic integral; see Gradsteyn and Rhyzek (2000). Numerical methods provide an alternative solution procedure. However, we may determine much qualitative information about the motion by merely studying the roots of the cubic polynomial on the right side of Eq. (10.2.11). These roots describe the conditions for which  $\dot{u}$  is zero, corresponding to either an extreme or a

Conservation of angular momentum about the axis of symmetry requires that the total rate of rotation about that axis,  $\omega_z = \dot{\phi} + \dot{\psi} \cos \theta$ , remain constant. This means that a decrease in the precession rate or an increase in the nutation angle will be compensated by an increase in the spin rate. The effect of the nutation on the precession rate may be seen from the expression for  $p_\psi$ , Eqs. (10.2.4). This term originates from two sources: the projection of the spin momentum  $p_\phi$  onto the precession axis, and the angular momentum associated with the precession itself. The equivalent moment of inertia for the latter effect is  $I' (\sin \theta)^2$ . Increasing the nutation angle increases this moment of inertia, while it simultaneously decreases the projection of  $p_\phi$ . Hence an increase in the nutation angle has competing effects on the precession rate, depending on the value of  $p_\phi$  relative to  $p_\psi$ .


Equation (10.2.8) indicates that changing the nutation angle also has competing effects on the mechanical energy. The portion of the kinetic energy attributable to the precession and spin rates might increase or decrease when  $\theta$  increases, depending on the values of  $\beta_\phi$  and  $\beta_\psi$ . This is accompanied by a decrease in the potential energy with increasing  $\theta$ . The nutational portion of the mechanical energy, that is,  $I' \dot{\theta}^2/2$ , must maintain the balance between kinetic and potential energy. At the extremes of the nutational motion, the change in potential energy is exactly compensated by the change in the precession and spin kinetic energy, so the nutational energy vanishes at those locations.

- *Unidirectional Precession*

This is the case in which the precession rate  $\dot{\psi}$  never changes sign. According to Eq. (10.2.13), such a situation is encountered if  $u_0 \leq u_1$  or  $u_0 \geq u_2$ . The sense of the precessional motion that is imparted at the initial instant continues throughout the motion. The nutation angle has its maximum and minimum values at  $u = u_1$  and  $u_2$ , but the precession continues at those locations. As shown in Fig. 10.9, the path of point  $P$  at its highest and lowest elevations is tangent to horizontal circles on the unit sphere. One way in which we may initiate a unidirectional precession is to release the top at the highest elevation of point  $P$ , where  $u = u_2$ , with the precession rate set in the desired sense, and the initial nutation rate set to zero, corresponding to  $\dot{u} = 0$ . The initial precession rate should be relatively large, sufficient to make  $u_0 = \beta_\psi / \beta_\phi$  exceed  $u_2$ .

- *Looping Precession*


This response is characterized by a precession that reverses direction, although the overall motion is in one direction. Such a motion corresponds to  $u_1 \leq u_0 \leq u_2$ . The reversal of direction is indicated by  $\dot{\psi} = 0$ , whose occurrence is indicated by Eq.



**Figure 10.9.** Path of the spin axis of a top in unidirectional precession.

## 10.2 Spinning Top

661



**Figure 10.10.** Path of the spin axis of a top in looping precession.


(10.2.13) to correspond to  $u = u_0$ . The tangent to the path at these locations coincides with a meridian of the unit circle. In contrast, the nutation rate vanishes at the lowest and highest elevations. At those locations, the tangent to the path is horizontal, with movement at the low point indicating the direction of the overall precession. As shown in Fig. 10.10, the movement at the upper limit is opposite the overall motion. (The overall precession might proceed oppositely to the motion depicted in the figure.)

A looping precession may be attained by releasing a top at the highest elevation,  $u = u_2$ , with a comparatively small precession rate. The nutation rate at release must be zero in order for  $u_2$  to be the maximum elevation. As the top falls, the portion of the precession associated with  $\beta_\psi$  is eventually overwhelmed by the counter effect associated with  $\beta_\phi$ . The elevation  $u_0$  marks the location where these effects balance.

- *Cuspidal Motion*

This case is a transition between the unidirectional and looping precessions previously discussed. Like looping precession, the precession comes to rest, but this occurs at the highest elevation,  $u_0 = u_2$ . Because the tangent to the path at the highest elevation coincides with the meridian, the path at that location has a cusp. As shown in Fig. 10.11, the path of point  $P$  resembles a cycloidal path that is wrapped around the unit sphere.

Cuspidal motion may be attained by releasing the top at the highest elevation,  $u = u_2$ , with no initial precessional or nutational motion. The precessional motion that arises as the top falls is therefore due to only the spin momentum  $\beta_\phi$ . As the top falls, it gains kinetic energy and loses potential energy. Conservation of  $\beta_\psi$  and  $\beta_\phi$  causes the the precession rate to increase, until at the low point the contributions of the precession and spin rates to the kinetic energy equal the decrease in the potential energy, so  $\dot{\theta}$  vanishes. Incidentally, we may prove by this reasoning that the cusps cannot arise at the lowest elevation, where  $u = u_1$ . Such a motion would lead to



**Figure 10.11.** Path of the spin axis of a top in cuspidal precession.

## 10.2 Spinning Top

665

The roots in Eq. (10.2.31) entail no approximations, but we usually are interested in the case of a fast top. In that case  $\dot{\phi}$  is large, which leads to simplification of the formula based on a binomial series expansion of the square root, which gives

$$[I^2\dot{\phi}^2 - 4mgL(I' - I)\cos\theta]^{1/2} \approx I\dot{\phi} - 2mgL\frac{(I' - I)}{I\dot{\phi}}\cos\theta. \quad (10.2.33)$$

This reduces the roots to

$$\dot{\psi}_1 = \frac{mgL}{I\dot{\phi}}, \quad \dot{\psi}_2 = \frac{I}{(I' - I)\cos\theta}\dot{\phi}. \quad (10.2.34)$$

The first root,  $\dot{\psi}_1$ , is inversely proportional to  $\dot{\phi}$ , so it is comparatively low. The fast precession rate  $\dot{\psi}_2$  matches the value obtained from Eqs. (10.1.6) for a symmetric body in free motion. In essence, the spin and precession rates in the fast case are so high that the gravitational moment is negligible in comparison with the moments required to alter the angular momentum of the top. Steady precession of a top usually occurs at the slow precession rate, because the kinetic energy required to attain  $\dot{\psi}_2$  is prohibitive.

A special case of steady rotation is the *sleeping top*, which is the term used when the axis of symmetry of the top is vertical,  $\sin\theta = 0$ . The precession and spin are indistinguishable in a sleeping top, because the rotations are about concurrent axes. (The name “sleeping top” stems from the merger of spin and precession, which causes a polished body of revolution without markings to appear to be stationary.) Because of the similarity of precession and spin in such a rotation, some of the relations for steady precession become trivial. For example,  $\sin\theta = 0$  identically satisfies Eq. (10.2.30), which is the condition for  $\ddot{\theta}$  being identically zero. However, all relations for steady precession remain valid in the limit as  $\theta \rightarrow 0$ . We treat this degenerate case by noting that the angular velocity of a sleeping top is merely

$$\omega = \dot{\psi} + \dot{\phi}. \quad (10.2.35)$$

Hence, we find from Eq. (10.2.32) that the minimum rotation rate required for a top to sleep is

$$\omega > \omega_{\text{cr}} = \left[ \frac{4mgL(I' - I)}{I^2} \right]^{1/2}. \quad (10.2.36)$$

Our analysis suggests that the axis of symmetry cannot remain vertical if  $\omega$  is below this value. However, we saw earlier that  $\ddot{\theta} = 0$  whenever  $\sin\theta = 0$ , which suggests that the top will sleep for any spin rate if  $\theta = \dot{\theta} = 0$  when the top is released. In that condition the angular momentum is vertical, and therefore constant, and the moment of the gravity force about the pivot point vanishes. In essence, by obtaining the sleeping top as a special case, we have demonstrated that  $\theta = 0$  is unstable if  $\omega < \omega_{\text{cr}}$ .

In actuality, the effect of friction at the apex  $O$  is to slow the rate of rotation. When the value of  $\omega$  for a sleeping top falls below  $\omega_{\text{cr}}$ , the top begins to nutate. Because the nutational velocity is zero at the instant when the rotation rate falls

below critical, the ensuing motion is a cuspidal precession. If the spin rate decreases slowly, the amplitude of the nutation will slowly increase until the top hits the ground or falls from its support.

**EXAMPLE 10.3** A 2-kg top is in a state of steady slow precession at a spin rate of 500 rev/min with its axis at  $\theta = 120^\circ$ . A vertical impulsive force acting through the axis of symmetry suddenly induces an upward nutation, such that the ensuing motion is observed to be cuspidal. The radii of gyration of the top about its pivot are 360 mm and 480 mm parallel and transversely to the axis of symmetry, respectively, and the distance from the center of mass to the pivot is 200 mm. Determine (a) the nutation rate induced by the impulsive force, (b) the largest and smallest values of the nutation angle in the cuspidal precession, (c) the number of cusps in the path of the axis of symmetry for one revolution of the top about the vertical axis, and (d) the maximum, minimum, and average precession rates in the cuspidal motion.

**SOLUTION** Many of the basic formulas for a spinning top are implemented in the solution of this example. We begin by evaluating the steady precession preceding the application of the impulse force. The first of Eqs. (10.2.34) gives an approximate value for the slow precession rate. We could use that relation provided that we verify that the associated value of  $\beta_\phi$  is sufficiently high to warrant using that expression. Instead, we use Eq. (10.2.31) to find the slow precession rate. The parameters for the present system are  $m = 2$  kg,  $I = m\kappa^2 = 0.2592$  kg-m<sup>2</sup>,  $I' = m(\kappa')^2 = 0.4608$  kg-m<sup>2</sup>,  $L = 0.2$  m, and  $\dot{\phi} = 52.36$  rad/s, which leads to the two roots

$$\dot{\psi}_1 = 0.28843 \text{ rad/s}, \quad \dot{\psi}_2 = -134.93 \text{ rad/s}.$$

Both values are extremely close to the approximations obtained from Eqs. (10.2.34). Because it is stated that the initial precession is slow, we use  $\dot{\psi}_1$  as the initial precession rate.

The impulsive force induces an unknown nutation rate  $\dot{\theta}$ , because it exerts a moment about the horizontal axis through the pivot. However, the spin and precession rates are not altered during the impulse interval because the force exerts no moment about either axis. We find  $\dot{\theta}$  from the fact that the subsequent precession is cuspidal. We need the values of the precession and spin momentum parameters to evaluate cuspidal motion, so we substitute the values of  $\dot{\psi}_1$  and  $\dot{\phi}$  into Eqs. (10.2.4), which gives

$$\beta_\phi = 29.371 \text{ rad/s}, \quad \beta_\psi = -14.469 \text{ rad/s}.$$

From this we find that the highest elevation in the cuspidal motion is

$$u_0 = \frac{\beta_\psi}{\beta_\phi} = -0.49264. \quad (1)$$



At the average precession rate, the time interval for one revolution about the vertical axis is

$$T = \frac{2\pi}{\dot{\psi}_{av}} = 21.68 \text{ s.}$$

The number of cusps is the ratio of this period to the period  $\Delta t$  for the  $\theta$  oscillation, so

$$N = 101.34.$$

**EXAMPLE 10.4** Example 5.4 examined the implications of the inverse square law for gravitation in the context of the oblateness of the Earth and the tilt of the Earth's polar axis. It was shown there that the Moon and the Sun each exert a force-couple system acting at the Earth's center of mass. Show that the primary consequence of these couples is a nearly steady precession of the Earth's polar axis about an axis that is normal to the orbital plane, accompanied by a very minor wobble. Determine the precession rate associated with each attracting body.

**SOLUTION** Although the role of gravitational moments exerted on the Earth is not like the effect of gravity on a spinning top, the implications of the similarities of a top and the Earth's rotation is quite interesting. It was shown in Example 5.4 that the moment exerted by the Moon is more than twice as large as the Sun's effect, so we start by considering the Moon's effect. The previous analysis found that the Moon's gravitational attraction can be resolved into a force and couple acting at the Earth's center (of mass) given by

$$\begin{aligned} \bar{F} &= \frac{GM_{\text{moon}}M_e}{R_{\text{moon}}^2} \bar{e}_R, \\ \bar{M} &= \frac{3GM_{\text{moon}}(I - I')}{R_{\text{moon}}^3} (\bar{e}_R \cdot \bar{k}) (\bar{e}_R \times \bar{k}), \end{aligned} \quad (1)$$

where  $\bar{k}$  is the unit vector from the South Pole to the North Pole,  $\bar{e}_R$  is the unit vector from the center of the Earth to the center of the Moon,  $R$  is the distance between centers, and  $I$  and  $I'$  are the centroidal moments of inertia, with  $I$  being about the polar axis. To describe the unit vectors and angular motion of the Earth, we let  $xyz$  be the body-fixed coordinate system, and let  $XYZ$  be a translating reference frame whose origin is always situated at the Earth's center with the  $XY$  plane coincident with the orbital plane of the Moon. An auxiliary coordinate system  $x'y'z'$  is defined such that it precesses about the  $Z$  axis by  $\psi$  and nutates about the  $y'$  axis by angle  $\theta$ . The  $y'$  axis, which is the line of nodes, lies in the orbital plane. The spin rate of  $xyz$  relative to  $x'y'z'$  is  $\dot{\phi}$ , which is the spin rate  $\omega_e$  of the Earth. As shown in the sketch, the radial line to the Moon coincides with the Moon's orbital plane, and this line rotates at the orbital speed  $\Omega$  of the Moon, which we consider to be constant. (By taking  $R_{\text{moon}}$  and  $\Omega$  to be constant, we are ignoring the eccentricity of the orbit.)

We are now ready to address the equations of motion. The angular velocity of the Earth is

$$\bar{\omega} = \dot{\psi} \bar{K} + \dot{\theta} \bar{j}' + \dot{\phi} \bar{k}' = -\dot{\psi} \sin \theta \bar{i}' + \dot{\theta} \bar{j}' + (\dot{\phi} + \dot{\psi} \cos \theta) \bar{k}'. \quad (5)$$

The translational and rotational portions of the motion are uncoupled, so the rotational kinetic energy is the same as in Eq. (10.2.2) for a spinning top. Rather than using potential energy to describe the role of gravity, it is easier to evaluate the virtual work done by the gravitational moment. The Eulerian angles are the generalized coordinates. The virtual rotation is found by analogy to the angular velocity to be

$$\delta \bar{\Theta} = -\delta \psi \sin \theta \bar{i}' + \delta \theta \bar{j}' + (\delta \phi + \delta \psi \cos \theta) \bar{k}'.$$

The virtual work is  $\bar{M} \cdot \delta \bar{\Theta}$ , which leads to the generalized forces being

$$Q_\psi = \Gamma (\sin \theta)^2 \sin (2\Omega t - 2\psi), \quad Q_\theta = -\Gamma \sin \theta \cos \theta [1 + \cos (2\Omega t - 2\psi)].$$

The spin angle does not appear explicitly in  $T$  and  $Q_\phi = 0$ , so the associated generalized momentum is conserved. Thus the Lagrange equation for the spin angle is the same as for a spinning top:

$$p_\phi = \frac{\partial T}{\partial \dot{\phi}} = I (\dot{\psi} \cos \theta + \dot{\phi}) \equiv I' \beta_\phi. \quad (6)$$

Unlike the precession angle of a spinning top, here the precession angle is not ignorable because the generalized forces depend on this variable. The Lagrange equation for the precession is

$$\begin{aligned} & \left[ I' (\sin \theta)^2 + I (\cos \theta)^2 \right] \ddot{\psi} + I \ddot{\theta} \cos \theta + 2(I - I') \dot{\psi} \dot{\theta} \sin \theta \cos \theta \\ & - I \dot{\theta} \dot{\phi} \sin \theta = \Gamma (\sin \theta)^2 \sin (2\Omega t - 2\psi). \end{aligned} \quad (7)$$

The equation of motion for the nutation is the same as that for the spinning top, except that the potential-energy term is replaced with the generalized force  $Q_\theta$ . Substitution of Eq. (6) into that equation gives

$$I' \ddot{\theta} - I' (\dot{\psi} \sin \theta) (\dot{\psi} \cos \theta - \beta_\phi) = -\Gamma \sin \theta \cos \theta [1 + \cos (2\Omega t - 2\psi)]. \quad (8)$$

We know from astronomical observation that the nutation angle is nearly constant. Furthermore, if the time-dependent term were not present in Eq. (6), a constant value of  $\theta$  would lead to a constant value of  $\dot{\psi}$ . Thus we let

$$\theta = \theta_0 + \varepsilon \theta_1(t), \quad \dot{\psi} = \dot{\psi}_0 + \varepsilon \dot{\psi}_1(t), \quad (9)$$

where  $\varepsilon$  is a small parameter and the quantities with subscript one are not large. When the leading-order terms that arise in Eq. (8) are matched to the constant portion of the right side, the result is

$$I' (\dot{\psi}_0 \sin \theta_0) (\dot{\psi}_0 \cos \theta_0 - \beta_\phi) = \Gamma \sin \theta_0 \cos \theta_0.$$

of the precession of the equinoxes is that 13 000 years from now the seasons will be reversed, so that the first day of summer in the Northern Hemisphere will come in December. Another consequence is that Polaris, which is popularly known as the North Star because it is almost concurrent with the Earth's polar axis, in the future will no longer be aligned in that manner.

One could proceed to analyze the second-order approximation associated with Eqs. (9). Because the first-order terms describe the effect of the mean value of the gravitational moment, the higher-order terms are driven by the oscillatory portion of the moment. The contributions of the Moon and the Sun add, but, as was noted previously, they have vastly different frequencies. In any event, the nutation and precession rates must exhibit minor fluctuations. The more noticeable one is the nutation, which represents a minor wobble. Earth-based astronomers must compensate for this wobble, as well as the precession, when they aim a telescope.

### 10.3 GYROSCOPES FOR INERTIAL GUIDANCE

The gyroscopic moment, which is associated with altering the direction of a rotation axis, is generally proportional to the product of rotation rates. We explore here a number of ways in which this effect has been employed in devices that guide moving vehicles autonomously. In essence, these devices provide an inertial reference system that moves with the vehicle, so they are referred to as *inertial guidance systems*. The conceptual pictures for our studies will be quite crude. In practice, the various pieces of equipment are manufactured with exceptionally high accuracy and with the finest bearings, in order to match as closely as possible the ideal conditions that we shall treat. Some of the concepts have been rendered obsolete with the availability of GPS navigation systems, but the virtue of the ones we examine is that they lead to self-contained systems. Also, modern electronic capabilities have made it possible to construct devices that achieve the same purpose with other technologies. For example, some systems exploit relativistic effects associated with the fact that light rays traveling in opposite directions through a rotating fiber-optic loop have differing phase speeds. However, many conventional gyroscopes are still in use, and their study will enhance our general understanding of fundamental phenomena.


#### 10.3.1 Free Gyroscope

The gyroscope appearing in Fig. 10.12 is said to be free because the rotation of the rotor is unconstrained. The outer gimbal permits precessional rotation, the inner gimbal permits nutation, and the rotor shaft permits spin. For our introductory study we ignore the effect of the motion of the vehicle supporting the outer gimbal. In that case the center point  $O$  is stationary, because the three rotation axes are concurrent at that point.

If the center of mass  $G$  of the rotor does not coincide with the fixed point  $O$ , the gimbals must rotate. The excitation is the moment of the gravity force about the line

### 10.3 Gyroscopes for Inertial Guidance

673



**Figure 10.12.** Rotations of a free gyro: precession of the outer gimbal, nutation of the inner gimbal, and spin of the rotor.

of nodes, which is the axis about which the inner gimbal rotates relative to the outer gimbal. The configuration of the system, with the center of mass situated on the spin axis relative to a fixed point that is also on that axis, is identical to that of a spinning top. It follows that the two systems behave in the same manner. In the special case in which the center of mass coincides with the fixed point  $O$ , the free gyroscope behaves like a body in free motion, Section 10.1, because there are no external moments. We shall employ the results of the previous sections, as necessary.

Suppose a steady precession, in which the nutation angle is constant, has been established. The relation among the precession rate, the spin rate, and the nutation angle is given by Eq. (10.2.31). In order for there to be a steady precession, the spin rate must exceed the minimum value given by Eq. (10.2.32). If the center of mass coincides with the fixed point  $O$ , then the steady slow precession rate is zero, which means that the axis of symmetry has a constant orientation.

An important question that must be addressed is whether the steady precession is a stable response. If it is not, then such motion would not be observed in reality. Our analysis of the dynamic stability of steady precession will follow the procedure used in Subsection 10.1.2 to study a pure spin of a body about either of its principal axes. We introduce a small disturbance of the nutation angle from the constant value it has when a steady precession has been established. Thus, let

$$\theta = \theta^* + \varepsilon \xi, \quad (10.3.1)$$

where  $\theta^*$  denotes the constant value for steady precession,  $\varepsilon$  is a small parameter, and  $\xi$  is a time-dependent function that is assumed to have unit order of magnitude.

This description of the nutation angle must satisfy the basic equation of motion, Eq. (10.2.7), which we multiply by  $(\sin \theta)^3$ . We require only the terms that have the leading order of magnitude, so we employ Taylor series and retain only terms that are either independent of, or proportional to,  $\varepsilon$ . For example,

$$\cos \theta = \cos \theta^* - \varepsilon \xi \sin \theta^*, \quad (\sin \theta)^4 = (\sin \theta^*)^4 + 4\varepsilon \xi (\sin \theta^*)^3 \cos \theta^*. \quad (10.3.2)$$

These series expansions are substituted into Eq. (10.2.7), and terms are grouped into those that are independent of  $\varepsilon$  and those that are proportional to  $\varepsilon$ . The former vanishes

because it is the relation that must be satisfied for steady precession, that is,

$$(\beta_\psi - \beta_\phi \cos \theta^*) (\beta_\phi - \beta_\psi \cos \theta^*) - \frac{\gamma}{2} (\sin \theta^*)^4 = 0. \quad (10.3.3)$$

Canceling the  $\varepsilon$  factor in the remaining terms leads to

$$\begin{aligned} (\sin \theta^*)^3 \ddot{\xi} + \{[\beta_\phi (\beta_\phi - \beta_\psi \cos \theta^*) \\ + \beta_\psi (\beta_\psi - \beta_\phi \cos \theta^*)] \sin \theta^* - 2\gamma (\sin \theta^*)^3 \cos \theta^*\} \xi = 0. \end{aligned} \quad (10.3.4)$$

The definitions of  $\beta_\psi$  and  $\beta_\phi$  in Eqs. (10.2.4) simplifies this differential equation to

$$\begin{aligned} \ddot{\xi} + K\xi &= 0, \\ K &= \beta_\phi^2 + (\dot{\psi}^* \sin \theta^*)^2 - 2\gamma \cos \theta^*. \end{aligned} \quad (10.3.5)$$

The steady precession is stable to small disturbances if the value of  $\xi$  remains bounded. Such a condition is obtained if  $K > 0$ , in which case the solution for  $\xi$  is oscillatory. However, Eq. (10.2.32) states that a steady precession can exist only if the spin rate, and therefore  $\beta_\phi$ , is sufficiently large. It follows that  $K > 0$  for any steady precession. In other words, if the spin momentum is sufficiently large to establish a steady precession at nutation angle  $\theta^*$ , then an attempt to change the nutation angle by a small amount will result in an oscillatory nutational motion whose mean value is  $\theta^*$ .

The balanced free gyroscope, for which  $\gamma = 0$  corresponding to  $L = 0$ , is stable regardless of the spin momentum. It has been used to provide an *inertial platform* as part of an inertial navigation system that tracks vehicle motion in aircraft and missiles. The concept uses a free gyroscope and accelerometers. An accelerometer measures acceleration in the direction that it is oriented. [As explained in most fundamental texts on vibrations, such as Ginsberg (2001), an accelerometer features a very small mass that is suspended by a stiff spring. The displacement of the mass relative to the base on which the spring is supported is proportional to the base acceleration.] Three accelerometers mounted orthogonally therefore can measure an acceleration vector. An inertial navigation system using a free gyroscope mounts the gyroscope and orthogonal accelerometers on a freely suspended platform. If the supports had ideal properties, the platform's inertia would prevent its rotation. In that case, the platform would constitute a translating reference frame, so the accelerometer would measure the absolute acceleration of the platform. However, friction and other nonideal effects, regardless of how small they are, cause the platform to rotate. Sensors measure the rotation of the gimbals relative to the gyroscope, whose axis indicates a invariant direction. Servomotors apply counterrotations to the platform in order to hold its orientation constant. (Because only rotations about two axes can be sensed with a single free gyroscope, two or more are required.) The absolute acceleration is obtained from the accelerometer outputs. It is integrated twice in order to determine the absolute position at each time instant. The position relative to the Earth is readily determined because the absolute motion of any point on the Earth is a known function of time.

A much simpler concept is the *directional gyroscope*. It uses the free gyroscope in Fig. 10.12 in the balanced case, with the spin axis aligned along the longitudinal axis of the flight vehicle. The  $Z$  axis, which is the bearing axis of the outer gimbal, is stationary

### 10.3 Gyroscopes for Inertial Guidance

675

with respect to the vehicle; it is aligned perpendicularly to the longitudinal axis. This defines the yaw axis. The spin axis of the idealized balanced free gyroscope maintains a constant orientation regardless of how its gimbals rotate. Thus the yaw angle can be measured with a sensor that measures the rotation of the mount with respect to the outer gimbal. Similarly, the pitch angle is the rotation of the outer gimbal with respect to the inner one. A *vertical gyroscope* uses a similar arrangement, with the spin axis aligned perpendicularly relative to the vehicle's longitudinal axis. This is equivalent to the yaw axis for the directional gyroscope. (For an airplane this would be the vertical direction.) The axis of the outer gimbal is aligned along the longitudinal axis. Then the rotation of the mount relative to the outer gimbal is the roll, and the rotation of the outer gimbal with respect to the inner is the pitch. In practice, friction at the bearings would cause the rotor axis to drift for both the directional and rate gyros. This is compensated by force sensors/actuators that apply smoothing torques to counter such deviations.

**EXAMPLE 10.5** To overcome the effects of friction, a servomotor applies a torque about the spin axis of an unbalanced gyroscope, with the result that the spin rate is constant. The initial conditions are such that the initial precession rate  $\dot{\psi}^*$  and nutation angle  $\theta^*$  correspond to steady precession. Determine whether the action of the servomotor can cause the gyroscope to be unstable to small disturbances.

**SOLUTION** The idea here is to develop the ability to analyze nonideal effects for gyroscopes. The primary difference between the present system and a free gyroscope is that there are only two degrees of freedom, because the spin rate  $\dot{\phi}$  is constrained, rather than the spin momentum  $\beta_\phi$  being constant. We commence to derive the equations of motion for the servogyroscope by using the energies in Eqs. (10.2.2) and (10.2.3):

$$T = \frac{1}{2} \left[ I' \dot{\psi}^2 (\sin \theta)^2 + I' \dot{\theta}^2 + I (\dot{\psi} \cos \theta + \dot{\phi})^2 \right], \quad V = mgL \cos \theta.$$

The precession angle is an ignorable generalized coordinate, because only its derivative appears in  $T$ . The corresponding conservation of momentum equation is identical to the first of Eqs. (10.2.4):

$$\beta_\psi = \dot{\psi} \left[ \frac{I}{I'} (\cos \theta)^2 + (\sin \theta)^2 \right] + \frac{I}{I'} \dot{\phi} \cos \theta. \quad (1)$$

We may find the actual value of  $\beta_\psi$  by substituting  $\dot{\psi}^*$  and  $\theta^*$ . Equation (10.2.6) is the Lagrange equation for  $\theta$  corresponding to arbitrary dependence of  $\psi$  and  $\phi$ . It may be written as

$$\ddot{\theta} + g(\psi, \theta) = 0, \quad (2)$$

$$g(\psi, \theta) = \left( \frac{I}{I'} - 1 \right) \dot{\psi}^2 \sin \theta \cos \theta + \left( \frac{I}{I'} \dot{\psi} \dot{\phi} - mgL \right) \sin \theta.$$




Figure 10.13. A gyrocompass on the surface of the Earth.

The gyrocompass bears much similarity to an unbalanced free gyroscope, except for the placement of the mass causing the imbalance. As shown in Fig. 10.13, the center of mass of the rotor is situated on the intersection of the precession and spin axes, but a small additional mass  $m$  is attached to the inner gimbal. This arrangement is selected in order that the gravitational moment be like that for a pendulum. The Earth-fixed coordinate system  $XYZ$  defined in Fig. 10.13 is introduced to describe the orientation relative to the Earth. The  $Z$  axis is oriented in the direction perceived as vertical to an observer on the Earth, and the  $X$  axis is situated in the northerly direction, which means that  $X$  is tangent to a meridian. In terms of these components the angular velocity of the Earth is

$$\bar{\omega}_e = \omega_e (\cos \lambda \bar{I} + \sin \lambda \bar{K}), \quad (10.3.6)$$

where  $\omega_e = 7.292(10^{-5})$  rad/s  $\approx 2\pi$  rad/24 h is the rotation rate.

The rotation of the gyrocompass' rotor is unconstrained. Eulerian angles are used to describe the orientation of the rotor, relative to  $XYZ$ . The  $xyz$  coordinate system, which is attached to the inner gimbal, facilitates the description. The  $z$  axis is aligned with the axis of symmetry of the rotor and the  $y$  axis is the line of nodes formed by the bearings of the inner gimbal. Our goal here is to determine whether there is any set of precession and nutation angles for which the axis of the rotor remains stationary relative to the Earth. For this reason we consider the values of  $\psi$  and  $\theta$  to be constant, and we also assume that  $\phi$  remains constant. The corresponding angular velocity of the rotor relative to  $XYZ$  is  $\dot{\phi}\bar{k}$ . The absolute angular velocity  $\bar{\omega}$  is the sum of this term and the angular velocity of the Earth-fixed reference frame. To express  $\bar{\omega}$  in terms of component relative to  $xyz$ , we refer to Fig. 10.13 to find that

$$\begin{aligned} \bar{I} &= \cos \psi [\cos \theta \bar{i} + \sin \theta \bar{k}] - \sin \psi \bar{j}, \\ \bar{J} &= \sin \psi [\cos \theta \bar{i} + \sin \theta \bar{k}] + \cos \psi \bar{j}, \\ \bar{K} &= -\sin \theta \bar{i} + \cos \theta \bar{k}. \end{aligned} \quad (10.3.7)$$

### 10.3 Gyroscopes for Inertial Guidance

679

Adding the Earth's rotation to the rotor spin then leads to

$$\begin{aligned}\bar{\omega} = \omega_e (\cos \lambda \cos \psi \cos \theta - \sin \lambda \sin \theta) \bar{i} - \omega_e \cos \lambda \sin \psi \bar{j} \\ + (\omega_e \cos \lambda \cos \psi \sin \theta + \omega_e \sin \lambda \cos \theta + \dot{\phi}) \bar{k}.\end{aligned}\quad (10.3.8)$$

Terms containing  $\omega_e$  have a very small value, so we may simplify the kinetic energy of the system by neglecting effects that are of the order of  $\omega_e^2$ . The corresponding kinetic energy for the system is

$$\begin{aligned}T = \frac{1}{2} (I' \omega_x^2 + I' \omega_y^2 + I \omega_z^2) \\ = \frac{1}{2} I [\dot{\phi}^2 + 2\omega_e \dot{\phi} (\cos \lambda \cos \psi \sin \theta + \sin \lambda \cos \theta)].\end{aligned}\quad (10.3.9)$$

The potential energy is associated with the unbalanced mass on the inner gimbal. When the datum is set at the elevation of center  $O$  of the rotor, we find that

$$V = mgL \cos\left(\frac{\pi}{2} + \theta\right) = -mgL \sin \theta. \quad (10.3.10)$$

There are no nonconservative forces in this ideal model, so the Lagrange's equations for the generalized coordinates in this case of steady precession are

$$\begin{aligned}\omega_e \dot{\phi} \cos \lambda \sin \psi \sin \theta &= 0, \\ I \omega_e \dot{\phi} (-\cos \lambda \cos \psi \cos \theta + \sin \lambda \sin \theta) - mgL \cos \theta &= 0, \\ \dot{\phi} + \omega_e (\cos \lambda \cos \psi \sin \theta + \sin \lambda \cos \theta) &= \beta_\phi,\end{aligned}\quad (10.3.11)$$

where  $\beta_\phi = p_\phi / I$  is the spin momentum parameter associated with the ignorable coordinate  $\phi$ .

Because of the smallness of  $\omega_e$ , the last of Eqs. (10.3.11) indicates that the spin momentum is primarily associated with the spin itself. The first equation is satisfied when  $\sin \theta = 0$  or  $\sin \psi = 0$ . The first possibility is not useful, because then the rotor does not provide any directional information. The second case is the one we seek, because it is satisfied when  $\psi = 0$  or  $\pi$ , which corresponds to the spin axis being aligned along the north-south meridian. Setting  $\cos \psi = \pm 1$  in the second of Eqs. (10.3.11) yields

$$(mgL \pm I \omega_e \dot{\phi} \cos \lambda) \cos \theta = I \omega_e \dot{\phi} \sin \lambda \sin \theta, \quad (10.3.12)$$

from which we find that

$$\cot \theta = \frac{I \omega_e \dot{\phi} \sin \lambda}{mgL \pm I \omega_e \dot{\phi} \cos \lambda}. \quad (10.3.13)$$

The smallness of  $\omega_e$  simplifies this result further. For any likely value of  $\dot{\phi}$ , the denominator term containing  $\omega_e$  can be ignored. Furthermore, because  $\cot \theta$  is very small,  $\theta$  is close to  $\pi/2$ , so that  $\cot \theta \equiv \tan(\pi/2 - \theta) \approx \pi/2 - \theta$ . Consequently, the nutation angle for steady motion is

$$\theta = \frac{\pi}{2} - \frac{I \omega_e \dot{\phi} \sin \lambda}{mgL}, \quad \psi = 0 \text{ or } \pi. \quad (10.3.14)$$



### 10.3 Gyroscopes for Inertial Guidance

683

angle simplify the equations. The result for  $\eta$  is

$$\begin{aligned} I'\ddot{\eta} + \frac{1}{2}I'\dot{\psi}^2 \sin 2\eta + I'\dot{\psi}\omega_e \left[ 2 \cos \lambda \cos \psi (\cos \eta)^2 + \sin \lambda \sin 2\eta \right] \\ - I\beta_\phi [\dot{\psi} \cos \eta - \omega_e (\cos \lambda \cos \psi \sin \eta - \sin \lambda \cos \eta)] \\ - I'\omega_e^2 (\cos \lambda \cos \psi \sin \eta - \sin \lambda \cos \eta) (\cos \lambda \cos \psi \cos \eta \\ + \sin \lambda \sin \eta) + mgL \sin \eta = 0, \end{aligned} \quad (4)$$

and the equation for  $\psi$  is

$$\begin{aligned} I'\ddot{\psi} (\cos \eta)^2 - I'\dot{\psi} \dot{\eta} \sin 2\eta + I\dot{\eta}\beta_\phi \cos \eta - I'\dot{\eta}\omega_e [\cos \lambda \cos \psi \cos 2\eta \\ + \sin \lambda \sin 2\eta] - I'\omega_e^2 \left[ \frac{1}{2} (\cos \lambda)^2 \sin 2\psi + \frac{1}{4} \sin 2\lambda \cos \eta \sin \psi \sin 2\eta \right] \\ + I\beta_\phi \omega_e \cos \lambda \sin \psi \cos \eta = 0. \end{aligned} \quad (5)$$

If the system is stable, then  $\eta$  and  $\psi$  will not grow relative to their initial magnitude. The smallness condition enables us to linearize Eqs. (4) and (5) by setting  $\cos \eta \approx 1$ ,  $\sin \eta \approx \eta$ ,  $\cos \psi \approx 1$ , and  $\sin \psi \approx \psi$ , and then dropping any terms that are quadratic or higher degree in the generalized coordinates. Concurrently, we also simplify the coefficients of the resulting equations by dropping any term containing  $\omega_e$  if it is added to a term that does not contain  $\omega_e$ . Another consistent approximation entails ignoring terms that are quadratic in  $\omega_e$ . The simplified linearized equations of motion are

$$\begin{aligned} I'\ddot{\eta} - I\beta_\phi \dot{\psi} + mgL\eta = I\beta_\phi \omega_e \sin \lambda, \\ I'\ddot{\psi} + I\beta_\phi \dot{\eta} + (I\beta_\phi \omega_e \cos \lambda) \psi = 0. \end{aligned} \quad (6)$$

These are a coupled pair of linear ordinary differential equations, in which the inhomogeneous term is a constant. We form the solution of these differential equations by adding a complementary solution to the constant particular solution. The latter are

$$\eta_p = \frac{I\beta_\phi \omega_e}{mgL} \sin \lambda, \quad \psi_p = 0.$$

The value of  $\beta_\phi$  is essentially the same as  $\dot{\phi}$  because the spin rate is high, so the preceding is the same as the gyrocompass' nominal steady angles, as given by Eqs. (10.3.14). To derive the homogeneous solution of Eqs. (6), we reason that a stable response will be marked by oscillations about the nominal state, which means that the homogeneous solution of the linear equations should be sinusoidal. Furthermore, the homogeneous terms in Eqs. (6) relate a generalized coordinate and its second derivative to the first derivative of the other generalized coordinate. Consequently, one generalized coordinate must be  $90^\circ$  out of phase relative to the other. A suitable trial form for the complementary solution therefore is

$$\eta_c = A \sin(\sigma t - \gamma), \quad \psi_c = B \cos(\sigma t - \gamma). \quad (7)$$

### 10.3 Gyroscopes for Inertial Guidance

685


the high-frequency mode much more than the low-frequency mode, in which case the oscillation at frequency  $\sigma_1$  is more persistent and therefore more likely to be observed.

In regard to the question of stability, we note that the values of  $\sigma_1$  and  $\sigma_2$  are always real. Hence, disturbances of the gyrocompass always result in bounded oscillations, corresponding to a stable steady motion. However, the value of  $\sigma_1$  becomes very small if  $\cos \lambda = 0$ , corresponding to locations near the North or South Pole. Hence, at those locations the gyrocompass executes very slow oscillations when disturbed. The northerly direction is indicated by the average value of  $\psi$ , that is, zero. The low oscillation frequency at the Earth's poles requires that  $\psi$  be measured over a long interval in order to see the average direction in which the rotor is aimed.

#### 10.3.3 Single-Axis Gyroscope

Safe operation of aircraft requires that the vehicle's angular velocity be monitored. The single-axis gyroscope, which has only an inner gimbal, provides such information because its nutation is essentially proportional to the precession rate. A conceptual model of a single-axis gyro appears in Fig. 10.15, where the platform is assumed to undergo arbitrary rotations about axes  $\xi$ ,  $\eta$ , and  $\zeta$  that are attached to the platform. These axes are defined such that the  $\xi\zeta$  plane is parallel to the platform, with  $\xi$  aligned with the bearing axis of the gimbal. The  $xyz$  reference frame is attached to the gimbal. Rotation of the gimbal relative to the platform is resisted by linear torsional springs whose total stiffness is  $K$ . A torsional damper whose constant is  $C$  acts in parallel with the springs. The springs are mounted such that they are undeformed in the position where the rotor axis is parallel to the platform.

The orientation of the rotor relative to the platform is defined by the spin angle  $\phi$  and the rotation  $\theta$  of the gimbal, which we consider to be a nutation about the  $x$  axis, with the precession set to zero. Thus  $\theta$  is the angle from the  $\zeta$  axis to the rotor axis. According to this definition,  $\theta = 0$  represents the undeformed position of the spring.



**Figure 10.15.** Conceptual model of a single-axis gyroscope that is mounted on a base whose angular velocity is  $\Omega$ .

### 10.3 Gyroscopes for Inertial Guidance

689

is specified as being about a body-fixed axis, the angular velocity components are found by projections onto the  $\xi\eta\zeta$  axes, so that

$$\Omega_\xi = 0, \quad \Omega_\eta = \Omega \sin \gamma, \quad \Omega_\zeta = \Omega \cos \gamma.$$

The response we seek is the solution to Eq. (10.3.24) for this rotation of the base, subject to the initial conditions that  $\theta = \dot{\theta} = 0$  when  $t = 0$ .

Several methods are available for determining this response. We exploit the similarity of the problem to that encountered in conventional transient vibrations. For the given angular velocity components, the conditions  $\dot{\phi} \gg \Omega_\eta$ ,  $\Omega_\zeta$ , and  $\dot{\Omega}_\xi / \Omega_\eta$  required for employing Eq. (10.3.24) are satisfied if  $\beta_\phi \gg \Omega$  and  $\beta_\phi \gg (\pi/\tau) \tan \gamma$ . (When  $\gamma = \pm\pi/2$ , the rotation is essentially about the  $\zeta$  axis. Such a rotation would presumably be measured by a rate gyro that is arranged orthogonally to the one under consideration.) We assume that  $\beta_\phi$  meets these conditions. Substitution of the given functional form of  $\Omega$  for  $t < \tau$  then leads to

$$I'\ddot{\theta} + C\dot{\theta} + K\theta = I\beta_\phi\Omega_0 \sin \gamma \sin\left(\frac{\pi t}{\tau}\right).$$

This represents a one-degree-of-freedom system having natural frequency  $\omega_{\text{nat}} = (K/I')^{1/2}$  and ratio of critical damping  $\sigma = 0.5C/(I'K)^{1/2}$  that is subjected to a sinusoidal excitation at frequency  $\pi/\tau$ . The response is the sum of the complementary solution and the particular solution. The latter, which is known as the steady-state response in vibration theory, consists of the quasi-static response, which is the amplitude that would be obtained if the system only had stiffness  $K$ , multiplied by a frequency response factor and delayed by a phase lag  $\delta$ . For the parameters of the present system the steady-state response is

$$\begin{aligned} \theta_{\text{ss}} &= \Theta \sin\left(\frac{\pi t}{\tau} - \delta\right), \quad \Theta = \frac{1}{D} \frac{I}{I'} \frac{\beta_\phi}{\omega_{\text{nat}}} \frac{\Omega_0}{\omega_{\text{nat}}} \sin \gamma, \\ D &= \left\{ \left[ 1 - \left( \frac{\pi}{\omega_{\text{nat}}\tau} \right)^2 \right]^2 + 4\sigma^2 \left( \frac{\pi}{\omega_{\text{nat}}\tau} \right)^2 \right\}^{1/2}, \\ \delta &= \tan^{-1} \left[ \frac{2\sigma\pi/\omega_{\text{nat}}\tau}{1 - (\pi/\omega_{\text{nat}}\tau)^2} \right], \quad 0 \leq \delta \leq \pi. \end{aligned} \quad (1)$$

The initial conditions must be satisfied by the combination of the particular and complementary solutions. Because the damping is stated to be less than critical,  $\sigma < 1$ , the complementary solution, whose form is the same as that of the free-vibration response, is oscillatory with an overall amplitude that decays exponentially in time, according to

$$\theta_c = \exp(-\sigma\omega_{\text{nat}}t) [A \sin(\omega_d t) + B \cos(\omega_d t)], \quad \omega_d = (1 - \sigma^2)^{1/2} \omega_{\text{nat}}. \quad (2)$$

Satisfaction of the initial conditions requires that  $\theta_{\text{ss}} + \theta_c = 0$  and  $\dot{\theta}_{\text{ss}} + \dot{\theta}_c = 0$  at  $t = 0$ . These represent two equations for  $A$  and  $B$ . The corresponding

response is

$$\theta = \Theta \sin \left( \frac{\pi t}{\tau} - \delta \right) + \Theta \exp(-\sigma \omega_{\text{nat}} t) \left[ \frac{(\sigma \omega_{\text{nat}} \tau) \sin \delta - \pi \cos \delta}{(1 - \sigma^2)^{1/2} \omega_{\text{nat}} \tau} \sin(\omega_d t) + \sin \delta \cos(\omega_d t) \right], \quad 0 \leq t \leq \tau. \quad (3)$$

The airplane's rotation ceases at  $t = \tau$ , after which the rotor executes a free vibration. Equation (2) describes such a response if we change  $t$  to the elapsed time measured from the instant when the rotation ceases, which is  $t' = t - \tau$ . The initial conditions for this response are the values of  $\theta$  and  $\dot{\theta}$  obtained from Eq. (3) at the instant when the rotation ended. Let us denote these values as  $\theta_\tau$  and  $\dot{\theta}_\tau$ . Then the free response is given by

$$\theta = \exp[-\sigma \omega_{\text{nat}}(t - \tau)] \left\{ \frac{\dot{\theta}_\tau + \sigma \omega_{\text{nat}} \theta_\tau}{\omega_d} \sin[\omega_d(t - \tau)] + \theta_\tau \cos[\omega_d(t - \tau)] \right\}, \quad t \geq \tau. \quad (4)$$

Equations (3) and (4) describe the response for any set of system parameters for which  $\sigma < 1$ . We desire that both expressions match Eq. (10.3.27). The rotation rate is given, and the stiffness parameter may be written as  $K = I' \omega_{\text{nat}}^2$ , so the desired nutation is described by

$$\theta_{\text{ideal}} = \frac{I \Omega_\eta}{K} \dot{\phi} = \begin{cases} \frac{I}{I'} \frac{\dot{\phi}}{\omega_{\text{nat}}} \frac{\Omega_0}{\omega_{\text{nat}}} \sin \gamma \sin \left( \frac{\pi t}{\tau} \right) & \text{if } 0 \leq t \leq \tau \\ 0 & \text{if } t > \tau \end{cases}. \quad (5)$$

In general, the spin rate will be much larger than the rate at which the aircraft rotates, so  $\dot{\phi} \gg \Omega_0$ , which means that  $\beta_\phi \approx \dot{\phi}$ . When this condition applies,  $\Theta$ , which is defined in Eqs. (1), is the coefficient appearing in  $\theta_{\text{ideal}}$  multiplied by the frequency response factor  $1/D$ . Thus comparing Eq. (3) to  $\theta_{\text{ideal}}$  in Eq. (5) for  $t < \tau$  shows that the ideal response will be obtained if  $D$  is as close to unity as possible and  $\delta$  is very small. In addition  $\sigma \omega_{\text{nat}}$  should be very large, so that the exponential factor quickly decays. Furthermore, if  $\sigma \omega_{\text{nat}}$  is very large, then Eq. (4) indicates that  $\theta$  will decay to zero soon after  $t = \tau$ , which matches the ideal response in Eq. (5) for  $t > \tau$ .


Because  $\sigma < 1$ , the condition of large  $\sigma \omega_{\text{nat}}$  requires that  $\omega_{\text{nat}}$  itself be large. In addition, the analysis began with the requirements that  $\dot{\phi} \gg \Omega_\eta$ ,  $\Omega_\xi$  and  $\dot{\Omega}_\xi / \Omega_\eta$ . The first two conditions are met when the spin rate is sufficiently high to warrant approximating  $\beta_\phi$  as  $\dot{\phi}$ . The third condition requires  $\dot{\phi} \gg \pi / \tau$ .

Fortunately, simultaneous satisfaction of each condition is attained if the natural frequency  $\omega_{\text{nat}}$  is very high, the damping ratio  $\sigma$  is as large as possible, subject to the condition that  $\sigma < 1$ , and the spin rate is much higher than both the airplane's peak angular velocity and the fluctuation rate  $\pi / \tau$  of that angular velocity. These requirements are not difficult to meet, because the spin, roll, and yaw motions of even

## HOMEWORK PROBLEMS


**EXERCISE 10.1** An axially symmetric Earth satellite, whose ratio of principal moments of inertia is  $I/I' = 1.6$ , precesses about its axis once every 2 s. The spin rate in this state is 0.1 rad/s. Determine the overall rate of rotation and the angle from the axis of symmetry to the precession axis. Then determine the minimum angular impulse that a set of control rockets fastened to the satellite must exert in order to bring the precession axis into coincidence with the axis of symmetry. What is the rotation rate of the satellite at the conclusion of such a maneuver? (Assume that the rockets act impulsively.)

**EXERCISE 10.2** A coin is tossed into the air with plane horizontal and its initial angular velocity at  $15^\circ$  off-vertical, as shown in the sketch. Construct the space and body cones at the instant of release, and also evaluate the precession and spin rates.



Exercise 10.2


**EXERCISE 10.3** The cylinder, whose mass is 20 kg, translates downward at  $v = 40$  m/s with its axis of symmetry horizontal. The spin rate about that axis is  $\Omega = 50$  rad/s. Its circular edge collides with the ledge, with the result that its center of mass has a downward velocity of 10 m/s immediately after the collision. Friction between the cylinder and the ledge is negligible. Describe the rotational motion of the cylinder after impact.



Exercise 10.3

**EXERCISE 10.4** Prove that the polhode description of free motion for an arbitrary body reduces to the space and body cone analogy when the body is axisymmetric.

**EXERCISE 10.5** The communications satellite was precessing steadily about its  $z$  axis at 2 rad/s when the steering thruster was turned on, resulting in the application of an average thrust force of 20 kN for a 100 ms interval. The inertia properties relative to the principal  $xyz$  axes are  $I_{xx} = 750$ ,  $I_{yy} = I_{zz} = 1500$  kg-m<sup>2</sup>. (From the viewpoint of inertia the satellite may be considered to be axisymmetric relative to the  $x$  axis.) Determine the orientation of the satellite's angular momentum when the thruster was turned off. Then determine the nutation angle, and the precession and spin rates for the subsequent free motion.




Exercise 10.5

## Homework Problems

695

Then the rotation of the gimbal consists of precession  $\psi$  about the direction indicated by  $\bar{H}$  and a nutation  $\theta_g$  about the gimbal axis. Correspondingly, the rotation of the satellite relative to the gimbal is  $\theta$  in the opposite sense from  $\theta_g$  and the rotation of the flywheel relative to the gimbal is  $\phi$  about the spin axis, with  $\dot{\phi} = \Omega$ .

**EXERCISE 10.14** The device shown is a gyropendulum, which has been used in some applications to locate the vertical direction. The spin rate  $\dot{\phi}$  is held constant by a servomotor. Let  $m$  be the mass, and let  $I$  and  $I'$  be the centroidal principal moments of inertia of the flywheel parallel and transverse to the spin axis; ignore the inertia of the gimbals. Evaluate the nutation response  $\theta(t)$  and the precessional response  $\psi(t)$  of the flywheel to a disturbance that causes it to rotate by very small angles away from the vertical reference position, at which  $\theta = \pi/2$ . Compare the frequency of these responses with that of a simple pendulum, and use that result to discuss an advantage of the gyropendulum.



Exercise 10.14

**EXERCISE 10.15** Consider the gyropendulum in Exercise 10.14. Because of movement of the vehicle, the center point  $O$  has a constant acceleration  $\dot{v}$  directed parallel to the axis of the outer gimbal (that is,  $\bar{a}_O = \dot{v}\bar{e}_{B/A}$ ). Let this acceleration be directed at angle  $\beta$  north of east. Derive equations of motion for the Eulerian angles including the effect of the Earth's rotation, and of the movement of the vehicle in a great circle at angular speed  $v/R_e$ .

**EXERCISE 10.16** The platform of an integrating gyroscope rotates about the  $\eta$  axis in a time-dependent manner. Consider an angular speed that consists of an average value  $\Omega_0$ , over which is superposed a harmonic fluctuation at amplitude  $\Omega_1$  and frequency  $\lambda$ , that is,  $\Omega_\eta = \Omega_0 + \Omega_1 \sin(\lambda t)$ . What conditions must be true if the nutational response  $\theta(t)$  following the initial transient phase is to be proportional to the mean rotation  $\Omega_0$ ?


**EXERCISE 10.17** A top is initially in a state of steady precession at a precession rate  $\dot{\psi}^*$  and a nutation angle  $\theta^*$ . Application of an impulsive force in the direction of the precession suddenly changes the precession rate by the amount  $\varepsilon\dot{\psi}^*$ , where  $|\varepsilon| \ll 1$ . It is desired to determine the precessional and nutational responses after cessation of the impulsive force. Toward that end, perform a perturbation analysis of the basic motion equations for a top, Eqs. (10.2.4) and (10.2.6), with  $\dot{\psi} = \dot{\psi}^* + \varepsilon\dot{\psi}_1$ ,  $\theta = \theta^* + \varepsilon\theta_1$ , and  $\phi = \phi^* + \varepsilon\phi_1$ , where the quantities having a subscript "1" are not large.

**EXERCISE 10.18** Whirling is a phenomenon in turbomachinery in which a rotating shaft undergoes displacement as a beam, with the plane in which the displacement occurs rotating at an angular speed that might differ from the shaft speed. To study this effect,

## Appendix

### CENTROIDAL INERTIA PROPERTIES\*


#### Slender bar



$$m = \rho AL,$$

$$I_{xx} \approx 0, \quad I_{yy} = I_{zz} = \frac{1}{12}mL^2.$$

#### Cylinder




$$m = \pi \rho R^2 L,$$

$$I_{xx} = I_{yy} = \frac{1}{12}m(3R^2 + L^2), \quad I_{zz} = \frac{1}{2}mR^2.$$

\* Products of inertia that are not listed are zero.

### Semicylinder




$$m = \frac{1}{2} \pi \rho R^2 L,$$

$$I_{xx} = \left( \frac{1}{4} - \frac{16}{9\pi^2} \right) m R^2 + \frac{1}{12} m L^2,$$

$$I_{yy} = \frac{m}{12} (3R^2 + L^2), \quad I_{zz} = \left( \frac{1}{2} - \frac{16}{9\pi^2} \right) m R^2.$$


### Rectangular parallelepiped



$$m = \rho abc,$$

$$I_{xx} = \frac{1}{12} m (b^2 + c^2), \quad I_{yy} = \frac{1}{12} m (a^2 + c^2), \quad I_{zz} = \frac{1}{12} m (a^2 + b^2).$$

### Right prism





## Appendix


699

$$m = \frac{1}{2}\rho abc,$$

$$I_{xx} = \frac{1}{18}m(b^2 + c^2), \quad I_{yy} = \frac{1}{36}m(3a^2 + 2c^2), \quad I_{zz} = \frac{1}{36}m(3a^2 + 2b^2),$$

$$I_{yz} = -\frac{1}{36}mbc,$$

## Right tetrahedron




$$m = \frac{1}{6}\rho abc,$$

$$I_{xx} = \frac{3}{80}m(b^2 + c^2), \quad I_{yy} = \frac{3}{80}m(a^2 + c^2), \quad I_{zz} = \frac{3}{80}m(a^2 + b^2),$$

$$I_{xy} = -\frac{1}{80}mab, \quad I_{yz} = -\frac{1}{80}mbc, \quad I_{xz} = -\frac{1}{80}mac.$$

## Sphere




$$m = \frac{4}{3}\pi\rho R^3,$$

$$I_{xx} = I_{yy} = I_{zz} = \frac{2}{5}mR^2.$$

700

Appendix


### Hemisphere



$$m = \frac{2}{3}\pi\rho R^3,$$

$$I_{xx} = I_{yy} = \frac{83}{320}mR^2, \quad I_{zz} = \frac{2}{5}mR^2.$$


### Ellipsoid



$$m = \frac{4}{3}\pi\rho abc,$$

$$I_{xx} = \frac{1}{5}m(b^2 + c^2), \quad I_{yy} = \frac{1}{5}m(a^2 + c^2), \quad I_{zz} = \frac{1}{5}m(a^2 + b^2).$$


### Semiellipsoid



$$m = \frac{2}{3}\pi\rho abc,$$

$$I_{xx} = m\left(\frac{1}{5}b^2 + \frac{19}{320}c^2\right), \quad I_{yy} = m\left(\frac{1}{5}a^2 + \frac{19}{320}c^2\right), \quad I_{zz} = \frac{1}{5}m(a^2 + b^2).$$


**Semicircular plate ( $h \ll R$ )**



$$m = \frac{1}{2} \pi \rho R^2 h,$$

$$I_{xx} = \frac{1}{4} m R^2, \quad I_{yy} = \left( \frac{1}{4} - \frac{16}{9\pi^2} \right) m R^2, \quad I_{zz} = I_{xx} + I_{yy}.$$


**Semicircular wire arc**



$$m = \pi \rho A R,$$

$$I_{xx} = \left( \frac{1}{2} - \frac{4}{\pi^2} \right) m R^2, \quad I_{yy} = \frac{1}{2} m R^2, \quad I_{zz} = I_{xx} + I_{yy}.$$

**Monomial sector plate ( $h \ll a, b$ )**



$$m = \frac{1}{n+1} \rho h a b,$$

$$I_{xx} = \left[ \frac{n+1}{3(3n+1)} - \frac{(n+1)^2}{4(2n+1)^2} \right] m b^2, \quad I_{yy} = \left[ \frac{n+1}{n+3} - \frac{(n+1)^2}{(n+2)^2} \right] m a^2,$$

$$I_{zz} = I_{xx} + I_{yy}, \quad I_{xy} = \left[ \frac{1}{4} - \frac{(n+1)^2}{(2n+1)(n+2)} \right] m a b.$$

## Answers to Selected Homework Problems

- 1.1  $\bar{F} = 3009\bar{i} - 3492\bar{j} + 1937\bar{k}$  N,  $\bar{M}_A = 7749\bar{i} - 12034\bar{k}$ ,  $M_{\text{shaft}} = -11624$  N-m.
- 1.4  $c_1 = -143.39$ ,  $c_2 = -0.534501$ ,  $c_3 = 440.334$  rad/s.
- 1.6  $F^1 = 336.8$ ,  $F^2 = 386.2$  N.
- 1.8  $\bar{v}_P = [\varepsilon\alpha \cos(\alpha t) \cos \theta - R\alpha t \sin \theta]\bar{i} + [\varepsilon\alpha \cos(\beta t) \sin \theta + R\alpha t \cos \theta]\bar{j}$ ,  
 $\theta = \frac{1}{2}\alpha t^2$ ,  $\bar{v}_{\parallel} = \varepsilon\alpha \cos(\alpha t)$ ,  $\bar{v}_{\perp} = R\alpha t$ .
- 1.10  $\bar{v} = [\dot{x} + L_1\dot{\theta}_1 \cos \theta_1 + L_2(\dot{\theta}_1 + \dot{\theta}_2) \cos(\theta_1 + \theta_2)]\bar{i}$   
 $- [L_1\dot{\theta}_1 \sin \theta_1 + L_2(\dot{\theta}_1 + \dot{\theta}_2) \sin(\theta_1 + \theta_2)]\bar{j}$ ,  
 where  $\dot{x} = 1000 \cos(50t)$  mm/s,  $\dot{\theta}_1 = -10\pi \sin(50t)$  rad/s,  
 $\dot{\theta}_2 = 10\pi \cos(50t - \pi/3)$  rad/s.
- 2.1  $\bar{v} = [2gR \sin(s/R)]^{1/2} \bar{e}_t$ ,  $\bar{a} = g \cos(s/R) \bar{e}_t + 2g \sin(s/R) \bar{e}_n$ .
- 2.3 (a)  $s = s_0/4$ ; (b)  $s = s_0/2$ ; (c)  $R = 2s_0/\pi$ ; (d)  $\sin(\pi s/s_0) = (2/3)^{1/2}$ .
- 2.6  $\bar{v} = (0.1451\bar{i} - 0.4785\bar{j})\beta$ ,  $\bar{a} = (0.105280\bar{i} - 0.347154\bar{j})(\beta^2/k)$ .
- 2.9  $\bar{v} = v_0(1 - k\beta \sinh \eta) \left( \frac{\bar{i} + \sinh \eta \bar{j}}{\cosh \eta} \right)$ ,  
 $\bar{a} = -v_0^2 k(1 - k\beta \sinh \eta) \left( \frac{\bar{i} + \sinh \eta \bar{j}}{\cosh \eta} \right) + \frac{v_0^2}{\beta} (1 - k\beta \sinh \eta)^2 \left[ \frac{-\sinh \eta \bar{i} + \bar{j}}{(\cosh \eta)^3} \right]$ .
- 2.11  $\bar{e}_t = -0.4804\bar{i} + 0.27740\bar{j} + 0.8321\bar{k}$ ,  $\bar{e}_n = -0.5160\bar{i} + 0.6769\bar{j} - 0.5241\bar{k}$ ,  
 $\bar{e}_b = -0.7086\bar{i} - 0.6818\bar{j} - 0.1818\bar{k}$ ,  $\rho = 6.392$  m,  $\tau = 40.33$  m.
- 2.14  $\bar{e}_b = \frac{\rho}{(s')^3} \bar{r}' \times \bar{r}''$ ,  $\tau = \frac{(s')^6}{\rho^2 (\bar{r}' \times \bar{r}'') \cdot \bar{r}'''}$ ,  
 where  $\rho = \frac{(s')^3}{[(\bar{r}'' \cdot \bar{r}'')(s')^2 - (\bar{r}' \cdot \bar{r}'')^2]^{1/2}}$ .
- 2.16  $\bar{v} = L\beta [-\sin(\beta t)\bar{i} + \cos(\beta t)\bar{j} - 2\sin(2\beta t)\bar{k}]$ ,  
 $\bar{a} = L\beta^2 [-\cos(\beta t)\bar{i} - \sin(\beta t)\bar{j} - 4\cos(2\beta t)\bar{k}]$ .
- 2.19 (a)  $x = 32.72$  m; (b)  $\beta = 35.61^\circ$ .
- 2.21 (a)  $v_0 = 0.2887 \left( \frac{\alpha H^3}{m} \right)^{1/2}$ ; (b)  $t_f = 1.3095 \left( \frac{m}{\alpha H} \right)^{1/2}$ ;  $y_f = 0.8574 \left( \frac{mg}{\alpha H} \right)$ .

- 2.24 (a)  $\bar{v} = u\bar{i} + \frac{\pi Hu}{L} \cos\left(\frac{\pi x}{L}\right) \bar{j}$ ,  $\bar{a} = -\frac{\pi^2 Hu^2}{L^2} \sin\left(\frac{\pi x}{L}\right) \bar{j}$ ;  
 (b)  $\max(v) = u \left[ 1 + \left( \frac{\pi H}{L} \right)^2 \right]^{1/2}$  at  $x = nL$ ,  $n$  is an integer;  
 (c)  $\max(|\bar{a}|) = \frac{\pi^2 Hu^2}{L^2}$  at  $x = \frac{2n-1}{2}L$ ; (d)  $u < \left( \frac{gL^2}{\pi^2 H} \right)^{1/2}$ .
- 2.26  $x = \frac{\dot{y}_0}{u} [1 - \cos(\mu t)] + \frac{\dot{x}_0}{u} \sin(\mu t)$ ,  $y = \frac{\dot{y}_0}{u} \sin(\mu t) - \frac{\dot{x}_0}{u} [1 - \cos(\mu t)]$ ,  
 $z = \dot{z}_0 t$ , helical path.
- 2.28  $\bar{v} = (c\beta)^{1/2} \lambda \bar{e}_R - \frac{2\pi}{3} (c\beta)^{1/2} \gamma \lambda \bar{e}_\theta + \frac{8\pi}{3} \lambda \beta \bar{e}_z$ ,  
 $\bar{a} = -\frac{\pi}{3} (c\beta)^{1/2} \gamma^2 \lambda^2 \bar{e}_R + \left( \frac{2\pi}{\sqrt{3}} - 1 \right) (c\beta)^{1/2} \gamma \lambda^2 \bar{e}_\theta + 2\beta \lambda^2 \bar{e}_z$ .
- 2.31  $\bar{v} = u \cot \theta \bar{e}_R + L\Omega \sin \theta \bar{e}_\theta - u \bar{e}_z$ ,  $\bar{a} = -\left( \frac{u^2}{L(\sin \theta)^3} + L\Omega^2 \sin \theta \right) \bar{e}_R + 2\Omega u \cot \theta \bar{e}_\theta$ .
- 2.33  $N = 555.7 \text{ N}$ ,  $\mu = 1.788$ .
- 2.36  $\bar{v} = ah(\dot{\alpha} \bar{e}_\alpha + \dot{\beta} \bar{e}_\beta)$ ,  
 $\bar{a} = a \left[ h\ddot{\alpha} + \frac{\dot{\alpha}^2 - \dot{\beta}^2}{h} (\sinh \alpha) (\cosh \alpha) - 2 \frac{\dot{\alpha}\dot{\beta}}{h} (\sin \beta) (\cos \beta) \right] \bar{e}_\alpha$   
 $+ \left[ h\ddot{\beta} + \frac{\dot{\alpha}^2 - \dot{\beta}^2}{h} (\sin \beta) (\cos \beta) + 2 \frac{\dot{\alpha}\dot{\beta}}{h} (\sinh \alpha) (\cosh \alpha) \right] \bar{e}_\beta$ .
- 2.39  $v = 12.329 \text{ m/s}$ ,  $\dot{v} = 8.922 \text{ m/s}^2$ ,  $\rho = 0.2689 \text{ m}$ .
- 2.41  $\bar{v} = (\dot{R} \cos \theta - R\dot{\theta} \sin \theta) \bar{i} + (\dot{R} \sin \theta + R\dot{\theta} \cos \theta) \bar{j}$ ,  
 $\bar{a} = (\ddot{R} \cos \theta - 2\dot{R}\dot{\theta} \sin \theta - R\ddot{\theta} \sin \theta - R\dot{\theta}^2 \cos \theta) \bar{i}$   
 $+ (\ddot{R} \sin \theta + 2\dot{R}\dot{\theta} \cos \theta + R\ddot{\theta} \cos \theta - R\dot{\theta}^2 \sin \theta) \bar{j}$ .
- 2.44  $v = A\omega \left[ 1 + 3(\sin \theta)^2 \right]^{1/2}$ ,  $\dot{v} = 3\omega^2 A \frac{\sin \theta \cos \theta}{\left[ 1 + 3(\sin \theta)^2 \right]^{1/2}}$ ,  
 $\bar{a} \cdot \bar{e}_n = \frac{2\omega^2 A}{\left[ 1 + 3(\sin \theta)^2 \right]^{1/2}}$ .
- 2.46  $\dot{r} = -350.0 \text{ m/s}$ ,  $\dot{\lambda} = 0.06239 \text{ rad/s}$ ,  $\dot{\theta} = -0.0324 \text{ rad/s}$ ,  
 $\ddot{r} = 40.40 \text{ m/s}^2$ ,  $\ddot{\lambda} = 0.02345 \text{ rad/s}^2$ ,  $\ddot{\theta} = -0.00516 \text{ rad/s}^2$ .
- 2.49  $\bar{v} = \dot{\theta} (R' \bar{e}_R + R \bar{e}_\theta)$ ,  $\bar{a} = \dot{\theta}^2 [(R'' - R) \bar{e}_R + 2R' \bar{e}_\theta]$ ,  $\rho = \frac{[(R')^2 + R^2]^{3/2}}{R''R - R^2 - 2(R')^2}$ .
- 2.51  $\bar{v} = 29.48 \text{ m/s}$ ,  $\bar{a} = -781.3 \text{ m/s}^2$ ,  $F = 280.4 \text{ N}$ .
- 2.54  $v = 30.05 \text{ m/s}$ ,  $\dot{v} = -520.8 \text{ m/s}^2$ ,  $F = 40.01 \text{ N}$ .

Answers to Selected Homework Problems

705

$$3.1 \quad [R] = \begin{bmatrix} 0.8321 & -0.5547 & 0 \\ 0.3714 & 0.5571 & 0.7428 \\ -0.412 & -0.618 & 0.6695 \end{bmatrix}, \quad \bar{r}_{C/A} = 0.4828\bar{j} - 0.5356\bar{k} \text{ m.}$$

$$3.4 \quad [R] = \begin{bmatrix} -0.9285 & 0.3714 & 0 \\ -0.1564 & -0.3910 & 0.9070 \\ 0.3369 & 0.8422 & 0.4211 \end{bmatrix}, \quad \bar{r}_{O/A} = 46.42\bar{i} + 7.82\bar{j} - 16.84\bar{k} \text{ m.}$$

$$3.6 \quad (a) [x_E \ y_E \ z_E] = [-75.09 \ -48.32 \ -42.73] \text{ mm;}$$

$$(b) [X_E \ Y_E \ Z_E] = [-1.62 \ -98.80 \ -6.06] \text{ mm.}$$

$$3.9 \quad \beta = \cos^{-1}(0.7192 \cos \theta - 0.6428 \sin \theta).$$

$$3.11 \quad [X_C \ Y_C \ Z_C] = [0.1465 \ 0.3357 \ 0.0766] \text{ m.}$$

$$3.14 \quad \phi = 77.14^\circ \text{ about } \bar{K}' = 0.9265\bar{I} - 0.3258\bar{J} - 0.1881\bar{K}.$$

$$3.16 \quad [R] = \begin{bmatrix} 0.3185 & 0.8209 & -0.4740 \\ -0.8209 & 0.4889 & 0.29510 \\ 0.4740 & -0.29510 & 0.8296 \end{bmatrix}, \quad 50.58^\circ \text{ between original and new } y \text{ axes.}$$

$$3.19 \quad \Delta \bar{r}_C = -406.9\bar{I} - 378.6\bar{J} - 505.1\bar{K} \text{ mm.}$$

$$3.21 \quad \Delta \bar{r}_C = -171.88\bar{I} + 173.38\bar{J} - 13.76\bar{K} \text{ mm.}$$

$$3.24 \quad \Delta \bar{r}_C = -49.65\bar{I} - 33.59\bar{J} + 5.30\bar{K} \text{ mm,}$$

$$\bar{v}_C(t=0) \Delta t = -56.12\bar{I} - 25.55\bar{J} + 5.80\bar{K} \text{ mm.}$$

$$3.26 \quad \bar{\omega} = 1000\pi\bar{i} + 0.16667\bar{k} \text{ rad/s, } \bar{\alpha} = 166.7\pi\bar{j} \text{ rad/s}^2,$$

where  $\bar{i} = \bar{e}_t$  and  $\bar{j} = \bar{e}_n$  for the airplane's path.

$$3.29 \quad \theta = 90^\circ: \bar{\omega} = 5236\bar{j} - 20\bar{k} \text{ rad/s, } \bar{\alpha} = 104720\bar{i} + 100\bar{k} \text{ rad/s}^2.$$

$$\theta = 60^\circ: \bar{\omega} = 5246\bar{j} - 17.32\bar{k} \text{ rad/s, } \bar{\alpha} = 90690\bar{i} - 50\bar{j} + 86.60\bar{k} \text{ rad/s}^2.$$

$$3.32 \quad \bar{\omega} = -0.4330(\dot{\theta} + 2\dot{\beta})\bar{i} + 0.5(\dot{\theta} + 2\dot{\gamma})\bar{j} + 0.250(3\dot{\theta} - 2\dot{\beta})\bar{k},$$

$$\bar{\alpha} = -0.250(\dot{\theta}\dot{\beta} + 3\dot{\theta}\dot{\gamma} - 2\dot{\beta}\dot{\gamma})\bar{i} - 0.8660\dot{\theta}\dot{\beta}\bar{j} + 0.4330(\dot{\theta}\dot{\beta} - \dot{\theta}\dot{\gamma} - 2\dot{\beta}\dot{\gamma})\bar{k}.$$

$$3.34 \quad \bar{a}_C = [L\ddot{\theta} \sin 2\theta - L\dot{\theta}^2(9 + \cos 2\theta)]\bar{i} + [L\ddot{\theta}(3 + \cos 2\theta) + L\dot{\theta}^2 \sin 2\theta]\bar{j}, \quad \bar{i} = \bar{e}_{C/B}.$$

$$3.37 \quad \bar{a}_{B/A} = (-\Omega^2 H + 2\Omega\dot{\theta} W \sin \theta)\bar{i} - (\Omega^2 + \dot{\theta}^2)W(\cos \theta)\bar{j} - \dot{\theta}^2 W \sin \theta \bar{k}.$$

$$3.39 \quad \bar{v}_E = -(226.2L + 102.6R)\bar{j} - 10(L + R)\bar{k},$$

$$\bar{a}_E = -(2.285L + 1.064R)10^4\bar{i} + 1508(L + R)\bar{j} - (1.656L + 0.740)10^4\bar{k}.$$

$$3.42 \quad \bar{v}_A = -32.83\bar{i} - 11.736\bar{j} + 35.68\bar{k} \text{ m/s, } \bar{a}_A = -1259.4\bar{i} - 811.4\bar{j} - 1586.7\bar{k} \text{ m/s}^2,$$

where  $\bar{j} = \bar{e}_{B/A}$  and  $\bar{k} = \bar{e}_{B/A} \times \bar{e}_{C/B} / |\bar{e}_{B/A} \times \bar{e}_{C/B}|$ .

- 3.45  $\bar{\omega} = \left( \frac{v}{\tau} + v \frac{d\beta}{ds} \right) \bar{e}_t + \frac{v}{\rho} \bar{e}_b,$   
 $\bar{\alpha} = \left( \frac{\dot{v}}{\tau} - \frac{v^2}{\tau^2} \frac{d\tau}{ds} + \dot{v} \frac{d\beta}{ds} + v^2 \frac{d^2\beta}{ds^2} \right) \bar{e}_t + \frac{v^2}{\rho} \frac{d\beta}{ds} \bar{e}_n + \left( \frac{\dot{v}}{\rho} - \frac{v^2}{\rho^2} \frac{d\rho}{ds} \right) \bar{e}_b.$
- 3.47  $\dot{u} = (50 - \sin \theta) g + \dot{\theta}^2 L + \Omega^2 L (\cos \theta)^2,$   
 $N_{\text{horizontal}} = 2m\Omega (u \cos \theta - \dot{\theta} L \sin \theta), \quad N_{\text{vertical}} = m (g \cos \theta + \Omega^2 L \sin \theta + 2\dot{\theta} u).$
- 3.50  $\bar{v}_B = \dot{\xi} \bar{i} + \Omega \xi \sin \theta \bar{j} + \dot{\theta} \xi \bar{k},$   
 $\bar{a}_B = [\ddot{\xi} - \dot{\theta}^2 \xi - \Omega^2 \xi (\sin \theta)^2] \bar{i} + [2\Omega \xi \sin \theta + 2\Omega \dot{\theta} \xi \cos \theta] \bar{j}$   
 $+ [\ddot{\theta} \xi - \Omega^2 \xi \sin \theta \cos \theta + 2\dot{\theta} \dot{\xi}] \bar{k}.$
- 3.52  $\bar{\omega} = -0.9397\Omega \cos \phi \bar{i} + (0.3420\Omega + \dot{\phi}) \bar{j} - 0.9397\Omega \sin \theta \bar{k},$   
 $\bar{\alpha}_D = 0.9397\Omega \dot{\phi} \sin \phi \bar{i} + \ddot{\phi} \bar{j} - 0.9397\Omega \sin \phi \bar{k}.$   
 $\bar{v}_D = 1.9397\Omega L \sin \phi \bar{i} - 0.9397\Omega L \sin \phi \bar{j}$   
 $+ (-1.9397\Omega L \cos \phi - 0.3420\Omega L - L\dot{\phi}) \bar{k}$   
 $\bar{a}_D = L \left[ (-1 - 0.6634 \cos \phi + 0.8830 (\cos \phi)^2) \Omega^2 - \dot{\phi}^2 - 0.6480 \Omega \dot{\phi} \right] \bar{i}$   
 $- L [(1.8227 + 0.3214 \cos \phi) \Omega^2 + 1.8194 (\cos \phi) \Omega \dot{\phi}] \bar{j}$   
 $+ [-\ddot{\phi} + (0.8830 \cos \phi - 0.6634) (\sin \phi) \Omega^2] \bar{k}$
- 3.55  $(\bar{v}_B)_{x_2 y_2 z_2} = 45.06 \bar{i} - 41.30 \bar{j} \text{ m/s}, \quad (\bar{a}_B)_{x_2 y_2 z_2} = -19767 \bar{i} - 5072 \bar{j} \text{ m/s}^2.$
- 3.57  $\bar{a}_P = 2.343 \bar{i} - 9.145 \bar{j} - 5.553 \bar{k} \text{ m/s}^2.$
- 3.60  $s = \left[ \left( \frac{u}{2\omega_e \sin \lambda} \right)^2 - d^2 \right]^{1/2} + \left( \frac{u}{2\omega_e \sin \lambda} \right) \text{ to the right.}$
- 3.62 (a)  $x = 0, \quad y = -\cos \lambda \left( \frac{2\omega_e H}{g} \right)^{1/2} \left( \frac{2H}{3} \right);$   
 (b)  $x = 0, \quad y = \cos \lambda \left( \frac{2\omega_e H}{g} \right)^{1/2} \left( \frac{H}{3} + R_e \right).$
- 4.1  $\bar{v}_D = (R\omega_1 \cos \beta - R\omega_2 - L\dot{\beta}) \bar{i} + L\omega_1 \sin \beta \bar{j} - R\omega_1 \sin \beta \bar{k},$   
 $\bar{a}_D = (L\omega_1^2 \sin \beta \cos \beta - L\ddot{\beta}) \bar{i} + [-R(\omega_1^2 + \omega_2^2) + 2\omega_1 (L\dot{\beta} + R\omega_2) \cos \beta] \bar{j}$   
 $- [\omega_1^2 L (\sin \beta)^2 + L\dot{\beta}^2 + 2R\omega_2 \dot{\beta}] \bar{k}.$
- 4.3  $\dot{\phi} = 97.93 \text{ rad/s}, \quad \dot{\theta} = -20 \text{ rad/s}, \quad \dot{\psi} = -48.44 \text{ rad/s},$   
 $\bar{\omega} = 10.12 \bar{i} - 19.19 \bar{j} + 50.22 \bar{k} \text{ rad/s}.$
- 4.6  $[R] = [R_x(\phi)][R_y(\theta)][R_z(\psi)],$   
 $\bar{\omega} = (\dot{\phi} - \dot{\psi} \sin \theta) \bar{i} + (\dot{\theta} \cos \theta + \dot{\psi} \sin \phi \cos \theta) \bar{j} + (-\dot{\theta} \sin \theta + \dot{\psi} \cos \phi \cos \theta) \bar{k},$   
 $\bar{\alpha} = [\ddot{\phi} - \ddot{\psi} \sin \theta - \dot{\psi} \dot{\theta} \cos \theta] \bar{i} + [\ddot{\psi} \cos \theta \sin \phi + \ddot{\theta} \cos \phi - \dot{\psi} \dot{\theta} \sin \theta \sin \phi]$   
 $+ \dot{\psi} \dot{\phi} \cos \theta \cos \phi - \dot{\theta} \dot{\phi} \sin \phi] \bar{j} + [\ddot{\psi} \cos \theta \cos \phi - \ddot{\theta} \sin \phi - \dot{\psi} \dot{\theta} \sin \theta \cos \phi]$   
 $- \dot{\psi} \dot{\phi} \cos \theta \sin \phi - \dot{\theta} \dot{\phi} \cos \phi] \bar{k}.$

$$4.41 \quad \text{Precession: } \dot{\psi} = \Omega_1 + \frac{(\Omega_1 - \Omega_2)}{(\sin \beta)^2} \left[ \left( \frac{R}{r} - 1 \right) \cos \beta - 1 \right],$$

$$\text{Spin: } \dot{\phi} = \frac{(\Omega_1 - \Omega_2)}{(\sin \beta)^2} \left( \frac{R}{r} - 1 - \cos \beta \right),$$

$$\bar{\omega} = (\dot{\psi} \cos \beta + \dot{\phi}) \bar{i} + \dot{\psi} \sin \beta \bar{k}, \quad \bar{\alpha} = \dot{\phi} \dot{\psi} \sin \beta \bar{j},$$

$\bar{i}$  parallel to the cone generator,  $\bar{k}$  upward.

$$4.44 \quad \psi = 33.69^\circ, \quad \dot{\psi} = -15.428 \text{ rad/s}, \quad \dot{\theta} = 0.6934 \text{ rad/s}, \quad \dot{\phi} = 13.699 \text{ rad/s}.$$

$$4.46 \quad \bar{\omega} = 2\Omega (1 + \cos \beta) \bar{i} + \frac{u}{R(\sin \beta - 2 \cos \beta)} \bar{j} - \Omega \cos \beta \bar{k},$$

$$\bar{\alpha} = -\frac{2\Omega u \sin \beta}{R(\sin \beta - 2 \cos \beta)} \bar{i} - [\ddot{\beta} - \Omega^2 \cos \beta (2 + 2 \cos \beta - \sin \beta)] \bar{j} \\ + \frac{2\Omega u (1 + \cos \beta - \sin \beta)}{R(\sin \beta - 2 \cos \beta)} \bar{k}, \quad \bar{i} = \bar{e}_{C/B}, \quad \bar{k} \text{ upward}.$$

$$5.1 \quad \text{Initial } \bar{H}_O = 2mh^2\Omega \sin \theta (-\sin \theta \bar{i} + \cos \theta \bar{j}),$$

$$\Delta \bar{H}_O = -mh^2\Omega \sin 2\theta [1.523 (10^{-4}) \bar{j} + 0.01745 \bar{k}],$$

where  $XYZ$  is stationary, with  $X$  aligned with the shaft and  $Z$  perpendicular to the initial plane of the bars.

$$5.6 \quad m = \frac{7}{12} \pi \rho R^2 L, \quad I_{xx} = \frac{31}{160} \pi \rho R^4 L, \quad I_{yy} = I_{zz} = \pi \rho R^2 L \left( \frac{31}{320} R^2 + \frac{2}{15} L^2 \right).$$

$$5.9 \quad m = 6.369 \text{ kg}, \quad x_G = 1.1078 \text{ m}, \quad y_G = 0.5847 \text{ m},$$

$$I_{xx} = 3.544, \quad I_{yy} = 9.931, \quad I_{zz} = 13.475 \text{ kg-m}^2, \quad I_{xy} = 5.776 \text{ kg-m}^2.$$

$$5.11 \quad m = 414.1 \text{ kg}, \quad \bar{r}_{G/O} = 2.26 \bar{j} + 200 \bar{k} \text{ mm, centroidal } \hat{x}\hat{y}\hat{z} \text{ are principal axes with}$$

$$I_{\hat{x}\hat{x}} = 9.495, \quad I_{\hat{y}\hat{y}} = 9.498, \quad I_{\hat{z}\hat{z}} = 9.800 \text{ kg-m}^2.$$

$$5.13 \quad [I] = mR^2 \begin{bmatrix} 0.542 & 0.042 & 0 \\ 0.042 & 2.542 & 0 \\ 0 & 0 & 2.583 \end{bmatrix}.$$

$$5.16 \quad I_{xx} = 0.006667 - 0.004 (\cos \theta)^2, \quad I_{yy} = 0.002667 + 0.004 (\cos \theta)^2, \\ I_{xy} = -0.002 \sin 2\theta \text{ kg-m}^2.$$

$$5.19 \quad I_1 = 26.61 (10^{-6}), \quad I_2 = 456.7 (10^{-6}), \quad I_3 = 483.3 (10^{-6}) \text{ kg-m}^2.$$

$$5.21 \quad [I] = \begin{bmatrix} 191.5 & 229.6 & -64.8 \\ 229.6 & 1687.5 & -11.1 \\ -64.8 & -11.1 & 1613.0 \end{bmatrix} \text{ kg-m}^2.$$

$$5.26 \quad \bar{H}_C = \frac{1}{9} m L^2 \Omega \sin \theta \bar{j}, \quad d\bar{H}_C/dt = \frac{1}{9} m L^2 \Omega^2 \sin \theta \cos \theta \bar{k}.$$



$$6.16 \quad \ddot{\xi} + \dot{\psi}^2 \left[ \left( \frac{L}{4} - \xi \right) (\sin \theta)^2 - \frac{L}{6} \sin \theta \cos \theta \cos \phi \right] + \frac{L}{3} \dot{\psi} \dot{\phi} \sin \theta \cos \phi = g \cos \theta, \\ \frac{1}{27} L \ddot{\phi} - \dot{\psi}^2 \left[ \frac{1}{27} L (\sin \theta)^2 \sin \phi \cos \phi + \frac{1}{24} (L - 4\xi) \sin \theta \cos \theta \sin \phi \right] \\ - \frac{1}{3} \dot{\psi} \dot{\xi} \sin \theta \cos \phi = \frac{1}{6} g \sin \theta \sin \phi.$$

$$6.19 \quad \omega_1^2 > \frac{2gR}{0.8 + 2.5 \sin 2\theta}.$$

$$6.21 \quad N[L(1 + \cos \gamma) - R \sin \gamma] = mgL(1 + \cos \gamma) + mR^2\Omega^2 \left[ \left( \frac{L}{2R} \cos \gamma - \frac{L^2}{R^2} \sin \gamma \right) \right. \\ \left. (1 + \cos \gamma) - \frac{1}{4} \sin \gamma \cos \gamma \right], \quad \gamma = \frac{\pi}{6}.$$

$$6.24 \quad N_B = mg \cot \beta + m(R - r)\Omega_2^2 - \frac{2}{5}mr\dot{\psi}\dot{\phi} \cos \beta, \\ f_B = -\frac{2}{5}mr\dot{\phi}\dot{\psi}, \quad N_A = \frac{mg}{\sin \beta} - \frac{2}{5}mr\dot{\psi}\dot{\phi}, \\ \text{where } \dot{\phi} = \frac{R - r - r \cos \beta}{r(\sin \beta)^2}(\Omega_1 - \Omega_2) \text{ and } \dot{\psi} = \Omega_2 - \dot{\phi} \cos \beta.$$

$$6.26 \quad \text{Front-wheel drive: } \dot{v} = \mu g \frac{L - b}{L + \mu h}, \quad \text{rear-wheel drive: } \dot{v} = \mu g \frac{b}{L - \mu h}, \\ \text{all-wheel drive: } \dot{v} = \mu g.$$

$$6.29 \quad \ddot{\theta} = 0.9262 \frac{g}{L}.$$

$$6.31 \quad \ddot{\phi} = -13.845 \text{ rad/s}^2.$$

$$6.34 \quad (a) F_{\text{crit}} = \min \left( \frac{mg}{\sin \theta}, \frac{\mu mg (\kappa^2 + r_1^2)}{\kappa^2 (\cos \theta + \mu \sin \theta) + \mu r_1^2 \sin \theta + r_1 r_2} \right), \\ \dot{v} = \frac{F_{\text{crit}}}{m} \frac{r_1^2 \cos \theta - r_1 r_2}{\kappa^2 + r_1^2}.$$

$$6.36 \quad \dot{v} = \frac{1}{3}g, \quad \mu_{\min} = 0.2.$$

$$6.39 \quad F = \sigma v.$$

$$6.41 \quad \omega_A - \omega_B = \frac{gL}{R^2 \dot{\psi}}.$$

$$6.44 \quad \Delta N = 128.8 \text{ N (decrease at front wheels)}.$$

$$6.46 \quad v = 1.7194 \left( \frac{FR}{m} \right)^{1/2}.$$

$$6.49 \quad \max \phi = 37.49^\circ, \quad \dot{\phi} = 38.62 \text{ rad/s at } \phi = 37.49^\circ.$$

$$6.51 \quad v^2 = \frac{2FR^3}{m(R^2 + \kappa^2)} \left[ \theta + \sin \theta - \sqrt{5} + (8 - 2 \cos \theta - (\cos \theta)^2)^{1/2} \right].$$

$$6.54 \quad \max \phi = 37.49^\circ.$$

**Answers to Selected Homework Problems**

**711**

- 6.56 (a)  $\dot{\theta} = 4.3503 \left( \frac{g}{L} \right)^{1/2}$ , (b)  $\max(\theta) = 133.8^\circ$  above horizontal.
- 6.59 (a)  $\beta = 46.56^\circ$ ,  $\Omega_1 = 0.9494 \left( \frac{g}{L} \right)^{1/2}$ ,  
(b)  $P\Delta t = 0.1148m(gL)^{1/2}$ ,  $v_G = 1.1123(gL)^{1/2}$ .
- 6.61  $\omega_2 = \frac{mvh}{2I_A}$ , where point  $A$  is the corner where impact occurs.
- 6.64  $\omega_2 = 4.065 \text{ rad/s}$ ,  $\bar{v}_2 = 24.70 \text{ rad/s}$  at  $59.17^\circ$  above left horizontal.
- 6.66  $(\bar{v}_G)_2 = -0.2467v \sin \theta \bar{j}$ ,  $\omega_2 = -0.2220v \sin \theta$ ,  
 $\bar{v}_{\text{ball}} = (-\cos \theta \bar{i} - 0.0333 \sin \theta \bar{j})v$ .
- 6.69  $(\bar{v}_B)_2 = 0.8613v_1$  at  $50.74^\circ$  below the left direction.
- 6.71  $\bar{v}_G = 15.459 \text{ m/s}$  downward,  $\omega_2 = 17.441 \text{ rad/s}$  counterclockwise.
- 6.74  $\bar{v}_2 = 19.20\bar{i} + 1.61\bar{j} + 6\bar{k} \text{ m/s}$ ,  $\bar{\omega}_2 = 30.25\bar{i} + 170.12\bar{j} + 50\bar{k} \text{ rad/s}$ .
- 7.1  $2\beta(X-ut)\dot{X} - \dot{Y} - 2\beta(X-ut)u = 0$ ,  $Y = \beta(X-ut)^2$ .
- 7.3  $R\dot{\theta} + \dot{s} - \dot{X}_C \cos \theta + \dot{Y}_C \sin \theta = 0$ ,  $s\dot{\theta} + \dot{X}_C \sin \theta + \dot{Y}_C \cos \theta = 0$ ,  
both constraints are holonomic.
- 7.6  $\dot{x} \cos \theta - \dot{\theta} x \sin \theta = 0$ .
- 7.8  $\dot{\theta}_1 \sin \theta_1 + \dot{\theta}_2 \sin \theta_2 + \dot{\theta}_3 \sin \theta_3 = 0$ ,  $\dot{\theta}_1 \cos \theta_1 - \dot{\theta}_2 \cos \theta_2 - \dot{\theta}_3 \cos \theta_3 = 0$ .
- 7.11  $\dot{x}_A \sin(\theta + \beta) - L\dot{\theta} \cos \beta = 0$ .
- 7.14  $(\sin \beta - 2 \cos \beta)R\dot{\beta} - u = 0$ ,  $[2(1 + \cos \beta) - \sin \beta]\dot{\psi} + \dot{\phi} = 0$ .
- 7.16  $q_1 = y$ :  $Q_1^{\text{cons}} = -k(y - 1.5L) - 8\sigma L$ ,  $Q_1^{\text{nc}} = -\frac{F(3y^2 + 4L^2) + 2ML}{2L(4L^2 - y^2)^{1/2}}$ ,  
 $q_1 = \theta$ :  $Q_1^{\text{cons}} = -2kL^2(2 \sin \theta - 1.5) \cos \theta - 16\sigma L^2 \cos \theta$ ,  
 $Q_1^{\text{nc}} = -FL[2 + 6(\sin \theta)^2] - M$ .
- 7.19  $\delta W = -N_B \sin(\theta + \beta) \delta x_A + N_B L \delta \theta \cos \beta$ ,  
 $\delta x_A = L \delta \theta \frac{\cos \beta}{\sin(\theta \beta)}$  if kinematically admissible.
- 7.21  $V = -(x^2 - y^2)^{1/2}$ .
- 7.24  $m \left[ \frac{1}{3}L^2 + \frac{H^2}{(\cos \theta)^4} \right] \ddot{\theta} + 2m \frac{H^2}{(\cos \theta)^5} \dot{\theta}^2 + \frac{1}{2}mgL \cos \theta$   
 $+ kH^2 \frac{(\tan \theta - \tan \frac{\pi}{9})}{(\cos \theta)^2} + \frac{mgH}{(\cos \theta)^2} = -\Gamma$ ,  
 $\theta = 16.662^\circ$  for static equilibrium.
- 7.26  $3m\ddot{X} + m\ddot{s} \cos \theta + 2kX = 0$ ,  $m\ddot{s} + m\ddot{X} \cos \theta + ks - mg \sin \theta = 0$ .
- 7.29  $m[2\ddot{R}_1 + \ddot{R}_2 - (2R_1 + R_2)\dot{\theta}^2] + k(R_1 - L) + 2mgR_1 \sin \theta = 0$ ,  
 $m[\ddot{R}_1 + \ddot{R}_2 - (2R_1 + R_2)\dot{\theta}^2] + k(R_2 - L) + mgR_2 \sin \theta = 0$ .

$$\left\{ 4.25m_1 R^2 + m_2 R^2 \left[ 1 - 2 \sin 2\theta + 3 (\cos \theta)^2 \right] \right\} \ddot{\theta} - \frac{1}{2} m_2 R^2 (4 \cos 2\theta + 3 \sin 2\theta) \dot{\theta}^2 \\ + m_1 R^2 (4 + 3.75 \cos \theta) (\sin \theta) \dot{\psi}^2 - 2(m_1 + m_2) g R \cos \theta + m_2 g R \sin \theta \\ = F R (\sin \theta - 2 \cos \theta),$$

$$\frac{1}{2} m_1 R^2 (\ddot{\phi} + \ddot{\psi} \sin \theta + \dot{\psi} \dot{\theta} \cos \theta) = \lambda_1 R, \quad R (\sin \theta - 2 - 2 \cos \theta) \dot{\psi} + R \dot{\phi} = 0.$$

$$8.11 \quad (m_A + m_{AB}) \ddot{x}_A - \frac{1}{2} m_{AB} L (\ddot{\theta} \sin \theta + \dot{\theta}^2 \cos \theta) = F + \lambda_1 \sin (\beta + \theta),$$

$$\frac{1}{3} m_{AB} L^2 \ddot{\theta} - \frac{1}{2} m_{AB} L \ddot{x}_A \sin \theta = \lambda_1 L \cos \beta, \quad \dot{x}_A \sin (\beta + \theta) + \dot{\theta} L \cos \beta = 0.$$

$$8.13 \quad q_1 = X_C, \quad q_2 = Y_C, \quad q_3 = \theta, \quad \dot{X}_C \sin \theta - \dot{Y}_C \cos \theta = 0$$

$$\left( m + \frac{3}{2} m_w \right) \ddot{X}_C + m \ell (\ddot{\theta} \sin \theta + \dot{\theta}^2 \cos \theta) = (\bar{F}_1 + \bar{F}_2) \cdot \bar{I} + \lambda_1 \sin \theta,$$

$$\left( m + \frac{3}{2} m_w \right) \ddot{Y}_C - m \ell (\ddot{\theta} \cos \theta - \dot{\theta}^2 \sin \theta) = (\bar{F}_1 + \bar{F}_2) \cdot \bar{J} - \lambda_1 \cos \theta,$$

$$\left( I + \frac{1}{4} m_w R^2 \right) \ddot{\theta} + m \ell (\dot{X}_C \sin \theta - \dot{Y}_C \cos \theta) = \bar{r}_{A/C} \times \bar{F}_1 + \bar{r}_{B/C} \times \bar{F}_2.$$

$$8.15 \quad 4m\ddot{s} + 2mL\ddot{\theta} + 2mL\dot{\theta}^2 \cos \theta = F + \lambda_2 \sin \Omega t,$$

$$\left[ \frac{1}{6} + \frac{3}{2} (\sin \psi)^2 (\sin \theta)^2 \right] \ddot{\psi} - \frac{3}{8} \ddot{\theta} \sin 2\psi \sin 2\theta + \frac{3}{2} \dot{\psi}^2 \sin \psi \cos \psi (\sin \theta)^2 \\ + \frac{3}{4} \dot{\theta}^2 \sin 2\psi + \frac{3}{2} \dot{\psi} \dot{\theta} (\sin \psi)^2 \sin 2\theta = \frac{1}{mL} (\lambda_1 \cos \psi \sin \theta - \lambda_2 \cos \Omega t \sin \psi \sin \theta),$$

$$mL^2 \left[ \frac{1}{6} + \frac{3}{2} (\sin \theta)^2 + \frac{3}{2} (\cos \psi)^2 (\cos \theta)^2 \right] \ddot{\theta} + 2mL\dot{s} \sin \theta \\ + \frac{3}{2} mL^2 \dot{\theta}^2 \sin 2\theta \left[ 1 + (\cos \psi)^2 \right] - \frac{1}{2} mL^2 \dot{\psi}^2 \left[ \frac{1}{3} + 3 (\sin \psi)^2 \right] \sin 2\theta \\ = \lambda_1 L \sin \psi \cos \theta + \lambda_2 L [\sin \Omega t \sin \theta + \cos \Omega t \cos \psi \cos \theta],$$

$$L\dot{\psi} \cos \psi \sin \theta + L\dot{\theta} \sin \psi \cos \theta = 0,$$

$$\dot{s} \sin \Omega t - L\dot{\psi} \cos \Omega t \sin \psi \sin \theta + L\dot{\theta} [\sin \Omega t \sin \theta + \cos \Omega t \cos \psi \cos \theta] \\ + \Omega \left[ s \cos \Omega t - L \sin \Omega t \cos \psi \sin \theta - L (\cos \Omega t)^2 \right] = 0.$$

$$8.17 \quad X_G = -111.2 \text{ m}, \quad Y_G = -70.0 \text{ m}, \quad \theta = 56.2^\circ \text{ at } t = 60 \text{ s}.$$

$$8.19 \quad \theta \text{ passes } 89^\circ \text{ when } t = 9.28 \text{ s}.$$

$$8.22 \quad \max(\theta) = 80.73^\circ \text{ when } t = 1.995 \text{ s}.$$

$$8.25 \quad \frac{1}{2} \ddot{\theta} + \frac{4}{3\pi} \frac{g}{R} \sin \theta + \mu \left[ \frac{g}{R} - \frac{4}{3\pi} (\ddot{\theta} \sin \theta + \dot{\theta}^2 \cos \theta) \right] \text{sgn}(\dot{\theta}) = 0.$$

$$8.28 \quad \frac{1}{3} mL^2 \ddot{\phi} + \frac{1}{2} mL \ddot{Y}_B \sin \phi - \frac{1}{2} mg L \sin \phi = \mu |N_A| (\cos \phi) \text{sgn}(\dot{\phi}) - N_A \sin \phi,$$

$$m \ddot{Y}_B (\sin \phi)^2 + \frac{1}{2} mL \ddot{\phi} \sin \phi + \frac{1}{2} mL \dot{\phi}^2 \cos \phi = -\frac{H}{\sin \phi} N_A, \quad \dot{Y}_B (\sin \phi)^2 + H \dot{\phi} = 0.$$

**Answers to Selected Homework Problems**

**717**

$$9.32 \quad \dot{\gamma}_1 = v, \quad \dot{\gamma}_2 = \dot{\theta}, \quad \dot{X}_G = \dot{\gamma}_1 \cos \theta, \quad \dot{Y}_G = \dot{\gamma}_1 \sin \theta, \quad m\ddot{\gamma}_1 = F \cos \beta, \quad I\ddot{\gamma}_2 = -FD \sin \beta.$$

$$9.34 \quad \left[ \frac{1}{3} L^2 (\cos \theta)^5 - DL (\cos \theta)^4 + D^2 \cos \theta \right] \ddot{\gamma}_1 + \left[ 2D^2 - \frac{1}{2} DL (\cos \theta)^3 (\sin \theta) \dot{\gamma}_1^2 \right] \\ = g \left[ D - \frac{L}{2} (\cos \theta)^3 \right] (\cos \theta)^3, \quad \dot{\gamma}_1 = \dot{\theta}.$$

$$9.37 \quad \dot{\gamma}_1 = \dot{\psi}, \quad \dot{\gamma}_2 = \dot{\beta}, \quad \dot{\gamma}_1 - c_1 \dot{\gamma}_2 - c_2 \beta - c_3 = 0, \\ m \left[ k_1^2 (\sin \beta)^2 + \kappa_2^2 (\cos \beta)^2 \right] \ddot{\gamma}_1 + m (\kappa_1^2 - \kappa_2^2) (\dot{\gamma}_1 \dot{\gamma}_2 - \dot{\gamma}_1^2) \sin \beta \cos \beta \\ + m (\kappa_1^2 - \kappa_2^2) \dot{\gamma}_1 \Omega \cos \beta = \lambda_1, \\ m \kappa_2^2 \ddot{\gamma}_1 + m \kappa_1^2 \dot{\gamma}_1 \Omega \cos \beta - m (\kappa_1^2 - \kappa_2^2) \dot{\gamma}_1^2 \sin \beta \cos \beta = -c_1 \lambda_1.$$

$$9.39 \quad \dot{\gamma}_1 = r, \quad \dot{\gamma}_2 = \dot{\theta}, \quad \frac{7}{5} \ddot{\gamma}_1 - r \dot{\gamma}_2^2 = 0, \quad \left( r^2 + \frac{2}{5} R^2 \right) \ddot{\gamma}_2 + 2r \dot{\gamma}_1 \dot{\gamma}_2 = 0.$$

$$9.42 \quad \dot{\gamma}_1 = \dot{\theta}, \quad \frac{1}{2} m L^2 \left[ 1 + 8 (\cos \theta)^2 \right] \ddot{\gamma}_1 - \left( 4m L^2 \dot{\gamma}_1^2 + \frac{9}{2} \dot{\psi}^2 \right) \sin \theta \cos \theta \\ = (mgL - 2F) \sin \theta.$$

$$9.45 \quad \dot{\gamma}_1 = \dot{\beta}, \quad m \kappa_2^2 \ddot{\gamma}_1 + m \kappa_1^2 \Omega_1 \dot{\psi} \cos \beta + m (\kappa_2^2 - \kappa_1^2) \dot{\psi}^2 \sin \beta \cos \beta = M.$$

$$9.48 \quad \dot{\gamma}_1 L \cos \beta + \dot{\gamma}_2 \sin (\theta + \beta) = 0, \\ \left( \frac{1}{3} m_1 L^2 + m_2 L^2 + I_2 \right) \ddot{\gamma}_1 + \left( \frac{1}{2} m_1 + m_2 \right) L \ddot{\gamma}_2 \sin \theta + I_2 \ddot{\beta} = F \sin \beta + N_B \cos \beta, \\ \left[ m_1 + m_2 + m_3 + \frac{I_1}{R^2} \left( \frac{\cos \theta}{\cos \beta} \right)^2 \right] \ddot{\gamma}_2 + \left( \frac{1}{2} m_1 + m_3 \right) L (\ddot{\gamma}_1 \sin \theta + \dot{\gamma}_1^2 \cos \theta) \\ - \frac{I_1}{R^2} \dot{\gamma}_1 \dot{\gamma}_2 \frac{\sin \theta \cos \theta}{(\cos \beta)^2} + \frac{I_1}{R^2} \dot{\gamma}_2 \dot{\beta} \frac{(\cos \theta)^2 \sin \theta}{(\cos \beta)^3} \\ = -F \cos (\beta + \theta) - N_B \sin (\theta + \beta) + k (\ell - \ell_0), \quad \dot{\gamma}_1 = \dot{\theta}, \quad \dot{\gamma}_2 = \dot{\ell}.$$

$$9.50 \quad \dot{\gamma}_1 = v_A, \quad \dot{\gamma}_2 = \dot{\theta}, \quad \dot{\gamma}_3 = \dot{\beta}, \quad \dot{X}_A = \dot{\gamma}_1 \cos (\theta + \beta), \quad \dot{Y}_A = \dot{\gamma}_1 \sin (\theta + \beta), \\ \left[ m_1 \left( 1 + \frac{\kappa_1^2}{R^2} \right) + m_C \right] \ddot{\gamma}_1 - m_C \ddot{\gamma}_2 h \sin \beta + m_C \ddot{\gamma}_3 h \cos \beta = \frac{\Gamma}{R_1}, \\ \left( \frac{1}{2} m \kappa_1^2 + m_C h^2 + I_C \right) \ddot{\gamma}_2 + \frac{1}{2} m \kappa_1^2 \ddot{\gamma}_3 - m_C h [\dot{\gamma}_1 \sin \beta + \dot{\gamma}_1 (\dot{\gamma}_2 + \dot{\gamma}_3) \cos \beta] = 0, \\ \frac{1}{2} m \kappa_1^2 (\ddot{\gamma}_2 + \ddot{\gamma}_3) = \Gamma.$$

$$10.1 \quad |\bar{\omega}| = 3.135 \text{ rad/s}, \quad \theta = 94.87^\circ, \quad \Delta \bar{H}_G = -3.130 I' \bar{\ell}, \quad |\bar{\omega}_2| = -0.1667 \text{ rad/s}.$$

$$10.3 \quad \omega_x = 50 \text{ rad/s}, \quad \omega_z = 450 \text{ rad/s}, \quad \beta = 83.66^\circ, \quad \theta = 86.82^\circ.$$

$$10.6 \quad \bar{\omega} = 7.2902 (10^{-5}) \text{ rad/s about an axis through the center of the Earth at } 0.1558^\circ \text{ from the polar axis in the meridional plane at } 90^\circ \text{ from the meridian of impact.}$$

$$10.8 \quad \text{Precession about the } z \text{ axis; } \bar{\omega} = 7.594 \bar{i} + 6.275 \bar{k} \text{ rad/s @ } \max (\theta) = 45.91^\circ; \\ \bar{\omega} = 5.534 \bar{i} + 6.766 \bar{k} \text{ rad/s @ } \min (\theta) = 13.57^\circ.$$

10.11 Looping precession,  $\min(\theta) = 53.130^\circ$ ,  $\max(\theta) = 53.300^\circ$ ,  $\dot{\psi} = 0$  at  $\theta = 53.199^\circ$ .

$$10.14 \quad \psi = A_1 \cos\left(\frac{\omega^2}{\sigma}t + \nu_1\right) + A_2 \cos(\sigma t + \nu_2), \quad \omega^2 = \frac{mgL}{I'}, \quad \sigma = \frac{I}{I' + mL^2},$$

$$\theta = \frac{\pi}{2} + A_1 \sin\left(\frac{\omega^2}{\sigma}t + \nu_1\right) - A_2 \sin(\sigma t + \nu_2).$$

$$10.16 \quad \frac{I'\lambda}{c} \gg 1, \quad t \gg \frac{I'\Omega_1}{c\Omega_0}, \quad \frac{I'}{I} = O(1).$$

$$10.19 \quad \left[(I + C)(\cos\theta)^2 + (I' + A)\dot{\psi}(\sin\theta)^2 + A\right]\dot{\psi} + I\dot{\phi}\cos\theta = p_\psi,$$

$$I(\dot{\psi}\cos\theta + \dot{\phi}) = p_\phi, \quad (I' + B)\ddot{\theta} + (I + C - I' - A)\dot{\psi}^2\sin\theta\cos\theta + I\dot{\phi}\dot{\psi}\sin\theta = 0.$$

## Index

- Absolute system of units, 15
- Absolute acceleration, 11, 14, 136, 147, 150, 647
- Absolute displacement, 114, 134, 186
- Absolute position, 11, 91, 674
- Absolute velocity, 11, 91, 147, 341
- Absolute reference frame, 13, 178
- Acatastatic constraint, 412
- Acceleration
  - angular, see angular acceleration
  - centripetal, 36, 61, 71, 134, 148
  - constraint equation, 510, 513, 517, 519, 520, 601
  - Coriolis, see Coriolis acceleration
  - definition of, 10
  - free fall, 13, 148–150
  - generalized, see generalized acceleration
  - in Cartesian coordinates, 45
  - in curvilinear coordinates, 70–71
  - in linkages, 190
  - in rolling, 203–206
  - in spherical coordinates, 61–62
  - in terms of quasi-coordinates, 595
  - mixed kinematical description of, 76
  - normal, see acceleration, centripetal
  - of points in a rigid body, 175–176
  - quasi-, 595, 597
  - relative, 134, 136
  - tangential, 34–36
- Action integral, 555
- Admissible movement, 402, 411, 431
- Alembert, Jean Le Rond d', 23, 391
- Allowable point, for moments, 233–234, 236, 319, 341
- Angle
  - azimuthal, 51–52, 58, 637
  - direction, 92–93
  - of rotation, 99, 107–110
  - polar, 58
- Angular acceleration
  - in terms of Eulerian angles, 180
  - analysis of, 127–128, procedure, 128–129
  - of a rigid body, 127
  - relation to angular velocity components, 143, 276
- Angular momentum
  - definition, 20, 232
  - derivative of, 20, 234, 275–280, 297–299, 332–333
  - in free motion, 637–639, 643, 649–650
  - of a particle, 20
  - of a rigid body, 233–234, 241–242
  - of a spinning top, 657–658
  - of a system of particles, 232
  - using principal axes, 277
- Angular velocity,
  - definition, 122
  - analysis of, 127–129
  - in free motion, 638–640, 643–644
  - in terms of Eulerian angles, 180
  - of a rigid body, 136, 175
  - of the Earth, 148, 670–672
- Appell, Paul Emile, 25
- Arclength, 30–31, 38, 64, 200–201
- Asymptotic series, 663
- Augmented method, 511, 519
- Axes
  - body-fixed, 96, 99, 100
  - coordinate, 3, 45, 241
  - space-fixed, 100, 103
- Axis of rotation, 99–100, 108–110
- Axis of symmetry, 180, 242, 244, 270
- Azimuthal angle, 51–52, 58, 637
- Balanced free gyroscope, 674, 680
- Balancing, 302, 304, 320, 333
- Ball-and-socket joint, 184, 189, 234
- Bicycle, 333
- Binormal direction, 34, 43, 44
- Body cone, 213–214, 640, 652
- Body-fixed,
  - axes, 96, 99, 100
  - rotation, 100–101, 105
- Calculus of variations, 656–661
- Cardan joint, 196–200
- Cartesian coordinates, 3, 30, 38, 45
- Catastatic constraint, 412
- Center
  - instant, 176, 236
  - of curvature, 33

- Center (*cont.*)
  - of mass, 230–232, 234, 248–253, 300, 600
  - of percussion, 343, 368
- Central force, 14,
- Centripetal acceleration, *see* acceleration, centripetal
- Chasle's theorem, 175–176, 188, 228, 231, 233, 343, 345, 348
- Christoffel symbols, 66–67
- Classical mechanics, 1, 14, 556
- Collar connection, 186–187, 436
- Components
  - of a unit vector, 74, 93–94
  - of a vector, 3, 43, 45, 95–96
  - Composite shape, for inertia properties, 253
- Computational techniques,
  - augmented method, 511, 519
  - constraint stabilization, 520–521
  - embedded method, 516–519
  - for holonomic systems, 466–470
  - integrated multiplier, 510
  - orthogonal complement, 513–515, 519
- Condition number, 515
- Configuration constraint, *see* constraint equations, configuration
- Configuration space, 408–411, 414, 416, 427, 448, 554, 557, 560
- Conservation
  - of energy, 348, 658
  - of generalized momentum, 583, 667
  - for a spinning top,
  - of momentum, 21, 341, 644
  - of the Hamiltonian function, 578–580
- Conservative force, 345–346, 348
- virtual work of, 444–445
- Constrained generalized coordinates, 398, 400, 409, 432, 437, 456, 544
  - equations of motion for, 492–494, 508
  - initial conditions for, 521
- Constraint equations, 183, 398, 400–405
  - acatastatic, 412
  - catastatic, 412
  - configuration, 400–405, 409–412, 493–494, 520, 521
  - holonomic, 403–404, 520, 521
  - in the configuration space, 409–412, 432–434
  - nonholonomic, 403–405, 412, 493, 522, 591,
  - on acceleration, 510, 513, 517, 519, 520, 601
  - on quasi-velocities, 590, 591, 601, 617
  - on position, *see* configuration constraint
  - on velocity, 189, 190, 401–405, 411, 431, 493, 494, 508, 516, 520, 521
  - Pfaffian form, 402, 405, 411, 412, 592
  - relation to constraint forces, 431–433
  - rheonomic, 411–412, 493, 495
  - scleronomic, 410–411, 493, 494
  - time-dependent, 411–412, 493
- Constraint condition
  - ball-and-socket joint, 184, 189, 234
  - collar, 186–187
  - for planar motion, 128, 183–184, 186, 364
  - pin, 185–187
  - rolling, 200–206
  - slider, *see* collar
  - see also*, constraint equation
- Constraint force, 349, 350, 379, 391, 431–437, 449
  - contribution to generalized forces, 550, 493, 495, 536, 599
  - see also*, reaction
- Constraint matrix, *see* Jacobian constraint matrix
- Constraint stabilization method, 520–521
- Coordinate system, 3, 6, 10, 13, 95
  - global, 128, 129, 135, 136, 275
- Coordinates
  - affine, 28
  - Cartesian, *see* Cartesian coordinates
  - change due to rotation, 96
  - curvilinear, *see* curvilinear coordinates
  - cylindrical, *see* cylindrical coordinates
  - extrinsic, 30, 45
  - generalized, *see* generalized coordinates
  - hyperbolic-elliptic, 68–69
  - ignorable, 455, 482–485, 657
  - intrinsic, *see* path variables
  - quasi-, *see* quasi-coordinates
  - right-handed, 6, 95, 274
  - spherical, *see* spherical coordinates
- Coriolis acceleration, 54, 61, 71, 135, 571
  - in motion relative to the Earth, 150–151
- Coriolis, G., 24, 54
- Curve
  - parametric representation of, 38–39
  - properties of, 32–33, 43–44
- Curvilinear coordinates, 64–67, 69–71
  - see also*, coordinates
- Cycloidal path, 89, 201–202, 661
- Cylindrical coordinates, 51–54, 134
  - and Lagrange's equations, 450
- d'Alembert's inertial force, 14, 391–392, 394, 620
- Degrees of freedom, 183, 188, 397, 400, 404–405, 518, 552, 562, 585, 591
- Derivative
  - of a unit vector, 32–33, 43–44, 52–53, 60, 65–67, 123, 126, 127
  - of a vector, 9–10, 123
  - of angular momentum, 20, 232, 275–280
  - of angular velocity, *see* angular acceleration
  - relative to a moving reference frame, 11, 122, 206
- Differential equations of motion,
  - Gibbs-Appell, 600
  - Hamilton's, 575
  - Lagrange's, 449, 508
  - see also*, computational techniques,
- Differential-algebraic equation, 509
- Dimensional homogeneity, 15, 16
- Direction angles, 92–93
- Direction cosines, 92–95,

## Index

721

- for principal axes, 264, 268–270
- of an equivalent axis of rotation, 107–110
- Displacement, 112–115
  - definition, 17, 113
  - Eulerian, 115
  - infinitesimal, 17, 18, 119–121
  - kinematically admissible, 410
  - Lagrangian, 115
  - of a rigid body, 173–175
  - relative, 114–115, 120
  - virtual, see virtual displacement
- Dynamic imbalance, 302, 304, 320
- Earth
  - as a moving reference frame, 13, 16, 47–151, 154–158, 672, 680
  - forces acting on, 15–16, 148, 249–252, 668–672
  - mass of, 16
- Eigenvalue problem
  - for axis of rotation, 108–109
  - for principal axes, 268–270
  - for stability of free motion, 646
- Elevation
  - for gravitational potential energy, 346
  - of center of mass of a top, 657–665
- Ellipsoid of inertia, 263–264, 270
  - in Poinsot's construction, 647–652
- Elongation, of a spring, 347
- Embedding method, 516–519
- Energy
  - mechanical, 348, 350, 520, 572–573, 579
  - of a spinning top, 659–660
  - see also kinetic energy, potential energy
- Energy principles, see work-energy principles
- Equations of motion
  - Euler's, 277–278, 298–300, procedure, 300–301
  - first order form, 469–471, 509–519
  - for planar motion, 319–320
  - for a single-axis gyroscope, 686
  - for a spinning top, 657–658
  - for free motion, 644
  - for unsteady rolling, 504–508
  - Hamilton's, 575
  - Lagrange's, 449, 508
  - matrix form, 298, 301, 469–471, 510, 511, 512, 514, 518, 519
  - Newton's, 1, 14, 34–35, 46, 54, 62, 231
  - state-space form, 469–471, 509–519
- Equivalent,
  - vectors, 6
  - force systems, 250, 297–298, 332, 349, 392, 435, 616
- Error,
  - for a gyrocompass, 680–681
  - in an asymptotic series, 663
  - in solving differential equations of motion, 520–521
- Euler-Lagrange equation, 560, 565
- Euler's equations, 277–278, 298
  - from Gibbs-Appell equations, 589, 598, 602–603
- Euler's theorem, 106, 109
- Euler, Leonhard, 22–23
- Eulerian angles,
  - angular acceleration in terms of, 180
  - angular velocity in terms of, 180
  - definition, 178
  - for an arbitrary rotation axis, 109–110
  - for a free gyroscope, 673
  - for a gyrocompass, 678
  - for a spinning top, 667
  - for free motion, 638
  - for rotation of the earth, 669
  - for unsteady rolling, 505
  - rotation transformation in terms of, 179
- Extrinsic coordinates, 30, 45
- Fast top, 662, 664
- First moments of mass, 230–231, 234, 248, 250, 253, 340, 598
- Force, 14
  - conservative, 345–346, 348
  - generalized, see generalized force
  - gravitational, 16, 150, 230, 248–252, 346
  - reaction, see constraint force
  - resultant, see resultant force
  - spring, 347, 350
  - work done by, see work
- Force-couple system, 251, 297, 332, 344, 349, 395–396
- Fork-and-clevis joint, 18
- Foucault, Jean Louis, 158
- Foucault pendulum, 158
- Frame of reference, see reference frame
- Free body diagram, 14, 299, 300, 360, 364, 365, 394, 620
- Free fall acceleration, 13, 16, 148–150
- Free gyroscope, 672–675, 688
  - stability of, 677
- Free motion
  - of an arbitrary body, 643–647
    - Poinsot's construction, 647–652
  - of an axisymmetric body, 637–640, 652
  - stability of, 645–647, 652
- Frenet's formulas, 44, 126
- Friction, 322–324, 327–328, 330, 351, 365–366
  - in Lagrange's equations, 437, 495–496, 502, 509, 536–542
  - in Gibbs-Appell equations, 591, 600
  - rolling, 315, 335, 535
- Fully constrained system, 202, 204
- Galilean invariance, 15
- Galileo, Galilei, 21
- General motion, 175–176, 228, 300, 598
- Generalized acceleration, 469, 470, 508–509, 514, 517
- Generalized coordinates,
  - constrained, 398, 400, 409, 492–494, 516
  - dependence of kinetic energy on, 467, 582–583



- Generalized coordinates, (*cont.*)
  - dependence of potential energy on, 444, 582–583
  - for a Ritz series, 565–566
  - in conjunction with quasi-velocities, 589–591, 617
  - in the configuration space, 408–412, 421, 427, 431–432, 437, 555–557
  - initial conditions, 521
  - position in terms of, 415–416, 419, 447
  - selection of, 396–405, 432, 437, 455–456, 552, 620
  - unconstrained, 398, 409, 432, 450, 516
- Generalized force, 426–428
  - associated with quasi-coordinates, 595–596, 599
  - contribution of constraint forces, 431–437, 599
  - for Coulomb friction, 536–537
  - for a Ritz series, 567
  - in the configuration space, 427, 432–433
  - relation to potential energy, 444–445, 599
  - relation to power, 579–580
- Generalized momentum, 571–573, 582–584
  - for a gyrocompass, 682
  - for a spinning top, 657–658
- Generalized velocity, 401–402, 408, 411, 420, 467, 494, 575, 579, 583, 589–590
- Gibbs-Appell equations, xi, 594–596, 601, 616, 618–619
- Gibbs-Appell function, 596, 597–598, 599–600
  - Gibbs, Josiah Williard, 25, 589
- Gimbal of a gyroscope, 672–675, 678, 685
- Gimbal walk, 696
- Gradient, 270, 348, 410, 578, 649
- Gravitation
  - law of, 16, 150
  - force-couple resultant, 230, 248–252
  - potential energy, 346
- Gravitational constant, universal, 16, 248
- Gravitational system of units, 15–16
- Gyrocompass, 677–681
- Gyroscope, 461
  - free, 672–675
  - stability of, 677
  - single-axis type, 685–688
  - integrating type, 687
  - rate type, 687,
- Gyroscopic moment, 299, 320
- Hamilton's canonical equations, 571, 575
- Hamilton's principle, 552–557
  - using the calculus of variations, 558–561
  - with Ritz series, 565–568
- Hamilton, William Rowan, 24
- Hamiltonian function, 520, 572–574
  - conservation of, 578–580
  - relation to mechanical energy, 573, 579
- Herpolhode, 650
- Holonomic constraint, 403, 412, 520, 521
  - in the configuration space, 409–411
  - rheonomic, 411
  - scleronomic, 410
- Holonomic system, 432, 449, 466, 492, 494
- Ignorable coordinates, 455, 562–564
  - for a gyroscope, 657, 679
- Impulse-momentum principles
  - angular, 20–21, 338–341
  - generalized, 582–583
  - for collisions, 360–366
  - linear, 19–20, 338–340
- Impulsive force, 19–20, 339, 359–360, 364
- Independent coordinates, *see* generalized coordinates, unconstrained
- Inertia
  - coefficients, 276
  - ellipsoid, 263–264, 267, 270, 648
  - see also* Poinot's construction
  - matrix, 242, 263, 267–269
  - moment of, 17, 242, 263
  - product of, 242–243, 254, 255, 269
- Inertia properties
  - rotation transformation, 258–260, 267–270
  - translation transformation, 258–260, 263–264, 267–271
  - tabulation, 697–792
- Inertial force, *see* d'Alembert's inertial force
- Inertial guidance systems, *see* gyrocompass, gyroscope
- Inertial reference frame, 15–16, 91, 148, 232, 234, 672, 688
- Infinitesimal displacement, 17, 18, 120–121, 344, 347, 348, 392, 396, 408–409
- Infinitesimal rotations, 121, 123, 127, 344
- Initial conditions, 35, 360, 405, 470, 520, 521–522, 639, 643, 644, 658, 687
- Instantaneous axis of rotation, 134–135, 176
  - in free motion, 640
- Instantaneous center of zero velocity, 176
- Internal forces, 229–230, 233, 332–333, 344, 362, 394, 435, 553
- Intrinsic coordinates, 30
- Invariable plane, *see* Poinot's construction
- Inverse of rotation transformation, 93–94, 100, 108
- Jacobi's integral, 580–582
- Jacobian constraint matrix, 403, 433, 493, 510, 511, 513, 599
- Jerk, 11
- Kane's equations, xi, 589, 616–622
- Kinematically admissible, 402, 410–412, 431–432, 521, 591–592, 599
- Kinematics, definition of, x, 1
- Kinetic energy
  - for Lagrange's equations, 448, 466–468, 508
  - in Hamilton's equations, 572–573
  - in Hamilton's principle, 553–554, 556, 558
  - of an elastic bar, 628
  - of a moving cable, 562
  - of a gyrocompass, 679
  - of a particle, 18, 466–467

## Index

723

- of a rigid body, 345, 467
  - in free motion, 647–650
  - of a single-axis gyroscope, 686
  - of a spinning top, 657, 660, 665
  - of a system of particles, 235–237, 344, 554
  - rotational, 258, 263, 349, 621, 648
  - translational, 348, 621
- Kinetics, definition of, x, 1
- Lagrange multiplier, 433, 493, 495, 508–514, 519, 599–601
- Lagrange's equations, xi, 447–449, 553, 556–557, 578
  - evaluation of, 450, 467–468, 494
  - for constrained systems, 493, 509–510, 537
  - for ignorable coordinates, 585
  - for quasi-coordinates, 589
- Lagrange, Joseph-Louis, 23–24, 392, 447
- Lagrangian function, 449, 555, 558, 567, 572, 582–583, 585
- Latitude, 58, 148, 680
- Law
  - Newton's, see Newton's laws
  - of dimensional homogeneity, 15, 16
  - of gravitation, 16, 150
- Line of nodes, 179, 181, 277, 638, 643
- Linkage, 117–119, 124–125, 190–191
- Longitude, 58, 148
- Mass, 14
  - unit of, 15–16
  - of the Earth, 16
- Matrix form,
  - for vector algebra, 7
  - of angular momentum, 242, 276
  - of constraint equations, 403
  - of equations of motion, 298, 301, 469–470, 508–510, 601
  - of Hamiltonian function, 574
  - of inertia properties, 242, 267–270
  - of kinetic energy, 258, 573
  - see also, displacement, rotation transformation
- Mechanical energy, 348, 350, 543, 572–573, 579–580
  - in computations, 520
  - of a top, 659–660
- Mixed kinematical descriptions, 73–76
- Mohr's circle, 290
- Moment
  - equation of motion, see Euler's equations
  - gyroscopic, 299, 320
  - of a force, 9
  - of inertia, see inertia properties
  - of momentum, see angular momentum
  - resultant, 20, 21, 229–230, 233
- Momentum principles, see impulse-momentum principles
- Newton's laws, 1, 13–15, 34, 54, 62, 149–150
- Newton, Isaac, 14, 22–23
- Newtonian relativity, 15
- Nonholonomic system, 492, 601
- Normal direction, 32–33, 39, 44, 649
- Null space, 515
- Numerical methods, see computational techniques
- Nutation, 179–181, 277
  - in rolling, 205
  - in free motion, 638–640, 643–646
  - of a free gyroscope, 672–674
  - of a spinning top, 656–665
- Orientation, rotation transformation
- Orthogonal complement, 513–516, 518
- Orthogonality
  - of principal inertia axes, 269
  - of unit vectors, 43, 66, 95
- Osculating plane, 33–34, 43–44
- Parallel axis theorems, 253–255
- Partially constrained system, 188, 190
- Particle, 11, 14, 20
- Path, 11, 30–31, 36, 73, 558
  - in configuration space, 408–411, 414–415, 554–555
  - variational, 409–411, 416, 554–555, 557, 560
- Path integral, 17–18
- Path variables, 30–36, 43–44, 73–75
  - parametric form, 38–39
- Perturbation analysis,
  - for a free gyro, 673–674
  - for a spinning top, 663–664
  - for stability of free motion, 645–646
- Pfaffian form, 402–403, 404, 405, 411, 412, 592
- Pin connection, 185–187
- Planar motion, 19, 76
  - generalized coordinates for, 397–398
  - kinematics of, 128, 176, 163–184
  - kinetics of a rigid body, 242, 299 319–320, 360, 362, 364
- Poinsot's construction, 649–651
- Point
  - for Chasle's theorem, 175–176, 188, 228, 233, 649
  - for decomposition of kinetic energy, 236, 243, 245, 248
  - selection for moment equation, 233–234, 275, 319, 331
- Polar angle, 58
- Polhode, 650–652
- Position,
  - definition, 2, 6, 11
  - in Cartesian coordinates, 45
  - in curvilinear coordinates, 52, 58, 60, 64
  - in path variables, 30–31, 38
  - in relative motion, 91–92, 96, 112–113, 120
  - in terms of generalized coordinates, 415, 419–420
  - in the configuration space, 410–412
  - with respect to the Earth, 148–151
- Potential energy, 118, 346
  - and virtual work, 444–445, 554, 556
  - gravity, 346–347
  - spring, 347, 552

- Pound force, 16
- Power, 350, 579–580
- Precession, 178, 181, 300
  - cuspidal, 662–664
  - in free motion, 638–640, 643–647
  - looping, 661–662
  - of a free gyroscope, 672–674
  - of a gyrocompass, 677–680
  - of a single-axis gyroscope, 685, 688
  - of a spinning top, 656–665
  - of the equinoxes, 248, 252
  - regular, 639–640
  - retrograde, 639–640
  - steady, 306–309, 312–315, 530, 664–665
  - unidirectional, 660
- Principal axes, 244, 264, 267–270, 277, 298, 301, 320
  - for rotationally symmetric bodies, 269–270
- Principle
  - d'Alembert's,  $x$ , 14, 23, 24, 391–392, 394, 620
    - see also, principle of dynamic virtual work
  - Hamilton's, 24, 553–557, 558–561, 565–568
  - of dynamic virtual work,  $x$ , 392, 394–396, 447, 616–617
  - of impulse and momentum, see impulse-momentum principles
  - of virtual work,  $x$ , 392–393
  - of work and energy, see work-energy principle
- Products of inertia, 242–243, 255, 269
- Pure rotation, 175–176, 234, 236, 253, 296, 300, 345, 394, 396, 598, 652
- Quasi-coordinate, 589–591,
- Quasi-velocity, 589–592, 596, 599–601, 617–622
- Radius
  - of curvature, 32–33, 39
  - of gyration, 242
- Rate gyroscope, 687
- Reaction,
  - description of, 299–301, 333, 391, 432–435, 493–495
  - impulsive, 339, 364–365
  - Newton's Third Law, 14, 149
  - normal, 35
  - relation to kinematics, 173, 183, 234, 431–437
  - see also constraint force, free body diagram
- Redundant constraint, 300
- Reference frame
  - absolute, 11, 13, 91, 147–148, 178
  - angular motion of, 127–129, 147
  - body-fixed, 96, 99–101
  - displacement relative to, 114–115
  - Earth-fixed, 13, 147–148
  - Galilean, 15, 136
  - inertial, 15, 136
  - motion relative to, 11, 134–135, 232, 421
  - translating, 135–136, 231–232, 638
- Relative acceleration, 134–135, 147–151
- Relative velocity, 122, 134–135, 147–151
- Relative position, 14, 91, 151, 552
- Resultant force
  - for a particle, 14, 17–18, 19, 35, 46, 54, 62, 149, 228
  - for a rigid body, 228, 296–299, 341, 344–345, 348, 392
  - for a system of particles, 229
  - for a system of rigid bodies, 331–333
  - of gravity, 248–252
- Resultant moment, 20–21
  - for a rigid body, 234, 296–299, 341, 349, 392
  - for a system of particles, 229–230
  - for a system of rigid bodies, 331–333
  - of gravity, 248–252
- Rheonomic constraint, 411–412, 493, 495
- Right-hand,
  - rule, 5, 99–100, 121, 176
  - coordinate system, 6, 45, 52, 59, 65, 95, 269
- Rigid body
  - definition of, 91
  - equations of motion for, 277–278, 298, 319–320
  - Gibbs-Appell function for, 597–598
  - kinematics of, 136, 173–176
  - virtual displacement of, 421
- Rigid system, 190
- Ritz, Walther, 25–26
- Rolling
  - kinematics of, 200–206
  - kinetics of steady motion, 312–315
  - kinetics of planar motion, 322–324
  - work done by friction, 351–352
  - unsteady, 206, 504–508, 522–528
- Rotation
  - about a coordinate axis, see simple rotation
  - about an arbitrary axis, 106–110
    - see also, Eulerian angles
  - body-fixed, 100–101
  - infinitesimal, 120–121
  - of the Earth, 13, 15, 147–151
  - of the osculating plane, 44
  - pure, 175–176, 234, 236, 253, 296, 300, 345, 394, 396, 598, 652
  - sequence of, 100–101, 103–105
  - simple, 99–100
  - space-fixed, 103–105
  - spatial, 100, 105, 299
- Rotation transformation, 92–96
  - in terms of Eulerian angles, 109–110, 178–180
  - inverse of, 93–94
  - of inertia properties, 253, 258–260
- Rotational kinetic energy, see kinetic energy
- Routh, Edward John, 24–25
- Routh's method, 583–585
- Scleromic constraint, 410–411, 493, 494
- Screw motion, 176
- Sequence of rotations, see rotation, sequence
- SI units, 15–16
- Single-axis gyroscope, 685–688
- Singular value decomposition, 514–515

## Index

725

- Sleeping top, 665
- Slider, see collar connection
- Slug, mass unit, 17
- Space cone, 213–214, 640, 652
- Space-fixed
  - axes, 100, 103, 638
  - rotations, 103–105, 121
- Speed, 33, 48–51
- Spherical coordinates, 51, 58–62, 70, 168, 246–247
  - for virtual displacement, 420
- Spherical pendulum, 154–158
- Spin
  - Eulerian angle, 179–180
  - in free motion, 637–640, 643–644
  - of a free gyroscope, 673–675
  - of a gyrocompass, 678
  - of a single-axis gyroscope, 685–686
  - of a top, 657–665
- Spinning top, 656–666
- Spring, linearly elastic, 347
- Stability
  - of a gyrocompass, 681–685
  - of asteady precession, 306–309
  - of a rolling disk, 532–533
  - of a servo-driven gyroscope, 675–677
  - of a sleeping top, 685–666
  - of free motion, 645–647
- State-space equations
  - for a holonomic system, 469–470
  - for constrained generalized coordinates, 491, 509–514, 516–519
- Static equilibrium, 14, 20, 228, 233, 234, 392–393
- Static indeterminacy, 300
- Steady precession, see precession
- Stiffness of a spring, 347, 666
- Stretch ratio, 64–67
- Symmetry, for inertia properties,
- System
  - holonomic, 409–412, 432, 449, 466–468, 492
  - nonholonomic, 404, 412, 492, 601
  - of particles, 228–232, 467, 596
  - of rigid bodies, 331–334, 467
  - time-dependent, 411–413, 493, 579–580
- Tangent-normal components, see path variables
- Tangential
  - direction, 32–33, 38, 44
  - acceleration, 33–34, 35
- Tensor of inertia properties, 259
- Torsion
  - of a curve, 44
  - of an elastic bar, 560, 628
- Transformation
  - of inertia properties, see inertia properties
  - oh a unit vector, see rotation transformation
- Translation
  - motion, 15, 91, 115, 175–176, 228, 234
  - transformation of inertia properties, see parallel axis theorems
  - transformation of position coordinates, 91–92, 113, 174
- Translational kinetic energy, 348, 621
- U. S. Customary units, 16
- Unit sphere, see spinning top
- Unit vectors
  - evaluation, 4
  - for Cartesian coordinates, 3, 4, 6, 45
  - for curvilinear coordinates, 52–53, 59–61, 64–66, 69–71
  - for path variables, 32–34, 38–39, 43–44, 126
  - in a mixed kinematical description, 73–76
  - matrix representation, 94–95, 259, 267–270
  - rate of change of, 123, 126, 127, 134, 275, 278
  - transformation of, see rotation transformation
- Units
  - absolute, 15
  - gravitational, 15–16
  - SI, 15–16
  - U. S. customary, 16
- Universal gravitational constant, 16
- Universal joint, see cardan joint
- Variational path, 409–411, 414–416, 554–555, 557, 560
- Vector algebra, 1–7
- Vector calculus, 9–11
- Velocity
  - absolute, 11, 91, 147, 341
  - angular, see angular velocity
  - definition of, 9–10
  - for rigid body motion, 136, 173–176
  - generalized, see generalized velocity
  - in Cartesian coordinates, 45
  - in curvilinear coordinates, 53, 60, 69–70
  - in path variables, 31, 33–35
  - in rolling, 201–205
  - in terms of generalized coordinates, 401–403, 419–421, 447, 466, 572, 579
  - in terms of quasi-coordinates, 589–591, 617–618
  - mixed kinematical description of, 73–76
  - of linkages, 124–125, 190–191
  - relation to virtual displacement, 419–421
  - relative, 122, 134–135, 147–151
- Velocity constraint equations
  - for generalized coordinates, 401–404, 431, 493, 521
  - for quasi-velocities, 590, 601
  - in conjunction with computational methods, 508–520
  - in a kinematical analysis, 189, 190, 203
  - in the configuration space, 409–412
- Virtual displacement, xi, 392–394, 396
  - analytical method, 415–416
  - in terms of quasi-coordinates, 591
  - in the configuration space, 410–412
  - kinematical method, 419–421
  - relation to physical displacement, 416
  - relation to velocity, 419–421

**726**

Virtual movement, 392–396, 411, 415, 431–432,  
435–436, 444, 555, 591  
see also, virtual displacement  
Virtual work, x–xi, 415, 426–428, 431–432, 435–437,  
444, 496, 555, 567  
for a rolling body, 437–439  
principle of, 392–393  
in configuration space, 427–428, 432–433  
in terms of quasi-coordinates, 594–596,  
599

***Index***

Weight, 15, 16  
Work, 17–18, 343–350  
in rolling, 351–352  
of a conservative force, 345–348  
virtual, see virtual work  
Work-energy principle  
for a particle, 18  
for a system of particles, 235  
for a rigid body, 343–350  
for a time-dependent system, 579–580